

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
9 April 2009 (09.04.2009)

PCT

(10) International Publication Number
WO 2009/046372 A2

(51) International Patent Classification:
A61F 2/06 (2006.01)

(74) Agents: ANDERSON, William, B. et al.; Grant Anderson LLP, c/o PortfolioIP, P.O. Box 52050, Minneapolis, MN 55402 (US).

(21) International Application Number:
PCT/US2008/078846

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 3 October 2008 (03.10.2008)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

Published:

(26) Publication Language: English

— without international search report and to be republished upon receipt of that report

(30) Priority Data:
60/977,617 4 October 2007 (04.10.2007) US

(71) Applicant (for all designated States except US): TRIVASCULAR2, INC. [US/US]; 3910 Brickway Blvd., Santa Rosa, CA 95403 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CHOBOTOV, Michael, V. [US/US]; 3805 Skyfarm Drive, Santa Rosa, CA 95403 (US). WHIRLEY, Robert, G. [US/US]; 3709 Paxton Place, Santa Rosa, CA 95404 (US). HUMPHREY, Joseph, W. [US/US]; 3823 Skyfarm Drive, Santa Rosa, CA 95403 (US).



WO 2009/046372 A2

(54) Title: MODULAR VASCULAR GRAFT FOR LOW PROFILE PERCUTANEOUS DELIVERY

(57) Abstract: A hybrid modular endovascular graft wherein a main graft is sized to span at least a portion of a target vessel lesion in a large percentage of patients. Graft extensions may be secured to the main graft to extend the main graft and provide a sealing function for some applications.

MODULAR VASCULAR GRAFT FOR LOW PROFILE PERCUTANEOUS DELIVERY**BACKGROUND**

[0001] An aneurysm is a medical condition indicated generally by an expansion and weakening of the wall of an artery of a patient. Aneurysms can develop at various sites within a patient's body. Thoracic aortic aneurysms (TAAs) or abdominal aortic aneurysms (AAAs) are manifested by an expansion and weakening of the aorta which is a serious and life threatening condition for which intervention is generally indicated. Existing methods of treating aneurysms include invasive surgical procedures with graft replacement of the affected vessel or body lumen or reinforcement of the vessel with a graft.

[0002] Surgical procedures to treat aortic aneurysms can have relatively high morbidity and mortality rates due to the risk factors inherent to surgical repair of this disease as well as long hospital stays and painful recoveries. This is especially true for surgical repair of TAAs, which is generally regarded as involving higher risk and more difficulty when compared to surgical repair of AAAs. An example of a surgical procedure involving repair of a AAA is described in a book titled *Surgical Treatment of Aortic Aneurysms* by Denton A. Cooley, M.D., published in 1986 by W. B. Saunders Company.

[0003] Due to the inherent risks and complexities of surgical repair of aortic aneurysms, endovascular repair has become a widely-used alternative therapy, most notably in treating AAAs. Early work in this field is exemplified by Lawrence, Jr. et al. in "Percutaneous Endovascular Graft: Experimental Evaluation", *Radiology* (May 1987) and by Mirich et al. in "Percutaneously Placed Endovascular Grafts for Aortic Aneurysms: Feasibility Study," *Radiology* (March 1989). Commercially available endoprostheses for the endovascular treatment of AAAs include the AneuRx® stent graft manufactured by Medtronic, Inc. of Minneapolis, MN, the Zenith® stent graft system sold by Cook, Inc. of Bloomington, IN, the PowerLink® stent-graft system manufactured by Endologix, Inc. of Irvine, CA, and the Excluder® stent graft system manufactured by W.L. Gore & Associates, Inc. of Newark, DE. A

commercially available stent graft for the treatment of TAAs is the TAG™ system manufactured by W.L. Gore & Associates, Inc.

[0004] When deploying devices by catheter or other suitable instrument, it is advantageous to have a flexible and low profile stent graft and delivery system for passage through the various guiding catheters as well as the patient's sometimes tortuous anatomy. Many of the existing endovascular devices and methods for treatment of aneurysms, while representing significant advancement over previous devices and methods, use systems having relatively large transverse profiles, often up to 24 French. Also, such existing systems have greater than desired lateral stiffness, which can complicate the delivery process. In addition, the sizing of stent grafts may be important to achieve a favorable clinical result. In order to properly size a stent graft, the treating facility typically must maintain a large and expensive inventory of stent grafts in order to accommodate the varied sizes of patient vessels due to varied patient sizes and vessel morphologies. Alternatively, intervention may be delayed while awaiting custom size stent grafts to be manufactured and sent to the treating facility. As such, minimally invasive endovascular treatment of aneurysms is not available for many patients that would benefit from such a procedure and can be more difficult to carry out for those patients for whom the procedure is indicated. What has been needed are stent graft systems and methods that are adaptable to a wide range of patient anatomies and that can be safely and reliably deployed using a flexible low profile system.

SUMMARY

[0005] Some embodiments of a modular endovascular graft assembly include a bifurcated main graft member formed from a supple graft material having a main fluid flow lumen therein. The main graft member may also include an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and a network of inflatable channels disposed on the main graft member. The network of inflatable channels may be disposed anywhere on the main graft member including the ipsilateral and contralateral legs. The network of inflatable channels may be configured to accept a hardenable fill or inflation material to

provide structural rigidity to the main graft member when the network of inflatable channels is in an inflated state. The network of inflatable channels may also include at least one inflatable cuff disposed on a proximal portion of the main graft member which is configured to seal against an inside surface of a patient's vessel. The fill material can also have transient or chronic radiopacity to facilitate the placement of the modular limbs into the main graft member. A proximal anchor member may be disposed at a proximal end of the main graft member and be secured to the main graft member. The proximal anchor member may have a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts having a cross sectional area that is substantially the same as or greater than a cross sectional area of proximal stent portions or distal stent portions adjacent the strut. At least one ipsilateral graft extension having a fluid flow lumen disposed therein may be deployed with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member. At least one contralateral graft extension having a fluid flow lumen disposed therein may be deployed with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member. For some embodiments, an outside surface of the graft extension may be sealed to an inside surface of the contralateral leg of the main graft when the graft extension is in a deployed state. For some embodiments, the axial length of the ipsilateral and contralateral legs may be sufficient to provide adequate surface area contact with outer surfaces of graft extensions to provide sufficient friction to hold the graft extensions in place. For some embodiments, the ipsilateral and contralateral legs may have an axial length of at least about 2 cm. For some embodiments, the ipsilateral and contralateral legs may have an axial length of about 2 cm to about 6 cm, more specifically, about 3 cm to about 5 cm.

[0006] Some embodiments of a modular endovascular graft assembly include a bifurcated main graft member having an axial length of about 5 cm to about 10 cm formed from a supple graft material. The main graft member has a main fluid flow lumen therein, an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm. The main graft member also includes network of inflatable channels disposed on the main graft

member, including the ipsilateral and contralateral legs, which is configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state. The network of inflatable channels may also include at least one inflatable cuff disposed on a proximal portion of the main graft member configured to seal against an inside surface of a patient's vessel. A proximal anchor member may be disposed at a proximal end of the main graft member and secured to the main graft member. The proximal anchor member may have a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts. At least one ipsilateral graft extension having a fluid flow lumen disposed therein may have the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member. At least one contralateral graft extension having a fluid flow lumen disposed therein may have the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member.

[0007] Some embodiments of a method of treating a patient include providing a delivery catheter containing a radially constrained bifurcated main graft member. The main graft member may be formed from a supple graft material which has a main fluid flow lumen therein and which has an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen and a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen. The main graft member may also include a network of inflatable channels disposed on the main graft member. Inflatable channels of the network of inflatable channels may be disposed on any portion of the main graft member including the ipsilateral and contralateral legs of the main graft member. The main graft member may also include a proximal anchor member which is disposed at a proximal end of the main graft member and secured to the main graft member. The proximal anchor member may have a self-expanding proximal stent portion secured to a self-expanding distal stent portion. Such a delivery catheter may be axially positioned within the patient's vasculature such that the main graft member within the delivery catheter is disposed coextensively with a vascular defect of the patient's aorta. Once this positioning has been achieved, the proximal anchor member may be deployed so as to radially expand and engage an inner surface of the patient's vasculature and anchor the proximal anchor member to the patient's aorta. Thereafter, the network of inflatable

channels of the main graft member may be inflated with an inflation material so as to provide a more mechanically rigid structure of the main graft member. For some embodiments, inflation of the network of inflatable channels may also provide a seal between an outer surface of an inflatable cuff of the main graft member and an inside surface of the patient's body lumen in contact with the inflatable cuff. For some embodiments, a hardenable fill material may be used that may assume one or more solid configuration after inflation of the network of inflatable channels so as to provide additional mechanical rigidity as well as prevent leakage of the fill material. Some embodiments may also employ radiopaque inflation material to facilitate monitoring of the fill process and subsequent engagement of graft extensions. A second delivery catheter containing a radially constrained self-expanding contralateral graft extension may then be axially positioned in the contralateral leg of the main graft member with a proximal portion of the contralateral graft extension axially overlapped with an inner fluid flow lumen of the contralateral leg of the main graft member and a distal portion of the contralateral graft extension axially overlapped with a portion of the patient's contralateral iliac artery. Access to the contralateral leg of the main graft portion may be achieved by percutaneous access or femoral arteriotomy from the patient's contralateral femoral artery with a delivery sheath or the like. Once properly positioned, the self-expanding contralateral graft extension may be deployed by releasing the radial constraint of the second delivery catheter. As the contralateral graft extension self expands in an outward radial orientation, a seal between the inner fluid flow lumen of the contralateral graft extension, a fluid flow lumen of the contralateral leg and a fluid flow lumen of the contralateral iliac artery may be formed. A third delivery catheter containing a radially constrained self-expanding ipsilateral graft extension may also be axially positioned in the ipsilateral leg of the main graft member with a proximal portion of the ipsilateral graft extension axially overlapped with an inner fluid flow lumen of the ipsilateral leg of the main graft member and a distal portion of the ipsilateral graft extension axially overlapped with a portion of the patient's ipsilateral iliac artery. The self-expanding ipsilateral graft extension may then be deployed by releasing the radial constraint so as to form a seal between the inner fluid flow lumen of the ipsilateral graft extension, a fluid flow lumen of the ipsilateral leg and a fluid flow lumen of the ipsilateral iliac artery. The ipsilateral and contralateral graft extensions may be delivered and deployed in either order.

[0008] Some embodiments of a graft extension include a fluid flow lumen disposed therein, at least one layer of permeable PTFE material, at least one layer of semi-permeable or substantially non-permeable PTFE material having no discernable node and fibril structure and an interposed self-expanding stent formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration disposed between at least one outer layer and at least one inner layer of PTFE material.

[0009] These features of embodiments will become more apparent from the following detailed description when taken in conjunction with the accompanying exemplary drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is an elevation view of a modular graft assembly.

[0011] FIG. 1A is an elevation view of a proximal anchor member and connector ring of the modular graft assembly.

[0012] FIG. 2 is a transverse cross section of the modular graft assembly of FIG. 1 taken along lines 2-2 of FIG. 1.

[0013] FIG. 3 is a transverse cross section of the modular graft assembly of FIG. 1 taken along lines 3-3 of FIG. 1.

[0014] FIG. 4 is a transverse cross section of the graft extension of the modular graft assembly of FIG. 1 taken along lines 4-4 of FIG. 1.

[0015] FIG. 4A is an enlarged view of a junction between a graft extension and an ipsilateral leg of the graft assembly of FIG. 1 indicated by the encircled portion 4A-4A in FIG. 1.

[0016] FIG. 5A is an enlarged view of a junction between a proximal anchor member and connector ring of FIG. 1 indicated by the encircled portion 5A-5A in FIG. 1.

[0017] FIG. 5B is an exploded view of a junction between connector elements of the proximal anchor member and connector ring without a coil member.

[0018] FIG. 6A is an enlarged view of a junction between a distal stent portion and a proximal stent portion of the proximal anchor member of FIG. 1 indicated by the encircled portion 6A-6A in FIG. 1.

[0019] FIG. 6B is a transverse cross section of the proximal anchor member of the modular graft assembly of FIG. 1 taken along lines 6B-6B of FIG. 6A.

[0020] FIG. 6C is a transverse cross section of the proximal anchor member of the modular graft assembly of FIG. 1 taken along lines 6C-6C of FIG. 6A.

[0021] FIG. 6D is a transverse cross section of the proximal anchor member of the modular graft assembly of FIG. 1 taken along lines 6D-6D of FIG. 6A.

[0022] FIGS. 7-14 illustrate a deployment sequence of a modular graft system within the vasculature of a patient.

[0023] FIG. 15 is an elevation view of an embodiment of a graft extension.

[0024] FIG. 16 is a transverse cross sectional view of the graft extension of FIG. 15 taken along lines 16-16 of FIG. 15.

[0025] FIGS. 17A to 17E illustrate embodiments of graft extension configurations.

DETAILED DESCRIPTION

[0026] Embodiments of the invention are directed generally to methods and devices for treatment of fluid flow vessels with the body of a patient. Treatment of blood vessels is specifically indicated for some embodiments, and, more specifically, treatment of aneurysms, such as abdominal aortic aneurysms.

[0027] Some embodiments of a modular endovascular graft assembly may include a bifurcated main graft member formed from a supple graft material, such as ePTFE, having a main fluid flow lumen therein. The main graft member may also include an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen, a contralateral

leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and a network of inflatable channels disposed on the main graft member. For some embodiments, the main graft member may have an axial length of about 5 cm to about 10 cm, more specifically, about 6 cm to about 8 cm in order to span an aneurysm of a patient's aorta without engaging the patient's iliac arteries directly with the legs of the main graft member.

[0028] The inflatable channels of the network of inflatable channels may be disposed on any portion of the main graft member including the ipsilateral and contralateral legs. The network of inflatable channels may be configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state and the inflation material has been cured or hardened. Radiopaque inflation material may be used to facilitate monitoring of the fill process and subsequent engagement of graft extensions. The network of inflatable channels may also include at least one inflatable cuff disposed on a proximal portion of the main graft member which is configured to seal against an inside surface of a patient's vessel, such as the aorta.

[0029] A proximal anchor member is disposed at a proximal end of the main graft member and secured to the main graft member. The proximal anchor member has a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts. Some embodiments of the struts may have a cross sectional area that is substantially the same as or greater than a cross sectional area of proximal stent portions or distal stent portions adjacent the strut. Such a configuration may be useful in avoiding points of concentrated stress in the proximal anchor member or struts which couple components thereof. For some embodiments, the proximal stent of the proximal anchor member further includes a plurality of barbs having sharp tissue engaging tips that are configured to extend in a radial outward direction in a deployed expanded state. For some embodiments, the proximal anchor member includes a 4 crown proximal stent portion and a 8 crown distal stent portion which may be made from a superelastic alloy such as superelastic NiTi alloy.

[0030] At least one ipsilateral graft extension having a fluid flow lumen disposed therein may be deployed with the fluid flow lumen of the graft extension sealed to and in fluid

communication with the fluid flow lumen of the ipsilateral leg of the main graft member. In addition, at least one contralateral graft extension having a fluid flow lumen disposed therein may be deployed with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member. For some embodiments, the graft extensions may include an interposed self-expanding stent disposed between at least one outer layer and at least one inner layer of supple layers of graft material. The interposed stent disposed between the outer layer and inner layer of graft material may be formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration. For some embodiments, the interposed stent is may include a superelastic alloy such as superelastic NiTi alloy. In addition, the graft material of each graft extension may further include at least one axial zone of low permeability for some embodiments.

[0031] For some embodiments, an outside surface of the graft extension may be sealed to an inside surface of the contralateral leg of the main graft when the graft extension is in a deployed state. For some embodiments, the axial length of the ipsilateral and contralateral legs may be sufficient to provide adequate surface area contact with outer surfaces of graft extensions to provide sufficient friction to hold the graft extensions in place. For some embodiments, the ipsilateral and contralateral legs may have an axial length of at least about 2 cm. For some embodiments, the ipsilateral and contralateral legs may have an axial length of about 2 cm to about 6 cm, more specifically, about 3 cm to about 5 cm.

[0032] FIGS. 1-6 show a bifurcated embodiment of a modular graft assembly 10 for treatment of an abdominal aortic aneurysm. The graft assembly 10 includes a bifurcated main graft member 12, an ipsilateral graft extension 14 and contralateral graft extension 15. The main graft 12 has a wall portion 16 that bounds a main fluid flow lumen 18 disposed therein. An ipsilateral leg 20 of the main graft 12 has a ipsilateral port 22 and an ipsilateral fluid flow lumen 24 that is in fluid communication with the main fluid flow lumen 18 and the ipsilateral port 22. A contralateral leg 26 of the main graft 12 has a contralateral port 28 and a contralateral fluid flow lumen 30 that is in fluid communication with the main fluid flow lumen 18 and the

contralateral port 28. The main graft 12, ipsilateral leg 20 and contralateral leg 26 form a bifurcated "Y" shaped configuration.

[0033] The main fluid flow lumen 18 (shown in FIG. 2) of the main graft 12 generally may have a larger transverse dimension and area than a transverse dimension and area of either of the fluid flow lumens 24 and 30 (shown in FIG. 3) of the ipsilateral leg 20 or contralateral leg 26, respectively. A proximal anchor member 32 is disposed at a proximal end 31 of the main graft 12. The proximal anchor member 32 includes a proximal self-expanding stent 32A that is formed from an elongate element having a generally serpentine shape with four crowns or apices at either end. Each proximal apex or crown of the proximal stent 32A is coupled to alternating distal crowns or apices of an 8 crown distal self-expanding stent 32B. The distal self-expanding stent is formed from an elongate element having a generally serpentine shape. A distal end of the distal stent 32B may be mechanically coupled to a connector ring which is embedded in graft material of the proximal end of the main graft 12, or directly coupled to perforations in the proximal edge region of the main graft. Embodiments of the connector ring may be generally circular in shape have regular undulations about the circumference that may be substantially sinusoidal in shape. The proximal stent 32A includes outwardly extending barbs 33, that may be integrally formed with the struts of the stent for some embodiments, having sharp tissue penetrating tips that are configured to penetrate into tissue of an inside surface of a lumen within which the proximal stent 32A is deployed in an expanded state. Although the proximal anchor member 32 is shown as including self-expanding stents 32A and 32B, similar stents may be used that are configured to be inelastically expanded with outward radial pressure as might be generated by the expansion of an expandable balloon from within either or both stents 32A and 32B. The connector ring coupled to the proximal stent 32B may also be inelastically expandable.

[0034] With regard to graft embodiments discussed herein, such as graft assembly 10, and components thereof, as well as graft extensions 14 and 15, the term "proximal" refers to a location towards a patient's heart and the term "distal" refers to a location away from the patient's heart. With regard to delivery system catheters and components thereof discussed herein, the

term "distal" refers to a location that is disposed away from an operator who is using the catheter and the term "proximal" refers to a location towards the operator.

[0035] The ipsilateral graft extension 14 has a fluid flow lumen 44 disposed therein. The ipsilateral graft extension 14 has an outer surface which may be sized and configured to be sealed to an inside surface of the ipsilateral leg of the main graft with the inner fluid flow lumen 44 of the ipsilateral graft extension 14 in fluid communication with the fluid flow lumen 24 of the ipsilateral leg 20. Typically, an outside surface 46 of the graft extension 14 may be sealed to an inside surface 48 of the ipsilateral leg 20 of the main graft 12 when the graft extension 14 is in a deployed state. The contralateral graft extension 15 has a fluid flow lumen 45 disposed therein. The contralateral graft extension 15 has an outer surface 47 which may be sized and configured to be sealed to an inside surface 50 of the contralateral leg 26 of the main graft 12 with the inner fluid flow lumen 45 in fluid communication with the fluid flow lumen 30 of the contralateral leg 26. Typically, an outside surface 47 of the graft extension 15 may be sealed to an inside surface 50 of the contralateral leg 26 of the main graft 12 when the graft extension 15 is in a deployed state. For some embodiments, the axial length of the ipsilateral and contralateral legs 20 and 26 may be sufficient to provide adequate surface area contact between outer surfaces 46 and 47 of graft extensions 14 and 15 and respective inside surfaces 48 and 50 of the legs 20 and 26 to provide sufficient friction to hold the graft extensions 14 and 15 in place. Varying the amount of overlap between the legs and extensions can allow for different effective overall graft lengths to be achieved, thereby accommodating a range of anatomical sizes with fewer distinct main body and extension dimensions than would otherwise be required. For some embodiments, the ipsilateral and contralateral legs 20 and 26 may have an axial length of at least about 1 cm. For some embodiments, the ipsilateral and contralateral legs 20 and 26 may have an axial length of about 2 cm to about 6 cm, more specifically, about 3 cm to about 5 cm.

[0036] The graft extensions 14 and 15 may be formed from an inner layer or layers and outer layer or layers of flexible graft material, such as PTFE or ePTFE. The inner and outer layers of graft material may be formed from tubular extrusions, laminated wraps of multiple layers of graft material or materials, and the like. The inner or outer layers of graft material may be permeable, semi-permeable or substantially non-permeable for some embodiments. For some

embodiments, the nominal length of the extensions 14 and 15 may be permeable with one or more longitudinal sections, such as a middle longitudinal section, being semi-permeable or non-permeable. Some embodiments of the graft extensions 14 and 15 may have an overall tapered or flared configuration with a nominal inner lumen that tapers or flares when the graft extension is in a relaxed expanded state. For embodiments that include laminated wraps of material, the wraps may be carried out circumferentially, helically or in any other suitable configuration.

[0037] A radially expandable stent 51 may be interposed between the outer layer 54 and inner layer 56 of graft material of extensions 14 and 15. The interposed stent disposed between the outer layer and inner layer of graft material may be formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration. The helically wound stent 51 may be configured to be a self-expanding stent or radially expandable in an inelastic manner actuated by an outward radial force from a device such as an expandable balloon or the like. Some tubular prosthesis embodiments that may be used for graft extensions 14 and 15 are discussed in U.S. Patent No. 6,673,103 to Golds et al., filed May 16, 2000 titled "Mesh and Stent for Increased Flexibility", which is hereby incorporated by reference in its entirety herein.

[0038] The graft extensions 14 and 15 may optionally include attachment elements disposed on outer surfaces 46 and 47 (shown in FIG. 3) of their respective proximal ends or sections that may be used to couple to corresponding attachment elements disposed on inside surfaces of the respective ipsilateral leg 20 and contralateral leg of the main graft 12. Attachment element embodiments that may be used on outside surfaces 46 and 47 of the graft extensions 14 and 15 and inside surfaces 48 and 50 of legs 20 and 26 of the main graft 12 may include any of the attachment elements in International Patent Application No. PCT/US2005/008119, entitled "Modular Endovascular Graft", filed March 11, 2005, by Stephens, et al., published September 22, 2005, which is hereby incorporated by reference herein in its entirety. Some embodiments of modular grafts such as system 10 having attachment elements may include a first graft body section such as graft main body 12 and a second graft body section such as extensions 14 and 15. The first graft body section may have a first wall portion and a first attachment element disposed on the first wall portion and the second graft body section may have a second attachment element

disposed on a second wall portion of the second graft body section. The second attachment element may be configured to be secured to the first attachment element with respective fluid flow lumens of the first and second graft body sections sealed together. For some embodiments, the first and second attachment elements may be secured together in an overlapped portion of the first and second graft body sections. For some embodiments, the first attachment element may include a plurality of flexible hooks and the second attachment element includes a plurality of flexible loops adjacent each other wherein the flexible hooks are configured to mechanically engage the flexible loops when the first and second attachment elements are pressed together. For some embodiments, the first attachment element includes a plurality of buttons having an enlarged head portion regularly spaced from each other on a surface a first wall portion and a second attachment element includes an expandable mesh having a plurality of apertures configured to allow entry of the enlarged head portion of the buttons while the mesh is in a circumferentially constrained state and to capture the enlarged head portion of the buttons when the mesh is in a circumferentially expanded state. For some embodiments, the first attachment element includes a plurality of pins radially extending from a surface of a first wall portion and the second attachment element includes an expandable mesh having a plurality of apertures configured to allow entry of the pins when the first attachment element is pressed against the second attachment element. For some embodiments the first attachment element may include an inflatable cuff containing curable material and the second attachment element includes an expandable member with barbs configured to extend outwardly into the inflatable cuff and curable material.

[0039] The transverse dimension or diameter of the main fluid flow lumen 18 of some main graft embodiments 12 in a radially expanded state may be from about 12.0 mm to about 32.0 mm. The transverse dimension or diameter of the ipsilateral and contralateral fluid flow lumens 24 and 30 of the respective ipsilateral leg 20 and contralateral leg 26 may be from about 5 mm to about 20 mm for some embodiments. The axial length of the contralateral leg 26 is indicated by arrow 57 in FIG. 1. For some embodiments, the length of the legs 20 and 26 and may be from about 2 cm to about 6 cm. The transverse dimension of some embodiments of the graft extensions 14 and 15 when in a radially expanded state may be from about 5 mm to about 26 mm. The axial length of some embodiments of the graft extensions 14 and 15 may be from

about 2 cm to about 15 cm, specifically, about 5 cm to about 10 cm. Some embodiments of the ipsilateral and contralateral extension grafts 14 and 15 may have outer transverse dimensions or diameters of between about 10 mm to about 30 mm, more specifically, between about 15 mm and 25 mm when in an expanded state.

[0040] The main graft 12 and ipsilateral graft extensions 14 and 15 may be made at least partially from polytetrafluoroethylene (PTFE) which may include expanded polytetrafluoroethylene (ePTFE). In particular, main graft 12 and graft extensions 14 and 15 may include any number of layers of PTFE and/or ePTFE, including from about 2 to about 15 layers, having an uncompressed layered thickness of about 0.003 inch to about 0.015 inch for the supple graft material or materials alone without supporting or ancillary structures such as high strength stents, connector rings or the like. Unless otherwise specifically stated, the term "PTFE" as used herein includes PTFE, porous PTFE and ePTFE, any of which may be impermeable, semi-permeable, or permeable. Furthermore, the graft assembly and any portions thereof including the main body and extensions described herein may include all PTFE, all ePTFE, or a combination thereof. Such graft body sections may also include any alternative high strength, supple biocompatible materials, such as DACRON, suitable for graft applications. Descriptions of various constructions of graft body sections as well as other components of graft assembly 10 that may be used in any suitable combination for any of the embodiments discussed herein may be found in U.S. Patent Application Ser. No. 10/029,557, publication US 2003/0116260 A1, filed December 20, 2001 by Chobotov, et al., entitled "Method and Apparatus for Manufacturing an Endovascular Graft Section", U.S. Patent Application Ser. No. 10/029,584, filed December 20, 2001 by Chobotov et al., entitled "Endovascular Graft Joint and Method of Manufacture", U.S. Patent Application Ser. No. 10/029,559, entitled "Method and Apparatus for Shape Forming Endovascular Graft Material", filed on December 20, 2001 by Chobotov et al., U.S. Patent No. 7,147,660, filed December 20, 2002, by Chobotov et al., entitled "Advanced Endovascular Graft", U.S. Patent Application Ser. No. 11/106,131, publication US 2006/0233990A1, filed April 13, 2005, by Humphrey et al. entitled "PTFE Layers and Methods of Manufacturing", and U.S. Patent Application Ser. No. 11/106,150, publication US 2006/0233991, filed April 13, 2005, by Humphrey et al., entitled "PTFE Layers and Methods of Manufacturing", the entirety of each of which is incorporated herein by reference.

[0041] The laminated structure of various portions of the graft member 12, including ipsilateral and contralateral legs 20 and 26, extensions 14 and 15, or all of these, may include a variety of configurations wherein laminate materials having similar but different properties may be used together or individually. For example, some embodiments of a main body portion of the graft member 12 may have a laminated structure of about 1 layer to about 5 layers of porous ePTFE material having a mean nodal spacing of about 5 microns to about 35 microns, more specifically, about 10 microns to about 25 microns, and a thickness of about 0.0002 inches to about 0.002 inches, more specifically, about 0.0005 inches to about 0.0015 inches. The main body portion of the graft member 12 may also include about 1 layer to about 5 layers of semi-permeable PTFE having a first permeability and a thickness of about 0.0002 inches to about 0.002 inches, more specifically, about 0.0004 inches to about 0.001 inches. The main body portion may also include about 1 layer to about 5 layers of semi-permeable PTFE material having a second permeability different from the first permeability and a thickness of about 0.0002 inches to about 0.002 inches, more specifically, about 0.0004 inches to about 0.001 inches. Any suitable embodiments of the semi-permeable layers of PTFE discussed in U.S. Patent Applications 2006/0233990 and 2006/0233991, incorporated by reference above, may be used in these embodiments. The main body portion may also include about 1 layer to about 5 layers of PTFE having essentially no nodal spacing and very low or no liquid permeability and a thickness of about 0.0001 inches to about 0.0015 inches, more specifically, about 0.0002 inches to about 0.001 inches.

[0042] For embodiments of modular graft systems that do not include the attachment elements, outside surfaces 46 and 47 of the proximal ends of the graft extensions 14 and 15 may be expanded against the inside surfaces 48 and 50, respectively, of the fluid flow lumens of legs 20 and 26 of the graft member 12. This configuration may be used to seal the fluid flow lumens 44 and 45 of the graft extensions 14 and 15 to the fluid flow lumens 24 and 30 of the legs 20 and 26. Expandable members, such as expandable anchor members and the like, may be used to expand the graft extensions 14 and 15 against the inside surfaces 48 and 50 of the fluid flow lumens 24 and 30 of the legs 20 and 26.

[0043] A network of inflatable elements or channels 58 is disposed on the main graft 12 which may be inflated under pressure with an inflation material (not shown) through a main fill port 60 that has a lumen disposed therein in fluid communication with the network of inflatable channels 58. The inflation material may be retained within the network of inflatable channels 58 by a one way-valve (not shown), disposed within the lumen of the main fill port 60. The network of inflatable channels 58 may optionally be filled with a hardenable material that may be configured to harden, cure or otherwise increase in viscosity or become more rigid after being injected into the channels. Hardenable inflation materials such as gels, liquids or other flowable materials that are curable to a more solid or substantially hardened state may be used to provide mechanical support to the main graft 12 and legs by virtue of the mechanical properties of the hardened material disposed within the channels. The network of inflatable channels 58 may also provide structural support to the main graft 12 when in an inflated state due to the stiffness of the channels created by the increased interior pressure within the channels even if a non-hardenable inflation material, such as saline or the like, is used so long as an increased interior pressure can be maintained. Such an increase in stiffness or rigidity may be useful for a variety of purposes. For example, during deployment, inflation of the network of inflatable channels may urge the main graft body including the main flow channel and legs thereof to conform to a generally cylindrical configuration having open flow lumens which may be useful when attempting to locate and navigate the flow lumens of the contralateral or ipsilateral leg with a delivery catheter, guidewire or the like. Such location and navigation of the flow lumens of the main graft body and portions thereof may also be facilitated by the use of radiopaque inflation materials that provide enhanced visualization under fluoroscopic imaging.

[0044] The network of inflatable channels 58 may include one or more circumferential channels disposed completely or partially about the main graft or legs of the main graft as well as longitudinal or helical channels that may provide support as well as a conduit in communication with the circumferential channels that may be used for filling the network of inflatable channels with inflation material. Some embodiments may also employ radiopaque inflation material to facilitate monitoring of the fill process and subsequent engagement of graft extensions. The network of inflatable channels 58 may also include one or more one or more enlarged circumferential channels in the form of inflatable cuffs, such as proximal inflatable cuff 62,

which may be configured to seal to an inside surface of a patient's vessel such as a patient's abdominal aorta. Proximal inflatable cuff 62 is disposed on a proximal portion of the main graft 12 distal of the proximal anchor member 32 and has an outer surface that extends radially from a nominal outer surface of the main graft 12. The inflatable cuff 62 may be configured to expand radially beyond a nominal outer surface of the main graft 12 and provide a seal against an inside surface of a body lumen when the inflatable cuff 62 is inflated with an inflation material to an expanded state. The axial separation of the proximal anchor member 32 and proximal inflatable cuff 62 allows for spatial separation of the primary anchoring mechanism and at least part of the sealing function which may allow the graft to be restrained or otherwise compressed to a smaller outer profile for deployment from a delivery catheter. An interior cavity of the inflatable cuff 62 is in fluid communication with the interior cavity of the remaining network of inflatable channels and may have a transverse dimension or inner diameter of about 0.040 inch to about 0.250 inch.

[0045] Some embodiments of main graft member 12 may include about 1 to about 8 circumferential inflatable channels disposed about each leg 20 and 26 and about 1 to about 8 circumferential channels disposed about a main body portion of the main graft member 12. Some embodiments of the main graft body member 12 may include about 1 to about 4 longitudinal or axial inflatable channels that may serve to connect the circumferential inflatable channels. Some embodiments of the circumferential channels may extend a full circumference of the graft section upon which they are disposed, or they may extend only partially around the graft section upon which they are disposed. For the main graft member embodiment 12 shown in FIG. 1, the network of inflatable channels 58 includes the inflatable cuff 62 disposed adjacent the proximal end of the main body portion of the main graft member 12 and a circumferential channel disposed just distal of the inflatable cuff 62. Each leg 20 and 26 of the main graft member 12 includes 3 complete circumferential inflatable channels in axial series. Each leg 20 and 26 also has two partial circumferential inflatable channels disposed proximal of the complete circumferential inflatable channels. A longitudinal or axial channel extends substantially along the ipsilateral side of the main graft member 12 in fluid communication with the fill port 60 and circumferential channels of the ipsilateral leg 20 and the circumferential channels and inflatable cuff 62 at the proximal end of the main body portion. Another axial channel extends along the entire contralateral side of the main graft member 12 in fluid communication with the cuff 62,

circumferential channel at the proximal end of the main body portion and the circumferential channels of the contralateral leg 26.

[0046] Some of the inflatable channels of the graft member embodiments discussed herein may be disposed circumferentially and axially such as shown in the embodiment of FIG. 1. Alternatively, such inflatable channels may be disposed in spiral, helical, or other configurations. Examples of channel configurations suitable for embodiments of the present invention are described further in commonly-owned pending U.S. Patent Application Ser. No. 10/384,103, filed March 6, 2003 and entitled "Kink Resistant Endovascular Graft" to Kari et al., the entirety of which is incorporated herein by reference. All inflatable channel embodiments described herein as circumferential, may alternatively take on any of the aforementioned alternative configurations. Other modular graft embodiments are discussed in pending U.S. Patent Application Ser. No. 11/097,718, 2006/0224232, by Chobotov et al. titled "Hybrid Modular Endovascular Graft", filed April 1, 2005, which is hereby incorporated by reference herein in its entirety.

[0047] The inflatable cuff 62 and other network of inflatable channels 58 may be filled during deployment of the graft with any suitable inflation material. As discussed above, the inflation material may be used to provide outward pressure or a rigid structure from within the inflatable cuff 62 or network of inflatable channels 58. Biocompatible gases, liquids, gels or the like may be used, including curable polymeric materials or gels, such as the polymeric biomaterials described in pending U.S. Patent Application Ser. No. 09/496,231 filed February 1, 2000, and entitled "Biomaterials Formed by Nucleophilic Addition Reaction to Conjugated Unsaturated Groups" to Hubbell et al. and pending U.S. Patent Application Ser. No. 09/586,937, filed June 2, 2000, and entitled "Conjugate Addition Reactions for Controlled Delivery of Pharmaceutically Active Compounds" to Hubbell et al. and further discussed in commonly owned pending U.S. Patent Application Ser. No. 10/327,711, filed December 20, 2002, and entitled "Advanced Endovascular Graft" to Chobotov, et al., each of which is incorporated by reference herein in its entirety. Some embodiments may use inflation materials formed from glycidyl ether and amine materials, as discussed in U.S. Patent Application Ser. No. 11/097,467, publication number 2006/0222596, filed April 1, 2005, and entitled "Non-Degradable, Low-

Swelling, Water Soluble Radiopaque Hydrogel Polymer" to Askari and Whirley. Some inflation material embodiments may include an in situ formed hydrogel polymer having a first amount of diamine and a second amount of polyglycidyl ether wherein each of the amounts are present in a mammal or in a medical device, such as an inflatable graft, located in a mammal in an amount to produce an in situ formed hydrogel polymer that is biocompatible and has a cure time after mixing of about 10 seconds to about 30 minutes and wherein the volume of said hydrogel polymer swells less than 30 percent after curing and hydration. Some embodiments of the inflation material may include radiopaque material such as sodium iodide, potassium iodide, barium sulfate, Visipaque 320, Hypaque, Omnipaque 350, Hexabrix and the like. For some inflation material embodiments, the polyglycidyl ether may be selected from trimethylolpropane triglycidyl ether, sorbitol polyglycidyl ether, polyglycerol polyglycidyl ether, pentaerythritol polyglycidyl ether, diglycerol polyglycidyl ether, glycerol polyglycidyl ether, trimethylolpropane polyglycidyl ether, polyethylene glycol diglycidyl ether, resorcinol diglycidyl ether, glycidyl ester ether of p-hydroxy benzoic acid, neopentyl glycol diglycidyl ether, 1,6-hexanediol diglycidyl ether, bisphenol A $(PO)_2$ diglycidyl ether, hydroquinone diglycidyl ether, bisphenol S diglycidyl ether, terephthalic acid diglycidyl ester, and mixtures thereof. For some inflation material embodiments, the diamine may be selected from (poly)alkylene glycol having amino or alkylamino termini selected from the group consisting of polyethylene glycol (400) diamine, di-(3-aminopropyl) diethylene glycol, polyoxypropylenediamine, polyetherdiamine, polyoxyethylenediamine, triethyleneglycol diamine and mixtures thereof. For some embodiments, the diamine may be hydrophilic and the polyglycidyl ether may be hydrophilic prior to curing. For some embodiments, the diamine may be hydrophilic and the polyglycidyl ether is hydrophobic prior to curing. For some embodiments, the diamine may be hydrophobic and the polyglycidyl ether may be hydrophilic prior to curing.

[0048] Other inflation materials that may be used for some embodiments include polyethylene oxide materials and neopentyl glycol diacrylate materials which are discussed in U.S. Patent Nos. 6,610,035 and 6,176,849, which are incorporated by reference herein in their entirety. U.S. Patent No. 7,147,660 discussed above also includes inflation material embodiments that may be used for embodiments discussed herein.

[0049] Referring to FIG. 1A, the proximal anchor member 32 may be disposed on a proximal end of the main graft 12 and be secured to the connector ring 68 which is at least partially disposed on a proximal portion of the main graft 12. For some embodiments, the connector ring 68 may be embedded in the graft material of the proximal section of the main graft 12 and may also be secured by one or more flap elements of a PTFE layer or layers adjacent the connector ring 68. The flaps of adjacent layers may be folded over the connector ring and secured to the connector ring 68, adjacent layers of PTFE material or both. Adhesive materials such as FEP or the like may also be used to secure the connector ring 68 to the main graft body 12. The proximal connector ring 68 has connector elements 70 extending proximally from the connector ring 68 beyond the proximal end of the graft material of the main graft 12. The connector elements may be used to couple or be otherwise be secured to mating connector elements of the proximal anchor member 32 which extend distally from the distal side of the distal stent 32B of the proximal anchor member 32. The proximal anchor member 32 may have a cylindrical or ring-like configuration generally with elongate elements of the proximal and distal stents 32A and 32B of the anchor member being preformed in a serpentine or sine wave pattern of the cylinder. The proximal anchor member may have a transverse dimension or diameter that allows for anchoring in a variety of body lumen configurations. Some embodiments of a proximal anchor member 32 which may be suitable for use in a patient's abdominal aorta may have a transverse dimension or diameter of about 20 mm to about 40 mm. The elongate elements that form the proximal anchor member 32 may have a radial thickness of about 0.005 inch to about 0.040 inch. The width of the elongate elements that form the proximal anchor member 32 may be from about 0.01 inch to about 0.2 inch. U.S. Patent No. 7,147,660 discussed above also includes anchor member embodiments that may be used for embodiments discussed herein.

[0050] The proximal anchor member 32 is secured to the connector ring 68 with flanged connector elements 70 as shown in FIGS. 5A and 5B. The flanged connector elements 70 may be secured together with wire coils 70A configured to fit between ears of the flanged portions of the connector elements 70 that have a transverse dimension that is greater than a middle portion of the connector elements 70. The flanged portions provide a pair of opposed surfaces for the coil 70A to seat against and mechanically capture two adjacent connector elements 70 together.

The wire coils 70A used to couple the flanged elements may have an inner transverse dimension of about 0.005 inch to about 0.050 inch, more specifically, about 0.010 inch to about 0.030 inch, and have an axial length of about 2 to about 15 times their diameter, more specifically, about 4 to about 8 times their diameter.

[0051] Referring again to FIG. 1A, the proximal stent 32A is coupled to the distal stent 32B of the proximal anchor member 32 with struts 71 disposed between adjacent crowns of the two stents which are shown in more detail in FIGS. 6A-6D. The struts may be configured such that the cross sectional area of the material of the stents 32A and 32B and struts remains substantially constant from the proximal portion of the distal stent to the distal portion of the proximal stent. For some embodiments, the cross sectional area of the material in the area of the struts 71 is greater than the cross sectional area of either the proximal stent 32B or distal stent 32A adjacent the struts 71. Such a configuration may be useful in avoiding stress and strain concentrations at the junctions between the proximal and distal stents 32A and 32B.

[0052] A similar structural configuration may be used at the junction between the connector ring 68 and the distal end of the distal stent 32B. For this junction, the struts 72 disposed between the connector ring 68 and connector elements 70, as shown in FIG. 5A, may have a cross sectional area substantially the same as or greater than the cross sectional area of the connector ring 68 adjacent the connector element 70. In addition, the struts 73 disposed between the distal end of the distal stent 32B and the connector elements 70 of the distal stent 32B may have a cross sectional area that is substantially the same or greater than the cross sectional area of the distal stent 32B adjacent the strut 73. This configuration may be useful in avoiding stress and strain concentrations in the junction between the connector ring 68 and the distal stent 32B of the proximal anchor member 32.

[0053] The proximal anchor member 32 and components thereof may have a variety of configurations which may be collapsible to a small transverse dimension or diameter for percutaneous or other types of delivery and be expandable to engage the inside surface of the patient's vasculature to provide anchoring to the vasculature and prevent or oppose axial movement of the anchor member or the graft section attached thereto. Anchor member

embodiments 32 may be configured as a self-expanding anchor member having an undulating pattern and may be made from stainless steel, nickel titanium alloy or any other suitable material. The anchor member 32 may be configured to be balloon expandable or self-expanding in an outward radial direction from a radially compressed state. The distal anchor member 32 and connector ring 68 may be formed by cutting the configuration of these elements from a single tubular piece of a selected material, such as the materials discussed above. The proximal stent 32A of the anchor member 32 may also optionally include barbs 33 that are angled outwardly from the anchor members and are configured to engage tissue of the vessel wall and prevent axial movement of the anchor members once deployed. The proximal anchor member 32 and proximal and distal stents 32A and 32B thereof may have the same or similar features, dimensions or materials to those of the stents described in U.S. Patent Application Ser. No. 10/327,711, US 2003/0125797 A1, filed December 20, 2002, by Chobotov et al. which is hereby incorporated by reference in its entirety. The distal stent 32B of anchor member 32 may also be secured to connector ring 68 in the same or similar fashion as described in the incorporated application above.

[0054] It may be useful for some embodiments of the main graft 12 to have a nominal axial length which is configured to allow the use of the main graft 12 in a wide variety of vascular morphologies with supplementation by one or more graft extensions 14 and 15. A modular graft embodiment 10 is normally chosen in order to have a proper fit to the patient's vasculature. For some graft indications, it is necessary to produce a large number of size variations of the graft system, or graft assembly 10 components, in order to accommodate the size and configuration variations of each patient's vasculature in order to achieve an acceptable fit of the graft assembly 10 within the patient's vasculature. This can be very costly and time consuming for the manufacturer of the endovascular graft assembly 10 and the hospitals which must maintain a comprehensive inventory of the devices. In addition, this may require an inconvenient amount of shelf space in the hospital operating room or catheter lab. For some embodiments, main graft member 12 may have an axial length that is selected to allow anchoring of the proximal anchor member 32 adjacent the renal arteries extending from a patient's aorta with the legs of the bifurcated portion remaining clear of the iliac arteries in a large cross section of patients having

diverse physical size and vascular configurations. In this way, the need for customizing a graft assembly 10 for a particular patient or group of patients can be avoided.

[0055] For some embodiments, the axial length of the main graft member 12, and particularly the axial distance or separation between the proximal anchor member 32 and distal end of the ipsilateral and contralateral legs 20 and 26 may be selected to extend across an abdominal aortic aneurysm without extending into the iliac arteries of a selected patient. A selected patient may be a member of a group of patients who has the longest axial separation between the sealing point in the aorta just distal to the renal arteries and a distal most viable anchor and sealing point in the iliac arteries. In some embodiments for a particular patient group, the proximal end of the main graft member 12 is axially separated from the distal ends of the ipsilateral and contralateral legs 20 and 26 by a length of about 5 cm to about 10 cm, more specifically, about 6 cm to about 8 cm, as indicated by the arrow 74 in FIG. 1.

[0056] For some embodiments of sizing a main graft member embodiment 12, the separation of the proximal anchor member 32 and distal end of deployed graft extensions 14 and 15 is selected such that the separation is just long enough to span the separation between the renal arteries and the proximal most anchor and sealing point in the iliac artery or arteries of a patient. This distance may be determined from the patient, in a selected group of patients, that has the longest such separation in the selected group of patients. In addition, for these embodiments, this separation must be shorter than the separation between the renal arteries and hypogastric artery or arteries. The distance may be determined from the patient, in the selected group of patients, that has the shortest such separation in the selected group of patients. In this way, it may be possible to treat all members of a selected group of patients with a main graft member 12 embodiment or embodiments which have a common main graft body length. Such embodiments may be anchored to the patient's aorta distal of the patient's renal arteries and anchored distally in the patient's iliac artery or arteries, without blocking either the renal arteries or hypogastric artery or arteries. Such a modular graft system embodiment 10 may have an overall length including the main graft member 12 and deployed graft extensions 14 and 15 of about 10 cm to about 22 cm, specifically, about 11 cm to about 20 cm.

[0057] The careful sizing and configuring of the main graft 12 allows the use of a single main graft 12 embodiment or design to be adaptable to a wide range of patients when supplemented by one or more graft extensions 14 and 15. More specifically, a main graft 12 having an axial length of about 5 cm to about 8 cm may be properly deployed in a large percentage of potential patients. Once deployed, the fluid flow lumens 24 and 30 of the ipsilateral and contralateral legs 20 and 26 of the main graft 12 can then be sealed to the patient's iliac arteries with the deployment of graft extensions 14 and 15. Although the graft assembly 10 includes the option of using attachment elements to secure the graft extensions 14 and 15 to the ipsilateral leg and contralateral leg of the main graft 12, this may not be necessary in most cases and an adequate seal and mechanical fixation of a graft extensions 14 and 15 may be achieved with the use of a standard expandable member on the graft extensions 14 and 15 instead of an attachment element.

[0058] Some embodiments of a method of treating a patient include providing a delivery catheter containing a radially constrained bifurcated main graft member. The main graft member may be formed from a supple graft material which has a main fluid flow lumen therein and which has an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen and a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen. The main graft member may also include a network of inflatable channels disposed on the main graft member. Inflatable channels of the network of inflatable channels may be disposed on any portion of the main graft member including the ipsilateral and contralateral legs of the main graft member. The main graft member may also include a proximal anchor member which is disposed at a proximal end of the main graft member and secured to the main graft member. The proximal anchor member may have a self-expanding proximal stent portion secured to a self-expanding distal stent portion.

[0059] Such a delivery catheter may be axially positioned within the patient's vasculature such that the main graft member within the delivery catheter is disposed coextensively with a vascular defect of the patient's aorta. Once this positioning has been achieved, the proximal anchor member may be deployed so as to engage an inner surface of the patient's vasculature and anchor the proximal anchor member to the patient's aorta. Thereafter, the network of inflatable

channels of the main graft member may be inflated with an inflation material so as to provide a more mechanically rigid structure. For some embodiments, a curable or hardenable fill material may be used that may be cured after inflation of the network of inflatable channels so as to provide additional mechanical rigidity as well as prevent leakage of the fill material. Some embodiments may also employ radiopaque inflation material to facilitate monitoring of the fill process and subsequent engagement of graft extensions.

[0060] A second delivery catheter containing a radially constrained self-expanding contralateral graft extension may then be axially positioned in the contralateral leg of the main graft member with a proximal portion of the contralateral graft extension axially overlapped with an inner fluid flow lumen of the contralateral leg of the main graft member and a distal portion of the contralateral graft extension axially overlapped with a portion of the patient's contralateral iliac artery. Access to the contralateral leg of the main graft portion may be achieved by percutaneous access or femoral arteriotomy from the patient's contralateral femoral artery with a delivery sheath or the like. Once properly positioned, the self-expanding contralateral graft extension may be deployed by releasing the radial constraint of the second delivery catheter. As the contralateral graft extension self expands in an outward radial orientation, a seal between the inner fluid flow lumen of the contralateral graft extension, a fluid flow lumen of the contralateral leg and a fluid flow lumen of the contralateral iliac artery may be formed.

[0061] A third delivery catheter containing a radially constrained self-expanding ipsilateral graft extension may then be axially positioned in the ipsilateral leg of the main graft member with a proximal portion of the ipsilateral graft extension axially overlapped with an inner fluid flow lumen of the ipsilateral leg of the main graft member and a distal portion of the ipsilateral graft extension axially overlapped with a portion of the patient's ipsilateral iliac artery. The self-expanding ipsilateral graft extension may then be deployed by releasing the radial constraint so as to form a seal between the inner fluid flow lumen of the ipsilateral graft extension, a fluid flow lumen of the ipsilateral leg and a fluid flow lumen of the ipsilateral iliac artery.

[0062] For some method embodiments of treating the vasculature of a patient, a modular graft assembly, such as the modular graft assembly embodiments 10 discussed above, may be

used. FIGS. 7-14 illustrate an embodiment of a deployment sequence of an embodiment of a modular graft assembly. For endovascular methods, access to a patient's vasculature may be achieved by performing an arteriotomy or cut down to the patient's femoral artery or by other common techniques, such as the percutaneous Seldinger technique. For such techniques, a delivery sheath (not shown) may be placed in communication with the interior of the patient's vessel such as the femoral artery with the use of a dilator and guidewire assembly. Once the delivery sheath is positioned, access to the patient's vasculature may be achieved through the delivery sheath which may optionally be sealed by a hemostasis valve or other suitable mechanism. For some procedures, it may be necessary to obtain access via a delivery sheath or other suitable means to both femoral arteries of a patient with the delivery sheaths directed upstream towards the patient's aorta. In some applications a delivery sheath may not be needed and the delivery catheter 75 may be directly inserted into the patient's access vessel by either arteriotomy or percutaneous puncture.

[0063] Once the delivery sheath or sheaths have been properly positioned, a delivery catheter 75 containing a modular graft assembly component, such as graft member 12, may then be advanced over a guidewire 76 through the delivery sheath and into the patient's vasculature. In one specific deployment method embodiment, the main graft member 12 is advanced within a delivery catheter 75 through the patient's vessel, typically in a proximal direction from the ipsilateral iliac artery, to a desired site of deployment, such as the abdominal aorta, in a constrained state via a catheter or like device having a low profile and lateral flexibility for ease of delivery through the patient's vasculature. At the desired site of deployment, the proximal anchor member 32 of the main graft 12 is released from a constrained state and the proximal anchor member 32 is allowed to expand and secure a portion of the main graft 12 to the patient's vasculature. Deployment of the modular graft assembly 10 may be carried out by any suitable devices and methods, including techniques and accompanying apparatus as disclosed in U.S. Patent No. 6,761,733, entitled "Delivery Systems and Methods for Bifurcated Endovascular Graft" to Chobotov et al., filed on July 27, 2001, and U.S. Patent Application No. 11/205,793, entitled "Delivery System and Method for Bifurcated Graft" to Chobotov et al., filed August 15, 2005, which are incorporated by reference herein in their entirety.

[0064] The delivery catheter 75 may be advanced proximally upstream of blood flow, as indicated by arrows 77, into the vasculature of the patient including the iliac artery 78 and aorta 79 shown in FIG. 7. Other vessels of the patient's vasculature shown in the figures include the renal arteries 80 and hypogastric arteries 81. The delivery catheter 75 may be advanced into the aorta 79 of the patient until the main graft 12 is disposed substantially adjacent an aortic aneurysm 82 or other vascular defect to be treated. Once the delivery catheter 75 is so positioned, an outer sheath 83 of the delivery catheter 75 may be retracted distally so as to expose the main graft 12 which has been compressed and compacted to fit within the inner lumen of the outer sheath 83 of the delivery catheter 75 as shown in FIG. 8. In addition to being radially compressed when disposed within an inner lumen of the outer sheath 83 of the delivery catheter 75, the proximal stent 32A and distal stent 32B have been radially restrained by respective high strength flexible belts 86 in order to maintain a small profile and avoid engagement of the stents 32A and 32B with a body lumen wall until deployment of the stents 32A and 32B is initiated. The ends of the belts 86 may be secured by one or more wires or elongate rods 88 which extend through looped ends of the belts 86. Once the outer sheath 83 of the delivery catheter 75 has been retracted, the delivery catheter 75 and graft assembly embodiment 10 may be carefully positioned in an axial direction such that the distal stent 32B is disposed substantially even with the renal arteries 80 with the proximal anchor member 32 and proximal sealing cuff 62 positioned proximal of the aneurysm 82. The proximal anchor member 32 is then deployed and anchored to the patient's aorta 79.

[0065] Deployment of the proximal anchor member 32 may begin with deployment of the distal stent 32B by retracting the wire or rod 86 that couples ends of belt 88 restraining distal stent 32B. Additional axial positioning may typically be carried out even after deploying the distal stent 32B of the proximal anchor member 32. This may still be carried out in many circumstances as the distal stent portion 32B of the distal anchor 32 does not include tissue engaging barbs 33 for some embodiments and will provide only partial outward radial contact or frictional force on the inner lumen of the patient's vessel 79 until the proximal stent 32A is deployed. Once the belt 86 constraining the distal stent 32B has been released, the distal stent 32B self-expands in an outward radial direction until an outside surface of the proximal stent

32B makes contact with and engages an inner surface 90 of the patient's vessel 79 as shown in FIG. 9.

[0066] After the distal stent 32B has been deployed, the proximal stent 32A may then be deployed by retracting the wire 88 that couples the ends of the belt 86 restraining the proximal stent 32B. As the proximal stent 32A self-expands in an outward radial direction, an outside surface of the proximal stent 32A eventually makes contact with the inside surface 90 of the patient's aorta 79. For embodiments that include tissue engaging barbs 33 on the proximal stent 32A, the barbs may also be oriented and pushed in an outward radial direction so as to make contact and engage the inner surface tissue 90 of the patient's vessel 79, which further secures the proximal anchor member 32 to the patient's vessel 79 as shown in FIG. 10.

[0067] Once the proximal anchor member 32 has been secured to the inside surface 90 of the patient's vessel 79, the proximal inflatable cuff 62 may then be filled through the inflation port 60 with inflation material injected through an inflation tube 91 of the delivery catheter 75 which may serve to seal an outside surface of the inflatable cuff 62 to the inside surface 83 of the vessel 79. The remaining network of inflatable channels 58 are also filled with pressurized inflation material at the same time which provides a more rigid frame like structure to the graft 12 as shown in FIG. 11. For some embodiments, the inflation material may be a curable or hardenable material that may cured or hardened once the network of inflatable channels are filled to a desired level of material or pressure within the network. Some embodiments may also employ radiopaque inflation material to facilitate monitoring of the fill process and subsequent engagement of graft extensions. The material may be cured by any of the suitable methods discussed herein including time lapse, heat application, application of electromagnetic energy, ultrasonic energy application, chemical adding or mixing or the like.

[0068] The network of inflatable channels 58 may be partially or fully inflated by injection of a suitable inflation material into the main fill port 60 to provide rigidity to the network of inflatable channels 58 and the main graft 12. In addition, a seal is produced between the inflatable cuff 62 and the inside surface of the abdominal aorta 82. Although it is desirable to partially or fully inflate the network of inflatable channels 58 of the main graft 12 at this stage of

the deployment process, such inflation step optionally may be accomplished at a later stage if necessary.

[0069] Once the graft member 12 is anchored and the inflatable channels 58 thereof have been filled and expanded, a second delivery catheter 92 that contains the contralateral graft extension 15 may access the contralateral femoral artery directly or through a delivery sheath as discussed above. The second delivery catheter may be advanced proximally, as shown in FIG. 12, until the radially compressed contralateral graft extension 15 is in an axial position which overlaps the contralateral leg 26 of the graft member 12. The amount of desired overlap of the graft extension 15 with the contralateral leg 26 may vary depending on a variety of factors including vessel morphology, degree of vascular disease, patient status and the like. However, for some embodiments, the amount of axial overlap between the contralateral graft extension 15 and the contralateral leg 26 may be about 1 cm to about 5 cm, more specifically, about 2 cm to about 4 cm. This overlapped position may also provide for longitudinal overlap between the fluid flow lumen 45 of the graft extension 15 with the fluid flow lumen of the contralateral leg 26.

[0070] Once properly positioned, an outer sheath 94 of the second delivery catheter 92 which may radially restrain the contralateral graft extension 15, may be distally withdrawn while the graft extension 15 remains substantially axially fixed. This axial retraction of the outer sheath 94 of the second delivery catheter 92 deploys the contralateral graft extension 15 so as to allow the graft extension 15 to radially self-expand and engage the inner lumen 30 of the contralateral leg 26 and inner surface of the contralateral iliac artery proximal of the contralateral leg 26 as shown in FIG. 13. The graft extension 15 may be so deployed to extend the contralateral leg 20 of the main graft 12 with the inner lumen 30 of the contralateral leg 26 sealed to the inner lumen 45 of the graft extension 15. Once the contralateral graft extension 15 has been deployed, the second delivery catheter 92 may be withdrawn from the patient's vasculature.

[0071] For some embodiments, up to the time that the network of inflatable channels 58 have been filled with inflation material which has been cured or hardened, an elongate tether 96 may be used to axially restrain the graft 12 and prevent axial separation of the graft 12 from the

delivery catheter 75. This axial restraint may be important for embodiments wherein the inflation tube 91 of the delivery catheter 75 is secured to the fill port 60 of the network of inflatable channels 58 of the graft member 12 by an overlapped slip fit or interference fit only. For some embodiments, the inflation tube 91 may overlap with the fill tube 60 of the graft 12 by about 5 mm to about 25 mm, more specifically, about 10 mm to about 15 mm. The tether 96 loops through the flow lumens 24 and 30 of the ipsilateral and contralateral legs 20 and 26 of the graft member 12 and is secured to a handle on a proximal adapter (not shown) of the delivery catheter 75. The tether 96 is configured to have a length that is short enough to mechanically restrain distal axial movement of the main graft member 12 relative to the delivery catheter 75 so as to prevent decoupling of the inflation tube 91 from the inflation or fill port 60 of the main graft member 12. Once the inflation material has been fully injected into the network of inflatable channels 58 and cured or hardened, the tether 96 may be released and removed to allow distal retraction of the delivery catheter 75 as shown in FIG. 14.

[0072] Once the tether 96 has been released and the delivery catheter 75 retracted and decoupled from the graft main member 12 and patient's vasculature generally, a third delivery catheter (not shown) which contains the ipsilateral graft extension 14 may be advanced into the patient's vasculature directly or through an ipsilateral delivery sheath as discussed above. The third delivery catheter may have the same features, dimensions and materials as those of the second delivery catheter 92. The third delivery catheter may be advanced proximally through the patient's femoral artery and into the ipsilateral iliac artery 78 until the radially compressed ipsilateral graft extension 14 is in an axial position which overlaps the ipsilateral leg 20 of the graft member 12. Although not shown, this advancement of the third delivery catheter may be carried out in a manner which is the same as or similar to the deployment of the second delivery catheter 92 used for deployment of the contralateral graft extension 15 discussed above. The amount of desired overlap of the graft extension 14 with the ipsilateral leg 20 may once again vary depending on a variety of factors including vessel morphology, degree of vascular disease, patient status and the like. However, for some embodiments, the amount of axial overlap between the ipsilateral graft extension 14 and the ipsilateral leg 20 may be about 1 cm to about 5 cm, more specifically, about 2 cm to about 4 cm.

[0073] This overlapped position may also provide for longitudinal overlap between the fluid flow lumen 44 of the graft extension 14 with the fluid flow lumen 24 of the ipsilateral leg 20. Once properly positioned, an outer sheath of the third delivery catheter which may be configured to radially restrain the ipsilateral graft extension 14, may be distally withdrawn while the graft extension 14 remains substantially axially fixed. This axial retraction of the outer sheath of the third delivery catheter deploys the ipsilateral graft extension 14 so as to allow the graft extension 14 to radially self-expand and engage the inner lumen of the ipsilateral leg 20 and inner surface of the ipsilateral iliac artery proximal of the ipsilateral leg 20 as shown in FIG. 14. The extension 14 may be so deployed to extend the ipsilateral leg 20 of the main graft 12 with the inner lumen of the ipsilateral leg 20 sealed to the inner lumen 44 of the graft extension 14.

[0074] For some deployment embodiments, the patient's hypogastric arteries may be used to serve as a positioning reference point to ensure that the hypogastric arteries are not blocked by the deployment. Upon such a deployment, the distal end of a graft extension 14 or 15 may be deployed anywhere within a length of the ipsilateral or contralateral leg of the graft 12. Also, although only one graft extension is shown deployed on the ipsilateral side and contralateral side of the graft assembly 10, additional graft extensions 14 and 15 may be deployed within the already deployed graft extensions 14 and 15 in order to achieve a desired length extension of the ipsilateral leg 20 or contralateral leg 26. For some embodiments, about 1 to about 5 graft extensions 14 or 15 may be deployed on either the ipsilateral or contralateral sides of the graft assembly 10. Successive graft extensions 14 and 15 may be deployed within each other so as to longitudinally overlap fluid flow lumens of successive graft extensions.

[0075] Graft extensions 14 and 15, which may be interchangeable for some embodiments, or any other suitable extension devices or portions of the main graft section 12 may include a variety of suitable configurations. For some embodiments, graft extensions 14 and 15 may include a PTFE covered helical nitinol stent 51 as discussed above with layers of PTFE having a variety of characteristics. Regarding the stent 51, it may be formed from an elongate resilient element which is helically wound with a plurality of longitudinally spaced turns. Some stent embodiments 51 may be generally helical in configuration with serpentine or other regularly spaced undulations transverse to the helical path of the elongate stent element as shown in more

detail in FIG. 15. The ends of the stent element may be secured to adjacent ring portions of the stent 51 as shown to avoid exposure of element ends to either PTFE graft material or possible patient tissues. The stent element of the stent 51 shown in FIG. 15 is a continuous element from one end of the extension 14 to the other end thereof. The ends of the elongate element may be secured to adjacent ring members by any suitable means such as adhesive bonding, welding such as laser welding, soldering or the like. For some embodiments, the stent element may have a transverse dimension or diameter of about 0.005 inch to about 0.015 inch.

[0076] For some embodiments of graft extension 14, layers of materials having different properties may be used in combination to achieve a desired clinical performance. For example, some layers of PTFE covering the stent 51 may be permeable, semi-permeable or substantially non-permeable depending on the desired performance and material properties. FIG. 16 illustrates a transverse cross sectional view of an embodiment of extension 14 of FIG. 15 that shows an outer layer of PTFE 54 and an inner layer of PTFE 56. The layers 54 and 56 may be applied by a variety of methods and have a variety of configurations. For example, some layer embodiments may include extruded tubular structures applied axially over a mandrel or subassembly. Some layer embodiments 54 and 56 may be applied by wrapping layers circumferentially or wrapping tapes or ribbons in an overlapping helical pattern. For some embodiments, the outer layer 54 may be made from or include a semi-permeable or substantially non-permeable PTFE layer 100 and the inner layer 56 may be made of or include a permeable layer of PTFE 102.

[0077] The extension 14 may be made by forming the layers of material 100 and 102 together with the stent 51 over a mandrel, such as a cylindrical mandrel (not shown). Once the innermost layer 102 of the extension 14 has been wrapped about a shaped mandrel, a helical nitinol stent, such as helical stent 51, may be placed over the the innermost layered PTFE layer 56 and underlying mandrel. One or more additional layers of low permeability PTFE film or PTFE film having substantially no permeability 100 that does not have the traditional node fibril microstructure may be wrapped or otherwise added over the exterior of the stent 51. The mandrel may then be covered with a flexible tube such that the film and stent is sandwiched under pressure and sintered so as to raise the temperature for the PTFE material to undergo a

melt transformation in order to lock in its geometry and strength. The flexible tube (a manufacturing aid not shown) is removed from over the device and the resultant extension is removed from the mandrel.

[0078] FIG. 16 illustrates the layered structure of an extension embodiment 14 that has been conformed to a mandrel with the layers of PTFE material over the stent conforming to the stent element so as to form a cohesive structure. In addition, for some embodiments, an adhesives such as FEP or the like may be applied adjacent the stent prior to the application of the PTFE layer covering the stent, or at any other suitable time or location, in order to facilitate a bond between the stent element and the PTFE materials 100 and 102 adjacent the stent 51. For the embodiment of extension 14 shown in FIG. 16, the extension may have the same features, dimensions and materials as those discussed above with regard to the extension embodiment 14 shown in FIGS. 1-6. For some embodiments, the permeable PTFE material 102 may include an ePTFE material having uniaxial expansion with a uniaxial node fibril structure. PTFE materials having a multiaxial node fibril orientation may also be used for some embodiments. For some embodiments, the permeable material 102 may include about 1 to about 5 layers of material or more and have an inter nodal distance of about 10 microns to about 30 microns. The permeable material 102 may have a thickness for some embodiments of about 0.00005 inch to about 0.005 inch.

[0079] For some embodiments, the low permeability non-expanded PTFE material 100 may have a non-typical node fibril microstructure with essentially no nodal spacing and very low or no liquid permeability. The extensions 14 and 15 may include about 1 layer to about 5 layers of semi-permeable or substantially non-permeable PTFE material having a thickness of about 0.0001 inches to about 0.005 inches, more specifically, about 0.0004 inches to about 0.001 inches. Examples of such materials are described in U.S. Patent Application publication numbers 2006/0233990 and 2006/0233991 described above which are incorporated by reference in their entirety herein.

[0080] For some embodiments, the PTFE material 100 having low permeability or substantially no permeability may be made by providing a PTFE layer and applying a stretching

agent, such as an isopar lubricant material, to at least a portion of the PTFE layer and stretching the PTFE layer while the layer is wet with stretching agent. For some embodiments, the PTFE layer may be saturated with stretching agent while being stretched. For some embodiments, the PTFE layer may be stretched by a ratio of about 2:1 to about 20:1. For some embodiments, the wet stretching of the PTFE layer is carried out in a direction transverse to the machine direction of expansion. For some embodiments, the wet stretching of the PTFE layer is carried out at a temperature of about 80 degrees F to about 130 degrees F, or at a temperature that is just above the glass transition temperature of the PTFE layer material. For some embodiments, the PTFE layer provided is made by extruding a compounded PTFE resin through an extruder to form a PTFE ribbon extrudate. Such a PTFE material 100 may have substantially low porosity, low permeability, no discernable node and fibril structure and a thickness of about 0.00005 inch to about 0.005 inch. Some such PTFE materials may also have a closed cell microstructure with a plurality of interconnected high density regions having no discernable node and fibril structure between the high density regions. Some such PTFE materials may have low or no fluid permeability.

[0081] FIGS. 17A-17E illustrate schematic representations of several useful extension configurations 14 in transverse cross section that may have the same or similar materials, dimensions and features compared to those of the embodiment shown in FIG. 16 and the embodiment shown in FIG. 4 above. The cross sections shown do not indicate the conformal nature of the PTFE layers with the stent structure as shown in FIG. 16, but are meant to show the number, location and types of PTFE layers with respect to stent 51 for particular embodiments of extensions 14 and 15 and any other suitable extension embodiments, however, the conformal configuration of FIG. 16 may be produced in these embodiments by the methods discussed above. The embodiments of FIGS. 17A-17E are directed to extensions 14 that have low permeability or substantially no permeability and good structural integrity, particularly in areas where the PTFE layer material or materials meet the stent 51.

[0082] FIG. 17A illustrates an extension configuration 14 having one or more inner layers of permeable PTFE material 102 and one or more layers of semi-permeable or substantially non-permeable PTFE material 100 disposed between the inner layer and the stent 51. One or more

layers of semi-permeable or substantially non-permeable PTFE material is disposed outside the stent 51. Each of the layers of PTFE material has been wrapped, either circumferentially or helically, about itself to form a continuous tubular structure with overlapping ends or edges. FIG. 17 B illustrates an extension configuration that is substantially the same as that of FIG. 17A, except that the inner most layer or layers of PTFE material 102 do not connect along a longitudinal or helical line extending from one end of the extension 14 to the other end of the extension 14 as indicated by the gap in the inner most layer or layers shown in the FIG. 17B. As such, the inner most layer or layers of extension embodiment 14 of FIG. 17B forms a generally tubular structure, but it is not a closed or complete tubular structure. The tubular structures formed by the permeable material 102 in FIGS. 17A and 17B may have the node fibril direction of the material oriented substantially along the longitudinal axis of the extension 14 for some embodiments.

[0083] FIG. 17C illustrates an extension configuration 14 that is also substantially the same as that of FIG. 17A, except that the inner most layer or layers of permeable PTFE material are configured as a continuous extruded tubular structure as opposed to the wrapped structure indicated for the embodiments in FIGS. 17A and 17B. The layer or layers of semi-permeable or substantially non-permeable material 100 on either side of the stent 51 are shown with a helically or circumferentially wrapped structure with overlapping ends to form a continuous and closed tubular structure. FIG. 17D illustrates an extension configuration 14 having an extruded tubular inner most layer of permeable material 102 on the inside of the stent 51 and a similar layer of extruded tubular permeable PTFE material 102 on the opposite side of the stent 51. The layer or layers of extruded tubular permeable material 102 form respective closed and continuous tubular structures on either side of the stent 51. A layer or layers of semi-permeable or substantially non-permeable material 100 is disposed over the outer layer of permeable material 102 and is wrapped either circumferentially or helically with overlapping ends to form a closed tubular structure.

[0084] FIG. 17 E illustrates an extension configuration embodiment 14 having an inner tubular structure formed from a layer or adjacent layers of a semi-permeable or substantially non-permeable material 100 disposed adjacent a layer or adjacent layers of permeable material

102 which have been wrapped together to form a continuous and closed tubular structure disposed within the stent 51. The circumferential ends or edges of the layer of semi-permeable or substantially non-permeable material 100 extend circumferentially beyond the circumferential ends or edges of the permeable material 102. As such, the inner wrapped layers, which may be wrapped either helically or circumferentially, are arranged such that the permeable layer 102 never makes contact with itself or the stent 51.

[0085] With regard to the above detailed description, like reference numerals used therein refer to like elements that may have the same or similar dimensions, materials and configurations. While particular forms of embodiments have been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the embodiments of the invention. Accordingly, it is not intended that the invention be limited by the forgoing detailed description.

What is claimed is:

1. A modular endovascular graft assembly, comprising:

a bifurcated main graft member formed from a supple graft material having a main fluid flow lumen therein, an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and a network of inflatable channels disposed on the main graft member including the ipsilateral and contralateral legs which is configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state and which includes at least one inflatable cuff disposed on a proximal portion of the main graft member configured to seal against an inside surface of a patient's vessel;

a proximal anchor member disposed at a proximal end of the main graft member and secured to the main graft member and having a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts having a cross sectional area that is substantially the same as or greater than a cross sectional area of proximal stent portions or distal stent portions adjacent the strut;

at least one ipsilateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member; and

at least one contralateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member.

2. The graft assembly of claim 1 wherein the main graft member has an axial length of about 5 cm to about 10 cm.

3. The graft assembly of claim 2 wherein the main graft member has an axial length of about 6 cm to about 8 cm.
4. The graft assembly of claim 1 wherein the fluid flow lumens of the graft extensions are overlapped with the fluid flow lumens of respective distal legs of the main graft member.
5. The graft assembly of claim 1 wherein the proximal stent of the proximal anchor member further comprises a plurality of barbs having sharp tissue engaging tips that are configured to extend in a radial outward direction in a deployed expanded state.
6. The graft assembly of claim 1 wherein the supple graft material of the main graft and graft extensions comprise layered porous or expanded PTFE.
7. The graft assembly of claim 1 wherein the graft extensions comprise an interposed self-expanding stent disposed between at least one outer layer and at least one inner layer of supple layers of graft material and wherein the interposed stent disposed between the outer layer and inner layer of graft material may be formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration.
8. The graft assembly of claim 7 wherein the interposed stent is comprised of a superelastic alloy.
9. The graft assembly of claim 8 wherein the superelastic alloy comprises superelastic NiTi alloy.
10. The graft assembly of claim 7 wherein the graft material of each graft extension further comprises at least one axial zone of low permeability.
11. The graft assembly of claim 1 wherein the proximal stent portion of the proximal anchor member comprises a 4 crown stent.
12. The graft assembly of claim 1 wherein the distal stent portion of the proximal anchor member comprises an 8 crown stent.

13. The graft assembly of claim 1 wherein the proximal stent portion and distal stent portion of the proximal anchor member comprise a superelastic alloy.
14. The graft assembly of claim 13 wherein the superelastic alloy comprises superelastic NiTi alloy.
15. A modular endovascular graft assembly, comprising:

a bifurcated main graft member having an axial length of about 5 cm to about 10 cm formed from a supple graft material having a main fluid flow lumen therein, an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm, and a network of inflatable channels disposed on the main graft member including the ipsilateral and contralateral legs which is configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state and which includes at least one inflatable cuff disposed on a proximal portion of the main graft member configured to seal against an inside surface of a patient's vessel;

a proximal anchor member disposed at a proximal end of the main graft member and secured to the main graft member and having a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts;

at least one ipsilateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member; and

at least one contralateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member.

16. The graft assembly of claim 15 wherein the main graft member has an axial length of about 6 cm to about 8 cm.
17. The graft assembly of claim 15 wherein the fluid flow lumens of the graft extensions are overlapped with the fluid flow lumens of respective distal legs of the main graft member.
18. The graft assembly of claim 15 wherein the proximal stent of the proximal anchor member further comprises a plurality of barbs having sharp tissue engaging tips that are configured to extend in a radial outward direction in a deployed expanded state.
19. The graft assembly of claim 15 wherein the supple graft material of the main graft and graft extensions comprise layered porous or expanded PTFE.
20. The graft assembly of claim 15 wherein the graft extensions comprise an interposed self-expanding stent disposed between at least one outer layer and at least one inner layer of supple layers of graft material and wherein the interposed stent disposed between the outer layer and inner layer of graft material may be formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration.
21. The graft assembly of claim 20 wherein the interposed stent is comprised of a superelastic alloy.
22. The graft assembly of claim 21 wherein the superelastic alloy comprises superelastic NiTi alloy.
23. The graft assembly of embodiment 20 wherein the graft material of each graft extension further comprises at least one axial zone of low permeability.
24. The graft assembly of claim 15 wherein the proximal stent portion of the proximal anchor member comprises a 4 crown stent.
25. The graft assembly of claim 15 wherein the distal stent portion of the proximal anchor member comprises an 8 crown stent.

26. The graft assembly of claim 15 wherein the proximal stent portion and distal stent portion of the proximal anchor member comprise a superelastic alloy.
27. The graft assembly of claim 26 wherein the superelastic alloy comprises superelastic NiTi alloy.
28. A method of treating a patient, comprising:

providing a delivery catheter containing a radially constrained bifurcated main graft member formed from a supple graft material which has a main fluid flow lumen therein, which has an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen, which has a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen, which has a network of inflatable channels disposed on the main graft member including the ipsilateral and contralateral legs and which has a proximal anchor member disposed at a proximal end of the main graft member and secured to the main graft member and having a self-expanding proximal stent portion secured to a self-expanding distal stent portion;

axially positioning the delivery catheter within the patient's vasculature such that the main graft member within the delivery catheter is disposed coextensively with a vascular defect of the patient's aorta;

deploying the proximal anchor member so as to engage an inner surface of the patient's vasculature and anchor the proximal anchor member to the patient's aorta;

inflating the network of inflatable channels of the main graft member with an inflation material;

providing a second delivery catheter containing a radially constrained self-expanding contralateral graft extension;

axially positioning the second delivery catheter in the contralateral leg of the main graft member with a proximal portion of the contralateral graft extension axially

overlapped with an inner fluid flow lumen of the contralateral leg of the main graft member and a distal portion of the contralateral graft extension axially overlapped with a portion of the patient's contralateral iliac artery;

deploying the self-expanding contralateral graft extension by releasing the radial constraint so as to form a seal between the inner fluid flow lumen of the contralateral graft extension, a fluid flow lumen of the contralateral leg and a fluid flow lumen of the contralateral iliac artery;

providing a third delivery catheter containing a radially constrained self-expanding ipsilateral graft extension;

axially positioning the third delivery catheter in the ipsilateral leg of the main graft member with a proximal portion of the ipsilateral graft extension axially overlapped with an inner fluid flow lumen of the ipsilateral leg of the main graft member and a distal portion of the ipsilateral graft extension axially overlapped with a portion of the patient's ipsilateral iliac artery; and

deploying the self-expanding ipsilateral graft extension by releasing the radial constraint so as to form a seal between the inner fluid flow lumen of the ipsilateral graft extension, a fluid flow lumen of the ipsilateral leg and a fluid flow lumen of the ipsilateral iliac artery.

29. A modular endovascular graft assembly, comprising:

a bifurcated main graft member formed from a supple graft material having a main fluid flow lumen therein, an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and a network of inflatable channels disposed on the main graft member including the ipsilateral and contralateral legs which is configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state and which includes at least one inflatable cuff disposed on a proximal

portion of the main graft member configured to seal against an inside surface of a patient's vessel;

a proximal anchor member disposed at a proximal end of the main graft member and secured to the main graft member and having a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts having a cross sectional area that is substantially the same as or greater than a cross sectional area of proximal stent portions or distal stent portions adjacent the strut;

at least one ipsilateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member; and

at least one contralateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member.

30. A modular endovascular graft assembly, comprising:

a bifurcated main graft member having an axial length of about 5 cm to about 10 cm formed from a supple graft material having a main fluid flow lumen therein, an ipsilateral leg with an ipsilateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm, a contralateral leg with a contralateral fluid flow lumen in communication with the main fluid flow lumen and with an axial length of at least about 2 cm, and a network of inflatable channels disposed on the main graft member including the ipsilateral and contralateral legs which is configured to accept a hardenable fill material to provide structural rigidity to the main graft member when the network of inflatable channels are in an inflated state and which includes at least one inflatable cuff disposed on a proximal portion of the main graft member configured to seal against an inside surface of a patient's vessel;

a proximal anchor member disposed at a proximal end of the main graft member and secured to the main graft member and having a self-expanding proximal stent portion secured to a self-expanding distal stent portion with struts;

at least one ipsilateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the ipsilateral leg of the main graft member; and

at least one contralateral graft extension having a fluid flow lumen disposed therein with the fluid flow lumen of the graft extension sealed to and in fluid communication with the fluid flow lumen of the contralateral leg of the main graft member.

31. A graft extension, comprising

a fluid flow lumen disposed therein;

at least one layer of permeable PTFE material;

at least one layer of semi-permeable or substantially non-permeable PTFE material having no discernable node and fibril structure; and


an interposed self-expanding stent formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration disposed between at least one outer layer and at least one inner layer of PTFE material.

32. The graft extension of claim 31 wherein the interposed stent is comprised of a superelastic alloy.

33. The graft extension of claim 32 wherein the superelastic alloy comprises superelastic NiTi alloy.

34. The graft extension of claim 31 wherein the graft material of each graft extension further comprises at least one axial zone of low permeability.
35. The graft extension of claim 31 wherein the permeable PTFE material comprises an inter nodal distance of about 10 microns to about 30 microns.
36. The graft extension of claim 31 wherein the permeable material has a thickness of about 0.00005 inch to about 0.005 inch.
37. The graft extension of claim 31 wherein the semi-permeable or substantially non-permeable material comprises a thickness of about 0.00005 inch to about 0.005 inch.
38. The graft extension of claim 31 wherein the semi-permeable or substantially non-permeable material comprises substantially low porosity and a closed cell microstructure with a plurality of interconnected high density regions having no discernable node and fibril structure between the high density regions.

FIG. 1






FIG. 1A

FIG. 2





FIG. 3




FIG. 4




FIG. 4A




FIG. 5A







FIG. 5B

6/16



7/16




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14



15/16




FIG. 15




FIG. 16




FIG. 17A

FIG. 17B

16/16

