



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2783131 A1 2014/01/16

(21) **2 783 131**

(12) **DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) **A1**

(22) **Date de dépôt/Filing Date:** 2012/07/16

(41) **Mise à la disp. pub./Open to Public Insp.:** 2014/01/16

(51) **Cl.Int./Int.Cl.** *H01R 25/00* (2006.01),
H02G 15/08 (2006.01)

(71) **Demandeur/Applicant:**
BYRNE, NORMAN R., US

(72) **Inventeur/Inventor:**
BYRNE, NORMAN R., US

(74) **Agent:** BORDEN LADNER GERVAIS LLP

(54) **Titre :** CONNECTEUR A UNE ENTREE ET QUATRE SORTIES

(54) **Title:** ONE IN FOUR OUT CONNECTOR

(57) **Abrégé/Abstract:**

A one in four out connector assembly is disclosed having an internal wiring assembly with a series of wires. Connected to one end of each of the wires is an H-type wire. Connected to the opposing end of each of the wires is a single blade male terminal. The single blade male terminals form a power terminal group connectable to terminals of a junction block. The terminals of the H-type connectors form connector cable terminals which are connectable to at least four connector cable assemblies.



ABSTRACT

A one in four out connector assembly is disclosed having an internal wiring assembly with a series of wires. Connected to one end of each of the wires is an H-type
5 wire. Connected to the opposing end of each of the wires is a single blade male terminal. The single blade male terminals form a power terminal group connectable to terminals of a junction block. The terminals of the H-type connectors form connector cable terminals which are connectable to at least four connector cable assemblies.

ONE IN FOUR OUT CONNECTOR**BACKGROUND OF THE INVENTION**Field of the Invention

The invention relates to electrical power distribution systems and, more particularly, to systems having junction block assemblies and the requirement of providing
5 components which provide for multiple incoming and outgoing cable connections to the junction block assemblies.

Background Art

Known interior wall systems typically employ pre-fabricated modular units. These units are often joined together in various configurations, so as to divide a workplace into
10 smaller offices or work areas. Generally, such modular wall panels may be equipped with means for receiving general building power and, possibly, general communications. Such building power may, for example, be conventional AC power received either under floor or from relatively permanent walls or the like. In various types of environments comprising electrical equipment, or wherein electrical apparatus are otherwise employed,
15 interconnections of electrical components to incoming utility power are typically provided by means of cables or wires. For example, in office systems comprising modular furniture components, it is often necessary to provide electrical interconnections between incoming power supplies and various types of electrical devices typically used in an office environment, such as electric typewriters, lamps, etc. Computer-related devices, such as
20 video display terminals and similar peripherals, are also now commonly employed in various office and industrial environments.

One advantage inherent in modular office systems is the capability to rearrange furniture components as necessitated by changes in space requirements, resulting from changes in the number of personnel and other business-related considerations. However,
25 these modular systems must not only allow for change in furniture configurations, but also must provide for convenient interconnection of electrical devices to utility power, regardless of the spacial configuration of the modular systems and resultant variable distances between electrical devices.

In providing the interconnection of electrical apparatus and power inputs, it is
30 necessary to include an arrangement for feeding the incoming utility power to the power outlets. In stationary structures, such as conventional industrial buildings and the like, a

substantial amount of room would normally exist behind stationary walls and other areas in which to provide the requisite cabling for interconnecting incoming utility power to electrical receptacles mounted in the walls. Such systems, however, can be designed so as to remain stationary throughout their lifetime, without requiring general changes in the
5 office or industrial environment areas.

In addition to receiving electrical power from the general incoming building power supply, modular office systems typically require communications connections for office equipment such as telephones, internet communications and the like. The problems associated with providing distribution of communications essentially correspond to the
10 same problems existing with respect to distribution of conventional electrical power.

In this regard, it is known to provide modular wall panels with areas characterized as raceways. Often, these raceways are located along bottom edges of modular panels. The raceways are adapted to house electrical cabling and electrical junction blocks. The cabling and junction blocks are utilized to provide electrical outlets and electrical power
15 connections to adjacent panels. However, it is also apparent that to the extent reference is made herein to providing electrical outlets and electrical power connections for adjacent panels, the same issues exist with respect to providing communications among panels.

Still further, it is known that the raceway of one modular wall unit may be provided with a male connector at one end, and a female connector at another end. Pairs
20 of junction blocks, each provided with electrical outlets, made to be disposed at spaced-apart positions along the raceway. Conduits may be extended between the junction blocks and between the connectors in the junction blocks. In this manner, electrical interconnection is provided between the units.

The modular panels of a space-divider may be configured, such that adjacent
25 panels are in a straight line, or at various angular positions relative to each other. It is common to configure intersecting walls in such a fashion that three or four modular wall panels may intersect at right angles. Each of the panels typically requires electrical outlets, and may require outlets on both sides of the panels. In any event, electrical power has to be provided to all of the panels, and often only one of the panels at the multiple
30 panel junction is connected to a power supply source. Under such circumstances, the interconnecting wiring becomes a significant problem. That is, special modifications may have to be made to power systems of wall panels to be used in such a configuration. Because interchangeability of wall panels is highly desirable, custom modifications are

preferably avoided. Still further, modifications of wall panels on site at the installation facility is complex and may be relatively expensive.

In addition to the foregoing issues, problems can arise with respect to the use of junction blocks and the amount of room which may exist within a raceway. That is, raceways require sufficient room so as to provide for junction blocks, electrical outlet receptacle blocks, and cabling extending between junction blocks and between adjacent panels.

One example of a prior art system is illustrated in Propst's, *et al.*, U.S. Patent No. 4,382,648 issued May 10, 1983. In the Propst, *et al.* system, mating connectors of opposing panels are engaged when the panels are aligned in a straight line. When the panels are positioned in an intersecting relationship, specially manufactured couplers are utilized. One type of special coupler is used when the panels are positioned at right angles. Another type is used with adjoining panels arranged at angles other than right angles. Consequently, costly inventory of couplers must be maintained. The Propst, *et al.* system uses a double set of connectors comprising a male and female connector for each conductor to be interconnected. When a single one of these prior art panels intersects two adjacent panels, one of the specially manufactured couplers connects the female terminals to one of the adjacent panels, and another of the couplers connects the male terminals to the adjacent panel.

A further system is disclosed in Driscoll, U.S. Patent No. 4,135,775, issued January 23, 1979. In the Driscoll system, each panel is provided with an electrical outlet box in its raceway. Panels of different widths are provided with a pair of female connectors. Outlet boxes of adjacent panels are interconnected by means of flexible cables having male connectors at both ends. When three or four panels are adjoined in an intersecting arrangement, two cables may be connected the pair of female connectors at one end of an outlet box. In this manner, connection of two adjacent panels is facilitated.

With respect to both of the foregoing systems, and other than in the special intersecting relationship, one half of the double set of terminals of these systems is superfluous. There is a distinct disadvantage in modern day systems, where several independent electrical circuits are needed in a wall panel system, with each requiring separate connectors. Space for such circuits and their connectors is very limited in the raceway areas of modern, thin-line wall panels.

Other systems also exist with respect to electrical connectors, junction boxes, and the like. For example, Rodrigues, U.S. Patent No. 1,187,010 issued June 13, 1916, discloses a detachable and interchangeable electrical switch plug adapted for use in connection with various electrically heated appliances. A clamping device is positioned in
5 a fixed, but detachable relationship to one end of the plug. Means are provided to enclose and prevent sharp flexure of the cord comprising a flexible enclosing tube gripped under tension by the other end of the clamping device. The plug and the clamping device may be simultaneously removed from the socket.

Finizie, U.S. Patent No. 2,540,575, issued February 6, 1951, discloses a cord guide
10 member for utensil plugs. The concept is to reduce wear on the cord and the connector plug, and to provide a connection which will withstand heavy pulling strains without injury. Strain relief is also provided. A sectional body is equipped anteriorly adjacent one end of the body with terminals. The other end of the body contains an anterior chamber or socket. A pivotable cord-guiding member having a pivot member is movably
15 mounted in the socket. A wedge-shaped strain relief insert is received within a wedge-shaped recess in the pivot member. A cord extends into the pivot member and includes wires passing from the cord toward the terminals. The incoming portions of the wires are moved around the insert and firmly wedged within the recess.

Byrne, U.S. Patent No. 4,551,577, issued November 5, 1985, describes a
20 retractable power center. The power center provides for conveniently located electrical power source receptacles adapted to be mounted on a work surface. In one embodiment, the power center includes a rectangular housing received within a slot in a work surface. A clamping arrangement is utilized to secure the housing to the work surface. A lower extrusion is connected to the lower portion of the housing. A movable power carriage
25 mounts the receptacles and a catch assembly releasably maintains a carriage in a closed and retracted position. In response to manual activation, the catch assembly is released and springs tensioned between the carriage and the extrusion exert forces so as to extend the carriage upward into an extended, open position. In the open position, the user can energize the desired electrical devices from the receptacles, and then lower the carriage
30 into the retracted position.

Byrne, U.S. Patent No. 4,959,021, issued September 25, 1990, discloses a pivotable power feed connector having a pivotal connector adapted to be connected to a flexible conduit or cable. The cable has a series of conductors extending there through.

The connector is pivotably connected to a block assembly through which the conductors extend. The block assembly, in turn, is connectable to a contact block, with the conductors conductively connected to a set of prong terminals extending outwardly from the block. A cover is secured over the block so as to prevent the prong terminals from
5 being exposed during assembly and disassembly.

The cover automatically exposes the prong terminals as the power feed connector is moved into engagement with a receptacle in a modular office panel. The connector allows the conduit or cable to be swiveled to an arc of approximately 180 degrees to any desired position. The connector is also manually removable from interconnection with the
10 block assembly. Such removal allows the conduit or cable to be pulled back from the conductors and cut to a desired length. The connector includes a power feed cover which can be utilized in part to maintain the connector in either of two spatial configurations relative to the block assembly.

Nienhuis, *et al.*, U.S. Patent No. 5, 013,252, issued May 7, 1991, discloses an
15 electrified wall panel system having a power distribution server located within a wall panel unit. The server includes four receptacle module ports oriented in an h-shaped configuration. A first receptacle port is located on the first side of the wall panel unit and opens toward a first end of the unit. A second receptacle unit is also located on the first side of the wall panel unit, and opens toward a second end of the wall panel unit. A third
20 receptacle port and a second sided wall panel unit opens toward the first end of the wall panel unit, while correspondingly, a fourth receptacle port on the second side of the wall panel unit opens toward the second end of the wall panel unit. First and second harnesses are each electrically connected at first ends thereof to the power distribution server. They extend to opposite ends of the wall paneled unit and include connector ports on the second
25 ends thereof for providing electrical interconnection of adjacent wall panel units. The Nienhuis, *et al.* patent also discloses a system with a wall panel connector interchangeably usable with the interconnection of two, three or four units. The connector includes a hook member for connecting together adjacent vertical members of frames of adjacent wall panel units at a lower portion thereof. A draw naught for connecting together adjacent
30 vertical members of frames of adjacent wall panel units and an odd proportion thereof is provided by vertical displacement thereof.

Lincoln, *et al.*, U.S. Patent No. 5,073,120, issued December 17, 1991, discloses a power distribution assembly having a bussing distribution connector. The connector

includes a series of bus terminals positioned within an electrically insulative housing. A series of electrical terminals are positioned in the housing for distributing more than one electrical circuit. At least one ground terminal, one neutral terminal, and three hot terminals are provided. A grounding shell partially surrounds the bus connector and
5 includes a grounding tab grounding the one ground terminal to the metallic grounding shell. In another embodiment, two bus connectors are interconnected together, so as to provide for an increased number of output ports.

Byrne, U.S. Patent No. 5,096,431, issued March 17, 1992, discloses an outlet receptacle with rearrangeable terminals. The receptacle is provided with input terminals to
10 selected positions, for engagement with terminals of an electrical junction block. The block includes a series of terminals representing a plurality of different electrical circuits. The receptacle block has neutral, ground and positive flexible positive conductor bars electrically connected to neutral, ground and positive electrical terminals. Input terminals
15 of the block are formed integral with the flexible conductor bars and levers are provided for moving the terminal ends of the conductor bars to physically different positions. In one configuration, the receptacle block housing is provided with openings at opposing ends, and the flexible conductor bars have terminal ends controlled by levers at both ends of the outlet receptacle block. In another configuration, the block has output terminals in a front wall, and the input terminals of the receptacle block are formed as ends of the
20 flexible bars and extend at an approximately 90 degree angle to the bars. They further send through openings in the back wall of the outlet receptacle for engagement with terminals of a junction block. Levers are provided in the back wall of the receptacle block for positioning the terminal ends in alignment with different terminals of the junction block, and windowed openings in the front wall expose indices on the levers identifying
25 selected circuits.

Byrne, U.S. Patent No. 5,096,434, issued March 17, 1992, discloses an electrical interconnection assembly for use in wall panels of a space divider wall system. The system includes junction blocks having several receptacle connectors, so as to provide a plurality of electrical outlets on both sides of a wall panel. The junction block is
30 connected by means of conduits extending from both ends of the junction block to oppositely directed connector blocks for connection to adjoining panels. The assembly of the junction block and connector blocks allows electrical power to be supplied to one end of the panel and conducted to and through the junction block to other panels. The

receptacle connectors on the junction block each have one type of terminal configuration, e.g., a female electrical terminal configuration. One of the connector blocks is provided with the identical terminal configuration. The other connector block is provided with a matching terminal configuration, e.g., a male electrical terminal configuration. When two wall panels are joined at their respective edges, the male connector block may be readily connected to the female connector block in the adjacent panel. When two panels are joined to a third panel, all at one point, the arrangement of this invention allows the male connector block to be connected to the female connector block of one of the other two panels, and the male connector of the other of the two panels may be connected to one of the receptacle connectors of the junction block on either of the other two panels, in this manner establishing a three way interconnection arrangement. In a similar fashion, a fourth, or other additional panels may be added to the junction and plug into receptacle outlets of other panels in order to provide an arrangement of panels that is totally interconnected, electrically.

Snodgrass, *et al.*, U.S. Patent No. 5,164,544, issued November 17, 1992, describes an electrified space dividing panel having a panel member, raceway, modular, or electric system disposed in a raceway and raceway covers for gaining access to the system. The system includes a single terminal block having end and side sockets, with first and second electrical receptacles being respectively removeably engaged with the end socket and the side sockets, such that the first and second electrical receptacles are disposed in horizontally spaced, side-by-side relation and project outwardly for predetermined light dimensions through receptacle openings in one of the raceway covers. The raceway can include a web having an opening which cooperates with a support ear on the first receptacle during engagement of the first receptacle with an end socket, so as to provide additional lateral support for the electrical receptacle when a plug is removed there from.

Kilpatrick, *et al.*, U.S. Patent No. 5,178,555, discloses a kit which includes a junction box for installation along a raceway. The kit includes a mounting bracket having a first adjustable mounting mechanism for locating the bracket along the raceway. This provides an initial adjustment, and a second adjustable mounting mechanism is provided for securing the junction box to the mounting bracket. This adjustably locates the junction box along the mounting bracket, and provides a second or final adjustment to accurately locate the junction box between two pre-measured lengths of cable.

Byrne, U.S. Patent No. 5,259,787, issued November 9, 1993, discloses an electrical junction block mounting assembly, which may be utilized for mounting the junction block within a raceway. The assembly includes a cantilever beam formed on an outer wall of the junction block. This beam is provided with a transversely extending channel for engagement with a support structure. The beam is attached to the junction block by means of a resilient hinge section, and is provided with a first arm section extending between the hinge section and the channel, and a second arm section extending beyond the channel. The first arm section has a sloping surface sloping away from the outer channel between the hinge section of the panel. The second armed section has a sloping surface sloping toward the wall beyond the channel. The surfaces will contact a mounting rail or similar structure during installation of the junction block. In this manner, the hinged cantilever beam is deflected until the rail is in alignment with the channel for engagement with the structural support member.

One issue which exists with respect to power distribution systems for use in raceways and other configurations relates to the concept of providing components which permit power distribution in varying and multiple directions. Also, in some systems where the connector cable assemblies are essentially "inline," it may be desirable for an interconnected junction block assembly to have a directional orientation different from the particular orientation of the connector cable assemblies.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described with reference to the drawings, in which:

FIG. 1 is a prior art, fragmentary elevation view of a plurality of adjacent wall panels and electrical connection assemblies arranged in the panels;

FIG. 2 is a prior art, enlarged perspective view of one of the electrical interconnection assemblies of FIG. 1;

FIG. 3 is a prior art cross-sectional view taken along lines 3-3 of FIG. 2;

FIG. 4 is a prior art, enlarged perspective view of an outlet receptacle shown in FIG. 1;

FIG. 5 is a prior art side elevation view of the outlet receptacle of FIG. 4;

FIG. 6 is a prior art, fragmentary plan view of raceway areas of four wall panels, illustrating wall panel interconnections;

FIG. 7 is a prior art, fragmentary cross-sectional view taken along lines 7-7 of FIG. 2;

FIG. 8 is a prior art, perspective view of a receptacle contact blade shown in FIG. 7;

FIG. 9 is a plan view of a one in four out connector assembly in accordance with the invention, with the view of FIG. 9 and other views corresponding to the orientation of
5 the one in four out connector assembly shown in FIG. 32;

FIG. 10 is a front, elevation view of the connector assembly shown in FIG. 9;

FIG. 11 is a left-side end view of the connector assembly shown in FIG. 9;

FIG. 12 is an underside view of the connector assembly shown in FIG. 9;

FIG. 13 is a right-side end view of the connector assembly shown in FIG. 9;

10 FIG. 14 is what is being characterized as a rear, elevation view of the connector assembly shown in FIG. 9;

FIG. 15 is a right, perspective view of the connector assembly shown in FIG. 9;

FIG. 16 is a left, perspective view of the connector assembly shown in FIG. 9;

FIG. 17 is a further perspective view of the connector assembly shown in FIG. 9,
15 but with the view being at a rotation of 90° relative to the view of FIG. 16;

FIG. 18 is a perspective, partial and exploded view of a portion of the connector assembly shown in FIG. 9, and specifically showing a rear terminal section housing, and an internal wiring assembly comprising a series of wires having interconnected H-connectors and male terminal blades at their ends;

20 FIG. 19 is a perspective and exploded view similar to the view of FIG. 18, but showing the front housing half, cable connector, cable connector side cover and the internal wiring assembly as assembled with the rear housing half;

FIG. 20 is a perspective view of the connector assembly shown in FIG. 9, with the view being similar to FIG. 19, but showing, in an exploded format, the relative positioning
25 of the connector assembly side plates for assembly;

FIG. 21 is a perspective view showing the connector assembly in FIG. 9 in a fully assembled state;

FIG. 22 is an elevation view of the connector assembly shown in FIG. 9, with the view being similar to the views of FIGS. 11 and 13;

30 FIG. 22A is an enlarged view of a pair of terminal connector sets having a first upper key arrangement and a first intermediate key arrangement;

FIG. 23 is an elevation view of a further embodiment of the connector assembly, showing an alternative keying arrangement;

FIG. 23A is an enlarged view of the keying arrangement shown in FIG. 23, with the pair of terminal connector sets each having the first upper key arrangement and a second intermediate key arrangement;

FIG. 24 is an elevation view of a third embodiment of the connector assembly,
5 showing a still further alternative keying arrangement;

FIG. 24A is an enlarged view of a portion of FIG. 24, showing the pair of terminal connector sets as having a second upper key arrangement and the first intermediate key arrangement;

FIG. 25 is an elevation view of a still further embodiment of the connector
10 assembly, showing a still further alternative keying arrangement;

FIG. 25A is an enlarged view of the terminal connector sets shown in FIG. 25, with each of the pair of connector sets having the second upper key arrangement and the second intermediate key arrangement;

FIG. 26 is an elevation view of yet another embodiment of the connector assembly;

FIG. 26A is an enlarged view of the connector assembly shown in FIG. 26, and
15 showing the pair of terminal connector sets as having the second upper key arrangement and a third, alternative intermediate key arrangement;

FIG. 27 is a plan view of the connector assembly shown in FIG. 9, and expressly showing the power connector set of the connector assembly shown in FIG. 9;

FIG. 27A is an enlarged view of a portion of FIG. 27, and expressly showing the
20 power connector set as having a first upper key arrangement and a second intermediate key arrangement;

FIG. 28 is a plan view of a further embodiment of the connector assembly;

FIG. 28A is an enlarged view of a portion of the connector assembly shown in
25 FIG. 28, and showing the power connector group as having the first upper key arrangement and a second intermediate key arrangement;

FIG. 29 is a plan view of a still further embodiment of the connector assembly;

FIG. 29A is an enlarged view of a portion of the connector assembly shown in
FIG. 29, and showing a second upper key arrangement and a second intermediate key
30 arrangement;

FIG. 30 is a plan view of a still further embodiment of the connector assembly;

FIG. 30A is an enlarged view of a portion of the connector assembly shown in FIG. 30, and showing the power connector set as having the second upper key arrangement and the second intermediate key arrangement;

FIG. 31 is a plan view of a yet further embodiment of the connector assembly;

5 FIG. 31A is an enlarged view of a portion of the connector assembly shown in FIG. 31, and showing the power connector set as having the second upper key arrangement and a third intermediate key arrangement;

FIG. 32 is a perspective view showing the connector assembly of FIG. 9 as positioned for insertion into a raceway, and further showing positions of other components
10 to be interconnected to the connector assembly, the other components being a junction block with associated receptacle block, and four connector cable assemblies;

FIG. 33 is a perspective view similar to FIG. 32, but showing the four connector cable assemblies, connector assembly and junction block with associated receptacle block in a fully assembled state; and

15 FIG. 34 is a perspective view similar to FIG. 33, but showing the relative positioning of the four connector cable assemblies below a wall panel, with the receptacle block and junction block positioned above the connector assembly.

DESCRIPTION OF THE PREFERRED EMBODIMENT

20 The principles of the invention are disclosed, by way of example, in a one in four out connector assembly as illustrated in several embodiments shown in FIGS. 9 – 34. For purposes of brevity and description, the one in four out connector assembly will be described herein with alternative terms, such as "connector assembly." These connector assemblies advantageously provide the capability of electrically engaging a junction block
25 and at least four connector cable assemblies where the connector cable assemblies extend in a different direction and a different plane than an interconnected junction block assembly.

For purposes of describing power distribution configurations where vertical junction block assemblies in accordance with the invention may be utilized, the following
30 paragraphs describe prior art electrical interconnection assemblies which could be adapted for use within wall panels of a space divider wall system. These assemblies are shown in the prior art drawings of FIGS. 1-8. Specifically, FIGS. 1-8 describe and depict a junction block with several receptacle connectors, so as to accommodate a series of electrical

outlets on both sides of a wall panel. The junction block is connected by means of conduits extending from both ends of the junction block to associated connector blocks for connection to adjoining panels. Following the description of the prior art electrical interconnection assemblies, the vertical junction block assemblies in accordance with the invention will be described with respect to FIGS. 9-29.

FIG. 1 is a prior art fragmentary elevational view of adjacent modular wall panels 101, 102, 103 of a rearrangeable wall system. The wall panels are provided with electrical interconnection assemblies 105, 107 and 109 in a raceway area formed along the lower edge of panels 101, 102 and 103. Each of the panels is provided with substantially flat support legs 112 which allow for passage of electrical conduits in the raceway. Raceway covers, customarily used, have been omitted from the drawing in FIG. 1 to better show the electrical junction assemblies. Each of the electrical interconnection assemblies 105, 107, and 109 is provided with a junction block 120, a female electrical connector block 140 and a matching male connector block 145. The connector blocks 140, 145 are connected to associated junction blocks 120 by means of conduit sections 142 and 147, respectively. Each of the junction blocks 120 is shown in FIG. 1 to be provided with a pair of electrical outlet receptacles 150. Junction blocks 120 are double sided and corresponding pairs of outlet receptacles are provided on the opposite side of each of the wall panels 101, 102 and 103 (not shown in the drawing) to allow various electrical equipments to be plugged into the outlets from either side of the panel.

FIG. 2 is an enlarged perspective view of one of the electrical interconnection assemblies, for example assembly 107. The junction block 120 is provided with support lugs 122 by which the junction block is supported by standard fasteners extended through support tables extending from the bottom edge of the wall panel, e.g., wall panel 102. Junction block 120 comprises an elongated housing having opposing ends 121 and 123 and a symmetrical center section comprising four female receptacle connectors 126. Only one of the receptacle connectors 126 is fully exposed in FIG. 2. There is a pair of connectors 126 on each side of the housing and the connection on each side face in opposite directions. Support flanges 130 are provided adjacent each of the female connectors to provide support for electrical outlet receptacles engaged with the connectors 126. In this manner, junction block 120 is adapted to support four electrical outlet receptacles, two on each side of a wall panel to which junction block 120 is attached. The junction block assembly further comprises end connector block 140, provided with a

female connector 141, and connected via a standard electrical conduit 142, which may be a flexible conduit, to end 123 of junction block 120. Similarly, connector block 145, provided with a male connector 146 is connected via flexible conduit 147 to end 121 of junction block 120. In a straight line connection arrangement, as depicted for example in
5 FIG 1, wherein a plurality of panels are positioned adjacent each other, electrical power is transmitted between panels by connection of male connector block 145 to female connector block 140 of the adjacent junction assembly.

Electrical power is transmitted through the junction assembly by means of electrical wires disposed in the conduits 142, 147, terminated on connectors 141 and 146,
10 respectively, and connected to receptacle connectors 126 in junction block 120. Accordingly, electrical power is transmitted through interconnecting panels and is at the same time made available at electrical outlet receptacles in each panel. Conduit 147, provided with the male connector block 145, may be a fixed-length conduit and conduit 142 may be of a length such that female connector block 140 is positioned at substantially
15 the same distance from the panel edge in each panel independent of the width of the panel. Thus, female connector block 140 will always be accessible to male connector block 145 independent of the width of the panels. To accommodate panels of different widths, conduit 142 may be an expandable flexible conduit, such as are well known in the art. In that case, connector block 140 may be provided with an inner spatial area 136, as shown in
20 a partially broken-away view in FIG. 2. The inner spatial area 136 is provided for storage of excess length of electrical wiring 138 in a coiled or other configuration. The excess length of electrical wiring 138 may be withdrawn when conduit 142 is expanded to an extended length. This arrangement is similar to that disclosed in my earlier patent, U.S. Pat. No. 4,579,403 (dated Apr. 1, 1986) and entitled ELECTRICAL JUNCTION
25 ASSEMBLY WITH ADJUSTABLE CONNECTORS.

The conduit 147 is preferably a flexible conduit which may be bent to accommodate a connection to adjacent panels which are disposed at angular positions with respect to each other, rather than in a straight line. The junction assemblies of this invention readily accommodate an arrangement in which three or more panels are
30 disposed in an intersecting relationship, as will be discussed further herein with respect to FIG. 6. In such a configuration, the male connector block 145 of one of the panels may be connected to one of the female receptacle connectors 126 of a junction block assembly in an adjacent wall panel. For this purpose, the female connector 141 of connector block 140

and female receptacle connectors 126 on junction block 120 have been made identical. Similarly, the male connector 146 on connector block 145 has been made identical to the male connector of electrical outlet receptacle 150, shown in FIG. 1. Greater detail of the receptacle 150 is shown in FIG. 4 and is described below. As may be seen from FIG. 2,
5 the female connectors 126 and 141 are each provided with a pair of side flanges 129 having upper and lower recessed areas 128, for engagement with flanges 148 of a male connector to provide a locking arrangement. Figures 129, which are made of a resilient plastic material and formed integral to the housing to which they are connected, are provided with an outwardly extending inclined end surface 135. When surfaces 135 are
10 engaged by flanges such as flanges 148 of connector 146 on connector block 145, the flanges 129 will be deflected inward, allowing flanges 148 of the male connector to engage recesses 128 to provide a locking engagement of the male and the female connectors. A protuberance 137 is provided with a generally rounded edge surface 139 and acts as an entry guide as a male connector is engaged in female connector 126. The
15 female connectors 126, 141 are each provided with a plurality of female connector terminals 125 and a key lug 127. Male connector 146 is provided with a plurality of male connector terminals 149 and an opening 143 for receiving key lug 127.

The electrical outlet receptacle 150, shown in FIG. 4, is provided with male connectors 151 at both ends, allowing the receptacle to be plugged into any one of the four
20 female receptacle connectors 126 of junction block 120. As shown in FIG. 2, junction block 120 is provided with upper and lower support flanges 130 to support receptacles 150 in each of the four female connectors 126. The lower support flanges 130 are provided with a locking flange 132. The receptacle 150 is provided with a spring latch 152 disposed in recess 154 in the surface 156 of receptacle 150. Surface 156 engages one of
25 the lower support flanges 130 when the receptacle 150 is installed in the junction block 120. The locking flanges 132 will be aligned with the recess 154 when the receptacle 150 is inserted between flanges 130, causing the spring latch 152 to be depressed. The receptacle 150 may then be moved to either the left or to the right to engage one of the female connectors 126. Recesses 158 are provided in receptacle 150 to accommodate
30 locking flange 132 and movement to either the left or to the right by a sufficient distance will cause the spring latch 152 to be moved past locking flange 132, causing the spring latch 152 to return to its extended position. Hence, receptacle 150 will be retained in a locked position. The receptacle may be removed by depressing spring latch 152 and

sliding the receptacle 150 to either left or right to align the locking flange 132 with recess 154. FIG. 5 is a right-hand elevation of receptacle 150 showing a right-hand elevation or receptacle 150 showing right-hand male connector 151.

FIG. 3 is a cross-sectional view of junction block 120 taken along line 3-3 of FIG. 2. FIG. 3 shows two of the four receptacle connectors 126 of connector block 120. One of the two connectors 126 shown in FIG. 3 is disposed on each side of the central housing section 131, which contains a plurality of wires 133. An eight-wire system is shown in this illustrative embodiment. Each of the male and female connectors are provided with eight separate terminals, and eight separate electrical wires 133 extend through the connector blocks 140, 145, the conduits 142, 147 and the central section 131 of the junction block 120. By way of example, these may include two ground terminal wires, three neutral wires and three positive wires representing three separate circuits, with a shared ground for two of the circuits. Similarly, 10- or 12-wire systems may be readily accommodated, having corresponding number of terminals on each of the connectors and providing a greater number of separate circuits. The four female receptacle connectors 126 are each connected to the wires 133 by means of a plurality of contact blades, described later herein with respect to Figs. 7 and 8. Each wire, together with the connector block terminals and receptacle connector terminals to which it is connected, is referred to herein as a circuit element. A particular circuit may be selected for use by one of the receptacles 150 by appropriate wiring connections internal to the receptacle. Since all of the circuits are connected to each one of the receptacle connectors 126 of junction block 120, a connector block 145 of an adjacent panel, equipped with a male connector, may be connected to any one of the receptacle connectors 126. In this manner, electrical power may be provided to receptacle connectors to junction block 120 and to associated connector blocks 140, 145 and hence to any adjacent panels to which these connectors may be connected. Similarly, a connector block 145 equipped with a male connector connected to one of the female connectors 126 may receive electrical power for distribution to a panel to which the connector block 145 belongs. Such interconnecting arrangements are described further herein with respect to FIG. 6.

FIG. 7 is a fragmentary cross-sectional view along line 7-7 of FIG. 2. Shown in FIG. 7 is a contact blade structure 170 which is one of eight such blades disposed in central housing section 131. Each such blade is in electrical contact with one of the conductors 133. Connection to conductor 133 is made by means of a crimped connection

of blade extension member 172 to conductor 133. As may be more readily seen from the perspective view of FIG. 8, the extension member 172 is part of a center section 173 which is connected to left-hand upper and lower contact blades 174 and right-hand upper and lower contact blades 175. The upper and lower contact blades on each side from the female opening part of the conductor 126 for engagement with blades of a male connector.

FIG. 6 is a fragmentary plan view of raceway areas of four wall panels illustrating the connections of interconnection assemblies of the invention in a configuration in which the four panels are disposed at right angles to each other. As will be apparent from the following description, the specific angle at which the panels are positioned is not particularly significant. Each of the four panels is provided with an interconnection assembly, as shown in FIG. 2, comprising a junction block 120, a male connector block 145, and a female connector block 140 attached to the junction block 120 by means of flexible conduits 147 and 142, respectively. The junction block 120 is disposed within each panel raceway near one edge of the panel. Panels 200, 201, 202 are positioned such that the end at which these panels are joined to other panels is the end near which the junction block 120 is positioned. One of the panels, panel 203, is positioned with an opposite orientation in which the end near which the junction block 120 is located is positioned opposite the point of junction of the four panels. The flexible conduit 147, provided with the male connector block 145, extends beyond the end of the panel in which it is positioned, and the flexible conduit 142, provided with a female connector block 140, is terminated just short of the end of the panel.

Thus, as is also shown in FIG. 1, a connection is made between panels by extending the flexible conduit 147 with male connector block 145 into the raceway area of the adjacent panel to engage the female connector block 140 at the end of flexible conduit 142. In the configuration of FIG. 6, the male connector block 145 of panel 202 and its associated flexible conduit 147 extend into the raceway area of panel 202 to engage female connector block 140 of panel 203. It will be apparent that the connection as shown between panel 202 and 203 may be made whenever these panels are adjacent and independent of the angle at which the panels are disposed with respect to each other. In the configuration of FIG. 6, the flexible conduit 147, with its male connector block 145, associated with the panel 200 are extended into the raceway area of panel 202 for engagement with one of the female receptacle connectors 126 of junction block 120 in panel 202. In this manner, an electrical connection is established among the junction

blocks of the three panels 200, 202, and 203. Thus, electrical power provided from an external source to any one of these three may be distributed to the other two by means of the connection arrangement shown by way of example in FIG. 6. In the arrangement of FIG. 6, flexible conduit 147 and its male connector block 145 of panel 202 is connected to one of the female connectors 126 of junction block 120 of panel 200 thereby establishing an electrical connection between panels 200 and 201. This connection, in combination with the other connections shown in FIG. 6 and described in the previous sentences, completes an arrangement for establishing an electrical connection from any one of four panels to the entire four-panel configuration. Additional connections may be envisioned by connections of male connectors 145 from other panels into additional ones of the female receptacle connectors 126 of the junction blocks 120 of any of the panels 201 through 203, should one choose to provide an arrangement of more than four intersecting panels. Furthermore, additional conduits, such as conduit 210 shown in FIG. 6, may be connected by means of a male connector to any of the receptacle connectors 126 to provide electrical power to lamps or other fixtures.

It will be apparent to those skilled in the pertinent arts that still other embodiments of connector assemblies in accordance with the invention can be designed. That is, the principles of a connector assembly in accordance with the invention are not limited to the specific embodiments described herein. Accordingly, it will be apparent to those skilled in the art that modifications and other variations of the above-described illustrative embodiments of the invention may be effected without departing from the spirit and scope of the novel concepts of the invention.

CLAIMS:

1. A connector assembly for use with a power distribution system for carrying electrical power and for providing electrical devices external to said connector assembly
5 with access to said electrical power, said connector assembly comprising:
 - a front housing half;
 - a rear housing half;
 - an internal wiring assembly comprising a plurality of wires having H-type connectors connected at one end of each wire, and a single male blade terminal connected
10 at opposing ends of each wire;
 - a power connector set forming a connector housing around a terminal group comprising said single blade terminal;
 - at least four cable connector sets formed on said connector assembly, with each H-type connector forming one terminal in each one of said cable connector sets.

Application number / Numéro de demande: 2783/31

Figures: 1- 34 all pages

Pages: _____

Unscannable items received with this application
(Request original documents in File Prep. Section on the 10th floor)

Documents reçu avec cette demande ne pouvant être balayés
(Commander les documents originaux dans la section de la préparation
des dossiers au 10^{ième} étage)