



(51) International Patent Classification:  
**G01N 21/17** (2006.01)

(21) International Application Number:  
PCT/US2011/023767

(22) International Filing Date:  
4 February 2011 (04.02.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
61/301,340 4 February 2010 (04.02.2010) US

(71) Applicant (for all designated States except US): **SPECTRA SYSTEMS CORPORATION** [US/US]; 321 South Main Street, Providence, RI 02903 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LAWANDY, Nabil, M.** [US/US]; 80 Beauchamp Drive, Saundertown, RI 02874 (US).

(74) Agents: **FAJKOWSKI, James E.** et al.; K&L Gates LLP, State Street Financial Center, One Lincoln Street, Boston, MA 02111-2950 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: GAS ACTIVATED CHANGES TO LIGHT ABSORPTION AND EMISSION CHARACTERISTICS FOR SECURITY ARTICLES




FIG. 1

(57) Abstract: Disclosed are security articles and methods and systems for authenticating security articles using a plurality of stimuli. According to one embodiment, an illustrative security feature includes activation of phosphorescent or fluorescent materials by the simultaneous presence of a source of electromagnetic radiation and a specific gas environment. A detector detects a spectral emission of the security feature that results from the change in gas environment. The spectral emission may be compared to an expected emissive signature to determine authenticity of the security article.

**GAS ACTIVATED CHANGES TO LIGHT ABSORPTION  
AND EMISSION CHARACTERISTICS FOR SECURITY ARTICLES**

**RELATED APPLICATION**

5    [0001]    This application claims priority to provisional application USSN 61/301,340, filed February 4, 2010, the disclosure of which is herein incorporated by reference in its entirety.

**FIELD OF INVENTION**

10   [0002]    The present invention relates to security articles, and more specifically to security articles having light absorption and emission characteristics that change upon exposure to a specific gas environment.

**BACKGROUND**

15   [0003]    Counterfeiting and forgery have become significant concerns in the modern economy and marketplace. Advances in computing technology and printing techniques have increased the incidence of forgeries, counterfeited documents, and other fraudulent activities. Countless areas of today's high-technology society require and rely upon certification, authentication and protection of highly valuable documents, papers, currency and other materials. Thus, there is a need for security markings to be incorporated into currency, important documents, packaging, and other authentic materials to prevent unauthorized copying, forging, counterfeiting and other fraudulent use.

20   [0004]    While fraudulent activities such as counterfeiting currency and forging signatures or handwriting are common, methods of creating and perfecting forgeries and counterfeit documents have become easier and more available with the advent of highly sophisticated computer printing and processing. As far back as 1991, the United States Treasury has continually added security safeguard features to the denominations of currency in an

attempt to combat the use of counterfeit money. These safeguards have included watermarks, security threads embedded in the paper, microprinting, color-shifting ink, and the use of multi-colored bills.

[0005] Current methods of authentication of currency involve visual observation, scanning under ultraviolet lamps, notes containing security threads, and emissive materials such as inks and planchettes. Such security threads emit a distinct marking, color or code in response to exposure to the ultraviolet light. In some circumstances, the emissive features of different denominations of notes can emit different colors. In addition to the colors of the emission, a code number or other unique identifier can be detected by the naked eye when the note is exposed to ultraviolet light or excitation of some form.

[0006] Authentication of security articles, such as valuable documents or materials, affects many facets of the economy. Notary publics use a raised stamp to authenticate notarized documents. In turn, drivers' licenses, passports and other photographic identification contain holograms and microprinting. Similarly, sporting memorabilia and retail clothiers use holographic tags and stamps to prove authenticity. Even fashion designers are now including authentication devices in their clothing to prevent passing off of knock-offs as designer products.

[0007] For example, if a counterfeiter is aware there is a security thread in a bill or a watermark in a document, then replication of the security feature will be easier. Once a feature is made known, a counterfeiter may begin to develop specific strategies and solutions to overcome the security protections provided by the specific feature.

[0008] Accordingly, a need exists for security features that further reduce a counterfeiter's likelihood of success, even if they are aware of the existence of the security feature.

## SUMMARY

[0009] Embodiments of the invention include security articles and methods and systems for authenticating security articles using a plurality of stimuli. According to one embodiment, an illustrative security feature includes activation of phosphorescent or fluorescent materials by the simultaneous presence of a source of electromagnetic radiation and a specific gas environment. Thus, the radiation and gas serve as first and second stimuli.

[0010] Security articles, such as those described herein, may require more than one stimulus, e.g., application of both light and a gas environment, to detect the authentication feature. Further, such security articles may have security features that can be used either publicly, covertly, or both, i.e., having a first response for public access and a second response for covert usage.

[0011] In one embodiment, the invention relates to a security article. The security article can include a host material comprising a gas-activated security feature incorporated upon or within the host material, wherein the gas-activated security feature is capable of emitting a spectral emission that changes upon exposure to a change in gas environment of the gas-activated security feature. The host material may include a polymer. The host material may include a responsive portion and a non-responsive portion, wherein the gas-activated security feature may be incorporated upon or within the responsive portion. The host material may include a reference security feature. In such a case, the security feature and the reference security feature may emit different spectral emissions upon exposure to the change in gas environment. Also, in such a case, the security feature and the reference security feature may emit equivalent spectral emissions upon exposure to the change in gas environment. The gas-activated security feature may include a material selected from the group consisting of fluorescent material and phosphorescent material.

The gas-activated security feature may include a material selected from the group consisting of platinum(II) or palladium(II) porphyrins, platinum(II) or palladium(II) phthalocyanines or naphthalocyanines, ruthenium(II) tris-bipyridine type complexes, terbium(III) assorted complexes, perylene dyes, hydroxypyrene trisulfonic acid,

5 Reichardt's dye, and combinations thereof. The gas-activated security feature may be incorporated upon or within a carrier selected from the group consisting of an ink, a coating, a security thread, a planchette, a particle, a hologram, and a windowed region.

[0012] In another embodiment, the invention relates to a method of authenticating a security article. The method can include the steps of directing electromagnetic radiation  
10 to a security article comprising a gas-activated security feature; initiating a change in gas environment of the security feature; and detecting a spectral emission of the security feature resulting from the change in gas environment. The step of initiating a change in gas environment of the security feature may include removing gas from or injecting gas into a first gas environment of the security feature to create a second gas environment of  
15 the security feature. The method may further include the step of comparing the spectral emission with an expected spectral emission to determine authenticity of the security article. The method may further include the step of measuring a time response of the spectral emission. The method may further include the step of changing the spectral emission of the security feature from an original state to a gas-activated state. The  
20 method may further include the step of changing the spectral emission of the security feature from a gas-activated state to an original state.

[0013] In a further embodiment, the invention relates to a detector system for authenticating a security article. The system includes an electromagnetic radiation source for directing electromagnetic radiation to a security article comprising a gas-activated  
25 security feature; a gas environment source for initiating a change in gas environment of

the gas-activated security feature; and a detector for detecting a spectral emission of the gas-activated security feature resulting from the change in gas environment. The electromagnetic radiation source may include wavelengths selected from the group consisting of infrared, visible, and ultraviolet. The gas environment source may provide a gas environment selected from the group consisting of inert gas, water vapor, oxygen, carbon dioxide, chemical vapors, and human breath. The gas environment source may provide a gas environment by change in pressure or density, or by application of a vacuum. The detector system may further include a gas environment altering device that removes gas from or injects gas into the gas environment. The detector may be a spectrometer.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] These embodiments and other aspects of this invention will be readily apparent from the detailed description below and the appended drawings, which are meant to illustrate and not to limit the invention, and in which:

FIG. 1 is an illustrative embodiment of the invention showing a security article, an electromagnetic radiation source, a gas environment source, and a detector in accordance with an embodiment of the invention;

FIG. 2 is an illustrative graph of the spectral emission of a security article in accordance with an embodiment of the invention;

FIG. 3 depicts the application of a gas environment to a security article in accordance with an embodiment of the invention; and

FIG. 4 is an illustrative graph of the spectral emission of a security article in accordance with an embodiment of the invention.

### DETAILED DESCRIPTION

[0015] The invention will be more completely understood through the following detailed description, which should be read in conjunction with the attached drawings. Detailed embodiments of the invention are disclosed herein, however, it is to be understood that  
5 the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, specific functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the invention in virtually any appropriately detailed embodiment.

10 [0016] Embodiments of the invention include fluorescent or phosphorescent emissions from a security article upon the application of a specific gas environment. Specifically, application of a particular gas reveals unique spectral signatures of a security article. In one embodiment, exposing the security article to a gaseous excitation, i.e., a specific gas environment, reveals a unique spectral emission by which the security article may be  
15 authenticated. According to embodiments of the invention, excitation of the security article may include visible ambient light or sunlight, or may include other light or electromagnetic sources such as ultraviolet sources or infrared sources.

[0017] The specific gas environment to which the security article may be exposed may include both a responsive gaseous portion, which is capable of causing changes to the  
20 absorption or excitation of the security feature, and a non-responsive gaseous portion, which does not cause such a response to the security feature. According to one embodiment of the invention, the gas used for excitation may be a non-toxic, safe-exposure gas, such as an inert gas. According to other embodiments, the responsive gaseous portion may include water vapor, oxygen, carbon dioxide or other chemical  
25 vapors, or human breath, which has depleted oxygen levels compared to the atmosphere.

Further, the responsive gaseous portion may be the result of a change in the gas environment, such as a pressure or density change, e.g., by creating a vacuum.

[0018] The security article may include one or more gas sensitive materials, which may be disposed on or within a permeable host material, such as a polymer material. The gas sensitive material of the security article may be part of an ink, a coating, a security thread, a planchette, a particle, a hologram, or a windowed region in a document or banknote. The light emission spectrum of the security article can extend from the ultraviolet to the infrared, depending on the gas environment. The excitation response of the gas sensitive material is a result of the types of molecules used, the bonding capabilities of the material to a host material, and the permeability of the material to various gas constituents of the host material.

[0019] The absorption characteristics of the gas sensitive material change with exposure to a specific gas environment. The change in the absorption characteristics may result in a change of the visible color of the gas sensitive material. The changes in the absorption characteristics may result with or without the application of sources of light or electromagnetic radiation in addition to or instead of ambient light or sunlight. The light emission or color of the gas sensitive material may change upon excitation with a stimulus from an electromagnetic source, e.g., ultraviolet, visible or infrared. Thus, authenticity of a security article may be determined by measuring the intensity of the security feature's spectral emission or change thereof.

[0020] In addition, the gas sensitive material may have the characteristic that it changes color upon a stimulus from an electromagnetic source and has a relaxation or rate of change back to its original color determined by the gas environment. In other words, the light emission of the gas sensitive material may have a lifetime that depends on the specific gas environment or changes to the gas environment. The gas-activated security



feature may be in (1) an original state prior to application of electromagnetic radiation and/or a gas environment, (2) a gas-activated state simultaneous with or after application of electromagnetic radiation and/or a gas environment, or (3) reversion to an original state after application of electromagnetic radiation and/or a gas environment. The spectral  
5 emission may respond differently in the original, activated, and reversionary states. Thus, authenticity of a security article may also be determined by measuring fluorescence lifetime, i.e., a time response of the security feature's spectral emission or change thereof.

[0021] A detector system for analyzing the security features in a security article may include an electromagnetic or light excitation source, a device for spectral detection of  
10 absorption, color or emission, and a gas environment altering device, such as a pump, nozzle or jet from a gas source. The gas environment altering device may suck air away from around the security article or may blow a specific gas composition onto the security article. Alternatively, the gas environment altering device may include a straw-like device for blowing human breath onto the article. The detector system may also be  
15 capable of measuring the time response of the phase responses of spectral changes of the security article, e.g., with respect to periodic excitation by light or a gas environment.

[0022] The spectral emissions of a security article may be used to identify and verify the authenticity of the article. A spectral emission may be illustrated by showing the intensity of the feature as a function of wavelength. A spectral emission from a typical  
20 security feature yields a signature having detectable characteristics or patterns across the wavelength spectrum. According to one embodiment of the invention, the security feature is enhanced such that excitation of the feature creates a distinct spectral pattern that may be analyzed to verify authenticity. If, upon scanning the spectral emission of the article containing the feature, the expected emissive signature does not match an expected

signature, the article may be a forgery or may have been tampered with. If the signature matches the expected pattern or value, the document may be authentic.

[0023] FIG. 1 is an illustrative embodiment of the invention showing a security article, an electromagnetic radiation source, a gas environment source, and a detector. The security article 2 has a gas-activated security feature 4 incorporated upon or within a host material 5 6. An electromagnetic radiation source 8 directs electromagnetic radiation to the security article 2 having a gas-activated security feature 4. A gas environment source 10 initiates a change in gas environment of the security feature 4. A detector 12 detects a spectral emission 14 that results from the change in gas environment and/or simultaneous or 10 subsequent exposure to electromagnetic radiation.

[0024] FIG. 2 shows a spectral emission signature of a security feature in accordance with an embodiment of the invention. Specifically, FIG. 2 depicts the intensity of an emissive response from two excitation forms – one optical, one optical and gaseous – as a function of wavelength. A first spectral signature 16 is the result of optical excitation of the security feature; application of the optical excitation results in a higher emission over 15 certain wavelengths. A second spectral signature 18 results from the excitation of the security feature with optical and gaseous exposure simultaneously. As shown in the graph of FIG. 2, the spectral signature of the excitation including a specific gas environment results in a significantly higher emissive response. A detector system, such as a spectrometer, may easily read the higher intensity of the security article's emission as 20 part of the authentication process.

[0025] FIG. 3 depicts the application of an optical and gaseous excitation to a phosphorescent material. When exposed to ultraviolet light or another type of electromagnetic radiation and a specific gas from a jet 19, the phosphorescent material 20 25 exhibits a detectable intensity 21 in the region  $\lambda$  to which the light and gas are applied.

[0026] According to another embodiment of the invention, dual excitation materials or coatings may be included within existing phosphorescent or fluorescent emissive security features. FIG. 4 depicts a spectral graph (intensity versus wavelength) in accordance with an embodiment of the invention. A first spectral signature 22 exhibits a unique signature  
5 under optical and gaseous excitation. The first spectral emission of a chromophore, for example, yields a signature having unique and definable features at given wavelengths. In the example shown in FIG. 4, dips (absorption) and peaks (emissions) in the spectral emission occur at a certain wavelengths. These dips and peaks are undetectable to the human eye; however, the feature is machine-readable, requiring only the use of a  
10 spectrometer or other detector system. A second spectral emission 24 shows the effect of the non-responsive portions of the gas environment, thus highlighting the additional spectral signature, i.e., measurable and quantifiable spectral shifts, obtained upon application of optical and gaseous excitation in spectral signature 22.

[0027] According to an embodiment of the invention, a machine-detectable security  
15 feature is included in a security article such as a document, currency, or secondary packaging for items such as tobacco, luxury goods, or pharmaceuticals. The security feature may be, e.g., embedded within a security thread, planchette or as part of an ink, resulting in a visible change of the excited signature of the threads when viewed using an ultraviolet source or lamp or other appropriate excitation source. Application of a  
20 specific gas environment, however, may lead to both a color change in the security feature as well as measurable and quantifiable spectral shifts, as shown in FIG. 4. The security feature, while undetectable to the naked eye under some circumstances, emits a specific and distinct color as well as a unique spectral fingerprint under optical and gaseous excitation in a specific gas environment. Choices in different phosphors lead to  
25 different color and spectral emissions. The incorporation of a machine readable, covert

feature may be implemented without any change to the public perception of the excited emission signature, thereby making forgery or duplication of the document more difficult.

[0028] There are various classes of compounds that may exhibit either an increase or decrease of electromagnetic radiation emission, intensity changes, fluorescence, or other detectable changes upon exposure to a specific gas environment. For example and without limitation, in one embodiment, the following classes of compounds may be gas-activated in an oxygen environment or other gas environment: platinum(II) or palladium(II) porphyrins; platinum(II) or palladium(II) phthalocyanines or naphthalocyanines; ruthenium(II) tris-bipyridine type complexes; terbium(III) assorted complexes; and perylene dyes. For example and without limitation, in another embodiment, the following classes of compounds may be gas-activated in a carbon dioxide environment or other gas environment: hydroxypyrene trisulfonic acid ("HPTS") in wet polymer or sol-gel media. For example and without limitation, in a further embodiment, the following classes of compounds may be gas-activated in a water environment or other type of environment: ruthenium(II) tris-bipyridine type complexes; perylene dyes; and Reichardt's dye. In one embodiment, a water sensitive absorber can be used to selectively block absorption or emission from a fluorescent dye or other type of dye that is unaffected by water.

[0029] While embodiments of the invention disclosed herein describe detection of emissive features under the excitation of light and gas sources, one skilled in the art should recognize that advantages of the absorptive properties of a gas sensitive material may be utilized as a security feature. For example, according to another embodiment of the invention, a security feature may include phosphorescent material having an absorptive spectral response at certain wavelengths under optical excitation. Application

of a gaseous excitation to the material results in the recovery of the emissive intensity of the material.

[0030] While embodiments of the invention disclosed herein describe detection based on specific responses to excitation sources, one skilled in art should recognize that additional parameters may be incorporated, such as the temporal decay of emissions, the spectral signature of the host, and response time and change in emission under gaseous excitation, without deviating from the scope of the invention.

[0031] The aspects, embodiments, features, and examples of the invention are to be considered illustrative in all respects and are not intended to limit the invention, the scope of which is defined only by the claims. Other embodiments, modifications, and usages will be apparent to those skilled in the art without departing from the spirit and scope of the claimed invention.

[0032] The use of headings and sections in the application is not meant to limit the invention; each section can apply to any aspect, embodiment, or feature of the invention.

[0033] Throughout the application, where compositions are described as having, including, or comprising specific components, or where processes are described as having, including or comprising specific process steps, it is contemplated that compositions of the present teachings also consist essentially of, or consist of, the recited components, and that the processes of the present teachings also consist essentially of, or consist of, the recited process steps.

[0034] In the application, where an element or component is said to be included in and/or selected from a list of recited elements or components, it should be understood that the element or component can be any one of the recited elements or components and can be selected from a group consisting of two or more of the recited elements or components. Further, it should be understood that elements and/or features of a

composition, an apparatus, or a method described herein can be combined in a variety of ways without departing from the spirit and scope of the present teachings, whether explicit or implicit herein.

[0035] The use of the terms “include,” “includes,” “including,” “have,” “has,” or “having” should be generally understood as open-ended and non-limiting unless specifically stated otherwise.

[0036] The use of the singular herein includes the plural (and vice versa) unless specifically stated otherwise. Moreover, the singular forms “a,” “an,” and “the” include plural forms unless the context clearly dictates otherwise. In addition, where the use of the term “about” is before a quantitative value, the present teachings also include the specific quantitative value itself, unless specifically stated otherwise. As used herein, the term “about” refers to a  $\pm 10\%$  variation from the nominal value.

[0037] It should be understood that the order of steps or order for performing certain actions is immaterial so long as the present teachings remain operable. Moreover, two or more steps or actions may be conducted simultaneously.

[0038] Where a range or list of values is provided, each intervening value between the upper and lower limits of that range or list of values is individually contemplated and is encompassed within the invention as if each value were specifically enumerated herein. In addition, smaller ranges between and including the upper and lower limits of a given range are contemplated and encompassed within the invention. The listing of exemplary values or ranges is not a disclaimer of other values or ranges between and including the upper and lower limits of a given range.

[0039] While the invention has been described with reference to illustrative embodiments, it will be understood by those skilled in the art that various other changes, omissions and/or additions may be made and substantial equivalents may be substituted

for elements thereof without departing from the spirit and scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed for

5 carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims. Moreover, unless specifically stated any use of the terms first, second, etc. do not denote any order or importance, but rather the terms first, second, etc. are used to distinguish one element from another.

What is claimed is:

1. A security article, comprising:  
a host material comprising a gas-activated security feature incorporated upon or within the host material, wherein the gas-activated security feature is capable of emitting  
5 a spectral emission that changes upon exposure to a change in gas environment of the gas-activated security feature.
2. The security article of claim 1 wherein the host material comprises a polymer.
3. The security article of claim 1 wherein the host material comprises a  
10 responsive portion and a non-responsive portion, and wherein the gas-activated security feature is incorporated upon or within the responsive portion.
4. The security article of claim 1 wherein the host material further comprises a reference security feature.
5. The security article of claim 4 wherein the security feature and the  
15 reference security feature emit different spectral emissions upon exposure to the change in gas environment.
6. The security article of claim 4 wherein the security feature and the reference security feature emit equivalent spectral emissions upon exposure to the change in gas environment.
- 20 7. The security article of claim 1 wherein the gas-activated security feature comprises a material selected from the group consisting of fluorescent material and phosphorescent material.
8. The security article of claim 1 wherein the gas-activated security feature comprises a material selected from the group consisting of platinum(II) or palladium(II)  
25 porphyrins, platinum(II) or palladium(II) phthalocyanines or naphthalocyanines,



ruthenium(II) tris-bipyridine type complexes, terbium(III) assorted complexes, perylene dyes, hydroxypyrene trisulfonic acid, Reichardt's dye, and combinations thereof.

9. The security article of claim 1 wherein the gas-activated security feature is further incorporated upon or within a carrier selected from the group consisting of an ink,  
5 a coating, a security thread, a planchette, a particle, a hologram, and a windowed region.

10. A method of authenticating a security article, comprising the steps of:  
directing electromagnetic radiation to a security article comprising a gas-activated security feature;  
initiating a change in gas environment of the security feature; and  
10 detecting a spectral emission of the security feature resulting from the change in gas environment.

11. The method of claim 10 wherein the step of initiating a change in gas environment of the security feature comprises removing gas from or injecting gas into a first gas environment of the security feature to create a second gas environment of the  
15 security feature.

12. The method of claim 10 further comprising the step of comparing the spectral emission with an expected spectral emission to determine authenticity of the security article.

13. The method of claim 10 further comprising the step of measuring a time  
20 response of the spectral emission.

14. The method of claim 10 further comprising the step of changing the spectral emission of the security feature from an original state to a gas-activated state.

15. The method of claim 10 further comprising the step of changing the spectral emission of the security feature from a gas-activated state to an original state.

25 16. A detector system for authenticating a security article, comprising:

an electromagnetic radiation source for directing electromagnetic radiation to a security article comprising a gas-activated security feature;

a gas environment source for initiating a change in gas environment of the gas-activated security feature; and

5 a detector for detecting a spectral emission of the gas-activated security feature resulting from the change in gas environment.

17. The detector system of claim 16 wherein the electromagnetic radiation source includes wavelengths selected from the group consisting of infrared, visible, and ultraviolet.

10 18. The detector system of claim 16 wherein the gas environment source provides a gas environment selected from the group consisting of inert gas, water vapor, oxygen, carbon dioxide, chemical vapors, and human breath.

19. The detector system of claim 16 wherein the gas environment source provides a gas environment by change in pressure or density, or by application of a  
15 vacuum.

20. The detector system of claim 16 further comprising a gas environment altering device that removes gas from or injects gas into the gas environment.

21. The detector system of claim 16 wherein the detector is a spectrometer.

1/4




FIG. 1

2/4




FIG. 2




FIG. 3




FIG. 4

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US2011/023767

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - G01N 21/17 (2011.01)

USPC - 428/916

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - G01N 21/00, 17, 61, 62, 63, 64 (2011.01)

USPC - 359/2; 422/82.05, 82.08; 428/915, 916

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PatBase, Google Patents

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ---	WO 00/38283 A1 (LAWANDY) 29 June 2000 (29.06.2000) entire document	10, 12, 14-15
Y		1-9, 11, 13
Y	US 2005/0109983 A1 (PAI-PARANJAPE et al) 26 May 2005 (26.05.2005) entire document	1-9, 13, 16-21
Y	US 7,089,420 B1 (DURST et al) 08 August 2006 (08.08.2006) entire document	11, 16-21

☐ Further documents are listed in the continuation of Box C.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

17 March 2011

Date of mailing of the international search report

01 APR 2011

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents  
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300  
PCT OSP: 571-272-7774