

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2015205451 B2

(54) Title
Improvements in or relating to stand mixer arrangements

(51) International Patent Classification(s)
A47J 43/07 (2006.01) **A47J 43/044** (2006.01)

(21) Application No: **2015205451** (22) Date of Filing: **2015.01.09**

(87) WIPO No: **WO15/104557**

(30) Priority Data

(31) Number **1400345.3** (32) Date **2014.01.09** (33) Country **GB**

(43) Publication Date: **2015.07.16**

(44) Accepted Journal Date: **2019.08.08**

(71) Applicant(s)
Kenwood Limited

(72) Inventor(s)
Seidler, Mark;Weaden, Jamie

(74) Agent / Attorney
Griffith Hack, GPO Box 4164, Sydney, NSW, 2001, AU

(56) Related Art
GB 1464838 A
US 2275878 A
US 2003/0179645 A1
US 2517648 A
CN 201341811 Y

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2015/104557 A1

(43) International Publication Date
16 July 2015 (16.07.2015)

(51) International Patent Classification:
A47J 43/07 (2006.01) *A47J 43/044* (2006.01)

(74)

Agent: **HECTOR, Annabel Mary**; Mathys & Squire LLP,
The Shard, 32 London Bridge Street, London SE1 9SG
(GB).

(21) International Application Number:

PCT/GB2015/050039

(81)

Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:

9 January 2015 (09.01.2015)

(82)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1400345.3 9 January 2014 (09.01.2014) GB

(83)

(71) Applicant (for all designated States except US): **KENWOOD LIMITED** [GB/GB]; New Lane, Havant Hampshire PO9 2NH (GB).

(84)

Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPROVEMENTS IN OR RELATING TO STAND MIXER ARRANGEMENTS




Fig 3

(57) Abstract: A stand mixer arrangement includes a pedestal (20) for a mixing bowl (30); an electric motor and a drive system including a rotary drive outlet (60) disposed overhead of the bowl (30), capable of imparting a mixing action to a tool (12) suspended into the bowl (30) from a socket (62) supported by said drive outlet (60); and illumination means (70, 72, 74, 76) encircling, or substantially encircling, said drive outlet (60) and arranged to direct light into the mixing bowl (30).



Published:

— *with international search report (Art. 21(3))*

IMPROVEMENTS IN OR RELATING TO STAND MIXER ARRANGEMENTS

Technical Field

5 This disclosure relates to stand mixers, by which is meant the kind of motor-driven kitchen machine which is used to mix, or otherwise process, ingredients in a bowl by powered movement of one or more shanked tools which are suspended into the bowl from a head unit that carries a downwardly-facing rotary drive outlet, powered by the motor, and having

10 a socket to which the shank, or shanks, of the tool, or tools can be fitted for use. The powered movement of the shanked tool or tools is often, though not necessarily, planetary in nature.

Background Art

15 Such mixers conventionally comprise a generally C-shaped casing which provides a pedestal-like support for a mixing bowl, and a generally upright support portion supports the head unit so that it extends overhead of the bowl. Usually, the upright portion is hinged, to allow the head unit to be raised relative to the pedestal, so as to facilitate the fitment and

20 removal of the tools to and from the socket in the rotary drive outlet.

Stand mixers such as the Kenwood Chef kitchen machine are well known and have been well established in use for many years. Over the years, mixers of this kind have been adapted and developed so as to perform an

25 ever broadening range of functions, and many such appliances provide, for example, a plurality of additional drive outlets running at different speeds and with differing torque characteristics, thus enabling them to

drive a number of attachments, such as blenders and mincers, which, between them, can perform a wide range of tasks. This is beneficial for the user, because a single machine can be used to selectively host several attachments and thus perform a range of tasks which would otherwise 5 require the purchase and storage of several bespoke kitchen machines, each with their own motors and associated equipment.

Recent technical developments have provided stand mixers with a still broader operational capability, as it has been proposed to incorporate 10 heating arrangements into such machines, thereby to enable foodstuffs to be heated whilst being stirred or mixed by the normal planetary mixing action of the stand mixer. Of course, the heating arrangements can be used or not, according to user requirements, and it will also be appreciated that the heating temperature and the heating time are both 15 controllable, enabling the user to apply any desired degree of heating; for example sufficient to completely cook, to partially cook, or to merely warm ingredients.

In any event, when preparing food with a stand mixer, using the shanked 20 tools and the bowl, it is greatly advantageous for the user to have good visibility of the ingredients in the bowl, as this provides the user with the ability to exert greater control over the preparation process. Light naturally entering the bowl from its working environment is reduced due to the constructional arrangement of a stand mixer which, as explained, 25 has its head unit above the bowl and the tool or tools suspended from the downwardly-facing drive outlet.

Proposals have been made, for example as described in GB1464838 and in CN201861482, to increase the visibility of ingredients being worked in the bowl by incorporating an electrically powered light source mounted on the underside of the head unit of the appliance and offset from the 5 drive outlet. Such a light source can provide useful additional light into the bowl, but only from a single direction. With arrangements as proposed in the aforementioned patent publications, the mixing tool in the bowl casts a shadow onto the ingredients on the side of the bowl opposite the light, thus compromising the visibility of the ingredients.

10

In some circumstances, moreover, it is desirable to provide a bowl cover, usually made of transparent plastics material, to reduce unwanted egress of steam and/or to prevent ingredients being ejected from the bowl or other receptacle in which they are being stirred and/or heated. With 15 existing lighting arrangements, the bowl illumination is further compromised when the optional transparent bowl cover is fitted.

It is to be understood that, if any prior art is referred to herein, such reference does not constitute an admission that the prior art forms a part 20 of the common general knowledge in the art, in Australia or any other country.

Summary

In some forms, disclosed is a system that provides improved illumination 25 of the bowl interior and its contents.

According to the disclosure, there is provided a stand mixer arrangement for mixing ingredients in a mixing bowl, the stand mixer arrangement including a pedestal for a mixing bowl; an electric motor and a drive system including a downwardly facing rotary planetary drive outlet disposed overhead of the pedestal for the mixing bowl, capable of imparting a mixing action to a tool suspended into the mixing bowl from a socket supported by said rotary planetary drive outlet; and illumination means encircling, or substantially encircling, said (in some forms, the means comprising at least one light source) rotary planetary drive outlet and arranged to direct light downwardly into the mixing bowl, to illuminate ingredients therein.

In some embodiments, the socket may be supported on the axis of the rotary drive outlet, or in some embodiments it may be offset from said axis so as to describe a circular orbit around the axis, enabling a tool supported from the socket to perform a planetary motion by executing rotation about the socket axis as well as being bodily rotated around the axis of the drive outlet.

20 In some embodiments, the illumination means may comprise at least one light source.

25 In one embodiment, the illumination means may comprise an extended light source, such as an elongate filament and/or an array of discrete light sources, disposed under a common optically transmissive cover.

In some embodiments, the illumination means may comprise a plurality of separate light sources distributed around said drive outlet and each disposed under a respective optically transmissive cover.

- 5 In either event, there is provided improved illumination of ingredients within the bowl, because the light sources are positioned to encircle, or substantially encircle, the drive outlet, thereby significantly reducing the shadowing effect of the mixing tool.
- 10 Embodiments may incorporate the light source, or sources, into a single transparently-capped enclosure encircling the drive outlet.

The enclosure, or an annular cap therefor, in some forms may comprise a light-guide or lens to optimise the light emission for even illumination.

- 15 Where a bowl cover is provided, the cover may be configured to transmit the illumination to the bowl, and in such circumstances the cover may be formed with an annular window region through which the illumination from said source or sources of light can pass. The window region may be
- 20 apertured and/or include one or more elements formed as a lens or light-guide to enhance the illumination.

- 25 The light source(s) may be controlled manually to switch them on or off, and/or to vary the brightness level, for example by means of a user interface such as a control panel, or they may be controlled automatically for example by means of a control unit. The control unit may be in communication with one or more detectors arranged to detect a condition

such as an ambient light level or change in the ambient light level, an illumination level of the light source(s) or a change therein, or the position or change in position of a head unit of the mixer where the mixer has a head unit extending over the bowl which may be lifted to facilitate

5 access to the bowl and/or mixing tools.

Thus, the stand mixer may further comprise a control unit arranged to control the luminance of the illumination means, for example to actuate the illumination means to turn the light source(s) on or off, or to change

10 the brightness or luminance of the illumination means, for example to dim or brighten the illumination provided. Where the illumination means comprises a plurality of light sources, one or more of the light sources or one or more groups of light sources may be controlled separately.

15 In some forms, the control unit may control the luminance of the illumination means in dependence upon at least one of the following parameters: a position of the drive outlet in relation to the pedestal; an ambient light level; a user input; power consumption of the stand mixer; and the illumination of the illumination means, or a change in any one of

20 these parameters.

The disclosure extends to a stand mixer arrangement substantially as herein described with reference to and/or as shown in Figures 2-4.

25 The disclosure also provides a computer program and a computer program product for carrying out any of the methods described herein and/or for embodying any of the apparatus features described herein, and

a computer readable medium having stored thereon a program for carrying out any of the methods described herein and/or for embodying any of the apparatus features described herein.

5 Any apparatus feature as described herein may also be provided as a method feature, and vice versa. As used herein, means plus function features may be expressed alternatively in terms of their corresponding structure, such as a suitably programmed processor and associated memory.

10

Any feature in one aspect of the disclosure may be applied to other aspects of the disclosure, in any appropriate combination. In particular, method aspects may be applied to apparatus aspects, and vice versa. Furthermore, any, some and/or all features in one aspect can be applied to 15 any, some and/or all features in any other aspect, in any appropriate combination.

20

It should also be appreciated that particular combinations of the various features described and defined in any aspects of the disclosure can be implemented and/or supplied and/or used independently.

In order that the disclosure may be clearly understood and readily carried into effect, embodiments thereof will now be described, by way of example only, with reference to the accompanying drawings, of which:

25

Brief Description of the Drawings

Embodiments will now be described by way of example only, with reference to the accompanying drawings in which

Figure 1(a) shows, in perspective view, a typical stand mixer;

Figure 1(b) shows a detail of the drive outlet on the head of the stand

5 mixer;

Figure 2 shows, in side elevation, and with the head raised, a stand mixer provided with illumination;

Figure 3 shows a front elevational view of the mixer of Figure 2; and

Figure 4 shows a front elevational view of a mixer, and with the head

10 raised.

Detailed Description

Referring now to Figures 1(a) and 1(b), the stand mixer shown generally at 10 is a well-known and long-established piece of kitchen equipment.

15 This particular mixer has a heating capability, but such capability is optional in relation to this disclosure.

Stand mixers typically comprise a generally C-shaped casing which provides a pedestal-like support 20 for a mixing bowl 30 (see Figures 2 to 20 4), and a generally upright support portion 40 supporting a head unit 50 that extends, for operation, overhead of the bowl 30. The upright portion 40 is formed in two parts that can pivot relative to one another, so as to allow the head unit 50 to be lifted to facilitate the installation of tools and the fitting and removal of the bowl 30, and the head unit 50 carries a 25 downwardly-facing, motor-powered planetary drive outlet 60 to a socket 62 of which the shank of a kneading, whisking or other processing tool 12 (see Figures 2 and 3) is temporarily connected for use. The tool 12 is

suspended from the socket 62 of the drive outlet 60 and reaches down into the bowl 30 to mix ingredients therein.

Stand mixers are versatile appliances, and typically provide, in addition to the aforementioned outlet 60 used to drive the shanked mixing tool 12, at least one further drive outlet for driving attachments with different speed and/or torque requirements, and configured for performing other tasks. Typically, such additional drive outlets may be set up to drive the operating tool of a high speed attachment, such as a food processor or a blender, or a low-speed/high torque attachment, such as a mincer.

Typically, and as best seen in Figure 1(b), the drive outlet 60 of the stand mixer 10 comprises the socket 62 carried by a disc-shaped member 64 that itself is directly or indirectly driven from a gearbox in the head unit 50 so as to rotate, in a horizontal plane, relative to the head unit 50, about a vertical central axis 66 that is typically (though not necessarily) aligned with the central axis of the bowl 30. Thus a tool mounted with its shank inserted into the drive socket 60 is rotated about the axis of its shank, and is bodily rotated around the axis 66, thereby describing a planetary motion.

As mentioned above, the stand mixer 10 may also incorporate heating means (not shown, but usually accommodated within the base 20), enabling ingredients in the bowl 30 to be heated whilst being subjected to the mixing action. The heating mechanism, if provided, may be provided by any convenient agency or method.

Referring now additionally to Figures 2 and 3, a first embodiment utilises an extended, electrically powered light source 70 to provide improved illumination of the ingredients within the bowl. The light source encircles the drive outlet 60, thus also encircling the socket 62 and thereby

5 reducing the shadow of the mixing tool 12. This significantly improves the illumination within the bowl. In this embodiment, the extended light source 70, which may comprise an elongate filament or an array of individual point sources, such as LEDs, is housed in the head unit 50 beneath a single transparently-capped enclosure, the cap of which may be

10 formed as, or incorporate, a light-guide or lens around the gearbox outlet disc 64 of the gearbox outlet 60. Such a light-guide or lens, if provided, is configured to enhance the spread and orientation of the light so as to optimise the illumination of the contents of the bowl 30.

15 In a second embodiment, shown in Figure 4, a plurality of separate light sources, 72, 74 and 76, each of which may comprise an elongate filament or one or more individual point sources, such as LEDs, are distributed around the outlet 60, again so as to substantially encircle the socket 62.

20 In both embodiments, the light sources 70 or 72, 74, 76 may be mounted so as to remain stationary in the head unit whilst the disc 64 and the socket 62 rotate around the axis 66. In some forms, however, the light sources can be mounted so as to rotate with the disc 64.

25 In an alternative embodiment, the light sources 70, 72, 74, and 76 are automatically controlled by a control unit (not shown) in the stand mixer 10 to dim when the head unit 50 is in a lifted position. Where the light

sources are LEDs, the control unit achieves this dimming by, for example, controlling the LEDs to dim using pulse-width modulation when it detects (by, for example, a switch in the stand mixer 10 being actuated) that the head unit 50 is raised. Dimming of the light sources 70, 5 72, 74, and 76 when the head unit 50 is lifted (and thus no longer casts a shadow on the bowl 30) prevents unnecessary brightness in the area of the bowl 30.

Alternatively, the control unit uses feedback from a light-level sensor (not 10 shown) located, for example, on a surface of the stand mixer 10 in the vicinity of the bowl 30, to control the light sources 70, 72, 74, and 76 to provide an appropriate level of illumination based on ambient light conditions, thus avoiding excessive brightness or dimness in the area of the bowl 30 due to ambient light conditions. Manual control of the 15 brightness-level of the light sources 70, 72, 74, and 76 is also optionally provided through a user interface 42 of the stand mixer 10.

Where multiple light sources are used, each light source optionally has its own individual power-supply, drive, or control circuit. Alternatively, each 20 group of two or more light sources has its own dedicated power-supply, drive, or control circuit. These groups are comprised of neighbouring light sources, or, for example, the light sources are divided into four groups where every fourth light source, counting along a row of light sources, belongs to a given group. Advantageously, this multiple 25 redundancy helps prevent a single-source failure of the entire lighting array.

In some forms, the control unit of the stand mixer 10 detects a condition of the light source(s), such as the failure of a light source (or group of light sources) by, for example, a change in the illumination level in the area of the bowl 30 being detected by a sensor providing feedback to the 5 control unit, and in response drive the remaining light sources (or light sources within the group in which a light source has failed) to emit more light in order to compensate, thus preventing uneven or excessively dim illumination. Alternatively, failure-detection is achieved through detecting changes in power-consumption amongst the light sources or by 10 other methods known in the art.

In the foregoing embodiments, no transparent bowl cover is positioned between the lights and bowl, so naturally the illumination provided by the light sources 70 or 72, 74 and 76 is not compromised thereby.

15 In the event that a transparent bowl cover is positioned between the lights and bowl, the cover is in some forms designed so that the illumination is not compromised thereby. This can be achieved, for example, by designing the cover to have an annular gap in alignment with the light 20 source, or sources, with thin spider-web features holding the parts of the cover to either side of the annular gap. Alternatively, the cover can be designed to incorporate an annular lens-like feature to assist in directing the light into the required areas of the bowl 30.

25 The light sources in the foregoing embodiments are powered (via voltage-changing and/or transforming circuitry if necessary) from the mains electricity supply connected to the stand mixer. This need not be the

case, however, and the light sources may, in some forms be powered by any other means, including batteries (single-use or rechargeable), solar cells and/or so-called “supercapacitor” drivers, i.e. drive circuits employing dual-layer capacitors or similar devices.

5

It will be understood that the present disclosure has been described above purely by way of example, and modifications of detail can be made within the scope of the disclosure.

10

Each feature disclosed in the description, and (where appropriate) the claims and drawings may be provided independently or in any appropriate combination.

Reference numerals appearing in the claims are by way of illustration

15

only and shall have no limiting effect on the scope of the claims.

In the claims which follow and in the preceding description of the invention, except where the context requires otherwise due to express language or necessary implication, the word “comprise” or variations

20

such as “comprises” or “comprising” is used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

Claims:

1. A stand mixer arrangement for mixing ingredients in a mixing bowl comprising; an electric motor and a drive system including a downwardly facing rotary planetary drive outlet for being disposed overhead of a pedestal for the mixing bowl, capable of imparting a mixing action to a tool suspended into the mixing bowl from a socket supported by said rotary planetary drive outlet; and illumination means encircling, or substantially encircling, said rotary planetary drive outlet and arranged to direct light downwardly into the mixing bowl to illuminate ingredients therein.
15
2. An arrangement according to claim 1, wherein said illumination means comprises one or more extended light sources.
3. An arrangement according to claim 1, wherein said illumination means comprises a plurality of discrete electrically powered light sources.
4. An arrangement according to any preceding claim, wherein said illumination means comprises one or more light sources incorporated into a single transparent enclosure encircling the rotary planetary drive outlet.
20
5. An arrangement according to claim 4, wherein said enclosure, or an annular cap thereover, comprises optical means configured to optimise the light emission for even illumination.
25

6. An arrangement according to claim 5, wherein said optical means comprises one of a light-guide or a lens.
7. An arrangement according to any preceding claim, wherein a cover is provided for said mixing bowl, and wherein said cover is configured to
5 transmit the illumination from said illumination means into the mixing bowl.
8. An arrangement according to claim 7, wherein said cover is formed with an annular window region through which the illumination from said
10 illumination means can pass.
9. An arrangement according to claim 8, wherein said window region comprises an aperture formed in said cover.
- 15 10. An arrangement according to claim 8, wherein said window region includes one or more optical elements formed as a lens or light-guide to enhance the illumination of said mixing bowl.
11. An arrangement according to any preceding claim further
20 comprising a control unit arranged to control the illumination means.
12. An arrangement according to Claim 11, wherein the control unit is arranged to actuate the illumination means and/or to vary the level of luminance provided by the illumination means.
- 25 13. An arrangement according to Claim 11 or 12, wherein the control unit is arranged to control the illumination means in dependence upon at

least one of: a position of the rotary planetary drive outlet; an ambient light level; a user input; power consumption of the stand mixer; and/or an illumination level of the illumination means.

- 5 14. An arrangement as claimed in Claim 13, comprising at least one detector in communication with the control unit and arranged to detect at least one of: a position or change in the position of the rotary planetary drive outlet in relation to the pedestal; an ambient light level or change in an ambient light level; a user input; power consumption or change in
- 10 power consumption of the mixer and/or the illumination means; an illumination level or change in illumination level of the illumination means.




Fig 1a




Fig 1b




Fig 2




Fig 4




Fig 3