



US008666071B2

(12) **United States Patent**  
**Weber**

(10) **Patent No.:** **US 8,666,071 B2**  
(45) **Date of Patent:** **Mar. 4, 2014**

(54) **SYSTEM AND METHOD FOR DELIVERING SATELLITE SERVICES AT MULTIPLE SECURITY LEVELS**

(58) **Field of Classification Search**  
USPC ..... 380/271, 200-202, 210, 212, 37, 42;  
713/163, 150, 166; 725/25, 31;  
705/50-56

(75) Inventor: **Barry Jay Weber**, Carmel, IN (US)

See application file for complete search history.

(73) Assignee: **Thomson Licensing**,  
Boulogne-Billancourt (FR)

(56) **References Cited**

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 805 days.

U.S. PATENT DOCUMENTS

6,134,419 A 10/2000 Williams  
6,240,183 B1 \* 5/2001 Marchant ..... 380/28  
(Continued)

(21) Appl. No.: **11/794,750**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **Oct. 26, 2005**

DE 10244079 4/2004  
EP 1511316 3/2005

(86) PCT No.: **PCT/US2005/038751**

§ 371 (c)(1),  
(2), (4) Date: **Jul. 3, 2007**

(Continued)  
OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2007/050066**

PCT Pub. Date: **May 3, 2007**

Harrison, C. et al.: "SMPTE Conditional Access DC28.4 Working Document," ISO/IEC JTC1/SC29/WG11 MPEG01/M7503, Jul. 2001, 80 pgs., XP002341986.

(Continued)

(65) **Prior Publication Data**

US 2009/0225984 A1 Sep. 10, 2009

*Primary Examiner* — Nirav B Patel

(74) *Attorney, Agent, or Firm* — Robert D. Shedd; Vincent E. Duffy; Michael A. Pugel


(51) **Int. Cl.**  
**H04N 7/167** (2011.01)  
**H04N 21/2389** (2011.01)  
**H04N 21/2347** (2011.01)  
**G06F 21/10** (2013.01)  
**H04L 29/06** (2006.01)

(57) **ABSTRACT**

The disclosed embodiments relate to a system and method for delivering satellite services at multiple security levels. More specifically, there is provided a method comprising determining a level of security supported by a first set top box, encoding a first IP packet containing a satellite service using the level of security supported by the first set top box, transmitting the first IP encoded packet to the first set top box, determining a level of security supported by a second set top box, wherein the level of security supported by the second set top box is different from the level of security of the first set top box, encoding a second IP packet containing a satellite service using the level of security supported by the second set top box; and transmitting the second encoded IP packet to the second set top box.

(52) **U.S. Cl.**  
CPC ..... **H04N 21/2389** (2013.01); **H04N 21/2347** (2013.01); **H04N 7/167** (2013.01); **G06F 21/10** (2013.01); **H04L 29/06659** (2013.01); **H04L 29/06687** (2013.01)  
USPC ..... **380/212**; 380/210; 380/200; 380/201; 725/30

**14 Claims, 3 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

7,010,681 B1 \* 3/2006 Fletcher et al. .... 713/154  
 7,443,983 B2 \* 10/2008 Tanizawa et al. .... 380/270  
 7,607,022 B1 \* 10/2009 Qiu et al. .... 713/189  
 7,644,266 B2 \* 1/2010 Ahuja et al. .... 713/151  
 7,916,755 B2 \* 3/2011 Hasek et al. .... 370/486  
 2001/0047422 A1 \* 11/2001 McTernan et al. .... 709/231  
 2002/0048275 A1 4/2002 Atwater et al.  
 2002/0196939 A1 \* 12/2002 Unger et al. .... 380/216  
 2003/0145329 A1 \* 7/2003 Candelore ..... 725/87  
 2003/0219127 A1 \* 11/2003 Russ et al. .... 380/239  
 2004/0064688 A1 \* 4/2004 Jacobs ..... 713/150  
 2004/0101138 A1 5/2004 Revital et al.  
 2004/0136533 A1 \* 7/2004 Takagaki et al. .... 380/255  
 2004/0240466 A1 12/2004 Unitt et al.  
 2005/0028011 A1 \* 2/2005 Motoyoshi et al. .... 713/201  
 2005/0117743 A1 6/2005 Bender et al.  
 2005/0141704 A1 6/2005 Van Der Veen  
 2005/0154921 A1 \* 7/2005 Medvinsky ..... 713/201  
 2005/0169473 A1 \* 8/2005 Candelore ..... 380/239

2006/0047957 A1 \* 3/2006 Helms et al. .... 713/165  
 2006/0191002 A1 \* 8/2006 Lee et al. .... 726/13  
 2006/0245589 A1 \* 11/2006 Pinder ..... 380/42

FOREIGN PATENT DOCUMENTS

JP 9-116534 8/1999  
 JP 2000-19959 1/2000  
 JP 2002-10229 1/2002  
 JP 2005-184463 10/2008  
 WO WO 02/09429 1/2002  
 WO WO0209429 1/2002  
 WO WO0286725 10/2002  
 WO WO 2004/084445 9/2004  
 WO WO2006027749 3/2006

OTHER PUBLICATIONS

Mitra, S.: "IOLUS: A Framework for Scalable Secure Multicasting,"  
 Computer Communication Review, ACM, New York, NY, US, vol.  
 27, No. 4, Sep. 14, 1997, pp. 1-12, XP002931671.  
 International Search Report, dated Jul. 25, 2006.

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3

## SYSTEM AND METHOD FOR DELIVERING SATELLITE SERVICES AT MULTIPLE SECURITY LEVELS

This application claims the benefit, under 35 U.S.C. §365 of International Application PCT/US2005/038751, filed Oct. 26, 2005, which was published in accordance with PCT Article 21(2) on May 3, 2007 in English.

### FIELD OF THE INVENTION

The present invention relates generally to transmitting video or other services data over a network. More specifically, the present invention relates to a system for delivering satellite services at multiple security levels.

### BACKGROUND OF THE INVENTION

This section is intended to introduce the reader to various aspects of art, which may be related to various aspects of the present invention that are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

As most people are aware, satellite television systems, such as DirecTV, have become much more widespread over the past few years. In fact, since the introduction of DirecTV in 1994, more than twelve million American homes have become satellite TV subscribers. Most of these subscribers live in single-family homes where satellite dishes are relatively easy to install and connect. For example, the satellite dish may be installed on the roof of the house.

Many potential subscribers, however, live or temporarily reside in multi-dwelling units ("MDUs"), such as hotels or high-rise apartment buildings. Unfortunately, there are additional challenges involved with providing satellite TV services to the individual dwelling units within an MDU. It may be impractical and/or extremely expensive to provide and connect one satellite dish per dwelling. For example, in a high-rise apartment building with one thousand apartments, it may be impractical to mount one thousand satellite dishes on the roof of the building. Some conventional systems have avoided these issues by converting the digital satellite television signal into an analog signal that can be transmitted via a single coaxial cable to a plurality of dwellings. These systems, however, offer limited channels, have reduced quality compared to all-digital systems, and cannot provide the satellite TV experience that users who live in single family homes are accustomed to.

An improved system and/or method for providing satellite TV to a multi-dwelling unit is desirable.

### SUMMARY OF THE INVENTION

Certain aspects commensurate in scope with the originally claimed invention are set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of certain forms the invention might take and that these aspects are not intended to limit the scope of the invention. Indeed, the invention may encompass a variety of aspects that may not be set forth below.

The disclosed embodiments relate to a system and method for delivering satellite services at multiple security levels. More specifically, there is provided a method comprising determining a level of security supported by a first set top box

(22a), encoding a first IP packet containing a satellite service using the level of security supported by the first set top box (22a), transmitting the first IP encoded packet to the first set top box (22a), determining a level of security supported by a second set top box (22b), wherein the level of security supported by the second set top box (22b) is different from the level of security of the first set top box (22a), encoding a second IP packet containing a satellite service using the level of security supported by the second set top box (22b); and transmitting the second encoded IP packet to the second set top box (22b).

### BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the invention may become apparent upon reading the following detailed description and upon reference to the drawings in which:

FIG. 1 is a block diagram of an exemplary satellite television over IP system in accordance with one embodiment of the present invention;

FIG. 2 is another embodiment of the exemplary satellite television over IP system illustrated in FIG. 1; and

FIG. 3 is a block diagram of an exemplary satellite gateway of the present invention.

### DETAILED DESCRIPTION

One or more specific embodiments of the present invention will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

Turning to FIG. 1, a block diagram of an exemplary satellite television over IP system in accordance with one embodiment is illustrated and generally designated by a reference numeral 10. As illustrated, in one embodiment, the system 10 may include one or more satellite dishes 12a through 12m, a head-end unit, such as a satellite gateway 14, an IP distribution network 20, and one or more set top boxes ("STBs") 22a through 22n. Those of ordinary skill in the art, however, will appreciate that the embodiment of the system 10 illustrated in FIG. 1 is merely one potential embodiment of the system 10. As such, in alternate embodiments, the illustrated components of the system 10 may be rearranged or omitted or additional components may be added to the system 10. For example, with minor modifications, the system 10 may be configured to distributed non-satellite video and audio services.

The satellite dishes 12a-12m may be configured to receive video, audio, or other types of television-related data that is transmitted from satellites orbiting the earth. As will be described further below, in one embodiment the satellite dishes 12a-12m are configured to receive DirecTV programming over KU band from 10.7 to 12.75 Gigahertz ("GHz"). In alternate embodiments, however, the satellite dishes 12a-12m may be configured to receive other types of direct broadcast satellites ("DBS") or television receive-only ("TVRO") signal, such as Dish Network signals, ExpressVu signals, Star-

Choice signals, and the like. In still other non-satellite based systems, the satellite dishes **12a-12m** may be omitted from the system **10**.

In one embodiment, a low noise-block converter (“LNC”) within the satellite dishes **12a-12m** receives the incoming signal from the earth-orbiting satellite and converts these incoming signals to a frequency in the L band between 950 and 2150 Megahertz (“MHz”). As will be described in further detail below with regard to FIG. 2, each of the satellites **12a-12m** may be configured to receive one or more incoming satellite TV signals on a particular frequency (referred to as a transponder) and with a particular polarization and to convert these satellite signals to L band signals, each of which may contain a plurality of video or audio signals.

The satellite dishes **12a-12m** may be configured to transmit the L band signals to a head-end unit or gateway server, such as the satellite gateway **14**. In alternate, non-satellite embodiments, the head-end unit may be a cable television receiver, a high definition television receiver, or other video distribution system

The satellite gateway **14** includes a satellite tuning, demodulating, and demultiplexing module **16** and an IP wrapper module **18**. The module **16** may contain a plurality of tuners, demodulators, and demultiplexers to convert the modulated and multiplexed L band signals transmitted from the satellites **12a-12m** into a plurality single program transport streams (“SPTS”), each of which carries a service (e.g., television channel video, television channel audio, program guides, and so forth). In one embodiment, the module **16** is configured to produce a single program transport stream for all of the services received by the satellite dishes **12a-12m**. In an alternate embodiment, however, the module **16** may produce transport streams for only a subset of the services received by the satellite dishes **12a-12m**.

The satellite tuning, demodulating, and demultiplexing module **16** may transmit the SPTS to the IP wrapper module **18**. In one embodiment, the IP wrapper module **18** repackages the data within the SPTS into a plurality of internet protocol (“IP”) packets suitable for transmission over the IP distribution network **20**. For example, the IP wrapper module **18** may convert DirecTV protocol packets within the SPTS into IP packets. In addition, the IP wrapper module **18** may be configured to receive server requests from the STBs **22a-22n** and to multicast (i.e., broadcast to one or more of the STBs **22a-22n** over an IP address) the IP SPTS to those STBs **22a-22n** that had requested the particular service.

In an alternative embodiment, the IP wrapper module **18** may also be configured to multicast IP protocol SPTS for services not requested by one of the STBs **22a-22n**. It should be noted that the modules **16** and **18** are merely one exemplary embodiment of the satellite gateway **14**. In alternate embodiments, such as the one described below in regard to FIGS. 2 and 3, the functions of the modules **16** and **18** may be redistributed or consolidated amongst a variety of suitable components or modules.

The IP distribution network **20** may include one or more routers, switches, modem, splitters, or bridges. For example, in one embodiment, the satellite gateway **14** may be coupled to a master distribution frame (“MDF”) that is coupled to an intermediate distribution frame (“IDF”) that is coupled to a coax to Ethernet bridge that is coupled to a router that is coupled to one or more of the STBs **22a-22n**. In another embodiment, the IP distribution network **20** may be an MDF that is coupled to a Digital Subscriber Line Access Multiplexer (“DSLAM”) that is coupled to a DSL modem that is coupled to a router. In yet another embodiment, the IP distribution network may include a wireless network, such as

802.11 or WiMax network. In this type of embodiment, the STBs **22a-22n** may include a wireless receiver configured to receive the multicast IP packets. Those of ordinary skill in the art will appreciate that the above-described embodiments are merely exemplary. As such in alternate embodiments, a large number of suitable forms of IP distribution networks may be employed in the system **10**.

The IP distribution network **20** may be coupled to one or more STBs **22a-22n**. The STBs **22a-22n** may be any suitable type of video, audio, and/or other data receiver capable of receiving IP packets, such as the IP SPTS, over the IP distribution network **20**. It will be appreciated the term set top box (“STB”), as used herein, may encompass not only devices that sit upon televisions. Rather the STBs **22a-22n** may be any suitable form of video or audio receiver, whether internal or external to a television, display, or computer, that can be configured to function as described herein—including, but not limited to a video components, computers, wireless telephones, or other forms video recorder. In one embodiment, the STBs **22a-22n** may be a DirecTV receiver configured to receive services, such as video and/or audio, through an Ethernet port (amongst other inputs). In alternate embodiments, the STBs **22a-22n** may be designed and/or configured to receive the multicast transmission over coaxial cable, twisted pair, copper wire, or through the air via a wireless standard, such as the I.E.E.E. 802.11 standard.

As discussed above, the system **10** may receive video, audio, and/or other data transmitted by satellites in space, and process/convert this data for distribution over the IP distribution network **20**. Accordingly, FIG. 2 is another embodiment of the exemplary satellite television over IP system **10** in accordance with one embodiment. FIG. 2 illustrates three exemplary satellite dishes **12a-12c**. Each of the satellite dishes **12a-12c** may be configured to receive signals from one or more of the orbiting satellites. Those of ordinary skill will appreciate that the satellites and the signals that are transmitted from the satellites are often referred to by the orbital slots in which the satellites reside. For example, the satellite dish **12a** is configured to receive signals from a DirecTV satellite disposed in an orbital slot of 101 degrees. Likewise, the satellite dish **12b** receives signals from a satellite disposed at 119 degrees, and the satellite dish **12c** receives signals from a satellite disposed at orbital slot of 110 degrees. It will be appreciated that in alternate embodiments, the satellite dishes **12a-12c** may receive signals from a plurality of other satellites disclosed in a variety of orbital slots, such as the 95 degree orbital slot. In addition, the satellite dishes **12a-12c** may also be configured to receive polarized satellite signals. For example, in FIG. 2, the satellite dish **12a** is configured to receive signals that are both left polarized (illustrated in the figure as “101 L”) and right polarized (illustrated as “101 R”).

As described above in regard to FIG. 1, the satellite dishes **12a-12c** may receive satellite signals in the KU band and convert these signals into L band signals that are transmitted to the satellite gateway **14**. In some embodiments, however, the L band signals produced by the satellite dishes **12a-12c** may be merged into fewer signals or split into more signals prior to reaching the satellite gateway **14**. For example, as illustrated in FIG. 2, L band signals from the satellite dishes **12b** and **12c** may be merged by a switch **24** into a single L band signal containing L band signals from both the satellite at 110 degrees and the satellite at 119 degrees.

As illustrated, the system **10** may also include a plurality of 1:2 splitters **26a**, **26b**, **26c**, and **26d** to divide the L band signals transmitted from the satellite dishes **12a-12c** into two L band signals, each of which include half of the services of

the pre-split L band signal. In alternate embodiments, the 1:2 splitters **26a-26b** may be omitted or integrated into the satellite gateways **14a** and **14b**.

The newly split L band signals may be transmitted from the 1:2 splitters **26a-26d** into the satellite gateways **14a** and **14b**. The embodiment of the system **10** illustrated in FIG. 2 includes two of the satellite gateways **14a** and **14b**. In alternate embodiments, however, the system **10** may include any suitable number of satellite gateways **14**. For example, in one embodiment, the system may include three satellite gateways **14**.

The satellite gateways **14a** and **14b** may then further subdivide the L band signals and then tune to one or more services on the L band signal to produce one or more SPTS that may be repackaged into IP packets and multicast over the IP distribution network **20**. In addition, one or more of the satellite gateways **14a**, **14b** may also be coupled to a public switch telephone network (“PSTN”) **28**. Because the satellite gateways **14a**, **b** are coupled to the PSTN **28**, the STBs **22a-22n** may be able to communicate with a satellite service provider through the IP distribution network **20** and the satellite gateways **14a**, **b**. This functionality may advantageously eliminate the need to have each individual STBs **22a-22n** coupled directly to the PSTN **28**.

The IP distribution network **20** may also be coupled to an internet service provider (“ISP”) **30**. In one embodiment, the IP distribution network **20** may be employed to provide internet services, such as high-speed data access, to the STBs **22a-22n** and/or other suitable devices (not shown) that are coupled to the IP distribution network **20**.

As described above, the satellite gateways **14a**, **b** may be configured to receive the plurality of L band signals, to produce a plurality of SPTS, and to multicast requested SPTS over the IP distribution network **20**. Referring now to FIG. 3, a block diagram of an exemplary satellite gateway **14** is shown. As illustrated, the satellite gateway **14a**, **b** includes a power supply **40**, two front-ends **41a** and **41b** and a back-end **52**. The power supply **40** may be any one of a number of industry-standard AC or DC power supplies configurable to enable the front-ends **41a**, **b** and the back-end **52** to perform the functions described below.

The satellite gateway **14a**, **b** may also include two front-ends **41a**, **b**. In one embodiment, each of the front-ends, **41a**, **b** may be configured to receive two L band signal inputs from the 1:2 splitters **26a-26d** that were described above in regards to FIG. 2. For example, the front-end **41a** may receive two L band signals from the 1:2 splitter **26a** and the front-end **41b** may receive two L band signals from the 1:2 splitter **26b**. In one embodiment, each of the L band inputs into the front-end **41a**, **b** includes eight or fewer services.

The front-ends **41a**, **b** may then further sub-divide the L band inputs using 1:4 L band splitters **42a**, **42b**, **42c**, and **42d**. Once subdivided, the L band signals may pass into four banks **44a**, **44b**, **44c**, and **44d** of dual tuner links. Each of the dual tuner links within the banks **44a-44d** may be configured to tune to two services within the L band signals received by that individual dual tuner links to produce SPTS. Each of the dual tuner links may then transmit the SPTS to one of the low-voltage differential signaling (“LVDS”) drivers **48a**, **48b**, **48c**, and **48d**. The LVDS drivers **48a-48d** may be configured to amplify the transport signals for transmission to the back-end **52**. In alternate embodiments, different forms of differential drivers and/or amplifiers may be employed in place of the LVDS drivers **48a-48d**. Other embodiments may employ serialization of all of the transport signals together for routing to the back end **52**.

As illustrated, the front-ends **41a**, **b** may also include microprocessors **46a** and **46b**. In one embodiment, the microprocessors **46a**, **b** may control and/or relay commands to the banks **44a-44d** of dual tuner links and the 1:4 L band splitters **42a-42d**. The microprocessors **46a**, **b** may comprise ST10 microprocessors produce by ST Microelectronics. The microprocessors **46a**, **b** may be coupled to LVDS receiver and transmitter modules **50a** and **50b**. The LVDS receiver/transmitter modules **50a**, **b** may facilitate communications between the microprocessors **46a**, **b** and components on the back-end **52**, as will be described further below.

Turning next to the back-end **52**, the back-end **52** includes LVDS receivers **54a**, **54b**, **54c**, and **54d**, which are configured to receive transport stream signals transmitted by the LVDS drivers **48a-48d**. The back-end **52** also includes LVDS receiver/transmitter modules **56a** and **56b** which are configured to communicate with the LVDS receiver/transmitter modules **50a**, **b**.

As illustrated, the LVDS receivers **54a-54d** and the LVDS receiver/transmitters **56a**, **b** are configured to communicate with transport processors **58a** and **58b**. In one embodiment, the transport processors **58a**, **b** are configured to receive the SPTS produced by the dual tuner links in the front-ends **41a**, **b**. For example, in one embodiment, the transport processors **58a**, **b** may be configured to produce 16 SPTS. The transport processors **58a**, **b** may be configured to repack the SPTS into IP packets which can be multicast over the IP distribution network **20**. For example, the transport processors **58a**, **b** may repackage DirecTV protocol packets into IP protocol packets and then multicast these IP packets on an IP address to one or more of the STBs **22a-22n**.

The transport processors **58a**, **b** may also be coupled to a bus **62**, such as a 32 bit, 66 MHz peripheral component interconnect (“PCI”) bus. Through the bus **62**, the transport processors **58a**, **b** may communicate with a network processor **70**, an Ethernet interface **84**, and/or an expansion slot **66**. The network processor **70** may be configured to receive requests for services from the STBs **22a-22n** and to direct the transport processors **58a**, **b** to multicast the requested services. In one embodiment, the network processor is an IXP425 network processor produced by Intel. While not illustrated, the network processor **70** may also be configured to transmit status data to a front panel of the satellite gateway **14a**, **b** or to support debugging or monitoring of the satellite gateway **14a**, **b** through debug ports.

As illustrated, the transport processors **58a**, **b** may also be coupled to the Ethernet interface **68** via the bus **62**. In one embodiment, the Ethernet interface **68** is a gigabit Ethernet interface that provides either a copper wire or fiber-optic interface to the IP distribution network **20**. In addition, the bus **62** may also be coupled to an expansion slot, such as a PCI expansion slot to enable the upgrade or expansion of the satellite gateway **14a**, **b**.

The transport processors **58a**, **b** may also be coupled to a host bus **64**. In one embodiment, the host bus **64** is a 16-bit data bus that connects the transport processors **58a**, **b** to a modem **72**, which may be configured to communicate over the PSTN **28**, as described above. In alternate embodiments, the modem **72** may also be coupled to the bus **62**.

As described above, the satellite gateway **14** may transmit the IP packets across the IP distribution network **20** to the STBs **22a-22n**. In one embodiment, the satellite gateway **14** is configured to transmit IP packets using two or more levels of security (e.g., encryption) depending on the capabilities of each of the STBs **22a-22n**. More specifically, the satellite gateway **14** may be configured to multicast satellite services to each one of the STBs **22a-22n** at a security level supported

by that particular STB. For example, if an STB operating at a lower level of security (i.e., less encryption), requests a particular satellite service (CNN, for example), the satellite gateway **14** may generate a multicast of CNN with the IP packets in the multicast encrypted at the lower security level. If, at the same time, another one of the STBs **22a-22n** operating at a higher level of security (i.e., more encryption) also requests to receive CNN, the satellite gateway **14** may generate another multicast of CNN using the higher level of security. In one embodiment, the satellite gateway **14** may be configured to generate three different levels of security: network encryption, network encryption plus partial advanced encryption standard (“AES”), and network encryption plus full AES encryption (128-bit key encryption). In alternate embodiments, however, alternate encryption techniques or security schemes may be employed.

As stated above, the satellite gateway **14** may be configured to generate different multicasts to the STBs **22a-22n** depending on the security capabilities supported by each of the STBs **22a-22n**. In one embodiment, the satellite gateway **14** is configured to request the security capabilities supported by each of the STBs **22a-22n** when that particular STB is coupled (via the IP distribution network **20**) to the satellite gateway **14**. In this embodiment, the satellite gateway **14** may store the security capabilities of each of the STBs **22a-22n** and access these stored security capabilities when one of the STBs **22a-22n** requests satellite services from the satellite gateway **14**. In another embodiment, the satellite gateway **14** may look at the hardware and/or software characteristics of a particular one of the STBs **22a-22n** when that particular STB requests satellite services from the satellite gateway **14**. In yet another embodiment, the satellite gateway **14** may be configured to query the requesting STB **22a-22n** about its security capabilities.

While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms disclosed. Rather, the invention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.

What is claimed is:

1. A method comprising:
  - determining a first level of security supported by a first set top box responsive to a request from the first set top box, the first set top box being a part of a first plurality of set top boxes supporting the first level of security;
  - forming a first multicast directed to at least said first set top box, by encoding data received from a satellite service using the determined first level of security supported by the first set top box, wherein first IP packets of said first multicast contain data from said satellite service that have been encoded using the determined first level of security supported by the first plurality of set top boxes and wherein encoding to form the first multicast is performed after determining the first level of security and continues as further data is received from said satellite service;
  - transmitting the first IP encoded packets to at least the first set top box in the first plurality of set top boxes;
  - determining a second level of security supported by a second set top box responsive to a request from the second set top box, the second set top box being a part of a second plurality of set top boxes supporting the second level of security;

responsive to a determination that the second level of security supported by the second set top box is different from the first level of security supported by the first set top box, forming a second multicast directed to at least said second set top box by encoding data received from said satellite service using the determined second level of security supported by the second set top box, wherein second IP packets of said second multicast contain data from said satellite service that have been encoded using the determined second level of security supported by the second plurality of set top boxes and wherein said encoding to form the second multicast is performed after determining the second level of security supported by the second set top box and continues as further data is received from said satellite service; and

transmitting the second encoded IP packets to at least the second set top box in the second plurality of set top boxes, while the first plurality of set top boxes continues receiving the first multicast containing the first encoded IP packets.

2. The method of claim 1, wherein determining the level of security supported by the second set top box comprises determining that the second set top box supports network encryption.

3. The method of claim 2, wherein determining the level of security supported by the second set top box comprises determining that the second set top box supports partial 128-bit encryption.

4. The method of claim 2, wherein determining the level of security supported by the first set top box comprises determining that the first set top box supports full 128-bit encryption.

5. The method of claim 1, wherein encoding the first IP packet comprising encoding an IP packet containing data from a digital satellite service.

6. A satellite gateway comprising:

- a processor configured to determine a first level of security supported by a first set top box responsive to a request from the first set top box, the first set top box being a part of a first plurality of set top boxes supporting the first level of security, the processor further configured to determine a second level of security supported by a second set top box responsive to a request from the second set top box, the second set top box being a part of a second plurality of set top boxes supporting the second level of security;

- a transport processor configured to form a first multicast directed to at least said first set top box, by encoding data received from a satellite service using the determined first level of security supported by the first set top box, wherein first IP packets of said first multicast contain data from said satellite service that have been encoded using the determined first level of security supported by the first plurality of set top boxes and wherein encoding to form the first multicast is performed after determining the first level of security and continues as further data is received from said satellite service and, responsive to a determination that the second level of security supported by the second set top box is different from the first level of security supported by the first set top box, form a second multicast directed to at least said second set top box by encoding data received from said satellite service using the determined second level of security supported by the second set top box, wherein second IP packets of said second multicast contain data from said satellite service that have been encoded using the determined second level of security supported by the second plural-

9

ity of set top boxes and wherein said encoding to form the second multicast is performed after determining the second level of security supported by the second set top box and continues as further data is received from said satellite service; and

a network interface configured to transmit the first IP encoded packets to at least the first set top box in the first plurality of set top boxes and transmit the second encoded IP packets to at least the second set top box in the second plurality of set top boxes, while the first plurality of set top boxes continues receiving the first multicast containing the first encoded IP packets.

7. The satellite gateway of claim 6, wherein the processor of the satellite gateway is configured to determine if the second set top box supports network encryption.

8. The satellite gateway of claim 6, wherein the processor of the satellite gateway is configured to determine if the second set top box supports partial 128-bit encryption.

9. The satellite gateway of claim 6, wherein the processor of the satellite gateway is configured to determine if the first set top box supports full 128-bit encryption.

10. The satellite gateway of claim 6, wherein the transport processor of the satellite gateway is configured to encode the first IP packet with data from a digital satellite service.

11. A satellite gateway comprising:

processing means for determining a first level of security supported by a first set top box responsive to a request from the first set top box, the first set top box being a part of a first plurality of set top boxes supporting the first level of security;

transport processing means for forming a first multicast directed to at least said first set top box, by encoding data received from a satellite service using the determined first level of security supported by the first set top box, wherein first IP packets of said first multicast contain data from said satellite service that have been encoded using the determined first level of security supported by the first plurality of set top boxes and wherein encoding to form the first multicast is performed after determining the first level of security and continues as further data is received from said satellite service;

10

network interface means for transmitting the first IP encoded packets to at least the first set top box in the first plurality of set top boxes;

processing means for determining a second level of security supported by a second set top box responsive to a request from the second set top box, the second set top box being a part of a second plurality of set top boxes supporting the second level of security;

transport processing means for, responsive to a determination that the second level of security supported by the second set top box is different from the first level of security supported by the first set top box, forming a second multicast directed to at least said second set top box by encoding data received from said satellite service using the determined second level of security supported by the second set top box, wherein second IP packets of said second multicast contain data from said satellite service that have been encoded using the determined second level of security supported by the second plurality of set top boxes and wherein said encoding to form the second multicast is performed after determining the second level of security supported by the second set top box and continues as further data is received from said satellite service; and

network interface means for transmitting the second encoded IP packets to at least the second set top box in the second plurality of set top boxes, while the first plurality of set top boxes continues receiving the first multicast containing the first encoded IP packets.

12. The satellite gateway of claim 11 wherein determining the level of security supported by the second set top box comprises determining that the second set top box supports network encryption.

13. The satellite gateway of claim 11 wherein determining the level of security supported by the second set top box comprises determining that the second set top box supports partial 128-bit encryption.

14. The satellite gateway of claim 11 wherein determining a level of security supported by the first set top box comprises determining that the first set top box supports full 128-bit encryption.

\* \* \* \* \*