



US010938220B2

(12) **United States Patent**
Singh et al.

(10) **Patent No.:** **US 10,938,220 B2**

(45) **Date of Patent:** ***Mar. 2, 2021**

(54) **WIRELESS CONNECTOR SYSTEM**

(71) Applicant: **NuCurrent, Inc.**, Chicago, IL (US)

(72) Inventors: **Vinit Singh**, Austin, TX (US); **Pavel Shostak**, Chicago, IL (US); **Alberto Peralta**, Chicago, IL (US); **Jason Luzinski**, Chicago, IL (US); **Jacob D. Babcock**, Chicago, IL (US); **Michael Gotlieb**, Chicago, IL (US); **Glenn E Riese**, McHenry, IL (US); **Md. Nazmul Alam**, Lombard, IL (US); **Robert Giometti**, Buffalo Grove, IL (US); **Oleg Los**, Buffalo Grove, IL (US); **Unnati Wadkar**, Chicago, IL (US); **Mark Melone**, Chicago, IL (US)

(73) Assignee: **NuCurrent, Inc.**, Chicago, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 358 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/686,920**

(22) Filed: **Aug. 25, 2017**

(65) **Prior Publication Data**

US 2018/0062397 A1 Mar. 1, 2018

Related U.S. Application Data

(60) Provisional application No. 62/379,940, filed on Aug. 26, 2016.

(51) **Int. Cl.**
H02J 5/00 (2016.01)
H01F 38/14 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H02J 5/005** (2013.01); **H01F 38/14** (2013.01); **H01Q 1/38** (2013.01); **H01Q 1/42** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC G06F 11/1092; G06F 11/3409; G06F 11/3034; G06F 16/10; G06F 11/1458;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,911,605 A 11/1953 Wales, Jr.
2,797,393 A 6/1957 Clogston
(Continued)

FOREIGN PATENT DOCUMENTS

CN 2650300 10/2004
CN 201150058 Y 11/2008
(Continued)

OTHER PUBLICATIONS

Office Action dated Mar. 30, 2018 in corresponding CN Application No. 201310074946.8 (10 pages).
(Continued)


Primary Examiner — Pinping Sun

(74) *Attorney, Agent, or Firm* — Lee Sullivan Shea & Smith LLP

(57) **ABSTRACT**

Various embodiments of a wireless connector system are described. The system has a transmitter module and a receiver module that are configured to wirelessly transmit electrical energy and/or data via near field magnetic coupling. The wireless connector system is designed to increase the amount of wirelessly transmitted electrical power over a greater separation distance. The system is configured with various sensing circuits that alert the system to the presence of the receiver module to begin transfer of electrical power as well as undesirable objects and increased temperature that could interfere with the operation of the system. The wireless connector system is a relatively small foot print that is designed to be surface mounted.

27 Claims, 37 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,860,545	B2	10/2014	Singh et al.		2008/0164840	A1	7/2008	Kato et al.
8,892,034	B2	11/2014	McGuire et al.		2008/0164844	A1	7/2008	Kato et al.
8,898,885	B2	12/2014	Singh et al.		2008/0164960	A1	7/2008	Schnell et al.
8,901,880	B2*	12/2014	Cook	H02J 50/50 320/108	2008/0169910	A1	7/2008	Greene et al.
8,901,881	B2	12/2014	Partovi		2008/0205495	A1	8/2008	Trott
8,933,589	B2	1/2015	Bourilkov et al.		2008/0211320	A1	9/2008	Cook et al.
9,124,316	B2	9/2015	Langer		2008/0277386	A1	11/2008	Haimer
9,178,361	B2	11/2015	Liu et al.		2008/0278399	A1	11/2008	Nakajima et al.
9,178,369	B2	11/2015	Partovi		2008/0283277	A1	11/2008	Muramatsu et al.
9,196,958	B2	11/2015	Arnold et al.		2008/0303735	A1*	12/2008	Fujimoto H01Q 1/22 343/787
9,208,942	B2	12/2015	Singh et al.		2009/0015266	A1	1/2009	Narita et al.
9,209,636	B2	12/2015	Yoda et al.		2009/0058189	A1	3/2009	Cook et al.
9,230,732	B2	1/2016	Muratov et al.		2009/0079387	A1	3/2009	Jin et al.
9,231,412	B2	1/2016	Lisi et al.		2009/0079628	A1	3/2009	Rofougaran
9,252,846	B2	2/2016	Lee et al.		2009/0085706	A1	4/2009	Baarman et al.
9,252,876	B2	2/2016	Fischer et al.		2009/0096413	A1	4/2009	Partovi et al.
9,318,897	B2	4/2016	Brohlin et al.		2009/0108974	A1	4/2009	Raggam et al.
9,425,653	B2	8/2016	Cook et al.		2009/0134875	A1	5/2009	Tomiha et al.
9,432,090	B2*	8/2016	Wang	H04B 5/0037	2009/0140691	A1	6/2009	Jung
9,515,633	B1	12/2016	Long et al.		2009/0152542	A1	6/2009	Lee et al.
9,525,311	B2*	12/2016	Menegoli	H02J 50/15	2009/0197435	A1	8/2009	Jessup et al.
9,559,526	B2	1/2017	Von Novak, III et al.		2009/0230777	A1	9/2009	Baarman et al.
9,866,040	B2	1/2018	Kato		2009/0261778	A1*	10/2009	Kook H04B 5/0037 320/108
9,912,173	B2	3/2018	Tseng		2009/0261936	A1	10/2009	Widjaja et al.
9,912,174	B2	3/2018	Soar		2009/0271048	A1*	10/2009	Wakamatsu H02J 5/005 700/296
10,283,995	B2*	5/2019	Gunderson	H02J 50/90	2010/0007215	A1	1/2010	Sakuma
2002/0020554	A1	2/2002	Sakamoto et al.		2010/0033290	A1	2/2010	Liu
2002/0053992	A1	5/2002	Kawakami et al.		2010/0072588	A1	3/2010	Yang
2002/0071003	A1	6/2002	Kimura		2010/0127660	A1	5/2010	Cook et al.
2002/0075191	A1	6/2002	Yokoshima		2010/0141042	A1	6/2010	Kesler
2002/0101383	A1	8/2002	Junod		2010/0144308	A1	6/2010	Jin et al.
2002/0105080	A1	8/2002	Speakman		2010/0164296	A1	7/2010	Kurs et al.
2003/0006069	A1	1/2003	Watanabe		2010/0201310	A1	8/2010	Vorenkamp et al.
2003/0058180	A1	3/2003	Forster		2010/0219694	A1	9/2010	Kurs et al.
2003/0119677	A1	6/2003	Qiyian et al.		2010/0289599	A1	11/2010	Vangala
2003/0142929	A1	7/2003	Bartur et al.		2010/0289709	A1	11/2010	Guan
2003/0146875	A1	8/2003	Kirino		2010/0295701	A1	11/2010	Denis
2004/0000974	A1	1/2004	Ordenaal et al.		2011/0084656	A1	4/2011	Gao
2004/0085247	A1	5/2004	Mickle et al.		2011/0101788	A1	5/2011	Sun et al.
2004/0108311	A1	6/2004	de Rooij		2011/0127951	A1	6/2011	Walley et al.
2004/0118920	A1	6/2004	He		2011/0137379	A1	6/2011	Wosmek
2004/0140528	A1	7/2004	Kim et al.		2011/0181484	A1	7/2011	Pettus et al.
2004/0159460	A1	8/2004	Passiopoulos et al.		2011/0205315	A1*	8/2011	Saga B41J 2/17513 347/85
2004/0189528	A1	9/2004	Killen et al.		2011/0212691	A1	9/2011	Rott et al.
2004/0196605	A1	10/2004	Dinn et al.		2011/0024510	A1	10/2011	Kato et al.
2004/0217488	A1	11/2004	Luechinger		2011/0241437	A1	10/2011	Kanno
2004/0227608	A1	11/2004	Nakatani et al.		2011/0248891	A1	10/2011	Han et al.
2005/0043638	A1	2/2005	Chen		2011/0279198	A1	11/2011	Haner
2005/0121229	A1	6/2005	Takai et al.		2011/0291613	A1	12/2011	Rosik et al.
2005/0174628	A1	8/2005	Kelly et al.		2012/0038317	A1	2/2012	Miyamoto et al.
2005/0269693	A1*	12/2005	Green	H05K 3/366 257/723	2012/0062345	A1	3/2012	Kurs et al.
2006/0022772	A1	2/2006	Kanno et al.		2012/0095531	A1	4/2012	Derbas et al.
2006/0040628	A1	2/2006	Porret		2012/0169434	A1	7/2012	Masuda et al.
2006/0192645	A1	8/2006	Lee et al.		2012/0170337	A1	7/2012	Lisi et al.
2006/0284718	A1	12/2006	Baumgartner et al.		2012/0217819	A1	8/2012	Yamakawa et al.
2007/0018767	A1	1/2007	Gabara		2012/0223589	A1	9/2012	Low et al.
2007/0020969	A1	1/2007	Yungers		2012/0223590	A1	9/2012	Low et al.
2007/0023424	A1	2/2007	Weber		2012/0235500	A1	9/2012	Ganem et al.
2007/0045773	A1	3/2007	Mi et al.		2012/0235634	A1	9/2012	Hall et al.
2007/0046544	A1	3/2007	Murofushi et al.		2012/0235636	A1	9/2012	Partovi
2007/0080810	A1	4/2007	Juds		2012/0248887	A1	10/2012	Kesler et al.
2007/0095913	A1	5/2007	Takahashi et al.		2012/0249396	A1	10/2012	Parsche
2007/0120629	A1	5/2007	Schnell et al.		2012/0256494	A1	10/2012	Kesler et al.
2007/0139275	A1	6/2007	Deaett et al.		2012/0262109	A1*	10/2012	Toya H01M 10/44 320/108
2007/0179570	A1	8/2007	De Taboada		2012/0274148	A1*	11/2012	Sung H04B 5/0037 307/104
2007/0182367	A1	8/2007	Partovi		2012/0280765	A1	11/2012	Kurs et al.
2007/0267718	A1	11/2007	Lee		2012/0293011	A1	11/2012	Byun et al.
2007/0279287	A1	12/2007	Castaneda		2012/0305792	A1	12/2012	Kuwabara et al.
2008/0039332	A1	2/2008	Bernstein et al.		2012/0313579	A1*	12/2012	Matsumoto H02J 50/12 320/108
2008/0055178	A1	3/2008	Kim		2012/0315772	A1	12/2012	Joschika
2008/0062066	A1	3/2008	Arai		2012/0323512	A1	12/2012	Rhodin
2008/0067874	A1	3/2008	Tseng		2012/0326524	A1	12/2012	Matsumoto et al.
2008/0150693	A1	6/2008	You					

(56)	References Cited						
	U.S. PATENT DOCUMENTS			2015/0070190	A1*	3/2015	Wai Fong G01J 1/4204 340/870.3
				2015/0076922	A1	3/2015	Kato et al.
				2015/0091502	A1	4/2015	Mukherjee et al.
				2015/0115727	A1	4/2015	Carobolante et al.
				2015/0136858	A1	5/2015	Finn
				2015/0137746	A1	5/2015	Lee et al.
				2015/0140807	A1	5/2015	Mohammed
				2015/0145634	A1	5/2015	Kurz
				2015/0145635	A1	5/2015	Kurz et al.
				2015/0180440	A1	6/2015	Ishizuka
				2015/0200445	A1	7/2015	Murphy
				2015/0207541	A1*	7/2015	Kuroda H05K 1/0239 455/41.1
				2015/0234035	A1	8/2015	Lohoefer et al.
				2015/0236545	A1	8/2015	Song
				2015/0236550	A1	8/2015	Yang et al.
				2015/0249359	A1	9/2015	Gunderson
				2015/0255994	A1	9/2015	Kesler et al.
				2015/0280322	A1	10/2015	Saito
				2015/0290379	A1*	10/2015	Rudser A61N 1/37229 600/16
				2015/0318710	A1	11/2015	Lee et al.
				2015/0349110	A1	12/2015	Kocon
				2015/0349541	A1	12/2015	Yamamoto et al.
				2015/0351292	A1*	12/2015	Chang H01Q 1/526 361/749
				2015/0357827	A1	12/2015	Muratov et al.
				2015/0372493	A1	12/2015	Sankar
				2016/0001663	A1	1/2016	Chae et al.
				2016/0013565	A1	1/2016	Ortiz
				2016/0028265	A1	1/2016	Bell et al.
				2016/0036244	A1*	2/2016	Griffith A61F 2/54 307/104
				2016/0049826	A1	2/2016	Lee et al.
				2016/0056639	A1	2/2016	Mao
				2016/0056664	A1	2/2016	Partovi
				2016/0064952	A1	3/2016	Matsumoto et al.
				2016/0072306	A1	3/2016	Tsuda et al.
				2016/0105963	A1*	4/2016	Isom H01Q 1/50 343/906
				2016/0111889	A1	4/2016	Jeong
				2016/0118711	A1	4/2016	Finn
				2016/0126002	A1	5/2016	Chien et al.
				2016/0149416	A1	5/2016	Ha et al.
				2016/0156103	A1	6/2016	Bae
				2016/0156215	A1	6/2016	Bae
				2016/0165323	A1	6/2016	Hollis
				2016/0183034	A1	6/2016	Konanur et al.
				2016/0183056	A1	6/2016	Leabman
				2016/0197513	A1	7/2016	Uchimoto et al.
				2016/0224975	A1	8/2016	Na
				2016/0254679	A1	9/2016	Liu et al.
				2016/0264007	A1*	9/2016	Haase B60L 53/38
				2016/0285321	A1	9/2016	Akuzawa et al.
				2016/0325105	A1*	11/2016	Etzkorn A61N 1/37211
				2016/0330823	A1	11/2016	Hwa et al.
				2017/0025900	A1	1/2017	Amari et al.
				2017/0033610	A1	2/2017	Borin
				2017/0033613	A1	2/2017	Takahashi
				2017/0040846	A1	2/2017	Sankar
				2017/0070249	A1	3/2017	Irish et al.
				2017/0093198	A1*	3/2017	Graham H01F 38/14
				2017/0093222	A1*	3/2017	Joye H04B 5/0087
				2017/0111243	A1*	4/2017	Bell H04W 24/08
				2017/0117755	A1	4/2017	Muratov et al.
				2017/0126069	A1	5/2017	Martin
				2017/0126544	A1	5/2017	Vigneras et al.
				2017/0222466	A1	8/2017	Sankar
				2017/0240007	A1	8/2017	Chuang
				2017/0256956	A1	9/2017	Irish et al.
				2017/0346343	A1	11/2017	Atasoy et al.
				2017/0357338	A1	12/2017	Bell
				2017/0372837	A1	12/2017	Lee et al.
				2018/0013307	A1	1/2018	Pudipeddi
				2018/0043861	A1	2/2018	Kosugi
				2018/0054090	A1	2/2018	Von Novak, III
				2018/0062433	A1	3/2018	Singh et al.
				2018/0062436	A1	3/2018	Singh et al.
				2012/0326931	A1	12/2012	Murayama et al.
				2013/0015718	A1*	1/2013	Jung H04B 5/0087 307/104
				2013/0067737	A1	3/2013	Singh
				2013/0067738	A1	3/2013	Singh
				2013/0068499	A1	3/2013	Singh et al.
				2013/0068507	A1	3/2013	Singh et al.
				2013/0069748	A1*	3/2013	Singh H01F 38/14 336/115
				2013/0069749	A1	3/2013	Singh
				2013/0069750	A1	3/2013	Singh
				2013/0069843	A1	3/2013	Singh et al.
				2013/0076154	A1	3/2013	Baarman et al.
				2013/0093629	A1	4/2013	Chiu et al.
				2013/0099734	A1	4/2013	Lee et al.
				2013/0101133	A1	4/2013	Yoon et al.
				2013/0140900	A1	6/2013	Yu et al.
				2013/0146671	A1	6/2013	Grieshofer et al.
				2013/0147427	A1*	6/2013	Polu B60L 53/36 320/108
				2013/0154557	A1	6/2013	Lee et al.
				2013/0169060	A1	7/2013	Jung et al.
				2013/0181535	A1	7/2013	Muratov et al.
				2013/0199027	A1	8/2013	Singh et al.
				2013/0199028	A1	8/2013	Singh et al.
				2013/0200070	A1	8/2013	Singh
				2013/0200722	A1	8/2013	Singh
				2013/0200968	A1	8/2013	Singh
				2013/0200969	A1	8/2013	Singh et al.
				2013/0200976	A1	8/2013	Singh
				2013/0201589	A1	8/2013	Singh
				2013/0205582	A1	8/2013	Singh
				2013/0207744	A1	8/2013	Singh
				2013/0208389	A1	8/2013	Singh
				2013/0208390	A1	8/2013	Singh
				2013/0234899	A1	9/2013	Pope et al.
				2013/0257362	A1	10/2013	Lim et al.
				2013/0257670	A1	10/2013	Sovero et al.
				2013/0285605	A1	10/2013	Partovi
				2013/0293028	A1*	11/2013	Byun H01F 38/14 307/104
				2013/0300207	A1	11/2013	Wang
				2013/0335284	A1	12/2013	Hsu et al.
				2014/0008974	A1	1/2014	Miyamoto
				2014/0009110	A1	1/2014	Lee et al.
				2014/0015330	A1	1/2014	Byun et al.
				2014/0028111	A1	1/2014	Hansen
				2014/0035383	A1	2/2014	Riehl
				2014/0035793	A1	2/2014	Kato
				2014/0041218	A1	2/2014	Singh et al.
				2014/0047713	A1	2/2014	Singh et al.
				2014/0084946	A1	3/2014	Clark et al.
				2014/0162554	A1	6/2014	Sankar et al.
				2014/0168019	A1	6/2014	Hirobe
				2014/0183971	A1	7/2014	Endo
				2014/0184334	A1	7/2014	Nobbe et al.
				2014/0197694	A1	7/2014	Asanuma et al.
				2014/0203661	A1	7/2014	Dayan et al.
				2014/0226795	A1*	8/2014	Kitano A61B 6/4283 378/189
				2014/0231518	A1	8/2014	Yosui
				2014/0253052	A1*	9/2014	Goma H02J 50/05 320/166
				2014/0266019	A1	9/2014	Pigott
				2014/0266624	A1	9/2014	Van Bosch et al.
				2014/0302782	A1*	10/2014	Raab H02J 50/80 455/41.1
				2014/0306548	A1*	10/2014	Yang H02J 7/025 307/104
				2014/0312242	A1	10/2014	Valentino et al.
				2014/0319921	A1	10/2014	Lisi et al.
				2014/0361628	A1	12/2014	Keeling
				2015/0054455	A1	2/2015	Kim et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2018/0062438	A1*	3/2018	Singh	H01F 38/14
2018/0062439	A1	3/2018	Singh et al.		
2018/0062704	A1	3/2018	Singh et al.		
2018/0083669	A1	3/2018	Jeong et al.		
2018/0131231	A1	5/2018	Nakano et al.		
2018/0166921	A1	6/2018	Peralta		
2018/0167107	A1	6/2018	Peralta		
2018/0167108	A1	6/2018	Peralta		
2018/0167109	A1	6/2018	Peralta		
2018/0167110	A1	6/2018	Peralta		
2018/0168057	A1	6/2018	Peralta		
2018/0212649	A1	7/2018	Tenno		
2018/0219428	A1	8/2018	Bae		
2018/0315968	A1	11/2018	Koyama et al.		
2018/0339599	A1	11/2018	Iwamoto et al.		
2019/0027969	A1*	1/2019	Staring	H01F 27/28
2019/0052116	A1	2/2019	Bae		
2019/0140699	A1*	5/2019	Park	H02J 50/10
2019/0154448	A1*	5/2019	Cao	H02J 50/10
2019/0222060	A1*	7/2019	Leem	H02J 50/10
2019/0363545	A1	11/2019	Lee et al.		

FOREIGN PATENT DOCUMENTS

CN	203396791	U *	1/2014		
CN	103944196		7/2014		
CN	104037493	A	9/2014		
CN	104037494	A	9/2014		
EP	0310396		4/1989		
EP	0972268	B1 *	5/2002	G06K 19/07749
EP	1609503		12/2005		
EP	2031729		3/2009		
EP	2420953	A1	2/2012		
EP	2557630		2/2013		
EP	2775564	A1	9/2014		
EP	2775565	A1	9/2014		
JP	1-310518		12/1989		
JP	5-83249		4/1993		
JP	H0583249	A	4/1993		
JP	H08237021	A	9/1996		
JP	09-093005		4/1997		
JP	10-255629		9/1998		
JP	2007-7042569		2/2007		
JP	2008-160781		7/2008		
JP	2008-205215		9/2008		
JP	2008-307114		12/2008		
JP	2008-924285		12/2008		
JP	4329932	B2	9/2009		
JP	2001344574		12/2011		
JP	2012-147408		8/2012		
JP	2013-93429		5/2013		
JP	2014-175864	A	9/2014		
JP	2014-175865	A	9/2014		
KR	10-1216946	B1	1/2013		
KR	10-2013-0015618		2/2013		
KR	10-2014-0111554	A	9/2014		
KR	10-2014-0111794	A	9/2014		
KR	2014-0135357		11/2014		
KR	10-1559939	B1	10/2015		
KR	10-2010-0092741		8/2018		
TW	201436494	A	9/2014		
TW	2014436495	A	9/2014		
TW	1478461	B	3/2015		
WO	2008/050917		5/2008		
WO	WO 2010/104569		9/2010		
WO	2010/129369		11/2010		
WO	WO -2012132242	A1 *	10/2012		
WO	2014014425	A1	1/2014		
WO	2015158500	A1	10/2015		

OTHER PUBLICATIONS

Office Action dated Mar. 27, 2018 in corresponding CN Application No. 201310075086.X (10 pages).

Office Action issued in corresponding Japanese Patent Application No. 2013-047048 dated May 8, 2018 (2 pages).

Decision of Dismissal of Amendment issued in corresponding Japanese Patent Application No. 2013-047048 dated May 8, 2018 (7 pages).

Office Action issued Apr. 27, 2018 in corresponding TW Application No. 102108345 (11 pages).

Office Action dated Nov. 28, 2017 in corresponding JP Application No. 2013-047049 (5 pages).

Office Action dated Aug. 25, 2017 in corresponding CN Application No. 201310075086.X (10 pages).

Office Action dated Aug. 23, 2017 in corresponding CN Application No. 201310074946.8 (10 pages).

Office Action dated Sep. 12, 2018 in corresponding CN Application No. 201310074946.8 (9 pages).

Office Action dated Sep. 12, 2018 in corresponding CN Application No. 201310075086.X (10 pages).

Office Action dated Oct. 29, 2018 in corresponding KR Application No. 10-2013-0026135 (12 pages).

Office Action dated Oct. 29, 2018 in corresponding KR Application No. 10-2013-0025858 (12 pages).

Written Opinion and International Search Report issued in corresponding International Application No. PCT/US2017/065329 dated Feb. 21, 2018 (7 pages).

Office Action issued in corresponding Japanese Patent Application No. 2013-047048 dated Dec. 12, 2017 (11 pages).

International Search Report and Written Opinion issued in PCT/US2017/048708 dated Nov. 8, 2017 (10 pages).

EP Office Communication Pursuant to Article 94(3) dated Jan. 17, 2019 for EP App. No. 13001121.6-1216.

EP Communication pursuant to Rule 164(1) EPC regarding partial supplementary European Search Report for EP App. No. 16835665.7-1212 dated Feb. 14, 2019, 20 pages.

Muratov, V., Multi-Mode Wireless Power Systems can be a bridge to the Promised Land of Universal Contactless charging, Mediatek, Inc., Nov. 20, 2014, 15 pages.

Qi 2010, "System Description Wireless Power Transfer", vol. 1, Low Power, Part 1: Interface Definition, Version 1.0.1, Oct. 2010, Wireless Power Consortium, 86 pages.

Narayanan, R., "Wireless Power Charging Coil Changing Considerations", Wurth Elektronik, Feb. 23, 2015, 9 pages.

Barcelo, T., "Wireless Power User Guide", Linear Technology, Application Note 138, Oct. 2013, 8 pages.

Yoon, Y., "Embedded conductor technology for micromachined RF elements", Journal of Micromechanics and Microengineering, Jun. 2005, 11 pages.

Burghartz, J., "On the Design of RF Spiral Inductors on Silicon", IEEE Transactions on Electron Devices, vol. 50, No. 3, Mar. 2003, pp. 718-729.

Qi 2009, "System Description Wireless Power Transfer", vol. 1, Low Power, Version 0.95, Jul. 2009, 76 pages.

Lee, Y., "Antenna Circuit Design for RFID Applications", 2003 Microchip Technology, AN710, 50 pages.

Sun, M., et al., "Apparatus for Wireless Power and Data Transfer Over a Distance", University of Pittsburgh, Jun. 2009, 30 pages.

IPR2019-00858—Petition for Inter Partes Review of U.S. Pat. No. 8,680,960, *Samsung Electronics Co., Ltd. v. NuCurrent, Inc.*, 90 pages.

IPR2019-00858—Ex. 1001 U.S. Pat. No. 8,680,960.

IPR2019-00858—Ex 1004—File History for U.S. Pat. No. 8,680,960. Ex. 1002 Declaration of Dr. Steven Leeb, 115 pages.

Ex. 1003—CV of Dr. Steven B. Leeb, 7 pages.

Ex. 1005—US20070267718A1 to Lee, 13 pages.

Ex. 1006—Semat—Physics Chapters 29-32, 81 pages, (1958).

Ex 1009—US20090096413 to Partovi, 88 pages.

Ex 1010—IEEE Dictionary 1996 (excerpt), 9 pages.

Ex. 1011—US20070089773A1 to Koester et al., 26 pages.

Ex. 1012—US20120280765 to Kurs, 122 pages.

Ex. 1013—U.S. Pat. No. 6,432,497 to Bunyan, 12 pages.

Ex. 1014 U.S. Pat. No. 6,083,842 to Cheung et al., 8 pages.

Ex. 1015 Reinhold—Efficient Antenna Design of Inductive Coupled RFID—Systems with High Power Demand, Journal of Communication vol. 2, No. 6, Nov. 2007, 10 pages.

(56)

References Cited

OTHER PUBLICATIONS

- Ex. 1016 U.S. Pat. No. 4,549,042 to Akiba et al., 8 pages.
- Ex. 1017—U.S. Pat. No. 5,812,344 to Balakrishnan, 12 pages.
- Ex. 1018—Wheeler, *Formulas for the Skin* (1942), 13 pages.
- Ex. 1019—Kyriazidou—7236080, 12 pages.
- Ex. 1020 Alldred et al., “A 1.2 V, 60 Ghz radio receiver with onchip transformers and inductors in 90 nm CMOS,” *Proc. IEEE Compound Semiconductor Integrated Circuits SYmp.*, pp. 51-54, Nov. 2006 (“Alldred”), 12 pages.
- Ex. 1022 U.S. Pat. No. 9,912,173 to Tseng, 31 pages.
- Ex. 1023 U.S. Pat. No. 7,248,138 to Chiang, 18 pages.
- Ex. 1024 U.S. Pat. No. 5,084,958 to Yerman et al., 20 pages.
- Ex. 1025—US20070126544—Wotherspoon, 6 pages.
- Ex. 1028—U.S. Pat. No. 9,820,374 to Bois et al., 9 pages.
- Ex. 1029 U.S. Pat. No. 7,601,919 to Phan et al., 14 pages.
- Ex. 1030 U.S. Pat. No. 5,108,825 to Wojnarowski et al., 10 pages.
- Ex. 1031 Ahn 7305725, 9 pages.
- Ex. 1032—U.S. Pat. No. 5,745,331 to Shamouilian et al., 23 pages.
- Ex. 1033—Hu, et al., “AC Resistance to Planar Power Inductors and the Quasidistributed Gap Technique,” *IEEE Transactions on Power Electronics*, vol. 16, No. 4, Jul. 2001 (“Hu”), 13 pages.
- Ex. 1034—U.S. Pat. No. 6,608,363 to Fazelpour, 8 pages.
- Ex. 1035—IEEE Xplore web page, 2 pages.
- Ex. 1036 Kraemer et al., “Architecture Considerations for 60 GhzPulse Transceiver Front-Ends,” *CAS 2007 Proceedings* vol. 2, 2007, Int’l Semiconductor Conference (2007), 26 pages.
- Ex. 1037—Varonen et al., “V-band Balanced Resistive Mixer in 65-nm CMOS,” *Proceedings of the 33rd European Solid-State Circuits Conference* (2007), 22 pages.
- Ex. 1038—IEEE Xplore web page, 2 pages.
- Ex. 1039—Lopera et al., “A Multiwinding Modeling Method for High Frequency Transformers and Inductors”, *IEEE Transactions on Power Electronics*, vol. 18, No. 3, May 2003, 14 pages.
- Ex. 1040—Leonavicius et al., “Comparison of Realization Techniques for PFC Inductor Operating in Discontinuous Conduction Mode,” *IEEE Transactions on Power Electronics*, vol. 19, No. 2, Mar. 2004, 14 pages.
- Ex. 1041—Roshen, W.A., “Fringing Field Formulas and Winding Loss Due to an Air Gap,” *IEEE Transactions on Magnetics*, vol. 43, No. 8, Aug. 2007, 12 pages.
- IPR2019-00859—Petition for Inter Partes Review of U.S. Pat. No. 9,300,046, 87 pages.
- Ex. 1001 U.S. Pat. No. 9,300,046 to Singh et al., 50 pages.
- Ex. 1004—Prosecution History of U.S. Pat. No. 9,300,046, 322 pages (in two attachments A and B) due to size.
- IPR2019-00860—Petition for Inter Partes Review of U.S. Pat. No. 8,680,960, 86 pages.
- Ex. 1001—U.S. Pat. No. 8,680,960 to Singh et al., 50 pages.
- Ex. 1004—File History for U.S. Pat. No. 8,680,960, 201 pages. (in two attachments due to size).
- IPR2019-00861—Petition for Inter Partes Review of U.S. Pat. No. 9,300,046, 89 pages.
- IPR2019-00862—Petition for Inter Partes Review of U.S. Pat. No. 8,710,948, 88 pages.
- Ex. 1001 U.S. Pat. No. 8,710,948 to Singh et al., 50 pages.
- Ex. 1004 File History of U.S. Pat. No. 8,710,948 to Singh et al., 213 pages.
- IPR2019-0863 Petition for Inter Partes Review of U.S. Pat. No. 8,698,591, 89 pages.
- Ex. 1001 U.S. Pat. No. 8,698,591, 49 pages.
- Ex. 1004—Prosecution History of U.S. Pat. No. 8,698,591, 180 pages.
- EP Communication pursuant to Rule 62 EPC regarding extended European Search Report for EP App. No. 16835665.7-1212 dated May 15, 2019, 16 pages.
- Notification of Decision of Rejection for KR App. No. 10-2013-0025858 dated May 14, 2019, with English Translation, 8 pages.
- Notification of Decision of Rejection for KR 10-2013-0026135 dated May 14, 2019, 8 pages with translation.
- EP Communication of extended European Search Report for EP 19154162.2 dated Jun. 12, 2019, 9 pages.
- European Search Report dated Aug. 1, 2013 for EP Appln. No. 13001121.6 (6 pages).
- European Search Report dated Aug. 1, 2013 for EP Appln. No. 13001130.7 (6 pages).
- European Search Report dated Aug. 7, 2014 for EP Appln. No. 10751119.8 (12 pages).
- European Search Report dated Nov. 4, 2014 for EP Appln. No. 14000885.5 (8 pages).
- Office Action dated Sep. 27, 2016 in corresponding EP Appln. No. 13.001 121.6 (6 pages).
- Office Action dated Sep. 27, 2016 in corresponding EP Appln. No. 13.001 130.7 (6 pages).
- Office Action dated Jan. 31, 2017 in corresponding JP Appln. No. 2013-047049 (5 pages).
- Office Action dated Jun. 29, 2017 in corresponding EP Appln. No. 1400885.5 (4 pages).
- Office Action dated Feb. 21, 2017 in corresponding TW Appln. No. 102108342 (10 pages).
- Office Action dated Mar. 21, 2017 in corresponding JP Appln. 2013-047048 (12 pages).
- International Search Report and Written Opinion dated Oct. 14, 2016 for PCT/US2016/045588 (10 pages).
- International Search Report and Written Opinion dated Oct. 28, 2016 for PCT/US2016/047607 (9 pages).
- Relative Permittivity—Dielectric Constant—Jul. 2011 (3 pages).
- First Office Action for Chinese App. No. 201680058731.9 dated Aug. 5, 2019, English Translation, 6 pages.
- Extended Search Report for EP 19188841.1-1216 dated Sep. 10, 2019, 11 pages.
- Exhibit A-01: Invalidity Contentions: ‘960 Patent in View Jitsuo, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.), Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) By Japanese Patent Application Publication JP05082349A (“Jitsuo”), 56 pages.
- Exhibit A-02: Invalidity Contentions: ‘960 Patent in View of Kurs ‘694, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2010/0219694 A1 (“Kurs ‘694”), 59 pages.
- Exhibit A-03: Invalidity Contentions: ‘960 Patent in View of Sheng-Yuan, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2007/267718 A1 (“Sheng-Yuan”). 86 pages.
- Exhibit A-04: Invalidity Contentions: ‘960 Patent in View of Wotherspoon, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2007/0126544 A1 (“Wotherspoon”), 51 pages.
- Exhibit A-05: Invalidity Contentions: ‘960 Patent in View of Baarman ‘777, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2009/0230777A1 (“Baarman ‘777”), 50 pages.
- Exhibit A-06: Invalidity Contentions: ‘960 Patent in View of Bae, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Pat. No. 6,897,830 B2 (“Bae”), 80 pages.
- Exhibit A-07: Invalidity Contentions: ‘960 Patent in View of Ganem, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2012/0235500 A1 (“Steven J. Ganem”), 82 pages.
- Exhibit A-08: Invalidity Contentions: ‘960 Patent in View of Gao, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2011/084656 A1 (“Gao”), 39 pages.
- Exhibit A-09: Invalidity Contentions: ‘960 Patent in View of Burghartz & Rejaei, *NuCurrent v. Samsung Electronics America,*

(56)

References Cited

OTHER PUBLICATIONS

- Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by On the Design of RF Spiral Inductors on Silicon (“Burghartz & Rejaei”), 53 pages.
- Exhibit A-10: Invalidation Contentions: ‘960 Patent in View of Hasegawa ‘215, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Japanese Patent Application Publication 2008-205215 A (“Hasegawa Minoru”), 46 pages.
- Exhibit A-11: Invalidation Contentions: ‘960 Patent in View of Hasegawa ‘518, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by J.P. Patent Application Publication 01310518 A (“Hasegawa Michio ‘518”), 82 pages.
- Exhibit A-12: Invalidation Contentions: ‘960 Patent in View of Hasegawa Michio ‘631, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Pat. No. 4,959,631 A (“Hasegawa Michio ‘631”), 43 pages.
- Exhibit A-13: Invalidation Contentions: ‘960 Patent in View of Ishihara, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by JP Patent Application Publication 2008/294285 A (“Ishihara Keien”), 37 pages.
- Exhibit A-14: Invalidation Contentions: ‘960 Patent in View of Kato, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2008/164840 A1 (“Hiroshi Kato”), 35 pages.
- Exhibit A-15: Invalidation Contentions: ‘960 Patent in View of Kato, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2008/164844 A1 (“Hiroshi Kato”), 40 pages.
- Exhibit A-16: Invalidation Contentions: ‘960 Patent in View of Kimura, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2002/071003 A1 (“Isao Kimura”), 59 pages.
- Exhibit A-17: Invalidation Contentions: ‘960 Patent in View of Kurs ‘765, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2012/0280765 A1 (“Kurs ‘765”), 57 pages.
- Exhibit A-18: Invalidation Contentions: ‘960 Patent in View of Misumi, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Japanese Patent Application Publication JP 10255629 A (“Misumi Shuichi”), 37 pages.
- Exhibit A-19: Invalidation Contentions: ‘960 Patent in View of Nakatani, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2004/227608 A1 (“Toshifumi Nakatani”), 58 pages.
- Exhibit A-20: Invalidation Contentions: ‘960 Patent in View of Partovi ‘367, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2007/0182367 A1 (“Partovi ‘367”), 49 pages.
- Exhibit A-21: Invalidation Contentions: ‘960 Patent in View of Inventor Partovi ‘413, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2009/0096413 A1 (“Afshin Partovi ‘413”), 45 pages.
- Exhibit A-22: Invalidation Contentions: ‘960 Patent in View of Partovi ‘636, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2012/0235636 A1 (“Afshin Partovi ‘636”), 64 pages.
- Exhibit A-23: Invalidation Contentions: ‘960 Patent in View of Qi 0.95, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Version 0.95 (“Qi 0.95”), 26 pages.
- Exhibit A-24: Invalidation Contentions: ‘960 Patent in View of Qi 1.0.1, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Part 1: Interface Definition, Version 1.0.1 (“Qi 1.0.1”), 49 pages.
- Exhibit A-25: Invalidation Contentions: ‘960 Patent in View of Shima, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Pat. No. 5,808,587 A (“Hiroshi Shima”), 87 pages.
- Exhibit A-26: Invalidation Contentions: ‘960 Patent in View of Sun, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2011/0101788 A1 (“Sun”), 65 pages.
- Exhibit A-27: Invalidation Contentions: ‘960 Patent in View of Tseng, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Pat. No. 9,912,173 B2 (“Ryan Tseng”), 67 pages.
- Exhibit A-28: Invalidation Contentions: ‘960 Patent in View of Von Novak, III, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Pat. No. 9,559,526 B2 (“William H. Von Novak, III”), 57 pages.
- Exhibit A-29: Invalidation Contentions: ‘960 Patent in View of Yamakawa, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2012/0217819 A1 (“Yamakawa”), 40 pages.
- Exhibit A-30: Invalidation Contentions: ‘960 Patent in View of Yoon & Allen, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Embedded Conductor Technology For Micromachined Rf Elements (“Yoon & Allen”), 43 pages.
- Exhibit A-31: Invalidation Contentions: ‘960 Patent in View of the Blackberry Z30, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by the Blackberry Z30, 154 pages.
- Exhibit A-32: Invalidation Contentions: ‘960 Patent in View of the LG G2, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by the LG G2, 462 pages.
- Exhibit A-33: Invalidation Contentions: ‘960 Patent in View of the LG G3, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by the LG G3, 228 pages.
- Exhibit A-34: Invalidation Contentions: ‘960 Patent in View of the LG Nexus 5, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by the LG Nexus 5, 391 pages.
- Exhibit B-01: Invalidation Contentions: ‘046 Patent in View of Jitsuo, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Japanese Patent Application Publication JP05082349A (“Jitsuo”), 50 pages.
- Exhibit B-02: Invalidation Contentions: ‘046 Patent in View of Kurs ‘694, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2010/0219694 A1 (“Kurs ‘694”), 51 pages.
- Exhibit B-03: Invalidation Contentions: ‘046 Patent in View of Sheng-Yuan, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No.

(56)

References Cited

OTHER PUBLICATIONS

9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2007/267718 A1 (“Sheng-Yuan”), 76 pages.

Exhibit B-04: Invalidation Contentions: ‘046 Patent in View of Wotherspoon, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2007/0126544 A1 (“Wotherspoon”), 44 pages.

Exhibit B-05: Invalidation Contentions: ‘046 Patent in View of Baarman ‘777, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2009/0230777A1 (“Baarman ‘777”), 42 pages.

Exhibit B-06: Invalidation Contentions: ‘046 Patent in View of Bae, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Pat. No. 6,897,830 B2 (“Bae”), 71 pages.

Exhibit B-07: Invalidation Contentions: ‘046 Patent in View of Burghartz & Rejaei, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by On the Design of RF Spiral Inductors on Silicon (“Burghartz & Rejaei”), 45 pages.

Exhibit B-08: Invalidation Contentions: ‘046 Patent in View of Ganem, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2012/0235500 A1 (“Steven J. Ganem”), 75 pages.

Exhibit B-09: Invalidation Contentions: ‘046 Patent in View of Gao, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2011/084656 A1 (“Gao”), 33 pages.

Exhibit B-10: Invalidation Contentions: ‘046 Patent in View of Hasegawa ‘215, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Japanese Patent Application Publication 2008-205215 A (“Hasegawa Minoru”), 42 pages.

Exhibit B-11: Invalidation Contentions: ‘046 Patent in View of Hasegawa ‘518, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by J.P. Patent Application Publication 01310518 A (“Hasegawa Michio ‘518”), 69 pages.

Exhibit B-12: Invalidation Contentions: ‘046 Patent in View of Hasegawa Michio ‘631, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Pat. No. 4,959,631 A (“Hasegawa Michio ‘631”), 37 pages.

Exhibit B-13: Invalidation Contentions: ‘046 Patent in View of Ishihara, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by JP Patent Application Publication 2008/294285 A (“Ishihara Keien”), 33 pages.

Exhibit B-14: Invalidation Contentions: ‘046 Patent in View of Kato ‘840, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2008/164840 A1 (“Hiroshi Kato”), 32 pages.

Exhibit B-15: Invalidation Contentions: ‘046 Patent in View of Kato ‘844, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2008/164844 A1 (“Hiroshi Kato”), 37 pages.

Exhibit B-16: Invalidation Contentions: ‘046 Patent in View of Inventor Kimura, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2002/071003 A1 (“Isao Kimura”), 53 pages.

Exhibit C-33: Invalidation Contentions: Invalidation Contentions: ‘591 Patent in View of the LG G3 *NuCurrent v. Samsung Electronics*

America, Inc. et al., Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by the LG G3, 266 pages.

Exhibit C-34: Invalidation Contentions: ‘591 Patent in View of the LG Nexus 5, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by the LG Nexus 5, 468 pages.

Exhibit D-01: Invalidation Contentions: ‘948 Patent in View of Jitsuo, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by Japanese Patent Application Publication JP05082349A (“Jitsuo”), 54 pages.

Exhibit D-02: Invalidation Contentions: ‘948 Patent in View of Kurs, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2010/0219694 A1 (“Kurs”), 59 pages.

Exhibit D-03: Invalidation Contentions: ‘948 Patent in View of Sheng-Yuan, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2007/267718 A1 (“Sheng-Yuan”), 77 pages.

Exhibit D-04: Invalidation Contentions: ‘948 Patent in View of Wotherspoon, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2007/0126544 A1 (“Wotherspoon”), 52 pages.

Exhibit D-05: Invalidation Contentions: ‘948 Patent in View of Baarman, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2009/0230777A1 (“David W. Baarman”), 52 pages.

Exhibit D-06: Invalidation Contentions: ‘948 Patent in View of Bae, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Pat. No. 6,897,830 B2 (“Bae”), 82 pages.

Exhibit D-07: Invalidation Contentions: ‘948 Patent in View of Burghartz & Rejaei, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by On the Design of RF Spiral Inductors on Silicon (“Burghartz & Rejaei”), 52 pages.

Exhibit D-08: Invalidation Contentions: ‘948 Patent in View of Ganem, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2012/0235500 A1 (“Steven J. Ganem”), 92 pages.

Exhibit D-09: Invalidation Contentions: ‘948 Patent in View of Gao, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2011/084656 A1 (“Gao”), 44 pages.

Exhibit D-10: Invalidation Contentions: ‘948 Patent in View of Hasegawa ‘215, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by Japanese Patent Application Publication 2008-205215 A (“Hasegawa Minoru ‘215”), 46 pages.

Exhibit D-11: Invalidation Contentions: ‘948 Patent in View of Hasegawa Michio ‘631, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Pat. No. 4,959,631 A (“Hasegawa Michio ‘631”), 37 pages.

Exhibit D-12: Invalidation Contentions: ‘948 Patent in View of Hasegawa ‘518, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by J.P. Patent Application Publication 01310518 A (“Hasegawa Michio ‘518”), 78 pages.

Exhibit D-13: Invalidation Contentions: ‘948 Patent in View of Ishihara, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by JP Patent Application Publication 2008/294285 A (“Ishihara Keien”), 38 pages.

(56)

References Cited

OTHER PUBLICATIONS

Exhibit D-14: Invalidation Contentions: '948 Patent in View of Kato, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2008/164840 A1 ("Hiroshi Kato"), 34 pages.

Exhibit D-15: Invalidation Contentions: '948 Patent in View of Kato, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2008/164844 A1 ("Hiroshi Kato"), 39 pages.

Exhibit D-16: Invalidation Contentions: '948 Patent in View of Kimura, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2002/071003 A1 ("Isao Kimura"), 50 pages.

Exhibit D-17: Invalidation Contentions: '948 Patent in View of Kurs '765, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2012/0280765 A1 ("Kurs '765"), 57 pages.

Exhibit D-18: Invalidation Contentions: '948 Patent in View of Misumi, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by Japanese Patent Application Publication JP 10255629 A ("Misumi Shuichi"), 34 pages.

Exhibit D-19: Invalidation Contentions: '948 Patent in View of Nakatani, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2004/227608 A1 ("Toshifumi Nakatani"), 56 pages.

Exhibit D-20: Invalidation Contentions: '948 Patent in View of Partovi '367, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2007/0182367 A1 ("Partovi '367"), 51 pages.

Exhibit D-21: Invalidation Contentions: '948 Patent in View of Partovi '413, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2009/0096413 A1 ("Afshin Partovi '413"), 51 pages.

Exhibit D-22: Invalidation Contentions: '948 Patent in View of Partovi '636, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2012/0235636 A1 ("Afshin Partovi '636"), 67 pages.

Exhibit D-23: Invalidation Contentions: '948 Patent in View of Qi 0.95, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Version 0.95 ("Qi 0.95"), 28 pages.

Exhibit D-24: Invalidation Contentions: '948 Patent in View of Qi 1.0.1, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Part 1: Interface Definition, Version 1.0.1 ("Qi 1.0.1"), 55 pages.

Exhibit D-25: Invalidation Contentions: '948 Patent in View of Shima, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Pat. No. 5,808,587 A ("Hiroshi Shima"), 94 pages.

Exhibit D-26: Invalidation Contentions: '948 Patent in View of Sun, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2011/0101788 A1 ("Sun"), 63 pages.

Exhibit D-27: Invalidation Contentions: '948 Patent in View of Tseng, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No.

1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Pat. No. 9,912,173 B2 ("Ryan Tseng"), 75 pages.

Exhibit D-28: Invalidation Contentions: '948 Patent in View of Novak, III, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Pat. No. 9,559,526 B2 ("William H. Von Novak, III"), 73 pages.

Exhibit D-29: Invalidation Contentions: '948 Patent in View of Yamakawa, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by U.S. Patent Application Publication 2012/0217819 A1 ("Yamakawa"), 42 pages.

Exhibit D-30: Invalidation Contentions: '948 Patent in View of Yoon & Allen, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by Embedded Conductor Technology For Micromachined Rf Elements ("Yoon & Allen"), 41 pages.

Exhibit D-31—Invalidation Contentions: '948 Patent in View of the Blackberry Z30, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by the Blackberry Z30, 168 pages.

Exhibit D-32: Invalidation Contentions: '948 Patent in View of the LG G2, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by the LG G2, 511 pages.

Exhibit D-33—Invalidation Contentions: '948 Patent in View of LG G3, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by the LG G3, 249 pages.

Exhibit D-34—Invalidation Contentions: '948 Patent in View of the LG Nexus 5, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 ("the '948 Patent") by the LG Nexus 5, 434 pages.

Exhibit E-01: Invalidation Contentions: '729 Patent in View of Ha, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Publication No. 2016/0149416 ("Ha"), 99 pages.

Exhibit E-02: Invalidation Contentions: '729 Patent in View of Riehl, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Application Publication 2014/0035383 ("Riehl"), 50 pages.

Exhibit E-03 : Invalidation Contentions: '729 Patent in View of Baarman '154, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Application Publication No. 2013/0076154 ("Baarman '154"), 42 pages.

Exhibit E-04: Invalidation Contentions: '729 Patent in View of Kanno, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Application Publication 2011/0241437 ("Kanno"), 30 pages.

Exhibit E-05: Invalidation Contentions: '729 Patent in View of Kazuya, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by Japanese Patent Application Publication 2013093429 ("Kazuya"), 32 pages.

Exhibit E-06: Invalidation Contentions: '729 Patent in View of Muratov, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Application Publication No. 2015/0357827 ("Muratov"), 35 pages.

Exhibit E-07: Invalidation Contentions: '729 Patent in View of Sung, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 ("the '729 Patent") by United States Patent Publication No. 2012/0274148 ("Sung"), 27 pages.

Exhibit E-08 : Invalidation Contentions: '729 Patent in View of Kurz '635, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No.

(56) **References Cited**

OTHER PUBLICATIONS

- 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2015/0145635 (“Kurz ‘635”), 133 pages.
- Exhibit E-09: Invalidation Contentions: ‘729 Patent in View of Kurz ‘634, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2015/0145635 (“Kurz ‘634”), 122 pages.
- Exhibit E-10: Invalidation Contentions: ‘729 Patent in View of Lee ‘746, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Application Publication No. 2015/0137746 (“Lee ‘746”), 34 pages.
- Exhibit E-11: Invalidation Contentions: ‘729 Patent in View of Mukherjee, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2015/0091502 (“Mukherjee”), 32 pages.
- Exhibit E-12: Invalidation Contentions: ‘729 Patent in View of Asanuma, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Application Publication No. 2014/0197694 (“Asanuma”), 24 pages.
- Exhibit E-13: Invalidation Contentions: ‘729 Patent in View of Takashi, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2014/0008974 (“Takashi”), 77 pages.
- Exhibit E-14: Invalidation Contentions: ‘729 Patent in View of Hoon, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by Korean Patent Publication No. 20130015618 (“Hoon”), 28 pages.
- Ex. 1008—U.S. Publication 2012/0274148 to Sung et al., 13 pages.
- Ex. 1009—JP Patent No. 2013-93429 to Kazuya, 27 pages.
- Ex. 1010—U.S. Pub. No. 2015/0091502 to Mukherjee et al., 7 pages.
- Ex. 1011—KR Patent No. 10-2013-0045307 to Yu, 45 pages.
- Ex. 1012—IEEE Transactions on microwave theory and techniques, New York, NY 1953, 17 pages.
- Ex. 1013—Asa et al., A Novel Multi-Level Phase-Controlled Resonant Inverter with Common Mode Capacitor for Wireless EV Chargers, 6 pages.
- Ex. 1014—Abstract of A Novel Multi-Level Phase-Controlled Resonant Inverter with Common Mode Capacitor for Wireless EV Chargers, IEEE Xplore Digital Library, 2 pages.
- IPR2019-01217—Ex.1015—Wotherspoon—US 2007/0126544, 6 pages.
- PGR2019-00049—Petition for Post-Grant Review re U.S. Pat. No. 10,063,100, 112 pages.
- Ex. 1001—U.S. Pat. No. 10,063,100, 48 pages.
- PGR2019-00049—Ex. 1002—Declaration of Jacob Baker, Ph.D., P.E. In support of Petition for Post-Grant Review of U.S. Pat. No. 10,063,100, 141 pages.
- Ex. 1003—CV of R. Jacob Baker, Ph.D., P.E., 34 pages.
- Ex. 1004—File History of U.S. Appl. No. 14/821,157, Part 1, 475 pages.
- Ex. 1004—File History of U.S. Appl. No. 14/821,157, Part 2, 475 pages.
- Ex. 1004—File History of U.S. Appl. No. 14/821,157, Part 3, 438 pages.
- PGR2019-00050—Petition for Post-Grant Review of U.S. Pat. No. 10,063,100, 73 pages.
- PGR2019-00050—Ex. 1002 Declaration of R. Jacob Baker, Ph.D., P.E. In Support of Petition for Post-Grant Review of U.S. Pat. No. 10,063,100, 42 pages.
- PGR2019-00050—Ex. 1005 U.S. Pat. No. 9,941,729 to Peralta et al., 48 pages.
- PGR2019-00050—Ex. 1006 File History for U.S. Appl. No. 14/821,065, Part 1, 200 pages.
- PGR2019-00050—Ex. 1006 File History for U.S. Appl. No. 14/821,065, Part 2, 200 pages.
- PGR2019-00050—Ex. 1006 File History for U.S. Appl. No. 14/821,065, Part 3, 200 pages.
- PGR2019-00050—Ex. 1006 File History for U.S. Appl. No. 14/821,065, Part 4, 200 pages.
- PGR2019-0050—Ex. 1008—First Amended Complaint for *NuCurrent, Inc. v. Samsung Electronics Co., Ltd.; Samsung Electronics America, Inc.*, Case No. 6:18-cv-00051-JRG-KNM, 62 pages.
- PGR2019-0050—Ex. 1009—NuCurrent’s Opening Claim Construction Brief, Case No. 1:19-CV-00798-DLC, 31 pages.
- European Extended Search Report for EP Application No. 17879649.6-1202 dated Dec. 17, 2019.
- Exhibit B-17: Invalidation Contentions: ‘046 Patent in View of Kurs ‘765, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2012/0280765 A1 (“Kurs ‘765”), 50 pages.
- Exhibit B-18: Invalidation Contentions: ‘046 Patent in View of Misumi, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Japanese. Patent Application Publication JP 10255629 A (“Misumi Shuichi”), 33 pages.
- Exhibit B-19: Invalidation Contentions: ‘046 Patent in View of Nakatani, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2004/227608 A1 (“Toshifumi Nakatani”), 51 pages.
- Exhibit B-20: Invalidation Contentions: ‘046 Patent in View of Partovi ‘367, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2007/0182367 A1 (“Partovi ‘367”), 37 pages.
- Exhibit B-21: Invalidation Contentions: ‘046 Patent in View of Inventor Partovi ‘413, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2009/0096413 A1 (“Afshin Partovi ‘413”), 39 pages.
- Exhibit B-22: Invalidation Contentions: ‘046 Patent in View of Partovi ‘636, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2012/0235636 A1 (“Afshin Partovi ‘636”), 55 pages.
- Exhibit B-23: Invalidation Contentions: ‘046 Patent in View of Qi 0.95, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Version 0.95 (“Qi 0.95”), 23 pages.
- Exhibit B-24: Invalidation Contentions: ‘046 Patent in View of Qi 1.0.1, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Part 1: Interface Definition, Version 1.0.1 (“Qi 1.0.1”), 44 pages.
- Exhibit B-25: Invalidation Contentions: ‘046 Patent in View of Shima, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Pat. No. 5,808,587 A (“Hiroshi Shima”), 76 pages.
- Exhibit B-26: Invalidation Contentions: ‘046 Patent in View of Sun, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2011/0101788 A1 (“Sun”), 55 pages.
- Exhibit B-27: Invalidation Contentions: ‘046 Patent in View of Tseng, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Pat. No. 9,912,173 B2 (“Ryan Tseng”), 62 pages.
- Exhibit B-28: Invalidation Contentions: ‘046 Patent in View of Von Novak, III, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No.

(56)

References Cited

OTHER PUBLICATIONS

9,300,046 ("the '046 Patent") by U.S. Pat. No. 9,559,526 B2 ("William H. Von Novak, III"), 50 pages.

Exhibit B-29: Invalidity Contentions: '046 Patent in View of Yamakawa, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by U.S. Patent Application Publication 2012/0217819 A1 ("Yamakawa"), 36 pages.

Exhibit B-30: Invalidity Contentions: '046 Patent in View of Yoon & Allen, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by Embedded Conductor Technology For Micromachined Rf Elements ("Yoon & Allen"), 39 pages.

Exhibit B-31: Invalidity Contentions: '046 Patent in View of the Blackberry Z30, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by the Blackberry Z30, 135 pages.

Exhibit B-32: Invalidity Contentions: '046 Patent in View of the LG G2, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by the LG G2, 401 pages.

Exhibit B-33: Invalidity Contentions: '046 Patent in View of the LG G3, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by the LG G3, 200 pages.

Exhibit B-34: Invalidity Contentions: '046 Patent in View of the LG Nexus 5, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,300,046 ("the '046 Patent") by the LG Nexus 5, 340 pages.

Exhibit C-01: Invalidity Contentions: '591 Patent in View of Jitsuo, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by Japanese Patent Application Publication JP05082349A ("Jitsuo"), 59 pages.

Exhibit C-02: Invalidity Contentions: '591 Patent in View of Kurs '694, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2010/0219694 A1 ("Kurs '694"), 61 pages.

Exhibit C-03: Invalidity Contentions: '591 Patent in View of Sheng-Yuan, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2007/267718 A1 ("Sheng-Yuan"), 84 pages.

Exhibit C-04: Invalidity Contentions: '591 Patent in View of Wotherspoon, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2007/0126544 A1 ("Wotherspoon"), 58 pages.

Exhibit C-05: Invalidity Contentions: '591 Patent in View of Baarman '777, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2009/0230777 A1 ("Baarman '777"), 57 pages.

Exhibit C-06: Invalidity Contentions: '591 Patent in View of Burghartz & Rejaei, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by On the Design of RF Spiral Inductors on Silicon ("Burghartz & Rejaei"), 61 pages.

Exhibit C-07: Invalidity Contentions: '591 Patent in View of Ganem, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2012/0235500 A1 ("Steven J. Ganem"), 98 pages.

Exhibit C-08: Invalidity Contentions: '591 Patent in View of Gao, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2011/084656 A1 ("Gao"), 49 pages.

Exhibit C-09: Invalidity Contentions: '591 Patent in View of Hasegawa '215, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by Japanese Patent Application Publication 2008-205215 A ("Hasegawa Minoru"), 50 pages.

Exhibit C-10: Invalidity Contentions: '591 Patent in View of Hasegawa '518, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by J.P. Patent Application Publication 01310518 A ("Hasegawa Michio '518"), 85 pages.

Exhibit C-11: Invalidity Contentions: '591 Patent in View of Hasegawa '631, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Pat. No. 4,959,631 A ("Hasegawa '631"), 40 pages.

Exhibit C-12: Invalidity Contentions: '591 Patent in View of Ishihara, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by JP Patent Application Publication 2008/294285 A ("Ishihara Keien"), 40 pages.

Exhibit C-13: Invalidity Contentions: '591 Patent in View of Kato '840, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2008/164840 A1 ("Hiroshi Kato"), 35 pages.

Exhibit C-14: Invalidity Contentions: '591 Patent in View of Kato '844, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2008/164844 A1 ("Hiroshi Kato"), 39 pages.

Exhibit C-15: Invalidity Contentions: '591 Patent in View of Kimura, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2002/071003 A1 ("Isao Kimura"), 52 pages.

Exhibit C-16: Invalidity Contentions: '591 Patent in View of Kurs '765, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2012/0280765 A1 ("Kurs '765"), 61 pages.

Exhibit C-17: Invalidity Contentions: '591 Patent in View of Misum, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by Japanese Patent Application Publication JP 10255629 A ("Misum Shuichi"), 37 pages.

Exhibit C-18: Invalidity Contentions: '591 Patent in View of Nakatani, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2004/227608 A1 ("Toshifumi Nakatani"), 59 pages.

Exhibit C-19: Invalidity Contentions: '591 Patent in View of Partovi '367, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2007/0182367 A1 ("Partovi '367"), 55 pages.

Exhibit C-20: Invalidity Contentions: '591 Patent in View of Afshin Partovi '413, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2009/0096413 A1 ("Afshin Partovi '413"), 56 pages.

Exhibit C-21: Invalidity Contentions: '591 Patent in View of Partovi '636, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by U.S. Patent Application Publication 2012/0235636 A1 ("Afshin Partovi '636"), 77 pages.

Exhibit C-22: Invalidity Contentions: '591 Patent in View of Qi 0.95, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 8,698,591 ("the '591 Patent") by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Version 0.95 ("Qi 0.95"), 29 pages.

Exhibit C-23: Invalidity Contentions: '591 Patent in View of Qi 1.0.1, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case

(56) **References Cited**

OTHER PUBLICATIONS

No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by Qi System Description, *Wireless Power Transfer*, vol. 1: Low Power, Part 1: Interface Definition, Version 1.0.1 (“Qi 1.0.1”), 57 pages.

Exhibit C-24: Invalidation Contentions: ‘591 Patent in View of Shima, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Pat. No. 5,808,587 A (“Hiroshi Shima”), 102 pages.

Exhibit C-25: Invalidation Contentions: ‘591 Patent in View of Sun, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Patent Application Publication 2011/0101788 A1 (“Sun”), 68 pages.

Exhibit C-26: Invalidation Contentions: ‘591 Patent in View of Tseng, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Pat. No. 9,912,173 B2 (“Ryan Tseng”), 84 pages.

Exhibit C-27: Invalidation Contentions: ‘591 Patent in View of Von Novak, III, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Pat. No. 9,559,526 B2 (“William H. Von Novak, III”), 81 pages.

Exhibit C-28: Invalidation Contentions: ‘591 Patent in View of Yamakawa, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Patent Application Publication 2012/0217819 A1 (“Yamakawa”), 46 pages.

Exhibit C-29: Invalidation Contentions: ‘591 Patent in View of Yoon & Allen, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by Embedded Conductor Technology For Micromachined Rf Elements (“Yoon & Allen”), 14 pages.

Exhibit C-30: Invalidation Contentions: ‘591 Patent in View of Bae, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Pat. No. 6,897,830 B2 (“Bae”), 88 pages.

Exhibit C-31: Invalidation Contentions: ‘591 Patent in View of the Blackberry Z30, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by the Blackberry Z30, 180 pages.

Exhibit C-32: Invalidation Contentions: ‘591 Patent in View of the LG G2, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by the LG G2, 557 pages.

Exhibit E-15 : Invalidation Contentions: ‘729 Patent in View of Lee ‘710, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2015/0318710 (“Lee ‘710”), 42 pages.

Exhibit E-16: Invalidation Contentions: ‘729 Patent in View of Hisanori, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by Japanese Patent Publication No. 2012-147408 (“Hisanori”), 45 pages.

Exhibit E-17: Invalidation Contentions: ‘729 Patent in View of Muratov Presentation, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by Multi-Mode Wireless Power Systems can be a Bridge to the Promised Land of Universal Contactless Charging, presented by Vladimir Muratov (“Muratov Presentation”), 57 pages.

Exhibit E-18: Invalidation Contentions: ‘729 Patent in View of Han, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No.

1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by United States Patent Publication No. 2017/0353055 A1 (“Han”), 46 pages.

Exhibit E-19: Invalidation Contentions: ‘729 Patent in View of Riehl IEEE, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,941,729 (“the ‘729 Patent”) by Wireless Power Systems for Mobile Devices Supporting Inductive and Resonant Operating Modes, by Patrick S. Riehl et al., *IEEE Transactions on Microwave Theory and Techniques*, vol. 63, No. 3, Mar. 3, 2015 (Riehl IEEE), 56 pages.

Exhibit F-01: Invalidation Contentions: ‘960 Patent in View of Chung Yeon Ho, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by Korean Patent Application Publication 2010/0092741 A (“Chung Yeon Ho”), 34 pages.

Exhibit F-02: Invalidation Contentions: ‘960 Patent in View of Jung, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by U.S. Patent Application Publication 2009/0140691 A1 (“Chun-Kil Jung”), 58 pages.

Exhibit F-03: Invalidation Contentions: ‘960 Patent in View of Kook, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,680,960 (“the ‘960 Patent”) by WIPO Patent Application Publication 2008/050917 A1 (“Kook Yoon-Sang”), 30 pages.

Exhibit G-01: Invalidation Contentions: ‘046 Patent in View of Chung Yeon Ho, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by Korean Patent Application Publication 2010/0092741 A (“Chung Yeon Ho”), 33 pages.

Exhibit G-02: Invalidation Contentions: ‘046 Patent in View of Jung, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by U.S. Patent Application Publication 2009/0140691 A1 (“Chun-Kil Jung”), 49 pages.

Exhibit G-03: Invalidation Contentions: ‘046 Patent in View of Kook, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 9,300,046 (“the ‘046 Patent”) by WIPO Patent Application Publication 2008/050917 A1 (“Kook Yoon-Sang”), 26 pages.

Exhibit H-01: Invalidation Contentions: ‘591 Patent in View of Chung Yeon Ho, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by Korean Patent Application Publication 2010/0092741 A (“Chung Yeon Ho”), 43 pages.

Exhibit H-02: Invalidation Contentions: ‘591 Patent in View of Jung, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by U.S. Patent Application Publication 2009/0140691 A1 (“Chun-Kil Jung”), 88 pages.

Exhibit H-03: Invalidation Contentions: ‘591 Patent in View of Kook, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,698,591 (“the ‘591 Patent”) by WIPO Patent Application Publication 2008/050917 A1 (“Kook Yoon-Sang”), 49 pages.

Exhibit I-01: Invalidation Contentions: ‘948 Patent in View of Chung Yeon Ho, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by Korean Patent Application Publication 2010/0092741 A (“Chung Yeon Ho”), 39 pages.

Exhibit I-02: Invalidation Contentions: ‘948 Patent in View of Jung, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by U.S. Patent Application Publication 2009/0140691 A1 (“Chun-Kil Jung”), 78 pages.

Exhibit I-03: Invalidation Contentions: ‘948 Patent in View of Kook, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidation of U.S. Pat. No. 8,710,948 (“the ‘948 Patent”) by WIPO Patent Application Publication 2008/050917 A1 (“Kook Yoon-Sang”), 43 pages.

Exhibit J-01 : Invalidation Contentions: ‘729 Patent in View of Satoshi, *NuCurrent v. Samsung Electronics America, Inc. et al.*,

(56)

References Cited

OTHER PUBLICATIONS

Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by Japanese Patent Publication No. 2001-344574 (“Satoshi”), 19 pages.

Exhibit J-02: Invalidity Contentions: ’729 Patent in View of Takahashi, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by United States Patent Publication No. 2007/0095913 (“Takahashi”), 23 pages.

Exhibit J-03: Invalidity Contentions: ’729 Patent in View of Baarman ’953, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by United States Patent Application Publication No. 2011/0259953 (“Baarman ’953”), 31 pages.

Exhibit J-04: Invalidity Contentions: ’729 Patent in View of Carobolante, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by United States Patent Publication No. 2015/0115727 (“Carobolante”), 12 pages.

Exhibit J-05: Invalidity Contentions: ’729 Patent in View of Bae, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by United States Patent Publication No. 2016/0156103 (“Bae”), 6 pages.

Exhibit J-06: Invalidity Contentions: ’729 Patent in View of Singh, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by U.S. Pat. No. 8,680,960 (“Singh”), 3 pages.

Exhibit J-07: Invalidity Contentions: ’729 Patent in View of Qi 1.0.1, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by Qi System Description, Wireless Power Transfer, vol. 1: Low Power, Part 1: Interface Definition, Version 1.0.1 (“Qi 1.0.1”), 14 pages.

Exhibit J-08 : Invalidity Contentions: ’729 Patent in View of Narayanan, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by Application Note: Wireless Power Charging Coil Considerations, by Raghu Narayanan, Würth Elektronik (“Narayanan”), 6 pages.

Exhibit J-09: Invalidity Contentions: ’729 Patent in View of Barcelo, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.) Invalidity of U.S. Pat. No. 9,941,729 (“the ’729 Patent”) by Application Note 138: Wireless Power User Guide, by Trevor Barcelo, Linear Technology (“Barcelo”), 4 pages.

Exhibit K: Family Patents Combinations, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.), 103 pages.

Exhibit L: ’729 Patent Combinations, *NuCurrent v. Samsung Electronics America, Inc. et al.*, Case No. 1:19-cv-00798-DLC (S.D.N.Y.), 106 pages.

Decision Granting Institution of Inter Partes Review of IPR2019-0858, 44 pages.

IPR2019-00858, Exhibit 1042—Order Denying [167] Motion for Preliminary Injunction, 15 pages.

IPR2019-00859—Decision Granting Institution of Inter Partes Review for U.S. Pat. No. 9,300,046 B2, 48 pages.

IPR2019-00859—Ex. 1042—Order Denying [167] Motion for Preliminary Injunction, 15 pages.

IPR2019-00860—Decision Denying Institution of Inter Partes Review re U.S. Pat. No. 8,680,960 B2, 6 pages.

IPR2019-00860—Ex. 1042, Order Denying [167] Motion for Preliminary Injunction, 15 pages.

Decision Denying Institution of Inter Partes Review re U.S. Pat. No. 9,300,046 B2, 6 pages.

Decision Granting of Inter Partes Review Case IPR2019-00862 re U.S. Pat. No. 8,710,948 B2, 41 pages.

IPR2019-00862 Exhibit 1042—Order Denying [167] Motion for Preliminary injunction.

IPR2019-00863 Decision Granting Institution of Inter Partes Review re U.S. Pat. No. 8,698,591 B2, 42 pages.

IPR2019-00863—Ex. 1002 Corrected Leeb Declaration.

IPR2019-01217—Petition for Inter Partes Review of U.S. Pat. No. 9,941,729, 90 pages.

IPR2019-01217—Ex. 1001—U.S. Pat. No. 9,941,729, 48 pages.

IPR2019-01217—Ex. 1002—Declaration of R. Jacob Baker, Ph.D., P.E., In Support of Petition for Inter Partes Review of U.S. Pat. No. 9,941,729, 143 pages.

IPR2019-01217—Ex. 1003—CV of R. Jacob Baker, 35 pages.

IPR2019-01217—Ex. 1004—U.S. Appl. No. 14/821,065, part 1, 330 pages.

IPR2019-01217—Ex. 1004—U.S. Appl. No. 14/821,065, part 2, 430 pages.

IPR2019-01217—Ex. 1004—U.S. Appl. No. 14/821,065, part 3, 230 pages.

IPR2019-01217—Ex. 1004—U.S. Appl. No. 14/821,065, part 4, 299 pages.

Ex. 1005—U.S. Publication 2014-0035383 to Riehl, 11 pages.

Ex. 1006—Riehl IEEE Transactions on Microwave Theory and Techniques, Mar. 2015, vol. 63, No. 3, 17 pages.

Ex. 1007 U.S. Publication 2011/0241437 to Kanno, 21 pages.

CN Office Action, CN Application No. 201780060807.6 dated Mar. 4, 2020, 18 pages.

International Bureau, International Preliminary Report on Patentability dated Mar. 7, 2019, issued in connection with International Application No. PCT/US2017/048708, filed Aug. 25, 2017, 9 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18A

FIG. 18B




FIG. 18C

FIG. 18D




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 30A




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35

WIRELESS CONNECTOR SYSTEM

RELATED APPLICATION

This application claims priority to U.S. Provisional Application No. 62/379,940, filed on Aug. 26, 2016, the disclosure of which is entirely incorporated herein by reference.

TECHNICAL FIELD

The present disclosure generally relates to the wireless transmission of electrical energy and data. More specifically, this application relates to an electrical device that facilitates the wireless transmission electrical energy at multiple operating frequencies and frequency bands.

BACKGROUND

Prior art electrical connectors are traditionally constructed with a plurality of pins that physically plug into a corresponding receiving port. Each half of these connectors are typically assigned a male and a female designation which are subsequently mated to form an electrical contact.

Fundamentally, an electrical connector is an electro-mechanical device comprising electrical conductors that are used to electrically and mechanically join other conductors, electrical terminals of apparatus and equipment to create an electrical circuit. The term electrical connector generally covers a wide range of devices designed to connect, for example, small conductors employed in communication circuits to large cables and bus-bars. They are typically passive and consist of plugs (male) and jacks (female). The connection may be temporary, as for portable equipment, or may serve as a permanent electrical joint between two wires or devices.

Examples of prior art connectors include USB and HDMI plugs. The power levels for these connectors range from a few Watts to about 100 Watts (as, for example, for the recently released USB-C). These connectors are also constructed and rated to provide data capabilities of up to 10 Gbps or higher. In addition, there are numerous types of connectors, ranging from a simplistic "Wire Nut" to more complex USB connectors or RF connectors, which mostly comply with known connection interface standards, for example, Ethernet, CAN, IO-Link, and RS485. The power levels for these connectors can range from microwatts to megawatts.

Typical connector types are in-line splice couplers, T-tap connectors, terminal lugs, and stud connectors. Couplers join conductors end to end. T-tap connectors join a through conductor to another conductor at right angles. Terminal lugs join the conductor to a drilled tongue for bolting to the terminals of equipment. Stud connectors join the conductor to equipment studs. The stud clamp is typically threaded or smooth to match the stud.

Other connector types include split-bolt connectors that are generally of a compact construction and are widely used for splicing and taping wires. The split-bolt connector comprises a bolt-shape casting having a wide and deep lengthwise slot. Conductors are inserted in the slot and a nut clamps the conductors together inside the bolt.

Yet another type of connector is an expansion or flexible connector that allows for limited motion between the connected conductors. The clamp portions of the connector are joined by short lengths of flexible copper braid and may also be held in alignment by a telescoping guide.

Another type of traditional connectors include separable type connectors that generally consist of matched plugs and receptacles. Separable type connectors are designed to separate or disconnect a conductor or group of conductors from a circuit or system. Separable type connectors are commonly used for the connection of portable devices and appliances to an electric wiring system.

Traditional connectors also include locking type connectors that are designed such that a plug is inserted and twisted through a shaped opening, locking it securely in place. Thus, when connected, locking type connectors are generally not separated by a mechanical strain such as a pull on the connected cord.

Electrical connectors are generally characterized by a variety of parameters which include, but are not limited to, the number of electrical connections (i.e. pins), physical construction, size, shape, contact resistance, insulation between electrical connections, ruggedness to vibration, resistance to contaminants and pressure, reliability, estimated lifetime (number of connect/disconnect operations before failure), and ease of connecting and disconnecting. The physical electrical connections, such as pins, of traditional connectors, provide a passage for electrical energy and data. In addition, characteristics of electrical power and data, such as power ratings and data rates are also utilized to characterize various electrical connectors.

Operation of these prior art connectors is typically dependent on the physical connection between two electrically conductive components, such as a pin and a respective pad, port or jack within which the pin is received. The physical connection occurs at a microscopic level over a relatively small interface area between the physically contacting electrically conductive components, such as a pin and a corresponding receptacle. Furthermore, traditional connectors generally require a significant amount of mechanical force to ensure an adequate physical connection of the connecting members so that an electrical signal is safely passed through. This microscopic connecting area may become affected by different factors, such as harsh environments, vibration as well as wear and tear over time under normal operating conditions.

As such, the performance and reliability of these prior art connectors are largely dictated by the integrity of their physical connection. Furthermore, these traditional mechanical connectors generally require physical contact at a precise alignment to function properly.

Furthermore, wired connectors typically do not allow any relative motion between the male and the female portions. Over time, due to this physical contact, these mechanical connection points typically experience forces that can fatigue and damage the pin or port, thereby preventing proper functionality. Such prior art connectors may wear, flex, or may become corroded or damaged. As a result, the physical connection between the corresponding male and female portions such as a pin and respective port may become compromised, thereby resulting in a loss of data or electrical energy transfer therebetween due to an impaired or inoperable connector. Contamination, moisture and liquid ingress in a consumer, medical, military or industrial environment may pose undesirable problems, including outright failure to perform which may result in hazardous, unsafe or threatening conditions. In addition to improper functionality due to faulty physical connections, methods of wired communication, such as Universal Asynchronous Receiver and Transmitter Protocol (UART), Inter-Integrated Protocol (I2C), and Serial Peripheral Interface Protocol (SPI), may

have limited bandwidth capabilities in comparison to various wireless methods of communication.

Moreover, developments in automation and robotics have increased the demand for transferring electrical power between dynamically moving parts and assemblies of many different industrial devices. There is a significant challenge to transfer power under these conditions using conventional wired electrical connectors.

In addition to the deficiencies given above, such prior art connectors typically comprise an electrical cord that extends from the connector. Such electrical cords are generally not desired as they may also become damaged, resulting in a loss of data or energy transfer. Furthermore, such electrical cords may excessively occupy critical space and become an impediment to the user. Moreover, exposed or damaged cords may contaminate a sterilized environment. Furthermore, such exposed or damaged cords, for example, cords that have lost their electrical insulation, may become a hazard and potentially cause electrical shock to both humans and animals.

SUMMARY

Therefore, to address these problems, a wireless connector system is provided. In an embodiment, the wireless connector system of the present application enables the wireless transmission of electrical power and/or data between spaced apart transmitter and receiver modules using near field magnetic coupling (NFMC). In an embodiment, the respective transmitter and receiver wireless modules may be insulated and/or hermetically sealed.

The connectors have exposed contact pins and features allowing them to be assembled onto larger electrical circuits, such as a printed circuit board (PCB) or flexible circuit board (FPC) using an electrical component surface mount (SMT) assembly process.

Thus, provided is an electrical connector having a form factor that can replace or eliminate the need for wired connectors.

The wireless connector system of the present application provides a wireless power link that eliminates the need for a physical connection such as an electrical connector that physically joins two components together. Thus, by eliminating the physical connection, the wireless connector or power link can be completely encapsulated, preventing liquids and other debris from inhibiting proper functionality. Without physical contact, mechanical and environmental stresses and wear of the connector are eliminated and a more reliable and robust link to transfer power and data is achieved. This solution also allows for greater misalignment and/or relative movement between the transmitter and receiver compared to prior art connectors. This could allow these connectors to be used in applications which were not previously considered for wired connectors due to their limitations.

In one or more of the embodiments of the present application, a wireless connector system is provided that includes a transmitter module with a first substrate supporting a transmitter antenna, wherein the transmitter antenna is configured to transmit a wireless signal. In addition, the wireless connector system includes a second substrate supporting a transmitter module electronic circuit, wherein the transmitter module electronic circuit is electrically connected to the transmitter antenna. In addition, a first insulator is positioned between the transmitter module electronic circuit and the transmitter antenna. The wireless connector system further includes a receiver module with a third substrate supporting

a receiving antenna, wherein the receiving antenna is configured to receive the wireless signal. Furthermore, the wireless connector system includes a fourth substrate supporting a receiver module electronic circuit, wherein the receiver module electronic circuit is electrically connected to the receiver antenna. In addition, a second insulator is positioned between the receiver module electronic circuit and the receiver antenna.

The transmitter and receiver modules of the wireless connector system of the present application are designed with electrical circuitry that increases the amount of wirelessly transmitted electrical power over a greater separation distance between the transmitter and receiver modules. In addition, the wireless connector system may be configured with various sensors that detect the presence of an electrical energy transfer module, heat, or an undesirable foreign object. In an embodiment, the operation of the transmitter and/or the receiver module may be dependent upon information obtained from various sensors that may or may not be incorporated within the module.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of an embodiment of the wireless connector system of the present application.

FIG. 2 shows a block diagram of an embodiment of the wireless connector system of the present application.

FIGS. 3-6 illustrate electrical block diagrams of embodiments of the transmitter module.

FIGS. 7, 8A, and 8B show embodiments of a switching capacitance circuit that may be incorporated within the impedance matching circuit of the transmitter or receiver circuit of the present application.

FIGS. 9-12 illustrate electrical schematic diagrams of embodiments of the transmitter circuit.

FIG. 13 illustrates a block diagram of an embodiment of the receiver module of the wireless connector system of the present application.

FIG. 14 illustrates an electrical schematic diagram of an embodiment of the receiver circuit within the receiver module.

FIG. 15 is an electrical block diagram of an embodiment of the receiver module.

FIG. 16 illustrates an electrical schematic diagram of an embodiment of the receiver circuit within the receiver module.

FIG. 17 is an electrical block diagram of an embodiment of the receiver module.

FIGS. 18A-18D illustrate embodiments of capacitors within the impedance matching circuit that may be utilized in the transmitter or receiver circuit.

FIGS. 19-21 show embodiments of the transmitter and receiver modules of the present application.

FIGS. 22-23 illustrate embodiments of the transmitter and receiver modules of the wireless connector of the present application electrically connected to a host device.

FIG. 24 shows an embodiment of the positioning of the antenna and transmitter and receiver circuit board relative to shielding and spacer materials within the transmitter and receiver module housings.

FIGS. 25 and 26 illustrate embodiments of electrically connecting the transmitter and receiver modules to a circuit board of a host device.

FIGS. 27-30 illustrate embodiments of alternative structures of the transmitter or receiver modules of the present invention.

FIG. 30A is a cross-sectional view of the embodiment of the assembled transmitter module or receiver module shown in FIG. 30.

FIGS. 31-34 illustrate different embodiments of the transmitter or receiver module shown in FIGS. 27-30 mounted to a circuit board.

FIG. 35 shows an embodiment of an antenna that may be utilized in either or both the transmitter and receiver modules.

DETAILED DESCRIPTION

In the following description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant teachings. However, it should be apparent to those skilled in the art that the present teachings may be practiced without such details. In other instances, well known methods, procedures, components, and/or circuitry have been described at a relatively high-level, without detail, in order to avoid unnecessarily obscuring aspects of the present teachings.

The wireless connector system 10 of the present disclosure provides for the wireless transfer of electrical energy and/or data. More specifically, the wireless connector system 10 of the present invention provides for the wireless transfer of electrical energy and/or data via near field magnetic coupling. In an embodiment, the wireless connector system 10 comprises a transmitter module 12 configured to transmit electrical energy and a receiver module 14 configured to receive electrical energy transmitted by the transmitter module 12. In an embodiment, the transmitter module 12 is positioned spaced from the receiver module 14 so that electrical energy is wirelessly transmitted from the transmitter module 12 across a separation distance or gap 16 (FIGS. 2 and 19-22) where it is received by the receiver module 14. Thus, the combination of the transmitter and receiver modules 12, 14 provides for the wireless connector system 10 so that electrical energy can be transferred wirelessly without the need of a physical connection therebetween.

In this application, the inventive concepts particularly pertain to near-field magnetic coupling (NFM). Near-field magnetic coupling enables the transfer of electrical energy and/or data wirelessly through magnetic induction between a transmitting antenna and a corresponding receiving antenna. The NFC standard, based on near-field communication interface and protocol modes, is defined by ISO/IEC standard 18092. Furthermore, as defined herein "inductive charging" is a wireless charging technique that utilizes an alternating electromagnetic field to transfer electrical energy between two antennas. "Resonant inductive coupling" is defined herein as the near field wireless transmission of electrical energy between two magnetically coupled coils that are tuned to resonate at a similar frequency. As defined herein the term "shunt" means an electrically conductive pathway that is created by electrically joining two points of a circuit such that an electrical current or an electrical voltage may pass therethrough. As defined herein "mutual inductance" is the production of an electromotive force in a circuit by a change in current in a second circuit magnetically coupled to the first. As defined herein a "shielding material" is a material that captures a magnetic field. Examples of shielding material include, but are not limited to ferrite materials such as zinc comprising ferrite materials such as manganese-zinc, nickel-zinc, copper-zinc, magnesium-zinc, and combinations thereof. A shielding material thus may be used to direct a magnetic field to or away from

an object, such as a parasitic metal, depending on the position of the shielding material within or nearby an electrical circuit. Furthermore, a shielding material can be used to modify the shape and directionality of a magnetic field. As defined herein a parasitic material, such as a parasitic metal, is a material that induces eddy current losses in the inductor antenna. This is typically characterized by a decrease in inductance and an increase in resistance of the antenna, i.e., a decrease in the quality factor.

FIG. 1 shows a generic block diagram of the wireless connector system 10 of the present invention. As shown, the system 10 comprises the transmitter module 12 spaced from the receiver module 14 by the gap 16. The transmitter module 12 comprises a transmitter module circuit 18 that is electrically connected to a transmitter antenna 20. In an embodiment, the transmitter antenna 20 may comprise one or more antennas to facilitate the wireless transfer of electrical power and/or data. In an embodiment, the transmitter module circuit 18 is configured to modify electrical energy that is received from an electrical source (not shown) or a transmitter host device 22 that is electrically connected to the transmitter module 12. In an embodiment, the transmitter host device 22 may comprise an electrically operated device, a circuit board, an electronic assembly, or other electronic device. Examples of transmitter host devices include, but are not limited to, a medical device, a device that comprises an integrated circuit, such as a computer, and personal electronic devices, such as, but not limited to, eye glasses and clothing configured with electronic components.

The transmitter antenna 20 is configured to wirelessly transmit the electrical energy conditioned and modified for wireless transmission by the transmitter module circuit 18 via near-field magnetic induction coupling. In an embodiment, the transmitter module 12 may be electrically powered by the transmitter host device 22.

In an embodiment, the receiver module 14 comprises a receiver module circuit 24 that is electrically connected to a receiver antenna 26. The receiver antenna 26 is configured to receive electrical energy and/or data that is transmitted by the transmitter module 12. In an embodiment, the receiver module circuit 24 is configured to condition the received wireless electrical energy such that it can be used to electrically power a device or provide electrical energy to an electrical energy storage device such as a battery or capacitor.

In an embodiment, the receiver module 14 is electrically connected to a receiver host device 28. In an embodiment, the receiver host device 28 comprises an electrically operated device, a circuit board, an electronic assembly, or other electronic device. Examples of receiver host devices include, but are not limited to, a medical device, a device that comprises an integrated circuit, such as a computer, and personal electronic devices, such as not but limited to eye glasses and clothing configured with electronic components. In an embodiment, the receiver module 14 may be electrically powered from an electrical power source 105 (FIG. 17) supplied by the receiver host device 28. It is noted that at least one of the transmitter and receiver modules 12, 14 may be configured as a transceiver thereby enabling either or both the transmitter and receiver modules 12, 14 to transmit and receive electrical power and/or data.

In an embodiment, the transmitter module 12 and the receiver module 14 may be connected to the same host device to facilitate wireless transfer of electrical energy within the host device. Alternatively, the transmitter and receiver modules 12, 14 may be electrically connected to

different host devices thereby facilitating wireless transfer of electrical energy between two different devices.

FIG. 2 illustrates a block diagram of an embodiment of the wireless connector system 10 of the present application. As shown, the transmitter module circuit 18 comprises a gate driver 30 and an electrical power amplifier 32. A voltage supply and electrical ground, from the transmitter host device 22 are electrically connected to the gate driver 30 and the electrical power amplifier 32 of the transmitter module circuit 18. In an embodiment, the gate driver 30 is used to control the operation of the electrical power amplifier 32. In addition, a control signal and pulse width modulation signal, from the transmitter host device 22 are electrically connected to the gate driver 30 of the transmitter module circuit 18. In an embodiment, the control signal and pulse width modulator signal are used to control the operation of the transmitter module 12. The receiver module 14, which is illustrated comprising the receiver antenna 26, a rectifier 34 and a voltage regulator 36, is positioned spaced at the gap 16 from the transmitter module 12. As illustrated, an electrical power line, which is electrically connected to the receiver host device 28 and the receiver module circuit 24, exits the receiver module 14 to provide electrical power to a connected receiver host device 28. In an embodiment, the rectifier 34 is configured to rectify the received wireless electrical power from an alternating current electrical power to a direct current electrical power. The voltage regulator 36 is configured to modify the voltage of the received wireless electrical power before it exits the receiver module 14.

FIGS. 3-6 are block diagrams that illustrate embodiments of the transmitter module circuit 18 of the present invention that comprises various transmitter module sub-circuits. As illustrated in the embodiment shown in FIG. 3, the transmitter module circuit 18 comprises an electrical driver sub-circuit 38, an electrical impedance matching or network sub-circuit 40 and a receiver sensing sub-circuit 42. In addition, the transmitter module circuit 18, may comprise a voltage regulator 36 and a master control unit 44. Alternatively, as shown, the voltage regulator 36 and the master control unit 44 may be comprised within the transmitter host device 22.

In an embodiment, the voltage regulator 36 is configured to adjust the amplitude of the voltage of the electrical energy received from an electrical source, such as the transmitter host device 22, by the transmitter module circuit 18. In the embodiment shown, the voltage regulator 36 is electrically connected to an electrical power source 46 and the driver sub-circuit 38. In an embodiment, the electrical power source 46 may comprise an electrical storage device such as an electrochemical cell (not shown), a battery pack (not shown), or a capacitor (not shown). In addition, the electrical power source 46 may comprise an alternating or direct current electrical power from the transmitter host device 22. In an embodiment, the driver circuit 38 controls the operation of the electrical impedance matching or network sub-circuit 40 and/or the transmitter antenna 20. In an embodiment, the driver sub-circuit 38 may comprise an integrated circuit such as a half-bridge integrated circuit. In an embodiment, the driver sub-circuit 38 may be configured to convert at least a portion of the electrical power from a direct current electrical power to an alternating current electrical power for wireless transmission.

In an embodiment, the receiver sensing sub-circuit 42 is configured to detect the presence of the receiver module 14. In an embodiment, if the presence of the receiver module 14 is detected, wireless transmission of electrical power and/or data by the transmitter module 12 to the receiver module 14

is enabled. Likewise, in an embodiment, if the presence of the receiver module 14 is not detected, wireless transmission of electrical power and/or data is prevented from occurring. In addition, the master control unit 44, which may comprise an integrated circuit, is electrically connected to the driver sub-circuit 38. In an embodiment, the master control unit 44 controls the operation of the transmitter antenna 20 and transmitter module circuit 18. The electrical impedance matching or network circuit 40, which comprises at least one capacitor, is electrically connected to the electrical driver sub-circuit 38 and the transmitter antenna 20. The impedance matching circuit 40 provides a capacitance that is designed to adjust and match the electrical impedance of the receiver antenna 26 to a characteristic impedance of the power generator or the load at a driving frequency of the transmitter antenna 20.

In an embodiment, electrical power from an electrical source 46, such as the transmitter host device 22, is received by the voltage regulator 36 and the master control unit 44. A first portion of the electrical power, from the electrical power source 46, is configured to electrically power the components of the transmitter module 12 such as the master control unit 44. A second portion of the electrical power, from the electrical power source 46, is conditioned and modified for wireless transmission to the receiver module 14. In an embodiment, the voltage regulator 36 modifies the amplitude of the voltage of the second portion of electrical power to match the voltage requirements of the receiver host device 28. The second portion of the electrical power, conditioned by the transmitter module circuit 18 for wireless transmission, is received by the transmitter antenna 20 where it is wirelessly transmitted to the receiver module 14.

In an embodiment, as illustrated in FIG. 4, the transmitter module circuit 18 may also be configured with a power stage inverter 48, such as a dual field effect transistor power stage inverter. In an embodiment, the power stage inverter 48 is an electrical amplifier that is electrically connected to the driver sub-circuit 38 and the network analyzer sub-circuit 40. In an embodiment, the addition of the power inverter 48 within the transmitter module circuit 18 enables wireless transmission of an electrical power having an increased amplitude. For example, the addition of the inverter sub-circuit 48 enables the transmitter module 12 to transmit an electrical power from about 300 mW to about 600 mW. Without the embodiment of the power stage inverter 48, the transmitter module 12 is configured to transmit electrical power between about 100 mW to about 300 mW. Also, the power stage inverter 48 may be configured to modify the electrical power to be transmitted from a direct current electrical power to an alternating current electrical power.

As shown in FIG. 5, the transmitter module circuit 18 may be configured with a variety of sensing circuits. In addition to the receiver sensing sub-circuit 42, the transmitter module circuit 18 may also be configured with a thermal sense sub-circuit 50 and/or an object sensing sub-circuit 52. As illustrated, the thermal and object sensing sub-circuits 50, 52 are electrically connected to the transmitter master control unit 44. The thermal sense sub-circuit 50 is configured to monitor the temperature within the transmitter module 12. In an embodiment, if the master control unit 44 through the thermal sense sub-circuit 50 detects that the temperature within the transmitter module 12 to have increased from about 20° C. to about 50° C., the transmitter master control unit 44 prevents the operation of the transmitter module 12. In an embodiment, the thermal sensing sub-circuit 50 may comprise a thermocouple, a thermistor, such as a negative temperature coefficient (NTC) resistor, a resistance tempera-

ture detector (RTD), or combinations thereof. In an embodiment, the object detection sub-circuit 52 is electrically connected to the transmitter master control unit 44. In an embodiment, the object detection sub-circuit 52 is configured to detect the presence of an undesired object. In an embodiment, if the master control unit 44 through the object detection sub-circuit 52, detects the presence of an undesired object, the master control unit 44 prevents the operation of the transmitter module 12. In an embodiment, the object detection sub-circuit 52 utilizes an impedance change detection scheme in which the master control unit 44 analyzes a change in electrical impedance observed by the transmitter antenna 20 against a known, acceptable electrical impedance value or range of electrical impedance values. In addition, the object detection sub-circuit 52 may utilize a quality factor change detection scheme in which the master control unit 44 analyzes a change from a known quality factor value or range of quality factor values of the object being detected, such as the receiver antenna 26. In an embodiment, the object detection sub-circuit 52 may comprise an optical sensor, a Hall Effect sensor, or combination thereof. In an embodiment, these sensors, may be monitored using the master control unit 44, a computer (not shown), a comparator (not shown), or other active or passive monitoring methods known to one skilled in the art. Furthermore, the information obtained from the sensors may be used to control operation of the transmitter module 12, the receiver module 14, or the system 10. In addition, the transmitter module circuit 18 may be configured to transmit and receive data 54. In an embodiment, the transmitter module 12 may be configured to communicate to and from the receiver module 14 through modulation and demodulation of the data 54. In an embodiment, the data 54 may comprise information in for form of an electrical voltage and/or an electrical current.

FIG. 6 illustrates an embodiment of the transmitter module circuit 18 of the present application comprising the master control unit 44, the driver circuit 38 comprising a half-bridge driver, the power stage inverter 48 comprising a dual-field effect power stage inverter and the impedance matching circuit 40. A sensing line (SNS) connects the master control unit (MCU) 44 to at least one of the receiver sensing sub-circuit 42, the thermal sensing sub-circuit 50 and the object detection sub-circuit 52.

In an embodiment, as illustrated in FIGS. 7, 8A, and 8B, the impedance matching sub-circuit 40 may comprise a switch capacitance sub-circuit 56. In an embodiment, the switch capacitance sub-circuit 56 comprises an electrical switch 58 and at least two capacitors C_1 and C_2 that are connected in electrical parallel. As shown in FIG. 7, three capacitors C_1 , C_2 , and C_3 are connected in electrical parallel and the switch 58 is shown between capacitors C_1 and C_2 . In an embodiment, the capacitance of the impedance matching circuit 40 may be adjusted by the master control unit 44 by turning the switch 58 on and off, thereby dynamically connecting or disconnecting capacitors within the impedance matching sub-circuit 40 which adjusts the resulting impedance.

FIG. 8A illustrates an alternate embodiment of the switch capacitance sub-circuit 56 in which the switch 58 is electrically connected between capacitors C_4 and C_5 , that are electrically connected in parallel. In addition, inductor L_1 and resistor R_1 are electrically connected to capacitors C_4 and C_5 . FIG. 8B illustrates an alternate embodiment of a switch capacitor sub-circuit 56 comprising first and second switches 58, resistors R_2 , R_3 , and R_4 , capacitors C_6 and C_7 , and diodes D_1 - D_4 that may be incorporated within the

transmitter module circuit 18 or the receiver module circuit 24 to dynamically adjust the impedance of the impedance matching circuit 40.

FIGS. 9-12 are electrical schematic diagrams that illustrate embodiments of the transmitter module circuit 18 of the present application. In an embodiment, the transmitter module circuit 18 comprises the impedance matching sub-circuit 40, an electrical power sub-circuit 60 and a sensing sub-circuit 62, such as the receiver module sensing sub-circuit 42, the thermal sensing sub-circuit 50, the object sensing sub-circuit 52, or combinations thereof. In an embodiment, the electrical power sub-circuit 60 modifies and configures electrical power received from the electrical power source 46 to power the various circuits comprising the transmitter module 12 and provide electrical power for wireless transmission to the receiver module 14.

As illustrated in the embodiments shown in FIGS. 9 and 10, the electrical power sub-circuit 60 comprises the driver sub-circuit 38, such as a half-bridge driver circuit. Alternatively, in lieu of the driver sub-circuit 38, the electrical power sub-circuit 60 may comprise the master control unit 44. Electrical energy from the power source 46 or the transmitter host device 22 is received by the transmitter driver sub-circuit 38 or master control unit 44. The driver sub-circuit 38 or the master control unit 44 is configured to convert a portion of the electrical power from a direct current electrical power to an alternating current electrical power for wireless transmission. In addition, the driver sub-circuit 38 or master control unit 44 may be configured to adjust the amplitude of the voltage of the received electrical power. The driver sub-circuit 38 or master control unit 44 is also configured to provide electrical power to operate the other components that comprise the transmitter module 12.

In addition to the electrical power sub-circuit 60, the embodiments of the transmitter circuit shown in FIGS. 9 and 10 further illustrate different embodiments of the receiver module sensing sub-circuit 42. As illustrated in the embodiment of FIG. 9, the receiver module sensing sub-circuit 42 comprises an envelope tracker sub-circuit 64 comprising resistors R_5 and R_6 electrically connected in series, diode D_5 electrically connected in series to resistor R_5 , and capacitor C_{11} electrically connected between resistors R_5 and R_6 . The envelope tracker circuit 64 is configured to generate an analog voltage signal at node 66 that resides between resistors R_5 and R_6 . In an embodiment, the analog voltage is received by an analog to digital converter (not shown) that is electrically connected to the master control unit 44. In an embodiment, when the receiver module 14 is positioned within the magnetic field emanating from the transmitter antenna 20, the receiver antenna 26 within the receiver module 14 begins to resonate. The presence of the receiver antenna 26 within the magnetic field emanating from the transmitter antenna 20 establishes an electrical coupling between the transmitter and receiver antennas 20, 26 creates a shift in electrical impedance that is detected by the transmitter antenna 20. This change in electrical impedance which results when the receiver antenna 26 of the receiver module 14 is positioned within the magnetic field generates a change in electrical voltage at node 66. Thus, this voltage signal alerts the master control unit 44 of the transmitter module 12 which then begins transmission of electrical energy from the transmitter module 12 to the receiver module 14. For example, if a voltage greater than 0 is detected by the transmitter host device 22 or transmitter master control unit 44 from the voltage sense signal, it is determined that the receiver module 14 is present. In an

11

embodiment, if the receiver module **14** is determined to be present, the driver sub-circuit **38** or the transmitter master control unit **44** is activated and electrical power from the transmitter host device **22** or electrical power source **46** is wirelessly transmitted by the transmitter antenna **20** to the receiver module **14**.

FIG. **10** illustrates an alternate embodiment of the envelope tracker circuit **64**. In addition to resistors R_7 , R_8 , diode **D6**, and capacitor **C15**, the envelope tracker circuit **64** comprises integrated sub-circuit **67** that comprises integrated circuit **68**, capacitor C_{16} and resistors R_9 and R_{10} . In an embodiment, the integrated sub-circuit **67** is configured to convert the analog voltage received at node **69** into a digital signal that is received by the master control unit **44** within the transmitter module circuit **18**.

FIGS. **11** and **12**, illustrate alternate embodiments of the transmitter module circuit **18**. In particular, FIGS. **11** and **12** illustrate alternate embodiments of the electrical power sub-circuit **60**. As shown, the electrical power sub-circuit **60** of FIGS. **11** and **12** comprise a field effect transistor Q_1 (FIG. **11**) and Q_2 (FIG. **12**). In an embodiment, the electrical power sub-circuit **60** of FIGS. **11** and **12** are configured to drive the transmitter antenna **20** to allow for wireless power transfer. In an embodiment, as shown in FIG. **11**, the electrical power sub-circuit **60** comprises the field effect transistor (FET) Q_1 that is turned on and off by a control signal from the master control unit **44** or other signal generator, such as a signal generator that resides within the transmitter host device **22** to create the necessary input to control (FET) Q_1 and the wireless electrical power transfer. In an embodiment as illustrated in FIG. **11**, the electrical power sub-circuit **60** further comprises resistor R_{11} , capacitors C_{11} , C_{18} and inductors L_3 - L_5 .

In an embodiment, as shown in FIG. **12**, the field effect transistor (FET) Q_2 is electrically connected to power amplifier **60** comprising resistors R_{19} - R_{21} , inductor L_6 , and capacitors C_{25} - C_{28} , and integrated circuits **72** and **74** to modify a direct current (DC) voltage input to an alternating current (AC) amplified voltage signal that drives the transmitter antenna **20** to enable wireless electrical power transfer.

In addition to the electrical power sub-circuit **60**, the embodiments of the transmitter module circuit **18** shown in FIGS. **11** and **12** further illustrate various embodiments of the receiver module sensing sub-circuit **42**. As shown in FIG. **11**, the receiver sensing sub-circuit **42** comprises an operational amplifier **76** comprising capacitors C_{21} - C_{23} , resistors R_{12} - R_{17} and diode D_8 . As shown, the change in electrical impedance is detected at node **78** which resides between the transmitter antenna **20** and the impedance matching circuit **40** comprising capacitors C_{19} and C_{20} . The electrical impedance is then converted into an electrical current signal at node **80** by diode D_7 , resistor R_{18} , and capacitor C_{24} . The electrical current signal is received by the operational amplifier **76** which is configured to amplify the sense signal received at node **80**. In an embodiment, the operational amplifier **76** can also be configured to serve as a comparator in which an envelope detector voltage is compared against a set threshold to determine whether the receiver is present and output a digital signal (i.e., a "LOW" (binary 0) or "HIGH" (binary 1) signal) to the master control unit **44**.

The amplified signal is then received by the master control unit **44**. In an embodiment, amplifying the sense signal increases the resolution of detection thereby increasing the accuracy of the detecting for the presence of the receiver module **14**. In yet another embodiment illustrated in

12

FIG. **12**, the receiver sensing sub-circuit **42** comprises an electrical impedance signal conversion sub-circuit **82** and sense control sub-circuit **84**. In an embodiment, the electrical impedance signal conversion sub-circuit **82** comprises diode D_9 and resistor R_{25} which is electrically connected in parallel to capacitor C_{34} . The sense control sub-circuit **84** comprises integrated circuit **86**, resistors R_{22} - R_{27} , and capacitors C_{31} - C_{33} . In an embodiment, the electrical impedance at node **88** is converted to an electrical current signal at node **90** by diode D_9 , resistor R_{25} , and capacitor C_{34} . The electrical current signal is received by integrated circuit **86** within the sense control sub-circuit **84**. In an embodiment, the integrated circuit **86** is configured to convert the electrical current signal into an electrical data signal that sent to the master control unit **44** to notify the presence of the receiver module **14**.

FIG. **13** illustrates a block diagram of an embodiment of the receiver module circuit **24** that resides within the receiver module **14** of the present invention. The receiver module circuit **24** is configured to receive electrical power transmitted wirelessly via near field magnetic coupling from the transmitter antenna **20** of the transmitter module **12**. As illustrated in FIG. **13**, the receiver module circuit **24** comprises the receiver antenna **26**, a receiver impedance matching sub-circuit **92**, a rectifier **94**, and a voltage regulator **96**. As shown, the receiver antenna **26** is electrically connected to the receiver impedance matching circuit **92** that is electrically connected to the rectifier **94** and the voltage regulator **96**. In an embodiment, the receiver impedance matching circuit **92** is configured to adjust the electrical impedance of the receiver module **14** to match the electrical impedance of the transmitter module **12**. The rectifier **94** is configured to modify the received electrical power from an alternating current electrical power to a direct current electrical power. The voltage regulator **96** is configured to adjust the amplitude of the electrical voltage of the wirelessly received electrical power.

FIG. **14** is an electrical schematic diagram of the embodiment of the receiver module circuit **24** shown in FIG. **13**. As shown, the receiver antenna **26** comprising inductor L_9 is electrically connected to the impedance matching sub-circuit **92** comprising capacitors C_{35} - C_{37} . The impedance matching sub-circuit **92** is electrically connected to the rectifier **94** that comprises diodes D_{10} - D_{13} and the voltage regulator **96** comprising a low dropout linear voltage regulator.

FIG. **15** is a block diagram that illustrates an alternate embodiment of the receiver module circuit **24** within the receiver module **14** of the present application. As shown the receiver module circuit **14** comprises the receiver antenna **26**, the electrical impedance matching sub-circuit **92**, a voltage doubler sub-circuit **98**, the voltage regulator **96** and a receiver master control unit **100**. In an embodiment, the receiver antenna **26** is electrically connected to the electrical impedance matching circuit **92** which is configured to dynamically adjust and match the electrical impedance of the receiver antenna **26** to a characteristic impedance of the power generator or the load at a driving frequency of the transmitter antenna **20**. In the embodiment, the impedance matching circuit **92** is electrically connected to the voltage doubler sub-circuit **98** which is designed to rectify the wirelessly received electrical power from an alternating current electrical power to a direct current electrical power. The voltage doubler circuit **98** is also configured to increase, i.e., double, the voltage of the wirelessly received electrical power. As further shown in the embodiment, the voltage doubler sub-circuit **98** is electrically connected to the volt-

13

age regulator **96** which is designed to further adjust the amplitude of the voltage of the wirelessly received electrical power. The voltage regulator **96** is electrically connected to the receiver master control unit **100**. In an embodiment, the receiver master control unit **100** is configured to operate the receiver module circuit **24** within the receiver module **14**. In an embodiment, the electrical power wirelessly received from the transmitter module **12** and modified by the receiver module circuit **24** is used to power the host device and/or may be used to electrically charge an electrical storage device **102**, such as an electrochemical cell or capacitor.

FIG. **16** illustrates an electrical schematic diagram of the receiver module circuit **24** shown in FIG. **15**. As shown the receiver antenna **26** which comprises inductor L_{10} , is electrically connected to the electrical impedance matching sub-circuit **92** which comprises at least one capacitor. As illustrated, the electrical impedance matching sub-circuit **92** comprises capacitors C_{40} - C_{42} . As further illustrated in FIG. **16**, the electrical impedance matching circuit **92** is electrically connected to the voltage doubler sub-circuit **98** which comprises diodes D_{14} , D_{15} and capacitor C_{43} . Incorporation of the voltage doubler sub-circuit **98** within the receiver module circuit **24** rectifies the wirelessly received electrical power and increases the amount of electrical power that can be transmitted across the separation distance **16** between the transmitter and receiver modules **12**, **14**. In addition, the voltage regulator sub-circuit **97** which comprises voltage regulator **96** is electrically connected to resistors R_{28} - R_{30} and capacitors C_{44} and C_{45} is electrically connected to the voltage doubler sub-circuit **98**.

In an embodiment, the voltage doubler sub-circuit **98** allows for increased system efficiency due to a decrease in the electrical impedance experienced by the receiver module circuit **24**. Experimental results indicate that incorporation of the voltage doubler sub-circuit **98** within the receiver module circuit **24** decreases the electrical impedance of the circuit **24** from about 301Ω to about 31Ω under a no load condition and decreases the electrical impedance from about 154Ω to about 4.9Ω under full load conditions, a decrease in electrical impedance by as much as 97 percent. Since the voltage doubler sub-circuit **98** significantly reduces the electrical impedance of the receiver module circuit **24**, incorporation of the voltage doubler sub-circuit **98** within the receiver module circuit **24** thus provides for the transmission of a greater amount of electrical power across a module separation distance **16** at a given frequency. Furthermore, the voltage doubler sub-circuit **98** allows for decreased component sizes and increased system performance. Moreover, the voltage doubler sub-circuit **98** allows for the operation of the system **10**, specifically, wireless transfer of electrical energy and data, across a wider module separation distance **16** in comparison to other rectifying topologies (e.g., a full wave rectifier). For example, the receiver module **14** of the present invention configured with the voltage doubler sub-circuit **98** enables wireless transfer of electrical energy and/or data across a module separation distance **16** from about 0.5 mm to about 5 mm. In comparison, a receiver module that is not configured with the voltage doubler sub-circuit **98** allows for the transfer of electrical energy and/or data across a module separation distance **16** from about 0.5 mm to about 2 mm. The voltage doubler sub-circuit **98** thus enables an increase of the module separation distance **16** by about 100 percent or about double the module separation distance **16**. Furthermore, at closer separation distances, the electrical impedance of the gate driver or FET power stage is reduced allowing for increased wireless electrical power delivery.

14

FIG. **17** illustrates a block diagram of an embodiment of the receiver module circuit **24** of the present application. As shown, in addition to the receiver master control unit **100**, the receiver antenna **26**, the rectifier **94** and voltage regulator **96**, the receiver module circuit **24** may be configured with a thermal sense sub-circuit **104**. In an embodiment, the thermal sense sub-circuit **104** is configured to monitor the temperature within the receiver module **14**. In an embodiment, if the receiver master control unit **100** through the thermal sense sub-circuit **104** detects that the temperature within the receiver module increases from about 20°C . to about 50°C ., the receiver master control unit **100** prevents the operation of the receiver module **14**. In addition, the receiver module **14** may be configured to receive and transmit data to and from the transmitter module **12**. In an embodiment, the receiver module **14** may be configured to modulate and demodulate data from the transmitter module **12** to enable communication therebetween. In an embodiment, the wireless connector system **10** of the present application may be configured for in-band communication, such as in-band amplitude, phase, and/or frequency shift keying communication. In addition, the wireless connector system **10** of the present application may be configured for out of band communication. In band communication is based on the transfer of information/data across a wireless power signal. The wireless power signal is the carrier frequency, and the different methods (amplitude, frequency, and phase) modulate this carrier frequency to deliver the data. Out of band communication utilizes an external signal that is separate from the wireless power signal to deliver data/communication.

FIGS. **18A-18D** illustrate embodiments of impedance matching sub-circuits **40**, **92** which may be utilized within the receiver module circuit **24** and/or the transmitter module circuit **18**. As shown in the embodiment of FIG. **18A**, the impedance matching circuit **40**, **92** may comprise two capacitors C_{46} and C_{48} connected in electrical parallel and a shunt capacitor **C47** electrically connected between capacitors C_{46} and C_{48} . FIG. **18B** illustrates an embodiment in which a shunt capacitor C_{50} is electrically connected in parallel between capacitors C_{49} and C_{51} . FIG. **18C** illustrates an embodiment in which the electrical impedance matching circuit may comprise at least one capacitor C_{52} electrically connected to the positive side of the receiving or transmitter antenna. FIG. **18D** illustrates an embodiment in which two capacitors C_{53} and C_{54} are each electrically connected to the positive and negative terminals, respectively of the receiving or transmitter antenna.

In an embodiment, incorporating a shunt capacitor such as those shown in FIG. **18A** or **18B** enables electrical power to be transmitted across a greater separation distance **16**. In an embodiment, the shunt capacitor is used to boost the received voltage into the receiver rectifier **34** in comparison to a series only tuning topology. The shunt capacitor allows the resistance of the antenna to be modified in order to increase the amount of electrical power that can be transferred at a certain distance as well as increase the maximum operating distance of the system. In an embodiment, incorporating the shunt capacitor, as shown in FIG. **18A** or **18B**, within the electrical impedance matching sub-circuit **92** of the receiver module circuit **24** enables electrical power to be wirelessly transmitted over a 2 mm separation distance. The inventors have discovered that without the use of a shunt capacitor within the electrical impedance matching sub-circuit **92** of the receiver module circuit **24** of the receiver module **14**, wireless transmission of the electrical power spans a shorter separation distance. For example, the inven-

15

tors have discovered that the shunt capacitor enables electrical power to be wirelessly transmitted over a separation distance 16 that is about 50 percent longer in comparison to a receiver module that does not comprise a shunt capacitor for the same amount of electrical power transmitted.

FIGS. 19-22 illustrate embodiments of the wireless connector system 10 comprising the transmitter module 12 and the receiver module 14. As illustrated, the transmitter module 12 comprises a transmitter module housing 106 that encases the transmitter module circuit 18 and transmitter antenna 20 therewithin. The receiver module 14 comprises a receiver module housing 108 that encases the receiver module circuit 24 and receiver antenna 26 therewithin. In an embodiment, either or both the transmitter module housing 106 and the receiver module housing 108 are hermetically sealed. In an embodiment, at least one of the transmitter module housing 106 and the receiver module housing 108 may be composed of a polymeric material, a metal, a ceramic material or combinations thereof. In addition, either or both the transmitter module 12 and receiver module 14 may be immersed within an encapsulate material (not shown). This encapsulate material helps protect the circuitry of the modules 12, 14 and helps ensure a hermetic seal. It is noted that during operation of the wireless connector system 10, the transmitter and receiver modules 12, 14 are positioned such that the module separation distance 16 spans between the modules 12, 14. In an embodiment, the module separation distance 16 may range from about 0.1 mm to about 5 mm. In an embodiment, the module separation distance or gap 16 between the transmitter and receiver modules 12, 14 during operation of the system ranges from about 0.1 mm to about 2 mm. In an embodiment, the wireless connector system 10 of the present invention is configured to wirelessly transmit between about 1 mW to about 200 mW at a frequency greater than 5 MHz. In an embodiment, the wireless connector system 10 is configured to wirelessly transmit between about 1 mW to about 200 mW at a frequency that ranges from about 1 MHz to about 50 MHz between the transmitter and receiver modules 12, 14. In an embodiment, the wireless connector system 10 may operate at any frequency or frequencies, which may include, but is not limited to, 100 kHz, 6.78 MHz, 10 MHz, 13.56 MHz, 27.12 MHz, 433 MHz, 915 MHz, 1.8 GHz, 2.4 GHz, 60 GHz, and 5.7 GHz. In addition, such frequencies may include licensed frequency bands.

In an embodiment both the transmitter and receiver modules 12, 14 are of a compact size. In an embodiment, the transmitter module 12 has a length 110 that extends from a transmitter module proximal end 112 to a transmitter module distal end 114. The transmitter module 12 has a transmitter module width 116 oriented about perpendicular to the length 110. In an embodiment, the receiver module 14 has a receiver module length 120 that extends from a receiver module proximal end 122 to a receiver module distal end 124. The receiver module 14 comprises a receiver module width 126 oriented about perpendicular to the length 120. As illustrated in FIG. 19, in an embodiment, the transmitter module 12 comprises a transmitter module height 118 that extends about perpendicular to transmitter module length 110. In an embodiment, the receiver module 14 comprises a receiver module height 128 that extends about perpendicular to the receiver module length 120.

In an embodiment, either or both the transmitter and receiver modules 12, 14 are configured to be surface mounted. In an embodiment, as shown in FIG. 22, a plurality of brackets 130 mechanically support and electrically connect the modules 12, 14 to a circuit board 132 of the

16

respective host device. In addition, as illustrated in FIG. 21, each of the modules 12, 14 may comprise a plurality of castellations 134 that reside within an exterior surface of the transmitter module housing 106 and/or the receiver module housing 108. These castellations 134 provide a space within which a surface mount (not shown) may be positioned therewithin to mechanically secure the modules 12, 14 to a surface and provide an electrical connection to the host device.

In an embodiment, as shown in FIG. 23, at least one of the transmitter and receiver modules 12, 14 comprises a plurality of metal pads 136 positioned at an edge of an exterior surface of the module housing 106, 108. These metal pads 136 are designed to provide electrical contact of the module 12, 14 to a circuit board 132 or host device 22, 28. Furthermore, at least one of the transmitter and receiver modules 12, 14 may comprise at least one post 138 that outwardly extends from the exterior surface of the module housing 106, 108. These posts 138 mechanically support and secure the at least one transmitter module and receiver module 12, 14 to a circuit board 132 or a host device 22, 28. In addition, the modules 12, 14 may be electrically connected to circuit boards of their respective host devices through the use of welding, soldering, fasteners, such as pins, spring contacts, and the like.

FIG. 24 illustrates an embodiment of the construction within the housing 106, 108 of the respective modules 12, 14. In an embodiment each of the modules 12, 14 is constructed with a respective transmitter or receiver antenna 20, 26, and a module circuit board residing within the housing 106, 108 of the transmitter or receiver module 12, 14. In an embodiment, a transmitter module circuit board 140 resides within the transmitter module housing 106 and a receiver module circuit board 142 resides within the receiver module housing 108. In an embodiment, the transmitter antenna 20 and receiver antenna 26 resides within the housing 106, 108 at the distal end of their respective modules 12, 14. In an embodiment, the transmitter module circuit board 140 and the receiver module circuit board 142 reside within their respective transmitter module and receiver module housing 106, 108 at the proximal end of their respective modules 12, 14. In an embodiment, the transmitter antenna 20 is electrically connected to the transmitter module circuit board 140 and the receiver antenna 26 is electrically connected to the receiver module circuit board 142 using a flex connector, a board to board connector, a pin and socket connector, a spring contact connector, a pogo pin connector, a through-hole pin solder connector, a soldered wire connection, or a combination thereof.

In an embodiment, at least one of the transmitter and receiver modules 12, 14 may be constructed having a spacer 144 composed of an electrically insulating, non-magnetic material positioned within the housing 106, 108 of the transmitter or receiver module 12, 14. In an embodiment, the at least one spacer 144 is positioned between the transmitter or receiver module circuit board 140, 142 and the transmitting or receiving antenna 20, 26, respectively within the housing 106, 108. In an embodiment, at least one shielding material 146 may be positioned within the housing 106, 108 of either or both the transmitter and receiver modules 12, 14. In an embodiment, the at least one shielding material 146 is positioned between the transmitter or receiver module circuit board 140, 142 and the transmitter or receiver antenna 20, 26, respectively within the housing 106, 108. In an embodiment, the at least one shielding material 146 may be positioned between the transmitter or receiver module circuit board 140, 142 and the at least one spacer 144. In an

embodiment, the at least one shielding material **146** may be positioned between the at least one spacer **144** and the transmitter or receiver module antenna **20, 26**. As illustrated in the example shown in FIG. **25**, the transmitter or receiver antenna **20, 26** is positioned at the distal end of the respective modules **12, 14**. A spacer **144** is positioned proximal of the antenna **20, 26**, the shielding material **146** is positioned proximal of the spacer **144** and the transmitter or receiver module circuit board **140, 142** is positioned at the proximal end of the module **12, 14**. In an embodiment, during operation of the wireless connector system **10** of the present invention, the respective antennas **20, 26** of the transmitter and receiver modules **12, 14** are positioned facing each other across the module separation distance **16**. Table I below further illustrates the various sequences of positions within the housing **106, 108**. It is noted that Position 1 is the proximal end **112, 122** of the module and Position 4 is the distal end **114, 124** of the module **12, 14**, respectively. Position 2 is distal of Position 1 and Position 3 is distal of Position 2.

TABLE I

Example	Position 1	Position 2	Position 3	Position 4
1	Circuit Board	Spacer	Spacer	Antenna
2	Circuit Board	Shield	Spacer	Antenna
3	Circuit Board	Shield	Shield	Antenna
4	Circuit Board	Spacer	Shield	Antenna

In an embodiment, the circuit board may either be the transmitter module circuit board **140** or the receiver module circuit board **142**, the antenna may either be the transmitter antenna **20** or the receiver antenna **26**. The spacer **144** may comprise an electrically insulative material such as air, FR4, a polymeric material or a combination thereof. The shielding material **146** may comprise a ferrite material, a metal, or a combination thereof. It is noted that positioning the shielding material **146** closer to the transmitter or receiver antenna **20, 26**, such as detailed in Examples 3 and 4, of Table I, provides an increase in electrical inductance that results in an improved mutual inductance between transmitter and receiver modules **12, 14**.

As further illustrated in FIG. **25**, the electrically conductive bracket **130** electrically connects the circuit boards **140, 142** of the respective transmitter and receiver modules **12, 14** to the host device. As illustrated in the embodiments shown in FIGS. **25** and **26**, the host device is a circuit board. FIG. **26** illustrates a further embodiment in which the electrically conductive bracket **130** is positioned between position 1 and position 2. As specifically illustrated in FIG. **26**, the bracket **130** is positioned between the transmitter or receiver circuit board **140, 142** and the shielding material **146**. Alternatively, the bracket **130** may be positioned between the transmitter or receiver circuit board **140, 142** and the spacer **144**.

FIGS. **27-34** illustrate an alternate embodiment of a transmitter module **148** and a receiver module **150** having a hybrid rigid flex printed circuit board construction. In this construction, a module power circuit board, of either a transmitter module power circuit board **152** or a receiver module power circuit board **154** is electrically connected to an antenna assembly of either a transmitter antenna assembly **156** or a receiver antenna assembly **158**, respectively

(FIG. **27**). An electrical bridge or electrical connector **160** extends between and electrically connects the antenna assembly **156, 158** and the module power circuit board **152, 154**. This construction can also be used to provide a connection between the transmitter module circuit board **140** and the transmitter antenna **20**, and/or the receiver module circuit board **142** and the receiver antenna **26** by encapsulating one or more flexible printed circuit (FPC) layers that comprise the transmitter or receiver antenna **20, 26** inside one or more rigid (FR4) circuit board layers.

FIG. **27** illustrates an embodiment of the components that comprise the transmitter or receiver module **148, 150** having a hybrid rigid flex printed circuit board construction of the present invention. As shown, the module power circuit board of either the transmitter module power circuit board **152** or the receiver module power circuit board **154** is electrically connected to the antenna assembly of either the transmitter antenna assembly **156** or the receiver antenna assembly **158**, respectively, by the electrical connector **160**. In an embodiment, the electrical bridge or electrical connector **160** is flexible and is capable of bending. In an embodiment, the electrical bridge or electrical connector **160** comprises one or more sheets of copper, a circuit connector ribbon, flexible ribbon, an electrical flex connector, an electrically conductive ribbon, or combinations thereof.

In an embodiment, the transmitter module power circuit board **152** and the receiver module power circuit board **154** comprise a substrate **166** such as FR4 or printed circuit board that is substantially rigid and supports a variety of transmitter module power circuit board electrical components **162** or receiver module power circuit board electrical components **164**. In an embodiment, these electrical components **162, 164** may be surface mounted to an exterior surface of the transmitter module power circuit board **152** and the receiver module power circuit board **154**, respectively.

In an embodiment, the transmitter and receiver antenna assemblies **156, 158**, comprises a substrate **168**, such as a rigid printed circuit board or FR4 board that supports the transmitter or receiver antenna **20, 26**. As illustrated in FIG. **27**, the substrate **168** supports either the transmitter or receiver antenna **20, 26**. A shielding material **170**, such as a layer of ferrite material, is positioned over the transmitter or receiver antenna **20, 26**. In an embodiment, the shielding material **170**, such as a sheet of ferrite material may be laminated or adhered to the transmitter or receiver antenna **20, 26** with an adhesive.

In an embodiment, as illustrated in FIG. **28**, the antenna assembly **156, 158** is folded over the module power circuit board **152, 154**, to form a transmitter module assembly **172** or a receiver module assembly **174**, respectively. In an embodiment, as shown in FIG. **29**, a second shielding material **176**, such as a ferrite material, may be positioned between the antenna assembly **156, 158** and the module power circuit board **152, 154**. This construction provides many benefits that include, but are not limited to:

1. A continuous connection between the antenna assembly **156, 158** and the module power circuit board **162, 164**. In an embodiment, the antenna assembly **156, 158** may be positioned such that conductive traces of the antenna **20, 26** directly connect to the module power circuit board **162, 164**. This construction reduces the overall electrical impedance.
2. The antenna assembly **156, 158** and module power circuit board **162, 164** comprise a single structure (i.e., the transmitter module assembly **172** or the receiver module assembly **174**), thus increasing connection reli-

ability and manufacturing yield, and reducing the number of discrete components, complexity and assembly cost.

3. The structure enables a more simplified manufacturing process that allows for large scale manufacture.
4. Testing is simplified as both, the antenna and the power board can be tested at the same time.

FIG. 29 illustrates an exploded view of an embodiment of the transmitter module 148 or the receiver module 150 of the present application comprising the receiver or transmitter module assembly 172, 174 respectively. As shown in the embodiment, the transmitter 148 and/or the receiver module 150 comprise a spacer or housing structure 178 that separates the transmitter or receiver antenna assembly 156, 158 from the transmitter or receiver module power circuit board 152, 154, respectively. Alternatively, the housing structure 178 may provide a space therewithin in which the transmitter or receiver module assembly 172, 174 is positioned.

In an embodiment, the housing structure 178 comprises an electrically insulative material and acts as a spacer that separates the transmitter or receiver module assembly 172, 174 from additional shielding material that may be positioned on an exterior surface of the housing structure 178. As shown in the embodiment illustrated in FIG. 29, a third and fourth shielding material 180, 182, such as a ferrite material, may be positioned on the exterior surface of the housing structure 178. In an embodiment a layer of a rigid circuit board material 184 may be positioned in contact with the third and fourth shielding materials 180, 182 to provide added structural support. In an embodiment, the transmitter module 148 or the receiver module 150 may comprise a retention fastener 186 and/or a locating post 188 that outwardly extend from the housing sidewall. In an embodiment, the retention fastener 186 and/or the locating post 188 are used to precisely position the module 148, 150 on the transmitter module or receiver module host device 22, 28, such as a printed circuit board. In an embodiment, the retention fastener 186 and/or the locating post 188 retain the transmitter module 12 and/or the receiver module 14 to the respective host device 22, 28. Furthermore, the retention fastener 186 and/or the locating post 188 may be electrically connected to the respective host device 22, 28.

FIG. 30 illustrates an embodiment of an assembled transmitter or receiver module 148, 150 comprising two retention fasteners 186 and the locating post 188 that outwardly extend from the module housing structure 178. As shown, the housing structure 178 is positioned between the transmitter or receiver module power circuit board 152, 154 and the transmitter or receiver antenna assembly 156, 158. In this way, the retention fasteners 186 improve component retention that provides for balanced soldering and helps prevent potential component delamination during a solder reflow process. Furthermore, the retention fasteners 186 and the locating post 188 provide alignment guides for installation of the modules 148, 150.

FIG. 30A illustrates a cross-sectional view of the embodiment of the assembled module 12, 14 shown in FIG. 30. As shown, the module circuit board 140, 142 is positioned opposed from the antenna assembly 156, 158. The module spacer or housing structure 178 is positioned therebetween. In an embodiment, the spacer 178 may be of a solid structure having various cutouts for the positioning of the electrical components 162, 164. Alternatively, the spacer 178 may be constructed having a void space therewithin for the positioning of the electrical components 162, 164. In an embodiment, the spacer 178 may be constructed having a void space therewithin for the positioning of the module circuit board

140, 142 and the antenna assembly 156, 158. As illustrated, an adhesive layer 187 may be to adhere the module circuit board 140, 142 and the antenna assembly 156, 158 to the spacer 178.

FIGS. 31-34 illustrate various embodiments of the transmitter and receiver modules 148, 150 shown in FIGS. 27-30, mounted to a host device 22, 28 such as a circuit board. As shown, the modules 148, 150 may comprise a plurality of pads 190 that are electrically connected to the host device circuit board. Furthermore, as illustrated in FIG. 34, the modules 148, 150 may comprise alignment legs 192 (FIG. 34) that outwardly extend from the housing structure 178. In an embodiment, the alignment legs 192 provide an additional alignment aid and provide additional mechanical stability when the modules 148, 150 are mounted into an opening in the board 194 of the host device 22, 28. In an embodiment shown in FIG. 34, the transmitter and receiver modules 148, 150 may be positioned within an opening 194 that extends through the thickness of the host device circuit board 22, 28.

FIG. 35 illustrates a top view of an embodiment of an antenna 20, 26 that may be used with either of the transmitter module 12, 148 or the receiver module 14, 150. In an embodiment, the antenna 20, 26 is of a flat spiral coil configuration. In the embodiment shown, the antenna comprises four layers of alternating of an electrical conductor and electrically insulating layers integrated into a printed circuit board (PCB) or flexible circuit board (FPC). As shown, the antenna 20, 26 comprises two antenna segments that are electrically connected in series. As shown, the antenna 20, 26 is constructed having five turns of a copper trace 196 deposited on the surface of an insulative substrate 198 with a gap 200 of 15 to 200 microns between each trace 196. Each segment comprises an electrical conductor (e.g., trace 196) positioned on an insulative substrate 198 in an electrical parallel configuration. Non-limiting examples can be found in U.S. Pat. Nos. 2017/0040690, 2017/0040692, 2017/0040107, 2017/0040105, 2017/0040696, and 2017/0040688 all to Peralta et al., 2017/0040691, 2017/0040694 to Singh et al., 2017/0040693 to Luzinski and 2017/0040695 to Rajagopalan et al. all of which are assigned to the assignee of the present application and incorporated fully herein.

In addition, the antenna 20, 26 may be constructed having a multi-layer-multi-turn (MLMT) construction in which at least one insulator is positioned between a plurality of conductors. Non-limiting examples of antennas having an MLMT construction that may be incorporated within the transmitter module 12, 148 and/or the receiver module 14, 150 may be found in U.S. Pat. Nos. 8,610,530, 8,653,927, 8,680,960, 8,692,641, 8,692,642, 8,698,590, 8,698,591, 8,707,546, 8,710,948, 8,803,649, 8,823,481, 8,823,482, 8,855,786, 8,898,885, 9,208,942, 9,232,893, 9,300,046, all to Singh et al., assigned to the assignee of the present application are incorporated fully herein. It is also noted that other antennas such as, but not limited to, an antenna configured to send and receive signals in the UHF radio wave frequency such IEEE standard 802.15.1 may be incorporated within the wireless connector system 10 of the present invention.

The wireless connector system 10 is designed to operate in an efficient, stable and reliable manner to satisfy a variety of operating and environmental conditions. The system is designed to operate in a wide range of thermal and mechanical stress environments so that data and/or electrical energy is transmitted efficiently and with minimal loss. In addition, the wireless connector system 10 is designed with a small form factor using a fabrication technology that allows for

21

scalability, and at a cost that is amenable to developers and adopters. In addition, the wireless connector system 10 is designed to operate over a wide range of frequencies to meet the requirements of a wide range of applications.

In an embodiment the system may transmit electrical power on the order of about 100 μW to about 10 W. In another embodiment, electrical power around about 100 W may also be transmitted. Specifically considering near field magnetic coupling (NFMC) as the mechanism of wireless power transfer between the transmitter module 12, 148 and the receiver module 14, 150, it is well known that smaller sizes are generally more easily achievable if a higher operating frequency is selected. This is due to the inverse relationship of the required mutual inductance and the frequency of operation, as indicated by the following equation:

$$M = \frac{V_{induced}}{j * \omega * I_{Tx}}$$

Where:

$V_{induced}$ is induced voltage on the receiver coil
 I_{Tx} is the AC current flowing through the transmitter coil
 ω is the operating frequency multiplied by 2π

Since the required mutual inductance increases in order to enable the wireless transfer of electrical energy having increased, it is necessary to increase the inductance or coupling of the transmitter or receiver while minimizing AC losses. Mutual inductance can be calculated by the following relationship:

$$M = k * \sqrt{L_{Tx} * L_{Rx}}$$

M is the mutual inductance of the system
 k is the coupling of the system
 L_{Tx} is the inductance of the transmitter coil
 L_{Rx} is the inductance of the receiver coil

As the form factor of the antenna coil is reduced, attaining the required inductance on either the receiver or transmitter is accompanied by an increase in antenna coil resistance as the high number of turns required leads to a reduction in trace width. This increase in resistance typically reduces the quality factor of the coil and overall coil to coil efficiency of the system where the Quality factor is defined as:

$$Q = \frac{\omega * L}{R}$$

Where:

Q is the quality factor of the coil
 L is the inductance of the coil
 ω is the operating frequency of the coil in radians/s.
 Alternatively, the frequency of operation in Hz is ω divided by 2π
 R is the equivalent series resistance at the operating frequency

And coil to coil efficiency is defined as:

$$Eff = \frac{k^2 * Q_{Rx} * Q_{Tx}}{(1 + \sqrt{(1 + k^2 * Q_{Tx} * Q_{Tx})})^2}$$

Where:

Eff is the antenna to antenna efficiency of the system

22

k is the coupling of the system
 Q_{rx} is the quality factor of the receiver
 Q_{tx} is the quality factor of the transmitter

In an embodiment, the ferrite shield may be incorporated within the antenna structure to improve antenna performance. Selection of the ferrite shield material is dependent on the operating frequency as the complex magnetic permeability ($\mu = \mu' - j * \mu''$) is frequency dependent. The material may be a sintered flexible ferrite sheet or a rigid shield and may be composed of varying material compositions. Examples of materials may include, but are not limited to, zinc comprising ferrite materials such as manganese-zinc, nickel-zinc, copper-zinc, magnesium-zinc, and combinations thereof.

In addition, depending on the operating frequency and power requirements of the wireless connector system 10, a hybrid Litz wire and PCB coil antenna construction combination may be necessary to efficiently transfer power. In an embodiment, a hybrid Litz wire and PCB coil combination may comprise the transmitter antenna 20 or the receiver antenna 26 of a wrapped Litz wire construction and the other of the transmitter antenna 20 or the receiver antenna 26 may be constructed having a coil disposed on a surface of a circuit board such as the antenna shown in FIG. 35. Lower operating frequencies on the order of 100 kHz to several MHz range may require a certain mutual inductance between the transmitter and receiver antenna 20, 26. This is attainable by using a transmitter antenna 20 of a Litz wire construction having a novel ferrite core in combination with a receiver antenna 26 comprising a coil disposed on a surface of a circuit board, such as the antenna shown in FIG. 35.

In order to increase mutual inductance, the coupling and/or inductance of the transmitter module 12, 148 or the receiver module 14, 150 must be increased. However, due to the small form factor constraints, coupling is limited by the physical size of the connector modules. It is noted that using transmitter and receiver antennas 20, 26 of a construction comprising a coil disposed on the surface of a circuit board, such as the antenna shown in FIG. 35, may increase inductance and increase the resistance of the antenna coils thereby decreasing the quality factor Q and antenna to antenna efficiency.

In an embodiment, the wireless connector system 10 comprising a transmitter module 12, 148 having a transmitter antenna 20 of a Litz-wire construction and a shielding material and a receiver module 14, 150 having a receiver antenna 26 comprising a coil disposed on a surface of a circuit board (FIG. 35) may be used to increase the coupling and mutual inductance of a small form factor of the wireless connector system 10. To achieve a higher antenna to antenna efficiency, this configuration may be used to achieve the necessary power transfer while maintaining high Q factor at lower frequencies. These improvements may also increase the overall performance of the wireless connector system 10 having a relatively small form factor.

The choice of coil design and construction is determined by a combination of the following electrical and magnetic parameters:

- Inductance
- ESR (equivalent series resistance) at operating frequency
- Coupling (k)
- Mutual inductance (M)

For lower operating frequencies, i.e., from about 100 kHz to about 10 MHz, and for achieving increased power transmission on the order of about 0.1 mm to about 100 mm, this particular antenna topology is beneficial. For example, per the mutual inductance equations, if the power to be delivered

to a load is constant, while the operating frequency decreases, the mutual inductance between the transmitter and receiver antenna coils increases at a constant transmit current. Table II illustrates the improvement in mutual inductance. Table III illustrates the improvement in coupling and Table IV illustrates the improvement in antenna to antenna efficiency.

TABLE II

Transmitter Antenna Construction	Transmitter Antenna Shield	Receiver Antenna Construction	M (μH)
Coil on FR4 PCB	Sheet	Coil on FR4 PCB	0.35
Litz Wire	T-Core	Coil on FR4 PCB	1.35

TABLE III

Transmitter Antenna Construction	Transmitter Antenna Shield	Receiver Antenna Construction	Coupling
Coil on FR4 PCB	Sheet	Coil on FR4 PCB	0.26
Litz Wire	T-Core	Coil on FR4 PCB	0.29

TABLE IV

Transmitter Antenna Construction	Transmitter Antenna Shield	Receiver Antenna Construction	Antenna to Antenna efficiency
Coil on FR4 PCB	Sheet	Coil on FR4 PCB	57.9%
Litz Wire	T-Core	Coil on FR4 PCB	80.8%

In addition, if the system 10 is operated at a higher frequency, i.e., on the order of about 1 MHz or greater, the required mutual inductance will be reduced, thereby allowing for smaller transmitter and receiver antennas 20, 26 and modules 12, 14, 148, 150. As defined herein shielding material is a material that captures a magnetic field. An example of which is a ferrite material. In the embodiments detailed in Tables II-IV, a sheet of ferrite material is positioned directly adjacent to the transmitter antenna 20, for example, behind the transmitter antenna 20. As defined herein a "T-Core" shielding material is a magnetic field shield assembly comprising a sheet of shielding material, such as a ferrite material, placed directly behind the transmitter or receiver antenna 20, 26 and an additional second shielding material, such as a ferrite material, placed within the inside area of a coil in the plane of the transmitter or receiver antenna 20, 26. Furthermore, the transmitter module 12, 148 or the receiver module 14, 150 may be constructed having the respective transmitter or receiver antennas 20, 26 comprising a "C-core" shielding material in which the shielding material, such as a ferrite material, configured similarly to the letter "C", is positioned adjacent to the antenna 20, 26. In addition, the transmitter module 12, 148 or the receiver module 14, 150 may be constructed having the respective transmitter or receiver antennas 20, 26 comprising a "E-core" shielding material in which the shielding material, such as a ferrite material, configured similarly to the letter "E", is positioned adjacent to the antenna 20, 26.

In an embodiment, the wireless connector system 10 rated for a maximum 200 mW received DC power, can be configured having each transmitter module 12, 148 and receiver module 14, 150 comprise a form factor of about 11 mm×4 mm, and operate at a frequency that ranges from about 2 MHz to 30 MHz. However, this presents a key challenge in the antenna design. It is not typically cost effective, nor is it particularly reliable, to implement a wire wound Litz antenna that can fit in a footprint as small as 11 mm×4 mm. Furthermore, as the operating frequency is increased to about 6 MHz and greater, wire wound Litz antenna coils may not be suitable in terms of performance.

Utilizing relatively small sized printed circuit board or flexible printed circuit board (PCB/FPC) based coil-antennas allow for appropriate stackups, appropriate trace widths, gap widths and copper (or other conductive material) depths that are more suitable for higher frequencies. Further, printed circuit board and flex printed circuit board based coil-antennas are highly integrated into the PCB fabrication process, thereby allowing for integration with the rest of the circuitry. This also allows for the integration of MLMT antenna designs to reduce ESR and improve the Q of the antennas.

Furthermore, utilizing coils in a layered approach allows for other fabrication processes, for example, printing, printing on fabrics, semiconductor fabrication processes, such as a low temperature co-fired ceramic (LTCC) process, a high temperature co-fired ceramic (HTCC) process, and the like.

Small form factor PCB coil designs are suitable at higher operating frequencies due to a lower required inductance while maintaining a low coil ESR to minimize the power dissipated in the transmit and receive coils. Printed circuit board (PCB) coil antennas offer additional benefits from a manufacturing, cost and assembly standpoint compared to wire-wound antenna coil solutions. For applications with a strict requirement for overall assembly thickness, printed circuit board (PCB) coil antennas are preferred due to the reduced thickness possible even with multilayer construction.

The ferrite shield material selected for the coil combination also depends on the operating frequency as the complex magnetic permeability ($\mu = \mu' - j\mu''$) is frequency dependent. The material may be a sintered flexible ferrite sheet or a rigid shield and be composed of varying material compositions.

It is noted that the construction of the antenna 20, 26 is non-limiting. The antenna that is incorporated within a module may comprise magnetic wires or have a stamped metal construction. Furthermore, the antenna 20, 26 may utilize thick film, thin film or other printing fabrication technologies in its construction.

In an embodiment, incorporation of a transmitter or receiver antenna 20, 26 having a multi-layer-multi-turn (MLMT) construction significantly reduces the equivalent series resistance (ESR) of the respective transmitter module 12, 148 and receiver modules 14, 150 and the wireless connector system 10 of the present invention. The inventors have discovered that incorporation of at least one transmitter and receiver antenna 20, 26 having a multi-layer-multi-turn (MLMT) construction reduces equivalent series resistance (ESR) of the transmitter or receiver module 12, 14 by about 50 percent.

Furthermore, reducing ESR improves the overall system efficiency and reduces heating in the antenna 20, 26 and the system 10 by reducing the ($I^2 \times R$) losses in the coil. Table V shown below details the measured ESR for two multi-layer-multi-turn (MLMT) antenna designs in comparison to an antenna constructed comprising Litz wire wrapped around

an inductor. As shown in Table V below, the antenna constructed with an MLMT design exhibited a lower inductance, (0.60 μH) and a lower equivalent series resistance (ESR) (0.50 Ω) in comparison to the antenna having a traditional wound Litz wire construction. Thus, the transmitter or receiver antenna **20, 26** having a multi-layer-multi-turn (MLMT) construction contributes to the increased electrical performance of increased electrical power transmission and increased module separation distance **16** of the wireless connector system **10** of the present invention.

TABLE V

Antenna Design	Frequency (MHz)	Inductance (μH)	ESR (Ω)
Litz Wire	2	3.80	0.97
MLMT	2	0.60	0.50
MLMT	10	0.65	1.05

Exemplary ways of connecting the module to a host device include, but are not limited to, directly soldering or placing the at least one transmitter module **12, 148** and receiver module **14, 150** on a circuit board or a host device **22, 28**. Alternatively, the at least one transmitter module **12, 148** and receiver module **14, 150** could be connected to a circuit board or a host device **22, 28** using a wire/cable. Once connected to a host device **22, 28**, the full structure or at least a portion of the structure of the at least one transmitter module **12, 148** and receiver module **14, 150** may be encapsulated within an insulative coating.

In an embodiment, the operating procedure for the transmitter module **12, 148** that comprises a single antenna element may have the following operating process. In this embodiment, the wireless connector system **10** is a unidirectional power transfer system at a frequency, for example at 2.4 GHz. In an embodiment, the receiver module **14, 150** is brought in the vicinity of the transmitter module **12, 148**.

In an embodiment, the receiver sensing sub-circuit **42** within the transmitter module **12, 148** detects the presence of the receiver module **14, 150**. The master control unit (MCU) **44** within the transmitter module **12, 148** activates the system **10**, and an identification stage is initiated. The identification stage could be important to distinguish between a spurious sense signal versus a sense signal detecting a true receiver module **14, 150**. The identification could also be important to determine the specific type of the receiver module **14, 150** that would indicate to the transmitter module **12, 148** and the host device **22** what amount of power and type of data to transmit.

In an embodiment, once a positive identification of the receiver module **14, 150** is made, the transmitter module **12, 148** starts transmitting power. In an embodiment, the transmission of electrical power could cease under several conditions, including but not limited to:

- (1) removal of the receiver module
- (2) a thermal event wherein there is a temperature rise within the system that rises above a predetermined accepted limit (this thermal event could be at the transmitter module **12, 148** or the receiver module **14, 150**)
- (3) if the receiver module **14, 150** powers a battery, then the battery is fully charged
- (4) the power supply to the transmitter module **12, 148** is removed
- (5) if the power supply to the transmitter module **12, 148** is a battery, then the electrical power from the battery has dropped below a pre-determined threshold

It is noted that the above exemplary process is for a case when the transmitter module **12, 148** is configured as a single-purpose (only transmits) and the receiver module **14, 150** is configured as a single purpose (only receives), and there exists a single antenna element for each transmitter module **12, 148** and receiver module **14, 150**. In other words, this is a unidirectional wireless power system.

In another embodiment, the wireless connector system **10** of the present application could include a module that can operate both as a transmitter and as a receiver, i.e. a transceiver. In a further embodiment, the wireless connector system **10** of the present application may comprise a power and data transfer system in addition to a single antenna where the data is modulated into the power frequency.

In another embodiment, the wireless connector system **10** of the present invention may comprise multiple antennas within each transmitter module **12, 148** and receiver modules **14, 150**. If a multiple antenna system is employed, then the first antenna could be reserved for identification, diagnostics and any uni- or bi-directional data transfer, while the second antenna can be dedicated to power transfer.

In an embodiment, the reliability and repeatability of the receiver module presence sensing capability could be improved by using a calibration method, as described in the following steps.

1. When the transmitter module **12, 148** is in idle mode, and no object (such as the antenna coil of the receiver module) is present, the sense line within the transmitter module circuit **18** may be amplified or buffered and then connected to an Analog to Digital Converter (ADC). The ADC monitors (or samples) the sense line at predetermined time intervals converts the sense voltage in idle mode (V_{idle}) to a digital format whose value is stored in memory by the transmitter master control unit (MCU) **44**.
2. The ADC continues to sample the sense line while in idle mode by measuring the voltage (V_{idle}) and calculates the difference between consecutive values of V_{idle} designated as V_{delta} . A predetermined voltage threshold designated as $V_{threshold}$ is used to compare to V_{delta} . In this case, V_{delta} is less than $V_{threshold}$ since the changes in V_{idle} will be small while the device remains in idle mode (Scenario 1)
3. When an object is present (such as a receiver antenna coil) the sense line changes to a different voltage level (V_{active}) due to the mutual inductance (M) between the transmitter module **12, 148** and the receiver antenna coil. The ADC converts V_{active} to a digital format whose value is stored in memory by a microcontroller or master control unit (MCU) of the transmitter module **12, 148**.
4. The processor calculates the difference between the stored value of V_{idle} and V_{active} which is designated as V_{delta} and stores this value in a memory. The same predetermined threshold $V_{threshold}$ is used and compared to V_{delta} along with subsequent samples of V_{active} . In this case, since the sense line voltage has changed and V_{delta} will be greater than $V_{threshold}$ which indicates the presence of a receiver antenna coil. The processor can now switch the device to active mode (Scenario 2)
5. The ADC continues to sample the sense line while in active mode by measuring the voltage (V_{active}) and calculates the difference between consecutive values of V_{active} designated as V_{delta} . The same predetermined voltage threshold designated as $V_{threshold}$ is used to compare to V_{delta} . In this case, V_{delta} is less than

- V_{threshold} since the changes in V_{active} will be small while the device remains in active mode (Scenario 3)
6. When an object is removed (such as a receiver antenna coil) the sense line returns to the idle mode voltage level (V_{idle}) due to the Mutual Inductance (M) between the transmitter and receiver antenna coils. The ADC converts V_{idle} to a digital format whose value is stored in memory by a microcontroller or processor.
 7. The processor within the transmitter module **12, 148** calculates the difference between the stored value of V_{active} and V_{idle} which is designated as V_{delta} and stores this value in memory. The same predetermined threshold V_{threshold} is used and compared to V_{delta} along with subsequent samples of V_{idle}. In this case, since the sense line voltage has changed V_{delta} will be greater than V_{threshold} which indicates the removal of the receiver antenna coil. The processor can now switch the device back to idle mode (Scenario 4)
 8. It should be noted that this methodology is “self-calibrating” since any variation due to inherent manufacturing process tolerances are removed. The methodology also eliminates the need for a comparator and allows the use of lower cost components since greater module variability can be tolerated.

As used herein, the phrase “at least one of” preceding a series of items, with the term “and” or “or” to separate any of the items, modifies the list as a whole, rather than each member of the list (i.e., each item). The phrase “at least one of” does not require selection of at least one of each item listed; rather, the phrase allows a meaning that includes at least one of any one of the items, and/or at least one of any combination of the items, and/or at least one of each of the items. By way of example, the phrases “at least one of A, B, and C” or “at least one of A, B, or C” each refer to only A, only B, or only C; any combination of A, B, and C; and/or at least one of each of A, B, and C.

The predicate words “configured to”, “operable to”, and “programmed to” do not imply any particular tangible or intangible modification of a subject, but, rather, are intended to be used interchangeably. In one or more embodiments, a processor configured to monitor and control an operation or a component may also mean the processor being programmed to monitor and control the operation or the processor being operable to monitor and control the operation. Likewise, a processor configured to execute code can be construed as a processor programmed to execute code or operable to execute code.

A phrase such as “an aspect” does not imply that such aspect is essential to the subject technology or that such aspect applies to all configurations of the subject technology. A disclosure relating to an aspect may apply to all configurations, or one or more configurations. An aspect may provide one or more examples of the disclosure. A phrase such as an “aspect” may refer to one or more aspects and vice versa. A phrase such as an “embodiment” does not imply that such embodiment is essential to the subject technology or that such embodiment applies to all configurations of the subject technology. A disclosure relating to an embodiment may apply to all embodiments, or one or more embodiments. An embodiment may provide one or more examples of the disclosure. A phrase such as an “embodiment” may refer to one or more embodiments and vice versa. A phrase such as a “configuration” does not imply that such configuration is essential to the subject technology or that such configuration applies to all configurations of the subject technology. A disclosure relating to a configuration may apply to all configurations, or one or more configurations. A

configuration may provide one or more examples of the disclosure. A phrase such as a “configuration” may refer to one or more configurations and vice versa.

The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any embodiment described herein as “exemplary” or as an “example” is not necessarily to be construed as preferred or advantageous over other embodiments. Furthermore, to the extent that the term “include,” “have,” or the like is used in the description or the claims, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the term “include,” “have,” or the like is used in the description or the claims, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim.

All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. § 112, sixth paragraph, unless the element is expressly recited using the phrase “means for” or, in the case of a method claim, the element is recited using the phrase “step for.”

Reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” Unless specifically stated otherwise, the term “some” refers to one or more. Pronouns in the masculine (e.g., his) include the feminine and neuter gender (e.g., her and its) and vice versa. Headings and subheadings, if any, are used for convenience only and do not limit the subject disclosure.

While this specification contains many specifics, these should not be construed as limitations on the scope of what may be claimed, but rather as descriptions of particular implementations of the subject matter. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub combination or variation of a sub combination.

What is claimed is:

1. A wireless connector system for wireless power transfer via near field magnetic coupling (NFMC) at an operating frequency configured for the wireless power transfer, the wireless connector system comprising:

a transmitter module, comprising:

- a transmitter antenna configured to transmit electrical energy for the wireless power transfer at the operating frequency;
- a first substrate supporting the transmitter antenna;
- a second substrate supporting a transmitter module electronic circuit, wherein the transmitter module electronic circuit is electrically connected to the transmitter antenna; and

29

a first insulator positioned between the transmitter module electronic circuit and the transmitter antenna,
 a transmitter module master control sub-circuit; and
 a receiver module detection sub-circuit electrically connected to the transmitter module master control sub-circuit by a sense line, wherein the receiver module detection sub-circuit is configured to detect an electrical voltage on the sense line and calculate a detected voltage level;
 wherein the receiver module detection sub-circuit comprises an envelope tracker sub-circuit for receiver module sensing that includes a first resistor and a second resistor, wherein the sense line is between the first resistor and the second resistor;
 a receiver module, comprising:
 a receiving antenna configured for receiving the electrical energy for the wireless power transfer at the operating frequency;
 a third substrate supporting the receiving antenna;
 a fourth substrate supporting a receiver module electronic circuit, wherein the receiver module electronic circuit is electrically connected to the receiving antenna; and
 a second insulator positioned between the receiver module electronic circuit and the receiving antenna,
 wherein the receiver module detection sub-circuit is configured to compare the detected voltage level to an idle voltage level during an idle mode to determine a voltage change level, wherein the receiver module detection sub-circuit is configured to compare the voltage change level to a predetermined voltage threshold level that indicates the presence of the receiver module, the predetermined voltage threshold level stored in memory of the receiver module detection sub-circuit,
 wherein the receiver module detection sub-circuit enables configuration of the transmitter module master control sub-circuit to communicate with the receiver module, and
 wherein, when the voltage change level exceeds the predetermined voltage threshold level, the transmitter module master control sub-circuit transmits the electrical energy to the receiver module.

2. The wireless connector system of claim 1 wherein a first shielding material is positioned between the transmitter antenna and the transmitter module electronic circuit, a second shielding material is positioned between the receiving antenna and the receiver module electronic circuit, the first and second shielding materials comprising a ferrite material.

3. The wireless connector system of claim 2 wherein the first and second shielding materials comprise manganese-zinc, nickel-zinc, copper-zinc, magnesium-zinc, and combinations thereof.

4. The wireless connector system of claim 1 wherein the first or second substrate comprises a printed circuit board, a flex circuit board, or a combination thereof.

5. The wireless connector system of claim 1 wherein a plurality of spaced apart castellations are formed within an exterior surface of the first or second substrate.

6. The wireless connector system of claim 5 wherein the plurality of spaced apart castellations are plated with an electrically conductive material selected from a group consisting of gold, silver, platinum, palladium, copper, and combinations thereof, and wherein at least one of the plurality of spaced apart castellations is electrically contactable with an electronic circuit board.

30

7. The wireless connector system of claim 1 wherein a plurality of spaced apart electrically conductive pads are formed on an exterior surface of the first and second substrates, wherein at least one of the plurality of spaced apart electrically conductive pads is electrically contactable to an electronic circuit board.

8. The wireless connector system of claim 1 further configured to transmit an electrical power that ranges from about 100 μ W to about 10 W.

9. The wireless connector system of claim 1 wherein at least one of the receiving antenna and the transmitter antenna comprises a plurality of conductors and at least one insulator positioned between each of the plurality of conductors, the plurality of conductors having at least one turn.

10. The wireless connector system of claim 1 wherein the transmitter module electronic circuit comprises:
 a) a first electrical impedance matching sub-circuit electrically connected to the transmitter antenna, the first electrical impedance matching sub-circuit comprises at least one first capacitor and an electrical power inverter sub-circuit, wherein the first electrical impedance matching sub-circuit and the electrical power inverter sub-circuit are configured to prepare the electrical energy for transmission by the transmitter antenna;
 b) the transmitter module master control sub-circuit comprising a master control unit;
 c) a driver sub-circuit electrically connected to the transmitter module master control sub-circuit and the electrical power inverter sub-circuit; and
 d) a first voltage regulator sub-circuit electrically connected to the transmitter module master control sub-circuit and the electrical power inverter sub-circuit.

11. The wireless connector system of claim 10 wherein the driver sub-circuit comprises a half-bridge driver integrated circuit.

12. The wireless connector system of claim 10 wherein the electrical power inverter sub-circuit comprises a field effect transistor power stage inverter.

13. The wireless connector system of claim 1 wherein the receiver module electronic circuit comprises:
 a) a receiver module master control sub-circuit comprising a master control unit;
 b) a second electrical impedance matching sub-circuit electrically connected to the receiving antenna, the second electrical impedance matching sub-circuit comprising at least one second capacitor, wherein the second electrical impedance matching sub-circuit is configured to prepare the received electrical energy for use by an electronic device; and
 c) a second voltage regulator sub-circuit electrically connected to the receiver module master control sub-circuit.

14. The wireless connector system of claim 13 further comprising a voltage doubler sub-circuit, the voltage doubler sub-circuit electrically connected to the second electrical impedance matching sub-circuit and the second voltage regulator sub-circuit.

15. The wireless connector system of claim 1 wherein the receiver module further comprises a thermal sense sub-circuit electrically connected to the receiver module electronic circuit, wherein the thermal sense sub-circuit is configured to detect and measure a temperature within the receiver module.

16. The wireless connector system of claim 1 wherein the transmitter module further comprises a thermal detection sub-circuit electrically connected to the transmitter module

31

electronic circuit, wherein the thermal detection sub-circuit is configured to detect and measure a temperature within the transmitter module.

17. The wireless connector system of claim 1 wherein a switch capacitor sub-circuit is electrically connected within at least one of first and second electrical impedance matching sub-circuits, wherein the switch capacitor sub-circuit is configured to dynamically modify a capacitance of the at least one of the first and second electrical impedance matching sub-circuits.

18. The wireless connector system of claim 1 wherein the transmitter module comprises a transmitter housing, wherein the first substrate, the second substrate and the first insulator are positioned therewithin and the receiver module comprises a receiver housing wherein the third substrate, the fourth substrate and the second insulator are positioned therewithin.

19. The wireless connector system of claim 1, wherein the transmitter module is operatively associated with a host device, the host device operatively associated with a medical device, and

wherein the receiver module is operatively associated with the medical device.

20. The wireless connector system of claim 1, wherein the transmitter module is operatively associated with a host device, the host device operatively associated with eyeglasses, and

wherein the receiver module is operatively associated with the eyeglasses.

32

21. The wireless connector system of claim 1, wherein the operating frequency is selected from a range of about 100 kHz to about 50 MHz.

22. The wireless connector system of claim 1, wherein the operating frequency is about 6.78 MHz.

23. The wireless connector system of claim 1, wherein the operating frequency is about 13.56 MHz.

24. The wireless connector system of claim 23, wherein the wireless power transmission is based on Near Field Communications (NFC) standard, based on standards defined by ISO/IEC standard 18092.

25. The wireless connector system of claim 1 wherein, if the voltage change level exceeds the predetermined voltage threshold level, the transmitter module and receiver module are configured to initiate identification communication that includes the receiver module transmitting a signal that defines the amount of power to be transmitted from the transmitter module.

26. The wireless connector system of claim 25 wherein the transmitter module adjusts the power level of the signal based on the identification communication between the transmitter module and the receiver module.

27. The wireless connector system of claim 26, wherein the transmitter module further comprises a voltage regulator that increases or decreases the voltage to a power amplifier based on communication from the receiver module, and wherein the transmitter module ceases transmitting the signal, if the voltage change level is below the predetermined voltage threshold level.

* * * * *