



(12) **DEMANDE DE BREVET CANADIEN**
CANADIAN PATENT APPLICATION

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2019/09/27
(87) Date publication PCT/PCT Publication Date: 2020/04/09
(85) Entrée phase nationale/National Entry: 2021/04/06
(86) N° demande PCT/PCT Application No.: CA 2019/051382
(87) N° publication PCT/PCT Publication No.: 2020/069605
(30) Priorité/Priority: 2018/10/02 (US16/149,732)

(51) Cl.Int./Int.Cl. *G01G 3/00* (2006.01),
G01G 19/08 (2006.01), *G01G 23/01* (2006.01)
(71) Demandeur/Applicant:
BLACKBERRY LIMITED, CA
(72) Inventeur/Inventor:
BELL, GORDON, CA
(74) Agent: MOFFAT & CO.

(54) Titre : PROCEDE ET APPAREIL D'ESTIMATION DE MASSE DE MARCHANDISES A L'AIDE D'UN
ACCELEROMETRE VERTICAL
(54) Title: METHOD AND APPARATUS FOR CARGO MASS ESTIMATION USING A VERTICAL ACCELEROMETER




FIG. 1

(57) **Abrégé/Abstract:**

A method at a sensor apparatus affixed to a transportation asset. The method includes calibrating the sensor apparatus by initiating a vertical impact at the transportation asset, measuring spring oscillation and creating a model of the transportation asset. The method further includes detecting, subsequent to the calibrating, an impact event at the sensor apparatus. The method further includes measuring spring oscillation due to the impact event at the sensor apparatus and using the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

Abstract

A method at a sensor apparatus affixed to a transportation asset. The method includes calibrating the sensor apparatus by initiating a vertical impact at the transportation asset, measuring spring oscillation and creating a model of the transportation asset. The method further includes detecting, subsequent to the calibrating, an impact event at the sensor apparatus. The method further includes measuring spring oscillation due to the impact event at the sensor apparatus and using the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

METHOD AND APPARATUS FOR CARGO MASS ESTIMATION USING A VERTICAL ACCELEROMETER

FIELD OF THE DISCLOSURE

[0001] The present disclosure relates to the transportation of goods, and in particular relates to cargo mass estimation of containers or trailers for the transportation of goods.

BACKGROUND

[0002] During the transportation of goods, the trailer weight is an important piece of information that a transportation company needs to know. In particular, various provinces and states have weight limits for roads, and vehicles are not allowed to exceed such maximum allowable gross weight. Further, many jurisdictions collect taxes based on the weight of transported goods, and it is therefore important for a transportation company to know the gross weight of the trailer.

[0003] Further, the information on vehicle weight may be beneficial to the transportation company itself. In particular, a transportation company managing a fleet of vehicles needs to know which vehicles are full and which vehicles are empty. One way to determine this is based on the weight of the vehicle, since a dry or empty weight of the trailer is typically a known value.

[0004] Typically, a vehicle weight is determined by the container, trailer or similar asset proceeding to a weighing station. However, such information is then only available well after the vehicle has been loaded. Further, long periods of time may exist between weighing the container, trailer or similar asset.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The present disclosure will be better understood with reference to the drawings, in which:

[0006] **Figure 1** is a side elevational view of a container showing an example placement of a sensor apparatus;

[0007] **Figure 2** is block diagram of an example sensor apparatus capable of being used between embodiments of the present disclosure;

[0008] **Figure 3** is a block diagram showing an example architecture for the sensor apparatus of **Figure 2**;

[0009] **Figure 4** is a block diagram showing a trailer acting on a spring;

[0010] **Figure 5** is a block diagram showing the forces at the rear of a trailer or container;

[0011] **Figure 6** is a plot of an example oscillation as seen in by and accelerometer at the rear of a trailer or container;

[0012] **Figure 7** is a process diagram showing a process for calibration of a sensor apparatus for mass estimation;

[0013] **Figure 8** is a process diagram showing a process for estimating a mass of a trailer or container load;

[0014] **Figure 9** is a data flow diagram showing a process for using mass estimation to detect anomalies in a shipment; and

[0015] **Figure 10** is a block diagram of an example computing device or server capable of being used with the embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DRAWINGS

[0016] The present disclosure provides a method at a sensor apparatus affixed to a transportation asset, the method comprising: calibrating the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating

measuring spring oscillation and creating a model of the transportation asset; detecting, subsequent to the calibrating, an impact event at the sensor apparatus; measuring spring oscillation due to the impact event at the sensor apparatus; and using the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

[0017] The present disclosure further provides a sensor apparatus affixed to a transportation asset, the sensor apparatus comprising: a processor; and a communications subsystem, wherein the sensor apparatus is configured to: calibrate the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating measuring spring oscillation and creating a model of the transportation asset; detect, subsequent to the calibrating, an impact event at the sensor apparatus; measure spring oscillation due to the impact event at the sensor apparatus; and use the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

[0018] The present disclosure further provides a computer readable medium for storing instruction code, which, when executed by a processor of a sensor apparatus affixed to a transportation asset cause the sensor apparatus to: calibrate the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating measuring spring oscillation and creating a model of the transportation asset; detect, subsequent to the calibrating, an impact event at the sensor apparatus; measure spring oscillation due to the impact event at the sensor apparatus; and use the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

[0019] In accordance with the embodiments described below, cargo mass estimation methods and systems utilizing a vertical accelerometer are described.

[0020] In the embodiments described below, the mass estimation measurements are performed on a trailer which is connected to a tractor. However, in other

cases, the measurements may be made on other shipping containers, including, but not limited to, railcars, trucks, automobiles, among others.

[0021] In order to perform mass estimation, a sensor apparatus may be affixed to a container, trailer, or other similar asset. For example, such sensor apparatus may be mounted inside of a trailer or cargo container. Reference is now made to **Figure 1**.

[0022] In the embodiment of **Figure 1**, example truck trailer **110** is shown. In one embodiment, the computing device may be mounted on the back of the trailer. For example, in one embodiment the computing device may be mounted close to the top of the back door or on the rear side wall near the back door of the truck trailer **110**. This is shown, for example, with sensor apparatus **112** in the embodiment of **Figure 1**.

[0023] The location of computing device **112** near the rear of the trailer allows for maximum sensing of kinetic energy as a result of the vehicle hitting a significant bump.

[0024] However, in other cases it may be beneficial to have a different position for the sensor apparatus. Further, in some embodiments it may be useful to have a plurality of such sensor apparatuses within the trailer **110**.

[0025] The sensor apparatuses within trailer **110** may be used alone in some embodiments, or may be combined into sets of two or more sensor apparatuses and/or external sensors for load mass calculation.

[0026] **Apparatus**

[0027] One sensor apparatus for a vehicle or container is shown with regard to **Figure 2**. The sensor apparatus of **Figure 2** is however merely an example and other sensing devices could equally be used in accordance with the embodiments of the present disclosure.

[0028] Reference is now made to **Figure 2**, which shows an example sensor apparatus **210**. Sensor apparatus **210** can be any computing device or network node. Such sensor apparatus or network node may include any type of electronic device, including but not limited to, mobile devices such as smartphones or cellular telephones. Examples can further include fixed or mobile devices, such as internet of things (IoT) devices, endpoints, home automation devices, medical equipment in hospital or home environments, inventory tracking devices, environmental monitoring devices, energy management devices, infrastructure management devices, vehicles or devices for vehicles, fixed electronic devices, among others.

[0029] Sensor apparatus **210** comprises a processor **220** and at least one communications subsystem **230**, where the processor **220** and communications subsystem **230** cooperate to perform the methods of the embodiments described herein. Communications subsystem **230** may, in some embodiments, comprise multiple subsystems, for example for different radio technologies.

[0030] Communications subsystem **230** allows sensor apparatus **210** to communicate with other devices or network elements. Communications subsystem **230** may use one or more of a variety of communications types, including but not limited to cellular, satellite, Bluetooth™, Bluetooth™ Low Energy, Wi-Fi, wireless local area network (WLAN), sub-giga hertz radios, near field communications (NFC), IEEE 802.15, wired connections such as Ethernet or fiber, among other options.

[0031] As such, a communications subsystem **230** for wireless communications will typically have one or more receivers and transmitters, as well as associated components such as one or more antenna elements, local oscillators (LOs), and may include a processing module such as a digital signal processor (DSP) or System on Chip (SOC). As will be apparent to those skilled in the field of communications, the particular design of the communication subsystem **230** will

be dependent upon the communication network or communication technology on which the sensor apparatus is intended to operate.

[0032] Processor **220** generally controls the overall operation of the sensor apparatus **210** and is configured to execute programmable logic, which may be stored, along with data, using memory **240**. Memory **240** can be any tangible, non-transitory computer readable storage medium, including DRAM, Flash, optical (e.g., CD, DVD, etc.), magnetic (e.g., tape), flash drive, hard drive, or other memory known in the art.

[0033] Alternatively, or in addition to memory **240**, sensor apparatus **210** may access data or programmable logic from an external storage medium (not shown), for example through communications subsystem **230**.

[0034] In the embodiment of **Figure 2**, sensor apparatus **210** may utilize a plurality of sensors, which may either be part of sensor apparatus **210** in some embodiments or may communicate with sensor apparatus **210** in other embodiments. For internal sensors, processor **220** may receive input from a sensor subsystem **250**.

[0035] Examples of sensors in the embodiment of **Figure 2** include a positioning sensor **251**, a vibration sensor **252**, a temperature sensor **253**, one or more image sensors / cameras **254**, accelerometer **255**, light sensors **256**, gyroscopic sensors **257**, a door sensor **258**, and other sensors **259**. Other sensors may be any sensor that is capable of reading or obtaining data that may be useful for the sensor apparatus **210**. However, the sensors shown in the embodiment of **Figure 2** are merely examples, and in other embodiments, different sensors or a subset of sensors shown in **Figure 2** may be used. For example, in some cases the only sensor may be an accelerometer.

[0036] Further, accelerometer **255** would typically provide acceleration sensors in three dimensions. Thus, accelerometer **255** would generally include three

individual accelerometers. The readings from each of the three individual accelerometers could be isolated.

[0037] Communications between the various elements of sensor apparatus **210** may be through an internal bus **260** in one embodiment. However, other forms of communication are possible.

[0038] In the embodiment of **Figure 2**, a load detection sensor **270** may be controlled by sensor apparatus **210**. Load detection sensor **270** may, for example, be mounted together with sensor apparatus **210** or may form part of sensor apparatus **210**. Load detection sensor **270** may be a Time of Flight (ToF) sensor, an ultrasonic sensor, an RF sensor, or may be an image sensor used to project an array of dots in any light spectrum, including visible light, ultra-violet (UV) light, or infra-red (IR) light.

[0039] Sensor apparatus **210** may be affixed to any fixed or portable platform. For example, sensor apparatus **210** may be affixed to shipping containers or truck trailers in one embodiment, as for example described above with regard to **Figure 1**. In other embodiments, sensor apparatus **210** may be affixed to any vehicle for which a mass determination is needed, including self-propelled vehicles (e.g., automobiles, cars, trucks, buses, etc.), railed vehicles (e.g., trains and trams, etc.), and other types of vehicles including any combinations of any of the foregoing, whether currently existing or after arising, among others.

[0040] In other cases, sensor apparatus **210** may be part of a container that could be carried on or within a vehicle. In accordance with the present disclosure, the term container may include any sort of cargo or item transportation such as vehicles, intermodal containers, shipping bins, lock boxes, and other similar vessels.

[0041] Such a sensor apparatus **210** may be a power limited device. For example, sensor apparatus **210** could be a battery-operated device that can be

affixed to a shipping container or trailer in some embodiments. Other limited power sources could include any limited power supply, such as a small generator or dynamo, a fuel cell, solar power, energy harvesting, among other options.

[0042] In other embodiments, sensor apparatus **210** may utilize external power, for example from the battery or power system of a tractor pulling the trailer, via a wiring harness connected to a 7-pin plug, from a land power source for example on a plugged in recreational vehicle or from a building power supply, among other options. Thus, the sensor apparatus **210** may also be connected to a power cord that receives its power from a power source.

[0043] External power may further allow for recharging of batteries to allow the sensor apparatus **210** to then operate in a power limited mode again. Recharging methods may also include other power sources, such as, but not limited to, solar, electromagnetic, acoustic or vibration charging.

[0044] The sensor apparatus from **Figure 2** may be used in a variety of environments. One example environment in which the sensor apparatus may be used is shown with regard to **Figure 3**.

[0045] Referring to **Figure 3**, three sensor apparatuses, namely sensor apparatus **310**, sensor apparatus **312**, and sensor apparatus **314** are provided.

[0046] In the example of **Figure 3**, sensor apparatus **310** may communicate through a cellular base station **320** or through an access point **322**. Access point **322** may be any wireless communication access point.

[0047] Further, in some embodiments, sensor apparatus **310** could communicate through a wired access point such as Ethernet or fiber, among other options.

[0048] The communication may then proceed over a wide area network such as Internet **330** and proceed to servers **340** or **342**.

[0049] Similarly, sensor apparatus **312** and sensor apparatus **314** may communicate with servers **340** or server **342** through one or both of the base station **320** or access point **322**, among other options for such communication.

[0050] In other embodiments, any one of sensor apparatuses **310**, **312** or **314** may communicate through satellite communication technology. This, for example, may be useful if the sensor apparatus is travelling to areas that are outside of cellular coverage or access point coverage.

[0051] In other embodiments, sensor apparatus **312** may be out of range of access point **322**, and may communicate with sensor apparatus **310** to allow sensor apparatus **310** to act as a relay for communications.

[0052] Communication between sensor apparatus **310** and server **340** may be one directional or bidirectional. Thus, in one embodiment sensor apparatus **310** may provide information to server **340** but server **340** does not respond. In other cases, server **340** may issue commands to sensor apparatus **310** but data may be stored internally on sensor apparatus **310** until the sensor apparatus arrives at a particular location, possibly during a particular time window. In other cases, two-way communication may exist between sensor apparatus **310** and server **340**.

[0053] A server, central server, processing service, endpoint, Uniform Resource Identifier (URI), Uniform Resource Locator (URL), back-end, and/or processing system may be used interchangeably in the descriptions herein. The server functionality typically represents data processing/reporting that are not closely tied to the location of sensor apparatuses **310**, **312**, **314**, etc. For example, the server may be located essentially anywhere so long as it has network access to communicate with sensor apparatuses **310**, **312**, **314**, etc.

[0054] Server **340** may, for example, be a fleet management centralized monitoring station. In this case, server **340** may receive information from a

sensor apparatus associated with various trailers or cargo containers, providing information such as the location of such cargo containers, the temperature within such cargo containers, any unusual events including sudden decelerations, temperature warnings when the temperature is either too high or too low, cargo loading within the trailer, the mass of the trailer, among other data. The server **340** may compile such information and store it for future reference.

[0055] Other examples of functionality for server **340** are possible.

[0056] In the embodiment of **Figure 3**, servers **340** and **342** may further have access to third-party information or information from other servers within the network. For example, a data services provider **350** may provide information to server **340**. Similarly, a data repository or database **360** may also provide information to server **340**.

[0057] For example, data services provider **350** may be a subscription-based service used by server **340** to obtain current road and weather conditions, or may be an inventory control system in some cases.

[0058] Data repository or database **360** may for example provide information such as image data associated with a particular location, aerial maps, detailed street maps, or other such information.

[0059] The types of information provided by data service provider **350** or the data repository or database **360** is not limited to the above examples and the information provided could be any data useful to server **340**.

[0060] In some embodiments, information from data service provider **350** or the data repository from database **360** can be provided to one or more of sensor apparatuses **310**, **312**, or **314** for processing at those sensor apparatuses.

[0061] A sensor apparatus such as that described in **Figures 2** and **3** above may be used to find the mass of a container or trailer.

[0062] ***Calculating the Mass of a Trailer***

[0063] In accordance with some embodiments of the present disclosure, the rear segment of a transportation vehicle can be modelled as a simple spring with a mass “m” and a spring constant “k”. For example, reference is now made to **Figure 4**.

[0064] In the embodiment of **Figure 4**, a trailer **410** has a mass “m”. An exaggerated spring **420** is shown towards the rear of the trailer and may be linked to a wheel **422**, for example through an axle. The spring constant “k” of spring **420** is representative of how stiff the spring is.

[0065] The forces acting on the system of **Figure 4** are shown with regard to **Figure 5**. In particular, in the embodiment of **Figure 5** a mass “m” is pulled downwards due to gravity. The acceleration due to gravity is a constant downward acceleration of “mg”. The force due to a spring **520** which is not near its operating limits is “kx”, where x is the spring’s displacement from its rest position, and k is a constant for that particular spring.

[0066] In this circumstance, according to Hooke’s law, the vibration of a simple spring is always an oscillation with a period “T”, as expressed in equation 1 below.

$$T = \sqrt{m/k} \quad (1)$$

[0067] In equation 1, k is a constant value that depends on the physical characteristics of the system.

[0068] The actual motion is typically a Bessel function which decays over time with this same period. The decay of the oscillation depends on any non-linearities in the system, which may typically be dominated by the shock absorbers on the rear axles, but having some minimal impact due to air resistance and other frictions.

[0069] If a truck, trailer or other similar asset is loaded within safe operating limits, the springs on the axles should not experience any significant deformations, which may affect the period of oscillations.

[0070] The amplitude of the oscillations depends on the forces of any impacts between the wheels in the ground, but do not affect the oscillation period.

[0071] For example, reference is now made to **Figure 6**, which shows an example plot of the magnitude of the oscillations over time. As seen from **Figure 6**, the amplitude of the oscillations decreases over time. However, the period of the oscillation remains static.

[0072] Based on **Figure 6**, by measuring the period of oscillation as observed by an accelerometer in the vertical direction on a container, trailer or other similar asset, an estimate could be found for the mass. The estimate may be found by comparing the oscillation period with a similar measurement taken when the same container had a known load, for example when the container is empty.

[0073] For example, the equation for the oscillation at a known load may be shown as equation 2 below.

$$T_0 = \sqrt{m_0/k} \quad (2)$$

[0074] In equation 2 above, the period T_0 with known mass m_0 could be used in the detection of the mass increase at some later period.

[0075] For example, at some later time, after a significant impact has been detected in the container, trailer or similar asset, and after a new mass has been loaded onto the container, trailer or similar asset, the period of oscillation may be shown as that of equation 3.

$$T = \sqrt{(m + m_0)/k} \quad (3)$$

[0076] In equation 3 above, the period of oscillation depends on the original mass (empty mass for example) along with that the mass added when the container, trailer or similar asset was loaded. Substituting for k in equation 3 gives:

$$T = T_0 \sqrt{(1 + m)/m_0} \quad (4)$$

[0077] Utilizing equation 4 above, the comparing of the oscillation period T with the default oscillation period T_0 allows for the calculation of the new total mass $(m + m_0)$. Further, the mass added to the trailer m can be calculated since the remaining values are constant.

[0078] In practice, a real model would be more complicated than the embodiments of **Figures 4, 5, or 6**, and in various embodiments described below, modelling for a more complex system is described. However, the simplified version of **Figures 4, 5, or 6**, along with equations 1 to 4, may be utilized in some cases, since the motion at the back end of the vehicle would typically be dominated by the action of the rear springs acting on the rear axles.

[0079] Motion components due to forward wheels (if any), or induced from the coupling to the towing vehicle may not be significant in some cases for the very rear of vehicle where a measurement device may be attached.

[0080] In accordance with embodiments of the present disclosure, more complex modelling of systems may be done based on calibration, as described below. In particular, shock absorbers, dampers, airbags, among other items, may cause the rear axle to act as a non-simple spring. In this case, terms may be added to equations 1 to 4 to model such dampers, airbags or other items as second springs. Thus, the rear axle of a trailer may be modelled as a set of springs with a set of spring constants. In this case, the accelerometer may measure a plurality of oscillations.

[0081] A model of the series of oscillations can be calibrated for an empty load and therefore compared with the series of oscillations detected when the trailer hits a bump. In this way, a more accurate representation of the mass of the trailer may be found.

[0082] Further, in some cases, the harmonics due to the tow vehicle or front suspension may also be modelled. In particular, with enough insight as to the composition of the vehicle, the calibration as described below may further be utilized to account for such harmonics.

[0083] Also, in some cases, the model may be adapted to include other mechanical factors, such as extra axles and front axle coupling.

[0084] ***Calibration***

[0085] As indicated above, when a sensor apparatus is first installed on a trailer or container, the system may be calibrated to allow for mass measurements on the trailer.

[0086] In particular, reference is now made to **Figure 7**, which shows one example embodiment for calibrating a sensor apparatus to allow for mass measurements. The process of **Figure 7** starts at block **710** and proceeds to block **712** in which the trailer or container that the sensor apparatus is affixed to

is caused to have a vertical impact. For example, in one embodiment the vertical impact may involve driving the trailer or container over a drop to initiate the spring response.

[0087] In one case, an ideal bump may be a vertical curb with a distance of approximately 6 inches or 15 cm between the top and bottom. However other distances could equally be used, and for example 3 or 4 inches (7.5 to 10 cm) may be sufficient.

[0088] From block **712** the process proceeds to block **720** in which data is collected for a threshold period of time. In one case, the oscillation observed at the vertical accelerometer may look like that shown in the **Figure 6** above. In other cases, various oscillations may be combined together in more complex systems.

[0089] From block **720**, the process proceeds to block **730** in which an empty trailer is modelled. As will be appreciated by those in the art, trailers tends to be highly regulated and therefore the dry weight of the trailer would generally be known. Further, in some cases, the make and model of the trailer may be standardized and in this case the data for the dry weight of the trailer may be looked up from a database and inserted into the equations above.

[0090] If multiple oscillations are observed, then the multiple oscillations may be modelled in accordance with the embodiments described above. In particular, data about dampers, airbags, suspension, front links, among other information may be modelled based on the calibration process of **Figure 7**.

[0091] Once the empty trailer model is created, the process may then proceed to block **732**. At block **732**, a decision may be made on whether to repeat of the calibration steps in order to fine tune the model. For example, the repeating of the calibration steps may provide a better baseline for the model created at block

730. If the process is to repeat, the process proceeds from block **732** back to block **712**.

[0092] Conversely, if an accurate model has been derived then the process may proceed from block **732** to block **740** and end.

[0093] *Measurement*

[0094] in accordance with the embodiments of the present disclosure, the mass of the trailer may be found when an impact event between the trailer and the ground occurs. For example, this impact event may occur when the truck hits a bump, from a small bump on a well travelled road to a significant pothole, when the truck drives over a curb, when a speedbump is crossed, among other options.

[0095] As indicated above, the sensor apparatus may be a power limited device. Therefore, in one embodiment, it is beneficial to avoid continuously checking for impact events and to only wake a main processor when such impact event occurs. This may save battery life on the sensor apparatus.

[0096] Reference is now made to **Figure 8**, which shows a process of measuring the mass at the sensor apparatus. The process of **Figure 8** starts at block **810** and proceeds to block **812** in which a check is made to determine whether an impact event occurs. For example, the accelerometers may be very low power devices which may measure impacts. In this regard, a vertical accelerometer may be configured to provide a signal such as an interrupt to a main processor when an impact event occurs. Thus, if an impact event is sensed by an accelerometer at block **812**, the process may proceed to block **820** in which the accelerometer sends an interrupt to the main processor on a sensor apparatus in order to wake the main processor. The main processor is a higher power consumption device, and is therefore only woken for short time periods.

[0097] Once the processor is woken through the interrupt a block **820**, the sensor apparatus may record data received from the vertical accelerometer for a defined time period, as shown at block **830**. The defined time period may be preconfigured or may be set to dynamically by a server in some cases.

[0098] The process may then proceed to block **840** in which the recorded data is analyzed to find the period of oscillation of the trailer or container after the impact. This period of oscillation may then be utilized in the formula is derived from the model during a calibration to find the mass. As indicated above, since the other elements within the formula are constants, the mass of the load may be derived based on the period of oscillation of a loaded trailer.

[0099] In some cases, the analysis of block **840** may be done at a device different from the sensor apparatus. For example, rather than analyze the data at the sensor apparatus, after the data has been recorded it may be provided to a server such as server **340** from **Figure 3**. The server **340** could then analyze of the raw data to find the mass in some cases.

[00100] From block **840**, the process proceeds to block **850** and ends.

[00101] The process of **Figure 8** above therefore only wakes the main processor when an impact event occurs, thereby saving battery life on the processor. Further, in some cases, the process of **Figure 8** only occurs once, for example after a threshold event such as a door closing event on the trailer has occurred. In this way, the processor is not repeatedly woken up, but rather is only woken up once per trip. In other cases, the processor may be periodically woken up, but a threshold amount of time may need to elapse between measurements in order to avoid draining the battery on the sensor apparatus.

[00102] The processor of the sensor apparatus may transition back to a sleep state once the oscillations due to the impact event are recorded and, in some cases, once the data has been analyzed.

[00103] Thus, the process of **Figure 8** is an intermittent measurement tool that allows measurements to occur once or intermittently throughout a trip.

[00104] Based on the calibration and modelling of **Figures 7** and **8**, a measurement is generally accurate for standard trucks or containers on a standard trailer.

[00105] ***System Degradation***

[00106] The above systems and methods could provide for various enhancements for a transportation company. In one case, system degradation may be detected utilizing the techniques described above. In particular, an empty trailer should have the same oscillation pattern, for example as shown in **Figure 6**, over time. If the oscillation pattern is changing over time, this could be indicative of potential failures within the trailer. For example, the springs may be degrading and may need to be replaced.

[00107] Thus, a review of the oscillation periods and/or amplitudes over an extended time period may be indicative of system degradation, which may require operator intervention.

[00108] ***Loss Prevention***

[00109] The above systems and methods could further be utilized as part of loss prevention strategy by a transportation company. In particular, the method of **Figure 8** could be used whenever a trigger situation occurs.

[00110] For example, reference is now made to **Figure 9**. In the embodiment of **Figure 9**, a sensor apparatus **910** may communicate with a

server **912**. At block **920**, a check is made at the sensor apparatus **910** to determine whether a trigger condition has occurred.

[00111] For example, a trigger condition may be a door open or door close event. A transportation company may wish to measure the mass of the load subsequent to a door open or door close event to determine whether the mass increased or decreased and whether the door open or door close event corresponded with a loading or unloading event.

[00112] The trigger at block **920** could instead be a significant duration stop. For example, if the container or trailer is stopped for greater than a threshold period of time, a check could be made to determine whether the load mass has changed. For example, a load mass may change if the trailer was accessed by cutting a hole in the side of the trailer. In other cases, if the trailer is an open platform trailer, then a significant stop may allow for the unloading of the trailer. If the trailer is not supposed to be unloaded, then the transportation company may want to know about this.

[00113] In other cases, the trigger at block **920** could be data from a combination of sensors. For example, if the trailer is stopped and vibration is detected within the trailer, this may indicate movement within the trailer. Subsequently, when the trailer starts moving again then a load measurement may need to be taken.

[00114] Other examples of triggers at block **920** would be apparent to those skilled in the art having regard to the present disclosure.

[00115] The triggers at block **920** may be preconfigured, for example when a sensor apparatus **910** is installed or manufactured. In other cases, the triggers at block **920** may be provisioned onto the sensor apparatus, for example through server **912**.

[00116] From block **920**, if a trigger condition is not met, the process may continue to check for triggers at block **920**.

[00117] Once a trigger condition has been detected, the process proceeds to block **930** in which a mass measurement may be taken. The mass measurement at block **930** may be taken in accordance with the embodiment of **Figure 8** above.

[00118] In one embodiment, the process may then proceed to send the mass data to a server **912**, as is shown with message **932**. The server **912** may then check for anomalies, as described below, at block **934**.

[00119] In other cases, a check for anomalies, as shown at block **940** may be done on the sensor apparatus **910**.

[00120] The check for anomalies at either block **934** or block **940** may compare the detected mass at block **930** and the expected mass. For example, transportation company will typically know when scheduled loading or unloading of the trailer or container should occur. If the mass of the trailer load changes and no scheduled loading or unloading was to occur, this could indicate an anomaly which may need to be followed up on.

[00121] In some embodiments, input may be received at a sensor apparatus on the container or trailer indicating when a scheduled loading or unloading event should occur.

[00122] From block **940**, if an anomaly is detected then this may be reported to server **912**, as shown by message **942**.

[00123] The detection of an anomaly may cause an alert situation. For example, an operator of the transportation company may be provided with an alarm or warning indicating that an anomaly between the detected mass in the expected mass exists. Other options for actions upon anomaly detection are also possible.

[00124] ***Load Verification***

[00125] In still further embodiments, the systems and methods described above could be used for load verification. In particular, if a sensor apparatus such as sensor apparatus **210** from **Figure 2** is used to verify a load through a time of flight sensor or other similar load measurement sensor, then the mass determination as described above could be used to verify such loading.

[00126] Load sensors such as time-of-flight sensors could be fooled if a trailer is loaded differently than expected. For example, if the time of flight sensor is at the rear of the trailer and the trailer is loaded towards its rear, leaving a significant space near the front of the trailer, a time of flight sensor would be fooled. In particular, the time of flight sensor would indicate that the trailer is completely loaded. However, the mass of the trailer would indicate that the trailer may be mostly empty.

[00127] Thus, the correlation of the mass detection and load detection systems can be used for verification of the load status.

[00128] Based on the above, a mass estimation system and method are provided in which a sensor apparatus having a vertical accelerometer may be calibrated to model an empty trailer. Subsequently, an impact event may be detected, and the sensor apparatus may, for a defined period of time, obtain data from the vertical accelerometer. Such data may be analyzed to determine a period of oscillation and to apply such period of oscillation to formulas for the model derived during calibration.

[00129] In some cases, the mass estimated based on such measurements may then be compared with expected to data to find anomalies or deterioration within the trailer or container.

[00130] A server such as servers **340**, **342** or **350** may be any network node. For example, one simplified server that may perform the embodiments described above is provided with regards to **Figure 10**.

[00131] In **Figure 10**, server **1010** includes a processor **1020** and a communications subsystem **1030**, where the processor **1020** and communications subsystem **1030** cooperate to perform the methods of the embodiments described herein.

[00132] The processor **1020** is configured to execute programmable logic, which may be stored, along with data, on the server **1010**, and is shown in the example of **Figure 10** as memory **1040**. The memory **1040** can be any tangible, non-transitory computer readable storage medium, such as DRAM, Flash, optical (e.g., CD, DVD, etc.), magnetic (e.g., tape), flash drive, hard drive, or other memory known in the art. In one embodiment, processor **1020** may also be implemented entirely in hardware and not require any stored program to execute logic functions.

[00133] Alternatively, or in addition to the memory **1040**, the server **1010** may access data or programmable logic from an external storage medium, for example through the communications subsystem **1030**.

[00134] The communications subsystem **1030** allows the server **1010** to communicate with other devices or network elements.

[00135] Communications between the various elements of the server **1710** may be through an internal bus **1060** in one embodiment. However, other forms of communication are possible.

[00136] The embodiments described herein are examples of structures, systems or methods having elements corresponding to elements of the techniques of this application. This written description may enable those skilled in the art to make and use embodiments having alternative elements that likewise correspond to the elements of the techniques of this application. The intended scope of the techniques of this application thus includes other structures, systems or methods that do not differ from the techniques of this application as described herein, and further includes other structures, systems or methods with insubstantial differences from the techniques of this application as described herein.

[00137] While operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be employed. Moreover, the separation of various system components in the implementation described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems can generally be integrated together in a signal software product or packaged into multiple software products. In some cases, functions may be performed entirely in hardware and such a solution may be the functional equivalent of a software solution.

[00138] Also, techniques, systems, subsystems, and methods described and illustrated in the various implementations as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods. Other items shown or discussed as coupled or directly coupled or communicating

with each other may be indirectly coupled or communicating through some interface, device, or intermediate component, whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and may be made.

[00139] While the above detailed description has shown, described, and pointed out the fundamental novel features of the disclosure as applied to various implementations, it will be understood that various omissions, substitutions, and changes in the form and details of the system illustrated may be made by those skilled in the art. In addition, the order of method steps is not implied by the order they appear in the claims.

[00140] When messages are sent to/from an electronic device, such operations may not be immediate or from the server directly. They may be synchronously or asynchronously delivered, from a server or other computing system infrastructure supporting the devices/methods/systems described herein. The foregoing steps may include, in whole or in part, synchronous/asynchronous communications to/from the device/infrastructure. Moreover, communication from the electronic device may be to one or more endpoints on a network. These endpoints may be serviced by a server, a distributed computing system, a stream processor, etc. Content Delivery Networks (CDNs) may also provide communication to an electronic device. For example, rather than a typical server response, the server may also provision or indicate data for a content delivery network (CDN) to await download by the electronic device at a later time, such as a subsequent activity of electronic device. Thus, data may be sent directly from the server, or other infrastructure, such as a distributed infrastructure, or a CDN, as part of or separate from the system.

[00141] Typically, storage mediums can include any or some combination of the following: a semiconductor memory device such as a dynamic or static random access memory (a DRAM or SRAM), an erasable and programmable

read-only memory (EPROM), an electrically erasable and programmable read-only memory (EEPROM) and flash memory; a magnetic disk such as a fixed, floppy and removable disk; another magnetic medium including tape; an optical medium such as a compact disk (CD) or a digital video disk (DVD); or another type of storage device. Note that the instructions discussed above can be provided on one computer-readable or machine-readable storage medium, or alternatively, can be provided on multiple computer-readable or machine-readable storage media distributed in a large system having possibly plural nodes. Such computer-readable or machine-readable storage medium or media is (are) considered to be part of an article (or article of manufacture). An article or article of manufacture can refer to any manufactured single component or multiple components. The storage medium or media can be located either in the machine running the machine-readable instructions, or located at a remote site from which machine-readable instructions can be downloaded over a network for execution.

[00142] In the foregoing description, numerous details are set forth to provide an understanding of the subject disclosed herein. However, implementations may be practiced without some of these details. Other implementations may include modifications and variations from the details discussed above. It is intended that the appended claims cover such modifications and variations.

CLAIMS

1. A method at a sensor apparatus affixed to a transportation asset, the method comprising:

calibrating the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating measuring spring oscillation and creating a model of the transportation asset;

detecting, subsequent to the calibrating, an impact event at the sensor apparatus;

measuring spring oscillation due to the impact event at the sensor apparatus; and

using the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.

2. The method of claim 1, wherein the measuring comprises:

sending a signal from a vertical accelerometer in the sensor apparatus to wake a processor of the sensor apparatus; and

recording, using the processor of the sensor apparatus, oscillations detected by the vertical accelerometer.

3. The method of claim 2, wherein the recording is for a predetermined time period.

4. The method of claim 1, wherein the method further comprises, prior to the measuring, determining that a trigger condition for the measuring exists.

5. The method of claim 4, wherein the trigger condition is one or more of: a door open event; a door close event; a threshold time period elapsing from a previous oscillation measurement; or a threshold time period in which the transportation asset is stationary.

6. The method of claim 1, wherein the calibrating creates a model with a plurality of oscillations based on one or more of: dampers; shock absorbers; air bags; multiple axles; or tractor coupling.
7. The method of claim 1, wherein the calibrating uses an empty transportation asset mass entered into or looked up by the sensor apparatus.
8. The method of claim 1, further comprising:
 - using the measured spring oscillation over a time period to detect deterioration of components within the transportation asset.
9. The method of claim 1, further comprising comparing the load mass estimate with an expected load mass to determine anomalies.
10. A sensor apparatus affixed to a transportation asset, the sensor apparatus comprising:
 - a processor; and
 - a communications subsystem,wherein the sensor apparatus is configured to:
 - calibrate the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating measuring spring oscillation and creating a model of the transportation asset;
 - detect, subsequent to the calibrating, an impact event at the sensor apparatus;
 - measure spring oscillation due to the impact event at the sensor apparatus; and
 - use the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.
11. The sensor apparatus of claim 10, wherein the sensor apparatus is configured to measure by:

sending a signal from a vertical accelerometer in the sensor apparatus to wake a processor of the sensor apparatus; and

recording, using the processor of the sensor apparatus, oscillations detected by the vertical accelerometer.

12. The sensor apparatus of claim 11, wherein the sensor apparatus is configured to record is for a predetermined time period.

13. The sensor apparatus of claim 10, wherein the sensor apparatus is further configured to, prior to measuring, determine that a trigger condition for the measuring exists.

14. The sensor apparatus of claim 13, wherein the trigger condition is one or more of: a door open event; a door close event; a threshold time period elapsing from a previous oscillation measurement; or a threshold time period in which the transportation asset is stationary.

15. The sensor apparatus of claim 10, wherein the sensor apparatus is configured to calibrate by creating a model with a plurality of oscillations based on one or more of: dampers; shock absorbers; air bags; multiple axles; or tractor coupling.

16. The sensor apparatus of claim 10, wherein the sensor apparatus is configured to calibrate using an empty transportation asset mass entered into or looked up by the sensor apparatus.

17. The sensor apparatus of claim 10, wherein the sensor apparatus is further configured to:

use the measured spring oscillation over a time period to detect deterioration of components within the transportation asset.

18. The sensor apparatus of claim 10, wherein the sensor apparatus is further configured to compare the load mass estimate with an expected load mass to determine anomalies.

19. A computer readable medium for storing instruction code, which, when executed by a processor of a sensor apparatus affixed to a transportation asset cause the sensor apparatus to:

- calibrate the sensor apparatus by initiating a vertical impact at the transportation asset, the calibrating measuring spring oscillation and creating a model of the transportation asset;

- detect, subsequent to the calibrating, an impact event at the sensor apparatus;

- measure spring oscillation due to the impact event at the sensor apparatus; and

- use the measured spring oscillation in the model created during calibration to create a load mass estimate for the transportation asset.





FIG. 1

2/9



3/9




FIG. 3

4/9




FIG. 4




FIG. 5

5/9




FIG. 6

6/9





FIG. 7

7/9

**FIG. 8**

8/9





FIG. 9

9/9

**FIG. 10**




FIG. 1