



US008764223B2

(12) **United States Patent**
Tsukitani et al.

(10) **Patent No.:** **US 8,764,223 B2**

(45) **Date of Patent:** **Jul. 1, 2014**

(54) **LIGHTING DEVICE**

(71) Applicant: **Panasonic Corporation**, Osaka (JP)

(72) Inventors: **Ayako Tsukitani**, Kyoto (JP); **Takashi Saito**, Osaka (JP); **Akira Takashima**, Hyogo (JP); **Kouichi Wada**, Osaka (JP); **Yoshinori Karasawa**, Osaka (JP); **Toshihide Mori**, Osaka (JP); **Hiroshi Hamano**, Hyogo (JM); **Kensuke Yamazoe**, Osaka (JP)

(73) Assignee: **Panasonic Corporation**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/869,445**

(22) Filed: **Apr. 24, 2013**

(65) **Prior Publication Data**

US 2013/0299851 A1 Nov. 14, 2013

(30) **Foreign Application Priority Data**

May 11, 2012 (JP) 2012-109390

(51) **Int. Cl.**

F21V 21/002 (2006.01)
F21V 9/00 (2006.01)
F21S 4/00 (2006.01)
F21S 8/10 (2006.01)
H01L 33/48 (2010.01)
H01L 33/58 (2010.01)

(52) **U.S. Cl.**

CPC **F21V 9/00** (2013.01); **F21S 48/115** (2013.01); **F21S 48/1154** (2013.01); **H01L 33/48** (2013.01); **H01L 33/58** (2013.01)
USPC **362/230**; 362/227; 362/231; 362/235; 362/294; 315/297; 257/88; 257/98; 257/E23.069; 257/E23.067

(58) **Field of Classification Search**

CPC F21V 9/00; F21S 48/115; F21S 48/1154; H01L 33/48; H01L 33/58
USPC 362/227, 230, 231, 235, 294; 315/297; 257/88, 98, E23.069, E23.067
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,406,172 B1 6/2002 Harbers et al.
7,628,508 B2 12/2009 Kita et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 09-120797 5/1997
JP 2008-091232 4/2008

(Continued)

OTHER PUBLICATIONS

John F. Van Derlofske et al., "White Led sources for vehicle forward lighting", Proceedings of SPIE, vol. 4776, 2002, XP002711232, , pp. 195-205.

(Continued)


Primary Examiner — Dao H Nguyen

(74) *Attorney, Agent, or Firm* — Greenblum & Bernstein, P.L.C.

(57) **ABSTRACT**

A lighting device includes first and second light emission units. The first light emission unit emits light having a relatively low color temperature and a high feeling of contrast index. The second light emission unit emits light having a relatively high S/P ratio, which is the ratio of scotopic luminance to photopic luminance. The first light emission unit illuminates a region located at a vertical upper side of a region illuminated by the second light emission unit.

5 Claims, 4 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS

8,388,174	B2 *	3/2013	Rooymans	362/231
2003/0156425	A1	8/2003	Turnbull et al.	
2008/0080178	A1	4/2008	Kita et al.	
2009/0302343	A1	12/2009	Sato et al.	
2010/0237766	A1 *	9/2010	Baumgartner et al.	313/498
2012/0015444	A1 *	1/2012	Mazumdar et al.	436/169
2012/0087115	A1 *	4/2012	Maxik	362/231
2012/0268927	A1 *	10/2012	Saito et al.	362/227
2012/0287618	A1 *	11/2012	Saito	362/230

JP	2010-539689	12/2010
JP	2011-009059	1/2011
JP	2011-175802	9/2011
WO	01/01038	1/2001
WO	2009/033642	3/2009

OTHER PUBLICATIONS

Search report from E.P.O., mail date is Aug. 23, 2013.

* cited by examiner

Fig.1A




Fig.1B




Fig.2A




Fig.2B




Fig.3

	Tc	FCI	S/P Ratio
1st Light Emission Unit	2900K	145	1.5
2nd Light Emission Unit	7900K	85	2.1
High Color Rendering Light Bulb Color LED	2800K	118	1.3

Fig.4




Fig.5




Fig. 6




Fig. 7




Fig. 8




Fig. 9





Fig. 10

	Configuration	Tc	FCI	S/P Ratio
1st Light Emission Unit	A1	2800	136	1.3
	A2	2600	145	1.5
	A3	2600	130	1.3
2nd Light Emission Unit	B1	5200	103	2.1
	B2	6400	82	2.0
	B3	4500	112	2.0

Fig. 11



1

LIGHTING DEVICE

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is based upon and claims the benefit of priority from prior Japanese Patent Application No. 2012-109390, filed on May 11, 2012, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to a lighting device.

Lighting devices, such as a fluorescent lamp and a light emitting diode (LED), are generally designed to increase the photopic luminance for photopic vision under well-lit conditions. The human eye uses cone cells to sense brightness for photopic vision. Thus, a higher photopic luminance increases the sensitivity of the human eye to light.

However, for mesopic vision used in nighttime street and road scenarios, the human eye uses rod cells in addition to cone cells. The peak value of the spectral luminous efficiency for cone cells is 555 nm, whereas the peak value of the spectral luminous efficiency for rod cells is 507 nm. Thus, an increase in only the photopic luminance would not be effective. Such a shift in the spectral luminous efficiency is known as the Purkinje effect.

Japanese Laid-Open Patent Publication No. 2008-91232 describes an example of a lighting device that takes into consideration that the cone cells and the rod cells in the human retina both function under mesopic vision situations. The lighting device includes a plurality of light sources so that the cone cells and the rod cells are both able to function. At least one of the light sources emits light having a peak value in a wavelength band from between 450 to 550 nm, which includes 507 nm that is the peak wavelength of the spectral luminous efficiency for rod cells.

The lighting device takes into consideration the Purkinje effect and relatively increases the short wavelength components of visible light in the spectral distribution of the light source. This increases brightness sensitivity under mesopic vision situations. However, when plants, such as street trees, are illuminated with light adjusted to conform to mesopic vision situations, green leaves would appear bluish and unnatural. This would not be scenic.

SUMMARY OF THE INVENTION

One aspect of the present invention is a lighting device that includes first and second light emission units. The first light emission unit emits light having a relatively low color temperature and a high feeling of contrast index. The second light emission unit emits light having a relatively high S/P ratio, which is the ratio of scotopic luminance to photopic luminance. The first light emission unit illuminates a region located at a vertical upper side of a region illuminated by the second light emission unit.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention, together with objects and advantages thereof, may best be understood by reference to the following description of the presently preferred embodiments together with the accompanying drawings in which:

FIG. 1A is a schematic diagram of a lighting device according to one embodiment of the present invention;

2

FIG. 1B is a schematic diagram showing first and second light emission units of the lighting device shown in FIG. 1;

FIG. 2A is a diagram showing the operation of the lighting device;

FIG. 2B is a diagram showing the operation of the lighting device;

FIG. 3 is a table showing the spectral characteristics of the first and second light emission units in the lighting device of FIG. 1A and the spectral characteristics of a light source in a comparative example;

FIG. 4 is a graph showing the spectral characteristics of the first and second light emission units in the lighting device of FIG. 1A and the spectral characteristics of the light source in the comparative example;

FIG. 5 is a schematic diagram showing a lighting device according to a further embodiment of the present invention;

FIG. 6 is a schematic diagram showing a lighting device according to a further embodiment of the present invention;

FIG. 7 is a schematic diagram showing a lighting device according to a further embodiment of the present invention;

FIG. 8 is a graph showing the spectral characteristics of a first emission unit in a lighting device according to a further embodiment of the present invention;

FIG. 9 is a graph showing the spectral characteristics of a second emission unit in a lighting device according to a further embodiment of the present invention;

FIG. 10 is a table showing the spectral characteristics of first and second light emission units in a lighting device according to a further embodiment of the present invention; and

FIG. 11 is a schematic diagram showing a lighting device according to a further embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

A lighting device according to one embodiment of the present invention will now be described with reference to the drawings.

As shown in FIG. 1A, a lighting device 10 of the present invention includes a cylindrical pole 11 and a main body 12. A portion of the pole 11 is buried in the ground. The main body 12 is coupled to one end of the pole 11. The main body 12 includes a housing 12a, a plurality of (for example, six) first light emission units 21, and a plurality of (for example, three) second light emission units 22. The main body 12 is configured to emit light from a lower position than a human H and a street tree T.

The first light emission units 21 are arranged at a vertical upper side of the second light emission units 22 arranged in the housing 12a. Thus, as shown in FIGS. 2A and 2B, the first light emission units 21, which are located at the vertical upper side of the second light emission units 22, illuminate a vertical upper area A1. The second light emission units 22, which are located below the first light emission units 21, illuminate a lower area A2. The upper area A1 is a region suitable for the illumination of the leaves of the street tree T that are higher than the human H and separated by a predetermined distance from the lighting device 10. The lower area A2 is a region suitable for the illumination of the height of the human H and lower.

As shown in FIG. 1B, the first light emission units 21 and the second light emission units 22 each include an LED element 23 and a bowl-shaped condenser lens 24. The LED element 23 of the first light emission unit 21 has a spectral distribution (spectral characteristic) that differs from that of the LED element 23 of the second light emission unit 22.

Referring to FIG. 3, the first light emission unit **21** emits light having a color temperature T_c of approximately 2900 K, a feeling of contrast index (FCI) of 145, and an S/P ratio of 1.5. The solid line in FIG. 4 shows the spectral characteristic of the light emitted from the first light emission unit **21**. Further, referring to FIG. 3, the second light emission unit **22** emits light having a color temperature T_c of approximately 7900 K, an FCI of 85, and an S/P ratio of 2.1. The single-dashed line in FIG. 4 shows the spectral characteristic of the light emitted from the second light emission unit **22**.

The FCI may be expressed by the equation shown below. Here, $G_{LAB}(T)$ represents the color gamut area of a color combination sample for the four colors of red, blue, green, and yellow in LAB coordinates under a test light source, and $G_{LAB}(D65)$ represents the color gamut area of the four-color combination sample in LAB coordinates under a reference light source (6500 K).

$$FCI = \left[\frac{G_{LAB}(T)}{G_{LAB}(D65)} \right]^{1.5} \times 100 \quad \text{Equation 1}$$

Further, the S/P ratio is a performance evaluation index of visibility under a mesopic vision situation. The S/P ratio may be calculated from the equation shown below. Here, L_s represents the scotopic luminance, L_p represents the photopic luminance, $S(\lambda)$ represents the spectral radiant intensity of the light source, $V(\lambda)$ represents the spectral luminous efficiency under a photopic vision situation, and $V'(\lambda)$ represents the spectral luminous efficiency under a mesopic vision situation.

$$S/P \text{ ratio} = \frac{L_s}{L_p} \quad \text{Equation 2}$$

$$L_s = \int S(\lambda) * V'(\lambda) d\lambda$$

where

$$L_p = \int S(\lambda) * V(\lambda) d\lambda$$

The operation of the lighting device will now be described.

When supplied with power from a power supply (not shown), the lighting device **10** activates the first light emission units **21** and the second light emission units **22**.

The first light emission units **21** are arranged at the vertical upper side of the second light emission units **22**. Thus, the first light emission units **21** emit light that illuminates the upper area **A1**, and the second light emission units **22** emit light that illuminates the lower area **A2** (refer to FIGS. 2A and 2B). The upper area **A1** is located at the vertical upper side of the lower area **A2**. The light from the first light emission units **21** has a higher FCI than a high color rendering light bulb color LED having about the same color temperature that is shown in FIGS. 3 and 4. This allows the leaves of the street tree **T** located in the upper area **A1** to have a vivid appearance.

The light emitted from the second light emission units **22** illuminates the lower area **A2**, which is located at a vertical lower side of the upper area **A1** illuminated by the light from the first light emission units **21**. Further, the light from the second light emission units **22** has a higher S/P ratio than the light from a high color rendering light bulb color LED. This increases the brightness sensitivity of the human eye at the lower side of the street tree **T**, which is in a mesopic vision situation, and ensures that visibility is obtained.

The above embodiment has the advantages described below.

(1) The lighting device **10** of the present embodiment includes the first light emission units **21**, which emit light having a relatively low color temperature and a high FCI, and the second light emission units **22**, which emit light having a relatively high S/P ratio that is the ratio of the scotopic luminance to the photopic luminance. The first light emission units **21** are configured to illuminate a region (area **A1**) at the upper side of a region (area **A2**) illuminated by the second light emission units **22**. The first light emission units **21** illuminate the upper region with light having a low color temperature and a high FCI. This allows the street tree **T** and its leaves to have a vivid appearance. Further, the second light emission units **22** illuminate the lower region with light having a high S/P ratio. This increases the brightness sensitivity and visibility even in a mesopic vision situation in the vicinity of the street tree **T**.

(2) The color temperature of the light from the first light emission units **21** is lower than the center value of 4150 K for the color of white (3800 to 4500 K) as specified by JIS Z9112. Further, the FCI of the light from the first light emission units **21** is higher than the FCI (**123**) of an incandescent lamp. The S/P ratio of the light from the second light emission units **22** is 2.1. This increases the brightness sensitivity under a mesopic vision situation.

The present embodiment may be modified as described below.

In the above embodiment, although not particularly described, for example, the first light emission units **21** and the second light emission units **22** may emit light in different directions so that the first light emission units **21** illuminate a region at the upper side of the region illuminated by the second light emission units **22**. Examples of such structures will now be given.

Referring to FIG. 5, the lighting device **10** includes a lower housing **31** and an upper housing **32**, which is formed integrally with the lower housing **31**. The lower housing **31** accommodates the first light emission units **21** and includes an upper surface **31a** from which the light of the first light emission units **21** is emitted. The upper housing **32** accommodates the second light emission units **22** and includes a front surface **32a** from which the light of the second light emission units **22** is emitted. The light emitted from the first light emission units **21** intersects with the light from the second light emission units **22**. Then, the light from the first light emission units **21** illuminates the leaves of the street tree **T** and the like (area **A1**), and the light from the second light emission units **22** illuminates the lower side of the street tree **T** (area **A2**).

Referring to FIG. 6, the lighting device **10** includes a housing **35** having a curved front surface **35a**. The housing **35** accommodates the first light emission units **21** and the second light emission units **22**. The first light emission units **21** emit light in a vertical upper direction from the upper side of the front surface **35a**. The second light emission units **22** emit light from a lower side of the front surface **35a** of the housing **35** toward a region below the region illuminated by the first light emission units **21** and in a rather horizontal direction.

In the above embodiment, although not particularly described, for example, as shown in FIG. 7, the first light emission units **21** and the second light emission units **22** may be formed by a plurality of LED elements **40** having the same spectral distribution (spectral characteristic). The LED elements **40** are arranged on a front surface **41a** of a cylindrical housing **41**. A transparent disk **42** (transparent member) entirely covers the LED elements **40**. The transparent disk **42**

5

has a rear surface **42a** that contacts the front surface **41a**. A filter **43** is arranged on a vertical upper side of a front surface **42b** of the transparent disk **42**. The filter **43** contains a substance that absorbs light in the wavelength band around, for example, 570 nm (between green and yellow). The LED elements **40** that emit light along a path including the filter **43** form the first light emission units **21**. Further, the LED elements **40** that emit light along a path separated from the filter **43** form the second light emission units **22**. In this manner, a first light emission unit **21** includes at least one first LED element **40** and the filter **43**, which is arranged in the path of the light emitted from the first LED element **40**, and a second light emission unit **22** includes at least one second LED element **40** having the same spectral characteristic as the first LED element **40**.

In the above embodiment, the configurations of **A1** to **A3** illustrated in FIGS. **8** and **10** may be used as the first light emission units **21**.

Configuration A1

Combination of a high color rendering light bulb color LED and a neodymium glass filter that absorbs light in the wavelength band around 570 nm.

Configuration A2

Combination of a gallium nitride blue LED, a gallium nitride green LED, and a SCASN red fluorescent body.

Configuration A3

Combination of a high color rendering light bulb color LED and an AlInGa red LED.

Further, the configurations of **B1** to **B3** illustrated in FIGS. **9** and **10** may be used as the second light emission units **22**.

Configuration B1

Combination of a gallium nitride blue LED and a YAG yellow fluorescent body.

Configuration B2

Combination of a gallium nitride blue LED, a CASN red fluorescent body, and a BOSE green fluorescent body.

Configuration B3

Combination of a gallium nitride blue LED and a YAG yellow fluorescent body.

In the above embodiment, the first light emission units **21** and the second light emission units **22** are arranged in a single housing **12a**. Instead, as shown in FIG. **11**, the first light emission units **21** and the second light emission units **22** may be arranged in separate housings **45** and **46**.

In the above embodiment, although not particularly described, the lighting device may include, for example, an illumination position changing means, that allows for a change in the direction light is emitted from the first light emission units **21** and the second light emission units **22**. That is, the lighting device may be pivotal. As shown in FIG. **11**, the housing **45**, which includes the first light emission units **21**, is pivotal about a pivot shaft **45a**, and may be fixed at a certain position by a stopper (not shown). Further, the housing **46**, which includes the second light emission units **22**, is

6

pivotal about a pivot shaft **46a**, and may be fixed at a certain position by a stopper (not shown). The first light emission units **21** are pivotal at the upper side of the second light emission units **22**. The second light emission units **22** are pivotal at the lower side of the first light emission units **21**.

In this manner, a lighting device according to a further embodiment of the present invention includes an illumination position changing means for changing an illumination position of at least one of a first light emission unit and a second light emission unit without changing an order in which a region illuminated by the first light emission unit and a region illuminated by the second light emission unit are arranged in a vertical direction.

This allows the position illuminated by either one of the first light emission unit and the second light emission unit to be changed.

It should be apparent to those skilled in the art that the present invention may be embodied in many other specific forms without departing from the spirit or scope of the invention. Therefore, the present examples and embodiments are to be considered as illustrative and not restrictive, and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalence of the appended claims.

The invention claimed is:

1. A lighting device comprising:

a first light emission unit that emits light having a relatively low color temperature and a high feeling of contrast index; and

a second light emission unit that emits light having a relatively high S/P ratio, which is the ratio of scotopic luminance to photopic luminance,

wherein the first light emission unit illuminates a region located at a vertical upper side of a region illuminated by the second light emission unit.

2. The lighting device according to claim 1, wherein the first light emission unit is configured to emit light having a color temperature that is 4150 K or less and a feeling of contrast index that is greater than 123, and the second light emission unit is configured to emit light having an S/P ratio that is 2.1 or greater.

3. The lighting device according to claim 2, wherein the first light emission unit includes at least one first LED element, and a filter arranged in a path of light emitted from the at least one first LED element.

4. The lighting device according to claim 3, wherein the second light emission unit includes at least one second LED element having a spectral characteristic that is the same as the first LED element.

5. The lighting device according to claim 3, wherein the filter contains a substance that absorbs light in a wavelength band around 570 nm.

* * * * *