

[19] Patents Registry
The Hong Kong Special Administrative Region
香港特別行政區
專利註冊處

[11] 1145552 B
EP 2232357 B1

[12]

STANDARD PATENT SPECIFICATION
標準專利說明書

[21] Application No. 申請編號
10111901.3

[51] Int.Cl.⁸ G06F

[22] Date of filing 提交日期
20.12.2010

[54] TOUCH EVENT MODEL FOR WEB PAGES 用於WEB頁面的觸摸事件模型

Divisional application 13107101.6 filed on 18.06.2013.

分開申請編號 13107101.6 於 18.06.2013 提交

[30] Priority 優先權
04.03.2008 US US20080042067

[43] Date of publication of application 申請發表日期
21.04.2011

[45] Publication of the grant of the patent 批予專利的發表日期
04.08.2017

EP Application No. & Date 歐洲專利申請編號及日期

EP 09700006.1 03.03.2009

EP Publication No. & Date 歐洲專利申請發表編號及日期

EP 2232357 29.09.2010

Date of Grant in Designated Patent Office 指定專利當局批予專利日期

11.05.2016

[73] Proprietor 專利所有人

Apple, Inc.

1 Infinite Loop

Cupertino, CA 95014

UNITED STATES/UNITED STATES OF AMERICA

[72] Inventor 發明人

WILLIAMSON, Richard

BOLSINGA, Gregory Dennis

OMERNICK, Tim

[74] Agent and / or address for service 代理人及/或送達地址

EMILY YIP & CO

1st Floor, Kingsfield Centre

18 Shell Street

Fortress Hill HONG KONG



(11) **EP 2 232 357 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
11.05.2016 Bulletin 2016/19

(51) Int Cl.:
G06F 3/048 ^(2006.01) **G06F 17/22** ^(2006.01)
G06F 17/30 ^(2006.01)

(21) Application number: **09700006.1**

(86) International application number:
PCT/US2009/035856

(22) Date of filing: **03.03.2009**

(87) International publication number:
WO 2009/111458 (11.09.2009 Gazette 2009/37)

(54) **TOUCH EVENT MODEL FOR WEB PAGES**

BERÜHRUNGSEVENT FÜR WEBSEITEN

MODÈLE D'ÉVÉNEMENT TACTILE POUR DES PAGES WEB

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

(74) Representative: **Gillard, Matthew Paul et al**
Withers & Rogers LLP
4 More London Riverside
London
SE1 2AU (GB)

(30) Priority: **04.03.2008 US 42067**

(43) Date of publication of application:
29.09.2010 Bulletin 2010/39

(56) References cited:
EP-A- 1 517 228 WO-A-2006/094308
US-A1- 2005 162 402 US-A1- 2006 026 521
US-A1- 2006 161 871 US-B1- 6 323 846
US-B1- 6 570 557 US-B1- 6 677 932

(60) Divisional application:
12188748.3 / 2 549 370

(73) Proprietor: **APPLE INC.**
Cupertino, CA 95014 (US)

- "Document Object Model (DOM) Level 2 Events Specifications Version 1.0" W3C RECOMMENDATION, XX, XX, 13 November 2000 (2000-11-13), pages 1-47, XP002996169
- 'Java Programming/Applets/Event Listeners' WIKI BOOKS, [Online] 01 May 2007, XP055054024 Retrieved from the Internet:
<URL:http://en.wikibooks.org/w/index.php?title=Java_Programming/Applets/Event_Listener&oldid=849558> [retrieved on 2013-02-20]
- BROWN M H ET AL: "Distributed active objects", COMPUTER NETWORKS AND ISDN SYSTEMS, NORTH HOLLAND PUBLISHING. AMSTERDAM, NL, vol. 28, no. 11, 1 May 1996 (1996-05-01), pages 1037-1052, XP004018206, ISSN: 0169-7552, DOI: 10.1016/0169-7552(96)00033-5

(72) Inventors:

- **WILLIAMSON, Richard**
Los Gatos
California 95033 (US)
- **BOLSINGA, Gregory Dennis**
San Francisco
California 94102 (US)
- **OMERNICK, Tim**
Mountain View
California 94041 (US)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 232 357 B1

Description

TECHNICAL FIELD

[0001] This subject matter is generally related to web browsing services.

BACKGROUND

[0002] Web pages are created using a markup language which provides a means to describe a structure of text-based information in a document and to supplement that text with interactive forms, embedded images, and other objects. One popular markup language is HyperText Markup Language (HTML) which is written in the form of tags surrounded by angle brackets. HTML can describe the appearance and semantics of a web page, and can include embedded scripting language code (e.g., JavaScript®) which can affect the behavior of web browsers and other HTML processors. JavaScript® provides developers with the ability to add mouse event handlers or event listeners in a web page. These mouse event handlers can be assigned to specific regions of the web page and configured to receive mouse events in those regions, such as mouse up or mouse down events.

[0003] By contrast, web pages that are navigated with a touch sensitive device often need to respond to touch events generated by a user touching a web page with one or more fingers and making gestures. Conventional mouse event handlers cannot correctly interpret these touch events. Thus touch events require a different touch event model to correctly interpret touch events and to allow developers to fully utilize the capabilities of a touch sensitive display or device.

[0004] From patent publication US 2005/0162402 A1 (D1) there is known a data input device with a finger touch sensing surface.

[0005] From publication "Document Object Model (DOM) Level 2 Events Specification version 1.0 W3C RECOMMENDATION" there is known a document object model.

SUMMARY

[0006] One or more touch input signals can be obtained from a touch sensitive device. A touch event model can be used to determine touch and/or gesture events based on the touch input signals. The touch and/or gesture events can be associated with touch input signals generated from different regions of a web page displayed on the touch sensitive device. Access can be provided to at least one touch or gesture event through a programming interface.

[0007] In some implementations, a method includes: obtaining one or more touch input signals from a touch sensitive device, determining two or more touch events based on the touch input signals, where the touch events are associated with touch input signals associated with

two or more regions of a web page displayed on the touch sensitive device, and providing access to at least one touch event through a programming interface.

[0008] In other implementations, a method includes: obtaining one or more touch input signals from a touch sensitive device, determining two or more touch events based on the touch input signals, where the touch events are associated with touch input signals associated with two or more regions of a web page displayed on the touch sensitive device, and sending the two or more touch events to the web page for processing.

[0009] Other implementations are disclosed which are directed to systems, methods and computer-readable mediums.

DESCRIPTION OF DRAWINGS

[0010]

FIG. 1 illustrates an example web page document.

FIG. 2 illustrates a processing stack of an example multi-touch capable device.

FIG. 3 is a flow diagram of an example process for processing touch events.

FIG. 4 illustrates an example multi-touch capable device.

FIG. 5 is a block diagram of an example network operating environment for the multi-touch capable device of FIG. 4.

FIG. 6 is a block diagram of an example implementation of the multi-touch capable device of FIG. 4.

DETAILED DESCRIPTION

Example Web Page Structure and DOM

[0011] FIG. 1A shows an example web page 100 that can be displayed on a browser. The browser may be hosted on a portable device, such as the multi-touch capable device 400 of FIG. 4. One or more elements, element 102 ("element 1"), element 104 ("element 2"), and element 106 ("element 3") can be displayed on the web page 100. The elements 102, 104, 106 can correspond to regions of the web page 100 that a user can select and additional functionality can be provided as a result of the selection. The elements can, for example, correspond to buttons on the web page 100. The elements can also be nested so that one element contains another element. For example, element 104 contains element 108. In the example shown, the element 108 is a scrubber control nested within element 104 which can be a media player user interface, for example.

[0012] In some implementations, a user may perform various functions with the elements on the web page 100 using a finger instead of a mouse. The user can, for example, touch the elements of the web page 100 using the touch sensitive display 402 shown in FIG. 4. In one example, the user can select an element by touching the

element with one or more fingers and/or making a gesture, such as a swiping, pinching or rotating motion.. To recognize touch input signals, certain areas of the web page 100 may be associated with touch event handlers. This can be accomplished with a DOM and embedded scripting language, as will be described in reference to FIG.1B.

[0013] FIG. 1B is an exemplary DOM 150 associated with the web page 100. The DOM 150 provides a structural representation of the web page 100 and describes the web page content as a set of objects that a scripting language (e.g., JavaScript®) can interpret. In some implementations, the DOM 150 provides access to the structure of a web page by mapping the elements 102, 104, 106, 108 in the web page 100 to individual nodes of a tree. For example, element 102 corresponds to node 154. Element 104 corresponds to node 156. Element 106 corresponds to node 158. Element 108 corresponds to node 160. The root node 152 corresponds to the overall web page 100.

[0014] In some implementations, one or more elements 102, 104, 106, 108 in web page 100 can be associated with one or more corresponding touch event handler by associating corresponding nodes in the DOM 150 with the touch event handlers. Touch event handlers can be inserted into HTML tags of the web page 100 and can execute a scripting language to perform an action when, for example, a user touches or gestures within one of the elements on the web page 100. For example, JavaScript® can work with the DOM 150 to attach actions to different touch events.

[0015] In some implementations, one or more elements 102, 104, 106, 108 can receive touch input which is detected by an event handler or listener. The touch input can be detected and processed into touch events by a touch event model which can be implemented in one or more layers of a software stack, as described in reference to FIG. 2. The touch events can be further processed by the web page 100. The touch events can be in a format (e.g., attributes) that are easier to use in an application than raw touch input signals generated by the touch sensitive device. For example, each touch event can include a set of coordinates at which a touch is currently occurring.

[0016] Each element in the web page 100, and its associated event handler, can receive, process and handle touch events. For example, if driver 202 (FIG. 2) senses a touch point 110 associated with element 102, or a touch point 112 associated with element 104, the event handlers associated with elements 102 or 104 can each receive a separate touch event indicating that the element has been touched and can optionally send the touch event to the web page 100 for further processing. In some implementations, if a region of the web page 100 is touched that does not correspond to an event handler, a browser in the applications layer 214 can process the input, instead of the web page 100.

[0017] In some implementations, a touch event can be

detected per finger per node in the DOM 150. For example, a user can touch the touch sensitive display 402 at touch point 110 and touch point 112 at substantially the same time, and two separate touch events can be detected by the touch event model. A separate touch event can be detected for touch point 110 and touch point 112 because each node 102 and node 104 in the DOM 150 are associated with a separate touch event handler.

[0018] In some implementations, touch events can be delivered to the web page 100 as EventTargets. Some examples of touch events can include touchstart, touchmove, touchend, and touchcancel. Other touch events are possible. Touchstart is a touch event that is detected when a user first places a finger on the touch sensitive display 402 in a region on the web page 100 that is associated with an event handler. When the user moves his finger around on the web page 100, one or more touchmove events can be detected. When the user raises his finger off of the web page 100, a touchend event is detected. The touchcancel can be detected when the system interrupts regular event handling. For example, a touchcancel event can occur when the touch sensitive display 402 is locked out to prevent inadvertent touches.

[0019] In some implementations, gesture events can also be detected by combining two or more touch events. Like touch events, the gesture events (GestureEvents) can also be delivered to the web page 100 as EventTargets. Some examples of gesture events can be gesturestart, gesturechange, and gestureend. The gesture events can contain scale and/or rotation information. The rotation information can include a rotation value that is a relative delta in degrees. An element on the webpage 100 can be dynamically rotated base on the rotation value. The scale information can include a scaling value that is a relative delta in document pixels. An element on the webpage 100 associated with the gesture event can be dynamically resized based on the scaling value. Other gesture events are possible.

[0020] In some implementations, a touch list can be received that includes touch event data to identify one or more touches on the web page 100. The touch event data can include a touch identifier and at least one set of touch location coordinates. The touch list can also include touch event data to a touch event target associated with each touch. In some implementations, the one set of touch location coordinates can include client coordinates, page coordinates, and screen coordinates. In some implementations, the touch event data can identify one or more changed touches.

[0021] In some implementations, GestureEvents can be sent to the web page 100 before TouchEvents. For example, if a user places fingers on touch point 110 and touch point 112, then makes a rotating gesture with those fingers clockwise or counterclockwise on the touch sensitive display, the touch event model detects these multiple touch events and combines the touch events into a gesture event. The gesture event can then be sent to the web page 100, followed by the touch events that were

combined to form the gesture event. This way, a developer has access to a gesture event and the individual touch events of the gesture event which provides the developer with more flexibility when developing a web application.

[0022] In some implementations, the touch events are received in the following order: a touchstart event, one or more touchmove events and a touchend or touchcancel event. Using the example of FIG. 1A, when the user touches touch point 110, a first touchstart event is detected by a first touch event handler associated with element 102. When the user touches touch point 112, a second touchstart event is detected by a second touch event handler associated with element 104. As the user rotates her fingers without lifting her fingers, the first and second touch event handlers detect touchmove events which can be interpreted by the touch event model as a rotation gesture event. When the user finishes the rotation and lifts her fingers from the web page 100, the first and second touch event handlers detect touchend events. All or some of these touch events can be made available to developers through a touch event Application Programming Interface (API). The touch API can be made available to developers as a Software Development Kit (SDK) or as part of an application (e.g., as part of a browser tool kit). The touch event API can rely on other services, frameworks and an operating system to perform its various functions. These services, frameworks and operating system can be part of a software or processing stack, as described in reference to FIG. 2. where the touch events are associated with attributes that can be inserted in documents to define event actions in an application.

Example IDL

[0023] An example touch event model will now be described in Interface Description Language (IDL). The functionality and data structures of the IDL can be accessed through an API by a web designer or application developer. Access to touch events and/or gesture events can be associated with attributes that can be inserted in an markup language document (e.g., HTML, XML) to define event actions in an application. For example, the attributes can be inserted in one or more HTML tags in an HTML document for generating the web page displayed on the touch sensitive display 402. The event actions can include running an embedded script (e.g., JavaScript®).

```
interface [
  Conditional=TOUCH_EVENTS,
  GenerateConstructor
] TouchEvent : UIEvent {
  void initTouchEvent(in AtomicString type,
    in boolean canBubble,
    in boolean cancelable,
    in DOMWindow view,
```

```
    in long detail,
    in long screenX,
    in long screenY,
    in long clientX,
    in long clientY,
    in boolean ctrlKey,
    in boolean altKey,
    in boolean shiftKey,
    in boolean metaKey,
    in TouchList touches,
    in TouchList targetTouches,
    in TouchList changedTouches,
    in long scale,
    in long rotation);
  readonly attribute TouchList touches; // all
  touches
  readonly attribute TouchList targetTouches;
  // all touches in this TouchEvent Target
  readonly attribute TouchList changedTouches;
  // all touches changed in the current
  event
  readonly attribute long scale;
  readonly attribute long rotation;
  readonly attribute boolean ctrlKey;
  readonly attribute boolean shiftKey;
  readonly attribute boolean altKey;
  readonly attribute boolean metaKey;
};
interface [
  Conditional=TOUCH_EVENTS,
] Touch {
  readonly attribute EventTarget target;
  readonly attribute long identifier;
  readonly attribute long clientX;
  readonly attribute long clientY;
  readonly attribute long pageX;
  readonly attribute long pageY;
  readonly attribute long screenX;
  readonly attribute long screenY;
};
interface [
  Conditional=TOUCH_EVENTS,
  HasIndexGetter,
] TouchList {
  readonly attribute unsigned long length;
  Touch item(in unsigned long index);
};
interface [
  Conditional=TOUCH_EVENTS,
  GenerateConstructor
] GestureEvent: UIEvent {
  void initGestureEvent(in AtomicString type,
    in boolean canBubble,
    in boolean cancelable,
    in DOMWindow view,
    in long detail,
    in long screenX,
    in long screenY,
    in long clientX,
    in long clientY,
    in boolean ctrlKey,
    in boolean altKey,
    in boolean shiftKey,
```

```

        in boolean metaKey,
        in EventTarget target,
        in long scale,
        in long rotation);
readonly attribute EventTarget target;
readonly attribute long scale;
readonly attribute long rotation;
readonly attribute boolean ctrlKey;
readonly attribute boolean shiftKey;
readonly attribute boolean altKey;
readonly attribute boolean metaKey;
};
In Document.idl:
Touch createTouch(in EventTarget target,
        in long identifier,
        in long clientX,
        in long clientY,
        in long pageX,
        in long pageY,
        in long screenX,
        in long screenY)
    raises (DOMException);
[Custom] TouchList createTouchList()
    raises (DOMException);

```

[0024] The following is example of HTML code snippet for processing touch events using the example IDL above. The HTML below shows, for example, that the touch event listener TouchStart and GestureStart were added to an element with the HTML code:

```

this.element.addEventListener('touchstart',
function(e) { return
self.onTouchStart(e) }, false);
this.element.addEventListener('gesturestart',
function(e) { return
self.onGestureStart(e) }, false);

```

[0025] The HTML code corresponding to the IDL above may be as follows:

```

<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01
Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<html lang="en">
<head>
<meta http-equiv="Content-Type"
content="text/html; charset=utf-8">
<meta name="viewport" content="initial-
scale=1.0" />
<title>Transform Gestures</title>
<style type="text/css" media="screen">
    .box {
        position: absolute;
        height 150px;
        width: 150px;
        background-color:blue;
    }
    .box:active {
        background-color: red;
    }
    body {

```

```

        margin: 0px;
    }
    #container {
        position: absolute;
        width: 100%;
        height: 100%;
    }
    #main-box2 {
        top: 10px;
        left: 155px;
        background: red;
        z-index: 1;
    }
</style>
<script type="text/javascript"
charset="utf-8">
    var trackedObjectCount = 0;
    function Box(inElement)
    {
        var self = this;
        this.element = inElement;
        this.scale = 1.0;
        this.rotation = 0;
        this.position = ' 0,0';
        this.element.addEventListener('touchstart',
function(e) {return
self.onTouchStart(e)}, false);
        this.element.addEventListener('gesturestart',
function (e) { return
self.onGestureStart(e) }, false);
    }
    Box.prototype = {
        // position strings are "x,y" with no units
        get position()
        {
            return this._position;
        },
        set position(pos)
        {
            this._position = pos;
            var components = pos.split(',');
            var x = components[0];
            var y = components[1];
            const kUseTransform = true;
            if (kUseTransform) {
                this.element.style.webkitTransform
= 'rotate(' + this.rotation + 'deg) scale(' +
this.scale + ') translate(' + x +
'px,' + y + 'px)';
            }
            else {
                this.element.style.left= x +'px';
                this.element.style.top = y +'px';
            }
        },
        get x ()
        {
            return parseInt(this._position.split(',')
[0]);
        },
        set x(inX)
        {

```

```

var comps = this._position.split(',');
comps[0] = inX;
this.position = comps.join(',');
},
get y()
{
return
parseInt(this._position.split(',')[1]);
},
set y(inY)
{
var comps = this._position.split(',');
comps[1] = inY;
this.position = comps.join(',');
},
filterEvent: function(e)
{
// Prevent the browser from doing its
default thing (scroll, zoom)
e.preventDefault();
// Event listeners are added at the
document level, so we receive gesturechange
events for other elements.
return (e.target == this.element);
},
onTouchStart: function(e)
{
if (!this.filterEvent(e))
return false;
// Start tracking when the first finger
comes down in this element
if (e.targetTouches.length !=1)
return false;
this.startX = e.targetTouches[0].clientX;
this.startY = e.targetTouches[0].clientY;
var self = this;
if (!("touchMoveHandler" in this)) {
this.touchMoveHandler = function(e)
{ return self.onTouchMove(e) }
this.touchEndHandler = function(e)
{ return self.onTouchEnd(e) }
}
document.addEventListener('touchmove',
this.touchMoveHandler, false);
document.addEventListener('touchend',
this.touchEndHandler, false);
trackedObjectCount++;
return false;
},
onTouchMove: function(e)
{
if (!this.filterEvent(e))
return false;
// Don't track motion when multiple
touches are down in this element (that's a
gesture)
if (e.targetTouches.length !=1)
return false;
var leftDelta = e.targetTouches[0].clientX
- this.startX;
var topDelta = e.targetTouches[0].clientY
- this.startY;
var newLeft = (this.x) + leftDelta;

```

```

var newTop = (this.y) + topDelta;
this.position = newLeft + ',' + newTop;
this.startX = e.targetTouches[0].clientX;
this.startY = e.targetTouches[0].clientY;
return false;
},
onTouchEnd: function(e)
{
if (!this.filterEvent(e))
return false;
// Stop tracking when the last finger
is removed from this element
if (e.targetTouches.length > 0)
return false;
document.removeEventListener('touchmove',
this.touchMoveHandler, false);
document.removeEventListener('touchend',
this.touchEndHandler, false);
trackedObjectCount--;
return false;
},
onGestureStart: function(e)
{
if (!this.filterEvent(e))
return false;
var self = this;
if (!("gestureChangeHandler" in this)) {
this.gestureChangeHandler = function(e)
{ return self.onGestureChange(e) }
this.gestureEndHandler = function(e)
{ return self.onGestureEnd(e) }
}
document.addEventListener('gesturechange',
this.gestureChangeHandler, true);
document.addEventListener('gestureend',
this.gestureEndHandler, true);
return false;
},
onGestureChange: function(e)
{
if (!this.filterEvent(e))
return false;
// Only interpret gestures when tracking
one object. Otherwise, interpret raw
touch events
// to move the tracked objects.
if (trackedObjectCount == 1) {
this.scale += e.scaling * 0.01;
this.rotation += e.rotation / 2;
this.position = this.position;
}
return false;
},
onGestureEnd: function(e)
{
if (!this.filterEvent(e))
return false;
document.removeEventListener('gesturechange',
this.gestureChangeHandler,
true);
document.removeEventListener('gestureend',

```

```

this.gestureEndHandler, true);
    return false;
  },
}
function loaded ()
{
  new Box(document.getElementById('main-
box'));
  new Box(document.getElementById('main-
box2'));
}
window.addEventListener('load', loaded,
true);
</scrip>
</head>
<body>
<div id="container">
  <div id="main-box" class="box"></div>
  <div id="main-box2" class="box"></div>
</div>
</body>
</html>

```

Example Processing Stack for Multi-Touch Device

[0026] FIG. 2 is a diagram of a processing stack of an example multi-touch capable device. The touch event model described above can be implemented in one or more regions of the processing stack and user various resources in the stack. The hardware 200 layer can include various hardware interface components, such as a touch sensitive or enabled device or touch sensitive display. The touch sensitive device can include a display and a panel that senses multiple touches simultaneously. The hardware layer 200 can also include an accelerometer for detecting an orientation of the touch sensitive display or device (e.g., portrait, landscape). Thus signals indicative of orientation can be used by the touch event model to scale web pages for optimum display.

[0027] One or more drivers in a driver layer 202 can communicate with the hardware 200. For example, the drivers can receive and process touch input signals generated by the touch sensitive display or device in the hardware layer 200. A core Operating System (OS) 204 can communicate with the driver(s). The core OS 204 can process raw input data received from the driver(s). In some embodiments, the drivers can be considered to be a part of the core OS 204.

[0028] A set of OS application programming interfaces (APIs) 206 can communicate with the core OS 204. These APIs can be a set of APIs that are usually included with operating systems (such as, for example, Linux or UNIX APIs). A set of core foundation APIs 208 can utilize the OS APIs 206, and a set of foundation APIs 210 can utilize the core foundation APIs 208.

[0029] Web page software development kit (SDK) 210 can include a set of APIs designed for use by applications running on the device. The touch event APIs can, for example, be included in the Web page SDK 210. The

APIs of the Web page SDK 210 can utilize the foundation APIs 208. The Web page SDK 210 can, for example, include Web KIT provided by Apple Inc. The Web page SDK 210 can be offered as an API or can be accessible through an application, for example, a browser such as SAFARI®, provided by Apple Inc.

[0030] Applications 214 running on the device can utilize the APIs of the Web page SDK 210 to create web pages. The APIs of the Web page SDK 210 can, in turn, communicate with lower level elements, ultimately communicating with the touch sensitive display or device and various other user interface hardware. While each layer can utilize the layer underneath it, that is not always required. For example, in some embodiments, applications 214 can occasionally communicate with OS APIs 206.

Example Touch Event Process

[0031] FIG. 3 is a flow diagram of a process 300 for providing access to touch and/or gesture events though an API. The process 300 can begin by obtaining one or more touch input signals (302). The touch input signals can be obtained from a touch sensitive display or device. A determination of touch events and/or gestures can be made based on the touch input signals using a touch event model (304). The touch events can be associated with regions of a web page displayed on a touch sensitive display or device. For example, the touch sensitive display can be a display on a mobile phone, and a touch sensitive device can be a touch sensitive pad on a notebook computer. Access to touch events and/or gesture events can be provided through a programming interface (306). For example, with respect to the HTML snippet described above with reference to FIG. 2, the snippet can be inserted into an HTML document by the web developer to provides the developer with access to touch and/or gesture events. The touch events and/or gesture events can be further processed by code in the HTML document to initiate event actions (306).

Mobile Device Overview

[0032] FIG. 4 is a block diagram of an example multi-touch capable device 400. In some implementations, the multi-touch capable device 400 includes a touch sensitive display 402. The touch sensitive display 402 can implement liquid crystal display (LCD) technology, light emitting polymer display (LPD) technology, or some other display technology. The touch sensitive display 402 can be sensitive to haptic and/or tactile contact with a user.

[0033] In some implementations, the touch sensitive display 402 can comprise a multi-touch sensitive display 402. A touch sensitive display 402 can, for example, process multiple simultaneous touch points, including processing data related to the pressure, degree and/or position of each touch point. Such processing facilitates gestures and interactions with multiple fingers, chording,

and other interactions. Other touch sensitive display technologies can also be used, e.g., a display in which contact is made using a stylus or other pointing device. Some examples of multi-touch sensitive display technology are described in U.S. Patent Nos. 6,323,846, 6,570,557, 6,677,932, and U.S. Patent Publication 2002/0015024A1, each of which is incorporated by reference herein in its entirety. In some implementations, the multi-touch capable device 400 can display one or more graphical user interfaces on the touch sensitive display 402 for providing the user access to various system objects and for conveying information to the user.

Example Multi-Touch Capable Device Functionality

[0034] In some implementations, the multi-touch capable device 400 can implement multiple device functionalities, such as a telephony device, an e-mail device, a network data communication device, a Wi-Fi base station device, and a media processing device. In some implementations, the multi-touch capable device 400 can include a web browser 404 for displaying web pages (e.g., web page 100). The touch sensitive display 402 can receive touch input signals made on the web page 100 and the touch model described above can be used to determine touch and/or gesture events based on the touch input signals. In some implementations, the multi-touch capable device 400 can implement network distribution functionality. In some implementations, the touch sensitive display 402 can be locked down when the multi-touch capable device 400 is proximate to the user's ear. This lockdown would cause a touchcancel event as described in reference to FIG. 1B.

[0035] In some implementations, an accelerometer 472 can be utilized to detect movement of the multi-touch capable device 400, as indicated by the directional arrow 474. Accordingly, display objects and/or media can be presented according to a detected orientation, e.g., portrait or landscape. In some implementations, the multi-touch capable device 400 may include circuitry and sensors for supporting a location determining capability, such as that provided by the global positioning system (GPS) or other positioning systems (e.g., systems using Wi-Fi access points, television signals, cellular grids, Uniform Resource Locators (URLs)). In some implementations, a positioning system (e.g., a GPS receiver) can be integrated into the multi-touch capable device 400 or provided as a separate device that can be coupled to the multi-touch capable device 400 through an interface to provide access to location-based services. The multi-touch capable device 400 can also include one or more wireless communication subsystems.

[0036] In some implementations, a port device, e.g., a Universal Serial Bus (USB) port, or a docking port, or some other wired port connection, can be included. The port device can, for example, be utilized to establish a wired connection to other computing devices, such as other multi-touch capable devices 400, network access

devices, a personal computer, a printer, or other processing devices capable of receiving and/or transmitting data. In some implementations, the port device allows the multi-touch capable device 400 to synchronize with a host device using one or more protocols, such as, for example, the TCP/IP, HTTP, UDP and any other known protocol.

Network Operating Environment

[0037] FIG. 5 is a block diagram of an example network operating environment 600 for the multi-touch capable device 400 of FIG. 4. The multi-touch capable device 400 of FIG. 4 can, for example, communicate over one or more wired and/or wireless networks 510 in data communication. For example, a wireless network 512, e.g., a cellular network, can communicate with a wide area network (WAN) 514, such as the Internet, by use of a gateway 516. Likewise, an access point 518, such as an 802.11g wireless access point, can provide communication access to the wide area network 514. In some implementations, both voice and data communications can be established over the wireless network 512 and the access point 518. For example, the multi-touch capable device 400a can place and receive phone calls (e.g., using VoIP protocols), send and receive e-mail messages (e.g., using POP3 protocol), and retrieve electronic documents and/or streams, such as web pages, photographs, and videos, over the wireless network 512, gateway 516, and wide area network 514 (e.g., using TCP/IP or UDP protocols). Likewise, the multi-touch capable device 400b can place and receive phone calls, send and receive e-mail messages, and retrieve electronic documents over the access point 518 and the wide area network 514. In some implementations, the multi-touch capable device 400 can be physically connected to the access point 518 using one or more cables and the access point 518 can be a personal computer. In this configuration, the multi-touch capable device 400 can be referred to as a "tethered" device.

[0038] The multi-touch capable devices 400a and 400b can also establish communications by other means. For example, the multi-touch capable device 400a can communicate with other wireless devices, e.g., other multi-touch capable devices 400, cell phones, etc., over the wireless network 512. Likewise, the multi-touch capable device 400a and 400b can establish peer-to-peer communications 520, e.g., a personal area network, by use of one or more communication subsystems, such as the Bluetooth™ communication device 488 shown in FIG. 4. Other communication protocols and topologies can also be implemented.

[0039] The multi-touch capable device 400 can, for example, communicate with a network resource 530 over the one or more wired and/or wireless networks 510. For example, the network resource can be a web server for delivering web pages which can be touched via the touch model, as described in reference to FIGS. 1-2.

[0040] Other services can also be provided, including

a software update service that automatically determines whether software updates exist for software on the multi-touch capable device 400, then downloads the software updates to the multi-touch capable device 400 where it can be manually or automatically unpacked and/or installed.

Example Mobile Device Architecture

[0041] FIG. 6 is a block diagram 600 of an example implementation of the multi-touch capable device 400 of FIG. 4. The multi-touch capable device 400 can include a memory interface 602, one or more data processors, image processors and/or central processing units 604, and a peripherals interface 606. The memory interface 602, the one or more processors 604 and/or the peripherals interface 606 can be separate components or can be integrated in one or more integrated circuits. The various components in the multi-touch capable device 400 can be coupled by one or more communication buses or signal lines.

[0042] Sensors, devices and subsystems can be coupled to the peripherals interface 606 to facilitate multiple functionalities. For example, a motion sensor 610, a light sensor 612, and a proximity sensor 614 can be coupled to the peripherals interface 606 to facilitate the orientation, lighting and proximity functions described with respect to FIG. 4. Other sensors 616 can also be connected to the peripherals interface 606, such as a positioning system (e.g., GPS receiver), a temperature sensor, a biometric sensor, or other sensing device, to facilitate related functionalities.

[0043] A camera subsystem 620 and an optical sensor 622, e.g., a charged coupled device (CCD) or a complementary metal-oxide semiconductor (CMOS) optical sensor, can be utilized to facilitate camera functions, such as recording photographs and video clips.

[0044] Communication functions can be facilitated through one or more wireless communication subsystems 624, which can include radio frequency receivers and transmitters and/or optical (e.g., infrared) receivers and transmitters. The specific design and implementation of the communication subsystem 624 can depend on the communication network(s) over which the multi-touch capable device 400 is intended to operate. For example, a multi-touch capable device 400 may include communication subsystems 624 designed to operate over a GSM network, a GPRS network, an EDGE network, a Wi-Fi or WiMax network, and a Bluetooth™ network. In particular, the wireless communication subsystems 624 may include hosting protocols such that the device 500 may be configured as a base station for other wireless devices.

[0045] An audio subsystem 626 can be coupled to a speaker 628 and a microphone 630 to facilitate voice-enabled functions, such as voice recognition, voice replication, digital recording, and telephony functions.

[0046] The I/O subsystem 640 can include a touch

screen controller 642 and/or other input controller(s) 644. The touch-screen controller 642 can be coupled to a touch screen 646. The touch screen 646 and touch screen controller 642 can, for example, detect contact and movement or break thereof using any of a plurality of touch sensitivity technologies, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with the touch screen 646.

[0047] The other input controller(s) 644 can be coupled to other input/control devices 648, such as one or more buttons, rocker switches, thumb-wheel, infrared port, USB port, and/or a pointer device such as a stylus. The one or more buttons (not shown) can include an up/down button for volume control of the speaker 628 and/or the microphone 630.

[0048] In one implementation, a pressing of the button for a first duration may disengage a lock of the touch screen 646; and a pressing of the button for a second duration that is longer than the first duration may turn power to the multi-touch capable device 400 on or off. The user may be able to customize a functionality of one or more of the buttons. The touch screen 646 can, for example, also be used to implement virtual or soft buttons and/or a keypad or keyboard.

[0049] In some implementations, the multi-touch capable device 400 can present recorded audio and/or video files, such as MP3, AAC, and MPEG files. In some implementations, the multi-touch capable device 400 can include the functionality of an MP3 player, such as an iPod™. The multi-touch capable device 400 may, therefore, include a 32-pin connector that is compatible with the iPod. Other input/output and control devices can also be used.

[0050] The memory interface 602 can be coupled to memory 650. The memory 650 can include high-speed random access memory and/or non-volatile memory, such as one or more magnetic disk storage devices, one or more optical storage devices, and/or flash memory (e.g., NAND, NOR). The memory 650 can store an operating system 652, such as Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks. The operating system 652 may include instructions for handling basic system services and for performing hardware dependent tasks.

[0051] The memory 650 may also store communication instructions 654 to facilitate communicating with one or more additional devices, one or more computers and/or one or more servers. The memory 650 may include graphical user interface instructions 656 to facilitate graphic user interface processing; sensor processing instructions 658 to facilitate sensor-related processing and functions; phone instructions 660 to facilitate phone-related processes and functions; electronic messaging instructions 662 to facilitate electronic-messaging related processes and functions; web browsing instructions 664 to facilitate web browsing-related processes and func-

tions; media processing instructions 666 to facilitate media processing-related processes and functions; GPS/Navigation instructions 668 to facilitate GPS and navigation-related processes and instructions; camera instructions 670 to facilitate camera-related processes and functions; and/or other messaging instructions 672 to facilitate processes and functions, as described in reference to FIGS. 1-5.

[0052] Each of the above identified instructions and applications can correspond to a set of instructions for performing one or more functions described above. These instructions need not be implemented as separate software programs, procedures or modules. The memory 650 can include additional instructions or fewer instructions. Furthermore, various functions of the multi-touch capable device 400 may be implemented in hardware and/or in software, including in one or more signal processing and/or application specific integrated circuits.

[0053] The features described can be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations of them. The features can be implemented in a computer program product tangibly embodied in an information carrier, e.g., in a machine-readable storage device or in a propagated signal, for execution by a programmable processor; and method steps can be performed by a programmable processor executing a program of instructions to perform functions of the described implementations by operating on input data and generating output.

[0054] The described features can be implemented advantageously in one or more computer programs that are executable on a programmable system including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. A computer program is a set of instructions that can be used, directly or indirectly, in a computer to perform a certain activity or bring about a certain result. A computer program can be written in any form of programming language (e.g., Objective-C, Java), including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment.

[0055] Suitable processors for the execution of a program of instructions include, by way of example, both general and special purpose microprocessors, and the sole processor or one of multiple processors or cores, of any kind of computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer are a processor for executing instructions and one or more memories for storing instructions and data. Generally, a computer will also include, or be operatively coupled to communicate with, one or more mass storage devices for storing data files; such devices include magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical

disks. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits).

[0056] To provide for interaction with a user, the features can be implemented on a computer having a display device such as a CRT (cathode ray tube) or LCD (liquid crystal display) monitor for displaying information to the user and a keyboard and a pointing device such as a mouse or a trackball by which the user can provide input to the computer.

[0057] The features can be implemented in a computer system that includes a back-end component, such as a data server, or that includes a middleware component, such as an application server or an Internet server, or that includes a front-end component, such as a client computer having a graphical user interface or an Internet browser, or any combination of them. The components of the system can be connected by any form or medium of digital data communication such as a communication network. Examples of communication networks include, e.g., a LAN, a WAN, and the computers and networks forming the Internet.

[0058] The computer system can include clients and servers. A client and server are generally remote from each other and typically interact through a network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0059] A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made. For example, elements of one or more implementations may be combined, deleted, modified, or supplemented to form further implementations. As yet another example, the logic flows depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results. In addition, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the described systems. Accordingly, other implementations are within the scope of the following claims.

Claims

1. A method for processing touches comprising:

receiving (302) first and second touch input signals simultaneously, wherein the first and second touch input signals are associated with first and second regions, respectively, of a web page

- (100) displayed on a touch sensitive device (400), wherein each region is associated with a different respective node (152-160) in a document object model (150); the first touch input signal corresponds to a first touch input at a first location that corresponds to the first region of the web page, the second touch input signal corresponds to a second touch input at a second location that corresponds to the second region of the web page, and the second location is distinct from the first location;
- determining (304) a first touch event associated with the first region of the web page based on the first touch input signal;
- determining (304) a second touch event associated with the second region of the web page based on the second touch input signal;
- detecting a gesture event by combining the at least the first and second touch events; and
- sending the gesture event to the web page for processing.
2. The method of claim 1, wherein the touch events are from a group of touch events consisting of a touch start event, a touch move event, a touch end event and a touch cancel event.
 3. The method of claim 1, wherein a sequence of touch events are determined including a start touch event, one or more touch move events and a touch end or touch cancel event.
 4. The method of claim 1, wherein two or more touch events are determined to be a touch gesture.
 5. The method of claim 1, wherein the touch events occur at substantially the same time.
 6. The method of claim 1, wherein the web page regions are associated with nodes in the document object model and the nodes are at the same or different hierarchical levels of the document object model.
 7. The method of claim 1, wherein the web page corresponds to a markup language document with attributes that define event actions and that are associated with the gesture event.
 8. The method of claim 7, wherein the event actions include running JavaScript.
 9. The method of claim 1, wherein the web page corresponds to an HTML document with attributes in one or more HTML tags that define event actions and that are associated with the gesture event.
 10. The method of claim 1, wherein each touch event is associated with a single touch input signal.
 11. The method of claim 10, wherein each touch input signal is generated in response to touch input generated by a single finger touching the touch sensitive device.
 12. A computer-readable medium having instructions stored thereon, which, when executed by at least one processor (604), cause the at least one processor to perform operations comprising:
 - receiving (302) first and second touch input signals simultaneously, wherein the first and second touch input signals are associated with first and second regions, respectively, of a web page displayed on a touch sensitive device, wherein each region is associated with a different respective node in a document object model, the first touch input signal corresponds to a first touch input at a first location that corresponds to the first region of the web page, the second touch input signal corresponds to a second touch input at a second location that corresponds to the second region of the web page, and the second location is distinct from the first location;
 - determining (304) a first touch event associated with the first region of the web page based on the first touch input signal;
 - determining (304) a second touch event associated with the second region of the web page based on the second touch input signal;
 - detecting a gesture event by combining at least the first and second touch events; and
 - sending the gesture event to the web page for processing.
 13. The computer readable storage medium of claim 12, wherein a sequence of the touch events is a touch start event, one or more touch move events and a touch end or touch cancel event.
 14. The computer readable storage medium of claim 12, wherein the web page corresponds to a markup language document with attributes that define event actions and that are associated with the gesture event.
 15. The computer readable storage medium of claim 12, wherein the web page corresponds to an HTML document with attributes in one or more HTML tags that define event actions and that are associated with the gesture event.
 16. A system comprising:
 - at least one processor (604);
 - a computer-readable medium according to any one of claims 12 to 15, coupled to the at least one processor.

17. The system of claim 16, wherein the touch events are from a group of touch events consisting of a touch start event, a touch move event, a touch end event and a touch cancel event.
18. The system of claim 16, wherein two or more touch events are determined to be a touch gesture.
19. The system of claim 16, wherein the touch events occur at substantially the same time.

Patentansprüche

1. Verfahren zum Bearbeiten von Berührungen umfassend:

Gleichzeitiges Empfangen (302) erster und zweiter Berührungseingabesignale, wobei die ersten und zweiten Berührungseingabesignale mit ersten und zweiten Regionen auf einer Webseite (100), die auf einer berührungsempfindlichen Vorrichtung (400) angezeigt wird, entsprechend assoziiert sind, wobei jede Region mit einem unterschiedlichen entsprechenden Knoten (152-160) in einem Dokumentobjektmodell (150) assoziiert ist; wobei das erste Berührungseingabesignal einer ersten Berührungseingabe an einem ersten Ort entspricht, der der ersten Region auf der Webseite entspricht, wobei das zweite Berührungseingabesignal einer zweiten Berührungseingabe an einem zweiten Ort entspricht, der der zweiten Region auf der Webseite entspricht, und der zweite Ort unterschiedlich von dem ersten Ort ist; Bestimmen (304) eines ersten Berührungseignisses, das mit der ersten Region auf der Webseite assoziiert ist, basierend auf dem ersten Berührungseingabesignal; Bestimmen (304) eines zweiten Berührungseignisses, das mit der zweiten Region auf der Webseite assoziiert ist, basierend auf dem zweiten Berührungseingabesignal; Detektieren eines Gestenereignisses durch Kombinieren von zumindest dem ersten und zweiten Berührungseignissen; und Senden des Gestenereignisses an die Webseite zur Verarbeitung.

2. Verfahren nach Anspruch 1, wobei die Berührungseignisse aus einer Gruppe von Berührungseignissen stammen, bestehend aus einem Berührungseignisse, einem Berührungsbewegungseignisse, einem Berührungsendereignisse und einem Berührungabbruchereignisse.
3. Verfahren nach Anspruch 1, wobei eine Sequenz von Berührungseignissen bestimmt wird ein-

schließlich eines Berührungseignisses, eines oder mehrerer Berührungsbewegungseignissen und eines Berührungsend- oder Berührungabbruchereignisses.

5

4. Verfahren nach Anspruch 1, wobei bestimmt wird, dass zwei oder mehrere Berührungseignisse eine Berührungsgeste sind.

10

5. Verfahren nach Anspruch 1, wobei die Berührungseignisse im Wesentlichen zur selben Zeit auftreten.

15

6. Verfahren nach Anspruch 1, wobei die Webseitenregionen mit Knoten in dem Dokumentobjektmodell assoziiert sind und die Knoten auf der gleichen oder unterschiedlichen Hierarchiestufen des Dokumentobjektmodells sind.

20

7. Verfahren nach Anspruch 1, wobei die Webseite einem Markup-Language-Dokument entspricht, mit Attributen, die Ereignisaktionen definieren und die mit dem Gestenereignis assoziiert sind.

25

8. Verfahren nach Anspruch 7, wobei die Ereignisaktionen Ausführen von JavaScript beinhalten.

30

9. Verfahren nach Anspruch 1, wobei die Webseite einem HTML-Dokument mit Attributen in einem oder mehreren HTML-Tags entspricht, welche Ereignisaktionen definieren und welche mit dem Gestenereignis assoziiert sind.

35

10. Verfahren nach Anspruch 1, wobei jedes Berührungseignisse mit einem einzelnen Berührungseingabesignal assoziiert ist.

40

11. Verfahren nach Anspruch 10, wobei jedes Berührungseingabesignal in Antwort auf eine Berührungseingabe, die durch einen einzelnen Finger erzeugt wird, welcher die berührungsempfindliche Vorrichtung berührt, erzeugt wird.

45

12. Computerlesbares Medium, welches Anweisungen darauf gespeichert hat, welche, wenn sie durch zumindest einen Prozessor (604) ausgeführt werden, den zumindest einen Prozessor veranlassen, Operationen durchzuführen, die umfassen:

Gleichzeitiges Empfangen (302) von ersten und zweiten Berührungseingabesignalen, wobei die ersten und zweiten Berührungseingabesignale mit ersten und zweiten Regionen auf einer Webseite, die auf einer berührungsempfindlichen Vorrichtung angezeigt wird, entsprechend assoziiert sind, wobei jede Region mit einem unterschiedlichen entsprechenden Knoten in einem Dokumentobjektmodell assoziiert ist, wo-

- bei das erste Berührungseingabesignal einer ersten Berührungseingabe an einem ersten Ort entspricht, der der ersten Region auf der Webseite entspricht, wobei das zweiten Berührungseingabesignal einer zweiten Berührungseingabe an einem zweiten Ort entspricht, der der zweiten Region auf der Webseite entspricht, und der zweite Ort unterschiedlich von dem ersten Ort ist;
- Bestimmen (304) eines ersten Berührungseignisses, das mit der ersten Region auf der Webseite assoziiert ist, basierend auf dem ersten Berührungseingabesignal;
- Bestimmen (304) eines zweiten Berührungseignisses, das mit der zweiten Region auf der Webseite assoziiert ist, basierend auf dem zweiten Berührungseingabesignal;
- Detektieren eines Gestenereignisses durch Kombinieren von zumindest dem ersten und zweiten Berührungseignisse; und
- Senden des Gestenereignisses an die Webseite zur Verarbeitung.
13. Computerlesbares Speichermedium nach Anspruch 12, wobei eine Sequenz von den Berührungseignissen ein Berührungsstartereignis, ein oder mehrere Berührungsbewegungseignisse und ein Berührungsend- oder Berührungsabbruchereignis ist.
14. Computerlesbares Speichermedium nach Anspruch 12, wobei die Webseite einem Markup-Language-Dokument entspricht mit Attributen, die Ereignisaktionen definieren und die mit dem Gestenereignis assoziiert sind.
15. Computerlesbares Speichermedium nach Anspruch 12, wobei die Webseite einem HTML-Dokument entspricht mit Attributen in einem oder mehreren HTML-Tags, die Ereignisaktionen definieren und mit dem Gestenereignis assoziiert sind.
16. System umfassend:
- zumindest einen Prozessor (604);
- ein computerlesbares Medium gemäß irgendeinem der Ansprüche 12-15, das mit dem zumindest einen Prozessor gekoppelt ist.
17. System nach Anspruch 16, wobei die Berührungseignisse aus einer Gruppe von Berührungseignissen stammen, bestehend aus einem Berührungsstartereignis, einem Berührungsbewegungseignis, einem Berührungsendereignis und einem Berührungsabbruchereignis.
18. System nach Anspruch 16, wobei bestimmt wird, dass zwei oder mehrere Berührungseignisse eine Berührungsgeste sind.
19. System nach Anspruch 16, wobei die Berührungseignisse im Wesentlichen zur selben Zeit auftreten.

5

10

15

20

25

30

35

40

45

50

55

Revendications

1. Procédé pour le traitement de touchers comprenant :

la réception (302) de premier et deuxième signaux d'entrée tactile simultanément, dans lequel les premier et deuxième signaux d'entrée tactile sont associés respectivement à des première et deuxième régions d'une page web (100) affichée sur un dispositif à touche sensitive (400), dans lequel chaque région est associée à un noeud respectif différent (152-160) dans un modèle d'objet document (150) ;

le premier signal d'entrée tactile correspond à une première entrée tactile au niveau d'un premier emplacement qui correspond à la première région de la page web, le deuxième signal d'entrée tactile correspond à une deuxième entrée tactile au niveau d'un deuxième emplacement qui correspond à la deuxième région de la page web, et le deuxième emplacement est distinct du premier emplacement ;

la détermination (304) d'un premier événement tactile associé à la première région de la page web sur la base du premier signal d'entrée tactile ;

la détermination (304) d'un deuxième événement tactile associé à la deuxième région de la page web sur la base du deuxième signal d'entrée tactile ;

la détection d'un événement gestuel en combinant au moins les premier et deuxième événements tactiles ; et

l'envoi de l'événement gestuel à la page web pour le traitement.

2. Procédé selon la revendication 1, dans lequel les événements tactiles appartiennent à un groupe d'événements tactiles comprenant un événement de début de toucher, un événement de déplacement de toucher, un événement de fin de toucher et un événement d'annulation de toucher.

3. Procédé selon la revendication 1, dans lequel une séquence d'événements tactiles est déterminée comme comprenant un événement de début de toucher, un ou plusieurs événements de déplacement de toucher et un événement de fin de toucher ou d'annulation de toucher.

4. Procédé selon la revendication 1, dans lequel deux événements tactiles ou plus sont déterminés comme

- étant un geste tactile.
5. Procédé selon la revendication 1, dans lequel les événements tactiles se produisent sensiblement en même temps. 5
 6. Procédé selon la revendication 1, dans lequel les régions de page web sont associées à des noeuds dans le modèle d'objet document et les noeuds sont au même niveau hiérarchique ou à des niveaux hiérarchiques différents du modèle d'objet document. 10
 7. Procédé selon la revendication 1, dans lequel la page web correspond à un document de langage de balisage avec des attributs qui définissent des actions d'événement et qui sont associés à l'événement gestuel. 15
 8. Procédé selon la revendication 7, dans lequel les actions d'événement comprennent l'exécution de JavaScript. 20
 9. Procédé selon la revendication 1, dans lequel la page web correspond à un document HTML avec des attributs dans une ou plusieurs étiquettes HTML qui définissent des actions d'événement et qui sont associés à l'événement gestuel. 25
 10. Procédé selon la revendication 1, dans lequel chaque événement tactile est associé à un signal d'entrée tactile unique. 30
 11. Procédé selon la revendication 10, dans lequel chaque signal d'entrée tactile est généré en réponse à une entrée tactile générée par un seul doigt touchant le dispositif à touche sensitive. 35
 12. Support lisible par ordinateur ayant des instructions stockées dessus qui, quand elles sont exécutées par au moins un processeur (604), forcent l'au moins un processeur à effectuer des opérations comprenant : 40
 - la réception (302) de premier et deuxième signaux d'entrée tactile simultanément, dans lequel les premier et deuxième signaux d'entrée tactile sont associés respectivement à des première et deuxième régions d'une page web affichée sur un dispositif à touche sensitive, dans lequel chaque région est associée à un noeud respectif différent dans un modèle d'objet document, le premier signal d'entrée tactile correspond à une première entrée tactile au niveau d'un premier emplacement qui correspond à la première région de la page web, le deuxième signal d'entrée tactile correspond à une deuxième entrée tactile au niveau d'un deuxième emplacement qui correspond à la deuxième région de la page web, et le deuxième emplacement
- est distinct du premier emplacement ;
 la détermination (304) d'un premier événement tactile associé à la première région de la page web sur la base du premier signal d'entrée tactile ;
 la détermination (304) d'un deuxième événement tactile associé à la deuxième région de la page web sur la base du deuxième signal d'entrée tactile ;
 la détection d'un événement gestuel en combinant au moins les premier et deuxième événements tactiles ; et
 l'envoi de l'événement gestuel à la page web pour le traitement.
13. Support de stockage lisible par ordinateur selon la revendication 12, dans lequel une séquence d'événements tactiles est un événement de début de toucher, un ou plusieurs événements de déplacement de toucher et un événement de fin de toucher ou d'annulation de toucher.
 14. Support de stockage lisible par ordinateur selon la revendication 12, dans lequel la page web correspond à un document de langage de balisage avec des attributs qui définissent des actions d'événement et qui sont associés à l'événement gestuel.
 15. Support de stockage lisible par ordinateur selon la revendication 12, dans lequel la page web correspond à un document HTML avec des attributs dans une ou plusieurs étiquettes HTML qui définissent des actions d'événement et qui sont associés à l'événement gestuel.
 16. Système comprenant :
 - au moins un processeur (604) ;
 - un support lisible par ordinateur selon l'une quelconque des revendications 12 à 15, couplé à l'au moins un processeur.
 17. Système selon la revendication 16, dans lequel les événements tactiles appartiennent à un groupe d'événements tactiles comprenant un événement de début de toucher, un événement de déplacement de toucher, un événement de fin de toucher et un événement d'annulation de toucher.
 18. Système selon la revendication 16, dans lequel deux événements tactiles ou plus sont déterminés comme étant un geste tactile.
 19. Système selon la revendication 16, dans lequel les événements tactiles se produisent sensiblement en même temps.

Applications <u>212</u>
Web Page SDK Touch <u>210</u> Event API
Foundation <u>208</u>
Core foundation <u>206</u>
OS APIs <u>206</u>
Core OS <u>204</u>
Driver(s) <u>202</u>
Hardware <u>200</u>

FIG.2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20050162402 A1 [0004]
- US 6323846 B [0033]
- US 6570557 B [0033]
- US 6677932 B [0033]
- US 20020015024 A1 [0033]

Non-patent literature cited in the description

- *Document Object Model (DOM) Level 2 Events Specification version 1.0 W3C RECOMMENDATION [0005]*