



Office de la Propriété

Intellectuelle  
du Canada

Un organisme  
d'Industrie Canada

Canadian  
Intellectual Property  
Office

An agency of  
Industry Canada

CA 2716488 C 2016/08/30

(11)(21) **2 716 488**

(12) **BREVET CANADIEN**  
**CANADIAN PATENT**

(13) **C**

(86) **Date de dépôt PCT/PCT Filing Date:** 2009/03/13  
(87) **Date publication PCT/PCT Publication Date:** 2009/09/17  
(45) **Date de délivrance/Issue Date:** 2016/08/30  
(85) **Entrée phase nationale/National Entry:** 2010/08/20  
(86) **N° demande PCT/PCT Application No.:** US 2009/037160  
(87) **N° publication PCT/PCT Publication No.:** 2009/114808  
(30) **Priorité/Priority:** 2008/03/13 (US61/036,433)


(51) **Cl.Int./Int.Cl. A61M 1/00 (2006.01),**  
**A43B 13/40 (2006.01)**

(72) **Inventeurs/Inventors:**  
HARDMAN, IAN JAMES, GB;  
HALL, COLIN JOHN, GB;  
HEATON, KEITH PATRICK, GB

(73) **Propriétaire/Owner:**  
KCI LICENSING, INC., US

(74) **Agent:** BORDEN LADNER GERVAIS LLP

(54) **Titre : COLLECTEURS, APPAREILS, SYSTEMES ET PROCEDES POUR APPLIQUER UNE PRESSION REDUITE SUR UN SITE TISSULAIRE SUR UN PIED**  
(54) **Title: FOOT MANIFOLDS, APPARATUSES, SYSTEMS, AND METHODS FOR APPLYING REDUCED PRESSURE TO A TISSUE SITE ON A FOOT**



(57) **Abrégé/Abstract:**

Apparatuses, systems, and methods for applying reduced pressure to a tissue site on a foot are provided. An apparatus may include an insole (208) and a tissue contacting surface covering at least a portion of the insole. At least one portion of the tissue contacting surface (234) is removable to form a void (218). The apparatus may also include a reduced-pressure interface for receiving reduced pressure from a reduced-pressure source, and at least one flow channel fluidly coupled to the reduced-pressure interface and the void.

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

## CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
17 September 2009 (17.09.2009)(10) International Publication Number  
**WO 2009/114808 A8**(51) International Patent Classification:  
**A61M 1/00** (2006.01)      **A43B 13/40** (2006.01)(74) Agents: **WELCH, Gerald, T.** et al.; Sonnenschein, Nath & Rosenthal LLP, P.O. Box 061080, Wacker Drive Station, Sears Tower, Chicago, IL 60606 (US).

(21) International Application Number:

PCT/US2009/037160

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:

13 March 2009 (13.03.2009)

(71) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/036,433      13 March 2008 (13.03.2008)      US

(72) Inventors; and  
(75) Inventors/Applicants (for US only): **HARDMAN, Ian, James** [GB/GB]; 74 Victoria Avenue, Bournemouth, Dorset BH 9 2RP (GB). **HALL, Colin, John** [GB/GB]; 33 Oakdale Road, Poole, Dorset BH15 3LD (GB). **HEATON, Keith, Patrick** [GB/GB]; 3 Clifton Road, Penn Hill, Poole BH14 1TY (GB).

(84) Designated States (unless otherwise indicated, for every kind of national protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*[Continued on next page]*

(54) Title: FOOT MANIFOLDS, APPARATUSES, SYSTEMS, AND METHODS FOR APPLYING REDUCED PRESSURE TO A TISSUE SITE ON A FOOT




FIG. 2

(57) Abstract: Apparatuses, systems, and methods for applying reduced pressure to a tissue site on a foot are provided. An apparatus may include an insole (208) and a tissue contacting surface covering at least a portion of the insole. At least one portion of the tissue contacting surface (234) is removable to form a void (218). The apparatus may also include a reduced-pressure interface for receiving reduced pressure from a reduced-pressure source, and at least one flow channel fluidly coupled to the reduced-pressure interface and the void.

WO 2009/114808 A8

**WO 2009/114808 A8**

**(15) Information about Correction:**  
see Notice of 2 September 2010

**Published:**  
— *with international search report (Art. 21(3))*

**(48) Date of publication of this corrected version:**  
2 September 2010

**TITLE OF THE INVENTION****FOOT MANIFOLDS, APPARATUSES, SYSTEMS, AND METHODS FOR APPLYING  
REDUCED PRESSURE TO A TISSUE SITE ON A FOOT**

5

**BACKGROUND**

10 The illustrative embodiments relate generally to medical treatment systems and, more particularly, to foot manifolds, apparatuses, systems, and methods for applying reduced pressure to a tissue site on a foot.

15 Clinical studies and practice have shown that providing a reduced pressure in proximity to a tissue site augments and accelerates the growth of new tissue at the tissue site. The applications of this phenomenon are numerous, but application of reduced pressure has been particularly successful in treating wounds. This treatment (frequently referred to in the medical community as “negative pressure wound therapy,” “reduced pressure therapy,” or “vacuum therapy”) provides a number of benefits, which may include faster healing and increased formulation of granulation tissue.

20

**SUMMARY**

25 According to an illustrative embodiment, an apparatus for applying reduced pressure to a tissue site on a foot includes an insole and a tissue contacting surface covering at least a portion of the insole. At least one portion of the tissue contacting surface is removable to form a void. The apparatus may also include a reduced-pressure interface for receiving reduced pressure from a reduced-pressure source, and at least one flow channel fluidly coupled to the reduced-pressure interface and the void.

30 In one illustrative embodiment, a system may include, in addition to the apparatus described above, a reduced-pressure source operable to supply reduced pressure. The system may also include a delivery conduit operable to deliver reduced pressure from the reduced-pressure source to the reduced-pressure interface of the apparatus.

In one illustrative embodiment, a method for applying reduced pressure to a tissue site on a foot includes providing a foot manifold and removing a portion of a tissue contacting surface that covers an insole of the foot manifold to form a void. The method also includes aligning the void with the tissue site on the foot and creating a substantially pneumatic seal between the void and the tissue site. The method also includes applying reduced pressure from a reduced-pressure source to the void via a flow channel such that reduced pressure is applied to the tissue site.

In one illustrative embodiment, a method of manufacturing an apparatus for applying reduced pressure to a tissue site on a foot includes providing an insole and providing a tissue contacting surface. The method also includes covering at least a portion of the insole with the tissue contacting surface to form at least one flow channel operable to transfer reduced pressure.

Other objects, features, and advantages of the illustrative embodiments will become apparent with reference to the drawings and detailed description that follow.

15

## BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 illustrates a perspective view of a system for applying reduced pressure to a tissue site on a foot according to an illustrative embodiment;

FIGURE 2 illustrates a perspective view of an apparatus for applying reduced pressure to a tissue site on a foot according to an illustrative embodiment;

FIGURE 3A illustrates a cross-sectional view of the apparatus of FIGURE 2;

FIGURE 3B illustrates a cross-sectional view of the apparatus of FIGURE 2, the apparatus having a support member removed to form a void;

FIGURE 4A illustrates a top perspective view of a support member of the apparatus of FIGURE 2;

FIGURE 4B illustrates a bottom perspective view of the support member of FIGURE 4A;

FIGURE 5 illustrates an exploded perspective view of an apparatus for applying reduced pressure to a tissue site on a foot according to an illustrative embodiment;

FIGURE 6 illustrates a perspective view of the apparatus of FIGURE 5 with a portion of a sealing layer removed to form a void;

FIGURE 7 illustrates a cross-sectional view of a delivery conduit according to an illustrative embodiment;

FIGURE 8 illustrates a cross-sectional view of a delivery conduit according to an illustrative embodiment;

FIGURE 9 illustrates a top view of an apparatus for applying reduced pressure to a tissue site on a foot according to an illustrative embodiment; and

5 FIGURE 10 illustrates a perspective view of the apparatus of FIGURE 9 applied to a tissue site on a foot according to an illustrative embodiment.

## DETAILED DESCRIPTION

In the following detailed description of the illustrative embodiments, reference is made to the 10 accompanying drawings that form a part hereof. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is understood that other embodiments may be utilized and that logical structural, mechanical, electrical, and chemical changes may be made. To avoid detail not necessary to enable those skilled in the art to practice the embodiments described herein, the description may omit certain information known to those skilled in the art. The scope of 15 the claims should not be limited by the preferred embodiments set forth in the examples, but should be given the broadest interpretation consistent with the description as a whole.

Referring to FIGURE 1, an illustrative embodiment of a reduced-pressure treatment system 100 for providing reduced-pressure treatment to a tissue site 102, such as a wound 104, on a foot 105 of a patient is presented. The reduced-pressure treatment system 100 includes a foot manifold 106 that 20 receives reduced pressure from a reduced-pressure source 109, and which supplies reduced pressure to a tissue site on the foot 105. The foot manifold 106 includes an insole 108, and a tissue contacting surface 110 that covers the tissue facing surface of the insole 108. As used herein, “covers” includes fully or partially covering. The reduced pressure may be delivered to the foot manifold 106 through a delivery conduit 112, which may be inserted, or otherwise removably coupled, to a reduced-pressure 25 interface 114 located at the rear 116 of the insole 108. A portion of the tissue contacting surface 110 is removable to form a void 118, which may be aligned with the wound 104 when the foot manifold 106 and foot 105 are adjacent. One or more flow channels 120 in the insole 108 transfers reduced pressure from the reduced-pressure interface 114 to the void 118 such that reduced-pressure treatment is delivered to the wound 104.

30 As used herein, “reduced pressure” generally refers to a pressure less than the ambient pressure at a tissue site that is being subjected to treatment. In most cases, this reduced

pressure will be less than the atmospheric pressure at which the patient is located. Alternatively, the reduced pressure may be less than a hydrostatic pressure at the tissue site. In one embodiment, the reduced pressure may initially generate fluid flow in the delivery conduit 112 and proximate the wound 104. As the hydrostatic pressure around the wound 104 approaches the desired reduced pressure, the flow may subside, and the reduced pressure may be maintained. Unless otherwise indicated, values of pressure stated herein are gauge pressures. The reduced pressure delivered may be static or dynamic (patterned or random) and may be delivered continuously or intermittently. Although the terms "vacuum" and "negative pressure" may be used to describe the pressure applied to the tissue site, the actual pressure applied to the tissue site may be more than the pressure normally associated with a complete vacuum. Consistent with the use herein, an increase in reduced pressure or vacuum pressure typically refers to a relative reduction in absolute pressure. Unless otherwise indicated, as used herein, "or" does not require mutual exclusivity.

The wound 104 may be any type of wound, or damaged area of tissue, and may include 15 wounds from trauma, surgery, or other causes, such as a diabetic ulcer. The tissue site 102, which includes the wound 104, may be the bodily tissue of any human, animal, or other organism, including bone tissue, adipose tissue, muscle tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, ligaments, or any other tissue. Treatment of the tissue site 102 may include removal of fluids, e.g., exudate, or delivery of reduced pressure.

20 In the example in which the wound 104 is a foot ulcer, the insole 108 may also serve to off-load pressure from the wound 104, such as when the patient is walking or standing. The tissue contacting surface 110 may maintain contact with the tissue around the wound 104, thereby relieving pressure from the wound 104. The pressure exerted upon the wound 104 is reduced due to the presence of the void 118 adjacent the wound 104. In particular, because the 25 portion of the tissue contacting surface 110 that is adjacent the wound 104 is removed, the pressure exerted upon the wound 104 is reduced.

The foot manifold 106 may be used in conjunction with or in lieu of therapeutic casting systems, such as total contact casting and removable cast walkers. For example, the foot manifold 106 may be placed into a therapeutic casting system that is worn by the patient. In 30 another example, the foot manifold 106 may be inserted into any article of footwear, such as a shoe, boot, sandal, or sock.

The foot manifold 106 may also be secured to the foot 105 in other ways. For example, a securing member 122 may be at least partially wrapped around the insole 108 and the foot 105. Adhesive may be used to prevent the securing member 122 from unwrapping. If

desired, the foot 105 and the foot manifold 106 that have been wrapped by the securing member 122 may be placed in footwear, including a therapeutic casting system. The foot manifold 106 may also be secured to the foot 105 using one or more elastic bands that press the foot manifold 106 and foot 105 against one another.

5 In another example, the foot manifold 106 may adhere to the foot 105 without the need for the securing member 122 or footwear. In this example, the tissue contacting surface 110 of the foot manifold 106 may be made from or coated with an adhesive material that secures the foot 105 to the foot manifold 106.

A foam manifold 124 may be inserted into the void 118. The foam manifold 124 10 assists in applying reduced pressure to, delivering fluids to, or removing fluids from the wound 104. The foam manifold 124 typically includes a plurality of flow channels or pathways that are interconnected to improve distribution of fluids provided to and removed from the wound 104 adjacent the foam manifold 124. The foam manifold 124 may be a biocompatible material that is capable of being placed in contact with the wound 104 and 15 distributing reduced pressure to the wound 104. Examples of foam manifolds 124 may include, for example, without limitation, devices that have structural elements arranged to form flow channels, such as, for example, cellular foam, open-cell foam, porous tissue collections, liquids, gels, and foams that include, or cure to include, flow channels. The foam manifold 124 may be porous and may be made from foam, gauze, felted mat, or any other 20 material suited to a particular biological application. In one embodiment, the foam manifold 124 is a porous foam and includes a plurality of interconnected cells or pores that act as flow channels. The porous foam may be a polyurethane, open-cell, reticulated foam, such as a GranuFoam® material manufactured by Kinetic Concepts, Incorporated of San Antonio, 25 Texas. In some situations, the foam manifold 124 may also be used to distribute fluids, such as medications, antibacterials, growth factors, and various solutions to the wound 104. Other layers may be included in or on the foam manifold 124, such as absorptive materials, wicking materials, hydrophobic materials, and hydrophilic materials.

Reduced pressure is delivered to the void 118 through the flow channel 120. Although the foot manifold 106 is shown to have only a single flow channel 120, the foot manifold 106 30 may have any number of flow channels, such as flow channel 120, that are able to fluidly connect any portion of the insole 108 or tissue contacting surface 110 with the reduced-pressure interface 114. As described in the figures below, these flow channels may be interconnected, form any pattern, or defined by one or more grooves on the insole 108 or the

tissue contacting surface 110. The flow channel 120 may also be a tube or conduit that fluidly couples the reduced-pressure interface 114 to the void 118.

Reduced pressure is delivered to the flow channel 120 via the reduced-pressure interface 114. The reduced-pressure interface 114 may be any socket, port, hole, or other attachment capable of facilitate coupling, including the fluid coupling, between the delivery conduit 112 and the foot manifold 106. As used herein, the term "coupled" includes coupling via a separate object and includes direct coupling. The term "coupled" also encompasses two or more components that are continuous with one another by virtue of each of the components being formed from the same piece of material. Also, the term "coupled" may include chemical, such as via a chemical bond, mechanical, thermal, or electrical coupling. Fluid coupling means that fluid is in communication between the designated parts or locations.

In one non-limiting example, the reduced-pressure interface 114 may include a hole into which the delivery conduit 112 may be inserted, thereby forming an interference fit. Upon insertion of the delivery conduit 112 into the reduced-pressure interface 114, reduced pressure may be delivered to the flow channel 120 and the void 118 from the reduced-pressure source 109. A mechanism may also be used to secure the delivery conduit 112 to the reduced-pressure interface 114 to prevent the delivery conduit 112 from being pulled out of the reduced-pressure interface 114. In one embodiment, the delivery conduit 112 is integrally formed with the reduced-pressure interface 114 such that the delivery conduit 112 is fixedly coupled to the reduced-pressure interface 114. The reduced-pressure interface 114 may also include a swivel, hinge, or other movable attachment mechanism to permit the delivery conduit 112 to move or swivel relative to the insole 108.

The delivery conduit 112 may include one or more lumens through which a fluid may flow. In one embodiment, the delivery conduit 112 includes two or more lumens, any of which may be used to transfer reduced pressure to the foot manifold 106, transfer liquid, such as exudate, away from the foot manifold 106, or transfer therapeutic fluids to the foot manifold 106.

The reduced-pressure source 109 provides reduced pressure to the foot manifold 106. The reduced-pressure source 109 may be any means of supplying a reduced pressure, such a vacuum pump. While the amount and nature of reduced pressure applied to a site will typically vary according to the application, the reduced pressure will typically be between -5 mm Hg and -500 mm Hg.

A medial portion 125 of the delivery conduit 112 may have one or more devices, such as device 126. For example, the device 126 might be another fluid reservoir, or collection

member to hold exudates and other fluids removed. Other examples of the device 126 that might be included on the medial portion 125 of the delivery conduit 112 or otherwise fluidly coupled to the delivery conduit 112 include the following non-limiting examples: a pressure-feedback device, a volume detection system, a blood detection system, an infection detection system, a flow monitoring system, a temperature monitoring system, etc. Some of these devices may be formed integral to the reduced-pressure source 109. For example, a reduced-pressure port 128 on the reduced-pressure source 109 may include a filter member that includes one or more filters, e.g., an odor filter.

In use, a patient or caretaker may remove a portion of the tissue contacting surface 110 to form the void 118. The portion of the tissue contacting surface 110 that is removed is detachably mated to the insole 108, and may be chosen such that the void 118 aligns, or is otherwise adjacent, the wound 104 when the foot manifold 106 and the foot 105 are adjacent one another. Grid lines or markers may be included on the tissue contacting surface 110 to assist in choosing the appropriate portion of the tissue contacting surface 110 for removal. The foam manifold 124 may be inserted into the void 118. When in use, the foot 105 and the foot manifold 106 are disposed adjacent one another to create a substantially pneumatic seal between the void 118 and the wound 104. As described below, the substantially pneumatic seal may be facilitated in variety of ways, including through the use of a sealing member (not shown) or the tissue contacting layer 110 itself. Reduced pressure may then be applied to the foot manifold 106 from the reduced-pressure source 109. The reduced pressure may be transferred through the delivery conduit 112 and into the void 118 via the reduced-pressure interface 114 and the flow channel 120, thereby providing reduced-pressure treatment to the wound 104. The substantially pneumatic seal formed at the wound 104 helps to maintain the reduced pressure at therapeutic levels.

Referring to FIGURES 2, 3A-B, and 4A-B, an illustrative embodiment of the foot manifold 206 includes the insole 208. The foot manifold 206 also includes support members 232, which are functionally analogous to the tissue contacting surface 110 in FIGURE 1.

In one embodiment, the insole 208 is shaped and sized to approximate the plantar region 230 of the foot 205, but may also cover only a portion of the plantar region 230, such as the heel region. The insole 208 may also cover all or a portion of the dorsal region, toes, sides, or rear of the foot 205. The insole 208 includes a ridge 252, which may help to secure the foot 205 to the foot manifold 206 and prevent movement of the insole 208 relative to the foot 205 or the wound 204. In another example, the insole 208 does not have the ridge 252.

The insole 208 may be formed from any material. For example, the insole 208 may be composed of a flexible or elastic material, such as silicon, polyurethane, or a thermoplastic elastomer. The flexible or elastic composition of the insole 208 may also facilitate the insertion of the insole 208 into an article of footwear.

5 The support members 232 form a layer that covers a tissue facing surface 234 of the insole 208. The support members 232 contact the plantar region 230 of the foot 205, and may provide an off-loading function that can reduce the pressure exerted on the wound 204. Although shown as hexagonal, the support members 232 may have any shape, including, without limitation, a square, rectangle, triangle, octagon, polygon, circle, oval, or irregular 10 shape.

The flow channels 220 are disposed between the support members 232 and the insole 208, and are formed by a tissue facing surface 254 of the insole 208 and the grooves 236 on the insole-facing side 237 of the support members 232. The grooves 236 may be formed along three axes 238, 239, 240. Each side 242 of the support member 232 may include a groove 15 236. However, some support members 232, such as those support members on the periphery 244 of the layer formed by the support members 232, may have sides 242 that do not include a groove 236. When the support members 232 cover the insole 208, the grooves 236 form an interconnected network of flow channels 220 that distributes reduced pressure along the 20 interface 245 between the support members 232 and the insole 208. The support members 232 comes into contact with the insole 208, or may be coupled to the insole 208 using any known technique, including without limitation welding (e.g., ultrasonic or RF welding), bonding, adhesives, cements, etc. In one embodiment, the support members 232 are coupled to the insole 208 to seal the flow channels 220 and keep reduced pressure from leaking out of the flow channels 220 leading to the void 218.

25 In one embodiment, the grooves 236 are arch-shaped grooves. However, the grooves 236 may have any shape. For example, the grooves 236 may have one or more straight side walls such that, when the support member 232 is coupled to the insole 208, an at least partially polygonal flow channel is formed.

The support members 232 may include one or more insertion slots 246. The insertion 30 slots 246 may be adapted to receive a device that facilitates the removal of each of the support members 232, such as a scalpel. The insertion slots 246 may have any shape, and the shape may depend upon the type of device to be used in the removal of the support members 232.

The support members 232 at the periphery 244 include lap joints 248. In one example, the lap joints 248 are included only on those support members 232 on the periphery 244 of the

layer formed by the support members 232. The lap joints 248 facilitate a sealed connection between the support members 232 and the insole 208. Although the lap joints 248 are shown to be polygonal protrusions, the lap joints 248 may also be rounded protrusions or any other protrusion that can facilitate a sealed connection between the support members 232 and the 5 insole 208.

The support members 232 may also be made of any material capable of supporting the foot 205. For example, each of the support members 232 may be made of elastic, flexible, or soft materials. The elastic qualities of the support members 232 may lessen the pressure exerted upon the tissue site. Non-limiting examples of the material from which the support 10 members 232 may be composed include silicon (including soft, conformable silicon), polyurethane, and a thermoplastic elastomer (TPE).

Any one or more of the support members 232 may be removed to form the void 218. In Figure 2, support members 232a are removed to form the void 218. The support members 232a may be chosen based on their location on the insole 208 such that the wound 204 is 15 adjacent the void 218 when the foot 205 is placed adjacent the foot manifold 206. Markers, such as characters, may be included on the support members 232 to help locate the support members 232a that align with the wound 204. A sealing member 250 may be disposed around the void 218 and between the foot 205 and the support members 232 when the foot 205 is applied to the foot manifold 206. The foot 205 may be positioned on the sealing ring 250 and 20 the support members 232 such that a seal is formed at the void 218. The seal that is formed by the sealing member 250 helps to prevent the escape of reduced pressure from the void 218 such that a therapeutic reduced pressure may be maintained at the void 218 and applied to the wound 204.

The sealing member 250 may have any shape and may be made of any material that 25 helps to form a seal at the void 218. For example, the sealing member 250 may be a hydrogel ring. The sealing member 250 may also be formed from putty, silicon, closed cell polymer foam, TPE, or a soft, flexible, elastic, or adhesive material.

Upon removing the support members 232a, the void 218 may be fully or partially filled with the foam manifold 224. Before placement into the void 218, the foam manifold 224 may 30 be smaller, larger, or approximately equal in volume to the void 218. The shape of the foam manifold 224 may also be any predetermined shape, or customized to fit the void 218. Also, the foam manifold 224, once inserted into the void 218, may expand to fill the void 218, and may press against the insole 208 or the support members 232 adjacent the void 218

In one embodiment, the foam manifold 224 may be torn or cut from a foam sheet. The foam sheet may also be pre-cut to include foam manifold 224 that approximate the size of the void 218, or the size of the support member 232. In an alternate embodiment, the foam manifold 224 may be placed into or on the wound 204 prior to applying the foot 205 to the 5 foot manifold 206. In another embodiment, no foam manifold 224 need be used when treating the wound 204 with reduced pressure.

The foam manifold 224 in the void 218 may have a height 256 that approximates the height of the support members 232. The foam manifold 224 may also have a height 258 that is greater than the height of the support members 232, and which may touch the wound 204. In 10 another embodiment, the foam manifold 224 is shorter than the height 256 of the support member 232.

In FIGURE 3B, support member 232c, which is disposed between support members 232b and 232d in FIGURE 3A, has been removed to form the void 218. Reduced pressure that is applied to the foot manifold 206 passes through the interconnected flow channels 220 15 formed by the grooves 236 and the tissue facing surface 254 of the insole 208 to reach the void 218. As explained above, the sealing member 250 may be used to create a seal at the void 218 such that a therapeutic reduced pressure is maintained at the void 218 and applied to the wound 204. In the illustrative embodiments, reduced pressure may be applied only to those 20 portions of the foot 205 at which reduced-pressure treatment is desired, while supporting the remainder of the foot 205 using the support members 232.

Referring to FIGURES 5 and 6, a foot manifold 506 that includes a sealing layer 510 is shown according to an illustrative embodiment. The sealing layer 510 is functionally analogous to the tissue contacting layer 110 in FIGURE 1. The sealing layer 510 is bonded, or otherwise coupled, to the insole 508, and covers all or a portion of the insole 508.

The insole 508 includes a flow channels 520, which are interconnected and formed by 25 grooves 536 and protrusions 560 in the insole 508. The flow channels 520 form a grid. However, the flow channels 520 may form any pattern, including irregular patterns or no pattern at all. The flow channels 520 are further defined by an insole-contacting side of the sealing layer 510 when the sealing layer 510 abuts the insole 508. Reduced pressure may be 30 provided to the flow channels 520 via the delivery conduit 512.

The sealing layer 510 may be composed of any material. For example, the sealing layer 510 may be composed of a flexible material that is capable of providing a sealed connection between the sealing layer 510 and the insole 508. In one non-limiting example, the sealing layer 510 may be a hydrogel layer. The tissue-facing side 562 or the insole-facing side

of the sealing layer 510 may be adhesive. Adherence between the tissue-facing side 562 of the sealing layer 510 and the foot 105 may help to secure the foot 105 to the foot manifold 506.

A portion 532 may be identified, cut, and removed from the sealing layer 510 to form the void 518. The portion 532 may be removed using any device capable of cutting the sealing layer 510, such as a scalpel. A foam manifold may be inserted into the void 518. A foot may be disposed on top of the sealing layer 510 such that a tissue site, such as a wound, on the foot abuts the void 518. Reduced pressure may be transferred to the flow channels 520 via the delivery conduit 512, and the reduced pressure may be transferred through the flow channels 520 to the void 518.

The sealing characteristics of the sealing layer 510 help to prevent reduced pressure that is transferred to the void 518 from escaping, thereby maintaining a therapeutic reduced pressure for the tissue site abutting the void 518. The sealing layer 510 may thus eliminate the need for a sealing member. Using the sealing layer 510, the void 518 may be located anywhere on the sealing layer 510, and the portion 532 of the sealing layer 510 that is removed to form the void 518 may have any shape. The location and shape of the removed portion 532 may be determined based on a location and shape of a wound on a foot, such as a foot ulcer. Grid markers, such as grid lines, may be printed, or otherwise included, on the sealing layer 510 to help identify the portion of the sealing layer 510 that should be removed to align the void 518 with a wound on a foot. The grid markers may also help to determine the healing progress of the wound as the sealing layer 510 is replaced during overall treatment of the wound.

Referring to FIGURE 7, a delivery conduit 712 that is functionally analogous to the delivery conduit 112 in FIGURE 1 is shown according to an illustrative embodiment. The delivery conduit 712 has an elongated shape having a low profile. The elongated shape of the delivery conduit 712 alleviates the pressure points applied to the portions of the foot, ankle, or leg that are adjacent the delivery conduit 712. The delivery conduit 712 may also have other shapes, such as a circular, elliptical, polygonal, or curved "U" shape.

The delivery conduit 712 may also be made of any material, such as a flexible, elastic, or compressible material. The flexible, elastic, or compressible material may alleviate the pressure points applied to adjacent portions of the foot, ankle, or leg. Non-limiting examples of material from which the delivery conduit 712 may be formed include plastic, nylon, silicon, polyurethane, TPE, or PVC.

The delivery conduit 712 includes two lumens 766, 768. In one example, the lumens 766, 768 transfer reduced pressure to one or more flow channels in a foot manifold. The

delivery conduit 712 may have any number of lumens, including three or more lumens. In addition, one or more of the lumens in the delivery conduit 712 may be used to transport fluid, such as liquid or exudate, from a wound to a fluid collection apparatus. In other embodiments, the lumens 766, 768 may have any shape, such as a circular, elliptical, or polygonal shape.

5 The lumen 766 is bound by a first wall 770 and a second wall 771. Similarly, the lumen 768 is bound by a first wall 772 and a second wall 773. The first walls 770, 772 include protrusions 774, 775, respectively. The protrusion 774 prevents the first wall 770 from touching the second wall 771 when a force is applied to the delivery conduit 712 in a direction indicated by arrows 776. The protrusion 775 prevents the first wall 772 from 10 touching the second wall 773 when a force is applied to the delivery conduit 712 in a direction indicated by arrows 776. In this manner, the protrusions 774, 775 help prevent the lumens 766, 768 from collapsing.

15 The second walls 771, 773 include protrusions 777, 778, respectively. The protrusion 774 touches protrusion 777 when a force is applied to the delivery conduit 712 in a direction indicated by arrows 776 such that the portion of the first wall 770 and the second wall 771 that do not have protrusions 774 and 777 do not touch one another. Similarly, the protrusion 775 touches protrusion 778 when a force is applied to the delivery conduit 712 in a direction indicated by arrows 776 such that the portion of the first wall 772 and the second wall 773 that do not have protrusions 775 and 778 do not touch one another. The lumens 766, 768 may be 20 prevented from collapsing in this manner.

25 Referring to FIGURE 8, the delivery conduit 812 includes an angled divider 880, which separates lumens 866, 868 from one another. The angled divider 880 may alleviate pressure points on a foot, ankle, or leg when the foot, ankle, or leg presses against the delivery conduit 812 in a direction indicated by arrow 876. In this example, the angled divider 880 may flatten when the foot, ankle, or leg presses against the delivery conduit 812 in a direction indicated by arrow 876. The angled divider 880 may form an approximately 45 degree angle with the wall 873 of the lumen 868, or any other lumen wall in the delivery conduit 812.

30 Referring to FIGURES 9 and 10, an insole 908 is shown according to an illustrative embodiment. The insole 908 may be placed on a dorsal region 982 of the foot 905, and, in particular, at the toe region of the foot 905. In one example, the insole 908 may be composed of a foam, such as reticulated foam or a GranuFoam® material. The insole 908 may be coupled to the toe region of the foot 905 via the securing member 922. Reduced pressure may be applied to the toe region by the insole 908 using reduced pressure that is delivered from a reduced-pressure source and delivered via the delivery conduit 912.

The insole 908 includes protrusions 984, which may be inserted between the toes of the foot 905. The insole 908 may also include voids 918 through which reduced pressure may be applied to a region between the toes of the foot 905. In another non-limiting example, each of the protrusions 984 may be placed on an individual toe of the foot 905. The protrusions 984 5 may have any shape that facilitates the application of reduced pressure to the desired portion of the toe region of the foot 905.

Although the present invention and its advantages have been disclosed in the context of certain illustrative, non-limiting embodiments, it should be understood that various changes, substitutions, permutations, and alterations can be made without departing from the scope of 10 the invention as defined by the appended claims. It will be appreciated that any feature that is described in a connection to any one embodiment may also be applicable to any other embodiment.

**CLAIMS**

What is claimed is:

Claim 1. A system for applying a reduced pressure to a tissue site on a foot, the system  
5 comprising:  
a reduced-pressure source operable to supply the reduced pressure;  
a foot manifold in fluid communication with the reduced-pressure source and operable  
to supply the reduced pressure to a tissue site on a foot, the foot manifold comprising:  
an insole,  
10 a tissue contacting surface covering at least a portion of the insole, at least one  
portion of the tissue contacting surface being removable to form a void,  
a reduced-pressure interface for receiving reduced pressure from the reduced  
pressure source, and  
15 at least one flow channel fluidly coupled to the reduced-pressure interface and  
the void; and  
a delivery conduit operable to deliver reduced pressure from the reduced-pressure  
source to the reduced-pressure interface.

Claim 2. The system of claim 1, wherein the tissue contacting surface comprises a  
20 plurality of removable support members, and wherein the at least one flow channel is formed  
by at least one groove on an insole-facing side of each of the plurality of removable support  
members.

Claim 3. The system of claim 1, wherein the tissue contacting surface comprises a  
25 plurality of removable support members, and wherein the at least one flow channel comprises  
a plurality of interconnected flow channels formed by a plurality of grooves on an insole-  
facing side of the plurality of removable support members.

Claim 4. The system of claim 1, wherein the tissue contacting surface comprises a  
30 plurality of removable support members, and wherein at least one edge of each of the plurality  
of removable support members defines at least a portion of an insertion slot, the insertion slot

adapted to receive a device that facilitates removing each of the plurality of removable support members.

5 Claim 5. The system of claim 1, wherein the at least one flow channel is a tube transferring reduced pressure from the reduced pressure-pressure interface to the void.

10 Claim 6. The system of claim 1, further comprising:

a sealing member operable to substantially seal the void, the sealing member adapted to be disposed between the plurality of removable support members and the tissue site.

15 Claim 7. The system of claim 1, wherein the tissue contacting surface comprises a sealing layer, and wherein at least a portion of the sealing layer is removable to form the void.

20 Claim 8. The system of claim 1, wherein the tissue contacting surface comprises a sealing layer, and wherein the at least one flow channel is at least partially formed by a groove on the insole.

25 Claim 9. The system of claim 8, wherein the groove forms a grid pattern.

Claim 10. The system of claim 1, further comprising:

a foam manifold adapted to be inserted into the void, and further adapted to distribute reduced pressure to the tissue site.

25 Claim 11. The system of claim 1, further comprising:

a delivery tube coupled to the reduced-pressure interface and operable to transfer reduced pressure from the reduced pressure source to the reduced-pressure interface.

30 Claim 12. The system of claim 11, wherein the delivery conduit has an elongated cross sectional shape, wherein the delivery conduit comprises a plurality of lumens operable to transfer the reduced pressure from the reduced pressure source to the reduced-pressure

interface, and wherein at least one wall of each of the plurality of lumens has a protrusion operable to prevent the lumen from collapsing.

Claim 13. The system of claim 1, further comprising:

5 a securing member operable to secure the insole adjacent the tissue site.

Claim 14. The system of claim 1, wherein the void is adjacent the tissue site, and wherein the reduced pressure is applied to the tissue site via the void.

10 Claim 15. An apparatus for applying reduced pressure to a tissue site on a foot, the apparatus comprising:

an insole;

a tissue contacting surface covering at least a portion of the insole, at least one portion of the tissue contacting surface being removable to form a void;

15 a reduced-pressure interface for receiving reduced pressure from a reduced-pressure source; and

at least one flow channel fluidly coupled to the reduced-pressure interface and the void.

20 Claim 16. The apparatus of claim 15, wherein the tissue contacting surface comprises a plurality of removable support members, and wherein the at least one flow channel is formed by at least one groove on an insole-facing side of each of the plurality of removable support members.

25 Claim 17. The apparatus of claim 15, wherein the tissue contacting surface comprises a plurality of removable support members, and wherein the at least one flow channel comprises a plurality of interconnected flow channels formed by a plurality of grooves on an insole-facing side of the plurality of removable support members.

30 Claim 18. The apparatus of claim 15, wherein the tissue contacting surface comprises a plurality of removable support members, and wherein at least one edge of each of the plurality

of removable support members defines at least a portion of an insertion slot, the insertion slot adapted to receive a device that facilitates removing each of the plurality of removable support members.

5 Claim 19. The apparatus of claim 15, wherein the at least one flow channel is a tube transferring reduced pressure from the reduced pressure-pressure interface to the void.

Claim 20. The apparatus of claim 15, further comprising:

10 a sealing member operable to substantially seal the void, the sealing member adapted to be disposed between the plurality of removable support members and the tissue site.

Claim 21. The apparatus of claim 15, wherein the tissue contacting surface comprises a sealing layer, and wherein at least a portion of the sealing layer is removable to form the void.

15 Claim 22. The apparatus of claim 15, wherein the tissue contacting surface comprises a sealing layer, and wherein the at least one flow channel is at least partially formed by a groove on the insole.

Claim 23. The apparatus of claim 22, wherein the groove forms a grid pattern.

20

Claim 24. The apparatus of claim 15, further comprising:

a foam manifold adapted to be inserted into the void, and further adapted to distribute reduced pressure to the tissue site.

25 Claim 25. The apparatus of claim 15, further comprising:

a delivery conduit coupled to the reduced-pressure interface and operable to transfer reduced pressure from the reduced pressure source to the reduced-pressure interface.

30 Claim 26. The apparatus of claim 25, wherein the delivery conduit has an elongated cross sectional shape, wherein the delivery conduit comprises a plurality of lumens operable to transfer the reduced pressure from the reduced pressure source to the reduced-pressure

interface, and wherein at least one wall of each of the plurality of lumens has a protrusion operable to prevent the lumen from collapsing.

Claim 27. The apparatus of claim 15, further comprising:

a securing member operable to secure the insole adjacent the tissue site.

Claim 28. The apparatus of claim 15, wherein the void is adjacent the tissue site, and wherein the reduced pressure is applied to the tissue site via the void.

Claim 29. The apparatus of claim 15, wherein the at least one portion of the tissue contacting surface is detachably mated to the insole.

Claim 30. Use of a foot manifold for applying reduced pressure to a tissue site on a foot, the foot manifold having a portion of a tissue contacting surface that covers an insole of the foot manifold removed to provide a void;

wherein the void is for aligning with the tissue site on the foot; and

wherein a substantially pneumatic seal is formable between the void and the tissue site, and a reduced pressure from a reduced-pressure source is applicable to the void via a flow channel.

Claim 31. The use as claimed in claim 30, wherein the tissue contacting surface comprises a plurality of removable support members, and wherein at least one of the plurality of removable support members is removed to provide the void.

Claim 32. The use as claimed in claim 30, wherein the tissue contacting surface comprises a sealing layer, and the portion of the tissue contacting surface that is removed includes a portion of the sealing layer.

Claim 33. The use as claimed in claim 30, wherein a sealing member is positionable between the tissue contacting surface and the tissue site for creating the substantially pneumatic seal.

Claim 34. The use as claimed in claim 30, wherein a foam manifold is capable of being applied into the void.

Claim 35. A method of manufacturing an apparatus for applying reduced pressure to a tissue site on a foot, the method comprising:


- providing an insole;
- providing a tissue contacting surface; and
- covering at least a portion of the insole with the tissue contacting surface to form at least one flow channel operable to transfer reduced pressure.

Claim 36. The method of claim 35, further comprising:


- providing a reduced-pressure interface; and
- coupling the reduced-pressure interface to the insole.

1/7

FIG. 1



2/7



## FIG. 2

3/7




FIG. 3A




FIG. 3B

4/7




FIG. 4A





FIG. 4B

5/7



6/7




FIG. 6




FIG. 7




FIG. 8

7/7

