



US008142401B2

(12) **United States Patent**  
**Rosenberg**

(10) **Patent No.:** **US 8,142,401 B2**  
(45) **Date of Patent:** **Mar. 27, 2012**

(54) **ANCHOR INSTRUMENTATION AND METHODS**

(75) Inventor: **Michael S. Rosenberg**, Plymouth, MN (US)

(73) Assignee: **INTERRAD Medical, Inc.**, Plymouth, MN (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/793,261**

(22) Filed: **Jun. 3, 2010**

(65) **Prior Publication Data**

US 2010/0241084 A1 Sep. 23, 2010

**Related U.S. Application Data**

(62) Division of application No. 11/763,576, filed on Jun. 15, 2007, now Pat. No. 7,753,889.

(51) **Int. Cl.**  
**A61M 5/32** (2006.01)

(52) **U.S. Cl.** ..... **604/174**

(58) **Field of Classification Search** ..... 604/500,  
604/506-508, 174, 164.1, 164.11, 158, 175,  
604/192, 264

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,525,398 A	10/1950	Collins
3,059,645 A	10/1962	Hasbrouck et al.
3,108,595 A	10/1963	Overment
3,176,690 A	4/1965	H'Doubler
3,630,195 A	12/1971	Santomieri
3,677,250 A	7/1972	Thomas

3,717,151 A	2/1973	Collett
3,834,380 A	9/1974	Boyd
3,856,009 A	12/1974	Winnie
3,896,527 A	7/1975	Miller et al.
3,938,529 A	2/1976	Gibbons
4,043,346 A	8/1977	Mobley et al.
4,114,618 A	9/1978	Vargas
4,248,224 A	2/1981	Jones
4,309,994 A	1/1982	Grunwald
4,397,647 A	8/1983	Gordon
4,474,569 A	10/1984	Newkirk
4,592,356 A	6/1986	Gutierrez
4,645,492 A	2/1987	Weeks
4,665,906 A	5/1987	Jervis
4,799,495 A	1/1989	Hawkins et al.
4,804,359 A	2/1989	Grunwald et al.
4,813,930 A	3/1989	Elliott
4,936,823 A	6/1990	Colvin et al.
4,986,810 A	1/1991	Semrad

(Continued)

**FOREIGN PATENT DOCUMENTS**

FR 2 625 897 7/1989

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 60/412,453, filed Sep. 20, 2002, Claude.

(Continued)



*Primary Examiner* — Christopher D Koharski

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

Some embodiments of a medical device anchor system includes an anchor sleeve and a catheter (or other medical instrument) to advance through a working channel of the anchor sleeve. The anchor sleeve may have a subcutaneous cuff device arranged along an outer surface. In such circumstances, the embedded cuff device can inhibit the migration of infection from outside the skin and into the blood stream.

**20 Claims, 13 Drawing Sheets**



U.S. PATENT DOCUMENTS

5,041,085 A 8/1991 Osborne et al.  
 5,067,957 A 11/1991 Jervis  
 5,122,122 A 6/1992 Allgood  
 5,190,546 A 3/1993 Jervis  
 5,256,146 A 10/1993 Ensminger et al.  
 5,263,939 A 11/1993 Wortrich  
 5,312,337 A 5/1994 Flaherty et al.  
 5,344,439 A 9/1994 Otten  
 5,378,239 A 1/1995 Termin et al.  
 5,456,671 A 10/1995 Bierman  
 5,496,277 A 3/1996 Termin et al.  
 5,578,013 A 11/1996 Bierman  
 5,597,378 A 1/1997 Jervis  
 5,599,311 A 2/1997 Raulerson  
 5,681,288 A 10/1997 Schlitt  
 5,688,247 A 11/1997 Haindl et al.  
 5,702,371 A 12/1997 Bierman  
 5,722,959 A 3/1998 Bierman  
 5,728,133 A 3/1998 Kontos  
 5,741,234 A 4/1998 Aboul-Hosn  
 5,746,720 A 5/1998 Stouder, Jr.  
 5,755,697 A 5/1998 Jones et al.  
 5,769,821 A 6/1998 Abrahamson et al.  
 5,800,402 A 9/1998 Bierman  
 5,810,781 A 9/1998 Bierman  
 5,827,230 A 10/1998 Bierman  
 5,833,667 A 11/1998 Bierman  
 5,857,999 A 1/1999 Quick et al.  
 5,921,965 A 7/1999 Blei  
 5,928,266 A 7/1999 Kontos  
 5,944,732 A 8/1999 Raulerson et al.  
 5,947,931 A 9/1999 Bierman  
 5,971,960 A 10/1999 Flom et al.  
 5,989,265 A 11/1999 Bouquet De La Joliniere et al.  
 6,071,263 A 6/2000 Kirkman  
 6,213,979 B1 4/2001 Bierman  
 6,290,676 B1 9/2001 Bierman  
 6,413,240 B1 7/2002 Bierman et al.  
 6,447,485 B2 9/2002 Bierman

6,471,689 B1 10/2002 Joseph  
 6,475,207 B1 \* 11/2002 Maginot et al. .... 604/508  
 6,540,693 B2 4/2003 Burbank et al.  
 6,572,588 B1 6/2003 Bierman et al.  
 6,582,403 B1 6/2003 Bierman et al.  
 6,663,600 B2 12/2003 Bierman et al.  
 6,679,851 B2 1/2004 Burbank et al.  
 6,695,861 B1 2/2004 Rosenberg et al.  
 6,770,055 B2 8/2004 Bierman et al.  
 6,896,665 B2 5/2005 Picha et al.  
 6,958,044 B2 10/2005 Burbank et al.  
 7,056,286 B2 6/2006 Ravenscroft et al.  
 2002/0068898 A1 6/2002 McGuckin et al.  
 2002/0068899 A1 6/2002 McGuckin et al.  
 2002/0165489 A1 11/2002 McGuckin et al.  
 2005/0187578 A1 8/2005 Rosenberg et al.  
 2006/0129134 A1 6/2006 Kerr  
 2007/0078397 A1 4/2007 Weststrate  
 2007/0106330 A1 \* 5/2007 Rosenberg et al. .... 606/232  
 2007/0225651 A1 9/2007 Rosenberg et al.

FOREIGN PATENT DOCUMENTS

WO WO 91/15254 3/1991  
 WO WO 2004/026152 4/2004  
 WO WO 2005/039419 5/2005  
 WO WO 2005/102438 11/2005

OTHER PUBLICATIONS

Johnson & Johnson web page printout, "The EndoANCHOR Comparative Summary," printed Sep. 13, 2005.  
 Johnson & Johnson web page printout, "The EndoANCHOR Features and Benefits," printed Sep. 13, 2005.  
 Johnson & Johnson web page printout, "The EndoANCHOR Firing Sequence," printed Sep. 13, 2005.  
 Web Page printout of Statlock Device, author and date unknown.  
 European Search Report for EP 08158277.7, mailed Sep. 11, 2008, 9 pages.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 6B




FIG. 7






FIG. 9






FIG. 11




FIG. 12




FIG. 13




FIG. 14

## ANCHOR INSTRUMENTATION AND METHODS

### CROSS-REFERENCE TO RELATED APPLICATION(S)

This application is a division of U.S. patent application Ser. No. 11/763,576 filed on Jun. 15, 2007 by Michael S. Rosenberg, the contents of which are incorporated herein by reference.

### TECHNICAL FIELD

This document relates to anchor instrumentation, such as an anchor device for use in placement of a catheter or other medical instrument.

### BACKGROUND

Venous, arterial, and body fluid catheters are commonly used by physicians. For example, such catheters may be used to gain access to the vascular system for dialysis, for introducing pharmaceutical agents, for nutrition or fluids, for hemodynamic monitoring, and for blood draws. Alternatively, catheters can be used for drainage of fluid collections and to treat infection. Following introduction into the patient, the catheter is typically secured to the patient using a tape patch or by suturing an attached hub to the skin. Some catheters may be delivered to a particular site in the body and remain in position for an extended period of time. For example, chronic dialysis patients may have a dialysis catheter arranged in a blood vessel for weeks or months at a time.

### SUMMARY

Some embodiments of a medical device anchor system include an anchor sleeve and a catheter (or other medical instrument) to advance through a working channel of the anchor sleeve. The anchor sleeve may have a subcutaneous cuff device arranged along an outer surface. The subcutaneous cuff device can receive ingrowth of bodily tissue over a period of time when disposed in the subcutaneous layer. In such circumstances, the embedded cuff device can inhibit the migration of infection from outside the skin, along the anchor system, and into the blood stream. Furthermore, in the embodiments in which the cuff device is arranged on the anchor sleeve (rather than on the catheter body), the catheter can be distally advanced such that the cuff-to-tip distance from the subcutaneous cuff device to the catheter tip can be selectively adjusted. Thus, the cuff-to-tip distance can be customized by a practitioner while the catheter tip is inside the patient's body depending on the size of the patient, the anatomy of the patient, and other factors.

In some embodiments, an anchor sleeve device may include an elongate body that defines at least one working channel extending from a proximal portion to a distal tip portion. The anchor sleeve device may also include a subcutaneous anchor mechanism coupled to the elongate body. The subcutaneous anchor mechanism may have one or more flexible anchors that extend away from the body wall when in a deployed orientation in a subcutaneous layer. The anchor sleeve device may further include a subcutaneous cuff device arranged along an outer surface of the elongate body at a position distally of the one or more flexible anchors. The subcutaneous cuff device may comprise a biocompatible material to receive ingrowth of bodily tissue when disposed in the subcutaneous layer.

Particular embodiments may include an anchor system for placement of a catheter device. The anchor system may include an anchor sleeve having an elongate body that defines at least one working channel extending from a proximal portion to a distal tip portion of the anchor sleeve. The anchor sleeve may also have a subcutaneous cuff device arranged along an outer surface of the elongate body. The subcutaneous cuff device may comprise a biocompatible material to embed in bodily tissue when disposed in a subcutaneous layer. The anchor system may also include a catheter device to advance through the working channel of the anchor sleeve and into a targeted body site. The catheter device may define at least one lumen that extends to a catheter tip opening. When the catheter device is advanced through the working channel of the anchor sleeve, a distance from the subcutaneous cuff device to the catheter tip opening can be adjusted.

Some embodiments include a method of delivering a catheter device to an internal body site. The method may include advancing an anchor sleeve through a percutaneous opening so that a subcutaneous cuff device arranged along an outer surface of the anchor sleeve is disposed in a subcutaneous region. The subcutaneous cuff device may comprise a biocompatible material that receives tissue ingrowth when disposed in the subcutaneous region. The method may also include advancing a catheter device through a working channel of the anchor sleeve and toward a targeted body site. The catheter device may define at least one lumen that extends to a catheter tip. The distance from the subcutaneous cuff device to the catheter tip may define a cuff-to-tip distance. The method may further include adjusting the cuff-to-tip distance by moving the catheter device relative to the anchor sleeve while the subcutaneous cuff device is disposed in the subcutaneous region.

In certain embodiments, an anchor sleeve device includes an elongate body that defines at least one working channel extending from a proximal opening to a distal tip opening so as to receive a catheter. The anchor sleeve device may also include a subcutaneous anchor mechanism coupled to the elongate body. The subcutaneous anchor mechanism may have one or more flexible anchors that extend away from the body wall when in a deployed orientation in a subcutaneous layer. The anchor sleeve device may further include a locking device that releasably affixes to the catheter when the catheter is received in the working channel. The anchor sleeve device may also include an actuator that is adjustable relative to the elongate body from a first position to a second position. The adjustment of the actuator may simultaneously shift the flexible anchors to the deployed orientation and shift the locking device to compress at least a portion of an outer surface of the catheter when the catheter is received in the working channel.

These and other embodiments may provide one or more of the following advantages. First, the subcutaneous cuff device arranged along an outer surface of the anchor sleeve can serve as a barrier to infection. For example, the subcutaneous cuff device can receive ingrowth of bodily tissue or otherwise embedded into the surrounding tissue over a period of time, thereby inhibiting the migration of infection from outside the skin and into the blood stream.

Second, in some embodiments, a catheter or other medical instrument can be distally advanced such that the cuff-to-tip distance from the subcutaneous cuff device to the instrument tip can be selectively adjusted. Thus, the cuff-to-tip distance can be customized by a practitioner while the catheter tip is inside the patient's body depending on the size of the patient, the anatomy of the patient, and other factors.

Third, because the cuff-to-tip distance can be selectively adjusted by the practitioner during use in a patient, there is a

reduced need to maintain an inventory of catheters having a fixed cuff-to-tip distance. For example, some catheters included a cuff device affixed on an outer surface of the catheter body, thereby providing a fixed and nonadjustable cuff-to-tip distance. Hospitals or clinics would maintain a vast inventory of these catheter-cuff devices so that a wide variety of cuff-to-tip distances can be selected and used by the practitioners. In some embodiments described herein, the cuff device is arranged on an anchor sleeve that is movable relative to the catheter, thereby providing an adjustable cuff-to-tip distance. As such, hospitals or clinics may no longer be required to maintain vast inventories of catheters having a range of fixed cuff-to-tip distances.

Fourth, some embodiments of the anchor sleeve may include subcutaneous anchors that retain the anchor sleeve in the subcutaneous region. For example, the anchors may comprise adjustable tines comprising a material that exhibits superelasticity when used in a human body (e.g., Nitinol or the like). The anchors can be deployed in the subcutaneous region so as to at least temporarily retain the anchor sleeve in engagement with the patient's body while the cuff device embeds with the surrounding tissue over a period of time. Thereafter, the cuff device may function as a long term anchor instrument in place of, or in addition to, the previously described tines.

Fifth, some embodiments of the anchor sleeve may include a locking device that can be actuated to releasably secure the catheter (or other medical instrument) to the sleeve body after the catheter has been advanced through the sleeve device toward a targeted location. In some circumstances, the locking device can also form a seal around the catheter when connected thereto. A single actuator can be adjusted to contemporaneously shift the flexible anchors to a deployed orientation in the subcutaneous region and shift the locking device to act upon the catheter.

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

#### DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of an anchor sleeve device in accordance with some embodiments.

FIG. 2 is a perspective view of the anchor sleeve device of FIG. 1 with the anchors in a non-deployed position.

FIG. 3 is a side view of a portion of the anchor sleeve device of FIG. 1.

FIG. 4 is a cross-sectional view of the anchor sleeve device of FIG. 3.

FIG. 5 is another cross-sectional view of the anchor sleeve device of FIG. 3.

FIG. 6A is another cross-sectional view of the anchor sleeve device of FIG. 3.

FIG. 6B is an exploded perspective view of an actuator of the anchor sleeve of FIG. 6A.

FIG. 7 is a side view of the anchor sleeve device of FIG. 1 being advanced into a subcutaneous region.

FIG. 8 is another side view of the anchor sleeve device of FIG. 7 having the anchors in a deployed position and having a catheter device passing therethrough.

FIGS. 9-10 are top and side views of an anchor sleeve device having non-retractable anchors, in accordance with some embodiments.

FIG. 11 is a perspective view of an anchor sleeve device having no anchor tines, in accordance with some embodiments.

FIG. 12 is a perspective view of an anchor sleeve device having no cuff device, in accordance with some embodiments.

FIGS. 13-14 are perspective views of an anchor system used to advance a catheter device to a targeted site in a heart chamber.

Like reference symbols in the various drawings indicate like elements.

#### DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Some embodiments of a medical device anchor system include an anchor sleeve and a catheter (or other medical instrument) to advance through a working channel of the anchor sleeve. As described in more detail below, the anchor sleeve may have a subcutaneous cuff device that embeds with the surrounding bodily tissue when disposed in the subcutaneous layer over a period of time. In such circumstances, the embedded cuff device can inhibit the migration of infection from outside the skin, along the anchor system, and into the blood stream. Also as described in more detail below, the catheter is movable relative to the anchor sleeve, so the cuff-to-tip distance can be selectively adjusted by a practitioner while the catheter tip is inside the patient's body.

Referring to FIGS. 1-2, an anchor sleeve device **100** can be used in a system for placement of a catheter or other medical instrument into the body of a patient. The sleeve device **100** may include an elongate body **110**, into which a catheter or other medical instrument can be inserted. The sleeve device **100** includes a distal tip portion **120** that may penetrate through a skin entry point and into the subcutaneous layer adjacent to the skin. Also, the sleeve device **100** includes a proximal portion **130** that can remain external to the skin so as to provide an insertion path for a catheter or other medical instrument. As described in more detail below, some embodiments of the sleeve device **100** may include a cuff **140**, a depth indicator **150**, one or more subcutaneous anchors **160**, an actuator **170**, a stopper **180**, or a combination thereof.

In some embodiments, the sleeve device **100** may be inserted through a percutaneous opening formed in the skin (e.g., a puncture, an incision, or the like) and into the subcutaneous region so that the cuff **140** rests in the subcutaneous region (refer, for example, to FIGS. 7-8). The cuff **140** may be made of a biocompatible material (e.g., a polyester material such as Dacron, a polytetrafluoroethylene material such as a Goretex mesh, titanium mesh, or the like) that is configured to receive the ingrowth of bodily tissue or otherwise embed with the surrounding tissue. As such, the cuff **140** may embed in the subcutaneous tissue over a period of time to limit or prevent the migration of infection from outside the skin to components or anatomical structures (e.g., blood vessels) distal of the cuff **140**. After initial insertion of the sleeve device **100** into the subcutaneous region, the subcutaneous anchors **160** may be deployed in the subcutaneous region to assist in retention of the sleeve device **100** in position, thereby permitting the cuff **140** to sufficiently embed over a period of time (refer, for example, to FIG. 8).

In some embodiments, the sleeve device **100** may be used for long-term anchoring of a catheter or other medical instrument in a patient. For example, a chronic dialysis catheter may be advanced through the sleeve device **100** and into a patient requiring ongoing dialysis treatments. The dialysis catheter may reside in the patient's body for a long-term

period of weeks or months. The cuff **140** may be designed to function as a long-term anchor instrument and as a barrier for infection, which can be accomplished through tissue ingrowth into the cuff **140**. In this embodiment, the cuff **140** comprises a Dacron material, which may include polyester, and may have a porous texture to encourage tissue ingrowth. In alternative embodiments, the cuff **140** may comprise other materials (e.g., Goretex mesh, titanium mesh or the like) suitable for use in the subcutaneous region to encourage tissue ingrowth. In additional embodiments, a combination of biocompatible materials may be used in the cuff **140**. Although the sleeve device **100** is shown as having a single cuff **140** in this embodiment, it should be understood from the description herein that more than one cuff can be employed on an outer surface of the sleeve device **100**.

In some embodiments, the depth indicator **150** is present on the body **110** of the sleeve device **100** to assist the user in placing the sleeve device **100** to a desired depth in a patient. As described below in connection with FIGS. 7-8, the sleeve device **100** can be inserted through an entry point in the skin into the subcutaneous layer until the depth indicator **150** is adjacent to the epidermis at the skin entry point. In some embodiments, the depth indicator **150** can include one or more indentations in the body **110**. In additional embodiments, the depth indicator **150** could be one or more markings indicating the depth at which the sleeve device **100** has been inserted.

Still referring to FIGS. 1-2, the sleeve device **100** includes one or more subcutaneous anchors **160** for use in the temporary anchoring of at least a portion of body **110** in the subcutaneous layer under the skin. In some embodiments, the subcutaneous anchors **160** may comprise a material that exhibits superelasticity when used in the patient's body. As such, the subcutaneous anchors can flexibly shift from a non-deployed position to a deployed position when in the subcutaneous layer. For example, the anchors **160** may be formed from a length of nitinol wire or from a sheet of nitinol material, which has been processed to exhibit superelasticity below or at about a normal human body temperature, such as below or at about 37 degrees C. The nitinol material may comprise, for example, Nickel Titanium (NiTi), Niobium Titanium (NbTi), or the like. Alternatively, the subcutaneous anchors **160** may comprise a metal material such as stainless steel, spring steel, titanium, MP35N and other cobalt alloys, or the like. In these embodiments, the subcutaneous anchors **160** can be formed from a material or materials that allow them to be adjustable from a non-deployed position to a deployed position.

In some embodiments, the subcutaneous anchors **160** can be flexed to a stressed condition when in the non-deployed position (e.g., prior to placement of the sleeve device **100** in a patient). For example, as shown in FIG. 2, the subcutaneous anchors **160** may be retracted into the body **110** when in the non-deployed position. When deployed, as shown in FIG. 1, the subcutaneous anchors **160** can return to a shape (e.g., by exhibiting superelastic characteristics) that allows the subcutaneous anchors **160** to at least temporarily retain a portion or all of the body **110** in the subcutaneous region for a period of time until tissue has properly adhered to the cuff **140**. The subcutaneous anchors **160** may be designed with a curvature that facilitates the transition from the non-deployed to the deployed position. Furthermore, the curvature of the anchors **160** may be configured to eliminate or reduce the potential damage done to the skin during deployment of the anchors **160**. For example, the anchors **160** may include a convex curvature that abuts against the underside of the skin in a manner that prevents the tips of the anchors **160** from piercing through the skin.

In use, the subcutaneous anchors **160** can be shifted to the non-deployed position (refer, for example, to FIG. 2) prior to insertion so as to minimize resistance and possible damage to the skin when inserted through the skin entry point. When the anchor sleeve device **100** has been inserted to the intended depth inside the subcutaneous layer, the anchors **160** can be shifted to the deployed position (refer, for example, to FIG. 1) to provide at least temporary anchoring for some or all of the anchor sleeve device **100**. When removal of the anchor sleeve device **100** is desired, the subcutaneous anchors can be shifted to the non-deployed position prior to removal to minimize resistance and possible damage to the skin and subcutaneous region.

As shown in FIG. 2, the actuator **170** can be adjusted relative to the body so as to cause the subcutaneous anchors **160** to retract to the non-deployed position. In this embodiment, the actuator **170** can be depressed until it contacts the stopper **180** causing the subcutaneous anchors **160** to retract into the body **110**. Transitioning the subcutaneous anchors **160** from the deployed position (FIG. 1) to the non-deployed position (FIG. 2) can allow for easier insertion of the anchor sleeve device **100** into a subcutaneous region through the skin entry point. After the sleeve device **100** is inserted into the patient, the actuator **170** can be shifted away from the stopper **180** to urge the subcutaneous anchors **160** to extend from the body **110** (as shown in FIG. 1). In some embodiments, the anchors **160** can then act as temporary anchor for the sleeve device **100** for a period of time to allow the surrounding tissue to properly adhere to the cuff **140**.

Referring now to FIGS. 3-4, the body **110** of the sleeve device **100** may have an elongate shape and can comprise a biocompatible material, such as PEEK (polyetheretherketone), polyethylene, polyimide, or the like. The body **110** may have a modified elliptical cross-sectioned shape (as shown, for example, in FIG. 4) and may include a taper along the distal portion **120** that facilitates insertion of the sleeve device **100** through the skin of a patient. In this embodiment, the previously described cuff **140** is located on the body **110** adjacent to this taper (as shown in FIG. 3). Alternatively, the cuff **140** may be located along the tapered region closer to the distal tip, or may be located in a more proximal position closer to the anchors **160**. As shown in FIG. 3, the body **110** may also include anchor holes **112** through which the anchors **160** extend when deployed.

Referring to FIG. 4, in some embodiments, the sleeve device **100** can include one or more internal channels **200** and **210**. For example, the sleeve device **100** may include a working channel **200** to receive a catheter or other medical instrument, and may also include an actuator channel **210** to accommodate the actuation of the subcutaneous anchors **160**.

The working channel **200** can extend through the entire length of the sleeve device **100** from the distal tip portion **120** to the proximal portion **130**. After insertion of at least a portion of the body **110** into a subcutaneous region, the working channel **200** can be used to introduce a catheter or other medical instrument into a patient. Thus, the catheter can be introduced into the working channel **200** at the proximal portion **130** and inserted through the entire body **110** of the sleeve device **100** until it emerges from the distal tip portion **120**.

In the embodiment depicted in FIG. 4, the sleeve device **100** contains a single, round working channel **200**. In alternate embodiments of the sleeve device **100**, the working channel **200** need not be round or of the size depicted. For example, the working channel **200** may have a cross-sectional shape in the form of a square or other polygon that mates with the medical instrument to be passed therethrough. Also, the

working channel **200** need not be a single lumen. In alternate embodiments, the sleeve device **100** may include multiple working channels, such as adjacent channels or coaxial channels that permit the introduction of multiple medical instruments (e.g., catheters, endoscopes, or the like). Furthermore, the multiple working channels may be selectively sealable so that one working channel could be accessed while another is sealed. In such cases, it would be possible to introduce and secure several catheters at different points in time.

Still referring to FIGS. 3-4, the actuator channel **210** of the sleeve device **100** is formed in the body **110** and can movably receive an actuator rod **220**. The actuator channel **210** may be defined by one or more side walls **212** that can slidably engage the actuator rod **220**. Movement of the actuator rod **220** within the actuator channel **210** can urge the anchors **160** to extend from, or retract into, the actuator channel **210**. In this embodiment, the cross-sectional shape of the actuator rod **220** may be that of a quadrilateral to permit longitudinal movement of the actuator rod **220** while hindering the rotational movement of the actuator rod **220** about its longitudinal axis. While this embodiment of the anchor sleeve **100** contains an actuator channel **210**, other embodiments may have non-adjustable anchors or no anchors at all (refer, for example, to FIGS. 9-11) and as such may not include an actuator channel **210** or related components.

Referring now to FIG. 5, the actuator rod **220** of the sleeve device **100** can be reciprocated within the actuator channel **210** in the longitudinal direction of the sleeve device **100**. The actuator rod **220** may include a proximal end **222** that is coupled to the actuator **170** via, for example, a connector portion **171** of the actuator **170**. As such, movement of the actuator **170** can be translated to the actuator rod **220**. The actuator **170** can be slidably engaged with the body **110** and may include a circumferential inner wall **172** that can slidably mate with a circumferential outer wall **114** of the body **110**. When the actuator **170** is moved relative to the body **110**, the inner wall **172** and the outer wall **114** may stay in contact such that a seal is maintained against the transfer of liquids. The actuator rod **220** has a distal end **224** that can be advanced and retracted within the actuator channel **210** in response to the movement of the actuator **170**. The anchors **160** can be coupled to the actuator rod **220** such that movement of the actuator **170** (and the corresponding translation of the actuator rod **220** within the actuator channel **210**) causes the anchors **160** to shift between the non-deployed position and the deployed position. In this embodiment, the anchors **160** are integrally formed with the actuator rod **220** (e.g., formed from a nitinol material or the like).

The actuator channel **210** may not extend fully through the body **110** of the anchor sleeve **100**. For example, the actuator channel **210** may extend from the proximal portion **130** to a depth that extends to a terminal end **214**. In some embodiments, when the actuator **170** is pressed against the stopper **180**, the anchor actuator rod **220** is caused to advance within the anchor actuator channel **210** such that the distal end **224** of the actuator rod **220** approaches the terminal end **214** of the actuator channel **210**. In this embodiment, the anchors **160** are coupled to the actuator rod **220** so that the anchors **160** retract into the body **110** as the distal end **224** of the rod **220** approaches the terminal end **214** (shifts to the non-deployed state). In such circumstances, the anchors **160** may be flexed to a stressed condition while retained within the actuator channel **210**.

It should be understood from the description herein that, in some embodiments, the anchors **160** can be joined with the actuation rod **220** at a location other than the distal end **224**. For example, in other embodiments, the anchors **160** may be

connected to the actuator rod **220** along a middle region of the rod **220**. Also, in alternative embodiments, the anchors **160** may be non-integral with the actuator rod **220**. For example, the anchors may be formed separately from the actuator rod **220** and then mounted to the rod **220** using an adhesive, a weld, a connector, or the like.

As shown in FIG. 5, the actuator **170** can be pulled back from the stopper **180**, and this movement is translated to the actuator rod **220** via the connector portion **171**. The actuator rod **220** slides within the actuator channel **210** so that the distal end **224** of the rod shifts away from the terminal **214**. This motion of the actuator rod **220** causes the distal tips **161** of the anchors **160** to pass through the openings **112** and thereby extend outwardly from the body **110**. It should be understood from the description herein that, in alternative embodiments, the actuator rod **220** and anchors **160** could be configured so that pulling the actuator **170** in the direction away from the stopper **180** would cause the anchors **160** to transition to their non-deployed state, while pressing the actuator **170** in the direction of the stopper **180** would cause the anchors **160** to transition to the deployed state.

Referring now to FIG. 6A, the working channel **200** can extend through the length of the sleeve device **100** and can receive at least one catheter or other medical instrument. In some embodiments, the working channel **200** can have a diameter of about 3 French to about 30 French, and about 5 French to about 20 French, including particular ranges from about 3 French to about 7 French and about 12 French to about 17 French. As such, the working channel **200** can accept a wide range of catheters and medical instruments. The working channel **200** can extend from a proximal opening **202** located in the proximal portion **130** of the sleeve **100** to a distal opening **204** located in the distal tip portion **120** of the sleeve **100**. When a catheter or other medical instrument is inserted into the sleeve device **100**, it enters the working channel **200** via the proximal opening **202**, travels through an opening **116** in the body **110**, continues to travel down the working channel **200** until emerging from the distal opening **204**.

In some embodiments, the actuator **170** is slidably engaged with the body **110** such that the actuator **170** may move longitudinally relative to the stopper **180**. The sleeve device **100** may include a locking device **174** that can be adjusted to clamp to, or otherwise connect with, the catheter passing through the working channel **200**. As such, the locking device **174** serves as a mechanism that releasably secures the catheter to the sleeve device **100** after the catheter has been advanced through the sleeve device **100** toward a targeted location. In some circumstances, the locking device **174** can also form a seal around the catheter when connected thereto. As described in more detail below in connection with FIG. 6B, locking device **174** can include one or more components that extend from the proximal face **118** of the sleeve body **110**. In addition, the locking device **174** may also include side walls **178** which slidably engage an inner walls **179** of the actuator **170**, thus creating a dynamic seal as the actuator **170** moves longitudinally relative to the body **110**.

Referring now to FIG. 6B, some embodiments of the locking device **174** may include first and second jaws **175a-b** that operate to clamp upon the outer surface of the catheter when the catheter is position in the working channel **200**. (It should be understood that the catheter and the actuation rod **220** have been removed from view in FIG. 6B for purposes of illustrating the locking device **174**). For example, the first and second jaws **175a-b** can compress the catheter into a locking engagement in response to movement of the actuator **170**. As such, the catheter can be advanced through the working channel

**200** to a targeted location inside the patient's body. Thereafter, the actuator **170** can be shifted away from the stopper **180** so as to deploy the anchors **160** (as previously described in connection with FIG. 5). This movement of the actuator **170** can also cause the second jaw **175b** to shift relative to the first jaw **175a** so as to compress the outer surface of the catheter (or other medical instrument) disposed in the working channel **200**.

In this embodiment, the first jaw **175a** is a fixed component that extends from the proximal surface **118** of the sleeve body **100**. For example, the first jaw **175a** may be integrally formed with the sleeve body **100**. The second jaw **175b** is adjustable relative to the first jaw **175a** so as to provide a clamping action or other locking operation. For example, the second jaw **175b** can extend from the proximal surface **118** so as to be cantilevered from the sleeve body **110**. The second jaw **175b** may include at least one cam surface **176a** that slidably engages a guide member **177** of the actuator **170**. The cam surface **176a** can include a decline path or other configuration that causes the guide member **177** to force the second jaw **175b** toward the first jaw when the actuator **170** (and the guide member **177**) are moved away from the stopper **180**. Thus, the motion of the actuator **170** causes the guide member **177** to act upon the cam surface **176a** and shift the second jaw **175b** toward the first jaw **175a**, thereby causing the jaws **175a-b** to clamp or otherwise lock onto the medical instrument inside the working channel **200**.

It should be understood that, in some embodiments, the locking device **174** may include one or more seal members arranged between the opposing surfaces of the jaws **175a-b**. For example, a silicone seal having a half-cylinder shape can be affixed to the inner cylindrical face of the first jaw **175a**, and an opposing silicone seal having a half-cylinder shape can be affixed to the inner cylindrical face of the second jaw **175b**. As such, when the second jaw **175b** is forced toward the first jaw **175a**, the opposing seal members would surround and compress the outer surface of the catheter arranged in the working channel **200**. In such embodiments, the locking device **174** can form a seal around the catheter in addition to locking the catheter to the sleeve device **100**.

Still referring to FIG. 6B, the guide member **177** may be stopped at the end of its travel by a notch **176b** formed in the second jaw **175b**. The notch **176b** can be configured to mate with the guide member **177** so that further longitudinal movement of the guide member **177** (and the actuator **170**) is inhibited. In this embodiment, notch **176b** releases the guide member **177** when the actuator **170** is moved in a return path toward the stopper **180**. In such circumstances, the guide member **177** moves along the cam surface **176a** so that the second jaw **175b** can pivot away from the first jaw **175a**, thereby releasing the catheter from the locking engagement with the sleeve device **100**.

Referring now to FIG. 7, in some embodiments, the sleeve device **100** may be inserted through a hole in skin **10** of a patient until at least a portion of the body **110** is located in a subcutaneous region **20**. In preparation for insertion, the actuator **170** may be pressed against the stopper **180** to retract the anchors **160** through the anchor holes **112** and into the non-deployed position inside the body **110**. In particular embodiments, the sleeve device **100** can be introduced through a patient's skin prior to commencement of a medical procedure or other treatment. For example, the sleeve device **100** may penetrate the skin **10** and subcutaneous region **20** through a small incision made by a physician. In some cases a dilation instrument may be used to assist in advancing the sleeve device **100** through the incision.

In some embodiments, once the sleeve device **100** has been inserted through the skin **10**, at least a portion of the body **110** may be located inside the subcutaneous region **20**. In this example, the sleeve device **100** is inserted such that, for example, the distal tip portion **120**, the cuff **140**, and the anchor holes **112** are located inside the subcutaneous region **20**. In particular, the anchors holes **112** can be positioned in the subcutaneous region **20** proximate to the underside of the skin **10**. As such, the actuator **170**, the stopper **180**, and the proximal opening **202** remain external to the skin so that a practitioner has access to the proximal opening **202** (e.g., to insert the catheter) and the actuator **170** (e.g., to shift the anchors **160**). The sleeve device **100** can be positioned such that the distal opening **204** is adjacent to a targeted blood vessel **30** or other body lumen that will receive the catheter or other medical instrument passing through the sleeve **100**.

Referring to FIG. 8, after the sleeve device **100** has been placed such that at least a portion of the body **110** (e.g., the distal tip portion **120**, the cuff **140**, and the anchor holes **112**) is in the subcutaneous region **20**, the sleeve device **100** can be anchored at least temporarily through the use of the deployed anchors **160**. To deploy the anchors **160**, the actuator **170** can be shifted in a proximal direction away from the stopper **180**. In doing so, the anchors **160** are transitioned from the non-deployed position inside the body **110** to the deployed position outside of the body **110** by extending out of the anchor holes **112**. As the anchors **160** extend through the anchor holes **112**, they transition from their stressed shape inside the body **110** to their memory shape (e.g., curved shape in this example). When the anchors **160** extend from the anchor holes **112**, which are positioned just under the skin **10** in the subcutaneous region **20**, the curved shape of the anchors **160** can allow them to deploy adjacent to the skin **10** without tearing or otherwise damaging it. When deployed, the anchors **160** can exert a retainment force on the body **110** that secures the position of the sleeve device **100** relative to the skin entry point. In some embodiments, the anchors **160** may provide a holding force of about 1 lb. or greater, depending upon the medical procedure being performed, the materials comprising the anchors **160**, the geometry of the anchors **160**, and/or other factors. For example, the anchors **160** may provide a holding force of about 0.5 lbs or more, about 1 lb to about 20 lbs, about 1 lb to about 5 lbs, or about 2 lbs to about 3 lbs.

In some embodiments, while the anchors **160** are serving as a temporary or long-term device for retaining the sleeve device **100**, some bodily tissue can grow into or otherwise embed with the cuff **140** over a period of time. When embedded with the surrounding bodily tissue, the cuff **140** can serve as a long-term anchor for the sleeve device **100**, either in lieu of the anchors **160** or as a supplement to the anchors **160**. Furthermore, the cuff **140** can act as a barrier against infection, for example, by minimizing the transmittance of bacteria from the external surface of the skin **10** to underlying anatomical structures, such as the blood vessel **30**. In some embodiments, after a period of time has elapsed which is long enough for tissue to have grown into the cuff **140**, the anchors **160** may be transitioned back to their non-deployed position, thus no longer utilizing the anchors **160** to secure the sleeve device **100** in place. Alternatively, the anchors **160** may be left in their deployed position to act as an additional long-term anchor point for the sleeve device **100**.

Still referring to FIG. 8, the sleeve device **100** can be operated as part of a system including the sleeve device **100** and another medical instrument. When the sleeve device **100** has been inserted in the subcutaneous region **20** and has been anchored there (e.g., by the anchors **160**, the cuff **140**, or a

combination thereof), a medical instrument, such as a catheter **300**, can be introduced through the working channel **200** (FIGS. **4** and **6**) and into the body. For example, the catheter **300** can be inserted into the working channel **200** of the sleeve device **100** at the proximal opening **202**, and can continue to be advanced until it emerges from the distal opening **204** along the distal tip portion **120**. In the example depicted in FIG. **8**, the catheter **300** can continue to be advanced toward a penetration location into a targeted blood vessel **30**. As the sleeve device **100** and cuff **140** remain in place relative to the patient, the catheter **300** can be advanced until the catheter tip **302** reaches a targeted site within the body. Accordingly, the distance between the cuff **140** and the catheter tip **302** (e.g., the tip-to-cuff distance **310**) can be selectively adjusted depending on the patient's size, the patient's anatomy, the intended medical treatment, and other factors.

Advantageously, because the position of the catheter tip **302** is adjustable relative to the position of the sleeve device **100**, the tip-to-cuff distance **310** can be selected by the practitioner while the catheter tip **302** is advanced through the patient's body. Also, the tip-to-cuff distance **310** is adjustable at the time of insertion, so this distance need not be determined prior to the start of the procedure. Furthermore, such a system **5** that provides the adjustable tip-to-cuff distance **310** can reduce the need for hospitals or clinics to inventory a wide assortment of cuff-attached catheters, each having a non-adjustable tip-to-cuff length. Moreover, due to the adjustable nature of the tip-to-cuff distance **310**, the practitioner is not required to trim the distal portion of a catheter to achieve the desired dimensions, thereby by reducing the risk of over-shortening the catheter or altering features of the catheter tip.

Referring to FIG. **9**, some alternative embodiments the sleeve device **400** may include anchors **190** that do not retract into openings in the elongate body. For example, the anchors **190** may be designed to flex to a position against the side of the elongate body **110'** during insertion through the skin and then to elastically return to a deployed position (e.g., a curved shape in this example) after entering into the subcutaneous region. In the depicted embodiment, the sleeve device **400** includes two flexible, non-retractable anchors **190** that comprise a bio-compatible polymer material capable of elastically flexing during insertion into the subcutaneous region and capable of elastically flexing or plastically deforming during removal from the patient's skin. Similar to previously described embodiments, the anchors **190** can a material that exhibits superelasticity (e.g., Nitinol or the like). The anchors **190** can be deployed in the subcutaneous region so as to at least temporarily retain the anchor sleeve **400** in engagement with the patient's body while the cuff device embeds with the surrounding tissue over a period of time. In some embodiments, the anchors **190** may have grooves or notches formed therein to facilitate the proper flexing or deformation during insertion into the subcutaneous region or removal from the patient's skin, as described in more detail below. In these examples, the anchors **190** are not adjusted by an actuator, so the sleeve device **400** may not include, for example, an actuator channel **210**, an activation rod **220**, or an actuator **170** (as previously described in connection with FIG. **5**). In these embodiments, the sleeve device **400** can include one or more working channels **200** to receive a number of medical instruments. Furthermore, the sleeve device **400** may include a stationary handle **192** to assist in the insertion and removal of the sleeve device **400** from a patient.

In some embodiments, the anchors **190** may extend away from the plane of the outer wall **114'** of the body **110'**. As shown in FIG. **9**, some embodiments of the body **110'** may comprise one or more wall pockets **124** to receive the anchors

**190** in the event they are flexed to a non-deployed position against the body **110'** (e.g., during insertion or extraction from a patient). In these embodiments, the wall pocket **124** may serve to reduce the likelihood of trauma to the patient's skin during insertion by providing a space to accommodate one or more of the anchors **190**. When the sleeve device **400** is inserted into a patient, the anchors **190** may flex into a proximal region of the wall pocket **124** as they pass through the entry hole in the skin. Once the sleeve device **400** is inserted such that at least a portion of the body **110** (e.g., including the distal tip portion **120** and the cuff **140**) and the anchors **190** are located in the subcutaneous region **20**, the sleeve device **400** is in position such that the anchors **190** may return a deployed position similar to that shown in FIG. **9**. When the sleeve device **400** is removed from a patient, the anchors **190** are configured to elastically flex or plastically deform into a distal region of the wall pocket **124** as they exit from the hole in the skin.

Still referring to FIG. **9**, the sleeve device **400** can include a number of features that are similar to the previously described embodiments. For example, the sleeve device **400** can include the cuff **140** and the depth indicator **150** arranged on the elongate body **110'**. The sleeve device **400** may also include one or more working channels **200**. In some circumstances, the sleeve device **400** may include the working channel **200** as described in connection with FIGS. **6A-B** and other related features (e.g., the distal opening **204**) so as to receive a medical instrument such as a catheter **300**.

Referring now to FIGS. **9-10**, the sleeve device **400** may be introduced into a patient so that the anchors **190** may releasably secure at least a portion of the body **110** in the subcutaneous region **20** of a patient. The insertion force applied to the body **110'** may cause at least a portion of the anchors **190** to flex during insertion through the skin entry point. For example, each anchor **190** may superelastically flex toward a proximal region of the pocket **124** during insertion, and then can return to the deployed position (e.g., having a curved shape in this embodiment) when arranged in the subcutaneous region **20**. In the event the sleeve device **400** is to be removed from the subcutaneous region **20**, the removal force applied to the body **110'** may cause at least a portion of the anchors **190** to flex or deform toward a distal region of the wall pockets **124**. Thus, the anchors **190** may be self-actuated without the need for a separate actuation device (e.g., the actuator rod **220**, or the like) to extend or retract the anchors **190**.

In some embodiments, the sleeve device **400** may be introduced through a patient's skin prior to commencement of a medical procedure or other treatment. For example, the sleeve device **400** may be advanced through the skin **10** and into the subcutaneous region **20** via a small incision made by a physician. In some cases a dilation instrument may be used to assist in advancing the sleeve device **400**. As a result of an insertion force applied to the sleeve device **400** by the physician, the anchors **190** may be temporarily flexed from their unstressed configuration (as shown, for example, in FIG. **9**) to a proximally oriented configuration in which the anchors **190** extend substantially in a direction along the wall pockets **124** of the body **110'**. Such flexing action permits at least a portion of the anchors **190** to enter through the incision with a reduced likelihood of traumatizing the skin around the incision.

As shown in FIG. **10**, after the anchors **190** have passed through the skin **10**, the anchors **190** can return partially or fully toward the unstressed configuration (as shown, for example, in FIG. **9**) so as to deploy within the subcutaneous region **20**. For example, the subcutaneous region **20** may comprise fatty tissue in which the anchors **190** can move in a

13

sweeping arcuate motion away from the body 110'. Such deployment in the subcutaneous region 20 can releasably secure the sleeve device 400 to the patient's body for a period of time while the cuff 140 embeds with the surrounding tissue (as previously described). In this embodiment, the anchors 190 extend away from the outer wall 114' of the body 110' with a curvature so that the tips of the anchors 190 are not necessarily pointed at the underside of the skin 10. Such a configuration may be accomplished, for example, by inserting the anchors 190 further into the subcutaneous region 20 and then moving the anchors 190 with a slight pulling motion to permit the anchors 190 to sweep outwardly from the body 110'. It should be understood that, due to the vagaries of human anatomy and differing inward and outward forces during treatment, in some embodiments the orientation and position of the deployed anchors 190 may vary when deployed in the subcutaneous region 20. In some embodiments, the anchors 190 may provide a holding force of about 1 lb. or greater, depending upon the medical procedure being performed, the materials comprising the anchors 190, the geometry of the anchors 190, and/or other factors. For example, the anchors 190 may provide a holding force of about 0.5 lbs or more, about 1 lb to about 20 lbs, about 1 lb to about 5 lbs, or about 2 lbs to about 3 lbs.

In some embodiments, once the sleeve device 400 has been inserted through the skin 10, at least a portion of the body 110 may be located inside the subcutaneous region 20. In this example, the sleeve device 400 is inserted such that, for example, the distal tip portion 120, the cuff 140, and the anchors 190 are located inside the subcutaneous region 20, and the handle 192 remains external to the patient. Similar to previously described embodiments, the sleeve device 400 can be positioned such that the distal opening 204 is near to a blood vessel 30 and the proximal opening 202 is external to the patient so as to receive a catheter 300 (FIG. 8) or other medical instrument. As previously described in connection with FIG. 8, the distance between the cuff 140 and the catheter tip can be selectively adjusted depending on the patient's size, the patient's anatomy, the intended medical treatment, and other factors.

Still referring to FIG. 10, the sleeve device 400 may be removed by applying a removal force applied to the sleeve device 400 that overcomes the retainment force. In such circumstances, the anchors 190 may be flexed or deformed from their deployed configuration (as shown, for example, in FIG. 9) to a distally oriented configuration in which the anchors 190 extend substantially in a direction along the wall pockets 124 of the body 110. Such flexing action permits at least a portion of the anchors 190 to exit through the incision in the patient's skin with a reduced likelihood of traumatizing the skin around the incision. For example, the anchors 190 may have a curved configuration in which the tips do not point directly at the skin 10) when deployed in the subcutaneous region 20. As such, the removal force causes the anchors 190 to flex or deform (rather than substantially tear through the underside of the skin 10) in a generally sweeping motion toward the distally oriented configuration. In the embodiments in which the anchors 190 comprise a nitinol material exhibiting superelastic characteristics, the anchors 190 can return toward the unstressed configuration (as shown, for example in FIG. 10) following removal of the sleeve device 100 from the skin. In some alternative embodiments, the anchors 190 may comprise a biocompatible polymer material that can be elastically or plastically deformed into the distally oriented configuration as a result of the removal force applied to the sleeve device 100.

14

Referring to FIG. 11, some alternative embodiments of the sleeve device 410 may not include anchors 160 or 190. For example, the sleeve device 410 may be inserted through a hole in the patient's skin (as previously described) to a targeted position within the subcutaneous region 20. In such circumstances, the distal tip portion 120 and the cuff 140 can be located in the subcutaneous region, while the handle 192 remains external to the patient. The sleeve device 410 can be positioned such that the distal opening 204 is near to a blood vessel and the proximal opening 202 is external to the patient such that it can accept a catheter 300" or other medical instrument. Once in position, the sleeve device 410 may receive a temporary retainer (e.g., medical tape, stitches, or the like) to maintain the sleeve device 100 in a desired position for a period of time until the cuff 140 embeds with the surrounding tissue (as previously described) to thereby create a long-term anchor. In addition, the cuff 140 can provide a barrier to infection, as previously described.

In some embodiments, after placement of the sleeve 410 in a patient, a dual lumen catheter 300" with a staggered tip 304" can be introduced into the working channel 200 of the sleeve device 410. For example, the catheter 300" can be inserted into the proximal opening 202, and can continue to be advanced until it emerges from the distal tip portion 120. As with previously described embodiments, the tip-to-cuff distance 310 between the cuff 140 and the catheter tip 304" can be selectively adjusted by a practitioner while the catheter tip 304 is advanced in the patient's body.

Referring to FIG. 12, some alternative embodiments of the sleeve device 420 may employ the anchors 160 without the subcutaneous cuff device 140 arranged on the sleeve body 110. In such circumstances, the anchor sleeve device 420 may include the actuator 170 that adjust the anchors 160 from a non-deployed position (e.g., retracted inside the sleeve body 110) to the deployed position inside the subcutaneous region 20. As previously described in connection with FIG. 6B, the sleeve device 420 may include a locking device 174 that is shifted when the actuator 170 is moved to deploy the anchors 160. Although the subcutaneous cuff device 140 is not included on the body 110 in this particular embodiment, the anchors 160 can be deployed into the subcutaneous region to retain the sleeve device 420 to the patient's body while the catheter or other medical instrument is passed through the working channel 200 and into the targeted site in the patient's body. Thus, the user can readily operate the actuator 170 is a single motion that contemporaneously deploys the anchors 160 in the subcutaneous region and locks the sleeve body 110 to the catheter or other medical instrument. Furthermore, as previously described in connection with FIG. 6B, the locking device 174 can also form a seal around the catheter when compressed thereon. In such circumstances, the motion of the actuator 170 can cause the anchors 160 to deploy in the subcutaneous region and also cause the sleeve body 110 to lock with and seal around the catheter that resides in the working channel 200.

Referring now to FIGS. 13-14, particular embodiments of the sleeve device 100 may be particularly suited for use providing chronic dialysis treatment. For example, the sleeve device 100 (shown here as the embodiment described in connection with FIGS. 1-8) can be used as part of a system 6 for the placement of a dialysis catheter 320, which may be used to provide long-term hemodialysis treatment. In some patients requiring long-term hemodialysis, a dialysis catheter tip 322 can be positioned in the superior vena cava or right atrium to provide the inlet and outlet of the extracorporeal circuit. As such, the cuff 140 of the sleeve device 100 can embed with the tissue in the subcutaneous region near the skin

15

entry point so as to provide a barrier to infection. Because the path from the skin entry point (e.g., in the upper torso near the clavicle) to the targeted heart chamber 60 is not identical for all patient's, the system 6 advantageously permits the tip-to-cuff distance (e.g., the distance between the catheter tip 322 and the cuff 140) to be selectively adjusted by the practitioner during use.

In this example, a small incision 40 can be made in the upper torso (e.g., near the clavicle) through which the sleeve device 100 may be inserted and secured in the subcutaneous region as previously described. Similar to the embodiments described in connection with FIGS. 7-8, the sleeve device 100 may penetrate through the small incision and thereafter be advanced with the assistance of a dilation instrument. Once the sleeve device 100 has been inserted through the skin 10, at least a portion of the body 110 is located inside the subcutaneous region 20. In this example, the sleeve device 100 is inserted such that the distal tip portion 120, the cuff 140, and the anchor holes 112 are located inside the subcutaneous region 20 under the skin, and the actuator 170 and the stopper 180 remain external to the patient. The sleeve device 100 can be positioned such that the distal opening 204 is directed toward the jugular vein and the proximal opening 202 is external to the patient such that it can subsequently accept the catheter 320 or other medical instrument. Once the sleeve device 100 has been introduced, it can be anchored at least temporarily through the use of the deployed anchors 160. To deploy the anchors 160, the actuator 170 can be pulled back away from the stopper 180 (as previously described in connection with FIG. 8).

Still referring to FIG. 13, after the sleeve device 100 is at least temporarily secured in the subcutaneous region, the dialysis catheter 320 can be introduced through the working channel 200 (FIG. 8) of the sleeve device 100 and then directed toward the targeted heart chamber 60. In one example, the sleeve device 100 can be inserted into the subcutaneous layer through a skin insertion point in the chest near the clavicle. The dialysis catheter 320 can be advanced through the working channel 200 of the sleeve and into the subcutaneous region where it passes through a subcutaneous tunnel toward the jugular vein. An access needle (not shown in FIG. 13) can be used to create a venous entry 50 into the jugular vein approximately one to two centimeters above the clavicle. For instance, the Seldinger technique may be used to access the jugular vein followed by placement of a peel-away sheath. Thereafter, the tip portion 322 of the dialysis catheter 320 is advanced through the peel-away sheath at the venous entry point 50 and is directed into the targeted heart chamber 60 (e.g., the right atrium in this example) via the superior vena cava using, for example, ultrasound imaging or fluoroscopy guidance. The dialysis catheter 320 may include one or more markers along the catheter body to provide visualization using the medical imaging system. The peel-away sheath can be promptly removed and any skin opening in the neck (e.g., temporary skin opening for insertion of peel-away sheath) can be closed. The anchor sleeve device 100 can be secured in position on the patient's chest so as to provide long-term access for the dialysis catheter 320.

As previously described in connection with FIG. 8, the cuff 140 of the sleeve device 100 can embed with the surrounding tissue in the subcutaneous region so as to serve as a barrier to infection and to serve as a long-term anchor of the sleeve device 100. The anchors 160 can be deployed for a period of time so as to retain the sleeve device 100 in place while the cuff 140 receives the tissue ingrowth. When the cuff 140 is embedded with the tissue, the anchors 160 can be transitioned to the non-deployed position inside the body 110 by pushing

16

the actuator 170 in the direction of the stopper 180. Alternatively, the anchors 160 can be left in their deployed position in the subcutaneous layer 20 for the purpose of functioning as a supplemental anchoring feature.

Still referring to FIG. 13, catheter tip 322 can be advanced toward the targeted heart chamber 60 while the sleeve device 100 and cuff 140 remain generally stationary relative to the skin entry point. Accordingly, the distance between the cuff 140 and the catheter tip 322 (e.g., the tip-to-cuff distance) can be selectively adjusted depending on the patient's size, the patient's anatomy, the intended medical treatment, and other factors. As previously described, the tip-to-cuff distance can be advantageously selected by the practitioner while the catheter tip 322 is advanced through the patient's body. Also, the tip-to-cuff distance is adjustable at the time of insertion, so this distance need not be determined prior to the start of the procedure. Furthermore, this system 6 having the adjustable tip-to-cuff distance can reduce the need for hospitals or clinics to inventory a wide assortment of cuff-attached catheters, each having a non-adjustable tip-to-cuff length.

Referring now to FIG. 14, the dual lumen tip 322 of the dialysis catheter 320 can be arranged the right atrium 60 of the heart. After the final position of the tip 322 is verified using a medical imaging system, the dialysis catheter 320 can be used to perform the dialysis treatment. For example, the dialysis catheter 320 may include dual lumens that extend to distal ports at the staggered tip 322. In one embodiment, the staggered ports at the tip 322 may be separated by a distance of approximately one or two centimeters. The staggered position of these ports may facilitate the dialysis procedure. For example, a first port in the catheter tip 322 may be used to suction blood from the heart chamber 60 and into the extracorporeal circuit (not shown in FIGS. 13-14), and a second opening in the catheter tip 322 can be used to return the blood into the heart chamber. It should be understood that, in some embodiments, the sleeve device 100, 400, 410, or 420 described herein can be used with other medical instruments and can be used for treatments other than dialysis. For example, the sleeve device 100, 400, 410, or 420 can be used in combination with one or more Hickman catheters for delivery of chemotherapy treatment. The Hickman catheters may comprise single-lumen, double-lumen, or triple-lumen elongate bodies than can pass through one or more working channels of the sleeve device 100, 400, 410, or 420. In another example, the sleeve device 100, 400, 410, or 420 can be used in combination with at least one tunnel chest tube that is used to drain fluids from the lung cavity of the patient. In such circumstances, the sleeve device 100, 400, 410, or 420 can be retained in the subcutaneous region while the tunnel chest tube penetrates into the lung cavity (e.g., not necessarily into an artery or vein or the patient).

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A method of delivering a catheter device to an internal body site, comprising:  
 advancing an anchor sleeve through a percutaneous opening in a skin layer so that a subcutaneous cuff device arranged along an outer surface of the anchor sleeve is disposed in a subcutaneous region along an underside of the skin layer, the subcutaneous cuff device comprising a biocompatible material that receives tissue ingrowth when disposed in the subcutaneous region along the underside of the skin layer;

17

advancing a catheter device through a working channel of the anchor sleeve and toward a targeted body site such that a distal catheter tip is moved relative to the subcutaneous cuff device disposed in the subcutaneous region along the underside of the skin layer, wherein the distance from the subcutaneous cuff device to the distal catheter tip defining a cuff-to-tip distance;

adjusting the cuff-to-tip distance by moving the catheter device relative to the anchor sleeve while the subcutaneous cuff device is disposed in the subcutaneous region along the underside of the skin layer; and

releasably affixing the catheter device in the working channel by compressing a cylindrical surface portion of the anchor sleeve upon at least a portion of an outer circumferential surface of the catheter device so that the portion of the outer circumferential surface of catheter device is retained in a fixed relation to the anchor sleeve.

2. The method of claim 1, wherein the step of releasable affixing comprises actuating a locking device to releasably affixes the catheter device to the anchor sleeve when the catheter device reaches the targeted body site.

3. The method of claim 2, further comprising shifting one or more flexible anchors from a non-deployed orientation to a deployed orientation contemporaneously with the actuation of the locking device.

4. A method of delivering a catheter device to an internal body site, comprising:

advancing an anchor sleeve through a percutaneous opening in a skin layer so that a subcutaneous cuff device arranged along an outer surface of the anchor sleeve is disposed in a subcutaneous region along an underside of the skin layer, the subcutaneous cuff device comprising a biocompatible material that receives tissue ingrowth when disposed in the subcutaneous region along the underside of the skin layer;

advancing a catheter device through a working channel of the anchor sleeve and toward a targeted body site such that a distal catheter tip is moved relative to the subcutaneous cuff device disposed in the subcutaneous region along the underside of the skin layer, wherein the distance from the subcutaneous cuff device to the distal catheter tip defining a cuff-to-tip distance;

adjusting the cuff-to-tip distance by moving the catheter device relative to the anchor sleeve while the subcutaneous cuff device is disposed in the subcutaneous region along the underside of the skin layer;

actuating a locking device to releasably affixes the catheter device to the anchor sleeve when the catheter device reaches the targeted body site; and

shifting one or more flexible anchors from a non-deployed orientation to a deployed orientation contemporaneously with the actuation of the locking device, wherein the anchor sleeve comprises a main body and an actuator that is adjustable relative to the main body from a first position to a second position so as to simultaneously shift the flexible anchors to the deployed orientation and shift the locking device to compress at least a portion of an outer surface of the catheter device.

5. The method of claim 1, wherein the catheter device defines at least one lumen that extends to the distal catheter tip.

6. The method of claim 1, further comprising shifting first and second flexible curved anchors from a non-deployed orientation to a deployed orientation in the subcutaneous region along the underside of the skin layer.

7. The method of claim 6, wherein the subcutaneous cuff device is arranged along the outer surface of the anchor sleeve

18

at a position distally of the first and second flexible curved anchors while both the subcutaneous cuff device and the flexible curved anchors are deployed orientation in the subcutaneous region along the underside of the skin layer.

8. The method of claim 1, wherein the subcutaneous cuff device inhibits migration of infection when the cuff device is embedded in the subcutaneous region along the underside of the skin layer.

9. The method of claim 8, wherein the subcutaneous cuff device receives the ingrowth of bodily tissue over a period of time so as to inhibit the migration of infection from outside the skin and into the blood stream.

10. A method of delivering a catheter device to an internal body site, comprising:

advancing at least a portion of an anchor device through a percutaneous opening in a skin layer so that a subcutaneous cuff device arranged mounted to the anchor device is disposed in a subcutaneous region along an underside of the skin layer, the subcutaneous cuff device comprising a biocompatible material that receives tissue ingrowth when disposed in the subcutaneous region along the underside of the skin layer;

advancing a catheter device relative to a lockable portion of the anchor device and toward a targeted body site such that a distal catheter tip is moved relative to the subcutaneous cuff device disposed in the subcutaneous region along the underside of the skin layer, wherein the lockable portion of the anchor device is movable to secure with the catheter device, wherein the distance from the subcutaneous cuff device to the distal catheter tip defining a cuff-to-tip distance;

adjusting the cuff-to-tip distance by moving the catheter device relative to the anchor sleeve while the subcutaneous cuff device is disposed in the subcutaneous region along the underside of the skin layer; and

releasably securing the catheter device to the anchor device by compressing the lockable portion of the anchor device against at least a portion of an outer circumferential surface of the catheter device.

11. The method of claim 10, wherein securing the catheter device to the anchor device comprises moving the lockable portion of the anchor device to releasably secure the portion of the outer circumferential surface of the catheter device in a fixed relation to the anchor device after the catheter device is advanced to the targeted body site.

12. The method of claim 11, further comprising shifting one or more flexible anchors from a non-deployed orientation to a deployed orientation contemporaneously with the step of moving the lockable portion of the anchor device.

13. The method of claim 12, wherein the anchor device comprises a main body and an actuator that is adjustable relative to the main body from a first position to a second position so as to simultaneously shift the flexible anchors to the deployed orientation and shift the lockable portion to compress the outer surface of the catheter device.

14. The method of claim 10, wherein the catheter device defines at least one lumen that extends to the distal catheter tip.

15. The method of claim 10, further comprising shifting first and second flexible curved anchors of the anchor device from a non-deployed orientation to a deployed orientation in the subcutaneous region along the underside of the skin layer.

16. The method of claim 15, wherein the subcutaneous cuff device is mounted to the anchor device at a position distally of the first and second flexible curved anchors while both the

**19**

subcutaneous cuff device and the flexible curved anchors are deployed orientation in the subcutaneous region along the underside of the skin layer.

17. The method of claim 10, wherein the subcutaneous cuff device inhibits migration of infection when the cuff device is embedded in the subcutaneous region along the underside of the skin layer.

18. The method of claim 17, wherein the subcutaneous cuff device receives the ingrowth of bodily tissue over a period of time so as to inhibit the migration of infection from outside the skin and into the blood stream.

**20**

19. The method of claim 4, wherein the catheter device defines at least one lumen that extends to the distal catheter tip.

20. The method of claim 4, wherein the step of shifting one or more flexible anchors from the non-deployed orientation to the deployed orientation comprises positioning the flexible anchors in the deployed orientation in the subcutaneous region along the underside of the skin layer.

\* \* \* \* \*