




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>7</sup> : <b>F21V 7/04</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 00/50807</b></p> <p>(43) International Publication Date: 31 August 2000 (31.08.00)</p>
<p>(21) International Application Number: PCT/US00/04499</p> <p>(22) International Filing Date: 23 February 2000 (23.02.00)</p> <p>(30) Priority Data: 09/256,275                      23 February 1999 (23.02.99)                      US</p> <p>(71) Applicant (for all designated States except US): LUMITEX, INC. [US/US]; 8443 Dow Circle, Strongsville, OH 44136 (US).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): PARKER, Jeffery, R. [US/US]; 14389 Placid Cove Drive, Strongsville, OH 44136 (US). COGHLAN, Gregory, A. [US/US]; 7744 Maple Way Drive, Olmsted Falls, OH 44138 (US). EZELL, Robert, M. [US/US]; 1217 Jacoby Road, Copley, OH 44321 (US).</p> <p>(74) Agent: OTTO, Donald, D.; Renner, Otto, Boisselle &amp; Sklar, Llp, 1621 Euclid Avenue, 19th Floor, Cleveland, OH 44115 (US).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report.</p>

(54) Title: LIGHT EMITTING PANEL ASSEMBLIES



## (57) Abstract

Light emitting panel assemblies include a light emitting panel member (22) having a uniform or variable pattern of light extracting deformities (109) of well defined shapes in or on one or more surfaces of the light emitting panel (22). The size and shape as well as the depth and angular orientation and position or location of the light emitting of the light extracting deformities (109) may vary along the length and/or width of a panel surface area to obtain a desired light output distribution from the panel surface area. A focused light source (3) may be insert molded or cast within a light transition area of the light emitting panel to focus the light on an input surface of the light transition area with predetermined ray angles to fit a particular application. Molded supports may be provided on the panel member for supporting other parts or components in spaced relation therefrom.

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**TITLE: LIGHT EMITTING PANEL ASSEMBLIES**

5

**BACKGROUND OF THE INVENTION**

This invention relates generally, as indicated, to light emitting panel assemblies.

10

Light emitting panel assemblies are generally known. However, the present invention relates to several different light emitting panel assembly configurations which provide for better control of the light output from the panel assemblies and more efficient utilization of light to suit a particular application.

15

**SUMMARY OF THE INVENTION**

In accordance with one aspect of the invention, the light emitting panel assemblies include a light emitting panel member having a pattern of individual light extracting deformities of well defined shapes on or in one or more surface areas of the light emitting panel member.

20

In accordance with another aspect of the invention, each of the light extracting deformities includes a reflective or refractive surface of a predetermined slope for more precisely controlling the emission of light by each of said deformities.

25

In accordance with another aspect of the invention, each of the light extracting deformities has an end wall that produces a relatively small projected surface area on the panel surface area to allow the number of deformities on or in the panel surface areas to be increased.

30

In accordance with another aspect of the invention, the light extracting deformities have straight side walls.

In accordance with another aspect of the invention, the light extracting deformities have rounded side walls.

In accordance with another aspect of the invention, the light extracting deformities have planar surfaces in parallel spaced relation to the panel surface areas.

5 In accordance with another aspect of the invention, the panel member is transparent and includes one or more panel portions having opposite sides that are free of any reflective material, whereby light is free to pass through such opposite sides.

10 In accordance with another aspect of the invention, deformities on or in one or more of the panel portions are shaped to cause more of the light entering the panel member through an input edge to be emitted from one of the sides of the panel portions than the other side.

15 In accordance with another aspect of the invention, the one side of the panel portion through which more of the light is emitted may be placed in close proximity to a front face of a display for front lighting the display.

In accordance with another aspect of the invention, the light emitting deformities have planar surfaces through which light from the display passes with minimal optical distortion.

20 In accordance with another aspect of the invention, the pattern of light extracting deformities may be uniform or variable as desired to obtain a desired light output distribution from the panel surface areas.

25 In accordance with another aspect of the invention, the size and shape as well as the depth or height and angular orientation and location of the light extracting deformities may vary along the length and/or width of any given panel surface area to obtain a desired light output distribution from the panel member.

In accordance with yet another aspect of the invention, a focused light source may be insert molded or cast within a light transition area of the light emitting panel member.

In accordance with still another aspect of the invention, molded supports may be provided on the panel member for supporting other parts or components in spaced relation from the panel member.

5 In accordance with another aspect of the invention, an array of light sources may be mounted on a printed circuit board for directing light through a diffuser or lens mounted in spaced relation to the light sources for use in phototherapy treatment and the like.

10 The various light emitting panel assemblies of the present invention are relatively efficient panel assemblies that may be used to produce increased uniformity and higher light output from the panel members with lower power requirements, and allow the panel members to be made thinner and/or longer, and/or of various shapes and sizes.

15 To the accomplishment of the foregoing and related ends, the invention then comprises the features hereinafter fully described and particularly pointed out in the claims, the following description and the annexed drawings setting forth in detail certain illustrative embodiments of the invention, these being indicative, however, of but several of the various ways in which the principles of the invention may be employed.

## 20 BRIEF DESCRIPTION OF THE DRAWINGS

In the annexed drawings:

Figs. 1 through 3 are schematic perspective views of three different forms of light emitting panel assemblies in accordance with this invention;

25 Fig. 4a is an enlarged plan view of a portion of a light output area of a panel assembly showing one form of pattern of light extracting deformities on the light output area;

30 Figs. 4b, c and d are enlarged schematic perspective views of a portion of a light output area of a panel assembly showing other forms of light extracting deformities formed in or on the light output area;

Fig. 5 is an enlarged transverse section through the light emitting panel assembly of Fig. 3 taken generally on the plane of the line 5-5 thereof;

Fig. 6 is a schematic perspective view of another form of light emitting panel assembly in accordance with this invention;

Fig. 7 is a schematic top plan view of another form of light emitting panel assembly in accordance with this invention;

Fig. 8 is a schematic perspective view of another form of light emitting panel assembly in accordance with this invention;

Fig. 9 is a schematic top plan view of another form of light emitting panel assembly in accordance with this invention;

Fig. 10 is a schematic top plan view of still another form of light emitting panel assembly in accordance with this invention;

Fig. 11 is a side elevation view of the light emitting panel assembly of Fig. 10;

Fig. 11a is a fragmentary side elevation view showing a tapered or rounded end on the panel member in place of the prismatic surface shown in Figs. 10 and 11;

Fig. 12 is a schematic top plan view of another form of light emitting panel assembly in accordance with this invention;

Fig. 13 is a schematic side elevation view of the light emitting panel assembly of Fig. 12;

Figs. 14 and 15 are schematic perspective views of still other forms of light emitting panel assemblies in accordance with this invention;

Figs. 16 and 17 are enlarged schematic fragmentary plan views of a surface area of a light panel assembly showing still other forms of light extracting deformities in accordance with this invention formed on or in a surface of the panel member;

Figs. 18 and 19 are enlarged longitudinal sections through one of the light extracting deformities of Figs. 16 and 17, respectively;

5 Figs. 20 and 21 are enlarged schematic longitudinal sections through light extracting deformities similar to Figs. 18 and 19, respectively, except that the deformity end walls are shown extending substantially perpendicular to the panel surface instead of perpendicular to their respective reflective/refractive surfaces as shown in Figs. 18 and 19;

10 Figs. 22 through 30 are enlarged schematic perspective views of panel surface areas containing various patterns of individual light extracting deformities of other well defined shapes in accordance with this invention;

Fig. 31 is an enlarged schematic longitudinal section through another form of light extracting deformity in accordance with this invention;

15 Figs. 32 and 33 are enlarged schematic top plan views of panel surface areas containing light extracting deformities similar in shape to those shown in Figs. 28 and 29 arranged in a plurality of straight rows along the length and width of the panel surface area;

20 Figs. 34 and 35 are enlarged schematic top plan views of panel surface areas containing light extracting deformities also similar in shape to those shown in Figs. 28 and 29 arranged in staggered rows along the length of the panel surface areas;

Figs. 36 and 37 are enlarged schematic top plan views of panel surface areas containing a random or variable pattern of different sized light emitting deformities on the panel surface areas;

25 Fig. 38 is an enlarged schematic perspective view of a panel surface area showing light extracting deformities in accordance with this invention increasing in size as the distance of the deformities from the light source increases or intensity of the light increases along the length of the panel surface area;

Figs. 39 and 40 are schematic perspective views showing different angular orientations of the light extracting deformities along the length and width of a panel surface area;

5 Figs. 41 and 42 are enlarged perspective views schematically showing how exemplary light rays emitted from a focused light source are reflected or refracted by different individual light extracting deformities of well defined shapes in accordance with this invention;

10 Fig. 43 is a schematic perspective view showing a light emitting panel assembly similar to Fig. 42 placed on a front face of a display to provide front lighting for the display;

Fig. 44 is a schematic top plan view of another form of light emitting panel assembly in accordance with this invention for use in phototherapy treatment and the like; and

15 Figs. 45 through 47 are schematic side elevation views of still other forms of light emitting panel assemblies in accordance with this invention for use in phototherapy treatment and the like.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

20 Referring now in detail to the drawings, and initially to Fig. 1, there is schematically shown one form of light emitting panel assembly 1 in accordance with this invention including a transparent light emitting panel 2 and one or more light sources 3 which emit light in a predetermined pattern in a light transition member or area 4 used to make the transition from the light source 3 to the light emitting panel 2, as well known in the art. The light that is transmitted by the light transition area 4 to the  
25 transparent light emitting panel 2 may be emitted along the entire length of the panel or from one or more light output areas along the length of the panel as desired to produce a desired light output distribution to fit a particular application.

30 In Fig. 1 the light transition area 4 is shown as an integral extension of one end of the light emitting panel 2 and as being generally



rectangular in shape. However, the light transition area may be of other shapes suitable for embedding, potting, bonding or otherwise mounting the light source. Also, reflective or refractive surfaces may be provided to increase efficiency. Moreover, the light transition area 4 may be a  
5 separate piece suitably attached to the light input surface 13 of the panel member if desired. Also, the sides of the light transition area may be curved to more efficiently reflect or refract a portion of the light emitted from the light source through the light emitting panel at an acceptable angle.

10 Fig. 2 shows another form of light emitting panel assembly 5 in accordance with this invention including a panel light transition area 6 at one end of the light emitting panel 7 with sides 8, 9 around and behind the light source 3 shaped to more efficiently reflect and/or refract and focus the light emitted from the light source 3 that impinges on these  
15 surfaces back through the light transition area 6 at an acceptable angle for entering the light input surface 18 at one end of the light emitting panel 7. Also, a suitable reflective material or coating 10 may be provided on the portions of the sides of the light transition areas of the panel assemblies of Figs. 1 and 2 on which a portion of the light  
20 impinges for maximizing the amount of light or otherwise changing the light that is reflected back through the light transition areas and into the light emitting panels.

The panel assemblies shown in Figs. 1 and 2 include a single light source 3, whereas Fig. 3 shows another light emitting panel assembly 11  
25 in accordance with this invention including two light sources 3. Of course, it will be appreciated that the panel assemblies of the present invention may be provided with any number of light sources as desired, depending on the particular application.

30 The panel assembly 11 of Fig. 3 includes a light transition area 12 at one end of the light emitting panel 14 having reflective and/or refractive surfaces 15 around and behind each light source 3. These

surfaces 15 may be appropriately shaped including for example curved, straight and/or faceted surfaces, and if desired, suitable reflective materials or coatings may be provided on portions of these surfaces to more efficiently reflect and/or refract and focus a portion of the light emitted for example from an incandescent light source which emits light in a 360° pattern through the light transition areas 12 into the light input surface 19 of the light emitting panel 14.

The light sources 3 may be mechanically held in any suitable manner in slots, cavities or openings 16 machined, molded or otherwise formed in the light transition areas of the panel assemblies. However, preferably the light sources 3 are embedded, potted or bonded in the light transition areas in order to eliminate any air gaps or air interface surfaces between the light sources and surrounding light transition areas, thereby reducing light loss and increasing the light output emitted by the light emitting panels. Such mounting of the light sources may be accomplished, for example, by bonding the light sources 3 in the slots, cavities or openings 16 in the light transition areas using a sufficient quantity of a suitable embedding, potting or bonding material 17. The slots, cavities or openings 16 may be on the top, bottom, sides or back of the light transition areas. Bonding can also be accomplished by a variety of methods that do not incorporate extra material, for example, thermal bonding, heat staking, ultrasonic or plastic welding or the like. Other methods of bonding include insert molding and casting around the light source(s).

A transparent light emitting material of any suitable type, for example acrylic or polycarbonate, may be used for the light emitting panels. Also, the panels may be substantially flat, or curved, may be a single layer or multi-layers, and may have different thicknesses and shapes. Moreover, the panels may be flexible, or rigid, and may be made out of a variety of compounds. Further, the panels may be hollow, filled with liquid, air, or be solid, and may have holes or ridges in the panels.

Each light source 3 may also be of any suitable type including, for example, any of the types disclosed in U.S. Patent Nos. 4,897,771 and 5,005,108, assigned to the same assignee as the present application, the entire disclosures of which are incorporated herein by reference. In particular, the light sources 3 may be an arc lamp, an incandescent bulb which also may be colored, filtered or painted, a lens end bulb, a line light, a halogen lamp, a light emitting diode (LED), a chip from an LED, a neon bulb, a fluorescent tube, a fiber optic light pipe transmitting from a remote source, a laser or laser diode, or any other suitable light source. Additionally, the light sources 3 may be a multiple colored LED, or a combination of multiple colored radiation sources in order to provide a desired colored or white light output distribution. For example, a plurality of colored lights such as LEDs of different colors (red, blue, green) or a single LED with multiple colored chips may be employed to create white light or any other colored light output distribution by varying the intensities of each individual colored light.

A pattern of light extracting deformities or disruptions may be provided on one or both sides of the panel members or on one or more selected areas on one or both sides of the panel members, as desired. Fig. 4a schematically shows one such light surface area 20 on which a pattern of light extracting deformities or disruptions 21 is provided. As used herein, the term deformities or disruptions are used interchangeably to mean any change in the shape or geometry of the panel surface and/or coating or surface treatment that causes a portion of the light to be emitted. The pattern of light extracting deformities 21 shown in Fig. 4a includes a variable pattern which breaks up the light rays such that the internal angle of reflection of a portion of the light rays will be great enough to cause the light rays either to be emitted out of the panel through the side or sides on which the light extracting deformities 21 are provided or reflected back through the panel and emitted out the other side.

5 These deformities or disruptions 21 can be produced in a variety of  
manners, for example, by providing a painted pattern, an etched pattern,  
a machined pattern, a printed pattern, a hot stamped pattern, or a  
molded pattern or the like on selected light output areas of the panel  
members. An ink or printed pattern may be applied for example by pad  
printing, silk screening, ink jet, heat transfer film process or the like. The  
deformities may also be printed on a sheet or film which is used to apply  
the deformities to the panel member. This sheet or film may become a  
permanent part of the light panel assembly for example by attaching or  
10 otherwise positioning the sheet or film against one or both sides of the  
panel member similar to the sheet or film 27 shown in Figs. 3 and 5 in  
order to produce a desired effect.

15 By varying the density, opaqueness or translucence, shape, depth,  
color, area, index of refraction, or type of deformities 21 on an area or  
areas of the panels, the light output of the panels can be controlled. The  
deformities or disruptions may be used to control the percent of light  
emitted from any area of the panels. For example, less and/or smaller  
size deformities 21 may be placed on panel areas where less light output  
is wanted. Conversely, a greater percentage of and/or larger deformities  
20 may be placed on areas of the panels where greater light output is  
desired.

25 Varying the percentages and/or size of deformities in different  
areas of the panel is necessary in order to provide a uniform light output  
distribution. For example, the amount of light traveling through the  
panels will ordinarily be greater in areas closer to the light source than in  
other areas further removed from the light source. A pattern of light  
extracting deformities 21 may be used to adjust for the light variances  
within the panel members, for example, by providing a denser  
concentration of light extracting deformities with increased distance from  
30 the light source 3 thereby resulting in a more uniform light output  
distribution from the light emitting panels.

The deformities 21 may also be used to control the output ray angle distribution of the emitted light to suit a particular application. For example, if the panel assemblies are used to provide a liquid crystal display back light, the light output will be more efficient if the deformities 21 cause the light rays to emit from the panels at predetermined ray angles such that they will pass through the liquid crystal display with low loss.

Additionally, the pattern of light extracting deformities may be used to adjust for light output variances attributed to light extractions of the panel members. The pattern of light extracting deformities 21 may be printed on the light output areas utilizing a wide spectrum of paints, inks, coatings, epoxies, or the like, ranging from glossy to opaque or both, and may employ half-tone separation techniques to vary the deformity 21 coverage. Moreover, the pattern of light extracting deformities 21 may be multiple layers or vary in index of refraction.

Print patterns of light extracting deformities 21 may vary in shapes such as dots, squares, diamonds, ellipses, stars, random shapes, and the like, and are desirably .006 square inch per deformity/element or less. Also, print patterns that are 60 lines per inch or finer are desirably employed, thus making the deformities or shapes 21 in the print patterns nearly invisible to the human eye in a particular application thereby eliminating the detection of gradient or banding lines that are common to light extracting patterns utilizing larger elements. Additionally, the deformities may vary in shape and/or size along the length and/or width of the panel members. Also, a random placement pattern of the deformities may be utilized throughout the length and/or width of the panel members. The deformities may have shapes or a pattern with no specific angles to reduce moire or other interference effects. Examples of methods to create these random patterns are printing a pattern of shapes using stochastic print pattern techniques, frequency modulated half tone patterns, or random dot half tones. Moreover, the deformities

may be colored in order to effect color correction in the panel members. The color of the deformities may also vary throughout the panel members, for example to provide different colors for the same or different light output areas.

5 In addition to or in lieu of the patterns of light extracting deformities 21 shown in Fig. 4a, other light extracting deformities including prismatic surfaces, depressions or raised surfaces of various shapes using more complex shapes in a mold pattern may be molded, etched, stamped, thermoformed, hot stamped or the like into or on one  
10 or more areas of the panel member. Figs. 4b and 4c show panel areas 22 on which prismatic surfaces 23 or depressions 24 are formed in the panel areas, whereas Fig. 4d shows prismatic or other reflective or refractive surfaces 25 formed on the exterior of the panel area. The prismatic surfaces, depressions or raised surfaces will cause a portion of  
15 the light rays contacted thereby to be emitted from the panel member. Also, the angles of the prisms, depressions or other surfaces may be varied to direct the light in different directions to produce a desired light output distribution or effect. Moreover, the reflective or refractive surfaces may have shapes or a pattern with no specific angles to reduce  
20 moire or other interference effects.

As best seen in the cross sectional view of Fig. 5, a back reflector (including trans reflectors) 26 may be attached or positioned against one side of the panel member 14 of Fig. 3 using a suitable adhesive 28 or other method in order to improve light output efficiency of the panel  
25 assembly 11 by reflecting the light emitted from that side back through the panel for emission through the opposite side. Additionally, a pattern of light extracting deformities 21, 23, 24 and/or 25 may be provided on one or both sides of the panel member in order to change the path of the light so that the internal critical angle is exceeded and a portion of the  
30 light is emitted from one or both sides of the panel. Moreover, a transparent film, sheet or plate 27 may be attached or positioned against

the side or sides of the panel member from which light is emitted using a suitable adhesive 28 or other method in order to produce a desired effect.

5 The member 27 may be used to further improve the uniformity of the light output distribution. For example, the member 27 may be a colored film, a diffuser, or a label or display, a portion of which may be a transparent overlay that may be colored and/or have text or an image thereon.

10 If adhesive 28 is used to adhere the back reflector 26 and/or film 27 to the panel, the adhesive is preferably applied only along the side edges of the panel, and if desired the end edge opposite the light transition areas 12, but not over the entire surface area or areas of the panel because of the difficulty in consistently applying a uniform coating of adhesive to the panel. Also, the adhesive changes the internal critical angle of the light in a less controllable manner than the air gaps 30 (see 15 Fig. 5) which are formed between the respective panel surfaces and the back reflector 26 and/or film 27 when only adhered along the peripheral edges. Additionally, longer panel members are achievable when air gaps 30 are used. If adhesive were to be used over the entire surface, the 20 pattern of deformities could be adjusted to account for the additional attenuation in the light caused by the adhesive.

25 Referring further to Fig. 2, the panel assembly 5 shown therein also includes molded posts 31 at one or more corners of the panel 7 (four such posts being shown) which may be used to facilitate mounting of the panel assembly and providing structural support for other parts or components, for example, a display panel such as a liquid crystal display panel as desired.

30 Fig. 6 shows another form of light emitting panel assembly 32 in accordance with this invention including a panel member 33, one or more light sources 3, and one or more light output areas 34. In addition, the panel assembly 32 includes a tray 35 having a cavity or recess 36 in

which the panel assembly 32 is received. The tray 35 may act as a back reflector as well as end edge and/or side edge reflectors for the panel 33 and side and/or back reflectors 37 for the light sources 3. Additionally, one or more secondary reflective or refractive surfaces 38 may be provided on the panel member 33 and/or tray 35 to reflect a portion of the light around one or more corners or curves in a non-rectangular shaped panel member 33. These secondary reflective/refractive surfaces 38 may be flat, angled, faceted or curved, and may be used to extract a portion of the light away from the panel member in a predetermined pattern. Fig. 6 also shows multiple light output areas 34 on the panel member that emit light from one or more light sources 3.

Fig. 7 is a schematic illustration of still another form of light emitting panel assembly 40 in accordance with this invention including a panel member 41 having one or more light output areas 42 and one or more light transition areas (mixing areas) 43 containing a plurality of light sources 3 at one or both ends of the panel. Each transition area mixes the light from one or more light sources having different colors and/or intensities. In this particular embodiment, each of the light sources 3 desirably employs three colored LEDs (red, blue, green) in each transition mixing area 43 so that the light from the three LEDs can be mixed to produce a desired light output color that will be emitted from the light output area 42. Alternatively, each light source may be a single LED having multiple colored chips bonded to the lead film. Also, two colored LEDs or a single LED having two colored chips may be used for a particular application. By varying the intensities of the individual respective LEDs, virtually any colored light output or white light distribution can be achieved.

Fig. 8 shows yet another form of light emitting panel assembly 45 in accordance with this invention including a light emitting panel member 46 and a light source 3 in a light transition area 48 integral with one end of the panel member. In this particular embodiment, the panel member



46 is three-dimensionally curved, for example, such that light rays may be emitted in a manner that facilitates aesthetic design of a lighted display.

5 Fig. 9 schematically shows another form of light emitting panel assembly 50 in accordance with this invention, including a panel member 51 having multiple light output areas 52, and mounting posts and/or mounting tabs 53. This particular panel assembly 50 may serve as a structural member to support other parts or components as by providing  
10 holes or cavities 54, 55 in the panel member 51 which allow for the insertion of modular components or other parts into the panel member. Moreover, a separate cavity or recess 56 may be provided in the panel member 51 for receipt of a correspondingly shaped light transition area 57 having one or more light sources 3 embedded, bonded, cast, insert  
15 molded, epoxied, or otherwise mounted or positioned therein and a curved reflective or refractive surface 58 on the transition area 57 and/or wall of the cavity or recess 56 to redirect a portion of the light in a predetermined manner. In this way the light transition area 57 and/or panel member may be in the form of a separate insert which facilitates the easy placement of the light source in a modular manner. A reflector  
20 58 may be placed on the reflective or refractive surface of the cavity or recess 56 or insert 57. Where the reflector 58 is placed on the reflective or refractive surface of the cavity or recess 56, the cavity or recess may act as a mold permitting transparent material from which the transition area 57 is made to be cast around one or more light sources 3.

25 Figs. 10 and 11 schematically show another form of light emitting panel assembly 60 in accordance with this invention including a panel member 61 having one or more light output areas 62. In this particular embodiment, an off-axis light transition area 63 is provided that is thicker in cross section than the panel member to permit use of one or more light  
30 sources 3 embedded or otherwise mounted in the light transition area that are dimensionally thicker than the panel member. Also, a three-

dimensional reflective surface 64 (Fig. 11) may be provided on the transition area 63. Moreover, a prism 65 (Fig. 11) or tapered, rounded, or otherwise shaped end 66 (Fig. 11a) may be provided at the end of the panel opposite the light sources 3 to perform the function of an end reflector. The light sources 3 may be oriented at different angles relative to each other and offset to facilitate better mixing of the light rays 67 in the transition area 63 as schematically shown in Fig. 10 and/or to permit a shorter length transition area 63 to be used.

Figs. 12 and 13 schematically show still another form of light emitting panel assembly 70 in accordance with this invention which includes one or more light transition areas 71 at one or both ends of the panel member 72 each containing a single light source 73. The transition area or areas 71 shown in Figs. 12 and 13 collect light with multiple or three-dimensional surfaces and/or collect light in more than one plane. For example each transition area 71 shown in Figs. 12 and 13 has elliptical and parabolic shape surfaces 74 and 75 in different planes for directing the light rays 76 into the panel member at a desired angle.

Providing one or more transition areas at one or both ends of the panel member of any desired dimension to accommodate one or more light sources, with reflective and/or refractive surfaces on the transition areas for redirecting the light rays into the panel member at relatively low angles allows the light emitting panel member to be made much longer and thinner than would otherwise be possible. For example the panel members of the present invention may be made very thin, *i.e.*, 0.125 inch thick or less.

Fig. 14 schematically illustrates still another form of light emitting panel assembly 80 in accordance with this invention including a light emitting panel 81 and one or more light sources 3 positioned, embedded, potted, bonded or otherwise mounted in a light transition area 82 that is at an angle relative to the panel member 81 to permit more efficient use of space. An angled or curved reflective or refractive surface 83 is

provided at the junction of the panel member 81 with the transition area 82 in order to reflect/refract light from the light source 3 into the body of the panel member 81 for emission of light from one or more light emitting areas 84 along the length of the panel member.

5 Fig. 15 schematically illustrates still another form of light emitting panel assembly 90 in accordance with this invention including a light transition area 91 at one or both ends of a light emitting panel member 92 containing a slot 93 for sliding receipt of an LED or other suitable light source 3. Preferably the slot 93 extends into the transition area 91 from  
10 the back edge 94, whereby the light source 3 may be slid and/or snapped in place in the slot from the back, thus allowing the transition area to be made shorter and/or thinner. The light source 3 may be provided with wings, tabs or other surfaces 95 for engagement in correspondingly shaped recesses or grooves 96 or the like in the transition area 91 for  
15 locating and, if desired, securing the light source in place. Also, the light source 3 may be embedded, potted, bonded or otherwise secured within the slot 93 in the light transition area 91 of the panel member 92. Light from a secondary light source 97 may be projected through the panel member 92 for indication or some other effect.

20 Fig. 16 through 19 show other light extracting deformities 98 in accordance with this invention which may either be individual projections 99 on the respective panel surface areas 22 or individual depressions 100 in such panel surface areas. In either case, the light extracting deformities 98 differ from the light extracting deformities shown in Figs.  
25 4a, 4b, 4c and 4d in that each of the deformities 98 has a well defined shape including a reflective or refractive surface 101 that intersects the respective panel surface area 22 at one edge 102 and has a uniform slope throughout its length for more precisely controlling the emission of light by each of the deformities. Along a peripheral edge portion 103 of each reflective/refractive surface 101 is an end wall 104 of each  
30 deformity 98 that intersects the respective panel surface area at a

greater included angle  $\alpha$  than the included angle  $\alpha'$  between the reflective/refractive surfaces 101 and the panel surface area 22 (see Figs. 18 and 19) to minimize the projected surface area of the end walls on the panel surface area. This allows more deformities 98 to be placed  
5 on or in the panel surface areas than would otherwise be possible if the projected surface areas of the end walls 104 were substantially the same as or greater than the projected surface areas of the reflective/refractive surfaces 101.

In Figs. 16 and 17 the peripheral edge portions 103 of the reflective/refractive surfaces 101 and associated end walls 104 are  
10 curved in the transverse direction. Also, in Figs. 18 and 19 the end walls 104 of the deformities 98 are shown extending substantially perpendicular to the reflective/refractive surfaces 101 of the deformities. Alternatively, such end walls 104 may extend substantially perpendicular  
15 to the panel surface areas 22 as schematically shown in Figs. 20 and 21. This virtually eliminates any projected surface area of the end walls 104 on the panel surface areas 22 whereby the density of the deformities on the panel surface areas may be even further increased.

The light extracting deformities may also be of other well defined  
20 shapes to obtain a desired light output distribution from a panel surface area. Fig. 22 shows individual light extracting deformities 105 on a panel surface area 22 each including a generally planar, rectangular reflective/refractive surface 106 and associated end wall 107 of a uniform slope throughout their length and width and generally planar side  
25 walls 108. Alternatively, the deformities 105' may have rounded or curved side walls 109 as schematically shown in Fig. 23.

Fig. 24 shows individual light extracting deformities 110 on a  
30 panel surface area 22 each including a planar, sloping triangular shaped reflective/refractive surface 111 and associated planar, generally triangularly shaped side walls or end walls 112. Fig. 25 shows individual light extracting deformities 115 each including a planar sloping reflective/

refractive surface 116 having angled peripheral edge portions 117 and associated angled end and side walls 118 and 119.

Fig. 26 shows individual light extracting deformities 120 which are generally conically shaped, whereas Fig. 27 shows individual light  
5 extracting deformities 121 each including a rounded reflective/refractive surface 122 and rounded end wall 123 and rounded or curved side walls 124 all blended together.

Regardless of the particular shape of the reflective/refractive surfaces and end and side walls of the individual deformities, such  
10 deformities may also include planar surfaces intersecting the reflective/refractive surfaces and end and/or side walls in parallel spaced relation to the panel surface areas 22. Figs. 28 through 30 show deformities 125, 126 and 127 in the form of individual projections on a panel surface area 22 having representative shapes similar to those  
15 shown in Figs. 22, 23 and 26, respectively, except that each deformity is intersected by a planar surface 128 in parallel spaced relation to the panel surface area 22. In like manner, Fig. 31 shows one of a multitude of deformities 129 in the form of individual depressions 130 in a panel surface area 22 each intersected by a planar surface 128 in parallel  
20 spaced relation to the general planar surface of the panel surface area 22. Any light rays that impinge on such planar surfaces 128 at internal angles less than the critical angle for emission of light from the panel surface area 22 will be internally reflected by the planar surfaces 128, whereas any light rays impinging on such planar surfaces 128 at internal  
25 angles greater than the critical angle will be emitted by the planar surfaces with minimal optical discontinuities as schematically shown in Fig. 31.

Where the deformities are projections on the panel surface area 22, the reflective/refractive surfaces extend at an angle away from the  
30 panel in a direction generally opposite to that in which the light rays from the light source 3 travel through the panel as schematically shown in

Figs. 18 and 20. Where the deformities are depressions in the panel surface area, the reflective/refractive surfaces extend at an angle into the panel in the same general direction in which the light rays from the light source 3 travel through the panel member as schematically shown in Figs. 19 and 20.

Regardless of whether the deformities are projections or depressions on or in the panel surface areas 22, the slopes of the light reflecting/refractive surfaces of the deformities may be varied to cause the light rays impinging thereon to be either refracted out of the light emitting panel or reflected back through the panel and emitted out the opposite side of the panel which may be etched to diffuse the light emitted therefrom or covered by a transparent film, sheet or plate similar to the film 27 shown in Figs. 3 and 5 to produce a desired effect.

Also, the pattern of light extracting deformities on the panel surface areas may be uniform or variable as desired to obtain a desired light output distribution from the panel surface areas. Figs. 32 and 33 show deformities 125 and 126 similar in shape to those shown in Figs. 28 and 29 arranged in a plurality of generally straight uniformly spaced apart rows along the length and width of a panel surface area 22, whereas Figs. 34 and 35 show such deformities 125 and 126 arranged in staggered rows along the length of a panel surface area.

Also, the size, including the width, length and depth or height as well as the angular orientation and position or location of the light extracting deformities may vary along the length and/or width of any given panel surface area to obtain a desired light output distribution from the panel surface area. Figs. 36 and 37 show a random or variable pattern of different sized deformities 105 and 105' similar in shape to those shown in Figs. 22 and 23, respectively, arranged in staggered rows on a panel surface area 22, whereas Fig. 38 shows deformities 126 similar in shape to those shown in Fig. 29 increasing in size as the distance of the deformities from the light source increases or intensity of

the light decreases along the length and/or width of the panel surface area 22.

5 Figs. 39 and 40 schematically show different angular orientations of light extracting deformities 135 of any desired shape along the length and width of a panel surface area 22. In Fig. 39 the light extracting deformities 135 are arranged in straight rows 136 along the length of the panel surface area but the deformities in each of the rows are oriented to face the light source 3 so that all of the deformities are substantially in line with the light rays being emitted from the light source. In Fig. 40 the 10 deformities 135 are also oriented to face the light source 3 similar to Fig. 39. In addition, the rows 137 of deformities in Fig. 40 are in substantial radial alignment with the light source.

15 Figs. 41 and 42 schematically show how exemplary light rays 140 emitted from a focused light source 3 insert molded or cast within a light transition area 6 of a light emitting panel assembly 5 in accordance with this invention are reflected during their travel through the light emitting panel member 7 until they impinge upon individual light extracting deformities 98, 126 of well defined shapes on or in a panel surface area 22 causing more of the light rays to be reflected or refracted out of one 20 side 141 of the panel member than the other side 142. In Fig. 41 the exemplary light rays 140 are shown being reflected by the reflective/refractive surfaces 101 of the deformities 98 in the same general direction out through the same side 141 of the panel member, whereas in Fig. 42 the light rays 140 are shown being scattered in 25 different directions within the panel member 7 by the rounded side walls 109 of the deformities 126 before the light rays are reflected/refracted out of the same side 141 of the panel member. Such a pattern of individual light extracting deformities of well defined shapes in accordance with the present invention can cause 60 to 70% or more of 30 the light received through the input edge 18 of the panel member to be emitted from the same side of the panel member.

Fig. 43 schematically shows the side 141 of the light emitting panel assembly 5 of Fig. 42 from which a majority of the light is emitted placed against the front face 143 of a liquid crystal display or other signage 144 for front lighting the display/signage when the ambient light is not sufficient for proper illumination. The portions of the panel member 7 overlying the display/signage 144 are transparent without any back reflector, whereby when the light source 3 is energized, light will be emitted from the side 141 of the panel member 7 contacting the front face 143 of the display/signage 144 and then reflected back out through the panel member 7 including particularly the planar surfaces 128 on the deformities.

By selecting the optical index of refraction of the panel member 7 to closely match the substrate of the display/signage 144, the light reflected by the display/signage will pass through the planar surfaces 128 of the deformities with minimal optical discontinuities for ease of viewing the display/signage. Also, providing a random or variable pattern of light extracting deformities on the panel member insures that the spacing of the light extracting deformities does not match the pixel spacing of the display so as not to produce a headlight effect.

Because the light extracting deformities are of well defined shapes, the size, shape, location and orientation of each light extracting deformity can be individually adjusted or randomly varied at any given surface area of the panel member to spread the light output distribution uniformly across each panel surface area or obtain any other desired light output distribution at each panel surface area. Also, such light extracting deformities may be formed in or on any surface area of the panel member in any desired manner, such as by machining using a milling or laser cutter, or by molding or stamping or the like.

The light source 3 for the panel assemblies shown in Figs. 16, 17 and 39 through 43 may be of any suitable type as previously described. However, preferably such light source is a focused light source such as a



lens end bulb, a chip from an LED, or a laser or laser diode. Alternatively such light source may be an LED, incandescent lamp or other light source having an integral collector 145 (see Fig. 16) that collects the light from the light source and focuses the light. In either case the light from the light source is preferably focused in a predetermined pattern on the input surface 146 of the light transition area 6 which directs the light at an acceptable angle for entering the light input edge 18 of the light emitting panel 7 over a substantial portion of the cross sectional area of the panel.

Fig. 44 schematically illustrates still another form of light emitting panel assembly 150 in accordance with this invention which is particularly adapted to be used for different types of phototherapy treatment by exposing various portions of the skin or eyes of a person to light being emitted from the panel assembly to treat such conditions as neonatal hyperbilirubinemia, insomnia, sleep disorders or tiredness associated with jet lag or shift work, certain types of psychiatric disorders such as seasonal affective disorder (SAD) and depression and so on. To that end, the light emitting panel assembly 150 includes a light emitting panel member 151 which may be in the shape of a pad or blanket. At one or both ends of the panel member 151 are one or more light transition areas 152 containing one or more LEDs or other light sources 3 for uniformly supplying light of any desired wavelength to the panel input edge 154 at one or both ends of the panel member. If desired, the light sources may be different colored LEDs so that the light from the LEDs can be mixed to produce virtually any desired colored light output distribution including white light from the panel member. Also, white LEDs may be used for producing a white light output distribution from the panel member.

On one or more selected panel surface areas on one or both sides of the panel member 151 are a pattern of light extracting deformities or disruptions which are not shown in Fig. 44 but may be of any of the types previously described for producing a desired light output

distribution from the panel surface areas. The portion of the body of a person to receive phototherapy treatment may be placed in close association with or directly against the light emitting surface areas of the panel. Alternatively, the panel assembly 150 may be provided with  
5 molded portions 155 at strategic locations on the panel member 151 (for example at all four corners) for providing structural support for locating other parts or components such as a diffuser or lens 156 as schematically shown in Fig. 45.

Fig. 46 shows still another form of light emitting panel assembly  
10 160 in accordance with this invention for use in phototherapy treatment or other applications in which an array of LEDs or other light sources 3 are mounted on a printed circuit board 162 for directing light through a transparent member 163 which may be a diffuser or lens. The transparent member 163 is maintained in spaced apart relation from the  
15 printed circuit board 162 and light sources 3 mounted thereon by a plurality of upstanding supports 164 on a base 165 for the circuit board. Not only does this protect the circuit board 162 and light sources 3 against damage, but also provides an air gap 166 between the light sources 3 and transparent member 163 to facilitate dissipation of any  
20 heat that is produced by the light sources.

In Fig. 46 the circuit board 162 and transparent member 163 are shown as being substantially flat. However, it will be appreciated that such circuit board 162 and transparent member 163 may also be curved as schematically shown in Fig. 47 for supporting a body part such as an  
25 arm, leg or neck of a person receiving phototherapy treatment.

The various light emitting panel assemblies disclosed herein may be used for a great many different applications including for example liquid crystal display (LCD) or other signage back lighting or lighting in general, decorative and display lighting, automotive lighting, dental  
30 lighting, phototherapy or other medical lighting, membrane switch lighting, and sporting goods and apparel lighting or the like. Also the

5 panel assemblies may be made such that the panel members and deformities are transparent without a back reflector. This allows the panel assemblies to be used for example to front light an LCD or other display such that the display is viewed through the transparent panel members in the manner previously described.

10 Although the invention has been shown and described with respect to certain preferred embodiments, it is obvious that equivalent alterations and modifications will occur to others skilled in the art upon the reading and understanding of the specification. The present invention includes all such equivalent alterations and modifications, and is limited only by the scope of the claims.

## WHAT IS CLAIMED IS:

1. A light emitting panel assembly comprising a light emitting panel member having an input edge for receiving light from a light source, and a variable pattern of individual light extracting deformities on or in a panel surface of said panel member for producing a desired light output distribution from said panel member, each of said deformities having a well defined shape including a sloping first surface intersecting said panel surface for reflecting or refracting light rays impinging on said first surface, and a second surface extending between said first surface and said panel surface.

2. The panel assembly of claim 1 wherein said first surface has a projected surface area on said panel surface that is substantially greater than any projected surface area of said second surface on said panel surface.

3. The panel assembly of claim 1 wherein said second surface is substantially perpendicular to said first surface.

4. The panel assembly of claim 1 wherein said deformities comprise depressions in said panel surface.

5. The panel assembly of claim 1 wherein said deformities comprise raised surfaces on said panel surface.

6. The panel assembly of claim 1 wherein said first surface of each of said deformities is substantially planar throughout its length.

7. The panel assembly of claim 1 wherein said second surface of each of said deformities is substantially curved in a transverse direction throughout its length.

8. The panel assembly of claim 1 wherein each of said deformities includes side walls extending between said first surface and said panel surface.

9. The panel assembly of claim 1 wherein at least some of said deformities vary in size across a width of said panel surface.

10. The panel assembly of claim 1 wherein at least some of said deformities vary in size along a length of said panel surface.

11. The panel assembly of claim 1 wherein the orientation of at least some of said deformities varies across a width of said panel surface.

12. The panel assembly of claim 1 wherein the orientation of at least some of said deformities varies along a length and width of said panel surface.

13. The panel assembly of claim 1 wherein said deformities are randomly spaced on said panel surface.

14. The panel assembly of claim 1 wherein at least some of said deformities have rounded side walls.

15. The panel assembly of claim 1 wherein at least some of said deformities have planar side walls.

16. The panel assembly of claim 1 wherein at least some of said deformities have more surfaces than said first and second surfaces.

17. A light emitting panel assembly comprising a light emitting panel member having an input edge for receiving light from a light source, and a pattern of individual light extracting deformities on or in a panel surface of said panel member for producing a desired light output distribution from said panel member, at least some of said deformities having a well defined shape including at least two surfaces, one of said surfaces being substantially flat and having a larger surface area than another of said surfaces.

18. The panel assembly of claim 17 wherein said two surfaces intersect said panel surface.

19. A light emitting panel assembly comprising a transparent panel member that receives light through an input edge of said panel member, a pattern of individual light extracting deformities on or in one or more portions of said panel member, said one or more portions having front and back sides that are free of any reflective material whereby an

image can be viewed through said sides for front lighting of a display placed in close proximity to said back side, said deformities comprising discrete shapes that extend into said panel member.

5           20.    The panel assembly of claim 19 wherein said display has a front face in close proximity to said back side of said panel member for receiving light emitted from said back side.

          21.    The panel member of claim 20 wherein said display comprises a liquid crystal display.

10           22.    The panel assembly of claim 20 wherein said display comprises signage.

          23.    The panel assembly of claim 20 wherein said deformities are on said back side of said panel member which is closest to said display.

15           24.    The panel assembly of claim 20 wherein said deformities are shaped to reflect and refract the light out said back side of said panel member for front lighting said display.

          25.    The panel assembly of claim 24 wherein said deformities have one surface that refracts the light and at least one surface that reflects the light.

20           26.    A light emitting panel assembly comprising a light emitting panel member having oppositely facing panel surfaces and an input edge for receiving light from a light source, and a pattern of individual light extracting deformities on or in one of said panel surfaces for producing a desired light output distribution from said panel member, at least some of said deformities having planar surfaces in parallel spaced relation to said one panel surface.

25           27.    The panel assembly of claim 26 wherein said deformities comprise depressions in said one panel surface.

          28.    The panel assembly of claim 26 wherein said deformities comprise projections on said one panel surface.

30           29.    The panel assembly of claim 26 wherein at least some of said deformities have rounded side walls.

30. The panel assembly of claim 26 wherein at least some of said deformities have planar side walls.

5 31. The panel assembly of claim 26 wherein said deformities have first surfaces extending between said planar surfaces and said one panel surface at an angle for reflecting or refracting light rays impinging on said first surfaces, and second surfaces extending between said planar surfaces and said one panel surface.

10 32. The panel assembly of claim 31 wherein said first surfaces have a projected surface area on said one panel surface which is substantially greater than any projected surface area of said second surfaces on said one panel surface.

33. The panel assembly of claim 31 wherein at least some of said first and second surfaces are planar.

15 34. The panel assembly of claim 31 wherein at least some of said first surfaces are triangular in shape.

35. The panel assembly of claim 31 wherein at least some of said first surfaces have angled edges.

36. The panel assembly of claim 31 wherein at least some of said first surfaces vary in width.

20 37. The panel assembly of claim 31 wherein at least some of said first surfaces vary in height or depth.

38. The panel assembly of claim 26 wherein at least some of said deformities have planar side walls at opposite ends of said planar surfaces.

25 39. The panel assembly of claim 26 wherein at least some of said deformities have rounded side walls at opposite ends of said planar surfaces.

40. The panel assembly of claim 26 wherein said deformities are arranged in rows extending radially relative to said light source.

41. The panel assembly of claim 26 wherein said deformities are oriented to face said light source at different locations across the width of said panel member.

5 42. The panel assembly of claim 26 wherein said deformities are oriented to face said light source at different locations along the length of said panel member.

10 43. A light emitting panel assembly comprising a transparent panel member for receiving light through an input edge of said panel member, a pattern of individual light extracting deformities on or in one or more portions of said panel member, said one or more portions having opposite sides that are free of any reflective material whereby light is free to pass through said opposite sides, said deformities being shaped to cause more of the light that is received through said input edge of said panel member to be reflected or refracted out of one of said sides of said one or more portions than an other of said sides.

15 44. The panel assembly of claim 43 wherein said deformities are shaped to cause 60% or more of the light received through said input edge of said panel member to be reflected or refracted out of said one side of said panel member.

20 45. The panel assembly of claim 43 further comprising display means having a front face in close proximity to said one side of said panel member which emits the majority of the light.

25 46. The panel assembly of claim 45 wherein said display means is a liquid crystal display.

47. The panel assembly of claim 45 wherein said display means is signage.

30 48. The panel assembly of claim 45 wherein said deformities have planar surfaces in parallel spaced relation to said one side through which reflected light from said display means passes with minimal optical distortion.



49. The panel assembly of claim 48 wherein said display means comprises a liquid crystal display.

50. The panel assembly of claim 49 wherein said pattern of light extracting deformities is varied such that the spacing of said light extracting deformities does not match the pixel spacing of said liquid crystal display.

51. The panel assembly of claim 43 wherein at least some of said deformities have rounded side walls for scattering of the light emitted from said one side of said panel member.

52. The panel assembly of claim 43 wherein said light extracting deformities vary in shape.

53. The panel assembly of claim 43 wherein said light extracting deformities vary in size.

54. The panel assembly of claim 43 wherein said light extracting deformities have different angle orientations.

55. The panel assembly of claim 43 wherein said light extracting deformities vary in spacing.

56. The panel assembly of claim 43 wherein said light extracting deformities have reflective/refractive surfaces of varying slope.





FIG. 4d




FIG. 4a




FIG. 2




FIG. 4b




FIG. 4c
















FIG. 3










FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27






FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47

**INTERNATIONAL SEARCH REPORT**

International application No.  
PCT/US00/04499

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>				
IPC(7) :F21V 7/04 US CL :362/31, 26, 339 According to International Patent Classification (IPC) or to both national classification and IPC				
<b>B. FIELDS SEARCHED</b>				
Minimum documentation searched (classification system followed by classification symbols) U.S. : 362/31, 26, 331, 332, 339				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched NONE				
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) NONE				
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X	US 5,671,994 A (TAI et al.) 30 September 1997 (30-09-1997), whole document.	1-56		
X	US 5,590,945 A (SIMMS) 07 January 1997 (07-01-1997), whole document.	1-20, 22-45, 47-48, 50-56		
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.				
<table style="width:100%; border:none;"> <tr> <td style="width:50%; border:none;">           * Special categories of cited documents:            "A" document defining the general state of the art which is not considered to be of particular relevance            "E" earlier document published on or after the international filing date            "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)            "O" document referring to an oral disclosure, use, exhibition or other means            "P" document published prior to the international filing date but later than the priority date claimed         </td> <td style="width:50%; border:none;">           "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention            "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone            "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art            "&amp;" document member of the same patent family         </td> </tr> </table>			* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family			
Date of the actual completion of the international search 16 MAY 2000		Date of mailing of the international search report <b>12 JUN 2000</b>		
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer <b>THOMAS M. SEMBER</b> Telephone No. (703) 308-1938		

