




US 20170165536A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2017/0165536 A1**
(43) **Pub. Date: Jun. 15, 2017**(54) **METAL WOOD CLUB****Publication Classification**(71) Applicant: **Acushnet Company**, Fairhaven, MA (US)(51) **Int. Cl.**
A63B 53/04 (2006.01)(72) Inventors: **Sang Yi**, Carlsbad, CA (US); **Richard Sanchez**, Temecula, CA (US); **Thomas Orrin Bennett**, Carlsbad, CA (US)(52) **U.S. Cl.**
CPC .. **A63B 53/0466** (2013.01); **A63B 2053/0491** (2013.01); **A63B 2209/02** (2013.01)(73) Assignee: **Acushnet Company**, Fairhaven, MA (US)(57) **ABSTRACT**(21) Appl. No.: **15/154,692**(22) Filed: **May 13, 2016****Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/969,248, filed on Dec. 15, 2015, which is a continuation-in-part of application No. 14/966,316, filed on Dec. 11, 2015.

A golf club head having a body having a first receptacle having an aperture and a weight retention member affixed to the receptacle, the weight retention member having an opening, the weight retention member configured to receive a weighted insert, wherein at least a portion of the receptacle is located on the sole, wherein the receptacle includes a pair of perimeter walls, each of the perimeter walls substantially perpendicular to the sole adjacent the perimeter walls, wherein the pair of perimeter walls are separated by the aperture and are substantially parallel to one another.






FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5






FIG. 6






FIG. 8




FIG. 9






FIG. 11






FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 15





FIG. 16






FIG. 17





FIG. 18






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25






FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37





FIG. 38






FIG. 40




FIG. 41




FIG. 42




FIG. 43




Fig. 44




Fig. 45




Fig. 46




Fig. 47




Fig. 48




Fig. 49




Fig. 50




Fig. 51




Fig. 52




Fig. 53




Fig. 54




Fig. 55




Fig. 56




Fig. 57




Fig. 58




Fig. 59




Fig. 60




Fig. 61




Fig. 62




Fig. 63




Fig. 64




Fig. 65




Fig. 66




Fig. 67




Fig. 68





Fig. 69



F1ig. 70




Fig. 71




Fig. 72




Fig. 73




Fig. 74




Fig. 75




Fig. 76




Fig. 77




Fig. 78




Fig. 79




Fig. 80








Fig. 81








Fig. 8 6




Fig. 87




Fig. 88




Fig. 89




Fig. 91




Fig. 92




Fig. 93




Fig. 94




Fig. 95




Fig. 96




Fig. 97




Fig. 98




Fig. 99




Fig. 100




Fig. 101




Fig. 102




Fig. 103




Fig. 104




Fig. 105




Fig. 106

METAL WOOD CLUB

RELATED APPLICATIONS

[0001] The current application is a continuation-in-part of U.S. patent application Ser. No. 14/969,248, Metal Wood Club, to Sanchez et al., filed on Dec. 15, 2015, currently pending, which is a continuation-in-part of U.S. patent application Ser. No. 14/966,316, Metal Wood Club, to Knutson et al., filed on Dec. 11, 2015, currently pending, the disclosure of which is incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] This present technology generally relates to systems, devices, and methods related to golf clubs, and more specifically to a wood-type golf club head with improved physical attributes.

DESCRIPTION OF THE RELATED TECHNOLOGY

[0003] Golf club heads come in many different forms and makes, such as wood- or metal-type (including drivers and fairway woods), iron-type (including wedge-type club heads), utility- or specialty-type, and putter-type. Each of these styles has a prescribed function and make-up. The present invention relates primarily to hollow golf club heads, such as wood-type and utility-type (generally referred to herein as wood-type golf clubs).

[0004] Wood-type or metal-type golf club heads generally include a front or striking face, a crown, a sole and an arcuate skirt including a heel, a toe and a back. The crown and skirt are sometimes referred to as a shell. The front face interfaces with and strikes the golf ball. A plurality of grooves, sometimes referred to as “score lines,” may be provided on the face to assist in imparting spin to the ball and for decorative purposes. The crown is generally configured to have a particular look to the golfer and to provide structural rigidity for the striking face. The sole of the golf club is particularly important to the golf shot because it contacts and interacts with the ground during the swing.

[0005] The complexities of golf club design are well known. The specifications for each component of the club (i.e., the club head, shaft, grip, and subcomponents thereof) directly impact the performance of the club. Thus, by varying the design specifications, a golf club can be tailored to have specific performance characteristics.

[0006] The design and manufacture of wood-type club heads requires careful attention to club head construction. Among the many factors that must be considered are material selection, material treatment, structural integrity and overall geometrical design. Exemplary geometrical design considerations include loft, lie, face angle, horizontal face bulge, vertical face roll, face size, center of gravity, sole curvature, and overall head weight. The interior design of the club head may be tailored to achieve particular characteristics, such as by including hosel or shaft attachment means, perimeter weighting on the face or body of the club head, and fillers within hollow club heads. Club heads are typically formed from stainless steel, aluminum, or titanium and are cast, stamped, as by forming sheet metal with pressure, forged, or formed by a combination of any two or more of these processes.

[0007] The club heads may be formed from multiple pieces that are welded or otherwise joined together to form a hollow head, as is often the case of club heads designed with inserts, such as soleplates or crown plates. The multi-piece constructions facilitate access to the cavity formed within the club head, thereby permitting the attachment of various other components to the head such as internal weights and the club shaft. The cavity may remain empty, or may be partially or completely filled, such as with foam. An adhesive may be injected into the club head to provide the correct swing weight and to collect and retain any debris that may be in the club head. In addition, due to difficulties in manufacturing one-piece club heads to high dimensional tolerances, the use of multi-piece constructions allows the manufacture of a club head to a tight set of standards.

[0008] It is known to make wood-type golf clubs out of metallic materials. These clubs were originally manufactured primarily by casting durable metals such as stainless steel, aluminum, beryllium copper, etc. into a unitary structure comprising a metal body, face and hosel. As technology progressed, it became more desirable to increase the performance of the face of the club, usually by using a titanium material.

[0009] Players generally seek a metal wood driver and golf ball combination that delivers maximum distance and landing accuracy. The distance a ball travels after impact is dictated by the magnitude and direction of the ball's translational velocity and the ball's rotational velocity or spin. Environmental conditions, including atmospheric pressure, humidity, temperature, and wind speed, further influence the ball's flight. However, these environmental effects are beyond the control of the golf equipment manufacturer. Golf ball landing accuracy is driven by a number of factors as well. Some of these factors are attributed to club head design, such as center of gravity and club face flexibility.

[0010] Known methods to enhance the weight distribution of wood-type club heads to help reduce the club from being open upon contact with the ball usually include the addition of weights to the body casting itself or strategically adding a weight element at some point in the club. Many efforts have been made to incorporate weight elements into the wood-type club head. These weight elements are usually placed at specific locations, which will have a positive influence on the flight of the ball or to overcome a particular golfer's shortcomings.

[0011] The sole of the golf club is particularly important to the golf shot because it contacts and interacts with the ground during the golf shot. There are many sole configurations to optimize the performance of the club. Typically, the sole of the club is slightly curved such that when the club head is placed on the ground, the leading edge is located above the ground. The curvature toward the front of the club generally provides bounce. Bounce assists in preventing the club from digging into the ground and substantially slowing club head speed. The curvature toward the trailing edge generally prevents the club head from getting caught on the ground during the back swing.

[0012] The present invention is directed to an improved weighting system for wood-type golf clubs that increases the club's playability.

SUMMARY

[0013] The systems, methods, and devices described herein have innovative aspects, no single one of which is

indispensable or solely responsible for their desirable attributes. Without limiting the scope of the claims, some of the advantageous features will now be summarized.

[0014] One non-limiting embodiment of the present technology includes a golf club head comprising a body having a face, a sole, a crown, and a skirt joining the face, sole and crown; a hollow golf club interior within the body; the body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face; the body having a center of gravity; wherein the body comprises a receptacle, the receptacle comprising an aperture; a weight retention system configured to receive a weighted insert, the weight retention system comprising a weight retention member affixed to the receptacle, the weight retention member comprising an opening on one end of the weight retention member configured to receive the weighted insert, at least a portion of the weight retention member extending through the first aperture into the hollow golf club interior; wherein the weighted insert comprises a heavy end and a lighter end, wherein the weight retention member is configured to receive the weighted insert in both a first configuration and a second configuration, wherein the first configuration comprises the heavy end of the weighted insert adjacent the opening of the weight retention member and the second configuration comprises the lighter end of the weighted insert adjacent the opening of the weight retention member; wherein at least a portion of the receptacle is located on the sole; wherein the weight retention member is permanently affixed to the receptacle; wherein the receptacle includes a pair of perimeter walls, each of the perimeter walls are substantially perpendicular to the sole adjacent the perimeter walls, the pair of perimeter walls separated by the aperture, the pair of perimeter walls substantially parallel to one another; wherein the receptacle includes a pair of shelves connecting the pair of perimeter walls at each end of the aperture, wherein the shelves are substantially curved, the pair of shelves recessed towards the hollow golf club head interior from the sole; wherein the weight retention member abuts the pair of perimeter walls and the pair of shelves; wherein a majority of the body, by weight, is formed from a first material having a first density; wherein the weight retention member is formed from a second material, the second material having a second density and wherein the second density is less than the first density.

[0015] An additional non-limiting embodiment of the present technology includes a golf club head comprising a body having a face, a sole, a crown, and a skirt joining the face, sole and crown; a hollow golf club interior within the body; the body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face; the body having a center of gravity; wherein the body comprises a receptacle, the receptacle comprising an aperture; a weight retention system configured to receive a weighted insert, the weight retention system comprising a weight retention member affixed to the receptacle, the weight retention member comprising an opening on one end of the weight retention member configured to receive the weighted insert; wherein at least a portion of the receptacle is located on the sole; wherein the weight retention member is permanently affixed to the receptacle; wherein the receptacle includes a pair of perimeter walls, each of the perimeter walls formed at an angle relative to the sole adjacent the

receptacle, the pair of perimeter walls separated by the aperture; wherein the receptacle includes a pair of shelves connecting the pair of perimeter walls at each end of the aperture, the pair of shelves recessed towards the hollow golf club head interior from the sole; wherein the weight retention member abuts the pair of perimeter walls and the pair of shelves; wherein a majority of the body, by weight, is formed from a first material having a first density; wherein the weight retention member is formed from a second material, the second material having a second density and wherein the second density is less than the first density.

[0016] In an additional non-limiting embodiment of the present technology each of the perimeter walls are formed at an angle of at least 45 degrees relative to the sole adjacent the receptacle.

[0017] In an additional non-limiting embodiment of the present technology each of the perimeter walls are substantially perpendicular to the sole adjacent the receptacle.

[0018] In an additional non-limiting embodiment of the present technology at least a portion of the receptacle are located on the skirt.

[0019] In an additional non-limiting embodiment of the present technology at least a portion of the weight retention member extends through the aperture into the hollow golf club interior.

[0020] In an additional non-limiting embodiment of the present technology the weight retention member is formed of fiber reinforced plastic.

[0021] In an additional non-limiting embodiment of the present technology the weighted insert comprises a heavy end and a lighter end, wherein the weight retention member is configured to receive the weighted insert in both a first configuration and a second configuration, wherein the first configuration comprises the heavy end of the weighted insert adjacent the opening of the weight retention member and the second configuration comprises the lighter end of the weighted insert adjacent the opening of the weight retention member.

[0022] In an additional non-limiting embodiment of the present technology the weight retention system further comprises a head locking feature configured to lock the weighted insert in the weight retention system.

[0023] In an additional non-limiting embodiment of the present technology the weight retention member further comprises a pair of sidewalls, the pair of sidewalls substantially parallel to one another, the pair of sidewalls configured to abut the perimeter walls of the receptacle.

[0024] An additional non-limiting embodiment of the present technology includes a golf club head comprising a body having a face, a sole, a crown, and a skirt joining the face, sole and crown; a hollow golf club interior within the body; the body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face; the body having a center of gravity; wherein the body comprises a receptacle; a weight retention system configured to receive a weighted insert, the weight retention system comprising a weight retention member affixed to the receptacle, the weight retention member comprising an opening on one end of the weight retention member configured to receive the weighted insert; wherein the weighted insert comprises a heavy end and a lighter end, wherein the weight retention member is configured to receive the weighted insert in both a first configuration and a second configura-

tion, wherein the first configuration comprises the heavy end of the weighted insert adjacent the opening of the weight retention member and the second configuration comprises the lighter end of the weighted insert adjacent the opening of the weight retention member; wherein the weight retention member is permanently affixed to the receptacle; wherein the receptacle includes a pair of perimeter walls, each of the perimeter walls formed at an angle relative to the sole; wherein the receptacle includes a pair of shelves connecting the pair of perimeter walls at each end of the receptacle, the pair of shelves recessed towards the hollow golf club head interior from the sole; wherein the weight retention member abuts the pair of perimeter walls and the pair of shelves; wherein a majority of the body, by weight, is formed from a first material having a first density; wherein the weight retention member is formed from a second material, the second material having a second density and wherein the second density is less than the first density.

[0025] In an additional non-limiting embodiment of the present technology each of the perimeter walls are formed at an angle of at least 45 degrees relative to the sole adjacent the receptacle.

[0026] In an additional non-limiting embodiment of the present technology each of the perimeter walls are substantially perpendicular to the sole adjacent the receptacle.

[0027] In an additional non-limiting embodiment of the present technology at least a portion of the receptacle are located on the skirt.

[0028] In an additional non-limiting embodiment of the present technology at least a portion of the weight retention member extends through the aperture into the hollow golf club interior.

[0029] In an additional non-limiting embodiment of the present technology the weight retention member is formed of fiber reinforced plastic.

[0030] In an additional non-limiting embodiment of the present technology the weight retention system further comprises a head locking feature configured to lock the weighted insert in the weight retention system.

[0031] In an additional non-limiting embodiment of the present technology the weight retention member further comprises a pair of sidewalls, the pair of sidewalls substantially parallel to one another, the pair of sidewalls configured to abut the perimeter walls of the receptacle.

BRIEF DESCRIPTION OF THE DRAWINGS

[0032] The accompanying drawings form a part of the specification and are to be read in conjunction therewith. The illustrated embodiments, however, are merely examples and are not intended to be limiting. Like reference numbers and designations in the various drawings indicate like elements.

[0033] Preferred features of the present invention are disclosed in the accompanying drawings, wherein similar reference characters denote similar elements throughout the several views, and wherein:

[0034] FIG. 1 is a perspective view of an embodiment of a club head of the present invention;

[0035] FIG. 2 is bottom plan view of an embodiment of a club head of FIG. 1;

[0036] FIG. 3A is a front plan view of an embodiment of a club head according to FIG. 1 at impact with a golf ball;

[0037] FIG. 3B is a front plan view of an embodiment of a club head according to FIG. 1 at address;

[0038] FIG. 4A is bottom plan view of an embodiment of a club head of FIG. 1;

[0039] FIG. 4B is a cross-sectional view of the club head of FIG. 4 taken along line 3B-3B in FIG. 4;

[0040] FIG. 4C is a cross-sectional view of the club head of FIG. 4 taken along line 4C-4C in FIG. 4;

[0041] FIG. 4D is a cross-sectional view of the club head of FIG. 4 taken along line 4D-4D in FIG. 4;

[0042] FIG. 5 is a back view of the club head of FIG. 1;

[0043] FIG. 6 is a heel side view of the club head of FIG. 1;

[0044] FIG. 7A is a bottom plan view of a club head with the inventive sole of FIG. 1;

[0045] FIG. 7B is a cross sectional view of the club head of FIG. 7A taken along line 7B-7B;

[0046] FIG. 8 is a bottom plan view of another alternative embodiment of a club head of the present invention;

[0047] FIG. 9 is a top plan view of an alternative embodiment of a club head according to the present invention;

[0048] FIG. 10A is a front plan view of a club head according to an embodiment of the club head of FIG. 9;

[0049] FIG. 10B is a cross-sectional view of the club head of FIG. 10A, taken along lines 10B-10B;

[0050] FIG. 11 is a top plan view of the club head according to an embodiment of FIG. 9;

[0051] FIG. 12A is a front plan view of a club head according to an embodiment of the club head of FIG. 9;

[0052] FIG. 12B is a cross-sectional view of the club head of FIG. 12A, taken along lines 12B-12B;

[0053] FIG. 13 is a back perspective cut-out view of an embodiment of a club head according to FIG. 9;

[0054] FIG. 14 is a back view of the club head of FIG. 13;

[0055] FIG. 15 is a perspective view of a weight tube according to the embodiment of the FIG. 13;

[0056] FIG. 16 is a back perspective cut-out view of another embodiment of a club head according to FIG. 9;

[0057] FIG. 17 is a perspective view of a weight tube according to the embodiment of the FIG. 17;

[0058] FIG. 18 is a back perspective cut-out view of another embodiment of a club head according to FIG. 9;

[0059] FIG. 19 is a bottom plan view of another embodiment of a club head according to FIG. 9;

[0060] FIG. 20 is a front perspective cut-out view of another embodiment of a club head according to FIG. 9;

[0061] FIG. 21 is a graph depicting the movement of the center of gravity along the y-axis and z-axis according to the embodiment of FIG. 13;

[0062] FIG. 22 is a graph depicting the movement of the center of gravity along the y-axis and x-axis according to the embodiment of FIG. 13;

[0063] FIG. 23 is a graph depicting the movement of the center of gravity along the y-axis and z-axis according to the embodiment of FIG. 16; FIG. 24 is a graph depicting the movement of the center of gravity along the y-axis and x-axis according to the embodiment of FIG. 16;

[0064] FIG. 25 is a perspective view of a golf club head in accordance with an alternative embodiment of the present invention;

[0065] FIG. 26 is an exploded sole view of a golf club head according to the embodiment of FIG. 25;

[0066] FIG. 27 is a cross-sectional view of a golf club head according to the embodiment of FIG. 25, taken across cross-sectional line O;

[0067] FIG. 28 is an exploded sole view of a golf club head according to a further alternative embodiment of the invention;

[0068] FIG. 29 is a perspective view of a golf club head in accordance with an alternative embodiment of the present invention;

[0069] FIG. 30 is an exploded sole view of a golf club head according to the embodiment of FIG. 29;

[0070] FIG. 31 is a cross-sectional view of a golf club head according to the embodiment of FIG. 30, taken across cross-sectional line O;

[0071] FIG. 32 is an exploded sole view of a golf club head according to a further alternative embodiment of the invention;

[0072] FIG. 33 is an exploded sole view of a golf club head according to a further alternative embodiment of the invention.

[0073] FIG. 34 is an exploded view of a weighted insert in accordance with an alternative embodiment of the present invention;

[0074] FIG. 35 is an exploded view of a weighted insert in accordance with another alternative embodiment of the present invention;

[0075] FIG. 36 is a cross-sectional view of a weighted insert in accordance with an alternative embodiment of the present invention;

[0076] FIG. 37 is an exploded view of a weighted insert in accordance with another alternative embodiment of the present invention;

[0077] FIG. 38 is an exploded view of a weighted insert in accordance with another alternative embodiment of the present invention;

[0078] FIG. 39 is an exploded view of a golf club head having a weighted insert in accordance with an alternative embodiment of the present invention;

[0079] FIG. 40 is an exploded view of a weighted insert shown in FIG. 39;

[0080] FIG. 41 is an enlarged cross-sectional view of a cap of the weighted insert in accordance with an alternative embodiment of the present invention;

[0081] FIG. 42 is an enlarged cross-sectional view of a weighted insert in accordance with a further alternative embodiment of the present invention; and

[0082] FIG. 43 is an enlarged cross-sectional view of a weighted insert in accordance with another alternative embodiment of the present invention.

[0083] FIG. 44 of the accompanying drawings shows a perspective view of a weighted insert in accordance with another further alternative embodiment of the present invention.

[0084] FIG. 45 illustrates a cross section of a golf club head including the weighted insert of FIG. 44.

[0085] FIG. 46 illustrates a perspective view of the weighted insert of FIG. 44.

[0086] FIG. 47 illustrates a perspective view of a head locking member of the golf club head of FIG. 45.

[0087] FIG. 48 illustrates a perspective view of a head locking member of the golf club head of FIG. 45.

[0088] FIG. 49 of the accompanying drawings shows a perspective view of a weighted insert in accordance with another further alternative embodiment of the present invention.

[0089] FIG. 50 illustrates a cross section of a golf club head including the weighted insert of FIG. 49.

[0090] FIG. 51 illustrates a perspective view of the weighted insert of FIG. 49 including a spring and centering member.

[0091] FIG. 52 illustrates a perspective view of the spring and centering member of FIG. 51.

[0092] FIG. 53 illustrates a perspective view of a spring.

[0093] FIG. 54 illustrates a perspective view of a low friction member as well as the spring of FIG. 54.

[0094] FIG. 55 of the accompanying drawings shows a perspective view of an insert retaining member.

[0095] FIG. 56 illustrates a perspective view of a weighted insert with a sliding insert locking member.

[0096] FIG. 57 illustrates a perspective view of a sliding insert locking member.

[0097] FIG. 58 illustrates a perspective view of the weighted insert of FIG. 56.

[0098] FIG. 59 illustrates a cross sectional view of the weighted insert of FIG. 56 installed in the insert retaining member of FIG. 55.

[0099] FIG. 60 illustrates a perspective view of an additional embodiment of the weighted insert and sliding insert locking member of FIG. 56.

[0100] FIG. 61 illustrates a cross sectional view of the weighted insert and sliding insert locking member of FIG. 60.

[0101] FIG. 62 illustrates a perspective view of an additional embodiment of a weighted insert.

[0102] FIG. 63 illustrates a perspective view of components of the weighted insert of FIG. 62.

[0103] FIG. 64 illustrates a cross sectional view of the weighted insert of FIG. 62.

[0104] FIG. 65 illustrates a perspective view of an additional embodiment of a weighted insert.

[0105] FIG. 66 illustrates a cross sectional view of the weighted insert of FIG. 65.

[0106] FIG. 67 illustrates a perspective view of an additional embodiment of a weight insert.

[0107] FIG. 68 illustrates a perspective view of an insert retaining member configured to receive the weight insert of FIG. 67.

[0108] FIG. 69 is an end view of the insert retaining member of FIG. 68.

[0109] FIG. 70 is a cross sectional view of the weight insert of FIG. 67 installed in the insert retaining member of FIG. 68.

[0110] FIG. 71 illustrates an additional embodiment of a weighted insert.

[0111] FIG. 72 illustrates a perspective view of an insert retaining member configured to receive the weighted insert of FIG. 71.

[0112] FIG. 73 illustrates an additional embodiment of an insert retaining member.

[0113] FIG. 74 illustrates an additional embodiment of a weighted insert configured to reside in the insert retaining member of FIG. 73.

[0114] FIG. 75 illustrates a cross sectional view of the insert retaining member and weighted insert of FIGS. 73 and 74.

[0115] FIG. 76 illustrates a perspective view of an additional embodiment of a weighted insert.

[0116] FIG. 77 illustrates a cross sectional view of the weighted insert of FIG. 76.

[0117] FIG. 78 of the accompanying drawings illustrates a perspective view of one embodiment of a golf club head.

[0118] FIG. 79 illustrates a perspective view of the bottom of the golf club head of FIG. 78 including one embodiment of a weight retention system including a first weight retention member and a second weight retention member.

[0119] FIG. 80 illustrates a perspective view of one embodiment of the weight retention system of FIG. 79.

[0120] FIG. 81 illustrates a perspective view of the weight retention system of FIG. 80 including a third weight retention member.

[0121] FIG. 82 illustrates an additional perspective view of the weight retention system of FIG. 81.

[0122] FIG. 83 illustrates an additional perspective view of the weight retention system of FIG. 81.

[0123] FIG. 84 illustrates a perspective view of one embodiment of the insert retaining member of FIG. 81.

[0124] FIG. 85 illustrates a cross-sectional view of the third weight retention member of FIG. 81.

[0125] FIG. 86 illustrates a perspective view of a weighted insert.

[0126] FIG. 87 illustrates a perspective view of the bottom of the golf club head of FIG. 78 including the third weight retention member of FIG. 81.

[0127] FIG. 88 illustrates an additional perspective view of the golf club head of FIG. 87.

[0128] FIG. 89 illustrates an additional perspective view of the golf club head of FIG. 87.

[0129] FIG. 90 illustrates an additional perspective view of the golf club head of FIG. 87.

[0130] FIG. 91 illustrates a perspective view of the bottom of the golf club head without the weight retention system.

[0131] FIG. 92 illustrates an additional perspective view of the golf club head of FIG. 91.

[0132] FIG. 93 illustrates a cross-sectional view of the golf club head of FIG. 91.

[0133] FIG. 94 illustrates a cross-sectional view of the golf club head of FIG. 79.

[0134] FIG. 95 illustrates a cross-sectional view of the golf club head of FIG. 87.

[0135] FIG. 96 illustrates a bottom view of a golf club head 2050 including an additional embodiment of a weight retention system 4090.

[0136] FIG. 97 illustrates a perspective view of the golf club head 2050 of FIG. 96.

[0137] FIG. 98 illustrates an additional perspective view of the golf club head 2050 of FIG. 96.

[0138] FIG. 99 illustrates an additional perspective view of the golf club head 2050 of FIG. 96.

[0139] FIG. 100 illustrates a perspective view of the golf club head 2050 of FIG. 96 without the weight retention member.

[0140] FIG. 101 illustrates an additional perspective view of the golf club head 2050 of FIG. 100.

[0141] FIG. 102 illustrates a perspective view of one embodiment of a weight retention member 4092.

[0142] FIG. 103 illustrates an additional perspective view of the weight retention member 4092 of FIG. 102.

[0143] FIG. 104 illustrates an end view of the weight retention member 4092 of FIG. 102.

[0144] FIG. 105 illustrates a cross sectional view of the weight retention system 4090.

[0145] FIG. 106 illustrates an additional cross sectional view of the weight retention system 4090.

DETAILED DESCRIPTION

[0146] In the following detailed description, reference is made to the accompanying drawings, which form a part of the present disclosure. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented herein. It will be readily understood that the aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and form part of this disclosure. For example, a system or device may be implemented or a method may be practiced using any number of the aspects set forth herein. In addition, such a system or device may be implemented or such a method may be practiced using other structure, functionality, or structure and functionality in addition to or other than one or more of the aspects set forth herein. Alterations and further and further modifications of inventive features illustrated herein, and additional applications of the principles of the inventions as illustrated herein, which would occur to one skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

[0147] Other than in the operating examples, or unless otherwise expressly specified, all of the numerical ranges, amounts, values and percentages such as those for amounts of materials, moments of inertias, center of gravity locations, loft and draft angles, and others in the following portion of the specification may be read as if prefaced by the word “about” even though the term “about” may not expressly appear with the value, amount, or range. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0148] Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. Furthermore, when numerical ranges of varying scope are set forth herein, it is contemplated that any combination of these values inclusive of the recited values may be used.

[0149] In describing the present technology, the following terminology may have been used: The singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to an item includes reference to one or more items. The term “plurality” refers to two or more of an item. The term “substantially” means that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to those of skill in the art, may occur in amounts that do not preclude the effect the characteristic was

intended to provide. A plurality of items may be presented in a common list for convenience. However, these lists should be construed as though each member of the list is individually identified as a separate and unique member. Thus, no individual member of such list should be construed as a de facto equivalent of any other member of the same lists solely based on their presentation in a common group without indications to the contrary. Furthermore, where the terms “and” and “or” are used in conjunction with a list of items, they are to be interpreted broadly, in that any one or more of the listed items may be used alone or in combination with other listed items. The term “alternatively” refers to a selection of one of two or more alternatives, and is not intended to limit the selection of only those listed alternative or to only one of the listed alternatives at a time, unless the context clearly indicated otherwise.

[0150] Features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. After considering this discussion, and particularly after reading the section entitled “Detailed Description” one will understand how the illustrated features serve to explain certain principles of the present disclosure

[0151] FIG. 1 shows a golf club head **10** of the present invention. Club head **10** includes a body **12** having a strike face **14**, a sole **16**, a crown **18**, a skirt **20** and a hosel **22**. The body defines a hollow interior volume **24** (See FIGS. 4B-4D). Foam or other material may partially or completely fill the interior volume. Weights may be included within the interior volume. The face may be provided with grooves or score lines of varying design. The club head has a toe **26** and a heel **28**.

[0152] A golf club shaft (not shown) is attached at hosel **22** and is disposed along a shaft axis A-A. The hosel **22** may extend to the bottom of the club head **10**, may terminate at a location between the sole and crown portions **16** and **18** of the head **10**, or the hosel **22** may terminate flush with the crown portion **26**.

[0153] It is recommended that the inner volume **24** have a volume greater than 125 cubic centimeters, and more preferably greater than 175 cubic centimeters. Preferably, the mass of the inventive club head **10** is greater than 150 grams, but less than 220 grams; although the club head may have any suitable weight. The body **12** may be formed of sheets welded together or cast, preferably from steel, aluminum or titanium or any other suitable material or combination thereof.

[0154] The strike face **14** may be made by milling, casting, forging or stamping and forming. The face **14** may be made of any suitable material, including titanium, titanium alloy, carbon steel, stainless steel, beryllium copper, and other metals or composites. The face **14** may have any suitable thickness, and may be uniform or varied. As will be appreciated, the face **14** may be connected to the body **12** by any suitable means, including bonding and welding. Alternatively, the body **12** and face **14** may be cast simultaneously forming a homogeneous shell and eliminating the need to bond or otherwise permanently secure a separate face **14** to the body **12**. Alternatively, the sole **16** or crown **18** may be formed separately and fitted to the remainder of the body **12** as is known to those of skill in the art.

[0155] The sole **16** preferably has a complex shape that accomplishes two objectives. The first objective is to provide a surface for the club head **10** to sit on in the address

position that squares the face **14** to the target. The second objective is to provide a sole shape that gives more clearance to the ground at impact than would be available in a club head with a conventional sole. In order to achieve the first objective, an address portion or zero degree bounce portion **30** is provided. This portion is a sufficient area on the sole **16** on which the club head **10** may rest when placed at the address position by a golfer. The zero degree bounce portion **30** may be a flat portion provided on the sole **16**. The zero degree bounce portion **30** may be directly centered behind the face **16** or, as illustrated, may be provided more toward the heel **28**. As illustrated in FIGS. 1 and 2, the sole **16** has a zero degree bounce portion **30**, such that at address the club head **10** rests at this point and the face **14** is square to the target. The zero degree bounce portion **30** enables the club head **10** to sit just as a conventional club head without a sole having a complex shape. Thus, the complex sole of the inventive club head **10** does not adversely affect the way the club head sits at address.

[0156] In order to achieve the second objective, a portion of the sole **16** is relieved to give it a multi-relief surface **32** with a negative bounce. Preferably, a negative bounce portion **34** is provided on the sole **16** in a center portion that is spaced from the face **14** of the club head **10**. Thus, the club head **10** has two areas of bounce. As illustrated in FIGS. 3A and 3B, the impact position I_p of the club head **10** is different than an address position A_p because the dynamics of the golf swing cause the shaft to flex at impact thereby moving the position of the club head **10**. FIG. 3B illustrates the club head at address where the face is square to the target, the shaft axis A-A creates an angle with the ground G called the shaft angle $\square a$. As illustrated in FIG. 3A, during impact, the club head is rotated a few degrees upright, and the shaft axis A-A creates a different angle with the ground G called shaft angle $\square i$.

[0157] It will be appreciated that in one embodiment the toe **26** may be up at least 5 degrees at a first measurement, for example when the club head **10** sits at address, such that the face **14** measures square. At a second measurement, for example during impact with a golf ball, taken at a centered position the face **14** measures differently than the first measurement. For example, the face **14** may measure at least two degrees more open at the second measurement than the first measurement, or at least two degrees open at the second measurement than the first measurement. The centered position may comprise the negative bounce portion **34**, which may be a substantially flat surface. When the first measurement occurs at the address position, the shaft angle $\square a$ preferably measures about 55 to 45 degrees. When the second measurement occurs at impact of the club head **10** with a golf ball, the shaft angle $\square i$ measures about 55 degrees to 60 degrees.

[0158] As illustrated in FIGS. 1 and 2, the sole **16** features a multi-relief surface **32** to provide greater ground clearance at the trailing edge **36** of the sole **16** to minimize turf resistance. With this construction, the ground/sole contact point remains forward toward the leading edge **38** of the strike face **14**. Maintaining a forward ground/sole contact point improves directional control and ball flight, by reducing the potential of the club head **10** to bounce or skip onto the ball. This is particularly true of players that play the ball forward in their stance, or who sweep the ball from the turf

with a shallow angle of attack. Preferably, the multi-relief surface 32 sole features the negative bounce portion 32 and a cutaway portion 40.

[0159] The negative bounce portion 34 may have any desired overall shape; preferably the negative bounce portion 34 has a triangular shape as shown in FIGS. 1 and 2. FIGS. 4A-4D illustrates the negative bounce portion 34 and cutaway portion 40 in the sole 16. Cross-sectional views illustrated in FIGS. 4B and 4D show cutaway portion 40 in comparison with the regular surface 42 of a conventional club head sole. FIG. 4B illustrates the cross-sectional view of the center section of the club head 10 with the negative bounce portion 34 and cutaway portion 40 in comparison with the regular surface of a conventional club head sole 42.

[0160] The cutaway portion 40 extends from the negative bounce portion 34 to the trailing edge 36 of the club head 10. As illustrated in FIGS. 4B-D, the cutaway portion 40 continues and may gradually increase the negative surface from the plane S running along the bottom of the sole. Preferably, the cutaway portion 40 has a depth dcp of about 0.05 to 0.5 inch from the regular surface of a conventional club head sole 42; this depth may or may not be constant. FIGS. 5 and 6 illustrate the back 44 and heel 28 of the club head. The full extent of the cutaway portion 40 can be envisioned.

[0161] FIGS. 7A-7B illustrate the sole 16 of the club head 10 and a cross-sectional view through line 7B-7B which illustrates the multi-relief surface 32 of the sole 16. The negative bounce portion 34 is spaced a distance D1 from the strike face, where D1 is preferably about 0.1 to 1.0 inch. More preferably, D1 is about 0.35 to 0.65 inch from the strike face 14 of the club head 10. The distance D1 may be different for different club heads as it may depend on the face progression and the loft of the club head. As illustrated, the negative bounce portion 34 comprises a surface having an angle \square from a plane S running along the bottom of the sole 16 parallel to the z-axis of a coordinate system running through the club head. The negative bounce portion 34 comprises about a negative 0.5 to a negative 4.0 degree surface, such that the angle \square is about negative 0.5 to 4.0 degrees from the plane S. Preferably, the negative bounce portion 34 comprises about a negative 2.0 degree surface. It will be appreciated that the negative bounce portion 34 may have a constant angle or may have an angle that varies toward the back of the sole. The negative bounce portion 34 may have locations with multiple radii.

[0162] As illustrated, the multi-relief surface 32 includes both the negative bounce portion 34 and the cutaway portion 40 and these form a triangular shape. The triangular shape forms an angle \square , angle \square is preferably about 35 to 50 degrees, and more preferably about 38 to 44 degrees. The negative bounce portion 34 and cutaway portion 40 have a length L, length L is preferably about 1 to 5 inches, and more preferably about 2 to 4 inches.

[0163] FIG. 8 shows an alternative embodiment for the sole 16. The club head 46 features a multi-relief sole 32 as described above. The multi-relief sole features the negative bounce portion 34 and the cutaway portion 40. It will be appreciated that the negative bounce portion 34 and cutaway portion 40 may have any suitable shape.

[0164] In general, to increase the sweet spot, the center of gravity of the club head is moved toward the bottom and back of the club head. This permits an average golfer to launch the ball up in the air faster and hit the ball farther. In

addition, the moment of inertia of the club head is increased to minimize the distance and accuracy penalties associated with off-center hits. In order to move the weight down and back without increasing the overall weight of the club head, material or mass is generally taken from one area of the club head and moved to another. Materials can be taken from the face of the club, creating a thin club face, the crown and/or sole and placed toward the back of the club.

[0165] FIG. 9 illustrates a top of a club head 50 according to another embodiment of the present invention. Club head 50 includes a body 52 having a strike face 54, a sole 56 (see FIGS. 10A and 10B), a crown 58, a skirt 60 and a hosel 62. The body defines a hollow interior volume 64 (See FIGS. 10B and 12B). The face may be provided with grooves or score lines of varying design. The club head has a toe 66 and a heel 68.

[0166] FIG. 9 illustrates the center of gravity (c.g.) along the x-axis and z-axis. In order to improve playability of the club head 50 it is desired to be able to move the c.g. within the club head 50 to a more optimal position. Preferably, the club head 50 features a weight system 70 (see FIGS. 10A-10B and 12A-12B) to move the c.g. within the club head 50 to a more optimal position. Preferably, the c.g. is movable within a 6 mm distance along the z-axis in comparison to a club head without the weight system. More preferably, the c.g. is movable within a 4 mm distance along the z-axis. The c.g. may be movable within a 6 mm distance along the x-axis in comparison to a club head without the weight system, more preferably within a 2 mm distance, and still more preferably within a 0.5 mm distance. Additionally, the c.g. is moveable within a 6 mm distance along the y-axis in comparison to a club head without the weight system (See FIGS. 10A-10B and 12A-12B). Preferably the c.g. is moveable within a 2 mm distance along the y-axis.

[0167] The c.g. adjustability may not substantially affect the dynamic loft of the club head. For example, for a 3 mm front-back c.g. shift the dynamic loft changes about 0.4 degrees. When the c.g. is moved back, the backspin may increase, for example between 100 and 300 rpm per 3 mm of c.g. movement toward the rear of the club head.

[0168] FIG. 10A illustrates the front face 54 of the club head showing the x-axis and the y-axis. FIG. 10B is a cross-sectional view taken along lines 10B-10B of FIG. 10A. FIG. 10B depicts the inside of the club head featuring a weight system 70 according to the invention, and the c.g. may be moved along the z axis and y axis.

[0169] FIG. 10B depicts the weight system 70 as a tube 72 placed within the club head 50 within a plane formed by the y-axis and z-axis to adjust the c.g. of the club head. As illustrated in FIG. 11, it will be appreciated that more than one tube 72 may be provided within the club head 50. As illustrated in FIG. 10B, the weight system 70 features a tube 72 with a weight 74 at one end 76 of the tube 72. As shown in FIG. 10B, the weight 74 is placed the back of the club head 50 to move the c.g. to a desired location for desirable ball flight. When the weight 74 is located at a back of the club head 50, a shot hit off the club head 50 has increased backspin and a higher launch angle resulting in a softer landing. In an alternative embodiment, it will be appreciated that the tube 72 may feature multiple inserts varying in weight for placement within the tube 72 to move the c.g. of the club head 50 to a desired location.

[0170] As illustrated, the tube 72 is preferably provided at an angle within the club head 50. The tube 72 is angled

downward toward the face **54** of the club head **50**, such that the tube **72** is provided within the plane formed by the z-axis and y-axis. The tube **72** may be angled by an angle \square , where \square is at least 1 degree from the plane W formed by the z axis and x axis. Preferably, the tube is angled downward toward the face **54** by at least 3 degrees from the plane W formed by the z-axis and x-axis. More preferably, the tube **72** is angled downward toward the face of the club head **50** by about 3 to 7 degrees from the plane W formed by the z-axis and x-axis. It will be appreciated that although the tube **72** is described herein as being provided within a plane formed by the y-axis and z-axis, the tube **72** may be offset in either direction from that plane by any desired amount.

[0171] Now referring to FIG. 12A-12B, it will be appreciated that the tube **72** may be flipped within the club head **50**, such that the weight **74** is provided at the other end **76** of the club head **50**, closer to the face **54**, to move the c.g. to a different location for desirable ball flight. When the weight **74** is located at a front of the club head **50** a shot hit off the club head **50** has less backspin and a lower trajectory resulting in a shallower landing for increased distance. It will be appreciated that the tube **72** itself may be able to be inserted in the club head with the weight **74** in either direction, or that different tubes **72** may be selectable with the weight **74** at the desired end and then provided in the club head.

[0172] It will be appreciated that a club having the weight system **70**, such as the tube **72** and weight **74**, may also include the multi-relief surface **32** on the sole **56** as described above. For example, in FIGS. 10B and 12B the sole **56** may feature a multi-relief surface **32** with a negative bounce portion **34** and a cutaway portion **40** as described above. It will also be appreciated that the angle \square of the tube may be substantially parallel to the multi-relief surface **32**.

[0173] FIG. 13 illustrates how the tube **72** may be inserted into the club head **50**. A sheath **78** extending from a block **79** in the club head **50** receives the tube **72** with the weight **74**, and a fastener **80** locks the tube **72** in place within the club head **50**. The tube **72** is fastened to the outside of the club head **50** substantially flush with an outer surface **82** of the club head, as illustrated in FIG. 14.

[0174] FIG. 15 illustrates the tube **72** according to the embodiment of FIG. 13. The weight **74** is provided at an end **76** of the tube **72**. It will be appreciated that the tube **72** and weight **74** may be joined by threaded engagement, epoxy, mechanical lock or other joining method. The weight **74** may comprise tungsten or any other suitable material. The weight **74** has a mass of about 10 to 25 grams. The combined mass of the tube **72** and weight **74** is about 20 to 40 grams. Preferably, the tube **72** comprises aluminum, although any other suitable material may be used.

[0175] It is envisioned that the orientation of the tube **72** may be set during manufacture, may be modified by the user, or may be modifiable by the manufacturer or a designated fitting location. The tube **72** has a diameter td of about 0.3 to 0.5 inch and a length tl of about 2 to 3 inches. It will be appreciated that more than one tube **72** could be provided in the club head **50** at any one time as illustrated in FIG. 11, or that multiple tubes **72** with a different mass may be provided to the user or fitting location.

[0176] FIG. 16 illustrates an alternative embodiment for placement of the tube **72** within the club head **50**. In this embodiment, the tube **72** has threads **84** on both ends **86** and **88** that interlock in threaded engagement to the mating

threads **90** on a block **92** inside the club head adjacent the face **54** and threads **94** on a block **96** adjacent the skirt **60** of the club head **50**. The tube **72** is fastened to the inside of the club head **50** adjacent the face **54**. It is envisioned that the orientation of the tube **72** may be set during manufacture, may be modified by the user, or may be modifiable by the manufacturer or a designated fitting location.

[0177] FIG. 17 illustrates the tube **72** of the embodiment of FIG. 16 showing the dual threaded ends **86** and **88** of the tube that may be inserted in either direction into the club head **50** and threadedly received adjacent the face **54**. The tube **72** has a diameter td and a length tl as described above and the weight **74** and tube **72** have a similar mass as described above. The exterior of the tube **72** would align substantially flush with the outer surface **82** of the club head **50**.

[0178] FIG. 18 shows an alternative embodiment for the weight system **70** where a weight **98** may be slid along a pipe **100** provided in the club head **50**. The exterior surface **102** of the sole **56** of the club head **50** may feature a mechanism **104** to move the weight **98** along the pipe **100** to the desired location to move the c.g. for the desired ball flight as described above. Alternatively, the position of the weight **98** on the pipe **100** may be set during manufacture of the club head.

[0179] FIG. 19 features another alternative embodiment for the weight system **70**. This embodiment features two or more cavities **106** in the sole **56** of the club head **50** for receiving inserts **108**. The cavities **106** may be placed in any desired location on the club head **50**. As illustrated, the three cavities **106** are provided along an axis **O** offset from the x-axis. The cavities **106** may be aligned parallel to the x-axis or may be offset in either direction. The cavities **106** may be provided on an axis **O** offset from the x-axis by 0 to 90 degrees in either direction. The back portion **110** of the club head may feature deeper cavities **106** to mimic the angle of the tube **72** described above relative to the plane formed by the z-axis and x-axis. The inserts **108** may have different mass and may be placed in the different cavities **106** to move the c.g. to a desired location. The inserts **108** may be movable by the user, or they may be set at the time of manufacture or modifiable in a fitting environment.

[0180] FIG. 20 illustrates yet another alternative embodiment of the weighting system **70** for moving the center of gravity along the y-axis. As illustrated, the club head **50** features a vertical cavity **112** extending from the sole **56** into the hollow volume **64** of the club head. The cavity **112** may be placed in any desired location in the sole **56**, for example centered along the width of the face **54** and located more toward the back of the club head **50**, as illustrated. A weight **114** is made to fit within the cavity **112**, such that it mates securely within the cavity **112**. It will be appreciated that the weight **114** may be secured in the cavity in any suitable manner, including threaded engagement, epoxy, mechanical lock, or other joining method. As illustrated, the cavity **112** is cylindrical and the weight **114** is a corresponding cylindrical plug, although it will be appreciated that the weight **114** and mating cavity **112** may be any suitable shape and size. The weight **114** features a heavy end **116** and a lighter end **118**. The heavy or lighter end **116** and **118** may be placed closer to the sole **56** to move the c.g. to the desired location along the y-axis. It is envisioned that the orientation of the weight **114** may be set during manufacture, may be modified by the user, or may be modifiable by the

manufacturer or a designated fitting location. This embodiment may assist in isolating just one attribute, moving the c.g. along the y-axis, thereby making club fitting more straight forward.

[0181] As illustrated in FIG. 21, the movement of the c.g. is illustrated based on the construction of FIG. 13. It illustrates the movement of the c.g. along the y-axis and z-axis between a normal Titleist 904F fairway wood without a weight system, a club head 50 with the weight system 70 of FIG. 13 having the weight 74 in the back of the club head 50, and a club head 50 with the weight system 70 of FIG. 13 having the weight 74 in the front of the club head 50. FIG. 21 illustrates the relative position of the c.g. along the y-axis and z-axis for these various club heads.

[0182] As illustrated in FIG. 22, the movement of the c.g. is illustrated based on the construction of FIG. 13. It illustrates the movement of the c.g. along the y-axis and x-axis between a normal Titleist 904F fairway wood without a weight system, a club head 50 with the weight system 70 of FIG. 13 having the weight 74 in the back of the club head 50, and a club head 50 with the weight system 70 of FIG. 13 having the weight 74 in the front of the club head 50. FIG. 22 illustrates the relative position of the c.g. along the y-axis and x-axis for these various club heads.

[0183] As illustrated in FIG. 23, the movement of the c.g. is illustrated based on the construction of FIG. 16. It illustrates the movement of the c.g. along the y-axis and z-axis between a normal Titleist 904F fairway wood without a weight system, a club head 50 with the weight system 70 of FIG. 16 having the weight 74 in the back of the club head 50, and a club head 74 with the weight system 70 of FIG. 16 having the weight 74 in the front of the club head 50. FIG. 23 illustrates the relative position of the c.g. along the y-axis and z-axis for these various club heads.

[0184] As illustrated in FIG. 24, the movement of the c.g. is illustrated based on the construction of FIG. 16. It illustrates the movement of the c.g. along the y-axis and x-axis between a normal Titleist 904F fairway wood without a weight system, a club head 50 with the weight system 70 of FIG. 16 having the weight 74 in the back of the club head 50, and a club head 50 with the weight system 70 of FIG. 16 having the weight 74 in the front of the club head 50. FIG. 24 illustrates the relative position of the c.g. along the y-axis and x-axis for these various club heads. The locations of the c.g. shown in FIGS. 21-24 were calculated using a commercially available CAD (computer aided design) system.

[0185] FIG. 25 of the accompanying drawings shows a perspective view of a golf club head 250 in accordance with an alternative embodiment of the present invention. This embodiment of the present invention has one or more cavities 206 in the sole of the club head 250 for receiving a weighted insert 208. The cavity 206 in this embodiment may generally be shown in a generally elongated cylindrical shape with an opening 211 that exposes the cylindrical weighted insert 208 to the sole of the golf club head 250. The orientation of the cavity 206 and the weighted insert 208 may generally be offset at an angle from the striking face of the club head to promote the change in the center of gravity of the club head 250 along two or more axis. In order to show the offset angle of the weighted insert 208, FIG. 26 is provided showing an exploded sole view of a golf club 250 having a weighted insert 108 in accordance with this alternative embodiment of the present invention.

[0186] FIG. 26 of the accompanying drawings shows an exploded sole view of a golf club 250 having a weighted insert 208. More specifically, FIG. 26 shows the cavity 206 and the weighted insert 208 aligned along an axis O that is offset from the x-axis at an angle θ . This angle θ , similar to the prior discussion in FIG. 19, may generally be offset from the x-axis by an angle of 0 to 90 degrees in either direction, but more preferably between about 0 to about 90 degrees in the positive direction, more preferably between about 3 to about 45 degrees, and most preferably between about 5 to about 35 degrees all without departing from the scope and content of the present invention. Having the axis O offset from the x-axis is beneficial to the present invention because it allows the weighted insert 208 to alter the center of gravity of the golf club head along the x-axis and the z-axis simultaneously, depending on the orientation of the weighted insert 208. However, in order to achieve this, the weighted insert 208 must within itself, have some inherent weighting characteristics that favor such an extreme movement in the center of gravity.

[0187] The exploded view of the golf club 250 with the weighted insert 208 shown in FIG. 26 also allows the inherent weighting characteristics of the weighted insert 208 to be shown. In this figure, the weighted insert 208 may be further comprised of a heavy end 216, a lighter end 218, and a cap 219. The utilization of a heavy end 216 and a lighter end 218 in this type of weighted insert 208 maximizes the bi-directional adjustability of the elongated cylindrical weighted insert 208 to shift the center of gravity of the golf club head 250. In a first orientation, when the heavy end 216 is located close to the cap 219 near the toe end of the golf club head 250, the center of gravity of the golf club head is shifted forward and toe-ward relative to the neutral position; while in a second orientation, when the heavy end is located away from the cap 219 near the heel end of the golf club head 250, the center of gravity of the golf club head will be shifted rearward and heel-ward relative to the neutral position.

[0188] Due to the nature of the orientation of the weighted insert 208 being at an orientation that is offset from the x-axis, combined with its internal weighting components with a heavy end 216 and a lighter end 218, the length of the weighted insert 208 becomes important; as an increase in the length of the weighted insert 208 results in a greater effect on the center of gravity of the golf club head 250. Hence, in order to achieve a discernible change in the center of gravity of the golf club 250 by the change in orientation of the weighted insert 208, the length of the weighted insert 208 may generally be between about 50 mm to about 100 mm, more preferably between about 60 mm to about 90 mm, even more preferably between about 70 mm to about 80 mm.

[0189] The heavy end 216 of the weighted insert 208 may generally be comprised of a material having a relatively high density such as tungsten with a density of greater than about 10.9 g/cm³; however numerous other materials may be used without departing from the scope and content of the present invention so long as it has a density greater than the remainder of the weighted insert 208. The lighter end 218 of the weighted insert could be made out the same tungsten material as the heavy end 216, but in a smaller volume. However, alternative materials for the lighter end 218 such as steel, titanium, or any other material having a density greater than the central part of the weighted insert 208 all without departing from the scope and content of the present

invention. The central portion of the weighted insert **208** may generally be juxtaposed and placed between the heavy end and the lighter end. In order to maximize the effects of the heavy end **216** and the lighter end **218**, the central portion of the weighted insert **208** may generally be made out of a lightweight material such as carbon fiber composite, aluminum, magnesium, plastic, or any other lightweight material with a density of less than about 2.5 g/cm³ all without departing from the scope and content of the present invention.

[0190] In the embodiment shown, the threaded cap **219** may help retain the weighted insert **208** using a compressive force as shown in the cross-sectional view shown in FIG. 27. However, in alternative embodiments of the present invention, the cap **219** may be magnetic in nature to further enhance the bond between the cap **219** and the weighted insert **208**.

[0191] In order to illustrate the inner workings of the weighted insert **208** and the golf club **250**, FIG. 27 is provided here with a cross-sectional view of the golf club head **250** along cross-sectional line O, as shown previously in FIG. 26. The cross-sectional view of the golf club head **250** allows the relationship between the weighted insert **208**, the heavy end **216**, the lighter end **218**, the cap **219**, and the cavity **206** to be shown in more detail. As it can be seen in FIG. 27, the cavity **206** may generally have a chamfered portion around its terminal end, matching the geometries of the extremities of the heavier end **216** and the lighter end **218** to allow either the heavier end **216** or the lighter end **218** to sit inside the cavity **206**. Another feature worth identifying in this cross-sectional view is the difference in the construction of the heavy end **216** and the lighter end **218**. In order to create the mass difference between the heavy end **216** and the lighter end **218**, the heavy end **216** could be a dense solid piece of tungsten, while the lighter end **218** could be a hollow piece of tungsten. In alternative embodiments of the present invention, the lighter end **218** could even be made out of lightweight material such as aluminum, steel, or any other material having a density lower than tungsten all without departing from the scope and content of the present invention. In a further alternative embodiment of the present invention lighter end **218** may even be formed out of the same piece as the remainder of the weighted insert **208** without departing from the scope and content of the present invention. In order to further exaggerate the weighting effects, the central portion of the weighted insert **208** may generally be a hollow composite type material, as shown in the cross-sectional view in FIG. 27. Finally, FIG. 27 shows a threaded cap **219** to coincide with a threaded entry portion of the cavity **206** to secure the weighted insert **208** within the cavity **206**.

[0192] In an alternative embodiment of the present invention, the central portion of the weighted insert **208** could have some mass properties of its own. In one example, the central portion could have its own heavier side and a lighter side, creating even more weighting adjustments. In one setting, the heavier side **216** could be on the same side as the heavier side of the central portion, creating an ultra-heavy side and an ultra-light side to the weighted insert **208**. However, in another setting, the heavier side **216** could be paired with the lighter side of the central portion, with the weighting characteristics of the components cancelling each other out to create a more neutral setting.

[0193] In a further alternative embodiment of the present invention, the cap **219** may contain a see through window within the “cavity of the opening” to allow the user to see the terminal surface of the weighted insert **208**. The window, in one exemplary embodiment, may be made out of see through flexi-glass, however, numerous other materials may be used to provide a see through window without departing from the scope and content of the present invention. Having a see through window will allow the orientation of the weighted insert **208** to be seen without the need to disassemble the weighted insert **208** from the cavity **206**. In order to achieve this, the end surfaces of the weighted insert **208** could be painted different colors, with each of the two different colors indicating whether the lighter end **218** or the heavy end **216** is shown.

[0194] It should be noted that in this embodiment, the body portion of the weighted insert **208** is exposed to the external sole portion of the club head **250**, which allows an external component such as a sleeve **213** to be used to adjust the way the club head **250** contacts a ground plane. FIG. 28 of the accompanying drawings shows this exploded view of an alternative embodiment of the present invention wherein an additional sleeve **213** is added to the assembly, coinciding with the exposed portion **211** of the cavity **206**. The sleeve, as it can be seen, may generally circumferentially encompass the external surface of the weighted insert **208** to create the change in sole contact. In this embodiment, the sleeve **213** could be a triangular shape with each edge of the triangle having a different angle, thus creating three different methods for the golf club **250** to rest on the ground plane. However, numerous other geometries such as a cylindrical rod, a rectangular rod, an oval rod, or any other shape without departing from the scope and content of the present invention so long as it is capable of creating multiple different sole contacts. In a further alternative embodiment, the external walls of the sleeve **213** could even be tapered to create more of a change in the sole contact. The creation of different sole contact planes allows the golf club head to compensate and change for differences in the loft, lie, or even the face angle of the golf club head **250**.

[0195] Moving on to FIG. 29, a perspective sole view of a golf club head **250** in accordance with a further alternative embodiment of the present invention is shown. More specifically, the golf club head **250** shown in this embodiment is very similar to the golf club head **250** shown in FIGS. 25-28, except that the weighted insert **208** extends through the internal cavity of the golf club head **50** without being exposed to the sole portion of the golf club head. The weighted insert, although only exposed at the extremities, still have a cavity **206** at one end to allow the weighted insert to be used.

[0196] The exploded sole view of the golf club head **250** shown in FIG. 30 illustrates that the current embodiment still has the weighted insert placed along the axis O that is offset from the x-axis. The angle θ , similar to before, may generally be between about 0 to about 90 degrees in the positive direction, more preferably between about 3 to about 45 degrees, and most preferably between about 5 to about 35 degrees all without departing from the scope and content of the present invention. To illustrate the internal geometry of this alternative embodiment, a cross-sectional view is shown in FIG. 31 to provide and show how the weighted insert **208** is completely contained within the walls of the club head **250**.

[0197] FIGS. 32 and 33 shows exploded sole views of club heads 250 in accordance with further alternative embodiments of the present invention. More specifically, the club heads 250 shown here may generally be smaller sized metalwood type club heads such as a fairway wood or a hybrid type club heads 250. It should be noted here that these embodiments illustrate a very important relationship between the volume of the golf club head 250 and the angle θ of the weighted insert 208 relative to the x-axis. Because the adjustment of the center of gravity of the golf club head 250 is a very specific art form, the angle θ of placement of the weighted insert 208 along the sole is a key factor. More specifically, the relationship between the angle θ and the volume of the club head 250 could be quantified as an Angle to Volume Ratio, wherein the Angle to Volume Ratio is defined as the angle θ of the placement of the weighted insert 108 divided by the volume of the club head 250. The current invention, may generally have an Angle to Volume Ratio of between about 0.02 degrees/cc to about 0.25 degrees/cc, more preferably between about 0.05 degrees/cc to about 0.25 degrees/cc, most preferably between about 0.10 degrees/cc to about 0.20 degrees/cc.

[0198] FIG. 34 of the accompanying drawings shows an exploded view of a weighted insert 208 in accordance with an alternative embodiment of the present invention. The weighted insert 208 has a heavy end 216 piece of the weighted insert 208 and a light end 218 piece of the weighted insert 208 being created by cylindrical pieces that removably slide around a bolt 220. By reversing the orientation of the heavy end 216 piece and the light end 218 piece, the center of gravity of the weighted insert 208 could be adjusted without departing from the scope and content of the present invention. Needless to say, in alternative embodiments of the present invention there could be more than two weight members with different mass properties without departing from the scope and content of the present invention.

[0199] FIG. 35 of the accompanying drawings shows an exploded view of a weighted insert 208 in accordance with a further alternative embodiment of the present invention. The weighted insert 208 in this embodiment may be comprised of a heavy end 216 piece and a light end 218 piece, both fitting internally in a tube 221. Similar to the embodiment above, reversing the orientation of the heavy end 216 piece and the light end 218 piece can alter the center of gravity of the weighted insert 208, which can result in change of the center of gravity of the golf club head in general.

[0200] FIG. 36 of the accompanying drawings shows a cross-sectional view of a weighted insert 208 in accordance with an even further alternative embodiment of the present invention. In this embodiment of the present invention, the weighted insert 208 may contain a heavy end 216 piece that is threaded externally like a screw. The external threads of the heavy end 216 piece may then engage internal threads in the tube to allow the heavy end 216 piece to provide an infinitesimal amount of adjustment settings throughout the threaded region of the tube. The heavy end 216 piece is rotated within the tube via a tool that engages the heavy end 216 piece via an opening in one side of the weighted insert 208.

[0201] FIG. 37 of the accompanying drawings shows an exploded view of a weighted insert 208 in accordance with an even further alternative embodiment of the present inven-

tion wherein an alternative cap 219 is used. The cap 219 in this embodiment of the present invention may contain a pin 223 with a ball 224 at the end of the cap 219 to engage a "church key" shaped notch or slot 225. This ball and notch embodiment will allow the cap to be centered onto the weighted insert 208 and prevent the cap from being lost during disassembly and assembly. Although FIG. 37 only shows the ball and notch in the heavy end 216 portion of the weighted insert 208, the same geometry can be incorporated into the light end 218 to provide interchangeability of the orientation without departing from the scope and content of the present invention.

[0202] FIG. 38 of the accompanying drawings shows an exploded view of a weighted insert 208 in accordance with an even further alternative embodiment of the present invention. In this embodiment, the cap 219 is retained together with the weighted insert 208 using a snap fit 226 type mechanism that hooks onto a recessed rim 227 on the weighted insert 208 itself. In an alternative embodiment, the snap fit 226 could also be made out of a detent type mechanism that prohibits the cap from separating from the weighted insert 208 without departing from the scope and content of the present invention. It is worth noting that the weighted insert 208 has a recessed rim 227 at both the heavy end 216 and the light end 218, so the cap 219 could be placed at either extremity of the weighted insert without departing from the scope and content of the present invention.

[0203] FIG. 39 of the accompanying drawings shows an exploded view of a golf club 250 in accordance with a further alternative embodiment of the present invention. The weighted insert 208 in this embodiment be further comprised of a tube 230 to shield the weighted insert 208 from contact with any potential debris in the cavity of the golf club head 250. In this embodiment the tube 230 may generally have a diameter that is slightly bigger than the diameter of the weighted insert 208, and be snap fit into the cavity 206 without departing from the scope and content of the present invention. However, in other embodiments, the tube 230 may also be threaded into position in the cavity 206 instead of being snap fit in to provide more structural rigidity also without departing from the scope and content of the present invention. Furthermore, the tube 230 may also be glued into place without departing from the scope and content of the present invention.

[0204] In a preferred embodiment of the present invention, the tube 230 may generally be made out of a plastic type material in order to create this barrier against debris without adding additional weight to the weighted insert. However, numerous other material could be used without departing from the scope and content of the present invention so long as it provides a cover for the weighted insert.

[0205] FIG. 40 provides a close up view of the tube 230 in accordance with an embodiment of the invention as shown in FIG. 39. As it can be seen, the tube 230 has a notched opening, lengthwise along the entire length of the tube 230. This opening allows the tube to compress and reduce its diameter when it is being inserted into the cavity 206 shown in FIG. 39. When the tube decompresses thereby expanding its diameter, it will generally snap into a specific orientation within the cavity of the golf club head leaving the opening facing the crown portion of the golf club head. In an alternative embodiment of the present invention, the opening could be faced towards the back or front of the golf

club head to promote to help with the stress levels without departing from the scope and content of the present invention. Having the opening of the tube facing the crown portion of the golf club head is beneficial because most of the debris in the cavity of the golf club head tends to be located towards the sole portion of the golf club head. In addition to the debris, it is common knowledge that a type of glue is usually injected into the internal cavity of the golf club head to make final adjustments to the club head weight. This glue type material, if it comes in contact with the weighted insert **206**, may prevent it from being movable and interchangeable. In order to prevent this undesirable effect, the tube **230** cover is created to prevent such a contact.

[0206] FIG. **41** of the accompanying drawings shows an enlarged partial cross-sectional view of a weighted insert **208** in accordance with a further alternative embodiment of the present invention. In this embodiment, instead of using a snap fit or detent mechanism to secure the cap **219** to the heavy end **216** of the weighted member **208**, a clip **231** is used to secure the cap **219** to the weighted insert **208**.

[0207] FIG. **42** of the accompanying drawings shows an enlarged partial cross-sectional view of a weighted insert **208** in accordance with another alternative embodiment of the present invention. In this embodiment, the weighted insert is retained in the golf club head in tension rather than in compression as all of the previous embodiments have shown. In this embodiment, there is a slidable retainer **235** that can travel lengthwise along the weighted insert **208** to provide a stopping point for the weighted insert **208**. Once the retainer **235** is engaged, a screw can be used to secure the weighted insert in the cavity.

[0208] FIG. **43** of the accompanying drawings shows an enlarged partial cross-sectional view of a weighted insert **208** in accordance with another further alternative embodiment of the present invention. In this embodiment of the present invention, the weighted insert **208** is neither in tension nor compression. Rather, the weighted insert may have threads on both the heavy end **216** and the light end **218** to more securely attach the weighted insert **208** to the golf club head.

[0209] Low friction lubricants, materials, and coatings could be added to various portions of the weighted inserts, caps, cavities, etc described herein. Some advantages might include allowing the weighted insert to rotate freely within the cavity during impact between the golf club head and golf ball without affecting the locking mechanisms and minimizing the risk of inadvertent unlocking of the weighted insert. Examples of low friction coatings may include, for example, physical vapor deposition, teflon, molybdenum disulfide, etc.

[0210] FIG. **44** of the accompanying drawings shows a perspective view of a weighted insert **308** in accordance with another further alternative embodiment of the present invention. FIG. **45** illustrates a cross section of a golf club head **350** including the weighted insert **308** of FIG. **44**. FIG. **46** illustrates a perspective view of the weighted insert **308** of FIG. **44**. FIGS. **47** and **48** illustrate perspective views of a head locking member **330** of the golf club head **350** of FIG. **45**. In this embodiment, the weighted insert **308** has a heavy end **316** and a light end **318**. The weighted insert **308** can be inserted into a cavity **306** formed in the golf club head **350** either heavy end **316** first, as illustrated, or light end **318** first. By reversing the orientation of the weighted insert **308**, the center of gravity of the golf club head **350** can be

manipulated. The golf club head **350** can include a terminal member **320** at a terminal end **312** of the cavity **306** configured to receive the weighted insert **308**. The golf club head **350** can also include a head locking member **330** configured to receive the weighted insert **308**.

[0211] The weighted insert **308** can include an insert locking member **319** configured to lock the weighted insert **308** in the golf club head **350**. The insert locking member **319** can be configured to engage the head locking member **330**. The insert locking member **319** can include an insert locking feature **342**, as illustrated in FIG. **46**. The head locking member **330** can include a head locking feature **332** as illustrated in FIGS. **47** and **48**. The insert locking feature **342** and head locking feature **332** can be configured to lock the weighted insert **308** in the cavity **306** of the golf club head **350** by rotating the insert locking member **319** relative to the head locking member **330**. In a preferred embodiment, as illustrated in FIGS. **44-48**, the head locking member **330** and insert locking member **319** are configured to lock the weighted insert **308** with less than 180 degrees of rotation of the insert locking member **319**. In a more preferred embodiment, the head locking member **330** and insert locking member **319** are configured to lock the weighted insert **308** with less than 135 degrees of rotation. In a more preferred embodiment, the head locking member **330** and insert locking member **319** are configured to lock the weighted insert **308** with less than 90 degrees of rotation. In some embodiments, as illustrated in FIGS. **45** and **46**, the insert locking member **319** can abut the end of the weighted insert **308**, forcing it towards the terminal end of the cavity **306**. In some embodiments, it may releasably engage to each end of the weighted insert **308** similar to the cap **219** as illustrated in FIG. **38**. In other embodiments, the insert locking member **319** can be affixed to the weighted insert **308**. In some embodiments, the insert locking member **319** may be formed integrally with the weighted insert **308**. In some embodiments, the weighted insert can include an insert locking member **319** at both ends of the weighted insert **308**.

[0212] As illustrated in FIGS. **44**, **47**, and **48**, the head locking feature **332** of the head locking member **330** includes at least one slot **334** angled relative to a longitudinal axis of the weighted insert **308**, the longitudinal axis extending through the center and along the length of the weighted insert **308**. The insert locking member **319**, as illustrated in FIG. **46**, includes at least one protrusion configured to slide within the slot **334**. The insert locking member **319** also includes a tool engagement feature **309** configured to interact with a tool and allow a user to apply a torque to the insert locking member **309**. As the insert locking member **319** is rotated relative to the head locking member **330**, the protrusion slides along the slot **334**, forcing the insert locking member **319** to translate longitudinally towards the terminal member **320**, forcing the weighted insert **308** towards the terminal end **312** of the cavity **306**. Additionally, a spring **360** may be included in the cavity **306**. The spring **360** can be located near the terminal end **312** of the cavity **306** as illustrated in FIG. **45**. In additional embodiments, the spring **360** may be located in the open side **311** of the cavity **306**. In some embodiments, the spring **360** could be located in the insert locking member **319**. In another embodiment, the spring **360** could be located in a cap. The spring **360** can be compressed as the insert locking member **319** forces the weighted insert **308** towards the terminal end **312** of the cavity **306**. The head locking feature **332** can include a

locked position which locks the weighted insert 308 in the cavity 306. As illustrated in FIGS. 47 and 48, the slot 334 can include a detent 336 such that at full rotation of the insert locking member 319, the insert locking member 319 along with the weighted insert 308 is forced away from the terminal end 312 of the cavity 306 by the spring 360 a small distance, locking the protrusion of the insert locking feature 342 into the detent 336 of the slot 334 of the head locking member 330. Another way to describe the detent 336 would be that the slot 334 has an inflection point such that rotation of the insert locking member 319 initially forces the insert locking member 319 towards the terminal end 312 of the cavity 306 but once the insert locking feature 342 passes the inflection point in the slot 334, the insert locking member 319 is forced away from the terminal end 312 of the cavity 306. The insert locking member 319 is held in the locked position by the spring 360 forcing the insert locking feature 342 into the detent 336 of the slot 334, preventing rotation of the insert locking member 319 and thus preventing translation of the weight insert 308. In some embodiments, examples of springs 360 may include, coil springs, wave washer springs, conical washer springs, rubber springs, elastomer springs, as well as combinations thereof, etc.

[0213] The terminal member 320 and/or head locking member 330 can be integrated into various portions of the golf club head 350 which may include, for example, the sole (as illustrated), the skirt, the crown, etc. The terminal member 320 and/or head locking member 330 can be formed integrally in the club head 350 or it can be formed separately and affixed to the club head 350 as illustrated in FIG. 45. The terminal member 320 and/or head locking member 330 could be affixed to the golf club head 350 in a number of ways which may include, for example, welding, adhesive, threaded engagement, etc. FIG. 45 depicts the terminal member 320 and head locking member 330 incorporating male threads which engage female threads formed in the cavity 306 of the golf club head 350.

[0214] FIG. 49 of the accompanying drawings shows a perspective view of a weighted insert 408 in accordance with another further alternative embodiment of the present invention. FIG. 50 illustrates a cross section of a golf club head 450 including the weighted insert 408 of FIG. 49. FIG. 51 illustrates a perspective view of the weighted insert 408 of FIG. 49 including a spring 460 and centering member 462. FIG. 52 illustrates a perspective view of the spring 460 and centering member 462 of FIG. 51. FIG. 53 illustrates a perspective view of a spring 560. FIG. 54 illustrates a perspective view of a low friction member as well as the spring of FIG. 53.

[0215] The weighted insert 408 includes an insert locking member 419 integrated into each end of the weighted insert 408. This allows the weighted insert 408 to be flipped and reinserted into the golf club head 450 without the need to remove and reattach a removable insert locking member to the opposite end of the weighted insert 408. The head locking member 430 head locking feature 432 can include an additional track (not illustrated) to ensure the insert locking feature 442 can pass through, allowing the weighted insert 408 to be fully inserted into the cavity 406 of the golf club head 450. In another embodiment, the head locking member 430 could be centrally located in the cavity 406 and insert locking member 419 could be centrally located on the weighted insert 408, allowing a single insert locking mem-

ber 419 to interact with the head locking member 430, no matter the orientation of the weighted insert 408.

[0216] As illustrated in FIGS. 50 and 51, the cavity 406 can include a spring 460 and a centering member 462. The spring 460 can function as described in earlier embodiments. The spring 460 illustrated in FIG. 52 is composed of wave washers. Additionally, a centering member 462 can also reside in the cavity 406 to transfer the force of the spring 460 to the weighted insert 408. The centering member 462 can include a centering feature 464 which is pointed to help center the weighted insert 408 within the cavity 406 at the terminal end 412 of the cavity 406. The centering member 462 can be configured to engage the tool engagement feature 409 of the weighted insert 408. The centering member 462 can be configured to have a low coefficient of friction relative to either the weighted insert 408 or the spring 460, allowing the weighted insert 408 to rotate relative to the golf club head 450. In other embodiments, the weighted insert 408 can be centered by the inner wall of the terminal member of the cavity 406. As illustrated in FIGS. 53 and 54, the spring 560 can be non-metallic and may be comprised of rubber, elastomer, plastic, or other compressible materials. The spring 560 may also have reliefs formed in its geometry so as to ensure it does not become infinitely stiff as it is compressed inside the terminal end 412 of the cavity 406. Additionally, the weighted insert 508 and spring 560 may have tapered surfaces configured to engage one another when the weighted insert 508 is inserted into the cavity 406 of the golf club head 450. In some embodiments, as illustrated in FIG. 54, a low friction member 566 may be installed between the spring 560 and weighted insert 508 to promote low friction between the weighted insert 508 and spring 560, allowing the weighted insert 508 to rotate freely.

[0217] FIG. 55 of the accompanying drawings shows a perspective view of an insert retaining member 670. The embodiment illustrated in FIG. 59 incorporates the terminal member 620, and head locking member 630 into an insert retaining member 670. This allows the entire assembly to be permanently installed in the golf club head as a single piece, reducing assembly costs. In addition to including a head locking feature 632 to lock the weighted insert 608 in place, the insert retaining member 670 can include a sheath portion 672 (see FIG. 55) preventing debris and/or hot melt within the golf club head from contacting the weighted insert 608. In some embodiments, the sheath portion can be made of a lightweight material such as plastic and can also be made very thin. The sheath can be multi-material in that it includes a base structural portion with a plurality of apertures which is covered with a thin lightweight material sealing off the cavity from the remainder of the golf club head interior. The insert retaining member can be formed from a single piece or can be formed of a plurality of pieces. The insert retaining member can be permanently adhered to the golf club head in a number of ways which may include, for example, adhesives, welding, etc.

[0218] FIG. 56 illustrates a perspective view of a weighted insert 608 with a sliding insert locking member 619. FIG. 57 illustrates a perspective view of a sliding insert locking member 619. FIG. 58 illustrates a perspective view of the weighted insert 608 of FIG. 56. FIG. 59 illustrates a cross sectional view of the weighted insert 608 of FIG. 56 installed in the insert retaining member 670 of FIG. 55. The sliding insert locking member 619 of FIGS. 56-59 is configured to slide along the weighted insert 608 when the

orientation of the weighted insert **608** is flipped, allowing it to be located at the opening of the cavity and to engage the head locking feature **632**, locking the weighted insert **608** in place.

[0219] The weighted insert **608** can include anti-rotation features **644** configured to engage anti-rotation features **643** on the sliding insert locking member **619**, allowing torque applied to the weighted insert **608** via the tool engagement feature to be transferred to the sliding insert locking member **619**, and thus allowing the sliding insert locking member **619** to rotate relative to the head locking member **630** and lock the weighted insert **608** in place. In the embodiment illustrated in FIG. **59**, the head locking member **630** is integrated into the insert retaining member **670** and includes head locking features **632** similar to those described above.

[0220] As illustrated in FIG. **56**, the anti-rotation feature **644** of the weighted insert **608** can include rails protruding from the weighted insert **608** configured to engage the sliding insert locking member **619**. As illustrated in FIG. **57**, the anti-rotation member **643** of the sliding insert locking member **619** can include channels configured to engage the rails of the weighted insert **608**. In some embodiments, the channels and rails can resemble splines. In another embodiment, the roles could be reversed and the weighted insert **608** could include channels and the sliding insert locking member **619** could include rails. In addition, as illustrated in FIGS. **57** and **59**, the sliding insert locking member **619** can further include slide locks **680** configured to lock the sliding insert locking member **619** at the end of the weighted insert **608**. As illustrated in FIGS. **57** and **59**, the slide lock **680** can comprise one or more deflectable arms **682**, each having a shelf **684** configured to grab the end of the weighted insert **608** once it is slid to the end of the weighted insert **608**. When the user wants to slide the sliding insert locking member **619** to the opposite end of the weighted insert **608**, once a threshold slide force is applied to the sliding insert locking member **619**, the deflectable arm **682** will deflect, unlocking the sliding insert locking member **619** from the end of the weighted insert **608** and allowing it to slide towards the opposite end. The sliding insert locking member **619** can include slide locks **680** on the opposite end of the sliding insert locking member **619** configured to lock the sliding insert locking member **619** at the opposite end of the weighted insert **608**.

[0221] FIG. **60** illustrates a perspective view of an additional embodiment of the weighted insert and sliding insert locking member of FIG. **56**. FIG. **61** illustrates a cross sectional view of the weighted insert **708** and sliding insert locking member **719** of FIG. **60**. In the embodiment illustrated in FIGS. **60** and **61**, the insert locking feature **742** of the sliding insert locking member **719** comprises threads similar to the cap **219** illustrated in FIG. **38** configured to engage threads located on the head locking member (not illustrated), as opposed to the head locking features and insert locking features described herein.

[0222] FIG. **62** illustrates a perspective view of an additional embodiment of a weighted insert **808**. FIG. **63** illustrates a perspective view of components of the weighted insert **808** of FIG. **62**. FIG. **64** illustrates a cross sectional view of the weighted insert **808** of FIG. **62**. The weighted insert **808** illustrated in FIGS. **62-64** contains a spring **860** internally, and does not require an additional spring in the cavity of the golf club head. The weighted insert **808** includes a first portion **874** and a second portion **875**, the

second portion **875** configured to slide longitudinally along the axis of the weight insert **808**, relative to the first portion **874**. In one embodiment, as illustrated in FIG. **64**, the weight insert **808** may further comprise a third portion **876**. The first portion **874** can be affixed to the third portion **876**. The third portion **876** can include a sliding bore **861** configured to slidably receive the second portion **875**. The second portion **875** can be configured to slide within the sliding bore **861** of the third portion **876**. Additionally, the sliding bore **861** can include a spring **860**, configured to force the second portion **875** away from the first portion **874**. Additionally, the second portion **875** can include a slide stop **878**, configured to limit the travel of the second portion **875** relative to the third portion **876** once assembled. In an additional embodiment the first portion **874** may be formed integrally with the third portion **876**.

[0223] FIG. **65** illustrates a perspective view of an additional embodiment of a weighted insert **908**. FIG. **66** illustrates a cross sectional view of the weighted insert **908** of FIG. **65**. Similar to the weight insert **808** of FIGS. **62-64**, the weight insert **908** of FIGS. **65** and **66** does not require an additional spring as it is configured to decrease and increase in length when being used in conjunction with the other head locking features and insert locking features described herein. The weighted insert **908** of FIGS. **65** and **66** includes a first portion **974** at one end of the weight insert **908** and a second portion **975** at the opposite end of the weight insert **908**. The weight insert also includes a third portion **976** affixed to both the first portion **974** and the second portion **975**. The third portion **976** is configured to deform in length along the longitudinal axis of the weight insert **908** as the ends of the weight insert **908** are forced together. As illustrated in FIGS. **65** and **66**, the third portion **976** can include a spiral cut along at least a portion of its length, allowing the third portion **978** to act as a spring **960**. Additionally, the weight insert **908** can include a fourth portion **977** configured to slide within the third portion **976**, preventing any deformation that is not along the axis of the weight insert **908**, such as buckling. In another embodiment, the fourth portion **977** could be located around the third portion **976**.

[0224] Some of the embodiments described herein require compression of either the weighted insert or compression of the weighted insert along with a spring. In additional embodiments, the head locking feature and insert locking feature may load the weighted insert in tension rather than compression, locking the weighted insert in place. FIG. **76** illustrates a perspective view of an additional embodiment of a weighted insert **1308**. FIG. **77** illustrates a cross sectional view of the weighted insert **1308** of FIG. **76**. The weighted insert **1308** includes a first portion **1374** at one end of the weighted insert **1308** and a second portion **1375** at the opposite end of the weighted insert **1308**. The weight insert also includes a third portion **1376** affixed to both the first portion **1375** and second portion **1375**. The third portion **1376** is configured to deform in length along the longitudinal axis of the weighted insert **1308** as the ends of the weight insert **1308** are pulled apart. As illustrated in FIGS. **76** and **77**, the third portion **1376** can include an accordion like structure, acting like a spring. The weighted insert **1308** could include a fourth portion around the outside of the first portion **1374**, second portion **1375**, and third portion **1376**, configured to prevent any deformation that is not along the axis of the weight insert **1308**, such as buckling (not illustrated). In a tension loaded weighted insert such as

the weighted insert **1308** illustrated in FIGS. **76** and **77**, the channels of the head locking feature may be oriented at such an angle, that rotating the weighted insert **1308** relative to the golf club head would stretch the weighted insert **1308**. Additionally, the detents may be configured such that the tension in the weighted insert **1308** in a locked position helps to prevent the weighted insert **1308** from coming dislodged from the detent during play. The weighted insert **1308** can also include insert locking features **1319**, preferable at both ends of the weighted insert **1308**. The locking features **1319** can include protrusions **1342** configured to interact with a head locking feature.

[0225] FIG. **67** illustrates a perspective view of an additional embodiment of a weight insert **1008**. FIG. **68** illustrates a perspective view of an insert retaining member **1070** configured to receive the weight insert **1008** of FIG. **67**. FIG. **69** is an end view of the insert retaining member **1070** of FIG. **68**. FIG. **70** is a cross sectional view of the weight insert **1008** of FIG. **67** installed in the insert retaining member **1070** of FIG. **68**. The weight insert **1008** is configured to rotate into a locked position without the need for the weighted insert **1008** to translate longitudinally within the cavity of the golf club head. The insert locking feature **1042** of the weighted insert **1008** includes at least one protrusion. As illustrated in FIG. **67**, the insert locking feature **1042** includes at least one pair of protrusions with a relief **1046** between them. The protrusions can be shaped like a rail, extending in a direction substantially parallel to the axis of the weighted insert **1008**. The insert retaining member **1070** includes at least one channel **1085** to receive the insert locking feature **1042** as it is installed in the insert retaining member **1070**. Additionally, the insert retaining member **1070** includes a corresponding head locking feature **1032**. The head locking feature **1032** of the insert retaining member **1070** includes a protrusion **1087** configured to engage the relief **1046** of the insert locking feature **1042**. The protrusion **1087** of the head locking feature **1032** can be formed on a deflectable arm **1083**, which deflects as the weighted insert **1008** is rotated, and then snaps back as the protrusion **1087** of the head locking feature **1032** engages the relief **1046** of the insert locking feature **1042**, locking the weighted insert **1008** in the golf club head. As illustrated in FIG. **67**, the weighted insert **1008** can include insert locking features **1042** at each end of the weighted insert **1008**. In another embodiment the insert locking features **1042** may be located centrally on the weighted insert **1008**. In another embodiment, the insert locking features **1042** may be on a sliding insert locking member.

[0226] FIG. **71** illustrates an additional embodiment of a weighted insert **1108**. FIG. **72** illustrates a perspective view of an insert retaining member **1170** configured to receive the weighted insert **1108** of FIG. **71**. The weighted insert **1108** is similar to the weighted insert of FIGS. **67-70** however the protrusions and reliefs of the insert locking feature **1142** extend in a direction oblique to longitudinal axis of the weighted insert **1108**. Additionally, the protrusions **1187** of the head locking features **1132** are angled as well to engage the insert locking features **1142**.

[0227] FIG. **73** illustrates an additional embodiment of an insert retaining member **1270**. FIG. **74** illustrates an additional embodiment of a weighted insert **1208** configured to reside in the insert retaining member **1270** of FIG. **73**. FIG. **75** illustrates a cross sectional view of the insert retaining member **1270** and weighted insert **1208** of FIGS. **73** and **74**.

The weighted insert **1208** is similar to the weighted inserts of FIGS. **67-72**, with a few key differences. Rather than a pair of protrusions, the insert locking feature **1242** includes single protrusion without a relief. Additionally, the ends of the protrusions are tapered, allowing them to contact a corresponding taper of the head locking feature **1232** of the insert retaining member, further limiting longitudinal movement of the weighted insert **1208** inside the club head when the weighted insert **1208** is in a locked position. Additionally, rather than the deflectable arms **1282** of the head locking features **1232** being aligned perpendicular to the longitudinal axis of the weighted insert **1208** like in earlier embodiments, the deflectable arms **1282** are aligned oblique to the longitudinal axis of the weighted insert **1208** such that as the weighted insert **1208** is rotated into a locked position, the insert locking feature **1242** and head locking feature **1232** not only restrict rotation of the weighted insert **1208** relative to the insert retaining member **1270**, but also force the weighted insert **1208** towards the terminal end **1212** of the insert retaining member **1270**. This feature further reduces the chance of the weighted insert **1208** moving within the club head once in a locked position and prevents any rattling when the club head strikes a golf ball.

[0228] In a preferred embodiment, the head locking features and insert locking features described herein are configured to lock the weighted insert with less than 180 degrees of rotation of the insert locking member. In a more preferred embodiment, the head locking features and insert locking features are configured to lock the weighted insert **308** with less than 135 degrees of rotation. In a more preferred embodiment, the head locking features and insert locking features are configured to lock the weighted insert **308** with less than 90 degrees of rotation. Additionally, the head locking features and insert locking features described herein could be incorporated into other embodiments, for example replacing the threads of the cap **219** of the embodiment illustrated in FIG. **38**.

[0229] In some embodiments, the weighted inserts described herein may not have a heavy end and a lighter end, but may have a CG located centrally along their length. Such a neutral weighted insert could make for even more CG location options for the golf club head if used as an option in addition to a conventional weighted insert with a heavy end and a lighter end.

[0230] The insert locking features described and illustrated herein have generally been offset from the ends of the weighted insert. In some embodiments, not illustrated the insert locking features can be located immediately adjacent the ends of the weighted insert. Additionally, the slots of the head locking features described and illustrated herein have generally allowed for locking of the weighted insert inside the golf club head strictly via rotation of the insert locking member relative to the golf club head. In some embodiments, not illustrated, locking or unlocking of the weighted insert can be achieved with not only rotation of the insert locking member, but also via force along the longitudinal axis of the weighted insert exerted on the insert locking member via the tool. Additionally, the weighted inserts described and illustrated herein generally have a lightweight end and a heavy end such that their center of gravity is offset from their dimensional center. In additional embodiments, the weighted inserts may not have an offset center of gravity. The weighted insert may have two heavy ends or two light ends for example. In additional embodiments, the insert

locking members described and illustrated herein may include a seal to prevent any fluids or particles from entering or leaving the cavity and/or golf club head.

[0231] FIG. 78 of the accompanying drawings illustrates a perspective view of one embodiment of a golf club head 2050. FIG. 79 illustrates a perspective view of the bottom of the golf club head 2050 of FIG. 78 including one embodiment of a weight retention system 2090 including a first weight retention member 2091 and a second weight retention member 2092. FIG. 80 illustrates a perspective view of one embodiment of the weight retention system 2090 of FIG. 79. The golf club head 2050 includes a body having a striking face 2054, a sole 2056, a crown 2058, a skirt 2060, and a hosel 2062. The body defines a hollow interior 2064 (See FIGS. 93 and 94). The golf club head 2050 includes a weight retention system 2090 configured to receive a weighted insert 408. The weighted insert 408 is configured such that its center of gravity can be manipulated, by, for example, reversing the orientation of the weighted insert 408. The weight retention system 2090 can be configured to receive any of the weighted inserts described herein, although the weight retention system 2090 illustrated in FIGS. 79-83 and 94 is configured to retain a weighted insert 408 as illustrated in FIG. 86, also illustrated in FIG. 49 and described in further detail above.

[0232] The weight retention system 2090 can include a first weight retention member 2091 and a second weight retention member 2092 as illustrated in FIG. 79. The weight retention system can include a cavity configured to receive the weighted insert 408. The first weight retention member 2091 includes an opening 2011 to receive the weighted insert 408. The second weight retention member 2092 can comprise the terminal end 2012 of the cavity receiving the weighted insert 408. In some embodiments, the first weight retention member 2091 can be substantially similar to the head locking member 330 as described above and as illustrated in FIGS. 44, 45, 47 and 48.

[0233] FIG. 81 illustrates a perspective view of the weight retention system 2090 of FIG. 80 including a third weight retention member 2070. FIG. 82 illustrates an additional perspective view of the weight retention system 2090 of FIG. 81. FIG. 83 illustrates an additional perspective view of the weight retention system 2090 of FIG. 81. In the illustrated embodiments, the first weight retention member 2091 is formed separately from the second weight retention member 2092. In a preferred embodiment, the first weight retention member 2091 can be connected to the second weight retention member 2092 via a third weight retention member 2070. FIG. 84 illustrates a perspective view of one embodiment of the insert retaining member of FIG. 81. FIG. 85 illustrates a cross-sectional view of the third weight retention member of FIG. 81. The third weight retention member 2070 can be substantially similar to the insert retaining member 670 described herein and illustrated for example, in FIG. 55. The first weight retention member 2091 has an outer surface 2095 exposed to the exterior of the golf club head 2050 and an interior surface 2097. Similarly, the second weight retention member 2092 has an outer surface 2096 exposed to the exterior of the golf club head 2050 and an interior surface 2098.

[0234] The third weight retention member 2070 can include threads or another method of locking the third weight retention member 2070 to the second weight retention member 2092. The second weight retention member

2092 can include a terminal portion 2092 configured to receive and engage the terminal end of the third weight retention member 2070. Additionally, the third weight retention member 2070 can include a head locking feature 2032 as illustrated in FIGS. 84 and 85. In some embodiments, the head locking feature 2032 is substantially similar to the head locking feature 632 illustrated in FIG. 55. The head locking feature 2032 illustrated in FIGS. 84 and 85 includes at least one slot 2034 and at least one detent 2036 similar to the head locking feature 332 illustrated in FIGS. 47 and 48. Additionally, the head locking feature 2032 includes at least one longitudinal slot 2035 to allow a weighted insert 408 such as the one illustrated in FIG. 86, with a plurality of protrusions 442, to be inserted into the weight retention system 2090 in a plurality of orientations, by allowing at least one protrusion 442 to slide along the longitudinal slot until it reaches the terminal end 2012 where it can rotate freely within a terminal recess 2037. Additionally, the third weight retention member 2070 can include reliefs 2073 for weight savings.

[0235] FIG. 87 illustrates a perspective view of the bottom of the golf club head 2050 of FIG. 78 including the third weight retention member of FIG. 81. FIG. 88 illustrates an additional perspective view of the golf club head 2050 of FIG. 87. FIG. 89 illustrates an additional perspective view of the golf club head 2050 of FIG. 87. FIG. 90 illustrates an additional perspective view of the golf club head 2050 of FIG. 87. FIG. 91 illustrates a perspective view of the bottom of the golf club head 2050 without the weight retention system. FIG. 92 illustrates an additional perspective view of the golf club head 2050 of FIG. 91. FIG. 93 illustrates a cross-sectional view of the golf club head 2050 of FIG. 91. FIG. 94 illustrates a cross-sectional view of the golf club head 2050 of FIG. 79. FIG. 95 illustrates a cross-sectional view of the golf club head 2050 of FIG. 87.

[0236] In the illustrated embodiments, the first weight retention member 2091 is formed separately from the second weight retention member 2092. The third weight retention member 2070 can be formed separately from both the first weight retention member 2091 and second weight retention member 2092 as illustrated. In an additional embodiment, the third weight retention member 2070 can be formed integrally with the first weight retention member 2091. In another additional embodiment, the third weight retention member 2070 can be formed integrally with the second weight retention member 2092. In a preferred embodiment, the third weight retention member 2070 is affixed to the first weight retention member 2091 and second weight retention member 2092 after the first weight retention member 2091 and second weight retention member 2092 have been affixed to the golf club head 2050.

[0237] As illustrated in FIGS. 91-93, the golf club head 2050 includes a first receptacle 3001 and a second receptacle 3002. The first receptacle 3001 is configured to receive and permanently couple to the first weight retention member 2091 and the second receptacle 3002 is configured to receive and permanently couple to the second weight retention member 2092. Each receptacle 3001, 3002 can include a shelf 3005, 3006 which forms an exterior surface recessed towards the interior 2064 of the golf club head 2050 relative to the outer surface of the golf club head 2050. As illustrated in FIGS. 91-93, the shelves 3005, 3006 are recessed relative to the sole 2056. In other embodiments, not illustrated, the receptacles may not be recessed. The receptacles 3001, 3002 can include perimeter walls 3003, 3004 connecting the

shelves **3005**, **3006** to the golf club head **2050**. The receptacles **3001**, **3002** can also include apertures **3007**, **3008** exposing the golf club head interior **2064** to the exterior of the golf club head when the weight retention members **2091**, **2092** are not installed.

[0238] As illustrated in FIG. 94, the weight retention members **2091**, **2092** can be configured to reside in their respective receptacles **3001**, **3002**. The interior surfaces **2097**, **2098** of the weight retention members **2091**, **2092** can be configured to abut the shelves **3005**, **3006** of the receptacles **3001**, **3002**. Additionally, the perimeter walls **3003**, **3004** surround at least a portion of the weight retention members **2091**, **2092** helping to hold them in place. In a preferred embodiment, the interior surfaces **2097**, **2098** are permanently affixed to the receptacles **3001**, **3002**. Affixation can be achieved via adhesives, for example. The receptacles **3001**, **3002** allow for the weight retention members **2091**, **2092** to be installed such that the outer surfaces **2095**, **2096** are substantially flush with the outer surface of the golf club head **2050**, or more specifically the sole **2056**, as illustrated in FIGS. 86-88.

[0239] As illustrated in FIG. 95, once the first weight retention member **2091** is installed in the first receptacle **3001** and the second weight retention member **2092** is installed in the second receptacle **3002**, the third weight retention member **2070** can be installed through the opening of the **2011** of the first weight retention member **2091** and engage the second weight retention member **2092**. In some embodiments, the third weight retention member **2070**, can couple the first weight retention member **2091** to the second weight retention member **2092**, further increasing the strength of the weight retention system **2090**. In some embodiments, and as illustrated in FIGS. 91-95, at least a portion of the shelf **3005** of the first receptacle **3001** can be inclined relative to at least a portion of the shelf **3006** of the second receptacle **3002**, such that installation and engagement of the third weight retention member **2070** clamps the first weight retention member **2091** towards the second weight retention member **2092** and thus the first weight retention member **2091** against the first shelf **3005** and the second weight retention member **2092** against the second shelf **3006**.

[0240] Forming the weight retention members **2092**, **2092**, **2070** separately from the golf club head **2050** and then permanently affixing them to the golf club head **2050**, has advantages which include, for example, ease of manufacture, reduced weight, etc. The first weight retention member **2091**, second weight retention member **2092** and third weight retention member **2070** can be made from a variety of lightweight materials which may include, for example, plastic, composite, aluminum, magnesium, fiber reinforced plastic, fiberglass reinforced plastic, carbon fiber reinforced plastic, resin, polymer, urethane, thermoplastics, engineering thermoplastics, polyetheretherketone, nylon, fiber impregnated nylon, etc. It is preferable the lightweight materials have a lower density than the material from which the majority of the golf club head **2050** is formed, which may include for example, titanium or steel. As illustrated in FIG. 94, it can be advantageous to have distance D, defined as the shortest distance between the first weight retention member **2091** and the second weight retention member **2092**, to be greater than 5 millimeters.

[0241] In an alternative embodiment, not explicitly illustrated, the body of the golf club head can incorporate the

second weight retention member into its construction. Such an embodiment could include a combination of the terminal end **412** illustrated in FIG. 50 with the first weight retention member **2091** and third weight retention member **2070** illustrated in FIGS. 79-83 and the first receptacle **3001** illustrated in FIG. 91.

[0242] FIG. 96 illustrates a bottom view of a golf club head **2050** including an additional embodiment of a weight retention system **4090**. FIG. 97 illustrates a perspective view of the golf club head **2050** of FIG. 96. FIG. 98 illustrates an additional perspective view of the golf club head **2050** of FIG. 96. FIG. 99 illustrates an additional perspective view of the golf club head **2050** of FIG. 96.

[0243] The golf club head **2050** includes one embodiment of a weight retention system **4090** configured to receive a weighted insert **408** (see FIG. 86). The weight retention **4090** system can alternatively be configured to receive any of the other weighted inserts described herein. The weight retention system **4090** can include a weight retention member **4092**. As illustrated in FIGS. 96-99, the weight retention system **4090** can be located on the sole **2056** of the golf club head **2050**. The weight retention system includes an opening **4011** and a terminal end **4012**. The opening **4011** is configured to receive the weighted insert **408** which then slides into the cavity **4013** of the weight retention system **4090** towards the terminal end **4012**. The weight retention member **4092**, much like the weight retention members **2091** and **2092** of FIGS. 87-90, can be formed separately from the golf club head **2050** of a lightweight material and affixed to the golf club head **2050**.

[0244] FIG. 100 illustrates a perspective view of the golf club head **2050** of FIG. 96 without the weight retention member. FIG. 101 illustrates an additional perspective view of the golf club head **2050** of FIG. 100. The golf club head **2050** can include a receptacle **5002** configured to receive and permanently couple the weight retention member **4092** to the golf club head **2050**. In some embodiments, the receptacle can include an aperture **5008** exposing the golf club head interior to the exterior of the golf club head **2050** when the weight retention member **4092** is not installed. The receptacle **5002** can include a shelf **5006** configured to abut a portion of the weight retention member **4092**, the shelf **5006** being recessed from the outer surface of the golf club head. At least a portion of the shelf **5006** can be substantially parallel to the sole surface **2057** of the golf club head. The sole surface **2057** being the external surface of the sole **2056**. In some embodiments, as illustrated in FIGS. 100 and 101, the shelf **5006** can be a curved surface. The receptacle can include a shelf **5006** at each end of the receptacle, more specifically, the receptacle can include a shelf **5006** at the opening end of the receptacle **5002** and a shelf **5006** at the terminal end of the receptacle **5002**. In another embodiment, the receptacle **5002** may not include an aperture and the shelf **5006** may run the length of the receptacle **5002**.

[0245] Additionally, the receptacle can include perimeter walls **5004** configured to retain the weight retention member **4092**. The perimeter walls **5004** can be formed at an angle to the sole surface **2057**. As illustrated in FIGS. 100 and 101, the perimeter walls **5004** can be substantially perpendicular to the sole surface **2057**. The receptacle **5002** can include a perimeter wall **5004** on each side of the receptacle **5002**. The perimeter walls **5004** can be substantially parallel to each other.

[0246] FIG. 102 illustrates a perspective view of one embodiment of a weight retention member 4092. FIG. 103 illustrates an additional perspective view of the weight retention member 4092 of FIG. 102. The weight retention member 4092 can include abutment surfaces including an interior surface 4098 configured to abut the shelf 5006 and side walls 4094 configured to abut the perimeter walls 5004 of the receptacle 5002. Additionally, the weight retention member 4092 can include locating features 4099 to accurately locate the weight retention member 4092 within the receptacle 5002. The locating features 4099 can be protrusions configured to abut the ends of the aperture 5008 of the receptacle 5002. Additionally, the weight retention member 4092 can include an external portion 4096 configured to be visible from the exterior of the golf club head 2050. The external portion 4096 can be substantially flush with the sole surface 2057 of the golf club head. In other embodiments, the external portion 4096 can protrude proudly from the sole surface 2057.

[0247] FIG. 104 illustrates an end view of the weight retention member 4092 of FIG. 102. FIG. 105 illustrates a cross sectional view of the weight retention system 4090. FIG. 106 illustrates an additional cross sectional view of the weight retention system 4090. In some embodiments the weight retention system 4090 can also include an additional weight retention member 4070, as illustrated in FIGS. 105, and 106, similar to the third weight retention member 2070 illustrated in FIGS. 84 and 85. In some embodiments, the additional weight retention member 4070 can be formed separately from the weight retention member 4092. In other embodiments, the additional weight retention member 4070 can be formed integrally with the weight retention member 4092. The weight retention system 4090 can further include a head locking feature 2032 configured to lock and retain the weighted insert 408 within the weight retention system 4090.

[0248] In additional embodiments (not illustrated), a golf club head can include a plurality of weight retention systems so that the golf club head can have one more weighted inserts releasably affixed to the golf club head. The weight members can be selectively installed in a preferred weight retention system or even swapped between weight retention systems to optimize the center of gravity for a player's swing. In other embodiments each weight retention system can be configured to couple a plurality of weighted inserts to the golf club head.

[0249] In describing the present technology herein, certain features that are described in the context of separate implementations also can be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also can be implemented in multiple implementations separately or in any suitable sub combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub combination or variation of a sub combination.

[0250] Various modifications to the implementations described in this disclosure may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, the claims

are not intended to be limited to the implementations shown herein, but are to be accorded the widest scope consistent with this disclosure as well as the principle and novel features disclosed herein.

We claim:

1. A golf club head comprising:

a body having a face, a sole, a crown, and a skirt joining said face, sole and crown;

a hollow golf club interior within said body;

said body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face;

said body having a center of gravity;

wherein said body comprises a receptacle, said receptacle comprising an aperture;

a weight retention system configured to receive a weighted insert, said weight retention system comprising a weight retention member affixed to said receptacle, said weight retention member comprising an opening on one end of said weight retention member configured to receive said weighted insert, at least a portion of said weight retention member extending through said first aperture into said hollow golf club interior;

wherein said weighted insert comprises a heavy end and a lighter end, wherein said weight retention member is configured to receive said weighted insert in both a first configuration and a second configuration, wherein said first configuration comprises said heavy end of said weighted insert adjacent said opening of said weight retention member and said second configuration comprises said lighter end of said weighted insert adjacent said opening of said weight retention member;

wherein at least a portion of said receptacle is located on said sole;

wherein said weight retention member is permanently affixed to said receptacle;

wherein said receptacle includes a pair of perimeter walls, each of said perimeter walls are substantially perpendicular to said sole adjacent said perimeter walls, said pair of perimeter walls separated by said aperture, said pair of perimeter walls substantially parallel to one another;

wherein said receptacle includes a pair of shelves connecting said pair of perimeter walls at each end of said aperture, wherein said shelves are substantially curved, said pair of shelves recessed towards said hollow golf club head interior from said sole;

wherein said weight retention member abuts said pair of perimeter walls and said pair of shelves;

wherein a majority of said body, by weight, is formed from a first material having a first density;

wherein said weight retention member is formed from a second material, said second material having a second density and wherein said second density is less than said first density.

2. A golf club head comprising:

a body having a face, a sole, a crown, and a skirt joining said face, sole and crown;

a hollow golf club interior within said body;

said body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face;

said body having a center of gravity;

wherein said body comprises a receptacle, said receptacle comprising an aperture;

a weight retention system configured to receive a weighted insert, said weight retention system comprising a weight retention member affixed to said receptacle, said weight retention member comprising an opening on one end of said weight retention member configured to receive said weighted insert;

wherein at least a portion of said receptacle is located on said sole;

wherein said weight retention member is permanently affixed to said receptacle;

wherein said receptacle includes a pair of perimeter walls, each of said perimeter walls formed at an angle relative to said sole adjacent said receptacle, said pair of perimeter walls separated by said aperture;

wherein said receptacle includes a pair of shelves connecting said pair of perimeter walls at each end of said aperture, said pair of shelves recessed towards said hollow golf club head interior from said sole;

wherein said weight retention member abuts said pair of perimeter walls and said pair of shelves;

wherein a majority of said body, by weight, is formed from a first material having a first density;

wherein said weight retention member is formed from a second material, said second material having a second density and wherein said second density is less than said first density.

3. The golf club head of claim 2, wherein each of said perimeter walls are formed at an angle of at least 45 degrees relative to said sole adjacent said receptacle.

4. The golf club head of claim 3, wherein each of said perimeter walls are substantially perpendicular to said sole adjacent said receptacle.

5. The golf club head of claim 2, wherein at least a portion of said receptacle are located on said skirt.

6. The golf club head of claim 2, wherein at least a portion of said weight retention member extends through said aperture into said hollow golf club interior.

7. The golf club head of claim 2, wherein said weight retention member is formed of fiber reinforced plastic.

8. The golf club head of claim 2, wherein said weighted insert comprises a heavy end and a lighter end, wherein said weight retention member is configured to receive said weighted insert in both a first configuration and a second configuration, wherein said first configuration comprises said heavy end of said weighted insert adjacent said opening of said weight retention member and said second configuration comprises said lighter end of said weighted insert adjacent said opening of said weight retention member.

9. The golf club head of claim 2, wherein said weight retention system further comprises a head locking feature configured to lock said weighted insert in said weight retention system.

10. The golf club head of claim 2, wherein said weight retention member further comprises a pair of sidewalls, said pair of sidewalls substantially parallel to one another, said pair of sidewalls configured to abut said perimeter walls of said receptacle.

11. A golf club head comprising:

a body having a face, a sole, a crown, and a skirt joining said face, sole and crown;

a hollow golf club interior within said body;

said body having a coordinate system with an x-axis located horizontal to the club face, a y-axis located vertical to the club face, and a z-axis located through the club face;

said body having a center of gravity;

wherein said body comprises a receptacle;

a weight retention system configured to receive a weighted insert, said weight retention system comprising a weight retention member affixed to said receptacle, said weight retention member comprising an opening on one end of said weight retention member configured to receive said weighted insert;

wherein said weighted insert comprises a heavy end and a lighter end, wherein said weight retention member is configured to receive said weighted insert in both a first configuration and a second configuration, wherein said first configuration comprises said heavy end of said weighted insert adjacent said opening of said weight retention member and said second configuration comprises said lighter end of said weighted insert adjacent said opening of said weight retention member;

wherein said weight retention member is permanently affixed to said receptacle;

wherein said receptacle includes a pair of perimeter walls, each of said perimeter walls formed at an angle relative to said sole;

wherein said receptacle includes a pair of shelves connecting said pair of perimeter walls at each end of said receptacle, said pair of shelves recessed towards said hollow golf club head interior from said sole;

wherein said weight retention member abuts said pair of perimeter walls and said pair of shelves;

wherein a majority of said body, by weight, is formed from a first material having a first density;

wherein said weight retention member is formed from a second material, said second material having a second density and wherein said second density is less than said first density.

12. The golf club head of claim 11, wherein each of said perimeter walls are formed at an angle of at least 45 degrees relative to said sole adjacent said receptacle.

13. The golf club head of claim 12, wherein each of said perimeter walls are substantially perpendicular to said sole adjacent said receptacle.

14. The golf club head of claim 11, wherein at least a portion of said receptacle are located on said skirt.

15. The golf club head of claim 11, wherein at least a portion of said weight retention member extends through said aperture into said hollow golf club interior.

16. The golf club head of claim 11, wherein said weight retention member is formed of fiber reinforced plastic.

17. The golf club head of claim 11, wherein said weight retention system further comprises a head locking feature configured to lock said weighted insert in said weight retention system.

18. The golf club head of claim 11, wherein said weight retention member further comprises a pair of sidewalls, said

pair of sidewalls substantially parallel to one another, said pair of sidewalls configured to abut said perimeter walls of said receptacle.

* * * * *