



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2321024 C 2009/03/03

(11)(21) **2 321 024**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(22) Date de dépôt/Filing Date: 2000/09/27
(41) Mise à la disp. pub./Open to Public Insp.: 2001/03/30
(45) Date de délivrance/Issue Date: 2009/03/03
(30) Priorité/Priority: 1999/09/30 (US09/409,528)

(51) Cl.Int./Int.Cl. *A61L 15/46* (2006.01),
A61L 15/18 (2006.01)
(72) Inventeur/Inventor:
MOSCHEROSCH, MICHAEL, US
(73) Propriétaire/Owner:
MCNEIL-PPC, INC., US
(74) Agent: SMART & BIGGAR

(54) Titre : CONTROLE DE L'ODEUR D'ARTICLES ABSORBANTS
(54) Title: ODOR CONTROL IN ABSORBENT ARTICLES

(57) Abrégé/Abstract:

A method of odor control in disposable, absorbent articles is provided using odor control additives comprising phosphorous-containing compounds.



ABSTRACT

A method of odor control in disposable, absorbent articles is provided using odor control additives comprising phosphorous-containing compounds.

ODOR CONTROL IN ABSORBENT ARTICLES

The present invention relates to odor control in disposable, absorbent articles using phosphorous-containing compounds.

5

Background of the Invention

A variety of additives are currently used in disposable, absorbent articles for reducing or controlling malodors associated with body exudates. It is known that many malodors associated with body exudates are due to the microbial decomposition of lipids, particularly triglycerides and phospholipids, into fatty acids. U.S. Patent No. 4,356,190, for example, discloses the use of compounds such as EDTA to inhibit the formation of such fatty acids. Other materials as diverse as zeolites, baking soda, compounds containing active carbon, and charcoal have also been employed in absorbent articles for odor control. See for instance, U.S. Patent No. 5,306,487.

15

U.S. Patent No. 5,567,231 relates to a deodorant comprising 5 to 100 weight % of a calcium phosphate compound having a Ca/P molar ratio of 0.8 to 2.0. Materials such as filter sheets incorporating such a compound are taught to have improved adsorptivity to a wide variety of substances, such as oil-soluble substances, odor substances, viruses, etc.

Applicant has now discovered that malodors associated with the microbial decomposition of lipids in body exudates absorbent articles can be reduced or eliminated by incorporating into such absorbent articles an odor control additive comprising at least one water soluble salt containing an anion selected from the group consisting of $P_2O_7^{4-}$, $P_3O_9^{3-}$, and $P_3O_{10}^{5-}$. Alternatively, such odor control additive may comprise a water soluble compound of the formula $(APO_3)_n$, wherein A is a Group 1 element and n is 4 to 50.

25

Summary of the Invention

The present invention provides a disposable, absorbent article comprising a liquid permeable cover and an absorbent core, wherein said absorbent article contains an odor control additive comprising at least one water soluble salt containing an anion selected from the group consisting of $P_2O_7^{4-}$, $P_3O_9^{3-}$, and $P_3O_{10}^{5-}$.

30

The present invention also provides a disposable, absorbent article comprising a liquid permeable cover and an absorbent core, wherein said absorbent article contains an

74484-102

odor control additive comprising a water soluble compound of the formula $(\text{APO}_3)_n$, wherein A is a Group 1 element and n is 4 to 50.

The present invention further provides methods of
5 reducing malodors in a disposable, absorbent article, comprising incorporating into the absorbent article an odor control additive comprising at least one water soluble salt containing an anion selected from the group consisting of $\text{P}_2\text{O}_7^{4-}$, $\text{P}_3\text{O}_9^{3-}$, and $\text{P}_3\text{O}_{10}^{5-}$, or a water soluble compound of the
10 formula $(\text{APO}_3)_n$, wherein A is a Group 1 element and n is 4 to 50.

According to one aspect of the present invention, there is provided a disposable, absorbent article comprising a liquid permeable cover, an absorbent core and an odor
15 control additive, wherein the odor control additive is a water soluble salt containing an anion selected from the group consisting of $\text{P}_3\text{O}_9^{3-}$ and $\text{P}_3\text{O}_{10}^{5-}$ and a cation containing a Group 1 element or ammonium, wherein the cover comprises the odor control additive in an amount of 0.0155 to 1.55 mg
20 per mm^2 of the cover.

According to another aspect of the present invention, there is provided a method of reducing malodors in a disposable, absorbent article, comprising incorporating an odor control additive in an amount from 0.0155 to 1.55 mg
25 per mm^2 of layer into the absorbent article, wherein the absorbent article comprises a liquid permeable cover and an absorbent core, wherein the odor control additive is a water soluble salt containing an anion selected from the group consisting of $\text{P}_3\text{O}_9^{3-}$ and $\text{P}_3\text{O}_{10}^{5-}$ and a cation containing a
30 Group 1 element or ammonium.

74484-102

According to yet another aspect of the present invention, there is provided a method of reducing malodors in a disposable, absorbent article, comprising incorporating into the absorbent article an odor control additive
5 comprising a water soluble compound of the formula $(\text{APO}_3)_n$, wherein A is a Group 1 element and n is 4 to 50.

According to still another aspect of the present invention, there is provided a disposable, absorbent article comprising a liquid permeable cover, an absorbent core and
10 an odor control additive, wherein the odor control additive comprising a water soluble compound of the formula $(\text{APO}_3)_n$, wherein A is a Group 1 element and n is 4 to 50.

According to a further aspect of the present invention, there is provided use of a water soluble salt
15 containing an anion selected from the group consisting of $\text{P}_3\text{O}_9^{3-}$ and $\text{P}_3\text{O}_{10}^{5-}$ and a cation containing a Group 1 element or ammonium for reducing malodors in a disposable, absorbent article.

Detailed Description of the Invention

20 The absorbent article may for example be a sanitary napkin, pantiliner, diaper, incontinence pad, interlabial article, tampon or other intravaginal device, shoe liner, or other similar product for absorbing exudates from the body, such as menses, urine, feces, or sweat.
25 Preferably, the absorbent article is a sanitary napkin or a pantiliner. Such sanitary napkin or pantiliner may have an approximately rectangular, oval, dogbone, or peanut shape. Depending on the nature of the absorbent article, its size may vary. For example, sanitary napkins typically have a
30 caliper of about 1.4 to about 5 mm, a length of about 3 to about 16 inches, and a width of about 1 to about 5 inches.

74484-102

Pantiliners typically have a caliper of less than about 0.2 inches, a length of less than about 8 inches, and a width of less than about 3 inches.

The absorbent article generally comprises in
5 sequence from its body-facing surface to its garment-facing
surface liquid permeable cover, an absorbent core, and
optionally a backsheet. The cover of the absorbent article
may be formed from any fluid pervious material that is
comfortable against the skin and permits fluid to penetrate
10 to the absorbent core, which retains the fluid. The cover
should retain little or no fluid to provide a relatively dry
surface, since its external surface forms the body-facing
surface of the article. A variety of materials are known
for preparing covers, and any of these may be used. For
15 instance, the cover may be a fibrous non-woven fabric made
of fibers or filaments of polymers such as polyethylene,
polypropylene, polyester, or cellulose. Alternatively, the
cover may be formed from an apertured polymeric film. The
thickness of the cover may vary from approximately 0.001
20 to 0.062 inch, depending on the material chosen.

Generally, the cover is a single sheet of material
having a width sufficient to form the body-facing surface of
the article. The cover may be the same length, or optionally

longer than the absorbent core so as to form transverse ends. Such transverse ends may be sealed with other layers to fully enclose the absorbent core.

The absorbent core may be comprised of a loosely associated absorbent hydrophilic material such as cellulose fibers, including wood pulp, regenerated cellulose fibers or cotton fibers, or other absorbent materials generally known in the art, including
5 acrylic fibers, polyvinyl alcohol fibers, peat moss and superabsorbent polymers.

The absorbent article may further comprise a backsheet that is substantially or completely impermeable to liquids, the exterior of which forms the garment-facing surface of the article. The backsheet may comprise any thin, flexible, body fluid
10 impermeable material such as a polymeric film, for example, polyethylene, polypropylene, or cellophane. Alternatively, the backsheet may be a normally fluid permeable material that has been treated to be impermeable, such as impregnated fluid repellent paper or non-woven fabric material, or a flexible foam, such as polyurethane or cross-linked polyethylene. The thickness of the backsheet when formed from a polymeric
15 film typically is about 0.001 to 0.002 inch. A variety of materials are known in the art for use as backsheet, and any of these may be used.

Generally, the backsheet is a single sheet of material having a width sufficient to form the garment-facing surface of the absorbent article. The backsheet may extend around the sides of the absorbent core in a C-shaped configuration with the portions of
20 the backsheet adjacent its longitudinal edges extending upwardly from the garment-facing surface toward the body-facing surface of the article. Preferably the backsheet is breathable, i.e., a film that is a barrier to liquids but permits gases to transpire. Materials for this purpose include microporous films in which microporosity is created by stretching an oriented film. Single or multiple layers of permeable films, fabrics, and
25 combinations thereof that provide a tortuous path, and/or whose surface characteristics provide a liquid surface repellent to the penetration of liquids may also be used to provide a breathable backsheet.

The absorbent article may be applied to the crotch of underpants by placing the garment-facing surface of the absorbent article against the inside surface of the crotch of
30 the underpants. Strips of pressure sensitive adhesive may be applied to the garment-facing surface of the absorbent article to help maintain it in place. As used herein, the term "pressure-sensitive adhesive" refers to any releasable adhesive or releasable tenacious means. Suitable pressure sensitive adhesives include for example water-based

adhesives such as acrylate adhesives. Alternatively, the adhesive may comprise "hot melt" rubber adhesives or two-sided adhesive tape.

A paper release strip that has been coated on one side may be applied to protect the strips of adhesive prior to use. The coating, for example silicone, reduces adherence
5 of the coated side of the release strip to the adhesive. The release strip can be formed from any suitable sheet-like material which, when coated, adheres with sufficient tenacity to the adhesive to remain in place prior to use but can be readily removed when the absorbent article is to be used.

The absorbent article may comprise other known materials, layers, and additives,
10 such as transfer layers, foam layers, net-like layers, perfumes, medicaments, moisturizers, and the like, many examples of which are known in the art. The absorbent article can optionally be embossed with decorative designs using conventional techniques.

According to the invention, the absorbent article contains one or more odor control additives comprising one or more phosphorous-containing compounds of the
15 following types: 1) water soluble salts containing an anion selected from the group consisting of $P_2O_7^{4-}$, $P_3O_9^{3-}$, and $P_3O_{10}^{5-}$; and 2) water soluble compounds of the formula $(APO_3)_n$, wherein A is a Group 1 element and n is 4 to 50. The water soluble salts containing an anion selected from the group consisting of $P_2O_7^{4-}$, $P_3O_9^{3-}$, and $P_3O_{10}^{5-}$ preferably comprise a cation containing a Group 1 element or ammonium. More
20 preferably such water soluble salts comprise a cation containing sodium. Particularly preferred water soluble salts are tetrasodium pyrophosphate and pentasodium triphosphate.

In water soluble compounds of the formula $(APO_3)_n$, A is preferably sodium and n is preferably 4 to 50. More preferably n is 15 to 20.

25 In addition to the above phosphorous-containing compounds, the odor control additive may comprise other ingredients such as EDTA, zeolites, or other known odor control agents.

The odor control additive may be incorporated into or onto the cover, absorbent core, or backsheet of the absorbent article, or combinations thereof. Alternatively, if the
30 absorbent article comprises additional layers, such as a transfer layer, etc., the odor control additive may be incorporated into or onto such additional layers. Preferably, the cover of the absorbent article comprises the odor control additive, so the odor control additive is in close proximity to the body and the site of initial discharge of body exudates.

The physical form of the odor control additive is not critical to the invention. The odor control additive may be used in the form of powder or a liquid solution. It may also be incorporated into one or more adhesives used in the absorbent article. See for example U.S. Patent No. 4,186,743, which relates to the use of microcapsules containing a
5 deodorant material that are contained in the adhesive element of a sanitary napkin.

The amount of odor control additive used in the absorbent article depends on the size and nature of the layer it is being incorporated into and the absorbent article. Typically, the amount of odor control additive is used is to provide about 0.01 to about 1 gram of phosphorous-containing compound per square inch of layer. Preferably, about
10 0.02 to about 0.50 gram of phosphorous-containing compound per square inch of layer should be present in the absorbent article. However, even smaller amounts of odor control additive are capable of reducing malodor levels in the absorbent article.

It is believed the odor control additive helps to reduce malodors by interfering with the decomposition of lipids by bacteria into fatty acids in body exudates. The odor
15 control additive also has a somewhat basic pH and can therefore neutralize the fatty acids that are produced.

Advantageously, the phosphorous-containing compounds contained in the odor control additive are safe for contact with humans. They are also relatively less harmful to the environment than many other types of compounds. They are also less expensive than
20 EDTA for example.

The following example is intended to illustrate the invention further.

25

Example

A pantiliner is made according to the invention as follows. The pantiliner comprises a cover, an absorbent core, and a backsheet. The absorbent core is made of airlaid pulp. It is 35 mm wide, 150 mm long and 1.2 mm thick. The absorbent core also
30 contains 0.1 gram of tetrasodium pyrophosphate as an odor control additive. The tetrasodium pyrophosphate is used in the form of a powder, and is evenly dispersed over the absorbent core.

74484-102

CLAIMS:

1. A disposable, absorbent article comprising a liquid permeable cover, an absorbent core and an odor control additive, wherein the odor control additive is a water soluble salt containing an anion selected from the group consisting of $\text{P}_3\text{O}_9^{3-}$ and $\text{P}_3\text{O}_{10}^{5-}$ and a cation containing a Group 1 element or ammonium, wherein the cover comprises the odor control additive in an amount of 0.0155 to 1.55 mg per mm^2 of the cover.
2. The disposable absorbent article of claim 1, wherein said Group 1 element is sodium.
3. The disposable absorbent article of claim 1, wherein said odor control additive comprises pentasodium triphosphate.
4. The disposable absorbent article of any one of claims 1 to 3, wherein the absorbent core comprises a further amount of the odor control agent.
5. The disposable absorbent article of any one of claims 1 to 4, further comprising a backsheet, wherein the backsheet comprises a further amount of the odor control agent.
6. A method of reducing malodors in a disposable, absorbent article, comprising incorporating an odor control additive in an amount from 0.0155 to 1.55 mg per mm^2 of layer into the absorbent article, wherein the absorbent article comprises a liquid permeable cover and an absorbent core, wherein the odor control additive is a water soluble salt containing an anion selected from the group consisting of $\text{P}_3\text{O}_9^{3-}$ and $\text{P}_3\text{O}_{10}^{5-}$ and a cation containing a Group 1 element or ammonium.

74484-102

7. The method of claim 6, wherein said Group 1 element is sodium.

8. The method of claim 6, wherein said odor control additive comprises pentasodium triphosphate.

5 9. The method of any one of claims 6 to 8, wherein the amount of odor control additive is from 0.03 to 0.78 mg per mm² of layer.

10. A method of reducing malodors in a disposable, absorbent article, comprising incorporating into the
10 absorbent article an odor control additive comprising a water soluble compound of the formula (APO₃)_n, wherein A is a Group 1 element and n is 4 to 50.

11. The method of claim 10, wherein said Group 1 element is sodium, and n is 15 to 20.

15 12. Use of a water soluble salt containing an anion selected from the group consisting of P₃O₉³⁻ and P₃O₁₀⁵⁻ and a cation containing a Group 1 element or ammonium for reducing malodors in a disposable, absorbent article.

13. The use of claim 12, wherein said Group 1 element
20 is sodium.

SMART & BIGGAR

OTTAWA, CANADA

PATENT AGENTS