



(51) International Patent Classification:

G02C 11/06 (2006.01) G02B 27/01 (2006.01)
G02C 11/00 (2006.01)

(21) International Application Number:

PCT/US2016/031427

(22) International Filing Date:

09 May 2016 (09.05.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant: OAKLEY, INC. [US/US]; One Icon, Foothill Ranch, CA 92610 (US).

(72) Inventors: ANDERSON, Christopher, John; One Icon, Foothill Ranch, CA 92610 (US). MEUNIER, Benjamin, John; One Icon, Foothill Ranch, CA 92610 (US). SAYLOR, Ryan, Neil; One Icon, Foothill Ranch, CA 92610 (US). WILDE, Timothy, James; One Icon, Foothill Ranch, CA 92610 (US).

(74) Agent: HOLOUBEK, Michelle K.; STERNE, KESSLER, GOLDSTEIN & FOX P.L.L.C., 1100 New York Avenue, N.W., Washington, DC 20005-3934 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: MODULAR WEARABLE ELECTRONIC DEVICES, SYSTEMS, AND METHODS




FIG. 10




FIG. 15

(57) Abstract: A modular, wearable electronic system is disclosed. The modular, wearable electronic system can include an eyewear unit which can be worn on a user's head and one or more modular units which can removably couple with the eyewear unit via one or more ports and/or connectors. The eyewear unit and the modular unit can communicate with each other via the port or connector to which the eyewear unit and the modular unit are coupled. The modular units can supplement the functionality of the eyewear unit.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))*

Published:

- *with international search report (Art. 21(3))*

MODULAR WEARABLE ELECTRONIC DEVICES, SYSTEMS, AND METHODS

BACKGROUND

Field

[0001] The embodiments described herein relate generally to wearable electronic communication devices, systems, and methods. In particular, some embodiments described herein relate to wearable electronic communication devices and systems that can be placed on a user's head, such as eyewear.

Background

[0002] There are numerous situations in which it is convenient and preferable to include electronic communication features and functionality on devices and systems worn on a user's body, such as on a wearer's head. Many such devices and systems can convey signals to and receive signals from the user in a hands-free manner. As a result, the user can receive and/or send signals, such as audio and/or visual signals, in a convenient manner while focusing on other tasks.

[0003] However, advances and improvements in devices and systems with electronic communication features have been occurring at an extremely rapid pace. For example, processors have become more powerful and efficient, larger amounts of memory can be stored in a smaller space, new communication protocols have been developed which can provide significant advantages over older communication protocols, etc. As a result, older devices and systems can quickly become incompatible or antiquated within a short span of time, thereby requiring a user to purchase newer devices and systems on a frequent basis to remain up-to-date with respect to hardware and programs. This can present a problem to many users since such devices and systems may require elaborate and expensive components and systems to enable highly sophisticated functional communication features. Moreover, users are often interested in only a subset of new or enhanced features and functionality.

SUMMARY

[0004] Accordingly, there is a need for improved wearable electronic communication devices and systems. The electronic device or system can be provided with removably attachable interchangeable components, such as modular units, to supplement the capabilities of another component, such as a base unit including, but not limited to, a headworn wearable unit. The headworn wearable unit can be, for example, an eyewear such as an eyeglass frame or a goggle frame, either with or without lenses. The headworn wearable unit can be, as another example, a helmet. The electronic device or system can be contained in a housing that can be associated within a personal area network range of the wearer.

[0005] In some embodiments, an electronic system is provided with removably attachable interchangeable components, such as modular units, to supplement the capabilities of another component, such as an eyewear unit. The eyewear unit can include one or more components contained therein. For example, the eyewear unit can include a processor and memory for processing and storing data. The eyewear unit can include one or more sensors to obtain sensory data related to the environment, the user, and/or motion of the eyewear unit. To communicate with other devices, the eyewear unit can include components such as a receiver and transmitter (or transceiver) to enable wireless communication with other devices and/or a port or connector for wired communication with other devices. For example, a modular unit can be removably coupled to the eyewear unit via the port or connector. The modular unit can include components such as, but not limited to, a speaker and an ambient or biometric sensor. The modular unit can include other features to supplement the capabilities of the eyewear unit.

[0006] In some embodiments, an electronic system can include an eyewear unit configured to be worn on a user's head. The eyewear unit can include an input/output system which includes at least one wired connection, such as a port and/or connector. The electronic system can include a modular unit. The modular unit can include an input/output system which includes at least one wired connection, such as a port and/or connector. The modular unit can also include at least one of the following components: a processor, a memory, a sensor, a receiver configured to wirelessly communicate with at least one remote unit, a

transmitter configured to wirelessly communicate with at least one remote unit, and a transceiver configured to wirelessly communicate with at least one remote unit. The input/output systems of the eyewear unit and the modular unit can provide a wired electrical connection between the eyewear unit and the modular unit when in a coupled configuration via the at least one wired connection the eyewear unit and the at least one wired connection of the modular unit.

[0007] In some embodiments, an electronic system can include an eyewear unit configured to be worn on a user's head. The eyewear unit can include an input/output system including at least one wired connection, such as a port and/or connector. The electronic system can also include modular unit. The modular unit can include an input/output system including at least one wired connection, such as a port and/or connector, configured to removably couple to the at least one wired connection of the eyewear unit. The at least one wired connection of the eyewear unit and the at least one wired connection of the modular unit can provide a wired electrical connection between the eyewear unit and the modular unit when in a coupled configuration. The input/output systems and the eyewear unit and the modular unit can provide communication (e.g., the eyewear unit can transfer data to the modular unit and the modular unit can transfer data to the eyewear unit) between the eyewear unit and the modular unit via the coupled wired connections of the eyewear unit and the modular unit.

[0008] In some embodiments, the modular unit can include a second wired connection, wherein at least the second wired connection is configured to connect the modular unit to another modular unit. The input/output system of the modular unit can be configured to provide communication between the eyewear unit and the second unit modular unit (e.g., the eyewear unit can transfer data to the second modular unit and the second modular unit can transfer data to the eyewear unit). In some embodiments, the eyewear unit can include a power source configured to power the modular unit. The power source can provide power to the second modular unit via the coupled port and connector of the eyewear unit and the modular unit.

[0009] In some embodiments, an electronic system can include an eyewear unit and/or one or more modular units which are mechanically attached to and/or carried by the

eyewear unit. The eyewear unit and/or modular unit can serve as the central hub or node for multiple source devices in the form of remote units which are not carried by the eyewear unit (e.g., rather than a smart phone or some other mobile electronic device serving as the central hub or node).

[0010] In some embodiments, the modular unit can include an input/output system. The input/output system can include a receiver and a transmitter configured to wirelessly communicate with at least one remote unit. In some embodiments, the at least one remote unit can include a sensor. In some embodiments, the at least one remote unit can include a smart phone.

[0011] In some embodiments, the modular unit can be configured to be attached to the eyewear unit proximate the user's head. In some embodiments, the receiver of the modular unit can include two or more wireless protocols, for example Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, MMS, similar protocols, and other protocols which may be developed. A receiver of any eyewear unit may include one or more of these protocols. In some embodiments, the eyewear unit and/or modular unit can communicate with a remote unit having a first wireless protocol and a remote unit having a second wireless protocol. In some embodiments, an electronic system can include an eyewear unit, a modular unit, and an input/output system. The eyewear unit can be worn on a user's head and can include at least one port or connector. The modular unit can include a connector and/or a port, the connector and/or the port being configured to removably couple to the complimentary port or connector of the eyewear unit. The coupled port and connector of the eyewear and the modular unit can be configured to provide a wired electrical connection between the eyewear unit and the modular unit. The input/out system can be configured to provide communication between the eyewear unit and the modular unit via the coupled port and connector of the eyewear and the modular unit (e.g., the eyewear unit can transfer data to the modular unit and the modular unit can transfer data to the eyewear unit).

[0012] In some embodiments, the eyewear unit can include at least one of the following components: a processor, a memory, a sensor, a receiver configured to wirelessly communicate with at least one remote unit, and a transmitter configured to wirelessly

communicate with at least one remote unit. In some embodiments, the modular unit can include at least one of the following components: a processor, a memory, a sensor, a receiver configured to wirelessly communicate with at least one remote unit, and a transmitter configured to wirelessly communicate with at least one remote unit.

[0013] In some embodiments, the eyewear unit can include a processor and the modular unit can include a receiver and a transmitter. In some embodiments, the eyewear unit can include a processor and the modular unit can include a bone-conduction speaker. One or more source devices, such as a modular unit or a remote unit, can be devices for generating a signal indicative of any one or more of environmental information, biometric information, entertainment, and/or other information, including, but not limited to, an accelerometer, gyroscope, proximity sensor, temperature, humidity, altitude, barometric pressure, GPS, wind sensor, music, video, text-to-voice capabilities, and/or interpersonal communication. Source devices can also capture biometric data for transmission to the electronic device, such as body temperature, blood pressure, respiration characteristics including, but not limited to, rate and tidal volume, blood or respiration CO₂, pO₂, lactic acid, heart rate, and dermal moisture. The output from any of the foregoing source devices can be transmitted to the wearer via visual display, audio output, haptic feedback, or a combination of these transmission mechanisms, depending upon the nature of the data and desired display format.

[0014] The source devices can be unique, discrete, single function devices or devices that can sense or determine two or three or more parameters in a single device. In some embodiments, one or two or three or more source devices can be removably mechanically attached to and/or carried by the electronic device or system, while one or more other source devices may be worn by the wearer or equipment (e.g., bicycle, treadmill, or other equipment) and associated with the wearer within a personal area network range so that they may be paired in communication with the electronic device or system.

[0015] In some embodiments, the electronic device or system comprises an eyeglass or goggle or helmet support structure, having onboard electronics such as a power source, CPU, transceiver for pairing with any Bluetooth, ANT, ANT+, or other wireless protocol source device, one or two or more electrical and/or mechanical ports or connectors,

such as USB 3.0 ports or connectors, for removably receiving a complementary module having additional electronics.

[0016] In some embodiments, an electronic system is provided with one or two or more tactile feedback elements such as a haptic component. The system can include an eyewear unit wearable on a user's head with one or more components contained therein. For example, the eyewear unit can include a processor, memory, one or more sensors, and/or communication components such as a receiver, transmitter and/or port. The eyewear unit can include a haptic component designed to generate a tactile signal perceptible by the user.

[0017] In some embodiments, an electronic system can include an eyewear unit configured to be worn on a user's head. The eyewear unit can include at least one of a processor, a memory, a sensor, a receiver configured to wirelessly communicate with at least one remote unit, a transmitter configured to wirelessly communicate with at least one remote unit, and a wired connection. The eyewear unit can also include at least one haptic component configured to generate a tactile signal perceptible by the user.

[0018] In some embodiments, the at least one haptic component can include a piezoelectric actuator. In some embodiments, the at least one haptic component can provide a user with a tactile representation of data received from a sensor. In some embodiments, the at least one haptic component can provide a user with notifications of a trigger event. In some embodiments, the at least one haptic component can include two or more haptic components positioned on different regions of the eyewear unit. In some embodiments, the at least one haptic component can include a first haptic component positioned on a lateral region of the eyewear unit and a second haptic component positioned on an opposite lateral region of the eyewear unit. In some embodiments, the at least one haptic component can provide a user with navigation information. In some embodiments, a haptic component can be added to an existing eyewear unit via a modular unit and/or a remote unit.

[0019] In some embodiments, the system can include a visual component configured to display an image to the user. In some embodiments, the system can include an audio component configured to generate an audible signal perceptible by the user. In some embodiments, the system can include a haptic component configured to generate a tactile signal perceptible by the user. In some embodiments, the eyewear unit can include a sensor

and the at least one haptic component can be configured to provide a user with a tactile representation of data received from the sensor. In some embodiments, one or more of these components can be built into an existing eyewear unit. In some embodiments, one or more of these components can be added to an existing eyewear unit via a modular unit and/or a remote unit.

[0020] In some embodiments, the system can include one or more movable antennas. The movable antennas can transition from a first, stowed configuration to a second, deployed configuration. In some embodiments, an eyewear unit of the system can include one or more movable antennas. In some embodiments, a modular unit of the system can include one or more movable antennas. The movable antenna can be rotatable and/or translatable. In some embodiments, at least one of the movable antennas is rotatable. In some embodiments, the movable antenna can be rotatable along a generally vertical or a generally horizontal axis of rotation. In some embodiments, the movable antenna can be translatable. In some embodiments, in the deployed configuration, the movable antenna can be positioned such that a distance between a user and the antenna is between one-third to two-thirds a length of the antenna.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several examples of embodiments in accordance with the disclosure, and are not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through the use of the accompanying drawings.

[0022] FIGURE 1 illustrates a schematic of an embodiment of an electronic device or system in communication with a remote unit, the system having an eyewear unit and a modular unit.

[0023] FIGURE 2 illustrates an embodiment of electronics used in conjunction with a display device for providing retinal projection of an image onto the retina of a user.

[0024] FIGURE 3A illustrates a schematic of an embodiment of an electronic device or system in communication with multiple remote units, the system having an eyewear unit and a modular unit.

[0025] FIGURE 3B illustrates a schematic of an embodiment of the modular unit of Figure 3A.

[0026] FIGURE 4 illustrates a schematic of another embodiment of an electronic device or system in communication with multiple remote units, the system having an eyewear unit and a modular unit.

[0027] FIGURE 5A illustrates a left side view of an embodiment of an electronic device or system having an eyewear unit with an input/output system.

[0028] FIGURE 5B illustrates a left side view of another embodiment of an electronic device or system having an eyewear unit with an input/output system.

[0029] FIGURE 5C illustrates a front perspective view of another embodiment of an electronic device or system having an eyewear unit with an input/output system.

[0030] FIGURE 6 illustrates a schematic view of an embodiment of an electronic device or system having an eyewear unit and a modular unit, the modular unit being removably attachable with other peripherals.

[0031] FIGURE 7 illustrates a perspective view of an embodiment of a modular unit having a pitot tube.

[0032] FIGURE 8 illustrates a perspective view of an embodiment of a modular unit having a biometric sensor.

[0033] FIGURE 9A illustrates a schematic view of another embodiment of an electronic device or system having an eyewear unit and a plurality of modular units in an attached configuration.

[0034] FIGURE 9B illustrates a schematic view of the device or system of FIGURE 9A in a detached configuration.

[0035] FIGURE 10 illustrates a left side view of another embodiment of an electronic device or system having an eyewear unit and modular unit, the modular unit forming part of an earstem.

[0036] FIGURE 11 illustrates a rear perspective view of another embodiment of an electronic device or system having an eyewear unit and modular unit.

[0037] FIGURE 12 illustrates a rear perspective view of another embodiment of an electronic device or system having an eyewear unit and modular unit.

[0038] FIGURE 13A illustrates a top view of a schematic of an embodiment of a frame of an eyewear unit.

[0039] FIGURE 13B illustrates a front perspective view of the schematic of the frame of Figure 13A.

[0040] FIGURE 13C illustrates a front view of the schematic of the frame of Figure 13A.

[0041] FIGURE 13D illustrates a left side view of the schematic of the frame of Figure 13A.

[0042] FIGURE 14 illustrates a side view of an embodiment of an antenna attached to an earstem.

[0043] FIGURE 15 illustrates a top view of the antenna of Figure 14.

DETAILED DESCRIPTION

[0044] The present specification and drawings provide aspects and features of electronic devices or systems, such as a wearable device or system in the context of several embodiments of devices and methods. The wearable device or system can be a network or communication device or system. These embodiments are described and illustrated in connection with specific types of eyewear such as eyewear having a unitary lens. However, it is to be understood that the features and concepts discussed herein, such as integrated components, modular components, communication features, and communication functionality, can be applied to other types of headworn wearable devices and systems including, but not limited to, eyewear and helmets. Such eyewear can include eyeglasses and goggles having dual lens, a single lens, or no lens. Moreover, the electronic devices and systems can be attached to a proximate structure relevant to the intended use environment, such as, but not limited to, a bicycle handlebar or other portion of a bicycle. In addition, particular features of the devices, systems, and methods should not be taken as limiting, and

features of any one embodiment discussed herein can be combined with features of other embodiments as desired and when appropriate. Any feature, step, material, or structure described and/or illustrated in any embodiment can be used with or instead of any other feature, step, material, or structure described and/or illustrated in any other embodiment. Anything in this specification can be omitted in some embodiments; no features described or illustrated in this specification are essential or indispensable.

General System

[0045] With reference first to the embodiment of the electronic device or system **100**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 1, the system **100** can be designed to obtain, process, and/or convey data to and/or from a user of the system **100**. As shown in the illustrated embodiment, the system **100** can include a headworn wearable unit, such as an eyewear unit **110**, with one or more systems such as a processing system **120**, a signal conversion system **130**, a sensor system **140** (ambient or environmental, motion, biometric, and/or physiological), an input/output (I/O) system **150**, a user interface system **160**, and a power system **170**. The system **100** can also include one or more modular units **210** which can be removably coupled to the eyewear unit **110**. In some embodiments, one or more of the modular units **210** can function as source devices and provide signal sources for the system **100**. In some embodiments, the one or more modular units **210** can be removably coupled to and/or carried by the eyewear unit **110**. This can advantageously provide a more compact and combined form factor for the user and reduce the number of detached components. This can be beneficial when the user does not have sufficient storage or carrying space, such as pockets, to hold detached components.

[0046] As shown in the illustrated embodiment, each of the modular units **210** can include one or more systems. For example, the modular units **210** can include one or more systems such as a processing system **220**, a signal conversion system **230**, a sensor system **240**, an input/output (I/O) system **250**, a user interface system **260** and a power system **270**. As discussed in further detail below, processing system **220**, signal conversion system **230**, sensor system **240**, input/output (I/O) system **250**, user interface system **260** and/or power

system **270** can include the same or similar components to those discussed in connection with processing system **120**, signal conversion system **130**, sensor system **140**, input/output (I/O) system **150**, user interface system **160**, and/or power system **170**.

[0047] Each system can be in communication, wired and/or wirelessly, with one or more other systems. In some embodiments, some or all communications between systems can be two-way communication such that a first system may transmit data to and receive data from a second system. For example, two-way communications may be established between the processing system **120** and the signal conversion system **130**. The processing system **120** may transmit data to a speaker of the signal conversion system **130** and receive data from a microphone of the signal conversion system **130**. In some embodiments, some or all communications between systems can be one-way communications such that a first system may transfer data to a second system whereas the second system does not transfer data to the first system. For example, the user interface system **160** may transmit data to the processing system **120** and the processing system **120** may not transmit data to the user interface system **160**. It should be understood that one or two-way communication can be maintained between any systems described herein. Moreover, it should be understood that, when taken in its entirety, multiple systems can be in communication to each other via other system. For example, the sensor system **140** can be in communication with the signal conversion system **130** via intermediary communications with the processing system **120**.

[0048] As another example, wired and/or wireless two-way communications may be established between the eyewear unit **110** and one or more modular units **210**, such as via input/output systems **150**, **250**. The eyewear unit **110** may transmit data to one or more modular units **210** and receive data from one or more modular units **210**. In some embodiments, some or all communications between the eyewear unit **110** and one or more modular units **210** can be one-way communications such that the eyewear unit **110** may transfer data to one or more modular units **210** whereas one or more modular units **210** does not transfer data to the eyewear unit **110** or vice-versa. It should be understood that one or two-way communication can be maintained between one or more modular units **210** and the eyewear unit **110**. For example, two-way communications may exist between eyewear unit **110** and a first modular unit **210** whereas one-way communications may exist between

eyewear unit **110** and a second modular unit **210**. Moreover, it should be understood that, when taken in its entirety, multiple systems can be in communication to each other via other system. For example, a first modular unit **210** can communicate with a second modular unit **210** either directly via an input/output system **250** and/or through the eyewear unit **110** as an intermediary via input/output system **150**.

[0049] The systems can be in communication via a wired connection and/or via a wireless connection as illustrated by the solid connecting lines. One or more systems, such as those for the eyewear unit **110** and the modular unit **210**, can receive power from the power system **170** as shown by the dash-dot-dash lines. Of course, one or more systems, such as those for the eyewear unit **110** and the modular unit **210**, can receive power from the power system **270** either in addition to that received from the power system **170**, or solely from the power system **270**. Although the systems are shown as communicating to each other through the processing system **120**, it should be understood that the systems may bypass the processing system **120** and communicate directly with each other.

[0050] In some embodiments, one or more systems of the eyewear unit **110** can be integrated into or with a headworn wearable device, such as an eyewear. For example, one or more of the components of the systems of the eyewear unit **110** can be located on and/or within one or more components of the eyewear such as one or more of the earstems, frame, orbitals and/or lenses. In some embodiments, a plurality of components of the one or more systems can be distributed to different components of the eyewear to help distribute volume and/or weight in the eyewear, thereby enhancing performance and user comfort when utilizing the eyewear with the eyewear unit **110**.

[0051] In some embodiments, the one or more modular units **210** can be positioned such that a majority of the modular unit **210** is positioned outside the eyewear unit **110**. In some embodiments, the one or more modular units **210** can be positioned such that a majority of the modular unit **210** is hidden within a component of the eyewear, such as one or more of the earstems, frame, orbitals, and/or lenses.

[0052] The modular unit **210** can be a standalone device which can function without being connected to eyewear unit **110** or any other electronic devices. For example, the modular unit **210** can include a processing system **220**, a sensor system **240**, and a power

system **270** and be capable of recording information even while disconnected from another device. When attached to the eyewear unit **110**, the modular unit **210** can provide this data to the eyewear unit **110**. In some embodiments, the modular unit **210** can be a standalone device which provides timing functionality to an eyewear unit **110**. When removed from the eyewear unit **110**, the modular unit **210** can beneficially be used as a timing device (e.g., stopwatch, timer) in other settings. For example, such a modular unit **210** can be used at home, attached to another part of one's person such as a user's wrist, and/or attached to another structural component such as a bike handle. Moreover, the modular unit **210** can supplement the capabilities of the eyewear unit **110** such as by supplementing an existing processing system **120**, sensor system **140**, and/or power system **170** of the eyewear unit **110** or, in embodiments of eyewear unit **110** without one or more of these systems, wholly adding new functionality to the eyewear unit **110**.

[0053] The modular unit **210** may not be a standalone device. For example, the modular unit **210** may not include a power system **270** to provide power to electronics contained within the modular unit **210**. In some embodiments, the modular unit **210** can receive this power via connection to the eyewear unit **110** or another electronic device.

[0054] The eyewear unit **110** and/or the modular units **210** can be in communication, wired and/or wirelessly, with a remote unit **310**. As shown in the illustrated embodiment, the remote unit **310** can include one or more systems such as a processing system **320**, a signal conversion system **330**, a sensor system **340**, an input / output (I/O) system **350**, a user interface system **360**, and a power system **370**. As discussed in further detail below, processing system **320**, signal conversion system **330**, sensor system **340**, input/output (I/O) system **350**, user interface system **360** and/or power system **370** can include the same or similar components to those discussed in connection with processing systems **120**, **220**, signal conversion systems **130**, **230**, sensor systems **140**, **240**, input/output (I/O) systems **150**, **250**, user interface systems **160**, **260**, and/or power systems **170**, **270**.

[0055] The remote unit **310** can be a standalone device or can be operational only when in communication with the system **100** such as the eyewear unit **110** and/or the modular unit **210**. Examples of remote units **310** can include one or more electronic devices such as, but not limited to, standalone devices such as cell phones, smart phones, watches, smart

watches, PDAs, tablets, laptops, desktops, game consoles, MP3 players, iPods, cameras, fitness or gym equipment, sensors, and the like. For example, the one or more electronic devices can include, bike computers and other on-board vehicle sensors or systems, activity trackers such as a Fitbit, and other wearable and smart devices such as an Apple iWatch, an Apple iPhone, Android-based phones, and other such devices.

[0056] In some embodiments, the eyewear unit **110** and/or one or more of the modular units **210** can receive data from the remote units **310** and present or communicate this data to the user of the system **100**. For example, the eyewear unit **110** and/or one or more of the modular units **210** can be used to stream music from a remote unit **310**, such as a smart phone or MP3 player, and present that to the user. In some embodiments, the eyewear unit **110** and/or one of the modular units **210** can communicate with a remote unit **310**, such as a smart phone or cell phone, such that the user of the communication unit **100** can use the eyewear unit **110** and/or one of the modular units **210** for a phone call and/or for sending text messages. In some embodiments, the eyewear unit **110** and/or one or more of the modular units **210** can communicate with multiple remote units **310**

[0057] Use of a modular unit **210** with the eyewear unit **110** can advantageously supplement the features and functionality of the eyewear unit **110**. This can be particularly beneficial as it can allow a user to upgrade the device over time. In this manner, the usable lifespan of the eyewear unit **110** can be expanded thereby reducing waste and reducing total costs to the user who need not replace the eyewear unit **110** with a newer version of the eyewear unit **110** if newer functionality is desired. Moreover, in circumstances where the desired functionality may change depending on the activity being performed by the user, this system can beneficially allow the user to more effectively configure the system **100** depending on the activity.

[0058] In some embodiments, the eyewear unit **110** can omit systems such as a processing system **120** and/or signal conversion system **130**, which might include components which are expensive to manufacture and are quickly antiquated or rendered incompatible with other components by new developments in technology. The user can then purchase one or more modular units **210** to provide one or more of the upgraded, repaired, or missing systems, or to provide improvements or enhancements to the system. For example,

in some embodiments, the eyewear unit **110** can omit the wireless system **152** and the user can connect one or more modular units **210** to provide an input/output system **250** which includes wireless systems. This can be particularly advantageous as wireless protocols often vary for remote units **310** from different manufacturers and, in some instances, from the same manufacturer. The one or more modular units **210** can provide one or more wireless protocols. In some embodiments, the eyewear unit **110** can omit the processing system **120**, signal conversion system **130**, the sensor system **140**, and/or the wireless system **152** and the user can connect one or more modular units **210** to provide the missing systems.

[0059] Moreover, it is contemplated that due to advances in technology, systems on the eyewear unit **110** itself can eventually become antiquated by newer technology. The modular unit **210** can be used to supplement or replace existing systems on the eyewear unit **110**. For example, the modular unit **210** can be used to assist in providing faster, more efficient, and/or otherwise enhanced operation of the device by including one or more supplemental components, such as a power system **270** and/or supplement storage of data by including a memory with processing system **220**. This ability to supplement or improve the existing systems of the device can also be beneficial as the user need not be inconvenienced with purchasing an entirely new eyewear unit **110** to upgrade certain features and functionality. Rather, the user can purchase modular units **210** to add or upgrade components, features and/or functionality of the system **100**.

[0060] As should be understood from the discussion of the multiple systems below, it should be appreciated that any of the components can be omitted from one or more of the systems of the eyewear unit **110** and/or modular unit **210**. Accordingly, it should be understood that any combination of such components between the eyewear unit **110** and/or modular unit **210** can be achieved as desired by the user.

[0061] For example, in some embodiments, the modular unit **210** can include systems and/or components which are not present on the eyewear unit **110** or vice versa. For example, in some embodiments, the eyewear unit **110** can include solely a power system **170** and the modular unit **210** can include one or more of a processing system **220**, a signal conversion system **230**, a sensor system **240**, an input/output (I/O) system **250**, and a user interface system **260**. The eyewear unit **110** can provide power to the modular unit **210** via a

port or connector of the eyewear unit **110** similar to those described in connection with I/O system **150** below. In this manner, a user can specifically choose modular units **210** which provide the functionality that the user desires. This can beneficially reduce total costs to the user as the user need not purchase modular units **210** with functionality that the user does not desire. Moreover, selection of specific functionality can further reduce size and/or weight of the system **100**.

[0062] As another example, in some embodiments, the eyewear unit **110** can include an I/O system **150** and the modular unit **210** can include an I/O system **250** and one or both of the eyewear unit **110** and the modular unit **210** can include a power system. This can beneficially provide for a greater degree of connectivity with other devices. For example, the I/O system **250** can be a more up-to-date wireless protocol capable of communicating with newer devices. In some embodiments, the eyewear unit **110** can include a processing system **120** and power system **170** in addition to the I/O system **150**. In some embodiments, the modular unit **210** can include one or more other systems, such as a processing system **220**, a signal conversion system **230**, a sensor system **240**, a user interface system **260**, and/or a power system **270** in addition to the I/O system **150**. In some embodiments, the modular unit **210** can provide one or more of the following functionality: additional processing capabilities such as a second microprocessor, image capture (e.g., still camera and/or video camera), audio input devices (e.g., microphones, such as a bone conduction microphone), audio output devices (e.g., in-ear speakers, bone conduction speakers, directional audio speakers, outwardly facing speakers), physiological sensing (e.g., heart rate sensors, blood-oxygen sensors, and the like), environmental sensing (e.g., air temperature sensors, air humidity sensors, air quality sensors, pressure sensors, wind speed sensors which can be used in calculating power, and the like), motions sensors (e.g., accelerometers, gyroscope, and the like), biometric calculations (e.g., skin temperature and air temperature to calculate hydration, biochemical sensors to determine sweat characteristics, EEG sensors), provision of directions (e.g., audio and/or visual indicators such as a turn signal and/or haptic feedback, GPS), additional wireless capabilities (e.g., receivers, transmitters, and/or transceivers) which can add new protocols or supplement existing protocols (e.g., a second Bluetooth connection), Wi-Fi, or any other protocol described herein, wind noise reduction (e.g., windscreens,

specific housing shapes), enhanced audio (e.g., enhanced speakers), enhanced booms (e.g., built-in power sources such as batteries, different sizes such as smaller sizes designed to better fit women), user interfaces (e.g., touch controls or buttons), power charging (e.g., one or more ports or connectors which allow for charging of the system while still allowing a user to listen to the boom), safety features (e.g., LED lights, radar system which can be rear-facing, peer-to-peer communications), and other functionality.

[0063] Use of a remote unit **310** with the system **100** can also advantageously enhance the features and functionality of the system **100**. For example, the remote unit **310** can include systems and/or components which are not present on the system **100** or vice versa. Similar to the description in connection with modular unit **210**, the user can purchase one or more remote units **310** to provide additional components, features and/or functionality. As should be understood from the discussion of the multiple systems below, it should be appreciated that any of the components can be omitted from one or more of the systems of the system **100** and/or remote unit **310**. Accordingly, it should be understood that any combination of such components between the system **100** and/or remote unit **310** can be achieved as desired by the user.

[0064] Although the discussion below of the multiple systems is primarily in reference to the eyewear unit **110**, it should be understood that such discussion also pertains to systems of the modular unit **210** and the remote unit **310**. For example, it should be understood that any or all of the components discussed in connection with processing system **120**, signal conversion system **130**, sensor system **140**, I/O system **150**, user interface system **160**, and/or power system **170** can also be included instead of or in addition to those described and/or illustrated in processing systems **220**, **320**, signal conversion systems **230**, **330**, sensor systems **240**, **340**, I/O systems **250**, **350**, user interface systems **260**, **360**, and/or power systems **270**, **370**.

Processing System

[0065] As shown in the illustrated embodiment of Figure 1, the support structure such as eyewear unit **110** of the system **100** can include a processing system **120** which can be designed to process and/or store data received from one or more of the other systems of

the system, such as the eyewear unit **110**, modular unit **210**, and/or remote unit **310**. As shown in the illustrated embodiment, the processing system **120** can include one or more components, such as a processor **122**, a memory **124** and program **126**. The processor **122** can be a microprocessor or central processing unit (CPU) designed to receive data from one or more of the other systems and transmit this processed data to one or more of the other systems. In some embodiments, the processor **122** can be designed to process this data in accordance with an algorithm from program **126**. The functionality of processor **122** and/or any other component of the eyewear unit **110**, modular unit **210**, and/or remote unit **310** can be modified and/or enhanced by utilizing a different program **126**. The processed data can also be stored in the memory **124** for later use. For example, the data stored in memory **124** can be retrieved at a later time for further processing by the processing system **120** and/or viewing by the user. In some embodiments, the program **126** can be software stored in memory **124** and/or firmware stored in hardware, such as the processor **122** and/or other components of the eyewear unit **110**. The program **126** can be updated, modified, fixed, and/or replaced, such as by receiving a new or modified program **126** through the system **100**, and/or by attaching the component in which the program **126** is stored or some other portion of the system to another computing device, either in a wired or wireless manner, to convey new or modified program information into the program **126**, or by replacing the component in which the program **126** is stored with another component containing a different program **126**.

[0066] Program **126** can include software which can provide one or more different features or user experiences when utilizing the system **100**. For example, such software can include one or more applications which provide one or more features and/or functionality such as, but not limited to, tracking designed to track and store a user's activity such as number of steps taken, amount of time the user was active, environmental conditions in which the system **100** has been used, and the like. The software can also include one or more features and functionality related to user operation of the eyewear unit **110**, modular unit **210**, and/or remote unit **310**, such as voice command functionality allowing for hands-free operation of the units **110**, **210**, **310**. In some embodiments, the software can enable one

or more other types of features and functionality such as conversion of text messages to voice messages and vice versa.

[0067] In some embodiments, the program **126** can include software found on mobile devices such as, but not limited to, cell phones, smart phones, PDAs, and tablets running Android, iOS, and/or Windows operating systems, etc. For example, the eyewear unit **110** can include an Android, iOS, and/or Windows operating system to enable compatibility with such software. In some embodiments, program **126** can include software found on other types of electronic devices including, but not limited to, laptops and desktops. Advantageously, in embodiments where such functionality is enabled in the eyewear unit **110**, the eyewear unit **110** of the system **100** can include one or more functions of other stand-alone mobile devices.

[0068] Although program **126** is illustrated as forming part of the processing system **120**, as noted above program **126** can include firmware which is built into any aspect of the system, such as in the processor **122** and/or any other components of the eyewear unit **110**. For example, program **126** can be used to control the operation of components of the eyewear unit **110** such as the various components of the signal conversion system **130**, sensor system **140**, I/O system **150**, user interface system **160** and/or the power system **170** or similar systems on the modular unit **210** and/or remote unit **310**. For example, the program **126** can be used to control the operation of the wireless system **152** of the I/O system **150** which can include a receiver, transmitter, and/or transceiver designed to communicate with other devices typically within a personal area network distance from the eyewear unit **110** using a wireless protocol such as, but not limited to, Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, and MMS. The program **126** can also be used to monitor the statuses of the one or more sensors of the system **100**.

[0069] In some embodiments, the modular unit **210** and/or remote unit **310** can include processing systems **220**, **320** having components, features and/or functionality similar to that described above in connection with processing system **120**. In some embodiments, the eyewear unit **110** can omit one or more components of the processing system **120** such that a user can provide such components with processing systems **220**, **320**. For example, the eyewear unit **110** can omit the processor **122**, memory **124** and/or program **126** allowing the

user to supply one or more of such components by connecting the eyewear unit **110** with a modular unit **210** and/or remote unit **310** via a wired connection and/or wirelessly. The eyewear unit **110** can include components which overlap with those of processing systems **220**, **320** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the processing system **120**. For example, the eyewear unit **110** can be provided with a power-efficient processor **122** to conserve battery life and a modular unit **210** and/or a remote unit **310** can include a more powerful processor. As another example, the modular unit **210** and/or remote unit **310** can have a processing system **220**, **320** designed to decode MP3s or other audio files and can provide such additional features and/or functionality to the eyewear unit **110** when connected. Of course, in some embodiments, one or more components of the processing systems **220**, **320** of the modular unit **210** and/or remote unit **310** can be omitted.

Signal Conversion System

[0070] With continued reference to the system **100** illustrated in Figure 1, the eyewear unit **110** of the system **100** can include a signal conversion system **130** which can be designed to convert signals from one form to another. The signal conversion system **130** can be designed to convert analog and/or digital electrical signals into signals more readily perceptible by the user of the eyewear unit **110** such as audio, visual, and/or tactile signals, etc. The signal conversion system **130** can be designed to convert audio, visual, and tactile signals into analog and/or digital electrical signals for processing by a processing system such as processing system **120**. Accordingly, as shown in the illustrated embodiment, the signal conversion system **130** can include one or more of a visual component **132**, an audio component **134** and a tactile component **136**.

[0071] In some embodiments, the visual component **132** can include a display device which can convert analog and/or digital signals into visual images and display them to the user. This may be accomplished by projecting an image or other data directly on the retina (i.e., retinal projection) and/or by displaying an image on an image plane such as a surface or screen within the wearer's field of view such as, but not limited to, an LCD screen, an OLED screen, a projector onto a surface such as a prism having an opaque surface, any

other display screen, or a combination of such devices. The display device may be driven by any of a wide variety of source materials, either carried on board the eyewear unit **110**, or in communication with the eyeglasses from another source, such as the modular unit **210** and/or the remote unit **310**, either via wired communication such as via a wired connection **158** such as a port and/or connector and/or wirelessly such as via the wireless system **152**.

[0072] In some embodiments, to provide such functionality, the display device can include a variety of components such as those described in connection with Figure 2, below. In some embodiments, the visual component **132** can include an image capture device which can convert visual images into analog and/or digital signals. For example, the image capture device can be a camera which can capture pictures and/or video. One or more visual components **132** can be removably coupled to one or more components of the system **100** to enable selective use of one or more of the visual components **132**. For example, in some embodiments, a user can attach a visual component **132** when needed to receive or transmit visual data, but then remove such visual component **132** when not needed, to reduce the weight and bulk of the eyewear and/or to change the appearance of the eyewear. The removable attachment between the visual component **132** and any other component of the system **100** can be accomplished using any suitable structures or methods, including but not limited to any of the wired or wireless structures or methods described and/or illustrated in this specification.

[0073] The visual component **132** can be used to provide the user with visualizations of data desired by the user. For example, the visual component **132** can be used to provide the user with a visualization of data received from one or more of the systems such as the sensors of the sensor system **140**. The visual component **132** can provide the user with a visual indicator of parameters being detected and/or measured by the sensors of the sensor system **140** such as, but not limited to, the user's heart rate, body temperature, velocity, acceleration, pace, distance traveled, power expended, energy expended, ambient temperature, pressure, altitude, body orientation and other such parameters and data. By providing a visual indication of such parameters, the user of the device can track such parameters on an ongoing or continuous or constant basis. Other visual indicators of parameters from other systems can also be shown such as the status of such systems. Other

types of data, such as pictures and/or videos, can be displayed using the visual component **132**. Moreover, the visual component **132** can be used as a camera to capture pictures and/or videos which can be advantageous to increase the safety of the user of the device. For example, the camera can be directed behind and/or laterally to provide the user with images of user's blind spots.

[0074] In some embodiments, the audio component **134** can include a speaker device which can convert analog and/or digital signals into sound waves and direct them to the user. This may be accomplished by generating pressure waves and directing these pressure waves to the user's ears, such as via a speaker, and/or by generating vibrations, such as via a bone-conduction speaker. In some embodiments, the audio component **134** can include an audio capture device which can convert sound waves into analog and/or digital signals. For example, the audio capture device can be a microphone.

[0075] The audio component **134** can be used to provide the user with audible representations of data desired by the user. For example, the audio component **134** can be used to provide the user with an audible representation of data received from one or more of the systems such as the sensors of the sensor system **140**. The audio component **134** can provide the user with intermittent and/or continuous audio updates of parameters being detected and/or measured by the sensors of the sensor system **140** such as, but not limited to, the user's heart rate, body temperature, velocity, pace, distance traveled, power expended, energy expended, ambient temperature, pressure, altitude and other such parameters and data. Other audio updates of parameters from other systems can be shown such as the status of such systems. Other types of data, such as music, voice calls, can also be audibly presented using the audio component **134**. The audio component **134** can be used as a microphone which can be used in conjunction with operating the eyewear unit **110**, modular unit **210**, and/or remote unit **310**, voice calls, and similar functions. In some embodiments, the microphone can be used in conjunction with a speaker for purposes of noise cancellation.

[0076] In some embodiments, the haptic component **136** can include a force or vibration device which can convert analog and/or digital signals into tactile feedback and direct them to the user. This may be accomplished by generating forces or vibrations, such as via one or more of an imbalanced motor, linear actuators, voice coils, piezoelectrics,

electrostatics, and/or electroactive polymers, etc. In some embodiments, the haptic component **136** can include a tactile capture device which can convert tactile forces into analog and/or digital signals. For example, the tactile capture device can comprise one or more piezoelectrics, electrostatics, electroactive polymers, any other device as desired, or a combination of any of these devices.

[0077] The haptic component **136** can be used to provide the user with tactile representations of data desired by the user. For example, the haptic component **136** can be used to provide the user with a tactile representation of data received from one or more of the systems such as the sensors of the sensor system **140**. Accordingly, the haptic component **136** can provide the user with intermittent and/or continuous tactile updates of parameters being detected and/or measured by the sensors of the sensor system **140** such as, but not limited to, the user's heart rate, body temperature, velocity, pace, distance traveled, power expended, energy expended, ambient temperature, pressure, altitude and other such parameters and data. In some embodiments, the haptic component **136** can vibrate to provide the user with notifications of trigger events. For example, the haptic component **136** can vibrate when an email or text message has been received, when a call is being received, and other types of trigger events.

[0078] In some embodiments, one or more haptic components **136** can be positioned on multiple components of the eyewear unit **110** and/or modular unit **210**. For example, haptic components **136** can be placed on lateral components of the eyewear unit **110**, such as earstems of an eyewear, and on anterior components of the eyewear unit **110**, such as the frame of the eyewear or the nosepiece of the eyewear. The different haptic components **136** can be activated separately or together based on the specific trigger event. For example, if an email or text message is received, a lateral haptic component **136** can be activated. If a call is being received, an anterior haptic component **136** can be activated. Separate activation of different haptic components **136** can help the user to more easily identify different trigger events.

[0079] In some embodiments, use of multiple haptic components **136** can be used to assist the user in navigation. For example, a haptic component **136** located to the left of the user's head can be activated to indicate to the user to turn left, a haptic component **136**

located to the right of the user's head can be activated to indicate to the user to turn right, and a haptic component **136** located to the front of the user's head can be activated to indicate to the user to continue proceeding forward. Use of haptic components **136** for navigation can be particularly beneficial for users of the eyewear unit **110** and/or modular unit **210** who are blind and/or deaf. This can also be particularly beneficial, even for those with full vision and/or hearing capabilities, when use of visual indicators and/or audio indicators may be intrusive or impractical during a particular activity, such as when other visual or audio indicators are already being utilized by a user. In some embodiments, the haptic components **136** can be used to inform a user of objects and/or persons in a user's blind spot. This can beneficially enhance the safety of the user of the device. As another example, visual indicators could potentially make the user more visible to others as a result of the light output in providing such indicators. Audio indicators can potentially be heard by others.

[0080] In some embodiments, the modular unit **210** and/or remote unit **310** can include signal conversion systems **230, 330** having components, features and/or functionality similar to or the same as any of those described above in connection with signal conversion system **130**. In some embodiments, the eyewear unit **110** can omit one or more components of the signal conversion system **130** such that a user can provide such components with signal conversion systems **230, 330**. For example, the eyewear unit **110** can omit the visual component **132**, audio component **134** and/or haptic component **136** thereby allowing the user to supply one or more of such components by connecting the eyewear unit **110** with a modular unit **210** and/or remote unit **310** via a wired connection and/or wirelessly. In some embodiments, an audio component such as an in-ear, on-ear, near-ear, over-the-ear, and/or an outwardly facing speaker can be provided on a modular unit **210** and/or remote unit **310**. For example, the remote unit **310** can have an outwardly facing speaker and serve as an external speaker. The eyewear unit **110** can include components which overlap with those of the signal conversion systems **230, 330** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the signal conversion system **130**. For example, the eyewear unit **110** can be provided with a speaker and a modular unit **210** and/or remote unit **310** can be provided with a microphone. In some embodiments, one

or more components of the signal conversion systems **230**, **330** of the modular unit **210** and/or remote unit **310** can be omitted.

Sensor System

[0081] With continued reference to the system **100** illustrated in Figure 1, the eyewear unit **110** of the system **100** can include a sensor system **140** which can be designed to obtain sensory data from the environment (e.g., an ambient or environmental sensor) and/or the user (a biometric and/or physiological sensor). Accordingly, as shown in the illustrated embodiment, the sensor system **140** can include a plurality of sensors including, but not limited to, one or more motion sensors **142**, one or more biometric and/or physiological sensors **144**, and one or more ambient or environmental sensors **146**. By utilizing data from the sensor system **140**, the eyewear unit **110** can provide beneficial data regarding the user's condition and/or the surrounding environment. The data received from the sensor system **140**, can be further processed by the processing system **120** to provide the user with general data about the user's activities, such as number of steps taken and duration of time the user was active.

[0082] The one or more motion sensors **142** can be designed to detect and/or measure movement or motion. The one or more motion sensors **142** can include any type of sensor which can detect and/or measure such movement or motion including, but not limited to, an accelerometer to detect and/or measure acceleration and a gyroscope to detect and/or measure orientation. Other types of sensors motion sensors **142** can also be used such as, but not limited to, a cadence sensor for measuring the rotational speed of a crank arm of a bicycle, a speed sensor for measuring the speed of a bike, a pedometer for measuring the number of steps taken by a user and similar sensors. It should be understood that some of these sensors may be more advantageously placed, for example, on one or more remote units **310** due to the positioning of such sensors relative to the user. For example, a cadence sensor and/or pedometer may be more advantageously placed proximate a user's feet.

[0083] The one or more physiological sensors **144** can be designed to detect and/or measure one or more physiologic parameters of the user. As such, the one or more physiological sensors **144** can include any type of sensor which can detect and/or measure

such physiological parameters including, but not limited to, sensors for monitoring cardiovascular parameters such as a heart rate sensor, a blood pressure sensor, a blood sugar sensor, and a blood-oxygen and/or blood CO₂ sensor, sensors for monitoring hydration levels and temperature of a user such as a perspiration sensor, a skin resistivity sensor, a hydration sensor, a dermal moisture sensor, an electrolyte sensor, and a body temperature sensor, and/or any other types of sensors, such as a lactic acid sensor and pO₂ sensor. Other types of physiological sensors **144** can be used as desired. It should be understood that some of these sensors may be more advantageously placed, for example, on one or more remote units **310** due to the positioning of such sensors relative to the user. For example, a heart rate sensor may be more advantageously placed in contact with or adjacent a user's chest.

[0084] The one or more ambient or environmental sensors **146** can be designed to detect and/or measure parameters of the surrounding environment. As such, the one or more ambient or environmental sensors **146** can include any type of sensor which can detect and/or measure such parameters including, but not limited to, an air temperature sensor, an air humidity sensor, a pressure sensor, an altitude sensor (such as an altimeter), an oxygen sensor, an air quality sensor, a wind speed sensor (such as a pitot tube), a solar irradiance sensor, a proximity sensor such as a sonar device, a magnetometer, and any other sensor which can detect parameters of the surrounding environment. In some embodiments, the ambient or environmental sensor **146** can include a range finder which can detect a distance to an object.

[0085] In some embodiments, the modular unit **210** and/or remote unit **310** can include sensor systems **240, 340** having components, features and/or functionality similar to that described above in connection with sensor system **140**. In some embodiments, the eyewear unit **110** can omit one or more components of the sensor system **140** such that a user can provide such components with sensor systems **240, 340**. For example, the eyewear unit **110** can omit the motion sensor **142**, physiological sensor **144** and/or ambient or environmental sensor **146** thereby allowing the user to supply one or more of such components by connecting the eyewear unit **110** with a modular unit **210** and/or remote unit **310** via a wired connection and/or wirelessly. In some embodiments, a heart rate sensor, gyroscope, accelerometer and/or magnetometer can be provided on a modular unit **210** and/or

remote unit **310**. Of course, the eyewear unit **110** can include components which overlap with those of the sensor systems **240**, **340** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the sensor system **140**. For example, the eyewear unit **110** can be provided with an accelerometer, gyroscope, and a modular unit **210** can be provided with a heart rate sensor and a remote unit **310** can be provided with a cadence sensor. In some embodiments, one or more components of the sensor systems **240**, **340** of the modular unit **210** and/or remote unit **310** can be omitted.

Input/Output (I/O) System

[0086] With continued reference to the system **100** illustrated in Figure 1, the eyewear unit **110** of the system **100** can include an I/O system **150** which can interface with one or more modular units **210** and/or one or more remote units **310**. As shown in the illustrated embodiment, the I/O system **150** can include a wireless system **152** as well as one or more wired connections **158**, such as ports and/or connectors, for removable mechanical and/or electrical coupling with another device such as one or more modular units **210**. As shown in the illustrated embodiment of Figure 1, the eyewear unit **110**, the modular unit **210**, and/or the remote unit **310** can each communicate with each other such that the units **110**, **210**, **310** can receive communications from and/or send communications to each other. For example, as shown in Figure 1, each of the respective input systems of each of the eyewear unit **110**, the modular unit **210**, and/or the remote unit **310** can receive communications from each of the respective output systems of each of the eyewear unit **110**, the modular unit **210**, and/or the remote unit **310**; and each of the respective output systems of each of the eyewear unit **110**, the modular unit **210**, and/or the remote unit **310** can send communications to each of the respective input systems of each of the eyewear unit **110**, the modular unit **210**, and/or remote unit **310**.

[0087] The wireless system **152** can include one or more receivers **154** to receive wireless signals from another device such as one or more remote units **310** and one or more transmitters **156** to send wireless signals to another device such as one or more remote units **310**. The wireless system **152** can include one or more transceivers which can perform both functions. The one or more receivers **154**, one or more transmitters **156**, and/or one or more

transceivers can include one or more antennas. The one or more antennas can be configured to receive one or more electronic signals including, but not limited to, Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, MMS, and/or any other type of signal. The one or more antennas can be positioned on any portion of the eyewear unit **110** including, but not limited to, portions of a face or frame such as a nosepiece region or nosepad, lateral regions of the face or frame, a brow, and/or orbital regions, portions of an earstem such as an anterior region of the earstem, a posterior region of the earstem, a bottom surface of the earstem, a top surface of the earstem, an outer surface of the earstem, and/or an inner surface of the earstem, and/or portions of a lens such as a periphery of the lens, an anterior surface of the lens, and/or a posterior surface of the lens. In some embodiments, the antennas can be positioned along bottom, top, outer, and/or inner surfaces of any portion of the eyewear unit **110**. In some embodiments, the antennas can be positioned along interior and/or exterior surfaces of the eyewear unit **110**. The one or more antennas can include movable antennas, such as antenna **1600**, discussed in further detail below in connection with Figures 14 and 15. For example, in some embodiments the movable antenna can be an articulating antenna which is coupled to the eyewear unit at a movable joint.

[0088] The one or more receivers **154** and/or one or more transmitters **156** can be designed to wirelessly communicate with other devices using one or more protocols. For example, the receiver **154** and/or transmitter **156** can include protocols such as Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, and MMS. The receiver **154** can be designed such that the eyewear unit **110** is viewed as an ANT+ master unit when communicating with other ANT+ devices. In some embodiments, the one or more receivers **154** and/or one or more transmitters **156** (or transceivers) can include two or more protocols such that the eyewear unit **110** can advantageously be used with a wider variety of devices such as modular units **210** and/or remote units **310**. In some embodiments, the one or more receivers and/or one or more transmitters (or transceivers) can utilize the two or more protocols simultaneously. In some embodiments, the receiver **154** can be designed to receive signals from a global positioning satellite (GPS). As shown in the

illustrated embodiment, the wireless system **310** can be designed to wirelessly communicate with the one or more remote units **310**.

[0089] The one or more wired connections **158**, such as ports and/or connectors, can allow for removable mechanical and/or electrical coupling with other devices such as one or more modular units **210**. The one or more wired connections **158** can be designed to be universally compatible with a variety of devices. For example, in some embodiments, the one or more wired connections **158** can include a Universal Serial Bus (USB) port and/or connector, such as USB 1.0, USB 2.0, USB 3.0, USB 3.1, and including microUSB and type-C ports and/or connectors, an IEEE 1394 (FireWire) port and/or connector, an Ethernet port and/or connector, a Thunderbolt port and/or connector, a Displayport port and/or connector, a DVI port and/or connector, an HDMI port and/or connector, an optical port and/or connector, a coaxial port and/or connector, and/or other ports and/or connectors. In some embodiments, the one or more wired connections **158** can have different mechanical and/or electrical connectors to allow for an even wider range of devices to be used. For example, a first wired connection **158** can be a USB 3.0 port or connector whereas a second wired connection **158** can be a Thunderbolt port or connector. As shown in the illustrated embodiment, the one or more wired connections **158** can be designed to mechanically and/or electrically couple with the one or more modular units **210**. The wired connections **158** can be positioned on any portion of the eyewear unit **110** including, but not limited to, portions of a face or frame such as a nosepiece region or nosepad, lateral regions of the face or frame, a brow, and/or orbital regions, portions of an earstem such as an anterior region of the earstem, a posterior region of the earstem, a bottom surface of the earstem, a top surface of the earstem, an outer surface of the earstem, and/or an inner surface of the earstem, and/or portions of a lens such as a periphery of the lens, an anterior surface of the lens, and/or a posterior surface of the lens. In some embodiments, the wired connections **158** can be positioned along bottom, top, outer, and/or inner surfaces of any portion of the eyewear unit **110**. In some embodiments, the wired connections **158** can be positioned along interior and/or exterior surfaces of the eyewear unit **110**.

[0090] The one or more modular units **210** can have different shapes, appearances, features, and/or functionality, but the modular units **210** can include generally

the same mechanical and/or electric connectors to wired connections **158** to enable interchangeability. In some embodiments, a vendor can provide a selection (simultaneously or over time) of a plurality of different interchangeable modular units **210** with multiple different shapes, sizes, and/or colors, and/or with different features and/or functionality. In this way, a user can purchase different modular units **210** to customize the user's system **100**, to upgrade the user's system **100**, and/or to replace broken or damaged components in the user's system **100**. In some embodiments where the modular unit **210** includes a universally compatible wired connection, such as a USB connector, the modular unit **210** can be connected to other devices which have a similar connector. For example, the modular unit **210** could be attached to devices such as, but not limited to, a computer, a smartphone, an audio/video player, and a vehicle entertainment system. In some embodiments, each or all of the modular units **210** can be standalone devices which can be removed from the eyewear unit **110** and function separately from the eyewear unit **110** or any other electronic devices.

[0091] In some embodiments, the modular units **210** are mounted in close proximity to the eyewear unit **110**. The eyewear unit **110** and modular unit **210** can be coupled to form a relatively compact, combined unit. This can be particularly advantageous in many situations as this can reduce the burden on the user of the system **100**. By placing both the eyewear unit **110** and the modular unit **210** in an eyewear, the user need not be inconvenienced with using such remote devices.

[0092] In some embodiments, the modular unit **210** and/or remote unit **310** can include I/O systems **250**, **350** having components, features and/or functionality similar to that described above in connection with I/O system **150**. For example, in some embodiments, the modular unit **210** can include a wireless system having a receiver, transmitter and/or transceiver similar to that discussed in connection with I/O system **150**. In some embodiments, the eyewear unit **110** can omit one or more components of the I/O system **150** such that a user can provide such components with I/O systems **250**, **350**. For example, the eyewear unit **110** can omit the wireless system **152** including the receiver **154** and/or transmitter **156**, and/or wired connection **158** thereby allowing the user to supply one or more of such components by connecting the eyewear unit **110** with a modular unit **210** and/or remote unit **310** having one or more of such components. In some embodiments, a port

and/or connector can be provided on a modular unit **210** and/or remote unit **310** to allow additional modular units **210** to be attached to the system **100**. The eyewear unit **110** can include components which overlap with those of the I/O systems **250**, **350** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the I/O system **150**. For example, the eyewear unit **110** can be provided with a wireless system **152** having Bluetooth and/or ANT+ protocols and the modular unit **210** can be provided with a wireless system having different protocols such as ZigBee or Wi-Fi. In some embodiments, the eyewear unit **110** can be provided with no wireless system **152** and the modular unit **210** can be provided with a wireless system having one or more different protocols. This can be particularly beneficial when wireless protocols are often updated thereby reducing the likelihood that the eyewear unit **110** will have an antiquated wireless protocol. In some embodiments, one or more components of the I/O systems **250**, **350** of the modular unit **210** and/or remote unit **310** can be omitted.

[0093] While the input/output system **110** have been generally described as having a wireless system **152** for communication with remote units **310** and one or more wired connections **158** for communication with modular units **210**, in some embodiments communications between the eyewear unit **110** and one or more modular units **210** can be via the wireless system **152** and/or wired connections **158** and/or communications between the eyewear unit **110** and the remote units **310** can be via the wireless system **152** and/or wired connections **158**. In some embodiments, communications between the modular unit **210** and the remote unit **310** can be via wireless systems of input/output systems **250**, **350**. In some embodiments, communications between the modular unit **210** and the remote unit **310** can be via one or more wireless systems and/or wired connections of the input/output systems **250**, **350**.

User Interface System

[0094] With continued reference to the system **100** illustrated in Figure 1, the eyewear unit **110** of the system **100** can include a user interface system **160** which can be designed to allow the user to operate the eyewear unit **110**, modular unit **210**, and/or remote

unit **310**. As shown in the illustrated embodiment, the user interface system **160** can include one or more actuators **162** and/or one or more sensors **164**.

[0095] In some embodiments, the one or more actuators **162** can include mechanical switches such as, but not limited to, toggle, rocker, button, and/or rotary switches. One or more actuators **162** can advantageously be used to provide tactile feedback when operating the switch such that the user can easily operate the device without having to view the actuators **162** directly. The actuators **162** can be used to control one or more operating parameters such as the on-off state of the eyewear unit **110**, modular unit **210**, and/or remote unit **310**, audio volume control, and/or video brightness control, etc.

[0096] In some embodiments, the one or more sensors **164** can include sensors which detect contact such as capacitive and/or resistive sensors. In some embodiments, the capacitive and/or resistive sensors can be designed to detect contact with a user's finger. For example, the user interface system **160** can include a touch screen having capacitive and/or resistive sensors on which the user can use different gestures to modify parameters of the eyewear unit **110**, modular unit **210** and/or remote unit **310**. Such gestures can include, but are not limited to, a frontward swipe, a rearward swipe, an upward swipe, a downward swipe, one or more taps such as a double or triple tap, pressing the screen for a specific duration of time, a multiple position tap, and any combination of the above. The touch screen can be sized to fit along any portion of the eyewear unit **110**, including but not limited to a face and/or an earstem of the eyewear unit **110**.

[0097] In some embodiments, the modular unit **210** and/or remote unit **310** can include user interface systems **260**, **360** having components, features and/or functionality similar to that described above in connection with user interface system **160**. In some embodiments, the eyewear unit **110** can omit one or more components of the user interface system **160** such that a user can provide such components with user interface systems **260**, **360**. For example, the eyewear unit **110** can omit the actuator **162** and/or sensor **164** thereby allowing the user to supply one or more of such components by connecting the eyewear unit **110**, via a wired connector and/or wirelessly, with a modular unit **210** and/or remote unit **310** having one or more of such components. This can be beneficial as it can allow a user to select a type of user interface that the user prefers and/or switch the type of user interface.

For example, a user may find it advantageous to use a user interface having tactile buttons for certain activities and may find it more advantageous to utilize a user interface having touch capabilities for other activities. Accordingly, the user may wish to swap between a tactile button user interface with a touch user interface based on the specific activity. Of course, the eyewear unit **110** can include components which overlap with those of the user interface systems **260, 360** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the user interface system **160**. Of course, in some embodiments, one or more components of the user interface systems **260, 360** of the modular unit **210** and/or remote unit **310** can be omitted.

Power System

[0098] With continued reference to the system **100** illustrated in Figure 1, the eyewear unit **110** of the system **100** can include a power system **170** which can be designed to provide energy to the one or more systems of the eyewear unit **110**, modular unit **210** and/or remote unit **310**. As shown in the illustrated embodiment, the power system **170** can include an energy storage component **172** and/or an energy generation component **174**.

[0099] The energy storage component **172** can be a device designed to store energy for use with the eyewear unit **110**, modular unit **210** and/or remote unit **310**. For example, the energy storage component **172** can be a battery device such as primary cell (non-rechargeable) and/or a secondary cell (rechargeable) such as, but not limited to, a Li-ion battery, LiPo battery, NiCad battery, and Ni-MH battery. The battery device can be designed to provide between about 50 mAh to about 500 mAh, about 150 mAh and/or any other energy storage capacity as desired. In some embodiments, the energy storage component **172** can be a capacitor, fuel cell, or other device which can store energy for later use.

[0100] The energy generation component **174** can be a device designed to generate energy from another source. The energy generation component **174** can be a device designed to convert kinetic energy, solar energy and/or thermal energy to electrical energy for powering the systems of eyewear unit **110**, modular unit **210** and/or remote unit **310**. The energy generation component **174** can be a device designed to convert electromagnetic

energy to electrical energy. In such an embodiment, the eyewear unit **110**, modular unit **210** and/or remote unit **310** can be wirelessly powered and charged.

[0101] In some embodiments, the modular unit **210** and/or remote unit **310** can include power systems **270**, **370** having components, features and/or functionality similar to that described above in connection with power system **170**. In some embodiments, the eyewear unit **110** can omit one or more components of the power system **170** such that a user can provide such components with power systems **270**, **370**. For example, the eyewear unit **110** can omit the energy storage component **172** and/or energy generation component **174** thereby allowing the user to supply one or more of such components by connecting the eyewear unit **110** with a modular unit **210** via a wired connection and/or wirelessly. In some embodiments, the modular unit **210** can be provided with an energy storage component such as a battery. The eyewear unit **110** can include components which overlap with those of the power systems **270**, **370** of the modular unit **210** and/or remote unit **310**. This can advantageously supplement and/or enhance the functionality of the power system **170**. For example, the modular unit **210** can include an energy storage component to supplement the energy storage component **172** of the eyewear unit **110** thereby increasing the duration of operation of the eyewear unit **110**, modular unit **210** and/or remote unit **310**. In some embodiments, one or more components of the power systems **270**, **370** of the modular unit **210** and/or remote unit **310** can be omitted.

Examples of Display Devices

[0102] With reference to the embodiment of electronics **400** illustrated on Figure 2, the display device can be operative to project at least one optical beam onto a retina of the wearer and/or displaying an image on a surface or screen within the wearer's field of view. The display device can be in optical and/or electrical communication with electronics **400** which provide the display device with optical image data that is utilized to produce the optical beam. The display device can include a transmission component **440**, as described below.

[0103] The electronics **400** can include an electronics module **401** that receives image data from an image source **402**. The image data can include data utilizable to create an

image, such as placement and intensity of color in the image. The electronics module **401**, as is known in the art, can be used to decipher the image data such that it can be optically portrayed by the electronics **400**. The electronics **400** can include one or more light sources **404**, color combining optics **406**, a photonics module **408**, and/or modulators **410**, etc. Any or all of these components can be in electronic communication with the electronic module **401** and receive the deciphered imaged data therefrom and create the image based on the deciphered image data.

[0104] The light sources **404** can convey the image in RGB (red, green, blue) and/or can be modulated and combined utilizing the color combining optics **406**, the photonics module **408**, and the modulators **410**. Finally, a scanner module **412**, which can be mounted on the display device, can project the optical beam onto the retina of the wearer in order to raster scan or “paint” or convey the optical image onto the retina. The scanner module **412** can include one or more micro electro-mechanical structures such as scanners **414**, a diffuser **415**, and/or a focusing lens **416**. The image can be painted or conveyed in RGB at the rate of at least approximately 30 times per minute or more for premium resolution. However, other scanning rates can also be used as desired. It should be understood that these components and systems can also be adapted for use in displaying an image on a surface or screen within the wearer’s field of view.

[0105] As mentioned above, embodiments can be favorably implemented in combination with various electronics **400**; it is also contemplated that with the advance of science, new and improved electrical and optical components can become available and be incorporated into embodiments. The optical beam can be directly or indirectly projected toward the eye of the wearer. Therefore, although Figure 2, as well as other figures, illustrate direct retinal projection, it is contemplated that the optical beam can be reflected off of other structures incorporated into the optical element, such as the lens or lenses of an eyewear or other reflective surface. Moreover, it should also be understood that at least some components described in connection with Figure 2 can also form part of other systems of the eyewear unit **110** including, but not limited to, the processing system **120** and the power system **170**.

[0106] In some embodiments, the display device can include visual display and/or optical components. These components can include a display such as a liquid crystal display (LCD), a plasma display, a semiconductor device (LD), a light-emitting diode (LED), an organic light emitting diode (OLED), active OLED, AMOLED, super AMOLED, a projector, direct retinal projection through virtual retinal display (VRD) or retinal scan display (RSD) using a retinal projector (RP), micro-electro-mechanical systems display, an electroluminescence (EL), a cathode ray tube (CRT), a digital micromirror device (DMD), prism(s), lens(es), fiber-optic transmission component(s), mirror(s), a holographic optical element (HOE), laser projection, 3D display components or circuitry, or another emissive, transmissive, or reflective display technology, or the like is preferably used. The system can produce real or virtual images for user perception. Further, the system can provide augmented visuals of natural objects perceived by the user.

[0107] The viewing plane for the system can be on a lens of the eyewear (goggles or eyeglasses) or spaced from the lens (either in front or behind the lens). The viewing plane can be real or virtual. Further, the system and/or eyewear can also comprise variable light attenuation features (e.g. electronic variable light attenuation) in the lens(es) or otherwise to enhance video display perception. The viewing plane can incorporate one or more display and/or light attenuation components.

[0108] In some embodiments, the display device can have a viewing surface or plane positioned along a surface of a lens or other surface of the eyewear. The display device can comprise one or more visual display units. The display device, such as an OLED display or otherwise, can provide a real or virtual image for the wearer. The display device can also incorporate light attenuation technology, such as electronic variable light attenuation. In some embodiments, the display device can be fitted onto a front or rear surface of a lens to provide a permanent or removable engagement with the lens.

[0109] In some embodiments, the display device can be positioned on an arm, such as a movable or articulating arm, of an eyewear unit or other component of the system.

Embodiments of Network Configurations

[0110] With reference now to the embodiment of the electronic device or system **500**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figures 3A and 3B, the system **500** can be designed to obtain, process, and/or convey data to a user of the system **500**. The system **500** can include both an eyewear unit **510** and a modular unit **550**, shown here as an earbud (e.g., a device that can be positioned in and/or retained by an inner portion of an ear), which can be removably coupled to the eyewear unit **510**. The eyewear unit **510** and the modular unit **550** can be similar to the eyewear unit **110** and the modular unit **210** described above in connection with Figure 1. Accordingly, the eyewear unit **510** and the modular unit **550** can include systems such as, but not limited to, a processing system, a signal conversion system, a sensor system, an input/output (I/O) system, a user interface system and a power system.

[0111] The eyewear unit **510** can include a microprocessor to process data, memory for data storage, wireless receivers and transmitters (or transceivers) with protocols used in the industry, such as Bluetooth and/or ANT+, or any future protocols to communicate with modular units and/or remote devices **580**, **582**, **584**, and a plurality of sensors such as environmental sensors (e.g., an altimeter, a temperature sensor, a humidity sensor, and the like), physiological sensors (e.g., a heart rate sensor, a blood-oxygen sensor, and the like), motions sensors (e.g., accelerometers, gyroscope, and the like), and/or other sensors. As shown in the illustrated embodiment, the components of one or more systems of the eyewear unit **510** can be integrated into an eyewear **512** thereby providing a relatively compact form factor. Accordingly, components such as a microprocessor, memory, wireless receivers and transmitters (or transceivers), and sensors can be provided within the multiple earstems **514**, frame **516**, nosepiece **518**, and/or lens or lenses **520** of the eyewear **512**.

[0112] In order to removably couple the modular unit **550** to the eyewear unit **510**, the eyewear unit **510** can include a port **522** such as a USB 3.0 Type-C port. This port **522** can also be used for other functionality such as updating software on the eyewear unit **510** and charging the eyewear unit **510**. As shown in the illustrated embodiment, the port **552** is positioned along a bottom portion of an earstem **514**. The port **552** can be positioned on any portion of the eyewear unit **510** including, but not limited to, portions of a face or frame such as a nosepiece region or nose pad, lateral regions of the face or frame, a brow,

and/or orbital regions, portions of an earstem such as an anterior region of the earstem, a posterior region of the earstem, a bottom surface of the earstem, a top surface of the earstem, an outer surface of the earstem, and/or an inner surface of the earstem, and/or portions of a lens such as a periphery of the lens, an anterior surface of the lens, and/or a posterior surface of the lens. In some embodiments, the port **552** can be positioned along bottom and/or top surfaces of the eyewear unit **510**. In some embodiments, the port **552** can be positioned along bottom, top, outer, and/or inner surfaces of any portion of eyewear unit **510**. While a single port **552** is described herein, two or more ports may be used and positioned on the eyewear unit **510**.

[0113] A simplified schematic of modular unit **550** is illustrated in Figure 3B. As shown in the illustrated embodiment, the modular unit **550** can include one or more modules **552**, **554**. For example, in some embodiments, module **552** can include components of a signal conversion system such as, but not limited to, a microphone, a speaker, a video display, a camera, haptics. As shown, module **552** can include an in-ear or mid-ear speaker. In some embodiments, module **554** can include a microprocessor, multiple sensors such as, but not limited to, an accelerometer, gyroscope, and magnetometer. The housing of the modular unit **550** can include one or more moveable joints **556** which permit translation and/or rotation about the joints **556**. Accordingly, this can advantageously allow a user to orient components of the modular unit **550**, such as the module **552**, into a proper position such that the user can utilize such components in a comfortable manner. In order to removably couple the modular unit **550** to the eyewear unit **510**, the modular unit **550** can include a connector **558** such as those described above in connection with input/output system **150**, including, but not limited to, a USB 3.0 Type-C connector. The modular unit **550** can receive communications from the eyewear unit **510** via the connection; and the eyewear unit **510** can receive communications from the modular unit **550** via the connection.

[0114] In some embodiments, a heart rate sensor can be provided in or proximate the module **552**. For example, the heart rate sensor can be a valence cell provided on or proximate the speaker of module **552** illustrated in Figure 3B. The modular unit **550** can include an additional port or connector. In some embodiments, the user can have an array of different modular units, such as but not limited to multiple single-purpose modular units,

each with a different sensor, so that the wearer can select one or more desired modular units to connect to the eyewear unit **510** to customize the nature of the data to the activity being performed by the wearer.

[0115] As shown in the illustrated embodiment, the eyewear unit **510** and/or modular unit **550** can wirelessly communicate with one or more remote units such as first, second and third remote units **580**, **582**, **584**. The first remote unit **580** can be an electronic device having advanced processing capabilities such as a smartphone, PDA, tablet, laptop, and the like. In some embodiments, when the eyewear unit **510** and/or the modular unit **550** is in communication with such a device, additional features and/or functionality from such electronic devices can be transferred directly to the eyewear unit **510**, to the modular unit **550**, and/or to the eyewear unit **510** via the modular unit **550** or vice versa. For example, the electronic device can have software applications which allow for advanced user voice controls over the electronic device such as voice control software or can have software applications allowing music playback of MP3s or music streaming. Such features and/or functionality can be transferred to the eyewear unit **510**, to the modular unit **550**, and/or to the eyewear unit **510** via the modular unit **550** or vice versa. The second remote unit **582** and third remote unit **584** can be other types of devices having less advanced processing capabilities such as, but not limited to, watches and sensors that can be worn by the wearer elsewhere on the wearer's body. It should be appreciated that the eyewear unit **510** and/or modular unit **550** can wirelessly communicate with remote units **580**, **582**, **584** via the same or different wireless protocols. As noted above, in some embodiments, the user can have an array of different remote units, such as but not limited to multiple single-purpose remote units each with a different sensor, so that the wearer can select one or more desired remote units to connect to the eyewear unit **510** to customize the nature of the data to the activity being performed by the wearer.

[0116] In some embodiments, the modular unit can be in wireless communication with some or all of the remote units. Moreover, in some embodiments, the modular unit can be in communication with additional modular units (not shown). In some embodiments, the eyewear unit need not be in communication with some or all of the modular and/or remote

units such as remote units. As shown in the illustrated embodiment, the modular unit can be in communication with some or all of the remote units.

[0117] With reference now to the embodiment of the electronic device or system **600**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 4, the system **600** can be similar to system **500**. As such, the system **600** can include both an eyewear unit **610** and a modular unit **650** which can be removably coupled to the eyewear unit **610**. The eyewear unit **610** and modular unit **650** can be similar to eyewear unit **510** and modular unit **550**. As shown in the illustrated embodiment, the eyewear unit **610** and/or modular unit **650** can wirelessly communicate with one or more remote units such as first, second and third remote units **680**, **682**, **684**. The first, second and third remote units **680**, **682**, **684** can be devices having less advanced processing capabilities such as, but not limited to, sensors. In some embodiments, the user can have an array of different remote units, such as but not limited to multiple single-purpose remote units, each with a different sensor, so that the wearer can select one or more desired remote units to connect to the eyewear unit **610** to customize the nature of the data to the activity being performed by the wearer. It should be appreciated that the system **600** can be used as a standalone unit without electronic devices with advanced processing capabilities such as smartphones, PDAs, and tablets. Rather, in some embodiments, such advanced processing capabilities can already be provided on the eyewear unit **610** and/or modular unit **650**.

Embodiments of Input/Output Systems

[0118] With reference now to the embodiments of electronic devices or systems **700a**, **700b**, **700c**, such as wearable devices or systems. The wearable device or system can be a network or communication device or system. As illustrated in Figures 5A-5C, the systems **700a**, **700b**, **700c** can include I/O systems **710a**, **710b**, **710c**, in the form of portion **712a**, **712b**, **712c**, **713c** to allow the user to connect the eyewear units **720a**, **720b**, **720c** to modular units **730a**, **730b**, **730c**. As shown in the illustrated embodiments, the ports **712a**, **712b**, **712c**, **713c** can be placed at various locations of the eyewear thereby providing vertical attachment as shown with port **712a**, anterior-posterior attachment as shown with portion

712b, lateral attachment as shown in port **712c**, and internal attachment as shown with port **713c**. The ports **712a**, **712b**, **712c**, **713c** can be oriented at any other angle, including between about 0 degrees (vertical) and about 360 degrees, between about 0 degrees (vertical) and about 90 degrees (anterior-posterior), about 30 degrees, about 45 degrees (see for example Figures 9A-B), and any other range of degrees within these ranges. As shown in Figure 5C, a wire **714c** can be used to facilitate connection with the ports.

Embodiments of Modular Units

[0119] With reference now to the embodiment of the electronic device or system **800**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 6, the system **800** can be designed to obtain, process, and/or convey data to a user of the system **800** similar to the systems described herein, such as systems **100**, **500**, **600**, **700a-c**. The system **800** can include both an eyewear unit **810** and a modular unit **850** which can be removably coupled to the eyewear unit **810**.

[0120] As shown in the illustrated embodiment, the eyewear unit **810** can include a connector **812**, such as a USB 3.0 Type-C connector, positioned at an end of a moveable arm **814**, and can be configured to communicate using any of the features or capabilities associated with the protocols for such connector or any other suitable connector. The moveable arm **814** can be moveable relative to the other portions of the eyewear unit **810**. For example, as shown in the illustrated embodiment, the other end of the moveable arm **814** can be pivotally coupled to the remaining portions of the eyewear unit **810** such that the moveable arm **814** can rotate relative to the remaining portions of the eyewear unit **810**. In some embodiments, the moveable arm **814** can translate relative to the remaining portions of the eyewear unit **810**.

[0121] As shown in the illustrated embodiment, the modular unit **850** can be used in connection with not only the eyewear unit **810** but also other devices. For example, the modular unit **850** can be used with an audio capable **860** for connection to other devices, such as an audio device. As shown in the illustrated embodiment, both the eyewear unit **810** and the audio cable **860** can connect to the modular unit **850** via a port **854**. The modular unit

850 can include an in-ear or mid-ear speaker **852**. In order to removably couple the modular unit **850** to the eyewear unit **810**, the modular unit **850** can include a port **854** such as a USB 3.0 Type-C port. As shown in the illustrated embodiment, the port **854** can be used to connect the modular unit **850** to other devices, such as an audio cable **860**, to allow the modular unit **850** to be used with other types of devices. Accordingly, the speaker **852** of the modular unit **850** can be used as headphones, for example, and can be used with other devices such as, but not limited to, audio/video players and smartphones.

[0122] Any of the modular units described herein can include one or more functionalities. For example, as shown in the embodiment of Figure 7, the modular unit **900** can include an audio signal conversion system and a sensor system. The modular unit **900** can include an in-ear or mid-ear speaker **902** and/or a wind speed sensor **904** in the form of a pitot tube, for example. In some embodiments, in order to removably couple the modular unit **900** to an eyewear unit, such as eyewear unit **810**, the modular unit **900** can include a port **906** such as a USB 3.0 Type-C port. As another example, as shown in the embodiment of Figure 8, the modular unit **1000** can include an in-ear or mid-ear speaker **1002** as well as a biometric sensor **1004** in the form of a biometric tape placed on a panel **1006**. As shown in the illustrated embodiment, the modular unit **1000** can include a moveable arm **1007**. In some embodiments, in order to removably couple the modular unit **1000** to an eyewear unit, such as eyewear unit **810**, the modular unit **1000** can include a port **1008** such as a USB 3.0 Type-C port.

[0123] Any of the modular units described herein can include multiple ports and/or connectors. For example, in some embodiments, the modular unit can include a first port and/or connector attached to an eyewear unit and a second port and/or connector attached to another modular unit. This can provide additional advantages for a user by allowing an even greater degree of customizability of the eyewear system. Such customization can include the ability to use particular modular units to obtain a fit which is best suited for the wearer. For example, reference is made to the embodiment of the electronic device or system **1100**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figures 9A-B, the system **1100** can include an eyewear unit **1110**, a modular unit **1150** in the form of a

boom, and a second modular unit **1160** in the form of an earbud. This can advantageously allow a greater range of interchangeability. For example, by providing a modular unit **1150** in the form of a boom, a user of the device can interchange the modular unit **1150** to better fit the user's preference, such as a different shape or material, so that the modular unit **1160** can be more comfortably positioned with respect to the user.

[0124] As shown in the illustrated embodiment, the boom **1150** includes body **1152**. In some embodiments, the body **1152** can be formed from a resilient or flexible material. The resilient or flexible material can be sufficiently rigid such that it maintains a deformed shape after deformation. This can allow the shape of the body **1152** to be altered by the user to attain a better fit. In some embodiments, the resilient or flexible material can be designed to return to its prior shape after some degree of deformation.

[0125] In some embodiments, modular units **1150**, **1160** can incorporate any of the systems and components described herein such as processing system **220**, signal conversion system **230**, sensor system **240** (ambient or environmental, motion, biometric, and/or physiological), input/output (I/O) system **250**, user interface system **260**, and/or power system **270**. For example, in some embodiments, modular unit **1150** can include an input/output system. This input/output system can be used, in some embodiments, to provide communication between the eyewear unit **1110** and the modular unit **1160**. In this manner, the eyewear unit **1100** can receive communications from one or both of the modular units **1150**, **1160**, the modular unit **1150** can receive communications from one or both of the eyewear unit **1100** and modular unit **1160**, and/or the modular unit **1160** can receive communications from one or both of the eyewear unit **1100** and the modular unit **1150**. As shown in the illustrated embodiment, the body **1152** has a connector **1154** at one end for attachment to a port **1112** of the eyewear unit **1110** and a port **1156** at a second end for receiving a connector **1162** of the modular unit **1160**. In some embodiments, modular unit **1150** can include a processing system and/or sensor system similar to those described herein. For example, the modular unit **1150** can include a heart rate sensor and an accelerometer.

[0126] With reference now to the embodiment of the electronic device or system **1200**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 10, in some embodiments, the

modular unit **1250** can form at least a portion of the eyewear unit **1210** for supporting the eyewear unit **1210** on a user. As shown in the illustrated embodiment, the eyewear unit **1210** can include a partial earstem **1212** having one or more connectors **1214**, **1216** onto which the modular unit **1250** can be connected. As shown in the illustrated embodiment, the modular unit **1250** can form a posterior portion of the earstem and can include an earstem portion **1252** with an integrated boom **1254**. In some embodiments, the earstem portion **1252** and/or the integrated boom **1254** can be formed from a resilient or flexible material. The resilient or flexible material can be sufficiently rigid such that it maintains a deformed shape after deformation. This can allow the shape of the earstem portion **1252** and/or integrated boom **1254** to be altered by the user to attain a better fit. In some embodiments, the resilient or flexible material can be designed to return to its prior shape after some degree of deformation. As shown in the illustrated embodiment, another modular unit **1256**, such as an earbud, can be removably attached to the integrated boom **1254**. In some embodiments, modular units **1250**, **1256** can incorporate any of the systems and components described herein such as processing system **220**, signal conversion system **230**, sensor system **240** (ambient or environmental, motion, biometric, and/or physiological), input/output (I/O) system **250**, user interface system **260**, and/or power system **270**. In some embodiments, electronics can be contained within the earstem portion **1252** and/or the boom **1254**.

[0127] While the modular unit **1250** incorporates an earstem portion **1252** and an integrated boom **1254**, in some embodiments the boom **1254** can be separate from the earstem portion **1252**. This can advantageously allow for a greater degree of modularity of components of the system **1200**. For example, the boom **1254** can be removably attachable to the earstem portion **1252** and/or the eyewear unit **1210**. In some embodiments, the second modular unit **1256** can be integrated with the boom **1254** and/or the earstem portion **1252**. In some embodiments, different modular units can include different shapes of earstems allowing a user to choose a modular unit which can provide a more comfortable fit. While the illustrated system **1200** includes a modular unit **1250** which forms a posterior portion of an earstem, the modular unit **1250** can be designed such that it forms any other portion of the earstem including the anterior portion, a middle portion, and/or the entirety of the earstem.

[0128] In some embodiments, the modular unit can form other portions of an eyewear. For example, the modular unit can be designed such that it functions as a nosepiece for the eyewear. In some embodiments, the modular unit can be designed such that it functions as a portion of the face of the eyewear such as a portion of the orbitals, the brow, an earsock, and/or a decorative element such as an icon.

[0129] With reference now to the embodiment of the electronic device or system **1300**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 11, the system **1300** can include an eyewear unit **1310** and a modular unit **1350**. As shown in the illustrated embodiment, the eyewear unit **1310** can include a port **1312** such as a USB 3.0 Type-C port for receiving a corresponding connector **1352** such as a USB 3.0 Type-C connector of the modular unit **1350**. Other types of ports **1312** and/or connectors **1352** can be used, such as those described herein. The eyewear unit **1310** can include one or more couplings **1314**, such as protrusions, to receive one or more couplings **1354**, such as complementary protrusions, of the modular unit **1350**. These couplings **1314**, **1354** can provide a more secure connection between the eyewear unit **1310** and the modular unit **1350** and can reduce the stress applied to the port **1312** and connector **1352**. In some embodiments, couplings **1314**, **1354** may be snap-fit mechanical couplings. As shown in the illustrated embodiment, the modular unit **1350** can include a boom **1356**, which includes one or more movable arms, to allow a user to properly position a portion of the modular unit **1350**, such as the speaker **1358**, with respect to the user. For example, in some embodiments the movable arms can be articulating arms which include one or more movable joints. In some embodiments, one or more components of the processing system **220**, the signal conversion system **230**, the sensor system **240**, the input/output system **250**, the user interface system **260**, the power system **270**, and/or any other components can be positioned within the movable arms of the boom **1356** of the modular unit **1350** or any other portion of the modular unit **1350**. In some embodiments, two or more ports and/or two or more connectors can be used. For example, in some embodiments, a first port and connector can be used for power transmission between the eyewear unit **1310** and the modular unit **1350**, and a second port and connector can be used for data transmission between the eyewear unit **1310** and the modular unit **1350**. In some

embodiments, port **1312** and connector **1352** can be used for data transmission and couplings **1314**, **1354** can be replaced with a port and connector for power transmission. In some embodiments, two or more couplings can be used.

[0130] With reference now to the embodiment of the electronic device or system **1400**, such as a wearable device or system. The wearable device or system can be a network or communication device or system. As illustrated in Figure 13, the system **1400** can include an eyewear unit **1410** and a modular unit **1450**. As shown in the illustrated embodiment, the eyewear unit **1410** can include a port **1412** such as a USB 3.0 Type-C port for receiving a corresponding connector **1452** such as a USB 3.0 Type-C connector of the modular unit **1450**. The eyewear unit **1410** can include one or more couplings **1414**, such as protrusions, to receive one or more couplings **1454**, such as complementary protrusions, of the modular unit **1450**. In some embodiments, couplings **1414**, **1454** may be snap-fit mechanical couplings. As shown in the illustrated embodiment, the modular unit **1450** can include two or more components **1458**, **1460** attached via a link **1456**. As shown in the illustrated embodiment, the link **1456** can be semi-rigid or flexible such as a flexible, flat wire. In some embodiments, one or more components of the processing system **220**, the signal conversion system **230**, the sensor system **240**, the input/output system **250**, the user interface system **260**, the power system **270**, and/or any other components can be included with the components, such as component **1458**, **1460**, and/or link **1456** of the modular unit **1450**. For example, the component **1460** can include components such as one or more speakers. The component **1458** can include components such as one or more connectors **1452**. In some embodiments, two or more components, such as components **1458**, **1460**, can be separable and can, in some embodiments, allow the components to be used in conjunction with other devices. For example, the component **1460** can be detached and used as a speaker for other electronic devices. In some embodiments, two or more ports and/or two or more connectors can be used. For example, in some embodiments, a first port and connector can be used for power transmission between the eyewear unit **1410** and the modular unit **1450**, and a second port and connector can be used for data transmission between the eyewear unit **1410** and the modular unit **1450**. In some embodiments, port **1412** and connector **1452** can be used for

data transmission, and couplings **1414**, **1454** can be replaced with a port and connector for power transmission. In some embodiments, two or more couplings can be used.

[0131] As discussed above in connection with Figure 1, any of the modular units discussed herein can include one or more components of the processing system **220**, the signal conversion system **230**, the sensor system **240**, the input/output system **250**, the user interface system **260**, the power system **270**, and/or any other components. In some embodiments, the modular units can include one or more sensors such as those described in connection with sensor system **140**, including, but not limited to, motions sensors designed to detect and/or measure movement or motion such as an accelerometer, a gyroscope, a cadence sensor, a speed sensor, a pedometer, and/or any other types of sensors, physiological sensors designed to detect and/or measure one or more physiologic parameters of the user such as a heart rate sensor, a heart rate sensor, a blood pressure sensor, a blood sugar sensor, and a blood-oxygen and/or blood CO₂ sensor, sensors for monitoring hydration levels and temperature of a user such as a perspiration sensor, a skin resistivity sensor, a hydration sensor, a dermal moisture sensor, an electrolyte sensor, and a body temperature sensor, and/or any other types of sensors, such as a lactic acid sensor and pO₂ sensor, and environmental sensors designed to detect and/or measure parameters of the surrounding environment, such as an air temperature sensor, an air humidity sensor, a pressure sensor, an altitude sensor (such as an altimeter), an oxygen sensor, an air quality sensor, a wind speed sensor (such as a pitot tube), a solar irradiance sensor, a proximity sensor such as a sonar device, a magnetometer, and any other sensor which can detect parameters of the surrounding environment.. The modular units can include a microphone to determine ambient noise and use such information in a noise-reduction or cancellation system. In some embodiments, the noise-reduction or cancellation system can be used in conjunction with a voice command system. This can advantageously increase the effectiveness of the voice command system in determining the specific commands given by the wearer. In some embodiments, the modular units can include components, software and/or firmware to communicate with the eyewear unit to allow the eyewear unit to determine the type of components included with the modular unit.

Examples of Structural Support for or Packaging of Components

[0132] With reference now to the embodiment of the electronic device or system **1500** of Figures 13A-D, the system **1500** can include an eyewear unit **1510** having a frame **1512** on which one or more components can be mounted and/or attached. The one or more components can be any of those described in connection with any of the embodiments described herein including but not limited to the system **100**. For example, the components can include any of those components discussed in connection with the processing system **120**, the signal conversion system **130**, the sensor system **140**, the input/output system **150**, the user interface system **160**, the power system **170**, and/or any other components as desired. These components can form part of the eyewear unit **1510**, similar to other eyewear units described herein, and can be used in conjunction with one or more modular units and/or remote units. The components can be mounted and/or attached using any of a variety of techniques including fastening the components to the frame **1512** via mechanical fasteners such as screws, bolts, rivets, clamps, and the like, chemical fasteners such as adhesives and the like, press fits, or can simply be maintained in place via use of other components of the eyewear unit **1510**.

[0133] As shown in the illustrated embodiment, the frame **1512** can include a front face **1514**, a left earstem **1516**, and a right earstem **1518**. In some embodiments, the eyewear includes dual lenses or a unitary lens, an orbital partially or completely surrounding the lenses or lens, and/or a rimless or frameless front face (e.g., with the lens or lenses attached to the earstems without a front frame). In some embodiments, the components can be mounted and/or attached to the front face **1514** (e.g., frame and/or lens or lenses), the left earstem **1516**, and/or the right earstem **1518**. For example, as shown in the illustrated embodiment, one or more components, such as a first component **1520** and a second component **1522**, can be attached to the left earstem **1516** and one or more components, such as a third component **1524** and a fourth component **1526** can be attached to the right earstem **1518**. As shown in the illustrated embodiment, components **1522** and/or **1526** can include a port and/or connector such as those described herein including, but not limited to, a USB 3.0 Type-C port. Components **1520** and/or **1524** can be parts of other systems described herein including a processing system, a signal conversion system, a sensor system, an input/output

system, a user interface system, and/or a power system. Fewer or greater number of components can be mounted and/or attached to the frame **1512** and the positioning of the components relative to each other can be changed. For example, in some embodiments, components can be attached and/or mounted to the front face **1514** such as, but not limited to, the nosepiece portion.

[0134] The components can be electrically coupled to allow the components to communicate with each other. In some embodiments, one or more of the components can be directly coupled electrically. The eyewear unit **1510** can include an electrical connector, such as a wire, for directly coupling two or more components together. The electrical connector can run along any surface of the eyewear unit **1510** such as, but not limited to, the top surfaces of the frame **1512**. In some embodiments, one or more components can be indirectly coupled electrically. For example, the one or more components can be coupled via a wireless connection such as, but not limited to, Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, and MMS.

[0135] In some embodiments, the first component **1520** can include one or more components such as those used for the processing system **120**, the signal conversion system **130**, the sensor system **140**, the input/output system **150**, the user interface system **160**, and/or the power system **170**. For example, the first component **1520** can include one or more circuit boards on which a processor **122**, memory **124**, one or more receivers **154**, one or more transmitters **156** (or transceivers), and/or one or more sensors such as an accelerometer can be included. The circuit board can be sized to fit within a frame of the eyewear unit **1510**.

[0136] In some embodiments, the third component **1524** can include a battery or other component from the power system **170**. In some embodiments, the battery can be chosen such that the eyewear unit **1510** can operate for about four hours. In some embodiments, the battery can be chosen such that it can operate for a greater or lesser duration than four hours, including between about 1 hour and about 10 hours, any duration within this range, and any other duration as desired. In some embodiments, the battery can have a relatively compact form factor and be sized to fit within a frame of the eyewear unit **1210**. In some embodiments, the eyewear unit **1510** can include components to enable wired

charging, such as via USB, and/or wireless charging, such as via inductive charging, of the battery.

[0137] In some embodiments, the eyewear unit **1510** can include a housing which can form at least part of an outer housing for the components and can serve as a mounting structure for a user interface system such as those described herein.

Movable Antenna

[0138] With reference now to the embodiment of the antenna **1600** of Figures 14 and 15, the antenna **1600** can be attached to a component of an electronic device or system including, but not limited to, electronic device or systems **100, 500, 600, 700a-c, 800, 1100, 1200, 1300, 1400, 1500**. As shown in the illustrated embodiment, the antenna **1600** can be attached to a portion of an earstem **1602**, such as an outer surface of the earstem **1602** with a portion of the antenna **1602** extending partially over a top surface of the earstem **1602**. In some embodiments the antenna **1600** can be positioned and/or attached to any portion of an eyewear unit, such as eyewear units **110, 510, 610, 810, 1100, 1210, 1310, 1410, 1510**, including, but not limited to, portions of a face or frame such as a nosepiece region or nosepad, lateral regions of the face or frame, a brow, and/or orbital regions, portions of an earstem such as an anterior region of the earstem, a posterior region of the earstem, a bottom surface of the earstem, a top surface of the earstem, an outer surface of the earstem, and/or an inner surface of the earstem, and/or portions of a lens such as a periphery of the lens, an anterior surface of the lens, and/or a posterior surface of the lens. In some embodiments, the antenna **1600** can be positioned and/or attached to any portion of a modular unit, such as modular units **210, 550, 650, 730a, 730b, 730c, 850, 900, 1000, 1150, 1160, 1250, 1256, 1350, 1450**. In some embodiments, the antenna **1600** can be positioned and/or attached to any portion of a remote unit, such as remote units **310, 580, 582, 584, 680, 682, 684**.

[0139] The antenna **1600** can be movably attached to the earstem **1602** such that at least a portion of the antenna **1600** can translate and/or rotate relative to the earstem **1602**. For example, in some embodiments, the entirety of the antenna **1600** can translate relative to the earstem **1602** or a portion of the antenna **1600** can translate relative to the earstem **1602** such as via telescoping. In embodiments where the antenna **1600** is attached to other portions

of system, such as other portions of the eyewear unit, the modular unit, and/or the remote unit, the antenna **1600** can translate and/or rotate relative to such portions of the system. The antenna **1600** can be rotated from a first or stowed configuration (not shown) in which the antenna **1600** is positioned closer to the earstem **1602** to a second or deployed configuration as shown in which at least a portion of the antenna **1600** is positioned away from the earstem **1602**. The first or stowed configuration can beneficially reduce the form factor of the antenna **1600** and component to which it is attached. This can reduce the likelihood that the antenna **1600** and/or the component to which it is attached is damaged when being stored. For example, the antenna **1600** can be positioned in the first or stowed configuration such that the antenna **1600** is generally flush with the earstem **1602**. The second or deployed configuration can beneficially enhance the performance of the antenna **1600**. The antenna **1600** can be configured to receive one or more electronic signals including, but not limited to, Bluetooth, Bluetooth Low Energy (Bluetooth Smart), ANT, ANT+, ZigBee, Wi-Fi, GSM, CDMA, MMS, and/or any other type of signal. In some instances, signal degradation may occur and/or noise may be generated as a result of positioning the antenna **1600** near a user's head. Such signal degradation and/or noise may be reduced, or generally eliminated, by positioning the antenna further from a user's head. This can beneficially enhance the signal received by electronics. For example, enhanced signals can beneficially increase the accuracy of data provided by a GPS receiver. Such enhanced signals can also be beneficial for reception and/or transmission of other types of signals, such as those utilized by Bluetooth and/or WiFi receivers, transmitters, and/or transceivers.

[0140] As shown in the illustrated embodiment, the antenna **1600** can rotate relative to the earstem **1602** along a generally vertical or superior-inferior axis of rotation when worn by a user along a coupling **1604**. The length **1606** of the antenna **1600** can be between approximately 10mm to approximately 60mm, between approximately 15mm to approximately 50mm, between approximately 20mm to approximately 40mm, approximately 30mm, any sub-range within any of these ranges, or any other length to receive a desired signal. In the deployed configuration the antenna **1600** can be positioned such that a distance **1608** between at least a portion of the antenna **1600**, such as an end **1601**, and a user's head can be between approximately 5mm to approximately 55mm, between approximately 10mm

to approximately 40mm, between approximately 15mm to approximately 25mm, approximately 15mm, any sub-range with any of these ranges, or any other distance to reduce signal degradation and/or noise based on the received signal. In some embodiments, the distance **1608** can be between approximately one-fourth to three-fourths the length **1610** of the antenna **1600**, between approximately one-third to two-thirds the length **1610** of the antenna **1600**, approximately one-half the length **1610** of the antenna **1600**, any sub-range within these ranges, or any other ratio as desired. In the deployed configuration the antenna **1600** can be positioned such that an angle **1610** between the antenna **1600** and the longitudinal axis of the earstem at that point is between approximately 10 degrees to approximately 90 degrees, between approximately 25 degrees to approximately 75 degrees, between approximately 40 degrees to approximately 60 degrees, approximately 45 degrees, any sub-range within these ranges, or any other angle as desired.

[0141] While the coupling **1604** as shown allows rotation along a generally vertical or superior-inferior axis of rotation, in some embodiments the coupling **1604** can allow for rotation along one or more other axes including but not limited as a horizontal axis including such as a longitudinal axis of the earstem **1602**. In some embodiments, the coupling **1604** can be a pin hinge, a “scissor door” hinge, a single shear hinge, a double shear hinge, a spherical hinge, a ball-and-socket hinge, a floating hinge, a scissor hinge, any other hinge or coupling which can allow for one or more translational and/or rotational degrees of freedom, and/or a combination of hinges. The antenna **1600** can include one or more segments with one or more hinges such as those described above. The antenna **1600** can include one or more segments which allow the antenna **1600** to extend from a first length to a second length. For example, the antenna **1600** can be telescoping.

[0142] In some embodiments, transitioning of the antenna **1600** from a first configuration, such as the stowed configuration, to a second configuration, such as the deployed configuration, and/or from the second configuration to the first configuration can be performed manually by the user. In some embodiments, transitioning of the antenna **1600** from a first configuration to a second configuration and/or from a second configuration to a first configuration can be performed automatically. For example, the system on which the antenna **1600** is used can detect when the system is being worn by a user and/or when the

antenna **1600** is in use. In systems which include an eyewear unit, the eyewear unit can include a proximity sensor and/or a strain sensor to detect when the eyewear unit is being worn by a user. Upon detecting that the system is being worn and/or that the antenna **1600** is in use, electromechanical components such as a solenoid or motor can transition the antenna **1600** from the first configuration to the second configuration. Upon detecting that the system is no longer being worn and/or that the antenna **1600** is no longer in use, electromechanical components can transition the antenna **1600** from the second configuration to the first configuration.

[0143] In some embodiments, the antenna **1600** can be stowed within an interior volume of a component of the system. For example, the antenna can be positioned within a front face or frame of an eyewear unit. In the first or stowed configuration, the antenna can be positioned within an interior volume of the front face or frame. In the second or deployed configuration, the antenna can be positioned exteriorly of the front face or frame, with the antenna extending anteriorly relative to the front face or frame. The antenna can extend generally longitudinally via telescoping action. In some embodiments, the antenna can be positioned behind a door in the stowed position such that the antenna is generally hidden when in the stowed position. The door can be rotated and/or translated towards an open position when the antenna is in the second or deployed configuration. While described in connection with the front face or frame, the antenna can be stowed within an interior volume any portion of an eyewear unit, modular unit, and/or remote unit as described above.

[0144] In some embodiments, the antenna can be stationary. In some embodiments, the antenna can be positioned radially or laterally outward of the component to which the antenna is attached. For example, the antenna can be positioned such that the distance between the antenna and the component to which it is attached is approximately the distance of a nosebridge region of an eyewear or a distance between two orbitals.

[0145] It should be emphasized that many variations and modifications may be made to the herein-described embodiments, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims. Moreover, any of the steps described herein can be performed simultaneously or in

an order different from the steps as ordered herein. Moreover, as should be apparent, the features and attributes of the specific embodiments disclosed herein may be combined in different ways to form additional embodiments, all of which fall within the scope of the present disclosure.

[0146] Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that such features, elements and/or steps are in any way required for one or more embodiments.

[0147] Moreover, the following terminology may have been used herein. The singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to an item includes reference to one or more of such items. The term “ones” refers to one, two, or more, and generally applies to the selection of some or all of a quantity. The term “about,” “approximately,” or “similar” means that quantities, dimensions, sizes, formulations, parameters, shapes and other characteristics need not be exact, but may be approximated and/or larger or smaller, as desired, reflecting acceptable tolerances, conversion factors, rounding off, measurement error and the like and other factors known to those of skill in the art. The term “substantially” means that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to those of skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.

[0148] A plurality of items may be presented in a common list for convenience. However, these lists should be construed as though each member of the list is individually identified as a separate and unique member. Thus, no individual member of such list should be construed as a de facto equivalent of any other member of the same list solely based on their presentation in a common group without indications to the contrary. Furthermore, where the terms “and” and “or” are used in conjunction with a list of items, they are to be interpreted broadly, in that any one or more of the listed items may be used alone or in

combination with other listed items. The term “alternatively” refers to selection of one of two or more alternatives, and is not intended to limit the selection to only those listed alternatives or to only one of the listed alternatives at a time, unless the context clearly indicates otherwise.

THE FOLLOWING IS CLAIMED:

1. A wearable electronic system comprising:
 - an eyewear unit configured to be worn on a user's head, the eyewear unit comprising an input/output system including at least one wired connection;
 - a modular unit comprising an input/output system including at least one wired connection configured to removably couple to the at least one wired connection of the eyewear unit, and at least one of the following components:
 - a processor;
 - a memory;
 - a sensor;
 - a receiver configured to wirelessly communicate with at least one remote unit;
 - a transmitter configured to wirelessly communicate with at least one remote unit, and
 - a transceiver configured to wirelessly communicate with at least one remote unit;
 - wherein the input/output systems of the eyewear unit and the modular unit are configured to provide a wired electrical connection between the eyewear unit and the modular unit when in a coupled configuration via the at least one wired connection of the eyewear unit and the at least one wired connection of the modular unit, and
 - wherein the wired connections are at least one of a port and connector.
2. The electronic system of Claim 1, wherein the modular unit comprises at least one of a receiver, a transmitter, and a transceiver.
3. The electronic system of Claim 2, wherein the modular unit is configured to wirelessly communicate with a remote unit.
4. The electronic system of Claim 3, wherein the remote unit comprises a sensor.
5. The electronic system of Claims 2 or 3, wherein the remote unit comprises an audio component.
6. The electronic system of Claim 5, wherein the audio component is an in-ear speaker.

7. The electronic system of Claim 5, wherein the audio component is an outwardly facing speaker and the remote unit is an external speaker.

8. The electronic system according to any of Claims 2-7, wherein the remote unit comprises a smart phone.

9. The wearable electronic system according to any of Claims 1-8, wherein the modular unit comprises the sensor, wherein the sensor is an ambient or biometric sensor.

10. The wearable electronic system according to any of Claims 1-9, wherein the eyewear unit further comprises at least one of the following components:

a processor;

a memory;

a sensor;

a receiver configured to wirelessly communicate with at least one remote unit;

a transmitter configured to wirelessly communicate with at least one remote unit; and

a transceiver configured to wirelessly communicate with at least one remote unit.

11. The wearable electronic system according to any of Claims 1-10, wherein the input/output system of the modular unit comprises a first wired connection and a second wired connection, where at least one of the first and second wired connections are configured to removably couple a second modular unit to the first modular unit and to provide communication between the eyewear unit and the second unit modular unit.

12. The wearable electronic system according to any of Claims 1-11, wherein the eyewear unit comprises a power source configured to power the modular unit via the wired connections of the eyewear unit and the modular unit.

13. The wearable electronic system of Claim 12, wherein the eyewear unit does not include a processor, a memory, a sensor, a receiver configured to wirelessly communicate with at least one remote unit, a transmitter configured to wirelessly communicate with at least one remote unit, and a transceiver configured to wirelessly communicate with at least one remote unit.

14. The wearable electronic system according to any of Claims 1-13, wherein the system further comprises one or more visual components configured to display an image to the user.

15. The wearable electronic system of Claim 14, wherein the modular unit further comprises at least one of the one or more visual components.

16. The wearable electronic system of Claim 14, wherein the eyewear unit further comprises at least one of the one or more the visual components.

17. The wearable electronic system according to any of Claims 1-16, wherein the system further comprises one or more audio components configured to generate an audible signal perceptible by the user.

18. The wearable electronic system of Claim 17, wherein the modular unit further comprises at least one of the one or more audio components.

19. The wearable electronic system of Claim 17, wherein the eyewear unit further comprises at least one of the one or more audio components.

20. The wearable electronic system according to any of Claims 17-20, wherein at least one of the one or more audio components comprises an in-ear speaker.

21. The wearable electronic system according to any of Claims 1-20, wherein the system further comprises one or more haptic components configured to generate a tactile signal perceptible by the user.

22. The wearable electronic system of Claim 21, wherein the modular unit further comprises at least one of the one or more haptic components.

23. The wearable electronic system of Claim 21, wherein the eyewear unit further comprises at least one of the one or more haptic components.

24. The wearable electronic system according to Claim 23, wherein the eyewear unit comprises a sensor, wherein the at least one haptic component is configured to provide a user with a tactile representation of data received from the sensor.

25. The wearable electronic system according to any of Claims 1-24, wherein the modular unit is configured to be attached to the eyewear unit proximate the user's head.

26. The wearable electronic system according to any of Claims 1-25, wherein the receiver comprises two or more wireless protocols.

27. The wearable electronic system of Claim 26, wherein the receiver is configured to receive data from an ANT+-enabled remote unit and a Bluetooth-enabled remote unit.

28. The wearable electronic system according to any of Claims 1-27, wherein the eyewear unit comprises at least one lens.

29. The wearable electronic system according to any of Claims 1-28, wherein at least one of the eyewear unit and the modular unit comprises one or more movable antennas each configured to transition from a first, stowed configuration to a second, deployed configuration.

30. The wearable electronic system of Claim 29, wherein the eyewear unit comprises one or more movable antennas.

31. The wearable electronic system of Claim 30, wherein the eyewear unit comprises a movable antenna on an earstem of the eyewear unit.

32. The wearable electronic system according to any of Claims 29-31, wherein the modular unit comprises one or more movable antennas.

33. The wearable electronic system according to any of Claims 29-32, wherein at least one of the movable antennas is rotatable relative to a component to which the antenna is attached.

34. The wearable electronic system according to any of Claims 29-33, wherein at least one of the movable antennas is rotatable about a generally vertical axis of rotation.

35. The wearable electronic system according to any of Claims 29-34, wherein at least one of the movable antennas is rotatable about a generally horizontal axis of rotation.

36. The wearable electronic system according to any of Claims 29-35, wherein at least one of the movable antennas is translatable relative to a component to which the antenna is attached.

37. The wearable electronic system according to any of Claims 29-36, wherein in the deployed configuration, at least one of the one or more movable antennas can be positioned such that a distance between a user and the antenna is between one-third to two-thirds a length of the antenna.

38. The wearable electronic system according to any of Claims 29-37, wherein at least one of the movable antennas comprises an electromechanical component.

39. The wearable electronic system according to any of Claims 29-38, wherein at least one of the movable antennas automatically transitions from the first configuration to the second configuration.

40. The wearable electronic system of Claim 39, wherein at least one of the movable antennas automatically transitions when the electronic system detects that electronic system is being worn by a wearer.

41. The wearable electronic system of Claim 39 or 40, wherein at least one of the movable antennas automatically transitions when the electronic system detects that the at least one movable antenna is in use.

42. The wearable electronic system according to any of Claims 29-41, wherein at least one of the movable antennas automatically transitions from the second configuration to the first configuration.

43. The wearable electronic system of Claim 42, wherein at least one of the movable antennas automatically transitions when the electronic system detects that the electronic system is being worn by a wearer.

44. The wearable electronic system of Claim 42 or 43, wherein at least one of the movable antennas automatically transitions when the electronic system detects that the at least one movable antenna is in use.

45. A wearable electronic system comprising:

an eyewear unit configured to be worn on a user's head, the eyewear unit comprising an input/output system including at least one wired connection;

a modular unit comprising an input/output system including at least one wired connection configured to removably couple to the at least one wired connection of the eyewear unit, wherein the at least one wired connection of the eyewear unit and the at least one wired connection of the modular unit are configured to provide a wired electrical connection between the eyewear unit and the modular unit when in a coupled configuration; and

wherein the input/output systems and the eyewear unit and the modular unit are configured to provide communication between the eyewear unit and the modular unit via the coupled wired connections of the eyewear unit and the modular unit, and

wherein the wired connections are at least one of a port and connector.

46. The wearable electronic system of Claim 45, wherein the eyewear unit further comprises at least one of the following components:

a processor;

a memory;

a sensor;

a receiver configured to wirelessly communicate with at least one remote unit;

and

a transmitter configured to wirelessly communicate with at least one remote unit.

47. The wearable electronic system according to Claim 46, wherein the modular unit further comprises at least one of the following components:

a processor;

a memory;

a sensor;

a receiver configured to wirelessly communicate with at least one remote unit;

and

a transmitter configured to wirelessly communicate with at least one remote unit.

48. The wearable electronic system according to Claim 47, wherein:

the eyewear unit comprises the processor, and

the modular unit comprises the receiver and the transmitter and is configured to serve as a node for wireless communication with multiple remote units.

49. The wearable electronic system according to Claim 47, wherein:

the modular unit comprises the sensor, and

the eyewear unit comprises the receiver and the transmitter and is configured to serve as a node for wireless communication with multiple remote units.

50. The wearable electronic system according to Claim 47, wherein:
the eyewear unit comprises the processor, and
the modular unit comprises a bone-conduction speaker.




FIG. 1







FIG. 2






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10






FIG. 15

**FIG. 12****FIG. 13A**




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 14




FIG. 15

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2016/031427

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-28, 45-50

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2016/031427

A. CLASSIFICATION OF SUBJECT MATTER
INV. G02C11/06 G02C11/00
ADD. G02B27/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G02C G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2007/030442 A1 (HOWELL THOMAS A [US] ET AL) 8 February 2007 (2007-02-08) figures 7,10,22 paragraphs [0083], [0094], [0095], [0098], [0109], [0120], [0139] paragraphs [0161], [0189], [0190], [0197], [0203], [0209], [0211] -----	1-28, 45-50
X	US 2007/046887 A1 (HOWELL THOMAS A [US] ET AL) 1 March 2007 (2007-03-01) figures 3K, 30, 4-6, 10B, 13C paragraph [0148] -----	1-28, 45-50
A	WO 2013/188343 A1 (PIXELOPTICS INC [US]) 19 December 2013 (2013-12-19) figures 20,21,45 paragraph [0320] -----	1

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

5 January 2017

Date of mailing of the international search report

27/03/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

de Lajarte, Gilles

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/031427

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2007030442 A1	08-02-2007	US 2007030442 A1	08-02-2007
		US 2011102734 A1	05-05-2011
		US 2012050668 A1	01-03-2012

US 2007046887 A1	01-03-2007	NONE	

WO 2013188343 A1	19-12-2013	AR 091410 A1	04-02-2015
		EP 2859405 A1	15-04-2015
		JP 2015522841 A	06-08-2015
		TW 201415113 A	16-04-2014
		US 2013329183 A1	12-12-2013
		WO 2013188343 A1	19-12-2013

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-28, 45-50

wired connection between eyewear unit and modular unit

2. claims: 29-44

movable antenna
