

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 199893234 B2**
(10) Patent No. **733143**

(54) Title
A pump impeller

(51)⁶ International Patent Classification(s)
F04D 029/18 F04D 029/22
F04D 007/02 F04D 029/24

(21) Application No: **199893234** (22) Application Date: **1998 .11 .17**

(30) Priority Data

(31) Number (32) Date (33) Country
9704222 1997 .11 .18 SE

(43) Publication Date : **1999 .06 .10**
(43) Publication Journal Date : **1999 .06 .10**
(44) Accepted Journal Date : **2001 .05 .10**

(71) Applicant(s)
ITT Manufacturing Enterprises, Inc.

(72) Inventor(s)
Ulf Arbeus


(74) Agent/Attorney
SPRUSON and FERGUSON,GPO Box 3898,SYDNEY NSW 2001

(56) Related Art
US 5749707
US 1763595
US 3644056

A PUMP IMPELLER

ABSTRACT

The invention concerns a pump impeller of a centrifugal- or a half axial type for pumping liquids, mainly sewage water. The pump impeller comprises a hub (1) provided with one or several vanes (2). The leading edges (3) of the vanes (2) being
5 strongly swept backwards. The size of the sweep angle (α) varies between 35 and 65 degrees at the connection with the hub (1) and 55 and 85 degrees at the periphery (5).




S & F Ref: 431854

AUSTRALIA
PATENTS ACT 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL



Name and Address
of Applicant: ITT Manufacturing Enterprises, Inc.
1105 North Market Street
Wilmington Delaware 19801
UNITED STATES OF AMERICA



Actual Inventor(s): Ulf Arbeus



Address for Service: Spruson & Ferguson, Patent Attorneys
Level 33 St Martins Tower, 31 Market Street
Sydney, New South Wales, 2000, Australia



Invention Title: A Pump Impeller

The following statement is a full description of this invention, including the best method of performing it known to me/us:-

The invention concerns a pump impeller and more precisely a pump impeller for centrifugal-or half axial pumps for pumping of fluids, mainly sewage water.

In literature there are lot of types of pumps and pump impellers for this purpose described, all however having certain disadvantages. Above all this concerns

5 problems with clogging and low efficiency.

Sewage water contains a lot of different types of pollutants, the amount and structure of which depend on the season and type of area from which the water emanates. In cities plastic material, hygiene articles, textile etc are common, while industrial areas may produce wearing particles. Experience shows that the worst problems are rags

10 and the like which stick to the leading edges of the vanes and become wound around the impeller hub. Such incidents cause frequent service intervals and a reduced efficiency.

In agriculture and pulp industry different kinds of special pumps are used, which should manage straw, grass, leaves and other types of organic material. For this purpose the leading edges of the vanes are swept backwards in order to cause the pollutants to be fed outwards to the periphery instead of getting stuck to the edges. Different types of disintegration means are often used for cutting the material and making the flow more easy. Examples are shown in SE-435 952, SE-375 831 and US- 4 347 035.

20 As pollutants in sewage water are of other types more difficult to master and as the operation times for sewage water pumps normally are much longer, the above mentioned special pumps do not fulfil the requirements when pumping sewage water, neither from a reliability nor from an efficiency point of view.

A sewage water pump quite often operates up to 12 hours a day which means that the energy consumption depends a lot on the total efficiency of the pump.

Tests have proven that it is possible to improve efficiency by up to 50 % for a sewage pump according to the invention as compared with known sewage pumps.

- 5 As the life cycle cost for an electrically driven pump normally is totally dominated by the energy cost (c:a 80 %), it is evident that such a dramatic increase will be extremely important.

In literature the designs of the pump impellers are described very generally, especially as regards the sweep of the leading edges. An unambiguous definition of said sweep does not exist.

Tests have shown that the design of the sweep angle distribution on the leading edges is very important in order to obtain the necessary self cleaning ability of the pump impeller. The nature of the pollutants also calls for different sweep angles in order to provide a good function.

15 Literature does not give any information about what is needed in order to obtain a gliding, transport, of pollutants outwards in a radial direction along the leading edges of the vanes. What is mentioned is in general that the edges shall be obtuse-angled, swept backwards etc. See SE-435 952.

- 20 When smaller pollutantans such as grass and other organic material are pumped, relatively small angles may be sufficient in order to obtain the radial transport and also to disintegrate the pollutants in the slot between pump impeller and the surrounding housing. In practice disintegration is obtained by the particles being cut through contact with the impeller and the housing when the former rotates having a periphery velocity of 10 to 25 m/s. This cutting process is improved by the surfaces
25 being provided with cutting devices, slots or the like. Compare SE-435 952. Such pumps are used for transport of pulp, manure etc.

When designing a pump impeller having vane leading edges swept backwards in order to obtain a self cleaning, a conflict arises between the distribution of the sweep angle, performance and other design parameters. In general it is true that an increased
 5 sweep angle means a less risk for clogging, but at the same time the efficiency decreases.

It is therefore desirable to design the leading edge of the vane in an optimum way as regards obtaining of the different functions and qualities for reliable and economic pumping of sewage water containing pollutants such as rags, fibres etc.

It is the object of the present invention to substantially overcome or at least
 10 ameliorate one or more of the disadvantages of the prior art.

Accordingly, the present invention provides a pump impeller of a centrifugal or half axial pump, said impeller being adapted for use in a pump for pumping sewage water, wherein said impeller is provided with a hub and one or several vanes, the leading edges of which being swept backwards towards the periphery, the exact sweep angle, defined in every point on the leading edge as the angle between the normal to the leading
 15 edge and the relative velocity of the pumped medium at that point, has value within an area limited by the interval 40-55 degrees at the connection of the leading edge to the hub and 60-75 degrees at the periphery and having a mainly even variation therebetween.

As shown in Fig 5, the preferred embodiment quantifies a band of the sweep
 20 angle distribution which admits a good function and efficiency. The range is connected to size, periphery velocity and material friction. The independent variable that is used to describe this, here called normalized radius, is defined as follows:

$$\text{Normalized radius} = (r - r_1) / (r_2 - r_1) \quad \text{Equation 1}$$

25

Where r_1 is the radius of the hub connection, r_2 the radius out to the periphery of the leading edge and where the radius according to a cylinder coordinate system having its origin in the center of the impeller shaft, defines the shortest distance between the actual point and a point on the extension of the impeller shaft. The sweep angle of the
 30 leading edge may be increased considerably outwards, from a minimum of 40 degrees at the hub connection to a minimum of 55 degrees at the periphery. The upper limit, 60-75 degrees, defines a boarder line above which the efficiency as well as the reliability are influenced in a negative way.



In a preferred embodiment, the sweep angle is almost independent of the operation point, i.e. different flows and heads, which also corresponds with different velocity triangles ($\bar{C}$, $\bar{U}$, $\bar{W}$).

The definition of the sweep angle will be described below with reference to the enclosed drawings.

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings, wherein:

Fig. 1 show a three dimensional view of a pump impeller according to the invention;

Fig. 2 shows a radial cut through a schematically drawn pump according to the invention;

Fig. 3 shows a schematic axial view of the inlet of the impeller;

Fig. 4 shows an enlargement of an area on the leading edge of an impeller vane; and

Fig. 5 is a diagram showing the relation between the back sweep of the leading edge and a standard radius according to the invention.

In the drawings 1 stands for an impeller hub, 2 a vane having a leading edge 3. 4 stands for the connection of the leading edge to the hub and 5 the periphery of the edge. 6 stands for the normal to the edge in a certain point. 7 stands for the wall of the pump housing, 8 the end of the hub, 9 the direction of rotation, α sweep angle, W_r the project relative velocity, the velocity of the fluid in a co-rotating coordinate system, and z the impeller shaft direction.

In order to design a desired pump impeller geometry in an optimum way, a correct definition of said sweep angle is a provision. The exact sweep angle α is in general a function of the geometry of the leading edge in a meridional view ($r - z$) as well as in an axial view ($r - \theta$), see Figs 2 and 3.

The exact definition will be a function of the curve that describes the form of the leading edge 3 and the local relative velocity $\bar{W}$ at that curve. This can be mathematically stated in the following way:



With traditional designations of the velocity triangle ($\bar{C}$, $\bar{U}$, $\bar{W}$) the relative velocity $\bar{W}(r)$ is a function of the position vector $\bar{r}$ in a co-rotating cylindric coordinate system. In the normal way the relative velocity $\bar{W}(r, \theta, z)$ can also be explained in its components (W_r, W_θ, W_z).

- 5 The three dimensional curve along the leading edge 3 can in a corresponding co-rotating coordinate system be described as a function $\bar{R}$ which depends on the position vector $\bar{r}$, i. e. $\bar{R} = \bar{R}(r, \theta, z)$.

An infinitesimal vector which is in parallel with the leading edge in every point can be defined as $d\bar{R}$. From the definition of scalar product an expression is obtained for the sweep angle α , defined as the angle between the normal to $d\bar{R}$ and $\bar{W}_R$, where $\bar{W}_R$ the projected relative velocity, is defined as the orthogonal projection of $\bar{W}_R$ onto the direction of $\bar{W}$ at zero incidence. This means that $\bar{W}_R$ and $\bar{W}$ are equal at or close to the nominal operating point, sometimes referred to the best efficiency point.

$$\alpha = \pi / 2 - \arccos [(d\bar{R} \cdot \bar{W}_R) / (|d\bar{R}| \cdot |\bar{W}_R|)] \quad \text{Equation 2}$$

15 If it is assumed that the absolute inlet velocity does not have any circumferential component which is normal, W_θ equals the peripheral velocity of the impeller.

By using these definitions and assumptions it will be shown below that α is independant of the flow. The conditions are that the leading edge lies in a plane that is essentially perpendicular to the direction z of the impeller shaft and that the

- 20 leading edge is located where the absolute inlet velocity is essentially axial, which means that the radial component of $\bar{W}_R$ is near zero. For the same reasons the circumferential component of $\bar{W}_R$, i. e. in θ direction, equals the peripheral velocity of the impeller and is independent of the flow. The axial component of $\bar{W}_R$ gives a neglectable contribution to α as dR_z is zero according to the above. This follows
25 from the definition of scalar product. Accordingly the flow dependant variable $\bar{W}_R$

According to a preferred embodiment of the invention the leading edge of the vane is located in a plane essentially perpendicular to the impeller shaft. With the knowledge that a pump very often operates within a broad field as concerns volume flow and head, the preferred embodiment admits that the self cleaning ability can be kept independant of different operation conditions.

The third part of the invention concerns a preferred embodiment where the connection of the leading edge to the hub is located adjacent the end 8 of the hub 1, i. e. the latter has no central protruding tip. This diminishes the risk for pollutants being wound around the central part of the impeller.



The claims defining the invention are as follows:

1. A pump impeller of a centrifugal or half axial pump, said impeller being adapted for use in a pump for pumping sewage water, wherein said impeller is provided
 5 with a hub and one or several vanes, the leading edges of which being swept backwards towards the periphery, the exact sweep angle, defined in every point on the leading edge as the angle between the normal to the leading edge and the relative velocity of the pumped medium at that point, has value within an area limited by the interval 40-55 degrees at the connection of the leading edge to the hub and 60-75 degrees at the
 10 periphery and having a mainly even variation therebetween.

2. A pump impeller according to claim 1, wherein the angle between the normal to the leading edge and the relative velocity of the pumped medium, at each point on the leading edge, has a value within the area limited by the interval 45-55 degrees at
 15 the connection of the leading edge to the hub and 62-72 degrees at the periphery and having a mainly even variation therebetween.

3. A pump impeller according to claim 1, wherein the leading edge of the vane is located essentially in a plane perpendicular to the impeller shaft where the
 20 absolute velocity of the pumped medium is mainly axial.

4. A pump impeller according to claim 1, wherein the connection of the leading edge to the hub is located adjacent the end of said hub.

5. A pump impeller substantially as hereinbefore described with reference
 25 to the accompanying drawings.

Dated 14 March, 2001

ITT Manufacturing Enterprises, Inc.

Patent Attorneys for the Applicant/Nominated Person

SPRUSON & FERGUSON



[R:\LIBLL\10739.doc:caa]

1/3




FIG. 1




FIG. 2




FIG. 3




FIG. 4

20190004

Leading edge sweep angle α as
a function of normalized radius.




FIG. 5