

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 May 2001 (25.05.2001)

PCT

(10) International Publication Number
WO 01/36293 A1

(51) International Patent Classification⁷: **B65D 75/58**

(72) **Inventor: REDMOND, Sanford**; c/o Sanford Redmond Inc., 780 East 134 Street, Bronx, NY 10454 (US).

(21) International Application Number: PCT/US00/31872

(22) International Filing Date:
20 November 2000 (20.11.2000)

(74) **Agents: PAULSON, Robert, E.** et al.; Morgan & Finnegan, L.L.P., 345 Park Avenue, New York, NY 10154-0053 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/166,504	19 November 1999 (19.11.1999)	US
60/184,512	24 February 2000 (24.02.2000)	US
60/185,779	29 February 2000 (29.02.2000)	US
60/211,865	14 June 2000 (14.06.2000)	US
60/212,977	21 June 2000 (21.06.2000)	US
60/224,654	11 August 2000 (11.08.2000)	US
60/228,434	28 August 2000 (28.08.2000)	US


(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) **Applicant: SANFORD REDMOND INC.** [US/US]; 780 East 134th Street, Bronx, NY 10454 (US).

[Continued on next page]

(54) **Title:** RECLOSABLE DISPENSER PACKAGE, RECLOSABLE OUTLET FORMING STRUCTURE AND METHOD AND APPARATUS FOR MAKING SAME



(57) **Abstract:** An aperture forming structure for a sealed containment and dispensing package for flowable products is provided. The structure includes a break away tip member (634) of thermoformable plastic. A cap (620) may be integrally formed with the aperture forming structure and may be used to protect the tip member or for closing the aperture. An alternative embodiment relates to a pouch (2100). By folding the corner of the pouch towards the body of the pouch a break away tip member is removed leaving a product outlet hole (2100b) in the pouch wall.

**Published:**

- *With international search report.*
- *Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**RECLOSABLE DISPENSER PACKAGE,
RECLOSABLE OUTLET FORMING STRUCTURE AND
METHOD AND APPARATUS FOR MAKING SAME**

This application claims priority to United States Provisional Application Serial No. 60/166,504, filed November 19, 1999, entitled "RECLOSABLE DISPENSER PACKAGE, RECLOSABLE OUTLET FORMING STRUCTURE AND METHOD AND APPARATUS FOR MAKING SAME", United States Provisional Application Serial No. 60/184,512 filed February 24, 2000, entitled "RECLOSABLE APERTURE FORMING MEANS", United States Provisional Application Serial No. 60/185,779 filed February 29, 2000, entitled "RECLOSABLE APERTURE FORMING MEANS", United States Provisional Application Serial No. 60/211,865 filed June 14, 2000, entitled "EASY OPENING POUCH", United States Provisional Application Serial No. 60/212,977 filed June 21, 2000, entitled "EASY OPENING POUCH", United States Provisional Application Serial No. 60/224,654 filed August 11, 2000, entitled "EASY OPEN POUCH", United States Provisional Application Serial No. 60/228,434 filed August 28, 2000 entitled "EASY OPENING POUCH", all by the same inventor of the instant non-provisional application, all of which are herein incorporated by reference.

FIELD OF THE INVENTION

This invention relates to easy opening, self-contained, easy to use, single or multiple use dispenser packages capable of economical, high speed production, manufactured from a broad range of materials, many of which are recyclable. They may contain such products as syrups, cream, cheeses, salad dressings, shampoo, hand-cream, liquid detergents, motor oil, toothpaste pates, pet food and many other products. It additionally relates to a package which has the capability of dispensing the contained product, e.g., mouthwash, cough syrup, confections, alcoholic beverages, etc., directly into the mouth of the user, and which also includes a reclosure cap member formed as an integral part of the package and which preferably is tethered to the package by a tether also formed integrally with the package. It will also be seen that the easy opening feature together with the reclosure cap and tether may be formed independently and sealed or adhered to the surface of many packages such as bags, milk containers, pouches, pillow packages (sachets), etc.

- 2 -

to make for very efficient low cost dispensing packages or squeeze bags. These squeeze bag type packages could dispense food pastes such as pet food, cremes, grease, yogurt, certain types of dough, cake frosting and could be made of everything from treated, coated paperboard plastic films, foils, laminates or coextrusions of these materials. The easy opening means of this application in its preferred embodiment is comprised of a drum-like protrusion from which a secondary frusto conical protrusion extends to create a tip which is encircled at its base by a fault line. To create the aperture this tip is broken away by applying light lateral finger pressure. In order to protect this breakaway tip during shipment or for reclosing the aperture, a tethered cap is also formed adjacent to the double protrusion. The tether functions not only to hold the cap, thereby preventing the cap from being lost, but also to hold the cap [on the tip] in place by acting like a spring.

In an alternate aperture forming system the initial drum like protrusion has, instead of a frusto-conical breakaway tip, a fault line pattern defined in its top surface, so designed as to rupture to create an outlet of various required shapes when a puncturing tool/plug is pressed into said fault line pattern. Such puncturing tool/plug may be formed instead of a cap and may be tethered or the cap may be double ended with a cap formation on one end and the puncturing tool/plug formation on the other. It will also be seen that a cap containing a protruding member formed within the cap similar to the style of a flower would perform as a central punch when the cap is pressed over the drum shaped protrusion. It will further be seen that in certain instances where a metal foil liner is required for a flowable product such as an alcoholic drink the drum shaped protrusion may be replaced by a moundlike protrusion with a central fault line pattern. The reason for such a moundlike shape instead of the drum shape is to prevent the stretching of the foil beyond its elastic limit at surface intersections in which case it would rupture during formation. Said pattern able to be punched open by a formed puncturing tool/plug said puncturing tool/plug may be thermoformed and tethered to the unit or may be independently made and the tether may have a formed ring at its free end into which the puncturing tool plug may be

- 3 -

seated.

This invention also relates to a method and apparatus for manufacturing the aforesaid formation and packaging, reliably at high speed, in many cases from fully recyclable material, so as to permit such packages to be produced at low cost and, in many cases, recyclable. Additionally the packages may use less plastic material than most other previously known portion packages leading to source reduction and environmental benefits even when non-recyclable materials are used.

BACKGROUND OF THE INVENTION

Various attempts have been made to provide a dispenser package in which a product may be packaged in the quantity normally required for single or multiple uses, and from which the contained product may be dispensed.

One type of such dispenser packages is a pillow pouch or sachet, typically made of relatively thin plastics and foils or combinations of laminated plastics and foils. These packages are most frequently encountered as containers for catsup, mustard, other condiments, homecare preparations such as hair conditioners, dyes and cremes, etc. Although this type of package is universally used, it is also universally disliked by the consumer. In order to access the contents, the pouch must be held in one hand while a tearing motion and force are applied by the other hand. Creating the initial tear to break the packages seal is often very difficult, often requiring the assistance of the user's teeth. Moreover, once the initial tear is created, the laminated foil and/or plastic material not only often tears in an uncontrolled fashion, but the holding pressure exerted by one of the user's hands often forces the contents out of the envelope not only before the user is ready to apply the contents, but even before the tearing motion is complete. Opening these packages leads to frayed tempers, broken fingernails, and chipped teeth, as well as other problems. The user must also use both hands to open the container. In the case of invalids, arthritis sufferers and other handicapped people, opening these packages is virtually impossible. Yet another problem associated with these prior packages is the impossibility of efficient reclosure, thereby precluding multiple use of the package, with consequent waste of the unused

- 4 -

contents. Further disadvantages include the sachet's inability to function effectively with low viscosity products such as coffee cream, mouthwash or alcoholic beverages, due to the inability of the torn opening to control the direction of flow of such liquids from the package. These packages also are generally totally unrecyclable, and therefore become environmental pollutants. As above-mentioned however, should continued use of these sachets be preferred, then the easy opening feature of this application may be readily and economically adhered to the sachet to make for an easy opening, reclosable, high-barrier package.

Another dispenser package is the peel-top cup used for butter, margarine, syrup, sauces, salad dressing, and other similar products. This type of package requires good eyesight and manual dexterity. Such packages are often used as coffee creamers and have many disadvantages, including difficulty in peeling off the top in order to open, as well as difficulty in pouring, accidental spilling, and the inability to be reclosed so as to preclude more than a single use. Again the inventions described herein can be adhered or integrally formed into these packages to make them easy opening and reclosable. Yet another type of dispenser package is the unsealed corrugated paper package used for salt and/or pepper, which upon bending along an interrupted line cut through the corrugations forms an opening through which the salt or other material contained in the package may flow. These packages only dispense dry, solid flowables with the assistance of gravity, and cannot be used to contain, no less dispense, "wet" or liquid flowable materials. The package of this invention can contain and readily dispense both liquids and dry granular products.

Small, very expensive, metal capped bottles are used for alcoholic drinks and are either poured or consumed directly from the bottle. These bottles may be reclosed, but often are sized for a single drink so they do not have to be reclosed. The instant package can be used for alcoholic beverages at a fraction of the cost of the bottles.

Everyone is familiar with the ubiquitous gable top milk carton and everyone is familiar with the varying degrees of difficulty in opening them. These

- 5 -

range from fingernail breaking to just plain unopenable without a knife or other tool.

They never truly reclose and at best are messy and unclean looking. In the U.S. there has been a move toward mounting a screw-on cap combination comprising a threaded nozzle member which is sealed onto one of the slanted gables of the carton and the other is an unattached screw-on cap. This little injection molded duo is costly to make and to install, possibly on the order of 3 to 5 cents and is commonly used on large gable top juice containers in the half gallon size. These are expensive, high profit items selling for about three dollars each and can bear the extra tariff for the screw-on outlets. There are however billions of these gable top units sold annually for milk and cream in varying sizes from half-pints to half gallons. Producers however are reluctant to increase carton cost significantly and the public continues to use difficult to open cartons.

The instant invention makes available a sealed and tamper evident outlet with a tethered cap, both formed in a single, small plastic unit which can be readily sealed or adhesively attached to the gable over a small pre-made hole. It is ultra low cost and may be made of polypropylene, high density polyethylene, PVC. Polyester etc. utilizing material costing small fractions of a cent. It will be seen that the cap serves a double purpose. It enables the outlet to be reclosed after opening and of equal importance, since the cap is in place over the breakaway tip during shipment it protects the tip from being accidentally hit or subjected to any forces which may open the outlet.

It may be seen that the lower drum-like formation beneath the breakaway tip may be elongated so that when the tip is broken away, an elongated nozzle remains which would allow the flowable substance to be ingested directly from the container or as in the case of motor oil, being poured directly into the engine oil inlet. Another disadvantage currently experienced with dispensing packages is the closing of the outlet opening. Closing the outlet opening of tubes is presently accomplished by means of an injection molded screw-on cap which normally includes a compressible gasketing material. The end of the tube requires a mating thread to

- 6 -

match the cap. Both the separately molded gasketed cap and the threaded tube result in increased manufacturing costs. Additionally, the cap, as often as not, is dropped and/or lost while it is being threaded on or off. Furthermore, there has been a growing trend to manufacture such tubes at still greater cost by providing hinged caps with a flat end surface which permits the tube to stand upright. Thus, the cap members currently in use have the disadvantage that they tend to increase the overall cost of manufacture of the dispensing package.

OBJECTS OF THE INVENTION

It is therefore an object of this invention to provide a new and improved means of creating an aperture in a thermoformable plastic material as well as an integrally formed cap and tether where necessary.

A further object is to form independently such aperture creating means with or without a cap and/or tether for adhesion to other forms of previously difficult to open or non-reclosable packaging.

Another object of this invention is to provide new and improved dispenser packages.

Another object of this invention is to provide a new and improved aperture-forming structure for a dispenser package which allows the user to easily and controllably dispense the contents of the package directly to the user's mouth or in a directionally controlled manner, as desired.

Another object of this invention is to provide a new and improved aperture-forming structure for a dispenser package which opens easily and reliably and yet which can be manufactured economically and at high speed.

Another object of this invention is to provide a new and improved reclosable dispenser package so that the contents thereof may be dispensed in consecutive uses and the outlet opening reclosed between uses.

A further object of this invention is to provide a new and improved reclosable package with an attached cap member formed from the same plastic film which cap member may be thereafter placed over the unopened aperture forming

- 7 -

means to protect it and/or to reclose the package after opening.

Another object of this invention is to provide a new and improved reclosable package and removable cap member which may be formed as an integral unit and where the cap member is attached to an integrally made tether and remains
5 attached to the package and which may be placed over the unopened aperture forming means to protect it from changes or accidental opening during shipping and handling.

Another object of this invention is to provide a new and improved reclosable package and tethered cap member which may be formed as an integral unit from a thermoformable material.

10 Another object of this invention is to provide a new and improved reclosable package and tethered cap member which may be formed as an integral unit from a thermoformable plastic material that is recyclable.

Another object of this invention is to provide a new and improved dispenser package and cap member wherein the cap member has an open-ended top of
15 predetermined shape so that, upon placing the cap over the aperture of the package the contents may be dispensed in such shaped stream.

Another object of this invention is to provide a new and improved dispenser package and cap member wherein the cap member includes a utensil device
20 such as tiny protrusions or a flattened surface structure so that the cap member may function as a tool to brush, spread, or otherwise handle the contents dispensed from the package.

Another object of the invention is to replace the cap member with a dual function punch/plug member capable of punching through a tough pre-scored
formation to create an aperture and to further act as a plug to close said aperture.

25 A still further object of this invention is to provide a new and improved method of making a dispenser package embodying the aforesaid features.

Another object of this invention is to provide a new and improved method of thermoforming a dispenser package from a recyclable plastic material at high speed and yet provide a finished package which may be easily and reliably opened

- 8 -

by the user.

Another object of this invention is to provide a new and improved apparatus for forming an aperture-forming structure for a dispenser package.

Another object of this invention is to provide a new and improved apparatus for forming a nozzle-like aperture structure in a dispenser package so that, upon opening, the contents of the package may be dispensed in a directionally controllable manner.

Another object of this invention is to provide a new and improved self-centering and self-aligning punch and die apparatus adapted to accurately and reliably form a thermoformable material into a hollow tip-like configuration having a peripherally extending fault line so as to permit the tip to be readily broken away by the user to form an aperture opening through which the contents of the package may be dispensed.

The foregoing specific objects and advantages of the invention are illustrative of those which can be achieved by the present invention and are not intended to be exhaustive or limiting of the possible advantages which may be realized. Thus, these and other objects and advantages of the invention will be apparent from the description herein or can be learned from practicing the invention, both as embodied herein or as modified in view of any variations which may be apparent to those of ordinary skill in the art, the same being realized and attained by means of the parts, constructions and instrumentations, and combinations thereof, as well as in the steps and processes pointed out in the appended claims. The present invention resides in the novel parts, constructions, arrangements, combinations, steps and processes, and improvements, herein shown and described.

SUMMARY OF THE INVENTION

Briefly described this invention is directed to a new reclosable aperture forming means which may be formed with an integrally formed cap member which may be tethered to said aperture forming means to create a unit which may be independently formed and adhesively or sealingly attached to a container wall or

- 9 -

surface over a hole in said container wall to create an easy opening, reclosable, when necessary, dispensing package. Said reclosable aperture forming means embodying an integral, hollow protrusion member preferably comprised of two stages, a drum shaped base from which extends a generally conical or frusto-conical tip, said tip member
5 having a fault line encircling it at its juncture with the flat top surface of the first drumlike formation which may be readily broken off to form an opening through which the contents of the package may be dispensed in a directionally controllable stream. After the tip of the protrusion member is broken off by applying light lateral finger pressure, the desired quantity of the contents may thereafter be expelled through
10 the opened nozzle-like outlet by gentle hand squeezing of the package.

In a second embodiment the entire reclosable aperture forming means may be integrally formed into what will become an easy to use reclosable dispensing package. In this second embodiment a generally relatively flexible, compressible pouch or container member is sealably attached to a cover member forming the top or
15 lid of the package. The cover member includes the new reclosable aperture forming means and tethered cap member as described above and similarly used.

In another desirable embodiment the pouch or container member has the integral hollow protrusion and tethered cap member thermoformed into the underside of its relatively stiff rim. The advantage of this version being that the cover
20 member then becomes a relatively thin skinlike member which is very easy to print and less expensive than the formed upper cover member.

The aforesaid cap member which is initially formed with the package as an integral unit is preferably formed along one peripheral edge of either the cover member forming the top or lid of the package relatively closely adjacent to the
25 breakaway protrusion member or on the underside of the rim. A cut line may create a tether member which permits the cap member to be mechanically removed by the user from its molded position in production and placed over the opened nozzle-like aperture forming means so as to protect the breakaway tip during shipping and handling, while remaining tethered to the package. As also preferably embodied, the aforesaid cap

- 10 -

member permits the end user of the package to readily open or reclose the package after each use.

* * * *

In other alternative embodiments of the dispenser package of the present invention:

(i) the breakaway protrusion member forming the aperture in the package may be broken off at the surface of the cover member forming the top or lid of the package, thereby eliminating the nozzle-like outlet configuration in those applications where the contents of the package don't require nozzle formation;

(ii) the cap member may be formed with miniature protrusions to act like a brush, or may have some other desired shape to perform some other desired tool function for use in handling the contents dispensed from the package, such as by brushing or spreading;

(iii) if reclosing the package is not required, the cap member may be open-ended having a predetermined shape such that, upon placing the cap member over the nozzle-like aperture of the package, the contents may be dispensed in such shaped stream;

(iv) the cap member may be provided with an internal central plug dimensioned to mate with the opening formed in the dispenser package to thereby serve as a plug to further ensure sealing of the opening after removal of the breakaway protrusion member; and

(v) the breakaway protrusion and tethered cap members may be formed in a portion of the cover member which extends beyond one end of the compressible pouch member at a predetermined angle and communicates with the product contained in the pouch by means of a shallow neck or channel, thereby facilitating application of the contents of the package onto a surface, such as, e.g., toothpaste onto a toothbrush or glue onto a break line. Alternatively, the breakaway protrusion member may be formed in the cover member directly over the pouch portion with the cap formed at an adjacent small flat area. This method yields a somewhat larger pouch volume while

- 11 -

using the same total amount of material.

It will be understood that the foregoing preferred embodiments of the dispenser package of the present invention may be thermoformed from a wide variety of plastic materials, including, e.g., PP (polypropylene) Barex, HDPE (high density polyethylene), HIPS (high impact polystyrene) and foamed HIPS, as well as various laminations and/or coextrusions of the aforesaid materials and other plastic materials, including, e.g., PP/EVOH (ethylene vinyl alcohol)/PP; Barex/PP; Barex/EVOH/PP; PET (polyethylene tetrafluoride)/LLDPE (linear low density polyethylene); PET/EVOH/LLDPE; PVC (polyvinylchloride)/LLDPE; NY (nylon)/LLDPE; and NY/EVOH/LLDPE. Alternatively, the aperture forming means and the dispenser packages of the present invention may be formed by injection molding.

It also will be understood that the foregoing preferred embodiments of the dispenser packages of the present invention may be manufactured in a wide variety of sizes, as desired, although the preferred size range is from about 2 ml capacity to about 4 fluid ounce capacity. Similarly, the aforesaid package may be manufactured in a wide range of dimensions. A typical size for a package containing 30 ml or 1 fluid ounce of material is on the order of about 1 inch deep by about 1 inch wide by about 3 to 4 inches long, which fits comfortably in the palm of the hand of most users. Furthermore, the independent formations of aperture forming means and the tethered caps may be applied to a very wide range of packaged from single use sizes to half gallons.

Briefly described, as preferably embodied, the apparatus of the present invention forming the preferred aperture-forming protrusion member in the cover member of the dispenser package includes a two-stage punch member which advances to engage and clamp a thermoformable material against a self-centering and self-aligning hollow anvil member. The first punch member advances to initially form a hollow, drum-shaped protrusion in a specific heated area of the thermoformable material. Thereafter, a second punch member preferably located within, and moveable relative to, the first punch member continues to advance forward. The second punch

- 12 -

member includes a first generally frusto-conically shaped surface adapted to form a substantially cylindrical or frusto-conically shaped hollow tip member extending from the drum-like protrusion formed by the first punch member. At the moment formation of the hollow tip member is completed, the forward advancement of the second punch
5 brings a second shallow conical surface into cooperating engagement with the peripheral edge or rim defining the hollow portion of the anvil member to thereby compress the wall of the formed hollow tip about a peripheral portion thereof to create a weakened fault line in the hollow tip protrusion member. As here preferably embodied, the aforesaid punch and anvil members create a fault line at the base of the
10 aforesaid hollow tip protrusion member which extends continuously about the periphery thereof.

In an alternative embodiment of the apparatus of the present invention, the heated sheet of thermoformable material is clamped against the anvil member and a single stage punch member having a generally frusto-conically shaped forward end
15 portion is thereafter advanced to form the aforesaid hollow, substantially cylindrical or frusto-conically shaped tip member. At the moment formation of the hollow tip member is completed, the rim of the anvil member compresses the wall of the hollow tip member about the periphery thereof to create a weakened fault line. It will be seen that the heated thermoformable film (material) may be clamped against a relatively
20 thin plate spaced away from the anvil which contains an accurately aligned hole centered on the aperture of the anvil member. In this embodiment, between the punch and anvil the film will be formed into a conical member as the punch is advanced through the plate and said conical member will then be further formed until it contacts the peripheral edge or rim at the opening of the aperture in the anvil. This alternate
25 apparatus creates a fault line banding or girdling the formed conically-shaped tip member at a predetermined point between its base and its apex.

It will be appreciated by those skilled in the art that the foregoing various brief descriptions and the following detailed description are exemplary and explanatory of the present invention, but are not intended to be restrictive thereof or

- 13 -

limiting of the advantages which can be achieved by the invention or various combinations thereof. The accompanying drawings, referred to herein and constituting in part hereof, illustrate preferred embodiments of the invention and, together with the detailed description, serve to explain the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevation view of a dispenser package constructed in accordance with the present invention with an integrally formed cap member;

FIG. 2 is a top plan view of the dispenser package of Figure 1;

FIG. 2a is a perspective view of a dispenser package constructed in accordance with the present invention with an integrally formed cap member on the underside of the containment members rim and their skin like unformed cover member;

FIG. 3 is an end view of the dispenser package of Figure 1;

FIG. 3a is an end view of the dispenser package of Figure 2a showing an unformed very thin flexible cover member;

FIG. 4 is a side view in elevation, partly sectional, of an apparatus constructed in accordance with the present invention for forming the breakaway tip and nozzle protrusion members in a heated sheet of thermoplastic material;

FIG. 5 is an enlarged sectional view, partly in elevation, of the first and second punch members and the self-aligning hollow anvil member illustrated in FIG. 4, this view illustrating formation of the first protrusion member in the thermoplastic sheet material;

FIG. 6 is an enlarged view similar to FIG. 5, illustrating formation of the second protrusion member in the thermoplastic sheet material;

FIG. 7 is an enlarged view of FIG. 6, illustrating formation of the peripherally extending weakened fault line at the base of the second protrusion member;

FIG. 7a an enlarged side plan view of first and second protrusion members according to one embodiment of the present invention;

- 14 -

FIG. 7b is an enlarged side plan view of first and second protrusion members according to one embodiment of the present invention;

FIG. 8 is an isometric view of the dispensing package of Figure 1;

FIG. 9 is an enlarged isometric view of the dispensing package of Figure 8, illustrating the cap member removed from its molded position and placed over the breakaway tip protrusion member;

FIG. 10 is a schematic illustration showing the use of a hollow punch member for forming a central sealing plug member in the cap member illustrated in the preceding drawings;

FIG. 11 is an isometric view of a cap member formed with a central plug from the apparatus of Figure 10;

FIG. 12 is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member forms a hollow frusto-conical protrusion in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the protruding tip;

FIG. 12a is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member forms a hollow frusto-conical protrusion having a right-cylindrical base in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the protruding tip;

FIG. 12b is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member having a spherical tip forms a hollow mound protrusion in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the mound;

- 15 -

FIG. 13 is a schematic elevation view of the breakaway tip formed by the punch and anvil members illustrated in FIG. 12;

FIG. 13a is a schematic elevation view of the breakaway tip formed by the punch and anvil members illustrated in FIG. 12a;

5 FIG. 14 is a top plan view of another embodiment of a dispenser package constructed in accordance with the present invention, wherein the breakaway tip and cap member are formed in a lateral extension of the cover member and the breakaway tip member communicates with the containment pouch through a shallow channel member;

10 FIG. 15 is a side view of the embodiment illustrated in FIG. 14;

FIG. 16 is an end view of the embodiment illustrated in FIG. 14;

FIG. 17 is a side view of the embodiment of the invention illustrated in FIG. 14, wherein the lateral extension of the cover member also extends angularly downwardly;

15 FIG. 18 is a schematic view of an alternate embodiment of the cap member, formed with bristles or nubs on its outer surface;

FIG. 19 is a schematic view of another alternate embodiment of the cap member, formed with a flattened spreader tool utensil on its outer surface;

20 FIGS. 20a-d are partial end views of still other alternate embodiments of the cap member of the present invention, each view illustrating an open-ended cap member;

FIG. 21a is a top plan view of a reclosable outlet aperture forming structure which can be applied to various forms of containers in accordance with an alternate embodiment of the present invention;

25 FIG. 21b is a side view of the reclosable outlet aperture forming structure shown in FIG. 21a;

FIG. 22a is a perspective view of the reclosable outlet aperture forming structure of FIGs. 21a-b, as applied to a milk carton, in which the cap is placed over the outlet;

- 16 -

FIG. 22b is a perspective view of the reclosable outlet aperture forming structure of FIGs. 21a-b, as applied to a milk carton, in which the cap is removed from the outlet so as to allow removal of the breakaway outlet tip;

FIG. 22c is a perspective view of the reclosable outlet aperture forming structure of FIGs. 21a-b, as applied to a milk carton, in which the breakaway tip is removed from the outlet to form an opening therethrough;

FIG. 22d is a perspective view of the milk carton of Figures 22a-c, in which the breakaway tip is removed from the outlet to form an opening through which milk is being poured;

FIG. 23 is a side view of a low profile breakaway tip in accordance with another embodiment of the present invention;

FIG. 23a is a side view of a low profile breakaway tip in accordance with another embodiment of the present invention;

FIG. 24 is a top view of the low profile breakaway tip of FIG. 23;

FIG. 24a is a top view of the low profile breakaway tip of FIG. 23a;

FIG. 25 is a perspective view of the low profile breakaway tip of FIG. 23 with the removed breakaway tip shown in phantom;

FIG. 26 is a side view of a cap for use with the low profile breakaway tip of FIG. 23;

FIG. 27 is a side view of a another embodiment of the present invention which utilizes a twist-lock or twist-threading arrangement to secure the cap to the base formation;

FIG. 28a is a perspective view of another embodiment of the present invention in which a tethered plug is used to open and close a pre-scored surface;

FIG. 28b is a perspective view of the embodiment of FIG. 29a in which the pre-scored surface has been opened;

FIG. 28c is a perspective view of the embodiment of FIG. 28a in which the plug has been placed in the outlet hole, thereby opening the hole along the pre-scored surface and/or plugging the hole;

- 17 -

FIGs. 29a-d are top views of the outlet of the embodiment of FIG. 28a depicting various types of scored surfaces formed in the outlet; and

FIGs. 30a-d are side views of the scored surfaces shown in FIGs. 29a-d, in which each of the scored surfaces has been penetrated to create an opening therethrough and a flap descending from the surface;

FIG. 31 is a partially elevated side view of an outlet forming structure according to an alternative embodiment of the present invention, having a punch/plug and a scored mount, as applied to a milk carton;

FIG. 32 is a top plan view of the outlet forming structure of Figure 31;

FIG. 33 is a side plan view of the outlet forming structure of Figures 31 and 32;

FIG. 34 is an enlarged elevated view of the outlet forming structure of Figures 31-33;

FIG. 35 is an enlarged side plan view of the outlet forming structure of Figures 31-34 showing the mound as punctured by the punch/plug;

FIG. 36 is an enlarged side plan view of the mound of Figures 31-35;

FIG. 37 is a side plan view of an alternative embodiment of the present invention in which an outlet forming structure, having a breakaway tip and cap, is applied to a foil package;

FIG. 38 is an enlarged side elevational view of the outlet forming structure of Figure 37;

FIG. 39 is an elevated plan view of an alternative embodiment of the present invention as applied to a foil package;

FIG. 37a is a side plan view of an alternative embodiment of the present invention in which an outlet forming structure is applied to a foil package;

FIG. 38a is a front plan view of the outlet forming structure of Figure 37a;

FIG. 39a is an elevated plan view of the outlet forming structure of Figures 37a and 38a;

- 18 -

FIG. 40 is a partial elevational view of an outlet forming structure according to another alternative embodiment of the present invention, having a snap-in auxiliary punch/plug/cap and protrusion member, that is manufactured by a pick-and-place method;

5 FIG. 40a is an enlarged side plan view of the outlet forming structure of Figure 40 showing the punch/plug/cap puncturing the protrusion member;

FIG. 41 is a top plan view of an alternative embodiment, wherein the outlet forming structures are formed from a single thermoplastic web in a mating arrangement;

10 FIG. 42 is a side plan view of an alternative embodiment of the present invention in which the reclosable container is provided with a scored protrusion and a dual purpose tethered punch/cap;

FIG. 43 is a top plan view of the reclosable container of Figure 42;

15 FIG. 44 is a top plan view of the reclosable container of Figures 42 and 43, wherein the tethered punch/cap is securely fastened over the scored protrusion;

FIG. 45 is an elevated plan view of an outlet forming structure according to one embodiment of the present invention;

FIGS. 46a-c are side plan views of a container for use with an outlet forming structure according to the present invention;

20 FIG. 47 is an elevated plan view of the container of Figures 46a-c with the outlet forming structure of Figure 45 mounted thereon;

FIG. 48 is a top plan view of a container according to an embodiment of the present invention;

FIG. 49 is a side plan view of the container of Figure 49;

25 FIG. 50 is a side plan view of the container of Figures 48 and 49 in a closed position;

FIG. 51 is a side perspective view of the container of Figures 48-50;

FIG. 52 is a side elevational view of a container according to an embodiment of the present invention;

- 19 -

FIG. 53 is an enlarged side plan view of the outlet forming structure of Figure 52;

FIG. 54 is a top plan view of a section of a web of thermoformable material having a series of outlet forming structures formed therein;

FIGS. 55a-55e disclose various views of a sachet with a breakaway tip formation; and

FIGS. 56a-56c disclose views of the flap of the sachet of FIGS. 55a-55e.

FIGS. 57a-57d disclose various views of a reclosable aperture forming means with a breakaway tip remaining attached to the cap after opening.

FIGS. 58a-58b disclose a further tampering evidence and a grip hole.

FIGS. 59a-59e disclose use of the reclosable aperture forming means in FIGS. 57a-57d on a container and a tube.

FIGS. 60a-60d disclose various views of another embodiment of a reclosable aperture forming means.

FIGS. 61a-61e disclose use of the reclosable aperture forming means in FIGS. 60a-60d on a container and a tube.

FIGS. 62a-62g disclose various views of another embodiment of an easy opening pouch.

FIG. 63 discloses an easy opening pouch illustrating seals 3000 to control the product flow from the containment pocket.

FIG. 64A is a top plan view of a peelable adhesive spot on the front face or wall of a pouch with a laser score line partially encircling a portion of the adhesive spot.

FIG. 64B is an enlarged view of the peelable adhesive spot shown in FIG. 64 with a full circle score line.

FIG. 65A illustrates the pouch shown in FIG. 64 in a frontal elevation with a portion of its top folded over into a flap which brings the encircled adhesive spot into contact with another part of the front face.

- 20 -

FIG. 65B is a side view of the pouch shown in FIG. 65A.

FIG. 65C is an enlarged view of the side view in FIG. 65B with encircled spot sealed to its own front face.

FIG. 66 illustrates an adhesive spot with a tongue shaped score line.

FIG. 67 illustrates the tongue shaped outlet created after the top of the pouch is folded over to create a flap and adhesive is sealed to another part of the front face after which the flap is then raised to open the pouch.

FIGS. 68 through 78 are illustrative examples of Redmond tubes, tube like packages and the reinforcement of breakaway tips.

DETAILED DESCRIPTION OF VARIOUS PREFERRED EMBODIMENTS

Referring now more particularly to FIGS. 1-4 and 9 of the accompanying drawings, there is illustrated a dispensing package indicated generally at **10** according to the present invention. The package **10** can be used for single or multiple uses and can be reclosed for further use.

As illustrated in FIGS. 1 and 4, the package **10** includes a cover member **11** formed from a flexible but relatively stiff generally flat sheet **12** of a thermoformable plastic material most suitable to the product contained and the protection that the contained product requires.

Materials such as high-impact polystyrene (HIPS), high density polyethylene (HDPE) polyester, HDPE/EVOH (high density polyethylene/ethylene vinyl alcohol), Borex, polypropylene, etc. may be used. HIPS, HDPE, and HDPE/EVOH are each low cost and can be recycled. HDPE/EVOH creates a superior O₂ barrier.

As will be understood by those skilled in the art, whereas plastics of similar material may be heat-sealed or bonded together, heat sealing different plastics together requires an adhesive layer. Preferably, linear low density polyethylene (LLDPE) is used as such a layer. Thus, multi-layered plastics formed by coextrusion

- 21 -

may be sealed together to form sheet **12** having sealant/barrier **14** of the present invention.

Also suitably bonded to one face of bonded sheet **12**, **14** is a flexible sheet **18** forming at least one pouch chamber **22** adjacent one face of the relatively stiff sheet **12** or bonded sheet **12**, **14** for containing a preferably flowable substance, e.g. a dry powdered or granulated material or a liquid material of any suitable viscosity capable of flowing under light to moderate hand pressure.

Advantageously, and as here preferably embodied, the layer of a suitable sealant/vapor impervious barrier material **14** is suitably integrally bonded to sheet **12** on the inner surface **16** which faces flexible sheet **18**. Flexible sheet **18**, advantageously formed by conventional means, such as vacuum forming, pressure forming, mechanical forming or combinations thereof, is likewise suitably integrally bonded to either inner surface **16** or sealant/barrier **14** of sheet **12**, as the case may be.

The bonds between substantially flat relatively stiff sheet **12**, sealant/barrier material **14** and flexible sheet **18** also may be formed by conventional means known to persons of ordinary skill in the packaging art, such as welding, heat sealing, or adhesive or cohesive bonding. It will be understood that the particular bonding method selected depends upon the particular properties of the materials used and the flowable substance(s) to be contained in the package.

Advantageously, and as preferably embodied, sheet **12** is preferably made of polypropylene (PP), Barex, high impact polystyrene (HIPS) or high-density polyethylene (HDPE), but when combined with barrier **14** may be made of polystyrene, polyester, EVOH (ethylene vinyl alcohol), polyvinyl chloride (PVC), polyethylene tetrafluoride (PET) or nylon, or a copolymer thereof, and barrier **14** is made of a suitable sealant/vapor impervious barrier material, preferably comprising saran and foil laminate, or comprising a laminate of foil and vinyl, or foil alone, depending on the nature of the contents to be contained.

A particularly tough high barrier construction comprises saran laminated on each side with polyethylene (sold by Dow Chemical Co. under the name

- 22 -

"Saranex") as barrier sheet **14**, in turn laminated onto polystyrene or polyester, forming the flexible but relatively stiff sheet **12**. The thickness of sheet **12** varies according to factors, such as the properties of the materials used, the flowable substance contained, and the intended usage. A generally utilized range is 4-12 mils (0.004-0.012"). As
5 previously noted, sheet **12** preferably is somewhat flexible, although more rigid than the material **18** forming pouch **22**, and preferably is stiffened by raised portion **11a** formed in cover **11** in the preferred construction of package **10**.

It will be understood by those of ordinary skill in the art that the bonds formed between materials **12**, **14** and **18** can be obtained by the conventional means
10 previously described, again depending on the nature of the flowable substance being contained.

It will be seen from the foregoing that the structure of FIGS. 1 and 2 forms an enclosed pouch or chamber **22** between the flexible sheet **18** and the relatively stiff member **12**, **14** in which a preferably flowable substance is contained
15 and from which the contained substance is dispensed.

In accordance with the present invention as preferably embodied, the relatively stiff generally flat sheet **12** forming cover **11** includes an aperture-forming protrusion structure **30** which includes a neck member **32** and a breakaway tip member **34** so that, upon removal of tip **34**, neck **32** forms a nozzle-like aperture in package **10**
20 through which the contents may be dispensed in a directionally controllable manner.

Neck and tip protrusions **32**, **34** preferably are substantially hollow, substantially cylindrical and tip **34** preferably is substantially cylindrical or frusto-conical. In the preferred embodiment as shown in the plan view of Figure 3, the aperture-forming protrusion structure **30** is located in cover **11** directly over pouch **22**
25 so that, when opened, nozzle aperture **32** communicates directly with the contents of pouch **22**.

In accordance with the present invention, as preferably embodied, dispenser package **10** includes a cap member **110** formed as an integral part of cover **11**. Advantageously, cap member **110** is removable from cover **11** along a line.

- 23 -

It will be seen that the cap **110** protects the breakaway tip structure **30** from inadvertently breaking off during shipping and handling prior to use, as well as providing a means to reclose the package after opening, i.e., after the protrusion tip member **34** is broken off. Thus, cap **110** protects the remaining contents of the package after each use, permitting multiple uses. The advantage of the tethered embodiment of the invention is that it costs practically nothing, acts as a side pressure spring to maintain the cap on the neck **32** at the opening, acts as a grasping member to assist removal of the cap for each subsequent use, and prevents loss of the cap before the contents of the package have been fully dispensed and the package is ready to be disposed of. Further details of the cap are explained below.

In practically all cases, however, it is believed preferable to provide the two-stage breakaway tip configuration since the first projecting cylindrical formation **32** acts as a nozzle yielding directionally controllable product dispensation, after the tip, i.e., second protrusion **34**, is broken off. Low and medium viscosity flowable products tend to squirt "side-ways" or spurt in non-controllable directions, when passing through an aperture formed in the plane of the cover member. Furthermore, elevating the breakaway tip from the surface of the cover member greatly enhances its ease of use with no practical increase in manufacturing cost.

In use, as here preferably embodied, package **10** preferably is positioned so that pouch or chamber **22** rests in the palm of the hand with the thumb resting on the cover **11**. The thumb or finger of the holding hand, or the user's other hand, if desired, may then be used to apply a light finger pressure against the side of protrusion tip **34**, i.e., the breakaway tip, thereby causing tip **34** to break off, leaving an open neck or nozzle-like aperture **32**.

Once tip **34** is removed and the package thereby opened, the contents of the package **10** may be expelled. This method of use depends on the type of substance contained in the package and where the user would like to place the contents. For example, if the package contains toothpaste, the open nozzle **32** preferably would be placed over a tooth brush, whereupon gentle squeezing of the package **10** will force the

- 24 -

toothpaste onto the toothbrush. If the contents of the package are intended to be placed directly into the user's mouth, or the mouth of a patient, such as for oral medicine or mouthwash, the open nozzle **32** then may be placed directly into the mouth and a portion, or all, of the contents may then be directed into the mouth by squeezing the package. When the desired quantity of the contents of the package has been expelled, if some contents remain, package **10** may then be reclosed for future use by placing cap **110** over the open nozzle **32**.

As previously mentioned, as here preferably embodied, package **10** further includes a cap **110**. While cap **110** may be formed separately from the other elements of package **10**, in the preferred embodiment cap **110** is integrally formed with and is at least partially detachable from the relatively stiff sheet **12** forming cover **11**, as shown in FIGS. 1-3, 9-10, 15-18, 22-23d, 29a-c, 32-35, 38-40, and 42-47, for example.

As shown in Figs. 1-3 and 8-9, cap **110** preferably is located at one corner in cover **11** so as to overhang pouch **22**. A cut line **114** allows cap **110** to be easily removed from cover **11**. Advantageously, as best seen in Fig. 10, cut line **114** extends only partially along the edge of cover **11** so as to provide a tether **130** to maintain cap **110** attached to package **10** even after the cap is placed over either the aperture-forming structure **30** or over the open nozzle **32**.

Cap **110** typically is unthreaded and is dimensioned to fit smoothly, yet securely, over the necked protrusion **32**, which preferably also is smooth and unthreaded, both before and after removal of tip **34**. Cap **110** has a base **126** which lies flat against the top of cover **11**. Tether **130** has several advantages. First, it has been discovered that the tether **130** acts as a spring pressing the cap against the sidewall of the necked protrusion **32**, thereby assisting to hold cap **110** in place when it is placed over the necked protrusion **32**. Additionally, tether **130** provides the added benefit of preventing the cap **110** from becoming lost and allows the user to grip the tether **130** to assist in removal of the cap **110** from the aperture-forming structure **30** or from open nozzle **32**.

- 25 -

Cap **110** of the present invention can be designed in several different embodiments. For example, in the embodiment shown in Figures 10 and 11, the cap can be formed from a hollow punch member **120** that forces the material into a hollow female member **122** with a central protrusion **124** to form a cap with a central plug **126**.

An alternative to the embodiment shown in Figs. 1-4 is shown in Figs. 2a and 3a. As shown, the container **10a** has generally the same configuration as container **10** depicted in Figs. 1-3 is made of the same materials. Specifically, pouch **22a** is formed between a flexible sheet **18a** and the very thin skin like sheet **12a, 14a**, in which a flowable substance is contained. Unlike the previous embodiment, the aperture-forming protrusion structure **30a** is formed on the underside of the flat sheet **18**. Similarly, the cap **110a** is formed on the underside of the sheet **18**. With such an arrangement, not only are the neck and tip protrusions **32a, 34a** of the protrusion structure **30a** protected from accidental rupture, but also the container **10a** is provided with a low cost flexible cover. In order for the protrusion structure **30a** to be in fluid communication with the contents of the pouch **22a**, the pouch **22a** is provided with a channel **11b** which communicates with the protrusion structure.

It will be understood that the aperture-forming protrusion structure **30** may be made by a variety of methods and apparatus. In accordance with the present invention, however, as preferably embodied, a web of thermoformable material to be formed into cover **11** is first heated to a sufficient forming temperature. The web is then formed into the hollow cylindrical protrusion **32** with a closed end. The closed end portion of the cylinder **32** is then further deformed in its central section to create the tip **34**. At the moment tip **34** is completely formed, the intersection of the base of tip **34** and cylinder **32** is compressed, reducing its thickness, to thereby create a fault line extending about the periphery of the base of tip **34**.

Also in accordance with the present invention, as here preferably embodied, aperture-forming protrusion **30** is formed by means of a self-centering and self-aligning male and female punch and die apparatus, indicated generally at **40**, as

- 26 -

shown in Figs. 4-7.

Apparatus **40** includes feed rollers **42** or other means to advance the web or film "F" of thermoformable material into a heating station **44** where a heater block **46** advances against the film to press the sheet against a stationary heater block **48**, which is temperature controlled by a thermocouple **50** and supplied with necessary power at connection **51**. An air cylinder **52** provides the driving force to move the heater block **46** by means of shaft **54**. The heater block **46** includes two heaters energized by an appropriate power source **58**.

A two-stage punch member **60** includes a first male punch **62** formed as a generally cylindrical hollow punch having a substantially flat end surface **64** at its operative end. When the first punch member is advanced, the end surface **64** engages and deforms the heated sheet of thermoformable, preferably plastic, material F, compressing the plastic against a similarly shaped, oppositely mounted, generally cylindrical hollow anvil member **66** movable in a bore **68** of a support **70**. The anvil **66** has an end face **71**. The first punch **62** has a clearance fit with the bore **68** so it can be moved therein to confront the end face of the anvil **66**. Anvil **66** has an aperture bore **67** formed as part of its hollow portion.

Anvil **66** is part of a spring-loaded rocker member **72**, preferably supported by a ball-shaped member **74**, or other similarly shaped curved rocker device, in a larger base opening **75** so as to be both resilient and self-centering and self-aligning with punch member **60**. Although rocker **74** is preferably curved or ball-shaped, a relatively flat surface in spring-mounted engagement with the base of adjustable mechanism **89** also serves to self-center the aperture opening **67** of anvil member **66** with respect to frusto-conical surface **84** and bevelled surface **83** of second punch **80**, more fully described hereinafter. The peripheral edge or rim of aperture **67** in anvil **66** is smaller than the bore of punch **62** to create an internal shoulder **76** when the opposing substantially flat end surfaces **64**, **71** of the hollow cylindrical punch member **62** and the anvil member **66** are brought together. The anvil and first punch are preferably made of hardened steel.

- 27 -

In use, at the end of the first stage of the formation of the aperture-forming protrusion **30**, shown in Figure 5, the plastic web F is formed into a projecting, closed end, hollow generally cylindrical drum-like shape, with the plastic web stretched across the end of the first generally cylindrical hollow punch, and clamped between the opposed facing end surfaces **64**, **71** of the punch and anvil members.

A second punch member **80** is mounted for travel within a hollow bore **81** and beyond the end face **64** of the first punch member **62**. The second punch member **80** includes a shaft **82** whose operative end surface includes a shallow bevel **83**, advantageously on the order of 45°, terminating into a conically-shaped portion **84** with a flat end face **85** forming a frusto-conically shaped tip, indicated generally at **86**. The second punch member and its bevel **83** advances into controlled engagement with the internal peripheral edge of the shoulder **76** formed at the opposed end surfaces **64**, **71** of the first punch **62** and anvil **66**.

In one aspect of the present invention, as preferably embodied, the second punch member **80** can be constructed in multiple parts. For example, each of the frusto-conical and beveled portions **84**, **83** may be formed separately and removably attached to the leading end surface of the shaft **82**, such as by threaded connections. Alternatively, shaft **82** and tip portions **83**, **84** may be formed as an integral unit. The second punch member is driven by air cylinder **87**.

It will be understood from the foregoing that the full length of the frusto-conical end **86** of punch **80** continues to travel past the formed internal shoulder **76** and into the anvil aperture **67** until such time as bevel surface **83** is brought into accurately controlled cooperating engagement with the internal peripheral edge of the internal shoulder **76** formed by the opposed end surfaces **64**, **71** of the first punch **62** and the anvil **66**. Advancement of punch surface **83** against shoulder **76** is accurately controlled by micrometer punch adjustment mechanism **88** and anvil adjustable stop mechanism **89**.

The still-heated closed end of the initially formed hollow cylinder **32**,

- 28 -

i.e., the first drum-like protrusion of the aperture-forming structure **30** is, in a second stage, further formed into a substantially cylindrical or frusto-conically shaped tip **34**, i.e., the second protrusion of the aperture-forming structure **30**, by the advancing second punch member until the shallow bevelled surface **83** of punch **80** engages the plastic sheet. At that time, the second punch surface **83** controllably compresses, cools and sets the plastic web **F** against the internal peripherally extending edge formed at shoulder **76** of the anvil to reduce the thickness, and thereby weaken, the wall of the plastic at the locus of the peripheral edge so as to form a narrow, peripherally extending indentation **100**, known as a rupture or fault line, at the base of tip protrusion **34**. It will be seen that fault line **100** permits the tip protrusion **34** to be readily broken away by means of only light lateral pressure to thereby form a nozzle-like outlet opening at neck protrusion **32**.

It should be noted that changes in the dimensions of the beveled end **86** and the anvil **66** are within the scope of the present invention. For example, it is often desirable to produce a fine stream of the contents of a container, such as motor oil. Consequently, the opening formed by the base of the tip protrusion **34** must be relatively small, such as shown in Fig. 8a. To form such an aperture-forming protrusion structure **30**, the end **86** is elongated, and the beveled surface **83** is positioned closer to the distal end **85**. Furthermore, the anvil **66** is provided with a relatively narrow opening. Consequently, as shown in Fig. 7a, the fault line **100** and the breakaway tip **34a** are smaller. Alternatively, the entire punch **82** and, therefore, protrusion structure **30** is made narrower.

In other applications, where the contents of a container are large particles, such as cat food, the opening must be relatively large, such as shown in Fig. 7b. To achieve a larger opening, the entire punch **82** and, therefore, protrusion structure **30** are made wider. Alternatively, the fault line **100** and the break away tip **34** are made larger.

In an alternate embodiment illustrated in Figures 12 and 13, a single punch **90** with a truncated end **92** can be used. The single punch **90** includes a

- 29 -

bevelled surface **94** which engages the film or web **F** of thermoplastic material to form the generally frusto-conical hollow tip protrusion **34**. As here embodied, thermoplastic web **F** is first clamped between shoulder plate **96** and face **97** of an outer punch member similar to punch **62**. Thereafter, punch **90** advances, whereupon end **94** forms web **F** into frusto-conical tip **34**, as shown as Fig. 13. As alternatively embodied, however, as best seen in Fig. 12, upon completion of the formation of tip **34**, the peripheral edge **76a** of anvil member **70** engages and compresses the outer surface of the frusto-conical wall of tip **34** to create a peripherally extending fault line **100a** along the projecting surface of tip **34** between its base and apex.

In yet another alternative embodiment illustrated in Figs. 12a and 13a, a single punch **91** with a beveled, truncated end **93** can be used to form the generally frusto-conical hollow tip protrusion **31**. The single punch **91** engages the film or web **F** of thermoplastic material with the beveled surface **93**. As with the embodiment shown in Figs. 13 and 14, the thermoplastic web **F** is first clamped between stop plate **95** and clamp means **98** of an outer punch member. Thereafter, punch **91** advances, whereupon end **93** forms web **F** into the frusto-conical tip **31**. As best shown in Fig. 13a, contact of the peripheral edge **77** of angle member **71** compresses the outer surface of the frusto-conical tip **31** to create a peripherally extending fault line **100b**. In contrast to the embodiment shown in Figs. 12 and 13, the stop plate **95** is situated adjacent the shaft of the punch **91**, below the beveled, truncated end **93**. Consequently, the thermoplastic web **F** is formed around the beveled end **93** as well as the right cylindrical shaft **91a**. As can best be seen in Fig. 13a, the resulting frusto-conical tip **31** has a breakaway tip **35**, a permanent projection **33**, and a right cylindrical section **33a**. The right cylindrical section **33a** is provided so a cap may be securely engaged with the tip **31**.

In an alternative embodiment illustrated in Figure 12b, a single punch **91B** has a spherical tip **93A**. The spherical tip **93A** engages the thermoplastic web **F** to form a hollow mound protrusion. As embodied, the thermoplastic web **F** is first clamp beneath a stop plate **95A**. Thereafter, punch **91B** advances, whereupon the spherical

- 30 -

end **93A** forms web F into a hollow mound. Furthermore, the punch **91B** is advanced forwards anvil **71A** until the outer surface of the web F engages the peripheral edge **77A** of anvil member **71A**, thereby creating a fault line that extends around the tip of the mound structures. It has been found that the spherical tip **93A** allows for self
5 alignment of the punch **91B** as the web F engages the peripheral edge **77A** of the anvil **71A**.

Referring now more particularly to Figs. 15-18 of the accompanying drawings, there is illustrated an alternate embodiment of the dispenser package of the present invention, indicated generally by reference numeral **200**. As here embodied,
10 cover **211** includes a lateral extension **211a** which extends beyond one end of the container pouch **222** and both the aperture-forming structure **230** and reclosure cap member **240** are formed in cover extension **211a**. A shallow channel member **250** communicates aperture-forming structure **230** with the contents of pouch **222**. Further alternatively, as shown in Fig. 17, lateral extension **211a** of cover **211** is formed on an
15 angle with respect to cover **11** so as to slope toward the pouch side of cover **11**.

It has been found that the embodiments of Fig. 14-17 are advantageous in that they facilitate dispensing the contents of the package onto a surface, such as butter or cream cheese onto a slice of bread or toothpaste onto a toothbrush.

Referring now more particularly to Figs. 18-20, there are shown several
20 other alternative embodiments of the cap member of the present invention. Thus, as shown at Fig. 18, the top of resealing cap **110** may include bristles or nubs to function as a brush member; as shown in Fig. 19, the top of cap **110** may have a flattened surface **270** capable of functioning as a spreading tool; as shown in Figs. 20a-d, cap
25 **110** may be open-ended and have a shaped edge configuration, such as shown at **280**, **281**, **282**, **283**, respectively, so that the contents of the package may be expelled in a shaped stream.

With reference to Figures 21a-b and 22a-c, an alternate embodiment of the present invention will now be shown and described. In accordance with this alternate embodiment, an independent thermoformed unit is used to create an outlet

- 31 -

aperture in a container. The independent thermoformed unit may take the form of a reclosable outlet forming structure **300**. The reclosable outlet forming structure **300** may generally comprise a cap **310**, a tether **320**, a base **330**, and a breakaway outlet tip **340**. Cap **310** may be connected to base **330** via tether **320**. Score **325** facilitates separation of the cap **310** from structure **300**. The reclosable outlet forming structure **300** may have a pre-applied adhesive or sealant in the area surrounding the base **330** to facilitate application of the structure **300** to a container, such as milk container **302**. As such, the structure **300** may be sealably or adhesively attached to any surface of a container requiring the subject outlet. In particular, the structure **300** may be sealed or adhered to the container in an area surrounding a hole in the container, but not in the area of the cap **310** or tether **320** which must be free of the container's surface. It is to be understood that reclosable outlet forming structure **300** may be attached to containers, such as milk carton **302**, prior to filling. As such, the structure **302** may be applied to a container when it is still a flat blank.

With reference to Figures 22a-d, use of the reclosable outlet forming structure **300** will now be shown and described. With reference to Figure 22a, prior to shipping of the container **302**, the cap **310** may be placed over the outlet forming structure base **330** prior to removal of the breakaway tip **340** so as to assure that the breakaway tip **340** does not accidentally break and the contents of container **302** do not escape while the container **302** is in transit. With reference to Figure 23b, the cap **310** is removed from base **330** to provide access to breakaway tip **340**. The container at this point is ready for opening. With reference to Figure 23c, the breakaway tip **340** is then removed to create an opening **350**. Opening **350** leads to a hole (not shown) in container **302** to allow pouring the contents of container **302** therethrough. With reference to FIG. 23a, the reclosable outlet forming structure **300** may be resealed by simply placing the cap **310** over base **330**.

In one embodiment of the present invention, base **330** and tip **340** are cylindrical or substantially cylindrical, although it is to be understood that other shapes may be used. In this embodiment, the opening **350** is made of PET-PVC-BAREX. It

- 32 -

is to be understood, however, that other materials in accordance with the present invention may be used.

As can be seen in Fig. 22d, the cylindrical outlet **330** and opening **350** act a nozzle direct the flow of the contents of the container **302** into a control stream.

5 With reference to Figures 23-26, a low profile breakaway tip and cap in accordance with another embodiment of the present invention is shown. In general, lowering the height of a breakaway tip **360** will lower the possibility that the tip **360** may be accidentally opened during transit or by handling. Lowering the height of the breakaway tip makes it more difficult, however, to grasp and remove the
10 breakaway tip. This difficulty is alleviated by creating undercuts or indents **370** in the sidewall of the breakaway tip **360**. These undercuts or indents **370** allows a user's finger to hook and break away the tip **360** in a single motion. Figure 25 is a perspective view of the low profile breakaway tip with the removed breakaway tip shown in phantom. With continuing reference to Figures 23-25, the undercuts or
15 indents **370** are preferably arranged in opposed positions to facilitate ease of use and manufacture. It is to be understood that the number and location of the undercuts/indents **370** may be varied. Once the breakaway tip **360** is removed from base **380**, a cap **394** may be used to reclose the opening (not shown) exposed by the removal of tip **360** in base **390**. Base indents **392** in base **380** are shaped and
20 dimensioned to receive opposed inward protrusions **396** of cap **394**. These protrusions **394** snap into indents **392**, thereby securing cap **390** to base **380**. A tether (not shown) may also be used to attach cap **390** to base **380**.

As shown in Figs. 23a and 24a, the base **390a** may have generally triangular cross-sectional area. Such a cross-sectional area, may aid in the dispensing
25 of various materials. Furthermore, the relatively large bottom of the base **390a** helps avoid accidental toppling of a container.

It is also to be understood that this embodiment of the present invention may be used in a wide variety of applications, including dispensers for creamers, unit dose medications, salad dressings, beauty aids, dental products, condiments, candy

- 33 -

confections, syrups, granular products, etc. It is also to be understood that this embodiment of the present invention may be manufactured by utilizing a male punch member in conjunction with a self-centering and receding female anvil system, as previously shown and described.

5 Although the use of a tether limits the rotation of a cap pressed onto a base formation, a twist-lock or twist-threading arrangement may also be used to secure the cap to the base. With reference to Figure 28, such an embodiment of the present invention which utilizes a twist-lock or twist-threading arrangement **400** to secure the cap **410** to the base formation **420** is shown. In this arrangement, cap **410** has an inner
10 protrusion **415** which engages cam surface **430** of base **420**. Upon rotation of cap **410** with respect to base **420**, inner protrusion **415** engages cam surface **430** to create a twist-lock or twist-thread arrangement. It is to be understood that a tether (not shown) may also be used in such an arrangement. Base **420** may also have a breakaway tip **425** attached thereto.

15 As an alternative to the breakaway tip and tethered cap arrangement, the present invention also includes a tethered plug/punch and scored surface arrangement as shown in Figures 28a-c, 29a-d and 30a-d. Figures 28a and 28b are perspective views of such an embodiment of the present invention in which a tethered plug is used to open and close a pre-scored surface. In this arrangement **450**, a plug **460** is used to
20 open a pre-scored surface **470** of outlet **480**. In this embodiment, the score is in the form of an interrupted circle, although it is to be understood that other types of scored surfaces, such as those shown in Figures 29a-d, may also be used. Figures 28b and 28c depict a flap **485** which is created when plug **460** is used to penetrate the scored surface **470**. A tether **490** may also be created through the use of a score **495** in
25 arrangement **450**. Plug **460**, which may be connected to arrangement **450** via this tether **490**, may also be used as a cork to close the outlet hole. As such, plug **460** may be used both as a plug and as an opening tool to create and/or plug an aperture in the pre-scored surface. In this embodiment, plug **460** has a conical shape, although it is to be understood that other shapes may be used. Similarly, as shown in Figures 28a and

- 34 -

29a-d, the score may have a partially circular shape, a V-shape, an X-shape, a star shape, or box shape, although it is to be understood that other patterns may also be utilized. Depending on the shape of the scored surface, the flap created by the penetration of plug **460** will differ. For example, the penetration of scored V-shaped surface **490** will create a flap **491**; the penetration of scored X-shaped surface **492** will create a flap **493**; the penetration of scored star-shaped surface **494** will create a flap **495**; and the penetration of a scored surface **496** will create a rectangular-shaped flap **497**.

An alternative embodiment of the present invention will now be discussed with reference to Figs. 31-36. In accordance with this alternative embodiment, a container **500** is provided with a reclosable outlet forming structure **510**. More specifically, the outlet former structure **510** comprises a curvilinear dome or mound **530** and a dual purpose punch/plug **520**. As will be apparent to one of skill in the art, the container **500** includes a hole, not shown, over which the mound **530** is secured. Because the punch/plug **520** must be lifted and inverted for insertion into the scored area **532**, it must not be sealed to the container **500**. On the other hand, the mound **530** portion of the outlet forming structure **510** must be securely adhered over the hole in the container **500**.

As can best be seen in Fig. 34, the outlet forming structure **510** comprises a layer of foil **534** laminated to the plastic forming the outlet forming structure **510**. The portion of the foil **534** underneath the mound **530** should be unsupported other than the adhesive used to secure it to the mound **530**. It should also be noted that the foil **534** is secured to the container **500**, about the hole in the container **500**, so that the contents do not leak out beneath the outlet forming structure **510**. The foil laminated adhesive should be one that gives adequate adhesion but sets up with minimal tensile strength of its own. In alternative embodiments, the adhesive may approach being brittle.

The mound **530** further includes a fault line pattern or scored pattern **532**. The fault lines **532** may take on any number of patterns, such as those shown in

- 35 -

Figs. 29a-d. As shown in Figs. 35 and 36, the foil **534** is laminated to the entire surface of the mound **530** and preferably, is not scored. In an alternative embodiment, the adhesive may be omitted from the fault line pattern **532**.

5 The punch/plug **520** is secured to the outlet forming structure **510** via a tether **524**. The tether **524** is created by a cut **522** through the foil/plastic laminate. As can best be seen in Fig. 32, the cut **522** preferably takes a curvilinear path, following the periphery of the outlet forming structure **510**. Such a cut **522** provides an elongated tether **524**.

10 In operation, the punch/plug **520** is firmly pushed into the fault line pattern **532** to rupture the scored mound **530**. This operation is best shown in Fig. 35. Having forced the punch/plug **520** through the scored area **532** of the mound **530**, an opening for dispensing the contents of the container **500** is formed. The punch/plug **520** is removed from the mound **530** so that contents of the container **500** may be dispensed. Because the scored area **532** has been deformed to the shape of the
15 punch/plug **520**, the punch/plug **520** may be reinserted into the scored area **532**, thereby resealing the container **500**.

In an alternative embodiment, however, the foil layer **534** may span the hollow base of the mound **530** by being laminated only to the periphery of the mound.

20 Of course, in such an embodiment, the punch/plug **520** must be long enough to extend past the plane of the foil **534** so that the foil **534** may be punctured. By wobbling the punch/plug **520** while inserted into the mound **530**, the opening in the foil is enlarged.

25 It should be noted that the mound **530** strengthens the outlet forming structure **510**. Furthermore, the shape of the mound **530** provides a nozzle function, directing the contents of the container **500** in an even stream. Depending upon the contents of the container **500**, the dimensions and shape of the mound **530** may be altered to provide the desired flow.

The outlet forming structure **510** of Figs. 31-36 are preferably manufactured with a punch similar to that described with reference to Fig. 12b. Of course, the tip of the punch need not be spherical, but rather may be elliptical,

- 36 -

parabolic, or any curvilinear shape. Furthermore, it is preferred that the foil and plastic be laminated into a single web prior to the formation of the mound by the punch. Thus, the dimensions of the mound, as defined by the shape of the punch tip, will be limited only by the physical properties of the materials used.

5 In an alternative embodiment, which will now be described with reference to Figs. 37-38, a reclosable outlet forming structure **610** according to the present invention is utilized with a flexible plasti-foil pouch **600**. In general, the foil pouch **600** is formed by folding a generally rectangular shaped piece of the foil plastic combination in half and sealing the three open edges thereof. A reclosable outlet
10 forming structure **610** is mounted on the seamless end **605** of the pouch **600**. The outlet forming structure **610**, which is sealed to the seamless end of the pouch **600** by applying an adhesive around a periphery of the base **612**, covers a hole, not shown, in the pouch **600**.

The outlet forming structure **610** may be of any type previously
15 disclosed above, such as those described with reference to Figs. 1-3, 8-9, 13, and 13a. In a preferred embodiment, as shown in Figs. 37 and 38, the outlet forming structure **610** includes an aperture forming protrusion **630**. More specifically, the aperture forming protrusion **630** includes a hollow cylindrical base **632** and a break-away tip **634**. A fault line **636** extends around the periphery of the protrusion structure **630**,
20 permitting the breakaway tips **634** to be broken away from the base **632** in the tip **634**. More specifically, the fault line **636** is a narrowed, stress concentrating area.

The outlet forming structure **610** also includes a cap **620**. The cap **620** is a hollow tapered member, which has an inside base diameter slightly larger than the outside diameter of the base **632** of the protrusion structure **630**. The cap **620** is
25 secured to the outlet forming structure **610** via a tether **624**. The tether **624** is formed by a cut **622** through the lower surface **612** of the outlet forming structure **610**. As can best be seen in Fig. 39, the curvilinear cut **622** separates the cap **620** from the protrusion structure **630** and follows the periphery of the base **612**. By having such a pattern, the cut **622** is relatively long and, consequently, produces a relatively long

- 37 -

tether **624**. Due to the long tether **624** and the fact that the portion of the base **612** that supports the cap **620** is not fastened to the pouch **600**, the cap **620** may be raised and securely placed over the outlet forming structure **630**.

In operation, a user applies sidewise finger pressure to the protrusion tip **634**, thereby causing it to break away from the protrusion base **632** along a fault line **636**. Because the protrusion structure **630** is substantially hollow, an aperture, not shown, is created. Furthermore, because the protrusion member **630** has been affixed to the pouch **600** over a hole in the pouch, not shown, the contents of the pouch **600** may be dispensed via the now opened protrusion neck **632**. The cap **620** is placed over the base **632** during shipping, so that accidental rupturing of the fault line **636** is prevented. Furthermore, cap **620** is placed over the base **632** to reclose the package **600** when only a portion of the contents of the package **600** has been dispensed.

In an alternative embodiment, shown in Fig. 39, the same outlet forming structure **610** is secured to the side of pouch **640**. In this embodiment, the pouch **640** is formed from two generally rectangular sheets of foil plastic laminate which are sealed together around all four sides of each sheet. As with the previous embodiment, the protrusion structure **630** is affixed to the pouch **640** over a hole, not shown, so the protrusion neck **632** is in fluid communication with the contents of the pouch **640**.

An alternative embodiment of the present invention employing an outlet forming structure **610a** disposed on a foil pouch **640a** will now be described with reference to Figures 37a, 38a, and 39a. Briefly described, the outlet forming structure **610a** is substantial the same as the outlet forming structure described with reference to Figures 37-39. Specifically, the outlet forming structure **610a** includes both a cap **620a** and a protrusion member **630a**. As best seen in Figure 39a, the foil pouch **640a** includes a lap seam on the side opposite the outlet forming structure **610a**.

An alternative embodiment of the present invention will now be described with reference to Fig. 40. A tethered punch/plug and base member with a star shaped fault pattern manufactured as a unit **700** is shown. A tether **730** is

- 38 -

connected to the base **710** at a proximal end thereof, a ring structure **740** connected to a distal end thereof, and a tapered punch/plug **760**. The punch/plug **760** is manufactured separately from the other components.

As shown, the ring structure **740** defines an opening **750**. The opening **750** is larger than the tip **762** of the punch/plug **760** yet smaller than the base **764** of the punch/plug **760**. Furthermore, the punch/plug **760** includes a circumferential indentation **766**. The indentation **766** is formed on the punch/plug **760** just below a point where the outside diameter of the punch/plug **760** becomes larger than the inside diameter of the opening **750**.

Therefore, once the components have been separately manufactured, the punch/plug **760** is snapped into the opening **750**. When snapped into the opening **750**, the tapered punch/plug **760** causes the slightly elastic ring structure **740** to expand until the ring structure **740** reaches the indentation **766**. Upon reaching the indentation **766**, the ring structure **740** snaps into the indentation **766**. Consequently, the punch/plug **760** becomes connected to the ring structure **740** and the other components.

In use, as shown in Figure 40a, the punch/plug **760** is used to puncture the scored section **722** of the protrusion structure **720**. Such operation is described in greater detail with reference to Figs. 28-30d.

Turning now to Fig. 41, one embodiment for manufacturing a reclosable outlet forming structure according to the present invention is shown. Specifically, a pair of reclosable outlet forming structures **870** and **880** are formed from the same piece of thermoplastic web **F**. Each reclosable outlet forming structure **870**, **880** comprises a protrusion structure **872**, **882** as well as cap **874**, **884**, respectively. As in the previously disclosed embodiments, each cap **874**, **884** is connected to the corresponding protruding structure **870**, **880** via a tether **876**, **886**.

It is to be understood that the mating, horse-shoe arrangement of the outlet forming structures **870**, **880** provides several benefits, such as reclining wasted portions of the web **F**, and that the manufacturing agreement may be repeated along the length of the web **F**.

- 39 -

Turning now to Figures 42-44, an alternative embodiment of the present invention is shown. Initially, it should be noted that the container 1000 shown is made of similar materials as described above with reference to Figure 1-3.

The container 1000 comprises a first deformable pouch 1010 and a
5 second deformable 1020. The two pouches 1010, 1020 are joined by a shallow conduit 1030. The deformable pouches 1010, 1020, as well as the joining conduit 1030, are sealed by a generally flat sheet 1040 of thermoformable plastic material. A hollow protrusion 1050 is integrally formed with the flat sheet of thermoformable plastic 1040. The hollow protrusion 1050 extends from the flat sheet 1040. The protrusion
10 1050 is directly above and in fluid communication with the conduit 1030. The container 1000 further includes a punch/cap 1060.

As can best be seen in Figure 43, the hollow protrusion 1050 has scores or fault lines 1055 on the top face thereof. Despite these fault lines 1055, which weaken the protrusion 1050, the container 1000 remains sealed. Further shown in
15 Figure 46, the punch/cap 1060 is partially separated from the remainder of the container 1000 by cut 1062. The cut 1062 which parallels one peripheral edge of the container 1000 creates a tether 1064.

In order to open the container 1000, the punch/cap 1060 is positioned over the protrusion 1050. The punch/cap 1060, and more specifically the pointed end
20 1066 of the punch/cap 1060 is forced through the score or fault lines 1055, thereby opening the hollow protrusion 1050. When punch/cap 1060 is removed from the hollow protrusion 1050, an opening, not shown, exists. The opening is formed by the permanent deformation of the portion of the protrusion member 1050 between the fault lines 1055. By inverting the container 1000 and gently squeezing either or both of the
25 pouches 1010, 1020 the material contained within the pouches is dispensed via the opening in the protrusion 1050.

It should be noted that in the preferred embodiment the protrusion 1050 is placed directly above the conduit 1030. As a result, the contents of the pouches 1010, 1020 can be dispensed in a controlled manner. Specifically, the shallow conduit

- 40 -

1030 provides resistance to the flowing contents so that the contents do not spout from the opened protrusion 1050 uncontrollably, particularly when the protrusion 1050 is initially punctured.

As shown in Figure 44, should less than all of the material contained within the pouch 1010, 1020 be dispensed, the container 1000 may be reclosed. Specifically, the punch/cap 1060 is inverted by twisting the tether 1064. Because the punch/cap 1060 is hollow, having an inside diameter substantially the same as or slightly larger than the outside diameter of the protrusion 1050, the punch/cap 1060 can be securely placed on the protrusion 1050.

With regard to the embodiment of Figures 42-44, it will be apparent to one skilled in the art that the invention is not limited by the type of outlet forming structure utilized. Specifically, any combination of break away tip, scored protrusion member, punch, plug, and cap may be employed. Furthermore, it should be understood that the particular shape of the pouches may vary according to the properties of the contents held therein.

An alternative embodiment of the present invention will now be described with reference to Figures 45-47. As shown in Figure 45, an outlet forming structure 1070 comprises a cap member 1072 and an aperture forming protrusion 1074. As with the embodiments discussed above, the cap member 1072 is connected to the aperture forming structure 1074 by a tether 1076. As can be seen, both the cap member 1072 and the aperture forming structure 1074 are formed in a curvilinear base 1078.

Because the outlet forming structure 1070 is formed in a curvilinear base 1078, it may be positioned on a container 1080 having a similar curvilinear surface. As shown in Figures 46a-c, one such container 1080 is generally spherical and formed in two halves 1082, 1084. The two halves 1082, 1084 are joined at one point along their circumferences, and are therefore hingeably connected. One half 1084 of the container 1080 includes an aperture 1086 formed therein.

In operation, as shown in Figure 47, the outlet forming structure 1070 is

- 41 -

affixed to the container 1080 such that the aperture forming structure 1074 is in alignment with the aperture 1086 in the container 1080. As further depicted in Figure 47, the cap member 1072, shown in a sectional view, may be positioned over the aperture forming structure 1074, thereby protecting it and sealing the container 180. It is to be understood that the shape of the container 1080 is merely representative of those that may be employed with the present invention, as the outlet forming structure may be formed on a curvilinear base having virtually any shape.

Another alternative embodiment of the present invention will now be described with reference to Figures 48-51. The container 1090 generally comprises a rectangular sheet 1091 of thermoformable material. At the center of the rectangular sheet 1091 is an aperture forming structure 1092, having a base and break away tip as described above with reference to the prior embodiments. On either side of the aperture forming structure 1092 are pouches 1098 formed on the underside of the sheet 1091 for holding any flowable substance. The pouches 1098 are in fluid communication with the aperture forming structure 1092.

Also formed in the rectangular sheet 1091 of thermoformable material is a cap member 1094. The cap member 1094 is preferably formed in one corner of the rectangular sheet 1091 and attached to the container 1090 via a tether 1096. The tether 1096 is formed by a cut 1097 extending along the perimeter of the container 1090.

The container 1090 may be folded generally in half along bending grooves 2006 disposed on either side of the aperture forming structure 1092. Specifically, the ends of the container 1090 are brought together as depicted by arrows "A" in Figure 49. Once the ends are brought together, a female package tie 2000 and a male package tie 2002, both of which are integrally formed in the sheet of thermoformable material 1091, are brought into engagement.

Engagement of the female package tie 2000 and the male package tie 2002 hold the container 1090 in the configuration as shown in Figures 50 and 51. In operation, lateral finger pressure on the tip of the aperture forming structure 1092

- 42 -

causes a fault line to rupture, thereby forming an aperture in the aperture forming structure 1092. Thus, the contents of the container 1090 may be dispensed from the aperture. As shown in Figure 51, the cap member 1094 may be placed over the aperture forming structure 1092, thereby preventing accidental rupturing of the fault line or accidental dispensing of the contents after the tip of the aperture forming structure 1092 has been removed.

Another alternative embodiment of the present invention will now be described with reference to Figures 52-54. As shown in Figure 52, an aperture forming structure 2016 according to the present invention may be positioned on a treated paper board tube 2012, thereby forming a sealed container 2010. The aperture forming structure 2016 comprises a generally hollow frusto-conical portion 2018, a hollow cylindrical portion 2019, and a breakaway tip 2020. Integrally formed with the aperture forming structure 2016 is a cap member 2022 and an associated tether 2024. As can best be seen in Figure 54, the tether 2024 is formed by a curvilinear cut which allows the cap member 2022 to be partially separated from the aperture forming structure 2016 so that the cap member 2022 may be positioned over the cylindrical portion 2019 and the breakaway tip 2020. Because the cap member 2022 has an inside diameter slightly larger than the outside diameter of the cylindrical portion 2019, the cap member 2022 fits snugly thereon, thereby sealing the container 2010.

As with the previously described embodiments, in operation, lateral pressure on the breakaway tip 2020 causes it to separate from the rest of the aperture forming structure 2016, thereby forming an aperture into the generally hollow aperture forming structure 2016. Thus, the contents of the container 2010 may be dispensed therefrom.

Another alternative embodiment is described in Figures 55a through 56c. This embodiment relates to a pouch or sachet like container 2100 generally used for dispensing such products as ketchup, condiments, salad dressing and many non-food products such as surgical jelly, etc. Many pouches have a serious flaw in that they are difficult to open and messy. This embodiment relates to a sachet 2100 which

- 43 -

is simple to open and cleanly dispenses product.

As shown in Figures 55a-56c, the sachet 2100 has a breakaway tip formation formed into the wall or face of the sachet located near one of its corners. By bending the end having the tip 2100c on it over and sealing the tip to the same wallface of the sachet 2100 the tip is then located to form a system which is easily and neatly opened. The user simply grasps the flap 2100a or bends it back. The sealed tip breaks away and leaves a product outlet hole 2100b in the wall.

It may be seen from the Figures that the tip could be located in the wall beneath a flap and sealed to the flap in which case the outlet hole would remain in the wall when the flap was folded back and the tip would remain on the flap. It may also be seen that the flap may be bent from a corner as shown in Figs. 56a-56c.

Another alternative embodiment is described in Figures 57a through 57d. This embodiment relates to an improved reclosable aperture forming means 2200 generally made of thermoformed plastic but not excluding plastic formed by other means or other formed materials. This improved unit 2200 does not require that a breakaway tip be broken away manually and/or disposed of. Instead, the improved unit 2200 embodies a system where a breakaway tip 2202, preferably reduced in height, has its uppermost surface 2204 sealingly attached to the upper inner surface 2206 of a cap member 2208. It may then be seen that the breakaway tip 2202 is automatically broken away from the lower formation 2210 at the fault line intersection 2212 of the tip 2202 and the upper surface 2214 of the lower formation 2210 when the cap 2208 is hinged up and away from its seat about said lower formation 2210. When the tip 2202 broken away from the lower formation 2210, an aperture or outlet 2216 is created. It may further be seen that the breakaway tip 2202 remains sealed to the inside of the cap 2208 which may be used normally to recap or open the aperture or outlet 2216 for dispensing or pouring out the contained product.

In its preferred embodiment, the breakaway tip 2202 should require a firm pull to break it away with an audible snap to insure the user that it was not tampered with. Break resistance is fully adjustable during manufacture. It can also be

- 44 -

seen that the unit may be made of clear plastic so that the tip may be seen before broken away to show any evidence of tampering.

As illustrated in Figures 59A and 59B, to further insure tamper evidence, even though there will be a snap, at least one additional tacking point 2302 may be made between the flap 2310 containing the cap 2208 and the flat plastic around the lower breakaway tip protrusion to create a tamper evidence. These points can be highlighted by making a circular cut about them with a tiny uncut tab 2304. Thus, if the flap is even raised partially, it will tear the tiny tab and leave a hole in the flap. it will also be understood that various styles of finger grips 2306 may be used. One simple one is a round hole in the lower portion of the flap 2310.

As illustrated in Figures 59a to 59e, the reclosable aperture forming means 2200 can be used on, for example, a milk carton or a tube holding, for example, toothpaste or hair gel. Although the reclosable aperture forming means 2200 can be also used on other packages such as, for example, bags, containers, pouches, pillow packages (e.g. sachets), etc.

An alternative embodiment is described with reference to Figures 60a through 60d. The embodiment 2400 illustrated in Figures 60a through 60d replaces the breakaway tip 2202 formed in the upper surface 2214 of the lower drum 2412 shaped formation of Figures 57a through 57d with a preformed outlet hole 2402 at the center of the surface drum 2412 surrounded by a generally flat rim 2404 to which is applied a peelable adhesive 2406. The peelable adhesive 2406 may be heat sealable, although cold seal or pressure sensitive or other variety may be used. The hinged cap member 2408 formerly sealed to the breakaway tip may be peelably adhered to the rim 2404 surrounding the outlet hole 2402 to effectively seal off the outlet. When the hinged cap 2408 is hinged up it peels away from the drum formation 2412 by rupturing the adhesive 2406 and effectively opens the outlet hole 2402. This entire system, made of thermo-formed plastic, can be either integrally formed into the wall of a container or sealingly attached to a container over a hole in the container wall.

It may also be seen that the inner top surface 2410 of the cap 2408

- 45 -

which covers the lower drum 2412 may have an adhesive applied to it rather than the rims 2404 and around the hole 2402. It may also be desirable to have the adhesive 2406 applied to the upper rim surface of the drum 2412 as well as the inner mating surface 2410 of the cap 2408. It may be seen that adhesive could be applied to the walls of the drum, however, it would be very difficult to rupture by hand. Since there is no longer a tip protrusion, the inner surface 2410 of the cap 2408 should be dimensioned so as to bring the adhesive into contact at the upper surface of the drum 2412.

As illustrated in Figures 61a to 61e, the reclosable aperture forming means 2400 can be used on, for example, a milk carton or a tube holding, for example, toothpaste or hair gel. Although the reclosable aperture forming means 2400 can be also used on other packages such as, for example, bags, containers, pouches, pillow packages (e.g. sachets), etc.

Another alternative embodiment is described in Figures 62a through 62g. This embodiment relates to an easy opening rectangular pouch 2500 or other shape or form of packaging wherein a hole 2502 is created in one wall or surface 2504 of the pouch etc. which is at least encircled with a peelable adhesive 2506. The opposite wall 2508, which is sealed to the side away from the adhesive 2506, which at least encircles the hole (aperture) 2502 on all its edges to create a containment pouch is then folded over to create a flap 2510 over the adhesive encircled hole 2502. The same surface of the flap 2510 with the hole 2502 in it is then sealed to the peelable adhesive 2506 on its own surface. This surface is preferably heat sealed together but a contact or pressure adhesive may be used to eliminate the need for heat. The pouch 2500 may then be opened by lifting the flap 2510 which peels away from the surface 2504 containing the outlet hole 2502 to allow the outlet hole to be exposed to the outside. It is understood that the adhesive 2506 may be applied just around the hole 2502 and/or on the surface below the hole which the hole 2502 touches when bent over or for convenience in manufacturing, the entire surface of the side of the pouch 2500 may be adhesive coated. The flap 2510 can also be a corner folded over such as, for

- 46 -

example, the embodiment illustrated in Figure 62g.

The purpose of the seals 2600 shown in Figure 63 is to seal together the front and back walls of the pouch restricting the width of the flow channel of the low viscosity product. Not only is the channel width restricted but due to the nature of the films, as the channel width is reduced the films of each wall will not expand to allow product to flow between them without pressure. In other words a valving action may be produced wherein the product will not drip or spill out when no pressure is exerted on the body of the pouch, squeeze the pouch for product flow, no squeeze, no flow or drip. It will be realized that outlet hole diameters on the order of .030 inches may be required for low viscosity products.

An easy opening rectangular pouch or other shape or form of packaging which has a fault line created in one wall or face of the pouch which at least partially encircles a portion of an area of a wall coated with peelable adhesive. The end portion of said pouch or a corner or like part of said pouch is then folded over to create a flap over the fault line partially encircled area of peelable adhesive. The surface of said flap is then sealed to the peelable adhesive at another location of its own surface at least within the confines of the area of adhesive encircled by the fault line. Either pressure sensitive or heat sealable adhesive may be used. The pouch may be opened by lifting the flap which tears out the fault line encircled adhesive together with the part of the wall it adhered to create an outlet aperture.

It may be seen that the peelable adhesive may extend beyond or outside of the at least partially encircling fault line but only the encircled wall area will be torn away to create the aperture.

It may also be seen that the outflow of product may be controlled by the additions of seals 3000 which extend in from the edge as in Fig. 63 of one of the drawings as well as seal patterns to create flow baffles. The flow control for the easy opening pouches, particularly for very low viscosity fluids such as, for example, soy sauce, skim milk, water, alcohol, solvents, or the like, comprise of at least one seal to block the rate of product flow from the containment pocket to the outlet hole.

- 47 -

Modern technology has developed laser systems which can put score or fault lines in very thin films. FIG. 64A is a top plan view of a peelable adhesive spot on the front face or wall of a pouch with a laser score line partially encircling a portion of the adhesive spot. FIG. 64B is an enlarged view of the peelable adhesive spot shown in FIG. 64 with a full circle score line. FIG. 65A illustrates the pouch shown in FIG. 64 in a frontal elevation with a portion of its top folded over into a flap which brings the encircled adhesive spot into contact with another part of the front face. FIG. 65B is a side view of the pouch shown in FIG. 65A. FIG. 65C is an enlarged view of the side view in FIG. 65B with encircled spot sealed to its own front face. FIG. 66 illustrates an adhesive spot with a tongue shaped score line. FIG. 67 illustrates the tongue shaped outlet created after the top of the pouch is folded over to create a flap and adhesive is sealed to another part of the front face after which the flap is then raised to open the pouch.

FIGS. 68 through 78 are illustrative examples of Redmond tubes, tube like packages and the reinforcement of breakaway tips.

It will remain understood by those skilled in the art that the present invention in its broader aspects is not limited to the particular embodiments shown and described herein, and that variations may be made without departing from the principles of the invention and without sacrificing its chief advantages.

- 48 -

I CLAIM:

1. A sealed containment and dispensing package for flowable products comprising an aperture forming means wherein a portion of said aperture forming means is folded over to create a flap member which is sealingly attached to a portion of its own surface it covers which when the flap member is folded back it produces an outlet aperture in its surface.

2. The package according to claim 1, wherein said aperture forming means comprises a breakaway tip member made of thermoformed plastic and is integral with such sealed containment package.

3. The package according to claim 2, wherein said breakaway tip member is located on said flap member.

4. The package according to claim 3, wherein the outermost surface of said breakaway tip member is sealingly attached to the portion of its own surface it covers.

5. The package according to claim 2, wherein the aperture forming means is made independently of said sealed containment package and subsequently sealingly integrated with said sealed containment package.

6. The package according to claim 5, where a portion of said aperture forming means includes a cap thermoformed adjacent to said breakaway tip member to fit over the base of said breakaway tip member to reclose the containment package after it has been opened by the formation of said aperture.

7. The package according to claim 1, wherein said sealed containment package has as its aperture forming means a pre-made hole pattern in one

- 49 -

1 wall of the flap member which when folded over is peelably sealed to said portion of
2 its own surface which it covers, at least completely encircling said pre-made hole
3 pattern.

4
5 8. The package according to claim 1, where said sealed
6 containment and dispensing package has as its aperture forming means a pre-made cut
7 pattern in one wall of said flap member which when folded over is peelably sealed to
8 said portion of its own surface which it covers, at least completely encircling said pre-
9 made cut pattern.

10
11 9. The package according to claim 1, where said sealed
12 containment and dispensing package has as its aperture forming means a pre-made
13 fault line score pattern in one wall of said flap member which when folded over is
14 peelably sealed to said portion of its own surface which it covers, at least across entire
15 said fault line pre-made score pattern.

16
17 10. The package according to claim 7, where said sealed
18 containment and dispensing package is a pouch style package.

19
20 11. The package according to claim 8, where said sealed
21 containment and dispensing package is a pouch style package.

22
23 12. The package according to claim 9, where said sealed
24 containment and dispensing package is a pouch style package.

25
26 13. The package of claim 9, where said sealed containment and
27 dispensing package is a tube style wherein the hinged flap member with said
28 protrusion forming a flat topped drum shaped cap member is a flat end seal on said
29 tube.

- 50 -

1 14. The package according to claim 9, where said aperture forming
2 means is made independently of such sealed containment and dispensing package for
3 subsequently sealingly integrating it with such sealed containment and dispensing
4 packages.

5
6 15. A sealed containment and dispensing package having an
7 aperture forming means made of thermoformed plastic comprising a pair of hinged
8 members, one member being a flap having a protrusion forming a flat topped drum
9 shaped cap member, the other member having a mating protrusion of similar shape to
10 said cap member with an aperture in its flat top surrounded by a generally flat rim so
11 located that when said flap with the drum shaped cap member is hinged over the
12 mating protrusion with the aperture in its flat top rim meets with the flat inner surface
13 of the cap where by virtue of a preapplied peelable adhesive to at least one of the flat
14 surfaces meeting they are peelably sealed together completely about said aperture.

15
16
17
18




FIG. 1




FIG. 2




FIG. 3




FIG. 2a




FIG. 3a




FIG. 4




FIG. 5







FIG. 6









FIG. 7b








FIG.13




FIG.12




FIG. 12b




FIG. 13a








FIG. 12a






FIG. 18




FIG. 19










FIG. 20a FIG. 20b FIG. 20c FIG. 20d








FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 23a




FIG. 24a




FIG. 27




FIG. 28a




FIG. 28b




FIG. 28c



FIG. 29a




FIG. 29b




FIG. 29c




FIG. 29d




FIG. 30a




FIG. 30b



FIG. 30c



FIG. 30d




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 38




FIG. 39




FIG. 37




FIG. 38a




FIG. 37a




FIG. 39a




FIG. 40




FIG. 40a







FIG. 4I






FIG. 47




FIG. 46a




FIG. 46b




FIG. 46c




FIG. 45




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 54




FIG. 53




FIG. 52






FIG. 5d

FIG. 55e




FIG. 55a

FIG. 55b








FIG 55c




F1658A



F1658B








Fig 60a




Fig 60b




Fig 60c






Fig 60d

Superior Products



Handwritten signature








FIG. 110
63


FLOW CONTROL FOR
EASY OPENING POUCHES
PARTICULARLY FOR VERY
LOW VISCOSITY FLUIDS
EG. SOY SAUCE, SKIM
MILK, WATER, ALCOHOL
SOLVENTS ETC. ETC.

COMPRISED OF AT LEAST
ONE SEAL TO BLOCK THE
RATE OF PRODUCT FLOW FROM THE
CONTAINMENT POCKET TO
THE OUTLET HOLE,






Sanford Palmer
Mar. 10, 1998.





ENG. R. R. R. R. R.

SEQUENTIAL FABRICATION DIAGRAMS FOR REDMOND TUBES

FIGURE 71 FIGURE 72





INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/31872

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65D75/58

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 27043 A (REDMOND) 31 July 1997 (1997-07-31)	1-6
A	the whole document	13-15
X	DE 75 33 999 U (4P VERPACKUNGEN) 26 May 1977 (1977-05-26) page 4, line 1 - line 21; figures	1
X	US 5 826 737 A (ZAKENSBERG) 27 October 1998 (1998-10-27) column 3, line 4 - line 39; figures	1,2,5,6
X	EP 0 322 980 A (CHEMISCHE INDUSTRIE FILOFORM) 5 July 1989 (1989-07-05) column 2, line 43 - column 4, line 12; figures	1

	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

14 March 2001

Date of mailing of the international search report

23/03/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Newell, P

INTERNATIONAL SEARCH REPORT

Intel inal Application No

PCI/US 00/31872

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 1 592 560 A (LIBIT) 8 July 1981 (1981-07-08) page 4, line 27 -page 5, line 38; figures 22,23 -----	2-4
A	US 3 788 549 A (OSTROWSKY) 29 January 1974 (1974-01-29) column 1, line 41 -column 3, line 6; figures -----	2-4,15
A	DE 93 06 584 U (STERN) 17 June 1993 (1993-06-17) page 3, line 1 - line 20; figures -----	7-14
A	US 5 779 110 A (BROWN) 14 July 1998 (1998-07-14) column 5, line 19 -column 6, line 63; figures 2,5 -----	15

INTERNATIONAL SEARCH REPORT

information on patent family members

Int. Application No

PCT/US 00/31872

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9727043 A	31-07-1997	AU 728169 B AU 1838197 A BR 9710943 A CA 2243962 A CN 1213337 A EP 0880435 A PL 328201 A SK 99998 A TR 9801435 T US 6062413 A CA 2243660 A EP 0918697 A TR 9801476 T US 6085942 A	04-01-2001 20-08-1997 24-10-2000 31-07-1997 07-04-1999 02-12-1998 18-01-1999 11-02-1999 21-05-1999 16-05-2000 07-08-1997 02-06-1999 21-05-1999 11-07-2000
DE 7533999 U	26-05-1977	NONE	
US 5826737 A	27-10-1998	AU 2274597 A WO 9729975 A	02-09-1997 21-08-1997
EP 322980 A	05-07-1989	NL 8703114 A DE 3872860 A DE 3872860 T ES 2032954 T US 4946040 A	17-07-1989 20-08-1992 28-01-1993 01-03-1993 07-08-1990
GB 1592560 A	08-07-1981	NONE	
US 3788549 A	29-01-1974	NONE	
DE 9306584 U	17-06-1993	NONE	
US 5779110 A	14-07-1998	US 5400912 A	28-03-1995