



US 20190160371A1

(19) **United States**(12) **Patent Application Publication**
Grauzer et al.(10) **Pub. No.: US 2019/0160371 A1**(43) **Pub. Date: May 30, 2019**(54) **PLAYING CARD SHUFFLERS INCLUDING
SHUFFLER SUPPORTS AND RELATED
METHODS**(71) Applicant: **Bally Gaming, Inc.**, Las Vegas, NV
(US)(72) Inventors: **Attila Grauzer**, Las Vegas, NV (US);
Oliver M. Schubert, Las Vegas, NV
(US); **James V. Kelly**, Las Vegas, NV
(US); **James B. Stasson**, Chaska, MN
(US); **Feraidoon Bourbour**, Eden
Prairie, MN (US); **Paul K. Scheper**,
Bloomington, MN (US)(21) Appl. No.: **16/264,166**(22) Filed: **Jan. 31, 2019****Related U.S. Application Data**(63) Continuation of application No. 14/050,102, filed on
Oct. 9, 2013, which is a continuation of application


No. 13/219,360, filed on Aug. 26, 2011, now Pat. No.
8,556,263, which is a continuation of application No.
12/725,245, filed on Mar. 16, 2010, now Pat. No.
8,025,294, which is a continuation of application No.
10/623,223, filed on Jul. 17, 2003, now Pat. No.
7,677,565, which is a continuation-in-part of appli-
cation No. 10/261,166, filed on Sep. 27, 2002, now
Pat. No. 7,036,818.

Publication Classification

(51) **Int. Cl.**
A63F 1/12 (2006.01)
(52) **U.S. Cl.**
CPC **A63F 1/12** (2013.01)

(57) **ABSTRACT**

A device for forming a random set of playing cards. The device may include a card receiving area for receiving an initial set of playing cards, a randomizing system for randomizing an order of the initial set of playing cards, and a card collection surface in a card collection area for receiving randomized playing cards.








Fig. 2








Fig. 4




Fig. 5

Fig. 6







Fig. 7










Fig. 10

PLAYING CARD SHUFFLERS INCLUDING SHUFFLER SUPPORTS AND RELATED METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 14/050,102, filed Oct. 9, 2013, pending, which is a continuation of U.S. patent application Ser. No. 13/219,360 filed Aug. 26, 2011, now U.S. Pat. No. 8,556,263, issued Oct. 15, 2013, which, in turn, is a continuation of U.S. patent application Ser. No. 12/725,245, filed Mar. 16, 2010, now U.S. Pat. No. 8,025,294, issued Sep. 27, 2011, which, in turn, is a continuation of U.S. patent application Ser. No. 10/623,223, filed Jul. 17, 2003, now U.S. Pat. No. 7,677,565, issued Mar. 16, 2010, which, in turn, is a continuation-in-part of U.S. patent application Ser. No. 10/261,166, filed Sep. 27, 2002, now U.S. Pat. No. 7,036,818, issued May 6, 2006, the disclosure of each of which is hereby incorporated herein in its entirety by this reference.

[0002] The subject matter of this application is related to co-pending U.S. patent application Ser. No. 14/667,551, filed Mar. 24, 2015, and to co-pending U.S. patent application Ser. No. 14/748,068, filed Jun. 23, 2015, pending.

TECHNICAL FIELD

[0003] This invention relates to a shuffling and sorting apparatus for providing randomly arranged articles and especially to the shuffling of playing cards for gaming uses. The invention also relates to a method and apparatus for providing randomly shuffled deck(s) of cards in a rapid and efficient manner and a capability of automatically calibrating the apparatus for various card sizes, card thicknesses, and for initial setup and having card reading capability for providing information on card rank and/or card suit on cards within the shuffler. The invention also relates to a device that can verify a set of cards (one or more decks) in a rapid non-randomizing event.

BACKGROUND

[0004] In the gaming industry, certain games require that batches of randomly shuffled cards be provided to players and sometimes to dealers in live card games. It is important that the cards are shuffled thoroughly and randomly to prevent players from having an advantage by knowing the position of specific cards or groups of cards in the final arrangement of cards delivered in the play of the game. At the same time, it is advantageous to have the deck(s) shuffled in a very short period of time so that there is minimal downtime in the play of the game.

[0005] Breeding et al., U.S. Pat. Nos. 6,139,014 and 6,068,258 (assigned to Shuffle Master, Inc.) describe a machine for shuffling multiple decks of playing cards in a batch-type process. The device includes a first vertically extending magazine for holding a stack of unshuffled playing cards, and second and third vertically extending magazines each for holding a stack of cards, the second and third magazines being horizontally spaced from and adjacent to the first magazine. A first card mover is positioned at the top of the first magazine for moving cards from the top of the stack of cards in the first magazine to the second and third magazines to cut the stack of unshuffled playing cards into two unshuffled stacks. Second and third card movers are at

the top of the second and third magazines, respectively, for randomly moving cards from the top of the stack of cards in the second and third magazines, respectively, back to the first magazine, thereby interleaving the cards to form a vertically registered stack of shuffled cards in the first magazine. Elevators are provided in the magazines to bring the cards into contact with the card movers. This shuffler design is currently marketed under the name MD1® shuffler and MD1.1™ shuffler in the United States and abroad.

[0006] Sines et al., U.S. Pat. No. 6,019,368 describes a playing card shuffler having an unshuffled stack holder that holds an in-feed array of playing cards. One or more ejectors are mounted adjacent the unshuffled stack holder to eject cards from the in-feed array at various random positions. Multiple ejectors are preferably mounted on a movable carriage. Extractors are advantageously used to assist in removing playing cards from the in-feed array. Removal resistors are used to provide counteracting forces resisting displacement of cards, to thereby provide more selective ejection of cards from the in-feed array. The automated playing card shuffler comprises a frame; an unshuffled stack holder for holding an unshuffled array of playing cards in a stacked configuration with adjacent cards in physical contact with each other and forming an unshuffled stack; a shuffled array receiver for holding a shuffled array of playing cards; at least one ejector for ejecting playing cards located at different positions within the unshuffled stack; and a drive which is controllable to achieve a plurality of different relative positions between the unshuffled stack holder and the at least one ejector. This shuffler design is currently marketed under the name RANDOM EJECTION SHUFFLER™.

[0007] Grauzer et al., U.S. Pat. No. 6,149,154 (assigned to Shuffle Master, Inc.) describes an apparatus for moving playing cards from a first group of cards into plural groups, each of the plural groups containing a random arrangement of cards, the apparatus comprising: a card receiver for receiving the first group of unshuffled cards; a single stack of card receiving compartments generally adjacent to the card receiver, the stack generally adjacent to and movable with respect to the first group of cards; and a drive mechanism that moves the stack by means of translation relative to the first group of unshuffled cards; a card moving mechanism between the card receiver and the stack; and a processing unit that controls the card moving mechanism and the drive mechanism so that a selected quantity of cards is moved into a selected number of compartments. This shuffler is currently marketed under the name ACE® shuffler in the United States and abroad.

[0008] Grauzer et al., U.S. Pat. No. 6,254,096 (assigned to Shuffle Master, Inc.) describes an apparatus for continuously shuffling playing cards, the apparatus comprising: a card receiver for receiving a first group of cards; a single stack of card receiving compartments generally adjacent to the card receiver, the stack generally vertically movable, wherein the compartments translate substantially vertically, and means for moving the stack; a card moving mechanism between the card receiver and the stack; a processing unit that controls the card moving mechanism and the means for moving the stack so that cards placed in the card receiver are moved into selected compartments; a second card receiver for receiving cards from the compartments; and a second card moving mechanism between the compartments and the second card receiver for moving cards from the compartments to the

second card receiver. This shuffler design is marketed under the name KING® shuffler in the United States and abroad.

[0009] Johnson et al., U.S. Pat. No. 5,944,310 describes a card handling apparatus comprising: a loading station for receiving cards to be shuffled; a chamber to receive a main stack of cards; delivery means for delivering individual cards from the loading station to the chamber; a dispensing station to dispense individual cards for a card game; transfer means for transferring a lowermost card from the main stack to the dispensing station; and a dispensing sensor for sensing one of the presence and absence of a card in the dispensing station. The dispensing sensor is coupled to the transfer means to cause a transfer of a card to the dispensing station when an absence of a card in the dispensing station is sensed by the dispensing sensor. Individual cards delivered from the loading station are randomly inserted by an insertion means into different randomly selected positions in the main stack to obtain a randomly shuffled main stack from which cards are individually dispensed. The insertion means includes vertically adjustable gripping means to separate the main stack into two spaced apart substacks to enable insertion of a card between the substacks by the insertion means. The gripping means is vertically positionable along the edges of the main stack. After gripping, the top portion of the stack is lifted, forming two substacks. At this time, a gap is created between the stacks. This shuffler is marketed under the name QUICKDRAW™ shuffler in the United States and abroad.

[0010] Similarly, Johnson et al., U.S. Pat. No. 5,683,085 describes an apparatus for shuffling or handling a batch of cards including a chamber in which a main stack of cards is supported, a loading station for holding a secondary stack of cards, and a card separating mechanism for separating cards at a series of positions along the main stack. The separating mechanism allows the introduction of cards from the secondary stack into the main stack at those positions. The separating mechanism grips cards at the series of positions along the stack and lifts those cards at and above the separation mechanism to define spaces in the main stack for introduction of cards from the secondary stack.

[0011] Sines et al., U.S. Pat. No. 5,676,372 describes an automated playing card shuffler, comprising: a frame; an unshuffled stack holder for holding an unshuffled stack of playing cards; a shuffled stack receiver for holding a shuffled stack of playing cards; at least one ejector carriage mounted adjacent to the unshuffled stack holder, the at least one ejector carriage and the unshuffled stack holder mounted to provide relative movement between the unshuffled stack holder and the at least one ejector carriage; a plurality of ejectors mounted upon the at least one ejector carriage adjacent the unshuffled stack holder for ejecting playing cards from the unshuffled stack, the ejecting occurring at various random positions along the unshuffled stack.

[0012] Johnson et al., U.S. Pat. No. 6,267,248 describes an apparatus for arranging playing cards in a desired order, the apparatus including: a housing; a sensor to sense playing cards prior to arranging; a feeder for feeding the playing cards sequentially past the sensor; a storage assembly having a plurality of storage locations in which playing cards may be arranged in groups in a desired order, wherein the storage assembly is adapted for movement in at least two directions during shuffling; a selectively programmable computer coupled to the sensor and to the storage assembly to assemble in the storage assembly groups of playing cards in a desired order; a delivery mechanism for selectively deliv-

ering playing cards located in selected storage locations of the storage assembly; and a collector for collecting arranged groups of playing cards. The storage assembly in one example of the invention is a carousel containing a plurality of card storage compartments. The device describes card value reading capability and irregular (e.g., missing or extra) card indication.

[0013] Grauzer et al., U.S. Pat. No. 6,651,981, describes a device for forming a random set of playing cards including a top surface and a bottom surface, and a card receiving area for receiving an initial set of playing cards. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is located in a card collection area for receiving randomized playing cards, the collection surface receiving cards so that all cards are received below the top surface of the device. An elevator is provided for raising the collection surface so that at least some randomized cards are elevated at least to the top surface of the device. A system for picking up segments of stacks and inserting cards into a gap created by lifting the stack is described.

[0014] McCrea, Jr., U.S. Pat. No. 5,605,334, describes a secure game table system for monitoring each hand in a progressive live card game. The progressive live card game has at least one deck with a predetermined number of cards, the secure game table system having players at a plurality of player positions and a dealer at a dealer position. The secure game table system comprises: a shoe for holding each card from at least one deck before being dealt by the dealer in the hand, the shoe having a detector for reading at least the value and the suit of each card, the detector issuing a signal corresponding at least to the value and suit for each card. A card-mixing system may be combined or associated with the card-reading shoe. A progressive bet sensor is located near each of the plurality of player positions for sensing the presence of a progressive bet. When the progressive bet is sensed, the progressive bet sensor issues a signal corresponding to the presence of the progressive bet. A card sensor located near each player position and the dealer position issues a signal when a card in the hand is received at the card sensor. A game control has a memory and is receptive of progressive bet signals from the progressive bet sensor at each player position for storing in memory which player positions placed a progressive bet. The game control is receptive of value and suit signals from the detector in the shoe for storing in memory at least the value and suit of each card dealt from the shoe in the hand. The game control is receptive of card-received signals from card sensors at each player position and the dealer position for correlating in memory each card dealt from the shoe in game sequence to each card received at a player position having a progressive bet sensed. The specification indicates that FIG. 16 is an illustration setting forth the addition of a single card reader to the automatic shuffler of U.S. Pat. No. 5,356,145 to Verschoor. In FIGS. 16 and 17 is set forth another embodiment of the secure shuffler of the U.S. Pat. No. 5,605,334, based upon the shuffler illustrated in FIGS. 12-16 of U.S. Pat. No. 5,356,145. The shuffler may be mounted on a base in which is contained a camera with a lens or lenses and the camera may be embedded in a base of the shuffler.

[0015] Block et al., U.S. Pat. No. 6,361,044, describes a top of a card table with a card dispensing hole therethrough and an arcuate edge covered by a transparent dome-shaped cover. A dealer position is centrally located on the tabletop. Multiple player stations are evenly spaced along the arcuate

edge. A rotatable card placement assembly includes an extendable arm that is connected to a card carrier that is operable to carry a card. In response to signals from a computer, the rotation of the assembly and the extension of the arm cause the card carrier to carry the card from the card dispensing hole to either the dealer position or any of the player positions. The card carries a barcode identification thereon. A barcode reader of the card carrier provides a signal representation of the identification of the card to the computer.

[0016] Stardust et al., U.S. Pat. No. 6,403,908, describes an automated method and apparatus for sequencing and/or inspecting decks of playing cards. The method and apparatus utilize pattern recognition technology or other image comparison technology to compare one or more images of a card with memory containing known images of a complete deck of playing cards to identify each card as it passes through the apparatus. Once the card is identified, it is temporarily stored in a location corresponding to or identified according to its position in a properly sequenced deck of playing cards. Once a full set of cards has been stored, the cards are released in proper sequence to a completed deck hopper. The method and apparatus also include an operator interface capable of displaying a magnified version of potential defects or problem areas contained on a card which may be then viewed by the operator on a monitor or screen and either accepted or rejected via operator input. The device is also capable of providing an overall wear rating for each deck of playing cards.

[0017] Many other patents provide for card reading capability in different physical manners, at different locations, and in different types of apparatus, from card reading shoes, to card reading racks, to table security control systems, such as disclosed in U.S. Pat. No. 4,667,959 (Pfeiffer et al.), U.S. Pat. No. 6,460,848 (Soltys et al., assigned to MindPlay LLC), U.S. Pat. No. 6,270,404 (Sines et al., automated system), U.S. Pat. No. 6,217,447 (Lofink et al.), U.S. Pat. No. 6,165,069 (Sines et al.), U.S. Pat. No. 5,779,546 (Meissner et al.), U.S. Pat. No. 6,117,012 (McCrea Jr.), U.S. Pat. No. 6,361,044 (Block et al.), U.S. Pat. No. 6,250,632 (Albrecht), U.S. Pat. No. 6,403,908 (Stardust et al.), U.S. Pat. No. 5,681,039 (Miller), U.S. Pat. No. 5,669,816 (Garczynski et al., assigned to Peripheral Dynamics), U.S. Pat. No. 5,722,893 (Hill et al., assigned to Smart Shoes, Inc.), U.S. Pat. No. 5,772,505 (Garczynski et al., assigned to Peripheral Dynamics), U.S. Pat. No. 6,039,650 (Hill, assigned to Smart Shoes, Inc.), U.S. Pat. No. 6,126,166 (Lorson et al., assigned to Advanced Casino Technologies), U.S. Pat. No. 5,941,769 (Order, unassigned), and WO 00/51076 (Purton, assigned to Dolphin Advanced Technologies Pty. Ltd.).

[0018] Although these and other structures are available for the manufacture of playing card shuffling apparatus, new improvements and new designs are desirable. In particular, it would be desirable to provide a batch-style shuffler that is faster, provides random shuffling, is more compact than currently available shuffler designs, and is capable of reading the rank and/or suit of each card.

BRIEF SUMMARY OF THE INVENTION

[0019] A device for forming a set of playing cards in a randomized order is described. The device includes a top surface and a bottom surface, and a card receiving area for receiving an initial set of playing cards. The device is also

capable of reading, recording, positioning and/or comparing information related to card rank, card suit, and specified card combinations. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is located in a card collection area for receiving randomized playing cards, the collection surface receiving cards so that all cards are received below the top surface of the device. An elevator is provided for raising the collection surface so that at least some randomized cards are elevated at least to the top surface of the device. An automatic system is provided in the device for accurately calibrating the vertical position of the collection surface and identifying specific card level positions on stacks of cards placed onto the collection surface. Sensors to identify at least one card level position and support surface positions are used to calibrate the performance of card pickup grippers, platform positions, and card positions on the platform. A calibration routine is performed by the device, and the automated calibration routine ensures a high level of performance of the device and reduces or eliminates the need for initial and periodic manual calibration and for technical maintenance on the device. A camera is provided within the device for reading the values (e.g., suit and rank) of cards, the camera reading values after cards are introduced into the device, before they are collected into a randomized set, and before they are removed. The device may also have an alternative mode, wherein cards are rapidly moved and read, but not shuffled, to verify complete sets of cards.

[0020] A device for forming a random set of playing cards is described. The device includes a top surface and a bottom surface of the device and a receiving area for receiving an initial set of playing cards. A randomizing system is provided for randomizing the initial set of playing cards. A collection surface is provided in a card collection area for receiving randomized playing cards. In one embodiment of the invention, a card feed mechanism individually transfers cards from the receiving area into the card collection area. The device further includes an elevator for raising and lowering the collection surface within the card collection area. At least one card supporting element within the card collection area supports and suspends a randomly determined number of cards within the card collection area. In one example of the invention, a pair of spaced-apart gripping members are provided to grasp the opposite edges of the group of cards being suspended.

[0021] A card insertion point is created in the card collection area beneath the suspended randomly determined group of cards. The card feed mechanism delivers a card into the insertion point. Card values may be read before or during card insertion. The cards are not required to be read as they are being removed from the shuffler (as in a reading head located in a dealer delivery portion of a shuffler), although such an additional reading capability may be added in some constructions (in addition to the internal reading of the rank and/or suit of cards) where there is a dealer card-by-card delivery section.

[0022] Card sensors may be provided to trigger camera activation so that the camera may distribute a single analog or digital snapshot of a card face and the camera does not have to send a steady stream of information. The card sensors (trigger sensors) may initiate or activate the image-taking procedure by the camera by noting a leading edge of a card, a trailing edge of the card, a time frame when the sensor is blocked, or a delayed activation (e.g., the card

triggers an image-taking event to occur after a specified time has elapsed, such as the time expected for a card to move from trigger sensor to the camera focal plane). A leading edge sensor may trigger camera activity when the leading edge of the card has passed over the camera focal point, and the edge then triggers the image-taking event at a time when the symbols are over the camera focal point or focal plane. A trailing edge sensor would trigger the camera event when the trailing edge has passed over the sensor, which is at a measured distance that places the symbols over the camera focal plane.

[0023] An automatic card shuffling device is disclosed. The device includes a microprocessor with memory for controlling the operation of the device. An in-feed compartment is provided for receiving cards to be randomized. In one example of the invention, the lower surface of the in-feed compartment is stationary. In another example of the invention, the lower surface is movable in a vertical direction by means of an elevator. A card moving mechanism moves cards individually from the in-feed compartment into a card mixing compartment. The card mixing compartment includes a plurality of substantially vertical supports and an opening for the passage of cards from the in-feed compartment. In one form of the invention, the opening consists of a slot. The card mixing compartment also includes a movable lower support surface and at least one stationary gripping arm, a lower edge of the gripping arm being proximate to the opening and the gripping arm, the opening allowing for the passage of cards into the card mixing compartment just below the gripped group of cards. The gripping arm is capable of suspending a card or a group of cards of a randomly determined size above the opening. In one example, the opening is a horizontal slot.

[0024] The device preferably includes an integrally formed automated calibration system. One function of the automated calibration system is to identify the vertical position of the elevator support platform relative to a lowermost gripping position of the grippers so that the stack of cards in the card mixing compartment can be separated at a precise location in the stack and so that a specific numbers of cards can be accurately lifted and specific card insert positions can be determined for insertion of cards into the randomizing stack of cards. Another function of the automated calibration system of the present invention is to automatically adjust the position of the grippers to compensate for different card length, width and/or card thicknesses. In one form of the invention, card values are read before or during card insertion. The value of the read card(s) may be stored in memory in the shuffling/randomizing device or sent to a distal memory for storage and/or immediate use.

[0025] Another function of the automated calibration system is to determine the number of incremental movements of elevator stepper motors that corresponds to the thickness of each card. This information is then used to determine a precise location of the elevator in order to form each point of separation in the group of cards during shuffling.

[0026] An elevator is provided for raising and lowering a movable card support surface. In operation, a vertical position of the elevator is randomly selected and the support surface is moved to the selected position. After the gripping arm grasps at least one side of the cards, the elevator lowers, suspending a group of cards, and creating a space (or point of insertion) beneath the gripping arm, wherein a single card

is moved from the in-feed compartment into the space created, thereby randomizing the order of the cards.

[0027] A method of calibrating a shuffling machine prior to and during the randomization of a group of cards is described. The method comprises the steps of placing a group of cards to be randomized into a card in-feed tray and removing a calibration card from the in-feed tray, and placing the card in the card randomizing area, also known as the card collection area. The elevator and grippers are operated until a precise location of the bottommost card that can be gripped is identified. Either before or after this calibration process, the card width is measured, and the grippers are adjusted to put sufficient tension on the cards to suspend the entire group of cards to be shuffled.

[0028] According to the invention, cards are individually fed from the card in-feed tray and delivered into a card collection area. The card collection area has a movable lower surface, and a stationary opening for receiving cards from the in-feed tray. The method includes elevating the movable lower surface to a randomly determined height and grasping at least one edge of a group of cards in the card collection area at a point just above the stationary opening. The method further includes the steps of lowering the movable lower surface to create an opening in a stack of cards formed on the lower surface, the opening located just beneath a lowermost point where the cards are grasped and inserting a card removed from the in-feed tray into the opening.

[0029] A device capable of automatically calibrating is described that is capable of automatically making adjustments to process cards of different dimensions. The device includes a card in-feed tray, a card moving mechanism that transports cards from the in-feed tray into a card collection area; an elevator within the card collection area that raises and lowers the group of fed cards; a device capable of suspending all or part of the fed cards above the card feeder; and a microprocessor that selects the position in the stack where the next card is to be inserted, and instructs the device capable of suspending and the elevator to create a gap, and then instructing the card moving mechanism to insert the card.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] FIG. 1 shows a perspective view of an example of an exterior shell of a shuffling apparatus of the present invention.

[0031] FIG. 2 shows a cutaway side view of internal elements of a shuffling apparatus according to teachings of the present invention.

[0032] FIG. 3 shows a perspective view of an offset card transport mechanism according to an embodiment of the invention.

[0033] FIG. 4 shows a top view of an offset card transport mechanism according to an embodiment of the present invention.

[0034] FIG. 5 shows a cross-sectional view of an embodiment of a picking system with a single or joint belt drive for moving picker elements.

[0035] FIG. 6 shows an elevated perspective view of one embodiment of a shuffling apparatus according to the invention.

[0036] FIG. 7 shows a side cutaway view of one embodiment of a shuffling apparatus according to the invention.

[0037] FIG. 8 shows a perspective view of a second example of an exterior shell of a shuffling apparatus of the present invention.

[0038] FIG. 9 shows a side cutaway view of one embodiment of a shuffling apparatus with card-reading camera available.

[0039] FIG. 10 shows a top cutaway view of another embodiment of a shuffling apparatus with card-reading camera available.

DETAILED DESCRIPTION

[0040] An automatic shuffling device is described for forming a randomly arranged set of playing cards. One embodiment of the device of the present invention shuffles between one and eight or more decks of cards (standard deck or decks of 52 cards each or 52 cards plus one or two jokers) and is particularly well suited for providing randomized batches of cards for games such as single-deck blackjack, poker, double-deck blackjack, and multi-deck blackjack, for example. Another embodiment of the invention is suitable for shuffling either a single deck or two decks of cards.

[0041] The device includes a top surface and a bottom surface, a card receiving area for receiving an initial set of playing cards to be randomized and a randomizing system for randomizing an order of the initial set of playing cards. The device further includes a card collection area and a card collection surface within the card collection area for receiving randomized playing cards, the collection surface receiving cards in a manner such that all cards are inserted into the collection area below the top surface of the device. An elevator is provided for raising and lowering the collection surface during shuffling, and elevating the shuffled (alternatively referred to as “randomized”) group of cards at least as high as the top surface of the device after shuffling (that is, the lowest card in the shuffled group of cards is raised to a level where it may be easily and manually removed from that level, preferably with the lowest card being level with or above a plane defining the top surface of the device). A card suspension mechanism, such as a pair of oppositely spaced grippers grasps some or all of the cards on the card collection surface. The elevator is lowered, creating a gap or point of insertion for the next card to be fed. Once shuffling is complete, the cards are elevated so that they can be removed by an attendant or dealer and used for dealing. While cards are being dealt, a second group of cards is being randomized. The use of two groups of cards eliminates any waiting on the part of the dealer or the casino patrons between rounds of play.

[0042] For example, because the device is able to transport cards rapidly and read card values (e.g., suit and rank, or special values, such as wild cards, jokers, etc.), the device may be used as a deck verification system as well as card shuffler/randomizer. There are a number of modes by which this can be practiced. The least complicated, but less preferred method is to have the device shuffle or randomize a complete set of cards and have each and all of the cards of the set read and compared to the expected content (e.g., in a look-up table for a regular or special deck, a number of regular or special decks, and the like). By comparing the read values to the stored values, the set of cards can be verified. The stored values can be provided from a previous reading of the set of cards (e.g., during an earlier shuffle/randomization) or from a separate reading of the cards from a separate device, such as a card reading tray (e.g., U.S. Pat.

No. 6,460,848), or a dealing shoe (e.g., U.S. Pat. Nos. 6,403,908; 5,605,334; 6,039,650; and 5,722,893). Comparison to the earlier stored values can be performed in the microprocessor in the shuffling device, or the information can be transferred from a port to a distal microprocessor (e.g., central computer) that also has the stored values, or at both locations.

[0043] A more preferred method would be to activate a special mode within the shuffling device wherein cards would be removed one at a time from the card in-feed tray of the shuffler (possibly in an order that had already been read from another device or by the shuffling device in an earlier reading of the cards), and there is a special support plate that can receive the entire set of cards without having to create openings for card insertion. For example, the grippers could be deactivated and all cards could be transferred in order onto the support plate. This can speed up the card set validation as compared to an actual shuffling or randomization process. In this fast verification mode, the camera may operate with single, quick shot images of each card or provide the data in a steady stream, since there would be less data (because of the faster movement of the cards and set of cards) as compared to a shuffling procedure. The data stream in the fast verification mode would not be as excessive as in a shuffling mode. Cards could be read when stationary or in motion, in the card in-feed tray or during transfer onto the support plate.

[0044] There are a number of special features that combine to make the present invention a significant advance over previously described card shuffling systems and card shuffling processes. Individual features that constitute an advance, alone or in combination with other features, include a system for automatically calibrating and inspecting the position and performance of an elevator for moving the final set of randomized cards upwardly so that the stack is accessible to the dealer or attendant. In one example of the invention, the elevator elevates the group of cards to the playing table surface. The same elevator advantageously assists in accomplishing shuffling within the card collection and/or mixing area.

[0045] The card collection area, in another example of the invention, has a plurality of vertical supports (e.g., two or three walls, or four walls with a manually accessible area where the lowest card may be gripped), and a movable lower surface. The elevator supports this movable lower surface (also referred to herein as the collection surface) and causes the surface to move back and forth (relatively up and down) in a substantially vertical direction. One function of the movement of the elevator (during the shuffling or randomizing sequence) is to position a stack of cards within the card collection area so that a card or cards can be inserted into the stack in a specifically selected or randomly selected precise position within the stack to randomize, organize, or arrange the cards in a desired order, such as “pack order” for inspection (particularly after reading the suit and rank of cards), or a randomized order so that the cards are shuffled into a set of cards that can be dealt to players. The insertion of cards may be performed in a number of ways, such as by lifting or by dropping a section of the stack and inserting one or more (and preferably just one) cards into the gap, by positioning the stack near a card insertion position and inserting one or more cards into the stack, or inserting a wedge-like element or blade between cards in the stack to elevate a portion of the stack where card(s) may be inserted

(as described in Breeding et al., U.S. Pat. No. 5,695,189 (assigned to Shuffle Master, Inc.), which is incorporated herein by reference).

[0046] In a preferred mode of operation of the shuffler of the present invention, a picking, gripping, or separating system is provided for suspending segments of the stack of cards present in the card collection area, creating an opening in the group of cards so that a card or cards can be inserted in specific locations relative to other cards in the deck. A variant of this system is described in U.S. patent application Ser. No. 09/967,502, filed Jan. 8, 2002, now U.S. Pat. No. 6,651,981, issued Nov. 25, 2003 (assigned to Shuffle Master, Inc.).

[0047] According to that invention, the picking, gripping or card suspending system is fixed in the vertical direction. By randomly selecting a vertical position for the movable base of the card receiving area prior to picking, the location of an opening created in the stack of cards by gripping a portion of the cards and lowering another portion of the cards below the gripping area is varied, with random insertion of cards into these openings causing randomization of the cards.

[0048] Offset rollers are the preferred mechanism provided for moving the individual cards from the card receiving area into the card collection area, although air jets, belts, injection plates, injection blades, and the like, may also be used for moving individual cards or small numbers of cards (e.g., one, two, three, four, or five cards) into the card receiving area. A stack stabilizing area is provided, in one example of the invention, for receiving an elevated final set of cards lifted from the card collection area. This stack stabilization area should be positioned or positionable above the top of the device or should begin at the top of the device. In another example of the invention, the elevator itself is equipped with a stack stabilizing structure that is lowered into the inside of the shuffler prior to the randomization of cards. In one embodiment later described in greater detail, a delivery or elevator platform provides its own card stabilization area or, in conjunction with an elevator drive arm, provides such a card stabilization area. In one example of the invention, a single belt drive is provided for driving two spaced-apart and opposed, vertically disposed picking elements in a card segment picking system. The picking elements are vertically disposed along the path of movement of the collection area of cards in the collection shaft, and are horizontally disposed or opposed with respect to each other. A microprocessor is provided that employs a random number generator to identify or create an intended (including random) distribution of an initial set of cards in the card receiving area at the conclusion of shuffling. The microprocessor executes movement of elements in the shuffling apparatus, including the opposed picking elements and the elevator, to effect placement of each card into spaces in the stack created by the shuffling apparatus, and a randomized set of cards is rapidly formed. That microprocessor (in the shuffling device or in an associated game device) or a separate or parallel microprocessor is used to direct the calibration steps. In one example of the invention, the picking elements move horizontally to grasp opposite edges of a group of cards. Other suspension systems are contemplated, such as inserting a flat member between the cards above the point of separation.

[0049] The individual and combined elements of the invention will be described in detail, after a more general

description of the invention is provided. A first general description of the invention is a device for forming a randomized set of playing cards comprising: a top surface and a bottom surface of the device; a receiving area for an initial set of playing cards; a randomizing system for randomizing the order of the initial set of playing cards; a collection surface in a card collection area for receiving the randomized playing cards; an elevator for raising the collection surface within the card collection area; and at least one card supporting element within the card collection area that is horizontally fixed with respect to the vertical. The card supporting element will support and suspend a precise number of a randomly determined number of cards within the card collection area to create a gap or space within the stack of cards within the collection area that is a card insertion point. The card insertion point or gap is created in the card collection area just below the lowermost portion of the card supporting element or elements. The card supporting elements then support a next group of cards, and the elevator beneath the card collection area is lowered, lowering a remaining group of cards and creating a gap.

[0050] The device may have one or more card supporting elements comprising at least one card supporting element vertically disposed on at least one side of the card collection area. In the alternative, the card supporting elements include at least two opposed supporting elements, such as flexible or soft (e.g., polymeric, elastomer, rubber or rubber-coated) gripping elements, that can move inwardly along a horizontal plane within the card collection area to contact and support the opposite edges of at least a portion of the stack, substack, or group of cards. Alternatively, a horizontally disposed flat member, such as a pair of forks or a flat plate, may be inserted between the cards, so that when the elevator is lowered, an insertion point or gap is formed. A "substack" may be defined as all cards within the collection area at or above a randomly selected card or position in the stack within the card collection area. The device preferably has a microprocessor communicatively connected to the device. The microprocessor in one example of the invention is programmed to determine a distance that the card supporting surface must be vertically moved in order to position each card in the desired order within the stack. In one example of the invention, cards fed into the card collection area may be placed anywhere in the stack, including the top or bottom position. This flexibility advantageously allows for a more random shuffle and avoids "dead" areas within the collected stack of cards.

[0051] The device of the present invention advantageously senses the length or width of the cards and adjusts the horizontal distance between the gripping arms so that cards of varying lengths or widths can be suspended. Whether the width or length is sensed depends on the designer's selected location of the grippers within the card collection area.

[0052] In one example of the invention, the microprocessor instructs the device to feed a first card into the card collection area and to grip the card at a width representing the width of a standard group of cards. If the sensors sense that a card is suspended, no adjustments to a horizontal spacing between gripping arms is necessary. If no suspended cards are sensed, the microprocessor instructs an adjustable gripping support mechanism to move a preselected distance and the gripping and sensing process is repeated. When the final adjustment has been made, cards are suspended and their presence is sensed. The microprocessor then retains

this gripping mechanism distance setting. Alternatively, when the processor instructs the grippers to suspend one or more cards and no suspended cards are sensed, the adjustment sequence is activated. This entire process will be described in further detail herein.

[0053] The microprocessor is communicatively connected to the device and is most preferably located within the exterior shell of the device. The microprocessor may be programmed to lower the card collection surface within the card collection area after the at least one card supporting element has contacted and supported cards suspending a group of cards within the card collection area, creating two vertically spaced substacks of cards, one suspended, separated by a gap or opening between the cards. Recognition of the presence of suspended and/or supported card(s) within the card collection area may be provided by sensors that are capable of sensing the presence of card(s) within the area by physical (e.g., weight), mechanical (e.g., pressure), electrical (e.g., resistance or conductance), optical (e.g., reflective, opacification, reading) or other sensing. The microprocessor may direct movement of one or more individual cards into the gap created between the two segments (upper and lower) of cards. The microprocessor may be programmed to randomly determine a distance that the card supporting surface must be vertically moved in order to position at least one specific card. This method, including measurement of card thickness, will be described in more detail below. In the alternative, the microprocessor may be programmed to select a specific card position below or above a certain card, creating the gap. When the card supporting element moves to contact cards within the card collection area, and the elevator moves the card supporting surface downwardly, a gap is created for receiving the next card.

[0054] The elevator operates in a unique manner to position cards relative to the pickers or grippers within the shuffling chamber. This unique operation offers significant benefits that remove the need for human intervention in the setup or continuing operation of the shuffling device. Among the alternative and optional unique features of the operation of the shuffling device of the present invention are included the following sequence of events. These events need not necessarily be combined within a single process to represent inventive steps, as individual steps and combinations of two or more steps may be used to define inventive processes.

[0055] In order to calibrate the shuffling device of the present invention to operate for a particular card size, a calibration set of cards comprising at least one card (usually one, although two, three, four or more cards could be used) is inserted into the shuffling chamber prior to shuffling. The elevator base plate defining the base of the shuffling chamber moves the calibration set of cards to the position within the chamber approximating a position within the gripper (not necessarily at a level or equal position with the bottom of the grippers), and the grippers move inwardly (towards opposed edges of the cards) and attempts to grip the card(s). If the grippers grip the card(s), a sensor identifies either that the card(s) have been gripped by the grippers or that the card(s) remain on the collection surface of the elevator (depending upon the position of the sensors). If there is no indication that a card(s) has been gripped, then the grippers move inwardly toward each other horizontally a set number of steps (e.g., "steps" being units of movement, as in movement through a microstepping motor or unit of movement through any other motivating system), and the process

is repeated. This gripping, sensing and moving sequence is repeated until the sensor(s) sense that a card has been lifted off the support plate and/or is supported in the grippers. The microprocessor identifies a fixed progression of steps of predetermined sizes that are used in this gripping calibration as well as the position that accomplished the gripping. These determinations of card dimensions, gripping positions and elevator position may be done independently and/or in concert.

[0056] It is logical to proceed with the gripping identification first. The grippers move inwardly a predetermined distance, initially and in repeated testing. For example, in the first gripping attempt, the grippers may move in 10 or 15 or other number of steps. A larger number than one step or unit is initially desirable to ensure that a rapid first grip is attained. After the first grip of a card(s) is sensed, then the microprocessor will widen the grip by fixed numbers of steps (here single steps may be used), with the widening occurring until no card is gripped. Once no card is gripped, a sufficient number of steps are added to the gripper movement to ensure gripping and even slight elastic bending of the card by the grippers so that more cards can be supported and so that cards will not slip. This may be 1, 2, 4, 5, 8, 10, 12, 15, or any other number of steps, to ensure that secure gripping is effected. This procedure defines the "gripping" and "card release" position of the grippers for a particular group of cards. The microprocessor records the stepper motor positions corresponding to the gripper positions and uses this information to position the grippers during shuffling.

[0057] Now the platform offset is to be set (as opposed to the gripper offset positioning). The elevator is put in a base or home position, which may be the position of the elevator (the height of the elevator) at the lowest position possible, or at a position below a framing support at the base of the collection chamber or some other predetermined position. The elevator is then raised in a series of a number of steps (again, in the initial gripping attempt, using larger numbers of steps is desirable to speed up the overall process, while during a more refined positioned identification/calibration sequence, smaller numbers of steps, even single steps, would be used) and the grippers are activated after each step, until the card is caught by the gripper for the first time. The number of steps moved each time for the first gripping action is preferably larger than single steps to assure that this card will be gripped at the lowermost edge of the grippers. Again, this may be 1, 2, 3, 4, 5, 8, 10, 15, etc., steps (or any number in between, or a larger number of steps). Once the calibration card(s) is gripped, this is an indication that the platform has now raised the cards to at least the bottom of the grippers. Once gripping has occurred, the elevator is then lowered by a smaller number of incremental stop positions (a finer adjustment) and a new position evaluated as to whether the grippers would then grip the calibration card. The process is repeated until the calibration card is just below the lowermost gripping position. This position is then recorded in memory. The repositioning is accomplished by lowering the elevator and support plate to a position well below the grippers and then raising the plate to a position a predetermined number of steps lower than the last position where the card(s) was gripped, and sensing whether the card was gripped at the new position. Depending upon the arrangement of the sensors, plates, and cards, it is possible to merely ungrasp the card, then lower the elevator one or

more predetermined number of steps, then attempt to regrip the card, and sense whether the card has been gripped.

[0058] Once the card has been lowered just below the gripper, a second calibration card is added to the card collection surface. The elevator position is registered and/or recorded. The precision of the system enables options in the practice of the invention, such as the following. After a single card has been gripped, and a position determined where that single card will not be gripped with a slightly lowered elevator position (e.g., movement downward, which may be anywhere from 2 to 20 steps or more), another calibration card or cards may then be added to the shuffling chamber on top of the calibration card(s). The elevator and grippers may then be exercised, with the elevator moving single steps until the sensor(s) determine that one card has been gripped and lifted off the support plate and another card(s) remains on the support plate. To this position is added a number of steps equal to a card's thickness, and this final position is defined as the platform offset and identifies the position where the bottommost card would be lifted off of the support plate.

[0059] Prior to inserting the first calibration card, the elevator is raised to a predetermined sensed position in the card collection area, and that position or elevation is recorded in memory. After the first group of cards are inserted and randomized, the procedure is repeated, this time either measuring the height of the elevator when the top card in the stack was at the original height of the elevator, or measuring a new height of the top of the stack of cards when the elevator returns to that recorded position. The difference in distances represents the thickness of the deck or group of cards. As each card is fed into the card collection surface, the number of cards is counted and this number is recorded. The processor uses both pieces of information to calculate an average card's thickness, and to associate the number of motor steps to one card thickness. This information is then used in positioning the elevator for precise placement in the next shuffle.

[0060] At this point, all of the remaining cards in the deck(s) may be added to the shuffling chamber (either directly, or into the card receiving chamber and then into the card shuffling chamber). The system may then check on the efficiency of the grippers by raising the deck to a level where all cards should be gripped, the grippers grip the entire deck (one, two, three or more times), and the elevator lowered. If no cards are dropped in the chamber, the system may proceed to normal shuffling procedures. If the grippers leave a card or if a card falls back into the shuffling chamber, the gripper action may be automatically or manually (by an operator signal) adjusted to provided greater force on the cards, and the deck lift procedure is then attempted again, until the entire deck is lifted. The entire calibration process may have to be repeated if there is any uncorrectable failure in a complete deck lift test procedure. The shuffler preferably includes a multiple-segment information display as described in Breeding et al., U.S. Pat. No. 6,325,373, titled "Method and Apparatus for Automatically Cutting and Shuffling Playing Cards," the disclosure of which is herein incorporated by reference. The display may then indicate information relating to the state of the shuffler, such as the indication "AUTO ADJUST COMPLETE" and the operator may proceed with normal shuffling procedures, with or without further instruction on the display panel.

[0061] The calibration process described above is preferably repeated periodically to compensate for swelling and bending of the cards. In a preferred form of the invention, two cards are fed into the device and separated prior to each shuffle to verify that the device is still properly calibrated. If the cards do not separate, the calibration sequence is repeated. The device of the present invention includes a jam recovery feature similar to that described in Breeding et al., U.S. Pat. No. 6,325,373. However, upon the fourth failure (or other number of failures) to recover from a jam, one or more of the calibration features described above are automatically activated.

[0062] This element of the total calibration process will thus calibrate the shuffling device in advance of any shuffling procedure with respect to the position of the bottom card (the card touching the elevator base plate or support plate) by moving the elevator up and down, by gripping and regripping the cards to identify a position where no cards are gripped and then a position where only one card is gripped. The other gripping-regripping procedure within the total calibration process will also identify and calibrate the shuffling apparatus with respect to the unique size of cards placed into the shuffling apparatus. Based on the knowledge of how many cards have been inserted into the shuffling chamber in the set (preferably one card and then two cards total), the microprocessor identifies and determines the position of the elevator support plate, the appropriate position of the elevator support plate with respect to the grippers, and the relative height of the number of cards in the set on the elevator card support plate. This information is stored for use with the particular stack of cards to be used in the shuffling process. When subsequent decks are inserted, the operator may optionally indicate that the decks are sufficiently similar that the entire process need not be performed or that the process may be initiated, or the machine may automatically make a check of a single card to determine if it appears to be the same size, and then initiate the shuffling program if the card is identified as the same size.

[0063] Additionally or alternatively, once the calibration set of cards has been first gripped, the grippers release the cards and regrip the cards, measuring any one or more of a) the position of the grippers relative to each other (with one or more of the two opposed grippers moving, the "steps" or other measurable indicator of extent of movement or position of the grippers) is determined and registered for use by the microprocessor; b) the force or tension between the grippers with the calibration set of cards or only one card gripped between the grippers; c) the height of a top card (or the single card) in the calibration set when cards are flexed by the force of the grippers (which may be measured by sensors positions in the shuffling chamber), or any other system may be used that identifies and/or measures a property or condition indicative of the gripping of the cards with a force in a range between a force insufficient to support the weight of the calibration set against slippage and bending the cards to a point where a card might lift off other cards in the calibration set. The calibration distance is typically in a range of between 93% and 99.5% of the width of the cards or, more typically, the length of the cards, as measured by picker movement.

[0064] The positioning, repositioning and gripping of the cards are performed automatically and directed by the microprocessor or an additional microprocessor (there may even be a networked central control computer, but a micro-

processor in the device is preferred). The elevator and the grippers are moved by steps or micro steps by a microstepping motor or other fine-movement control system (e.g., hydraulic system, screw system, geared system, and the like). The use of the automatic process eliminates the need for technicians to set up individual machines, which must be done at regular intervals because of wear on parts or when cards are replaced. As noted, the positioning may be performed with a calibration set as small as a single card. After the automated calibration or position determination has been performed, the microprocessor remembers that position and shuffling can be initiated with the stack of cards from which the calibration cards were taken.

[0065] This calibration or preshuffling protocol may be used in conjunction with any system where an elevator is used, whether with grippers, card inserting devices, injectors, and the like (as described above), and not only the specific apparatus shown in the figures. A similar calibration system for determining specific positions of carousel chambers in a carousel-type shuffling device may also be used, without grippers. The carousel may be rotated and the position of the shelves in the carousel with respect to other functional elements in the device may be determined. For example, card reading devices, card injection components, card removal elements, and card receiving chambers may be calibrated with regard to each other. As is understood by those ordinarily skilled in the art, there may be variations chosen among components, sequences of steps, and types of steps performed, with those changes still reflecting the spirit and scope of the invention disclosed herein.

[0066] In addition, the card collection chamber need not be vertically disposed. The chamber could be angled with respect to the vertical to improve contact between the card edges and the support structure located within the card collection area.

[0067] As noted, this description reflects a detailed description of the preferred practice of the invention with grippers. Alternative systems, such as those with injectors or stack wedges, may also be used with the calibration system of the invention with modifications reflecting the different systems. For example, where the calibration in the preferred embodiment addresses the level of the grippers with respect to cards and the elevator support plate, the system may be translated to calibration of air injectors, wedge lifters, and blade or plate injectors. This is done with an equivalent procedure for identifying the position of a card(s) placed on the support plate. For example, rather than performing repeated tests with a gripper, repeated tests may be performed with an air injector (to see when a card is ejected or injected by its operation), with a blade or plate injector (to see when a card is ejected or injected by its operation), or with a wedge separator with associated card(s) insertion (to see when the stack (e.g., a single card or a number of cards) is raised or when a card may be ejected or injected by its operation with minimum force).

[0068] The device of the present invention is also capable of monitoring card thickness and uses this information to accurately determine the location or position in the stack where separation is to occur. When combined with the ability to read card rank and suit, the device is capable of verifying that all cards are present and verifying the final order of the cards.

[0069] In another embodiment, a first sensor located in the shuffling chamber senses the height of the platform within

the shuffling chamber in its lowermost position prior to the beginning of the randomization process, when no cards are in the shuffling chamber. The sensor could also sense the platform position in any other predetermined or "home" position.

[0070] After randomization, when all cards have been transferred into the shuffling chamber, the platform is returned to this same position, and the same or another sensor located in the shuffling chamber (also referred to herein as the collection chamber) may sense the height of the top card in the stack. The difference between the two measurements represents the thickness of the stack of cards. This is an alternate method of measuring stack thickness.

[0071] Sensors (such as optical sensors, sonic sensors, physical sensors, electrical sensors, and the like, as previously described) sense cards as they are individually fed from the in-feed tray into the shuffling chamber. This information is used by the microprocessor to verify that the expected number of cards is present. In one example of the invention, if cards are missing or extra cards are present, the display will indicate a misdeal and will automatically unload.

[0072] The microprocessor uses the two height measurements and the card count to calculate an average card thickness. This thickness measurement is used to determine at what height the elevator must be in order to separate the stack between any two "target" cards.

[0073] The average card thickness can be recalculated each time the shuffler is activated upon power-up, or according to a schedule, such as every 10 to 30 minutes, with 20-minute intervals as one preferred example.

[0074] The inventors have recognized that deck thickness increases the more the cards are used, as humidity in the air increases, and as cards become worn. Under humid conditions, it might be desirable to check the card thickness more often than every 20 minutes. Under extreme conditions of continuous use and high humidity, it might be desirable to recalculate an average card thickness after the completion of every shuffle.

[0075] A novel method of determining an average card thickness measurement during shuffling is disclosed herein as an invention. The method includes providing a stack of cards, providing a card feeder capable of relative motion between the card feeder and the stack, and determining a home position of the stack platform. The home position indicates a height of the elevator platform when no cards are present in the stacking area. The method further includes feeding cards into the stacking area, counting a number of cards placed into the stacking area as they are fed, sensing a height of a topmost card in the stack when the elevator is returned to the same home position, and computing an average card thickness from the collected information (e.g., stack height divided by the number of cards equals the height per card).

[0076] The average card thickness is advantageously used to determine the position of card grippers used to grasp cards. Upon lowering the platform beneath the grippers, an opening is formed at a precise predetermined location, allowing precise placement of the next card between two "target" cards.

[0077] According to the present invention, a sensor is positioned at a point of insertion into the group of cards in the card collection area. Each time a gap is formed, the sensor verifies that the gap is open, e.g., that no cards are

suspended or are hanging due to static forces. The card feeder activates when the sensor indicates the opening is clear. This method avoids jams and provides faster shuffling as compared to programming a time delay between the gripping of cards and subsequent lowering of the elevator and the insertion of the next card.

[0078] Another general description of a preferred device according to the invention is a device for forming a randomized set of playing cards, the device comprising: a top surface and a bottom surface of the device; a receiving area for supporting an initial set of playing cards to be randomized; a randomizing system for randomizing the initial set of playing cards; and a collection surface in a card collection area for receiving randomized playing cards, the collection surface being movable in a vertical direction. In one example of the invention, cards are received onto the collection surface, either positioned directly on the surface or positioned indirectly on a card supported by the surface. All cards being randomized in this example are inserted into the card collection area at a location below the top surface of the device. In one example of the invention, cards are fed individually off of the bottom of the stack located in the card receiving area and into the card collection area.

[0079] An elevator is provided for raising the collection surface so that at the conclusion of shuffling, at least some randomized cards are elevated to a position at or above the top surface of the device. The elevator may be capable of raising all or part of the randomized cards at or above the top surface of the device. A cover may be provided to protect or mask the cards until they are elevated into a delivery position from which a dealer may remove the cards manually. The device may have a stack stabilizing area defined by a confining set of walls defining a shuffled card delivery area that confines all randomized cards along at least two, and preferably three edges after the randomized cards are elevated.

[0080] Alternatively, the card collection surface itself, elements positioned on the top surface of the shuffler or elements moved above the top surface of the shuffler may act to stabilize the cards so that they are more easily removed by the dealer's hand(s). The present invention also contemplates raising the shuffled group of cards to the top surface of the shuffler, where there are no confining structures around the cards. In one example of the invention, the top surface of the shuffler is flush-mounted into the gaming table surface, and the cards are delivered directly to the gaming table surface after shuffling.

[0081] The delivery area may be positioned such that its lower interior surface is at the same elevation as the top surface of the shuffler. The lower interior surface may be elevated above the top surface, or positioned beneath the top surface of the shuffler. In one example of the invention, the lower interior surface is at the same elevation as the top of the exterior of the shuffler. If the shuffler is mounted into and completely surrounded by a gaming table surface, it would be desirable to deliver cards so that the bottom card in the stack is at the same elevation as the gaming table surface.

[0082] The card receiving area may be sloped downwardly towards the randomizing system to assist movement of playing cards. The device may have at least one pick-off roller to remove cards one at a time from the card receiving area and to move cards, one at a time, toward the randomizing components of the system. Although in one example of the invention the randomizing system suspends cards and

inserts cards in a gap created below the suspended cards, other randomization systems can be employed, such as the random ejection shuffling technique disclosed in Sines et al., U.S. Pat. No. 5,584,483, the disclosure of which is hereby incorporated by reference. The at least one pair of speed-up rollers desirably receive cards from the at least one pick-off roller. A microprocessor preferably controls movement of the pick-off roller and the at least one pair of speed-up rollers. The first card is preferably moved by the pick-off roller so that, as later described in greater detail, movement of the pick-off roller is altered (i.e., stopped or otherwise altered so that tension contact with the card is reduced or ended) so that no card other than the first (lowermost) card is moved by either the pick-off roller or the at least one pair of speed-up rollers. This can be done by sensing of the movement or tension on the first card affected by the at least one pair of speed-up rollers, causing the pick-off roller to disengage from the drive mechanism and freely rotate and to not propel the card.

[0083] The microprocessor, for example, may be programmed to direct the pick-off roller to disengage from the drive mechanism and to cease propelling a first card being moved by the pick-off roller when it is sensed that the first card is being moved by the at least one pair of speed-up rollers. A preferred randomization system moves one card at a time into an area overlying the collection surface. It is desirable to have one card at a time positioned into a randomized set of playing cards over the playing card collection surface. Again, as with the first general structure, the card collection area may be bordered on two opposed sides by two vertically disposed, horizontally opposed movable card supporting elements. There is preferably an insertion point, such as an opening or slot, to the card collection area that is located below a bottom edge of the two movable card supporting elements. The card supporting surface is vertically positionable within the card collection area, usually under the control and direction of a microprocessor. For example, the card supporting surface is moved by a motor or elevator that is able to move incremental vertical distances that are no greater than the thickness of a playing card, such as incremental vertical distances that are no greater than one-half the thickness of a playing card. The motor may be, for example, a microstepper motor or an analog motor.

[0084] A sensor may be present within the collection area, below the top surface of the device, the sensor detecting a position of a top card of a group of cards in the card collection area below the group of suspended cards. In the alternative or in concert, the sensor detects the level of the card collection surface. In addition, a preferred embodiment of the device monitors the elevation of the top card when the two groups of cards are combined into one group, and adjusts for changes in the thickness of the deck due to swelling, humidity, card wear, bowing of cards, etc. A microprocessor is preferably present in the device to control vertical movement of the card collection surface. The sensor may identify the position of the collection surface to place the top card at a position level with the bottom of at least one card supporting element that is movable substantially horizontally from at least one side of the collection area towards playing cards within the card collection area.

[0085] In one example of the invention, an opening, such as a slot, is provided in a side wall of the card collection area to permit transfer of cards from the card receiving area into

the card collection area. The side wall may comprise a substantially solid support structure, adjoining edges of a plurality of vertical L-shaped corner support structures, or other equivalent structure capable of retaining a stack of cards in a substantially upright position. The microprocessor may be programmed to determine a distance that the card supporting surface must be vertically moved to position at least one specific card, including or other than the top card, at a bottom edge of the at least one card supporting element when the card supporting element moves to contact cards within the card collection area. As previously described, the at least one card supporting element may comprise at least two elements, such as gripping pads that move from horizontally opposed sides of the collection area towards playing cards within the card collection area.

[0086] The microprocessor may be programmed to lower the card collection surface within the card collection area after the at least one card supporting element has contacted and supported cards within the card collection area, creating two vertically spaced-apart segments or substacks of cards. The microprocessor directs movement of an individual card into the card supporting area between the two separated segments of cards. The microprocessor may direct movement of playing card moving elements within the device. The microprocessor randomly assigns final positions for each card within the initial set of playing cards, and then directs the device to arrange the initial set of playing cards into those randomly assigned final positions to form a final set of randomized playing cards. Each card is inserted into the building stack of collected (randomized or shuffled) cards by positioning them in respect to the other cards already in the stack. Thus, even if a first card is not intended to be adjacent to a particular card, but is intended to be above that particular card, the first card is positioned above (and possibly adjacent to) the particular card, and intervening cards in the intended sequence added between the first card and the particular card.

[0087] In one embodiment of the invention, the card receiving area is located such that individual cards are fed off of the bottom of the stack, through the slot formed in the card collection area, directly beneath the gripping elements. In another example of the invention, a card loading elevator is provided so that the cards can be loaded into the card receiving area at an elevation higher than that of the first embodiment. The elevator then lowers the cards to a vertical position aligned with the feed mechanism. The use of an elevator on the card loading area is also an ergonomic benefit, as the dealer can keep hand and arm movements at a consistent level and does not have to reach into the device or have to drop cards into the device. The cards to be randomized can be inserted at a level approximately equal to the top of the shuffler, which can also be the height at which a randomized set of cards can be removed from the device.

[0088] When the device is used to process large batches of cards, such as groups of eight decks, it is desirable to provide a feed elevator to lower the entire batch of cards beneath the top surface of the shuffler prior to shuffling. The card feeding mechanism from the card receiving area to the card collection or shuffling area is necessarily positioned lower in a shuffler that processes more cards than in a shuffler that processes fewer cards.

[0089] When a large number of cards is to be inserted into the machine for shuffling, a retaining structure may be provided, consisting of a card stop or frame to limit card

movement on up to three sides of the elevator. The open side or sides permit the dealer to load the stack from the side of the elevator, rather than trying to load the elevator from above, and allowing cards to fall freely and turn over.

[0090] A randomizing elevator is provided for moving the cards being randomized and operates to raise and lower the bottom card support surface of the card collection area. This elevator moves during randomization, and also aids in the delivery of the shuffled group of cards by raising the shuffled cards to a delivery area. Reference to the figures will assist in appreciation and enablement of the practice of the present invention. Upwardly extending side walls on the card collection surface, an elevator arm or extension of an elevator arm, or another element attached to the arm may move with the elevator and be used to move other portions of the shuffling apparatus. For example, the arm extension may be used to lift hinged or sliding covers over the cards as the cards are raised above a certain level that exceeds the normal shuffling elevation of the elevator.

[0091] FIG. 1 shows a partial perspective view of a top surface 4 of a first shuffling apparatus 2 according to a practice of the invention. In this example of the invention, the shuffling apparatus 2 randomizes one or two decks of cards (not shown). The shuffling apparatus 2 has a card accepting/receiving area 6 that is preferably provided with a stationary lower support surface that slopes downwardly from a nearest outer side 9 of the shuffling apparatus 2. A depression 10 is provided in that nearest outer side 9 to facilitate an operator's ability to place or remove cards into the card accepting/receiving area 6. The top surface 4 of the shuffling apparatus 2 is provided with a visual display 12 (e.g., LED, liquid crystal, micro monitor, semiconductor display, etc.), and a series of buttons, touch pads, lights and/or displays 24, 26, 28, and 30. These elements on the top surface 4 of the shuffling apparatus 2 may act to indicate power availability (on/off), shuffler state (jam, active shuffling, completed shuffling cycle, insufficient numbers of cards, missing cards, sufficient numbers of cards, complete deck(s), damaged or marked cards, entry functions for the dealer to identify the number of players, the number of cards per hand, access to fixed programming for various games, the number of decks being shuffled, card calibration information, and the like), or other information useful to the operator or casino.

[0092] Also shown in FIG. 1 is a separation plate 20 with a beveled edge 21 and two manual access facilitating recesses 22 that assists an operator in accessing and removing jammed cards between the card accepting/receiving area 6 and a shuffled card return area 32. The shuffled card return area 32 is shown to be provided with an elevator surface 14 and two separated card-supporting sides 34. In a preferred embodiment, sides 34 are removable. When the shuffling apparatus 2 is flush-mounted into and surrounded by the top of a gaming table surface, removal of sides 34 enables the shuffling apparatus 2 to lift shuffled groups of cards onto the gaming table surface for immediate use. The card supporting sides 34 surround a portion of the elevator surface 14 with interior faces 16 and blocking extensions 18. It is desirable to provide rounded or beveled edges 11 on edges that may come into contact with cards to prevent scratching, catching or snagging of cards, or scratching of operators' fingers or hands.

[0093] FIG. 2 shows a cutaway side view of a first embodiment of a shuffling apparatus 102 according to the

present invention. A top surface **104** is shown with a separation plate **120** and side panels **134** (card supporting sides) of a shuffled card return area **132**. A card accepting/receiving area **106** is recessed with respect to the top surface **104** and is shown with a declining sloping support surface **108**. At a front **135** of the sloping support surface **108** is an opening **136** (not able to be seen in the direct side view) or slot through which a bottom pick-off roller **138** may contact a bottom card in an unshuffled set of cards (not shown) within the card accepting/receiving area **106**. The bottom pick-off roller **138** drives a card in direction **140** by frictional contact towards a first pair of nip rollers or offset rollers **142**. In one example of the invention, the upper roller of offset rollers **142** is a break roller. This break roller retains the second top card for separation in the event that two cards are fed at the same time. In a preferred form of the invention, the upper roller does not rotate. In another form of the invention, the upper roller rotates, but is rotationally constrained.

[0094] There are two additional pairs of nip rollers or offset rollers **144** and **146** acting in concert (or only one of each pair is being driven) to move cards first moved by the first set of nip rollers **142**. In a preferred practice of the present invention, the operation of the apparatus **102** may perform in the following manner. When a card (not shown) is moved from the unshuffled card accepting/receiving area **106**, eventually another card in a stack of cards within the card accepting/receiving area **106** is exposed. The apparatus **102** is designed, programmed and controlled to operate so that individual cards are moved into the first set of nip rollers or offset rollers **142**. If more than one card from the card accepting/receiving area advances at any given time (even if in partial sequence, with a portion of one card overlapping another card), it will be more difficult or even impossible for the apparatus to direct individual cards into predetermined positions and shuffle the cards randomly.

[0095] If two cards are moved at the same time and positioned adjacent to each other, this uncontrollably decreases the randomness of the shuffling apparatus **102**. It is therefore desirable to provide a capability whereby, when a card is moved into the control area of the first set of nip rollers or offset rollers **142**, the drive function of the bottom pick-off roller **138** ceases on that card and/or before the bottom pick-off roller **138** drives the next card. This can be effected by a wide variety of techniques controlled or directed by a microprocessor, circuit board, programmable intelligence or fixed intelligence within the apparatus.

[0096] Among the non-limiting examples of these techniques are 1) a sensor so that when a pre-selected portion of the card (e.g., leading edge, trailing edge, and mark or feature on the card) passes a reading device, such as an optical reader, the bottom pick-off roller **138** is directed to disengage, revolve freely, or withdraw from the bottom of the set of cards; 2) the first set of nip rollers or offset rollers **142** may have a surface speed that is greater than the surface speed of the bottom pick-off roller **138**, so that engagement of a card applies tension against the bottom pick-off roller **138** and the roller disengages with free-rolling gearing, so that no forward-moving (in direction **140**) forces are applied to the first card or any other card exposed upon movement of the first card; 3) a timing sequence so that, upon movement of the bottom pick-off roller **138** for a defined period of time or for a defined amount of rotation (which correlates into a defined distance of movement of the first card), the bottom pick-off roller **138** disengages, withdraws, or other-

wise stops applying forces against the first card and thereby avoids applying forces against any other cards exposed by movement of the first card from the card accepting/receiving area **106**; and 4) providing a stepped surface (not shown) between bottom pick-off roller **138** and offset rollers **142** that contacts a leading edge of each card and will cause a card to be held up or retained in the event that more than one card feeds at a time.

[0097] The cards are eventually intended to be fed one at a time from final nip rollers or offset rollers **146** into the card mixing area **150**. The cards in the card mixing area **150** are supported on elevator platform **156**. The elevator platform **156** moves the stack of cards present in the card mixing area **150** up and down as a group in proximity with a pair of separation elements **154**. The pair of separation elements **154** grips an upper portion of cards, and supports those cards while the elevator drops sufficiently to provide an opening for insertion of a card into the stack. This movement within the apparatus **102** in the performance of the shuffling sequence offers a significant speed advantage in the shuffling operation as compared to U.S. Pat. No. 5,683,085, especially as the number of cards in the card mixing area **150** increases. Rather than having to lower the entire stack of cards to the bottom of the card receiving area and reposition the pickers (as required by U.S. Pat. No. 5,683,085), the cards in the present apparatus **102** may be dropped by the pickers or the elevator platform **156** needs to move only a slight distance to recombine the cards supported by the pair of separation elements **154** (e.g., a gripper, and insertion support, fingers, friction engaging support, rubber fingers, etc.) with the cards supported on the elevator platform **156**.

[0098] The stationary pair of gripping pads also maintains the alignment of the pads with respect to each other and grips the cards more securely than the device described in U.S. Pat. No. 5,683,085, reducing or eliminating the unintentional dropping of a card or cards that were intended to be gripped, rather than lowered. Whenever cards are dropped, the randomness of the final shuffle may be adversely affected. Although the first example of the invention shows a pair of oppositely positioned gripping members, it is possible to utilize just one gripper. For example, the opposite vertical support surface could be equipped with a rubber or neoprene strip, increasing frictional contact, allowing only one gripper to suspend groups of cards.

[0099] The elevator of a device with stationary grippers may then be moved to the next directed separation position, which would require, on average, less movement than having to reset the entire deck to the bottom of the card supporting area and then moving the picker, and then raising the picker to the card insertion point, as required in U.S. Pat. No. 5,683,085.

[0100] The microprocessor (not shown) controls and directs the operation of the shuffling apparatus **102**. The microprocessor also receives and responds to information provided to it. For example, a set of sensing devices, such as sensors **152**, are used to determine the movement point of the elevator platform **156** that positions the top card in a set of cards (not shown) within the card mixing area **150** at a specific elevation. The sensors **152** identify when an uppermost card on the elevator platform **156** or the top of the elevator platform **156** itself is level with the sensors **152**. This information is provided to the microprocessor. A reading system **170** may also be used to provide information, such as the number of cards that have been fed from the card

accepting/receiving area **106** into the card mixing area **150**, so that the number of cards shuffled and the number of cards present on the elevator platform **156** at any given time is known. This information, such as the number of cards present within the card mixing area **150**, is used by the microprocessor, as later explained, to randomly arrange and thus shuffle cards according to the programming of the system.

[0101] For example, the programming may be performed as follows. The number of cards in a set of cards intended to be used in the system is entered into the memory of the microprocessor. Each card in the set of cards is provided with a specific number that is associated with that particular card, herein referred to as the “original position number.” This is most conveniently done by assigning numbers according to positions within the original (unshuffled) set of cards. If cards are fed from the bottom of the stack into the randomizing apparatus, cards are assigned numbers from the bottom to the top. If cards are fed from the top of the stack or the front of a stack supported along its bottom edges, then the cards are numbered from top to bottom, or front to rear.

[0102] A random number generator (which may be part of the microprocessor, may be a separate component or may be external to the device) then assigns a random position number to each card within the original set of cards, the random position number being the randomly determined final position that each card will occupy in the randomly associated set of cards ultimately resulting in a shuffled set of cards. The microprocessor identifies each card by its original position number. This is most easily done when the original position number directly corresponds to its actual position in the set, such as the bottommost card being CARD **1**, the next card being CARD **2**, the next card being CARD **3**, etc. The microprocessor, taking the random position number, then directs the elevator platform **156** to move into position where the card can be properly inserted into the randomized or shuffled set of cards. For example, a set of randomized positions selected by a random number generator for a single deck is provided below. OPN is the Original Position Number and RPN is the Random Position Number.

OPN	RPN
1	13
2	6
3	39
4	51
5	2
6	12
7	44
8	40
9	3
10	17
11	25
12	1
13	49
14	10
15	21
16	29
17	33
18	11
19	52
20	5
21	18
22	28
23	34
24	9
25	48

-continued

OPN	RPN
26	16
27	14
28	31
29	50
30	7
31	46
32	23
33	41
34	19
35	35
36	26
37	42
38	8
39	43
40	4
41	20
42	47
43	37
44	30
45	24
46	38
47	15
48	36
49	45
50	32
51	27
52	22

[0103] The sequence of steps in the shuffling or randomizing procedure may be described as follows for the above table of card OPN's and RPN's. OPN CARD **1** is carried from the card accepting/receiving area **106** to the final nip rollers or offset rollers **146**. The final nip rollers or offset rollers **146** place CARD **1** onto the top of the elevator platform **156**. The elevator platform **156** has been appropriately positioned by sensors **152**. OPN CARD **2** is placed on top of CARD **1**, without the need for any gripping or lifting of cards. The microprocessor identifies the RPN position of CARD **3** as beneath both CARD **1** and CARD **2**, so the elevator platform **156** lifts the cards to the separation elements **154**, which grip both CARD **1** and CARD **2**, then support those two cards while the elevator platform **156** retracts, allowing CARD **3** to be placed between the elevator platform **156** and the two supported cards. The two cards (CARD **1** and CARD **2**) are then placed on top of CARD **3**, supported by the elevator platform **156**. The fourth card (CARD **4**) is assigned position RPN **51**. The elevator platform **156** would position the three cards in the pile so that all three cards would be lifted by the card separation element, and the fourth card inserted between the three cards (CARD **1**, CARD **2** and CARD **3**) and the elevator platform **156**. The fifth card (CARD **5**) has an RPN of **2**, so that the apparatus **102** merely requires that the four cards be positioned below the insertion point from the final nip rollers or offset rollers **146** by lowering the elevator platform **156**. Positioning of the sixth card (CARD **6**) with an RPN of **12** requires that the elevator platform **156** raise the complete stack of cards, the sensors **152** sense the top of the stack of cards, elevate the stack of cards so that the separation elements **154** grip only the top two cards (RPN positions **2** and **6**), lower the elevator platform **156** slightly, and then CARD **6** with an RPN of **12** can be properly inserted into an opening in the developing randomized set of cards. This type of process is performed until all 52 cards (for a single-deck game) or all 104 cards (for a double-deck game) are ran-

domly distributed into the final randomized set or shuffled set of cards. The apparatus may be designed for groups of cards larger than single 52-card decks, including 52-card decks with or without special cards (wild cards or jokers), special decks, two 52-card decks, and two fifty-two card decks plus special cards. Larger groupings of cards (e.g., more than 108 cards) may also be used, but the apparatus 102 of the first example of the invention has been shown as optimized for one- or two-deck shuffling.

[0104] Elevation of the elevator platform 156 may be effected by any number of commercially available systems. Motivation is preferably provided by a system with a high degree of consistency and control over the movement of the elevator, both in individual moves (e.g., individual steps or pulses) and in collective movement of the elevator (the steps or revolutions made by the moving system). It is important that the elevator be capable of providing precise and refined movement and repeated movements that do not exceed one card's thickness. If the minimum degree of movement of the elevator exceeds one card's thickness, then precise positioning could not be effected. It is preferred that the degree of control of movement of the elevator does not exceed at least one-half the card thickness. In this manner, precise positioning of the cards with respect to the separation elements 154 can be effected. Additionally, it is often desirable to standardize, adjust, or calibrate the position of the elevator (and/or cards on the elevator) at least once, and often at intervals, to ensure proper operation of the apparatus 102. In one example of the invention, the microprocessor calls for recalibration periodically, and provides the dealer with a warning or calibration instructions on the display 12 (FIG. 1).

[0105] As later described, a microstepping motor or other motor capable of precise, small, and controlled movements is preferred. The steps, for example, may be of such magnitudes that are smaller than a card's thickness, such as for example, individual steps of 0.0082 inch (approximately less than thickness of one card), 0.0041 inch (less than one-half of a card's thickness), 0.00206 inch (less than about one-quarter of a card's thickness), 0.0010 inch (less than about one-eighth of a card's thickness), 0.00050 inch (less than about one-sixteenth of a card's thickness), 0.00025 inch (less than about one-thirty-second of a thickness), 0.000125 inch (less than about one-sixty-fourth of a card's thickness), etc.

[0106] Particularly desirable elevator control mechanisms would be servo systems or stepper motors and geared or treaded drive belts (essentially more like digital systems). Stepper motors, such as microstepper motors, are commercially available that can provide, or can be readily adjusted to provide, incremental movements that are equal to or less than one card's thickness, including whole fractions of card thicknesses and indefinite percentages of card thicknesses. Exact correspondence between steps and card thickness is not essential, especially where the steps are quite small compared to the card thickness. For example, with a card thickness of about 0.279 mm, the steps may be 0.2 mm, 0.15 mm, 0.1 mm, 0.08 mm, 0.075 mm, 0.05 mm, 0.04 mm, 0.01 mm, 0.001 mm or smaller, and most values therebetween. It is most desirable to have smaller values, as some values, such as the 0.17 mm value of a step, can cause the gripper in the separation element to extend over both a target position to be separated and the next lower card in the stack to be gripped, with no intermediate stepping position being

available. This is within the control of the designer once the fundamentals of the process have been understood according to the present description of the practice of the invention. As shown in FIG. 2, a drive belt 164 is attached to two drive rollers 166 which move the elevator platform 156. The belt 164 is driven by a stepper motor system 171 that is capable of 0.00129-inch (0.003-mm) steps.

[0107] FIG. 3 shows a perspective cutaway of the sets of nip rollers or offset rollers 142, 144 and 146 of a first example of the invention. These are not truly sets of nip rollers, but are offset rollers, so that rollers 142a and 142b (not shown), 144a and 144b, 146a and 146b are not precisely linearly oriented. By selecting a nip width that is not so tight as to press a card from both sides of the card at a single position, and by selecting offset rollers rather than aligned nip rollers, fluid movement of the card, reduced damage to the card, and reduced jamming may be provided. This is a particularly desirable aspect of a preferred practice of the present invention, which is shown also in FIG. 4.

[0108] FIG. 4 shows a set of offset rollers 144a, 144b, 144c, 144d and 144e transporting a card 200. The card 200 is shown passing over rollers 144a and 144d and under rollers 144b, 144c and 144e. As can be seen, the rollers are not capable of contacting a card to precisely overlap at a specific point on opposite sides of a card.

[0109] FIG. 5 shows a cross-sectional view of one embodiment of a gripping system 204 that may be used in the practice of the invention. FIG. 5 shows two oppositely spaced support arms 206 and 208 that support gripping elements 210 and 212, which comprise semi-rigid gripping pads 214 and 216. These gripping pads 214 and 216 may be smooth, grooved, covered with high-friction material (e.g., rubber or neoprene), ribbed, straight, sloped, or the like, to take advantage of various physical properties and actions. The support arms 206 and 208 are attached to separately movable positioning arms 218 and 220. These positioning arms 218 and 220 are referred to as separately movable, in that they are not physically connected, but one tends to move from left to right while the other moves right to left (with respect to the view shown in FIG. 5) as the two positioning arms 218 and 220 move in and out (substantially horizontally) to grip or release the cards. However, preferably they do not move independently, but should move in concert. It is also desirable that they are fixed with respect to the vertical. If the positioning arms moved completely independently (horizontally, during gripping), with only one at a time moving to attempt to contact the cards, the first contacting arm could move cards out of vertical alignment. For this reason, it is preferred that two opposed gripping arms be used.

[0110] Although the positioning arms 218 and 220 may not move the contact pads 214 and 216 into contact with absolute precision, they should contact opposite edges of the cards at approximately the same time, without moving any card more than 5% of the length of a card (if contacted lengthwise) or 7% of the width of the card (if contacting the cards widthwise). An example of one mechanism for moving the positioning arms in concert is by having a drive belt 226 that engages opposite sides of two connectors 222 and 224 that are attached to positioning arms 220 and 218, respectively. The belt 226 contacts these connectors 222 and 224 on opposite sides, such as by contacting a rear side of connector 224, and by contacting a front side of connector 222. As the belt 226 is driven by rotors 228 and 230, with

both rotors **228** and **230** turning in direction **232**, connector **222** will be moved from left to right, and connector **224** will be moved from right to left. This will likewise move gripping pads **214** and **216** inwardly to grip cards. The use of such pads is much preferred over the use of rigid, pointed, spatula elements to separate cards, as these can damage cards, which not only can increase the need for replacement, but can also mark cards, which could reduce security.

[0111] Alternative constructions comprise a flat elastic or a rubbery surface with knobs or nubs that extend upwardly from the surface to grab cards when pressed into contact with the sides of the cards. These elements may be permanently affixed to the surfaces of the pickers or may be individually removable and replaceable. The knobs and the flat surface may be made of the same or different materials, and may be made of relatively harder or softer, relatively rigid or relatively flexible materials according to design parameters.

[0112] The apparatus may also contain additional features, such as card reading sensor(s) (e.g., an optical sensor, a neural sensing network, a video imaging apparatus, a bar-code reader, etc.), to identify suits and ranks of cards; feed means for feeding cards sequentially past the sensor(s) at various points within the apparatus; storing areas in which the cards are stored in a desired order or random order; selectively programmable artificial intelligence coupled to the sensor(s) and to the storing areas to assemble in the storing areas groups of articles in a desired order; delivery systems for selectively delivering the individual articles into the storing areas; and collector areas for collecting collated or randomized subgroups of cards.

[0113] The sensor(s) may include the ability to identify the presence of an article in particular areas, the movement or lack of movement in particular areas, the rank and/or value of a card, spurious or counterfeit cards, and marked cards. This can be suitably effected by providing the sensor with the capability of identifying one or more physical attributes of an article. This includes the sensor having the means to identify indicia on a surface of an article. The desired order may be a specific order of one or more decks of cards to be sorted into its original pack order or other specific order, or it may be a random order into which a complete set of articles is delivered from a plurality of sets of randomly arranged articles. For example, the specific order may be effected by feeding cards into the card accepting area with a sensor identifying the suit and rank, and having a pre-established program to assign cards, based upon their rank and suit, into particular distributions onto the elevator platform. For example, a casino may wish to arrange the cards into pack order at the end of a shift to verify all cards are present, or may want to deal cards out in a tournament in a specified random order. The sensing can take place in the card receiving area when the cards are stationary, or while the cards are in motion.

[0114] The suit, rank and position of all cards in the card accepting/receiving area will then be known, and the program can be applied to the cards without the use of a random number generator, but with the microprocessor identifying the required position for that card of particular suit and rank. The card may also be read between the offset rollers or between the last offset roller and the platform, although this last system will be relatively slow, as the information as to

the card content will be known at such a late time that the platform cannot be appropriately moved until the information is obtained.

[0115] For example, the desired order may be a complete pack of randomly arranged playing cards sorted from holding means which holds multiple decks, or a plurality of randomly oriented cards forming a plurality of packs of cards. This may be achieved by identifying the individual cards by optical readers, scanners or any other means, and then, under control of a computer means such as a microprocessor, placing an identified card into a specific collector means to ensure delivery of complete decks of cards in the desired compartment. The random number generator is used to place individual cards into random positions to ensure random delivery of one to eight or more decks of cards, depending on the size of the device.

[0116] In one aspect of the invention, the apparatus is adapted to provide one or more shuffled packs of cards, such as one or two decks for poker games or blackjack. According to another aspect of the invention, a method of randomizing a smaller or larger group of cards is accomplished using the device of the present invention. According to the invention, the method includes the steps of: 1) placing a group of cards to be randomized into a card in-feed tray; 2) removing cards individually from the card in-feed tray and delivering the cards into a card collection area, the card collection area having a movable lower surface and a stationary opening for receiving cards from the in-feed tray; 3) elevating the movable lower surface to a randomly determined height; 4) grasping at least one edge of a group of cards in the card collection area at a point just above the stationary opening; 5) lowering the movable lower surface to create an opening in a stack of cards formed on the lower surface, the opening located just beneath a lowermost point where the cards are grasped; and 6) inserting a card removed from the in-feed tray into the opening. According to the method of the present invention, steps **2** through **6** are repeated until all of the cards originally present in the in-feed tray are processed, forming a randomized group of cards.

[0117] As described above, the method and apparatus of the present invention can be used to randomize groups of cards, as well as sort cards into a particular desired order. When sensing equipment is used to detect rank and suit of the cards, the cards can be arranged in any predetermined order according to the invention. It is to be understood that numerous variations of the present invention are contemplated, and the disclosure is not intended to limit the scope of the invention to the examples described above. For example, it might be advantageous to tip the card mixing area **150** (FIG. 2) slightly, such that a top portion is farther away from the card accepting/receiving area **106** than a bottom portion. This would assist in aligning the stack vertically in card mixing area **150** and would increase the efficiency and accuracy of the randomization or ordering process. In one preferred embodiment, the card mixing area **150** is tipped between 3 degrees and 8 degrees from the vertical.

[0118] In another embodiment of the invention, the shuffler is mounted into a gaming table such that in-feed tray or card accepting/receiving area **106** is recessed beneath the top surface of the gaming table, and a lower horizontal surface of the elevator platform **156** in the delivery area or shuffled card return area **132** in its upright position is flush with the elevation of the gaming table surface.

[0119] Although the machine can sit on the tabletop, it is preferably mounted on a bracket having a support surface located beneath the gaming table surface, and is completely surrounded by the table top, enabling a dealer to obtain and return cards without undue lifting above the surface of the gaming table. In one embodiment, the entire shuffler is mounted into the gaming table such that the in-feed tray and card return areas are either flush or approximately flush with the gaming table surface. Such an arrangement would be particularly suited for use in conventional poker rooms.

[0120] In a second example of the invention, the device is configured to process larger groups of cards, such as a stack of eight complete decks. The individual components operate in much the same manner, but the specific configuration is designed to accommodate the greater height of the stack.

[0121] FIG. 6 shows a vertical perspective view of another apparatus 500 according to the invention. The apparatus 500 is shown with a flip-up cover 502 with sections 504 and 506 that overlie an elevator platform 512 and a card insertion area 510. An extension or tab 507 is provided to nest into open area 508 to assist lifting of the flip-up cover 502 when needed. The open area 508 leaves some additional space for a finger or tool to be inserted against the extension 507 to assist in its lifting. That additional space may be designed to accommodate only a tool so as to reduce any possibility of a player opening the shuffling apparatus 500. In a preferred embodiment of the invention, there is provided an arm extension 514 of the elevator platform 512 that contacts an internal edge 513 of the flip-up cover 502, here with a roller 515 shown as the contact element, to lift the flip-up cover 502 when the elevator platform 512 rises to a level where cards are to be removed, the extension 514 forcing the flip-up cover 502 to lift from a top surface 517 of the apparatus 500. The extension 514 also will buffer playing cards from moving as they are lifted from the elevator platform 512, although additional elements (not shown) may be used to restrain movement of the cards when elevated to a removal level. In this example of the invention, side panels are not used to stabilize the stack of delivered cards.

[0122] FIG. 6 also shows a display panel 516, which may be any format of visual display, particularly those such as LED panels, liquid crystal panels, CRT displays, plasma displays, digital or analog displays, dot-matrix displays, multi-segment displays, fixed-panel multiple-light displays, or the like, to provide information to a viewer (e.g., dealer, casino personnel, etc.). The display panel 516 may show any information useful to users of the apparatus 500, and show such information in sufficient detail as to enable transfer of significant amounts of information. Such information might include, by way of non-limiting examples, the number of cards present in the apparatus, the status of any shuffling or dealing operations (e.g., the number of complete shuffling cycles), hand information (such as the number of hands to be dealt, the number of hands that have been dealt, the number of cards in each hand, the position to which a hand has been dealt, etc.), security information (e.g., card jam identification, location of card jams, location of stuck cards, excess cards in the container, insufficient cards in the container, unauthorized entry into the apparatus, etc.), confirmation information (e.g., indicating that the apparatus is properly corresponding to an information-receiving facility, such as a network or microprocessor at a distal or proximal location), on/off status, self-check status, and any other information about play or the operation of the apparatus that would be

useful. It is preferred that the display panel 516 and the software driving the display panel 516 be capable of graphics display, not merely alphanumeric.

[0123] Buttons 518 and 520 can be on/off buttons, special function buttons (e.g., raise elevator to the card delivery position, operate jam sequence, reshuffle demand, security check, card count demand, etc.), and the like. A sensor 524 (e.g., optical sensor, pressure sensor, magnetic detector, sonar detector, etc.) is shown on the elevator platform 512 to detect the presence of cards or other objects on the elevator platform 512.

[0124] FIG. 7 is a side cutaway view of an apparatus 600 according to an aspect of the invention, which may be compared with FIG. 2 to provide an explanation of components and some of the variations possible within the practice of the invention. For example, the use of two belt drive motors 662 and 664 versus the three shown in FIG. 2 allows for the apparatus 600 to be shortened, with motor 662 driving a belt 666 that moves three rollers 668, 669 and 670. The pair of rollers 144 is removed from this example of the invention as superfluous. The two drive rollers 166 in FIG. 2 that raise the elevator platform 156 are partially eliminated by having an elevator drive belt 672 driven by a motor 674 and an attached spindle 676, which have been positioned in direct alignment with the drive belt 672 in FIG. 7, instead of the right-angle, double-belt connection shown in FIG. 2. Again, as the drive belt 672 moves far enough to display cards (not shown) on an elevator platform 612, an extension 614 presses against an edge 613 of a cover section 604, elevating a cover top 602. The apparatus 600 is preferably configured with sections 604 and 606 separated along area 680 so that they move independently. By separating these sections 604 and 606, only the cards readied for delivery are exposed, and access to area 682 where unshuffled cards are to be inserted is more restricted, especially where, as noted above, a tool or implement is needed to raise the cover section corresponding to 606 so that the unshuffled cards may not be too readily accessed.

[0125] In FIG. 7, the motors 662, 664 and 674 are preferably highly controlled in the degree of their movement. For example, one of the methods of providing precise control of motor movement is with microstepped motors. Such micro stepping of motors controls the precise amount of movement caused by the motor. This is especially important in motor 674 that drives the elevator platform 612 that in turn carries the cards (not shown) to be separated for random card insertion. With microstepping, the movement of the cards can be readily controlled to less than a card's thickness per microstep. With such control, with movements per microstep of no more than 0.9 a card's thickness, preferably less than 0.8 a card's thickness, less than 0.5 a card's thickness, less than 0.4 a card's thickness, less than 1/3 a card's thickness, less than 0.25 a card's thickness, less than 0.20 a card's thickness, and even less than 0.05 a card's thickness, much greater assurance of exact positioning of the elevator platform 612 and the cards thereon can be provided, further ensuring that cards will be inserted exactly where requested by operation of the microprocessor. Sensing elements 684 may be positioned within a picker or grabbing element 686 to analyze the position of the picker 686 with respect to cards being separated to determine if cards have been properly aligned with the picker 686 and properly separated. The picker 686 may alternatively be physically protruding sub-elements that grab small areas of cards, such

as rubber or elastomeric bumps, plastic bumps, metal nubs, or the like. Sensors may alternatively be placed on other surfaces adjacent the picker **686**, such as walls **688** or **690** or other adjacent walls or elements. For increased security and enhanced performance, it is preferred that multiple sensors be used, preferably multiple sensors that are spaced apart with regard to edges of the cards, and multiple sensors (i.e., at least two sensors) that are positioned so that not only the height can be sensed, but also misalignment or sloping, or bending of cards at different locations or positions. The sensors can work independently of or in tandem with the microprocessor/step motor/encoder operation.

[0126] The microstep motors will also assist the apparatus in internal checks for the correct position. For example, an encoder can be used to check the exact position of the elevator with regard to the measured movement and calculation of the precise movement of the elevator platform and hence the cards. The encoder can evaluate the position of the elevator platform through analysis and evaluation of information regarding, for example, the number of pulses per revolution of the spindle **676** on the motor **674**, which may be greater than 100 pulses per revolution, greater than 250 pulses per revolution, greater than 360 pulses per revolution, greater than 500 pulses per revolution or greater than 750 pulses per revolution, and, in preferred embodiments, greater than 1000 pulses per revolution, greater than 1200 pulses per revolution, and equal to or greater than 1440 pulses per revolution. In operation, the microprocessor moves the motor, the encoder counts the amount of movement driven by the motor, and then determines the actual position of the elevator platform or a space (e.g., four cards higher) relative to the elevator platform. The sensors may or may not be used to determine the correct position, initially calibrate movement and sensing positions on the platform, or as a security check.

[0127] An additional design improvement with respect to the apparatus **102** of FIG. 2 and that of the apparatus **500** and **600** of FIGS. 6 and 7, respectively, is the elimination of a staging area in the apparatus design of FIG. 2. After a card (not shown) in FIG. 2 passes from rollers **142** to rollers **144**, but before being passed to rollers **146**, the card would be held, or staged, by rollers **144**. This can be eliminated by the design of rollers **668**, **669**, and **670** shown in FIGS. 6 and 7, with the movement of the cards timed to the movement of the elevator platform **612** and the separation of the cards by the pickers **686**.

[0128] The apparatus **500** shown in FIG. 6 is also provided with an outer flange **528** extending around an upper edge **530** of the top surface **517** of the apparatus **500** that may be used to attach and support the apparatus **500** to a table or to support the apparatus **500** so that the top surface **517** is relatively parallel to the surface of the table.

[0129] The use of a shuffler whose shuffling mechanism is concealed completely beneath the gaming table surface potentially poses security issues to a casino. In the event of a system malfunction, the dealer might not be aware that a shuffling sequence has failed. Since there is no way to visualize the shuffling routine, and in order to avoid instances where the display lights may malfunction and erroneously show a shuffling sequence has been completed, an added level of security has been provided to the shuffler of the present invention.

[0130] According to the present invention, a number of cards to be randomized and the order of insertion of each

card into the card randomizing or shuffling compartment is predetermined by the random number generator and microprocessor. By adding an encoder to the motor or motors driving the elevator, and by sensing the presence of groups of suspended cards, the MPU can compare the data representing the commands and the resulting movements to verify a shuffle has occurred. In the absence of this verification, the shuffler can send a signal to the display to indicate a misdeal, to a central pit computer to notify management of the misdeal, to a game table computer (if any) with an output display to notify the dealer of a misdeal, to a central computer that notifies security, to a central system for initiating maintenance calls, or to combinations of the above.

[0131] Such a system is referred to as a “closed loop” system because the MPU creates the commands and then receives system signals verifying that the commands were properly executed.

[0132] Although the dealer control panel and display in the above examples of the present invention are located on the card shuffler, the present invention contemplates user-operated remote controls, such as a foot pedal, an infra-red remote control, the input of commands from a remote keyboard in the pit, or other device initiated by a dealer or by management. Unlike the shuffler operation driven by software from a game computer, pit computer or central computer system, the shuffler of the present invention is controllable by an operator using remote equipment such as what is described above.

[0133] Although the randomizing system has been described as a vertically disposed stack of cards with a means for gripping a portion of the cards, and lowering the remaining cards to form two separate subgroups, forming an insertion point, the invention contemplates the use of a shuffler with a carousel-type card collection area. The gripping pads in this example of the invention grip a portion of cards that are horizontally disposed, and the card collection area rotated to create an insertion point for the next card. The cards are pushed out one at a time, or in groups to a card collection area.

[0134] Referring now to FIG. 8, a perspective view of a shuffling machine **700** of the present invention is shown mounted to a shuffler support plate **702** behind a gaming table (not shown) that may or may not be modified to accommodate placement of the support plate **702**.

[0135] In this example of the invention, cards are loaded into an in-feed tray **706**. In one example of the invention (not shown), the lower surface of the in-feed tray **706** is substantially horizontal and is provided so that cards can be loaded into a top surface **708** of the shuffling machine **700**, and then lowered beneath the gaming table surface for randomization.

[0136] The in-feed tray **706** may be equipped with a card support structure similar to the vertical support structure **712** surrounding delivery tray **710**, which in a preferred embodiment has two vertical supports and two sides left open. Cards may be loaded into the in-feed tray **706** and into a card support structure (not shown), and lowered automatically in response to the dealer pushing downwardly on the top of the stack of cards or upon a signal received from the dealer controls (not shown).

[0137] In this example of the invention, the loading station is positioned near the playing surface (for example, a casino table) and at the dealer's side, allowing the machine to be

used without unnecessary strain or unusual physical movement on the part of the dealer. Loading and unloading large stacks of cards from the top of a machine that is mounted to eliminate lifting, straining or reaching large distances addresses a need long felt in the industry for a more ergonomically friendly card shuffler.

[0138] The delivery tray **710** in the second described embodiment also includes a two-sided vertical support structure **712** for supporting a group of randomized cards as the cards are raised to the top surface **708** of the shuffling machine **700**. It is to be understood that the vertical support structures **712** are preferably secured to the delivery tray **710**, but could also be secured to the frame, and attached in a manner to pop up into position when needed.

[0139] A method of handling cards is described, including inserting the cards into a card in-feed tray, feeding the cards into a card randomization apparatus, capturing the randomized cards in a support structure and raising the cards and support structure to an upper surface of the shuffler. The method may comprise providing a retractable support structure for extracting shuffled cards, inserting shuffled cards into the support structure while it is below the top surface of the device, moving the support structure to expose the cards and retracting the support structure both before and after card removal. The card in-feed tray may also be positioned on an elevator capable of lowering the group of cards into the apparatus prior to shuffling. When a second elevator is used, it is preferable to provide a retractable support structure for supporting the cards as the cards are lowered for shuffling.

[0140] The method preferably includes providing two separate support structures that support a vertically stacked group of cards on at least two surfaces, and preferably three. The support structure can be a solid three-sided box, could consist of three vertically disposed bars, two parallel plates and two angle irons to retain corners, any other structure that keeps the stack in vertical alignment, or any other suitable support structure. The structure can be fixed to the upper surface of the shuffler, can be fixed to the elevators or can be affixed to the frame of the shuffler and constructed to “pop up” when needed for card loading and unloading. Cover plates, such as hinged or rotating plates, can be provided over the two elevators to provide additional cover (e.g., dust cover and visual cover) over the card source and the card collection areas to ensure that visual inspection of the shuffling procedure can be reduced, and entry of foreign materials can be reduced. The cover plates should be light enough for the system to automatically lift the covers or for a dealer to easily lift the covers manually. The cards themselves may push up the cover plates, or a preceding post or element can be positioned on the elevator or supports attached or moving conjointly with the elevators to press against the interior surface of the cover plates to lift the plates in advance of contact with the cards.

[0141] The card reading capability, as described in greater technical detail later, can be used in a different number of modes and positions to get the benefits of the present invention. The card reading capability (by some visual data-taking element, such as a camera, scanner, reflection scanner, image bit recorder, image edge detector, or any other subcomponent that can image a card or convert a visual image of the card into reproducible data) can be located at various positions within the shuffler where it can be assured of imaging each card before it is removed from

the shuffler. This preferably is being done in the present invention internally in a shuffling machine where cards are not removed one at a time from a dealing end or fed as hands or groups of cards (but less than the entire set of cards) to be removed in a subgroup of the entire set of cards placed into the shuffler. In one example of the invention, a video camera is used as a rank/suit scanner

[0142] A desirable set of image capture devices (e.g., a CCD automatic camera) and sensors (e.g., light-emitting devices and light capture devices) will be described, although a wide variety of commercial technologies and commercial components are available. A preferred camera is the DRAGONFLY® automatic camera, provided by Point Grey Research, Inc., and includes a six-pin IEEE-1394 interface, asynchronous trigger, multiple frame rates, 640×480 or 1024×724 24-bit true color or 8-bit grayscale images, image acquisition software and plug-and-play capability. This can be combined with commercially available symbol recognition software. The commercially available image recognition software is trained on card symbols and taught to report image patterns as specific card suits and ranks. Once a standard card suit/rank recognition program has been developed, the training from one format of cards to another becomes more simply effected and can be done at the casino table or by a security team before the shuffler is placed on the table. Position sensors can be provided and enhanced by one of ordinary skill in the art from commercially available components that can be fitted by one ordinarily skilled in the art. For example, various optics, such as SICK® WT2S-N111 or WL2S-E111, OMRON® EE SPY302, or OPTEK® OP506A, may be used. A useful encoder can be purchased as US Digital encoder 24-300-B. An optical response switch can be provided as MicroSwitch SS541A.

[0143] The benefits of the present system may be used in those less preferred shuffling devices, including continuous shufflers, especially where the continuous shufflers monitor the position of cards in the shuffled set from which cards are removed for play of a game, so that a constant inventory of the number, suit, rank and position of each and all cards can be maintained. Numerous types of image data-taking devices or image capture devices that can provide the image data necessary to “read” the symbols on the card sufficiently so as to distinguish individual card’s rank at least by rank and preferably by rank and suit (and any other special markings that may be present on cards for special games) are available or are readily within the skill of the artisan to be constructed. Such image capture devices may be continuous (rapid frame-by-frame) video cameras, digital cameras, analog cameras, reader/scanners, edge response detectors, reflectance readers, and the like, and may optionally have lighting elements (for example, filament lighting, light-emitting diodes, lamps, electromagnetic spectrum emitters of any type, and the like) present to improve the lighting during image capture. The cards can be read during the randomization procedure either when the cards are stationary or in motion, without any special stop positions or delays in the movement of cards. The cards are read in such a manner that the rank and suit of each card in a complete set of cards (e.g., all of the cards within the device) are identified in a randomized set by position of each card and the rank and suit of each card in each position. It is also important to note that, in a shuffling mode, the final set of cards is a randomized set of cards and not merely a collection of cards in a slightly different order from an original set

of cards (e.g., previously played, unshuffled, hand-mixed, or the like). In another mode, cards are passed through the scanner without being shuffled for the purpose of rapidly verifying the content of the deck. One possible way of distinguishing a randomized deck of cards from a merely mixed deck or programmed collection of cards would be to use a statistical analysis program, or using another criteria, such as where fewer than 100% of the cards in a final set of at least 52 cards are not within ten cards' distance from adjacent cards within an original set.

[0144] As a general statement, the card reading capability should be directed towards a face of the cards so that edge reading (which requires specially marked cards) is not practiced or required. To do this, the camera or other image data-taking element should view at least a symbol-marked corner of a card. This is not a problem, as standard cards have their symbols (or suit and rank) in opposite corners so that rotating a card will leave the symbol in the same corner position for viewing. Given this background, the image data-taking component (hereinafter, an "IDC," or alternatively referred to as an image capture device) could be located as follows. If there is a feeding mechanism that moves individual cards from a deck or set of initial cards (usually unshuffled or previously used in a non-intended order) into a preliminary position before shuffling, the IDC could be located below the insertion area of the cards so that the bottom card is read before removal and after each bottom card is read, the next bottom card is exposed to the IDC and is read. If top cards are removed one at a time, then each top card as it is moved would be read from below by an IDC. This is less preferred as the IDC would be probably be maximally distanced from each card as it is read because of the height of the set of cards. The set of cards could be elevated to fix the IDC at an intermediate height to lessen this problem, but increased distance between the IDC and the cards would require better and more expensive optics and software.

[0145] If the set of cards is placed on a support and cards are removed one at a time from the bottom (preferably) or the top of the set of cards and moved directly into a shuffling operation (rather than stored, collected or buffered at this point), then the camera may be either directly below a transparent support (or exposed through a hole in the support) or at a position outside of a dimension of the set of cards (e.g., if in a vertical stack that forms a box-like structure, outside of the area of the bottom of the box), such as at an opening between an initial card support area and away from pick-off rollers or other first card moving elements within that area of the bottom, before a first set of rollers that exerts control over the card from the first card moving elements (e.g., braking rollers, speed-up rollers, nip rollers with any function, vacuum support movers, etc.), or after the first set of rollers exerts control over the card from the first card moving elements. The first card moving elements and all other card moving elements (except where otherwise specified) shall be discussed as rollers (usually nip rollers, although the pick-off rollers are not a set of nip rollers), such as pick-off rollers, for simplicity, it being understood that other card moving systems (e.g., plunger, pushing plates, etc.) may be used.

[0146] The card value (e.g., suit and/or rank) may be read after the first set of pick-off rollers, after the first set of nip rollers past the pick-off rollers, after a third set of rollers that exerts some control on the movement of cards after the first

set of nip rollers, such as when (in a preferred embodiment of the invention) cards are individually moved from a set of rollers to be inserted into a space between subgroups of cards in a forming stack of shuffled/randomized cards. In those positions, with the cards moving face down within the shuffling device, the face of the cards can be readily observed by an IDC and an image taken.

[0147] Looking at FIG. 9, a shuffling/randomizing device **800** is shown with an initial card set receiving area **802**. A set of pick-off rollers **804** and **806** are shown. The pick-off rollers (shown as two rollers **804** and **806**, but one, two, three or more linearly aligned or arrayed rollers can be used) move a card (not shown) from the bottom of a set of cards (not shown) placed into the initial card set receiving area **802** and through an access hole or slot **810** to a position where a second set of rollers **808** exert some control over the card exiting from the slot **810**. As the card is moved past rollers **808** (which may be called braking rollers for convenience, speed-up rollers, or any other term used in the jargon of the art), the face of the card with symbols thereon (not shown) is brought into focal area **816** where a camera **814** (or other IDC) may record the image of the face of the card. The card, at this time or subsequently, also has control exerted upon it by a next set of nip rollers **812**, usually referred to as speed-up rollers, as they may sometimes desirably be used with linear surface speeds slightly greater than the linear surface speed of the rollers **808**. Certain of the individual rollers in roller pairs may be brake rollers, free-turning rollers, or even stationary (not rotating) rollers to provide optional physical effects on the movement of and tension on cards. The rollers **812** move the card (not shown) into an insertion space **818**, which will be in an opening created between subgroups of cards (not shown) within elevator space **830**. The shuffling operation itself will be explained in greater detail later herein.

[0148] As noted elsewhere, the IDC may operate in a continuous "on" mode (less preferred, primarily because of the volume of data that is produced, but the use of data screening or filtering software that concentrates on symbol imagery, as by only including data following light background to dark background changes, may be used) or in a single screen-shot mode that is timed to the proper positioning of the symbol on the card in the focal area of the camera. Looking again at FIG. 9, the single screen shot can be seen and accomplished in a number of different ways. The time in which the various rollers **804**, **806**, **808** and **812** move the card from the initial card set receiving area **802** into the camera focal area **816** is quite consistent, so a triggering mechanism can be used to set off the camera **814** at an appropriate time when the card face is expected to be in the camera focal area **816**. Such triggers can include one or more of the following, such as optical position sensors **820** and **822** within the initial card set receiving area **802**, an optical sensor **824**, a nip pressure sensor (not specifically shown, but which could be within either nip roller **808**), and the like. When one of these triggers is activated, the camera **814** is instructed to time its shot to the time when the symbol-containing corner of the card is expected to be positioned within the camera focal area **816**. The card may be moving at this time and does not have to be stopped. The card may be stopped if desired or if time is needed for supported cards **832** to be moved to allow insertion of a card into the insertion space **818** between subgroups of cards. The underlying function is to have some triggering in the shuf-

fling/randomizing device **800** that will indicate with a sufficient degree of certainty when the symbol portion of a moving or moved card will be within the camera focal area **816**.

[0149] FIG. **10** shows a top cutaway view of a shuffler **900** with card reading camera **916** therein. The various elements are shown in a different view, such as pick-off rollers **904** and **906** within an initial card set receiving area **902**. Sensor **920** is shown in FIG. **9** as a card set sensor **920** that indicates that there are still cards in the initial card set receiving area **902**. Sensor **928** is in a more favorable card sensing position to act as a trigger for the camera **916**. A set of sensors **922** and **926** operate as card position sensors to check for jamming, clearance, alignment, and in-feed availability (into an elevator area **930**). Sensors **938** and **926** may also act to assure that a card to be fed into the elevator area **930** is properly positioned and available to be inserted by insert rollers **912**.

[0150] A desirable set of image capture devices (e.g., a CCD automatic camera) and sensors (e.g., light-emitting devices and light capture devices) will be described, although a wide variety of commercial technologies and commercial components are available. A preferred camera is the DRAGONFLY® automatic camera provided by Point Grey Research, Inc., and includes a six-pin IEEE-1394 interface, asynchronous trigger, multiple frame rates, 640×480 or 1024×724 24-bit true color or 8-bit grayscale images, image acquisition software and plug-and-play capability. This can be combined with commercially available symbol recognition software. The commercially available image recognition software is trained on card symbols and taught to report image patterns as specific card suits and ranks. Once a standard card suit/rank recognition program has been developed, the training from one format of cards to another becomes more simply effected and can be done at the casino table or by a security team before the shuffling apparatus **2** is placed on the table. Position sensors (e.g., sensors **32** and **34**) of FIG. **1** can be provided and enhanced by one of ordinary skill in the art from commercially available components that can be fitted by one ordinarily skilled in the art. For example, various optics, such as SICK® WT2S-N111 or WL2S-E111, OMRON® EE SPY302, or OPTTEK® OP506A, may be used. A useful encoder can be purchased as US Digital encoder 24-300-B. An optical response switch can be provided as MicroSwitch SS541A.

[0151] Once the symbol has been imaged, a signal is sent to a central processor where the information of the suit and rank of the individual cards is processed according to the objectives of the system. After each card has been read, the individual cards are moved by rollers to be deposited in a card collection area. Cards are delivered into the card collection area by being placed on a support tray. The trigger may also activate a light that is used in conjunction with the image capture device to improve image capture capability.

[0152] Another aspect of the invention is to provide a device for forming a random set of playing cards. The device may comprise:

[0153] a top surface and a bottom surface of the device;

[0154] a single card receiving area for receiving an initial set of playing cards;

[0155] a randomizing system for randomizing the order of an initial set of playing cards;

[0156] a single card collection surface in a card collection area for receiving randomized playing cards one at

a time into the single card collection area to form a single randomized set of playing cards, the single card collection surface receiving cards so that all playing cards from the initial set of playing cards are received below the top surface of the device;

[0157] an image capture device that reads the rank and suit of each card after it has begun leaving the single card receiving area and before being received on the single card collection surface; and

[0158] access for removal of a single randomized set of playing cards as a complete set.

[0159] The access allows the complete set of randomized cards to be removed as a batch from the randomization device, rather than feeding the cards one at a time to a delivery end (e.g., shoe end) of the device. This can allow the device to be more compact and allow the device to operate independent of card delivery and in a batch manner as opposed to a continuous shuffler manner.

[0160] All of the apparatus, devices and methods disclosed and claimed herein can be made and executed without undue experimentation in light of the present disclosure. While the apparatus, devices and methods of this invention have been described in terms of both generic descriptions and preferred embodiments, it will be apparent to those skilled in the art that variations may be applied to the apparatus, devices and methods described herein without departing from the concept and scope of the invention. More specifically, it will be apparent that certain elements, components, steps, and sequences that are functionally related to the preferred embodiments may be substituted for the elements, components, steps, and sequences described and/or claimed herein while the same or similar results would be achieved. All such similar substitutions and modifications apparent to those skilled in the art are deemed to be within the scope and concept of the invention as defined by the appended claims.

[0161] The unique combination of the accurate imaging reading capability of the present system and the specific positioning capability and recording (indexing) of specific cards whose value (rank and suit) can be specifically identified and associated with a specific position with the final randomized set of cards, provides excellent security to casinos and players. As the card sequences in the shuffled set of final cards can be exactly known, this information can be used along with other security devices, such as table card reading cameras, discard trays with card reading capability, and the like, to add a high degree of certainty that a fair and honest game is being played at a specific location. Special bonus hands in games such as LET IT RIDE® poker, THREE CARD POKER® game, CRAZY 4 POKER™, and the like, can be immediately verified by a central computer or the shuffler itself by indicating that a specific value or rank of hand was properly dealt to a specific position on the table. Present-day security may sometimes have to hand verify an entire deck or set of cards, which can take five to ten minutes of table downtime. This is distracting to players and is an economic loss to the casino.

[0162] Although a description of preferred embodiments has been presented, various changes, including those mentioned above, could be made without deviating from the spirit of the present invention. It is desired, therefore, that reference be made to the appended claims rather than to the foregoing description to indicate the scope of the invention.

What is claimed is:

1. An automatic playing card shuffler comprising:
 - a housing configured to be utilized at a gaming table, the housing comprising a playing card support surface in a playing card receiver for accepting a group of playing cards to be shuffled from a location proximate a top surface of the gaming table;
 - a shuffler support plate mounted to the housing, wherein the shuffler support plate is configured to position the housing adjacent the gaming table;
 - a randomizing system for randomizing the order of the group of playing cards to provide randomized playing cards;
 - a collection surface for supporting the randomized playing cards; and
 - an elevator for raising the collection surface to an elevation to enable a dealer to manually remove all of the randomized playing cards at one time from the location proximate the top surface of the gaming table.
2. The automatic playing card shuffler of claim 1, wherein the group of playing cards is configured to be inserted into the playing card receiver from above the shuffler support plate.
3. The automatic playing card shuffler of claim 1, wherein the shuffler support plate at least partially supports the housing.
4. The automatic playing card shuffler of claim 1, wherein the playing card shuffler is configured to transport the group of playing cards from the location proximate a top surface of the gaming table to a location within the housing.
5. The automatic playing card shuffler of claim 4, wherein the playing card shuffler is configured to lower the group of playing cards into the housing in a direction away from the top surface of the gaming table.
6. The automatic playing card shuffler of claim 5, wherein the playing card shuffler is configured to shuffle the group of playing cards at the lowered location within the housing.
7. The automatic playing card shuffler of claim 1, wherein the housing comprises an upper, substantially flat top surface, the upper, substantially flat top surface configured to be positioned substantially at an elevation with top surface of the gaming table.
8. The automatic playing card shuffler of claim 7, wherein the collection surface is configured to be positioned at an elevational level at least at the upper, substantially flat top surface of the housing.
9. The automatic playing card shuffler of claim 1, further comprising a movable cover over the collection surface, the movable cover allowing manual access to the collection surface when the movable cover is opened and preventing manual access to the collection surface when the movable cover is closed.
10. The automatic playing card shuffler of claim 9, wherein the movable cover is configured to be elevated over the housing in an open position.
11. The automatic playing card shuffler of claim 9, wherein the movable cover is configured to be elevated by an extension coupled to the elevator.
12. The automatic playing card shuffler of claim 9, wherein the movable cover is configured to be mechanically lifted by the automatic playing card shuffler.
13. The automatic playing card shuffler of claim 9, wherein the movable cover is configured to move by translating the movable cover between an open position and a closed position.
14. A playing card shuffler comprising:
 - a housing comprising a playing card support surface in a playing card receiver for accepting a group of playing cards to be shuffled;
 - a shuffler support plate mounted to the housing, wherein the shuffler support plate is configured to position the housing immediately proximate a gaming device having a playing surface, the shuffler support plate configured to position an upper portion of the housing at an elevational level substantially the same as a playing surface of the gaming device;
 - a randomizing system for randomizing the order of the group of playing cards resulting in randomized playing cards;
 - a collection surface for supporting the randomized playing cards; and
 - an elevator for raising the collection surface to an elevation to enable a dealer to manually remove all of the randomized playing cards at one time from a location proximate the playing surface of the gaming device.
15. The playing card shuffler of claim 14, further comprising a movable cover configured to be elevated over the housing in an open position to enable the dealer to unload the randomized playing cards from the housing.
16. The playing card shuffler of claim 15, wherein the movable cover is configured to be elevated by an extension coupled to the elevator.
17. The playing card shuffler of claim 14, wherein the shuffler support plate is configured to position the housing adjacent the gaming table.
18. The playing card shuffler of claim 14, wherein the playing card support surface is configured to be positioned at an elevational level proximate the upper portion of the housing.
19. The playing card shuffler of claim 14, wherein the collection surface is configured to be raised to an elevational level at least at an upper surface of the housing.
20. A method of installing a playing card shuffler, the method comprising:
 - positioning a shuffler support plate adjacent a gaming table; and
 - mounting a housing of the playing card shuffler to the shuffler support plate, the housing configured to accept a group of playing cards to be shuffled from a location proximate a playing surface of the gaming table and through an upper portion of the housing, to randomize the group of playing cards, and to provide the randomized group of playing cards back through the upper portion of the housing back to the location proximate the playing surface of the gaming table.

* * * * *