




(86) Date de dépôt PCT/PCT Filing Date: 2005/06/08  
(87) Date publication PCT/PCT Publication Date: 2005/12/22  
(45) Date de délivrance/Issue Date: 2014/11/25  
(85) Entrée phase nationale/National Entry: 2006/11/17  
(86) N° demande PCT/PCT Application No.: IB 2005/002631  
(87) N° publication PCT/PCT Publication No.: 2005/120400  
(30) Priorités/Priorities: 2004/06/09 (FR0406211);  
2004/09/29 (US10/951,766)

(51) Cl.Int./Int.Cl. *A61F 2/44* (2006.01),  
*A61F 2/46* (2006.01)  
(72) Inventeurs/Inventors:  
LEONARD, ALAIN, FR;  
OGLAZA, JEAN-FRANCOIS, FR;  
RENAUD, CHRISTIAN, FR;  
HUET, GILDAS, FR  
(73) Propriétaire/Owner:  
VEXIM, FR  
(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : PROCÉDES ET DISPOSITIF POUR LA RESTAURATION OSSEUSE  
(54) Title: METHODS AND APPARATUSES FOR BONE RESTORATION



(57) Abrégé/Abstract:

Methods and apparatuses for restoration of human or animal bone anatomy, which may include introduction, into a bone of an expansible implant (1) capable of expansion in a single determined plane (2), positioning the expansible implant in the bone in order to correspond the single determined plane with a bone restoration plane and opening out the expansible implant in the bone restoration plane. A first support surface (8) and a second support surface (9) spread tissues within bone. The embodiments of the invention may also include injecting a filling material around the implant.





**WO 2005/120400 A3**



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

5

## METHODS AND APPARATUSES FOR BONE RESTORATION

### 10 Field Of The Invention

The present invention relates to the field of surgery and medical implants and more particularly to devices and methods for restoring human or animal bone anatomy using medical bone implants.

### 15 Background Of The Invention

Various causes can be at the root of bone compression, in particular osteoporosis which causes (for example) natural vertebral compression under the weight of the individual, but also traumas, with the two causes occasionally being combined. Such bone compressions can affect the vertebrae but also concern other  
20 bones, such as the radius and the femur, for example.

Several vertebroplasty techniques are known for effecting a vertebral correction i.e., to restore a vertebra to its original shape, or a shape similar to the latter. For example, one technique includes the introduction of an inflatable balloon into a vertebra, then introducing a fluid under pressure into the balloon in order to  
25 force the cortical shell of the vertebra, and in particular the lower and upper



5 vertebral plateaus, to correct the shape of the vertebra under the effect of the pressure. This technique is known by as kyphoplasty. Once the osseous cortical shell has been corrected, the balloon is then deflated, and withdrawn from the vertebra in order to be able to inject a cement into the cortical shell which is intended to impart, sufficient mechanical resistance for the correction to have a significant duration in  
10 time.

A notable disadvantage of the kyphoplasty method resides in its numerous manipulations, in particular inflation, and in the necessity to withdraw the balloon from the patient's body. Furthermore, the expansion of a balloon is poorly controlled because the balloon's volume is multi-directional, which often causes a large  
15 pressure to be placed on the cortical shell in unsuitable directions. Such large pressures risk bursting of the cortical shell and, in particular, the lateral part of the cortical shell connecting the lower and upper plateaus of a vertebra.

Other vertebral implants exist which are intended to fill a cavity in a vertebra. Such implants, however, generally adopt a radial expansion principle  
20 obtained by formation of a plurality of points which stand normally to the longitudinal axis of the implant under the effect of contraction of the latter. Such implants impose too high a pressure on individual points which may pierce the material on which the points support. Furthermore, similar to kyphoplasty, very high pressure can cause bursting of the tissues or organ walls, such as the cortical shell,  
25 for example. Furthermore, the radial expansion of some implants does not allow a particular expansion direction to be favoured.

## SUMMARY OF THE INVENTION

Embodiments of the present invention reduce the above noted disadvantages  
30 and provide additional advantages over the prior art devices for bone restoration. More particularly, some embodiments of the present invention include methods for restoration of human or animal bone anatomy, and include one or more of the following steps:

- introduction, into a bone for restoring, of an expansible implant according to a single determined expansion plane which is preferably intrinsic to the implant,
- positioning the expansible implant in the bone in order to make the expansion plane correspond with a bone restoration plane,
- 5 - opening out the expansible implant in the bone restoration plane, and
- injecting a filling material in and/or around the implant.

The method, according to some embodiments of the invention, allows the creation of a reinforced structure resulting in a solid structure (i.e., the implant incorporated by a hardened filling material thanks to the expansion of the implant). Moreover, the filling  
10 material can be injected under relatively low pressure since the implant remains in place which enables the preservation of the dimensions of the corrected bone structure by the expansion of the implant.

It is another feature of an embodiment of the present invention that an expansible implant may be expanded/opened-out in a bone restoration plane to a determined value:  
15 between a minimum thickness (e.g., the thickness of the implant before any expansion), and a maximum thickness (e.g., the thickness of the implant after maximum expansion). Such a feature allows the expansion value of the implant to be controlled, for example, for a given vertebral correction.

Another advantageous feature of an embodiment of the present invention includes  
20 the opening out of an expansible implant by opening out a first and/or a second opposite plate, forming (respectively) first and a second support surfaces for the bone. Such a feature allows the pressure which is exerted by the implant on tissues in contact with the implant to be reduced by increasing the contact or support surface on the tissues.

The length of the implant may also be sized to be substantially equal to at least  
25 one of the first and second support surfaces in the bone. Such a feature allows optimization of a ratio of the support length (on the tissues) to the length of the implant. The closer this ratio is to one, the more the implant will be viable in places requiring a small length. Moreover, this feature also allows the introduction of a filling material at



5 low injection pressure. Low injection pressure is preferable so as to avoid having filling material injected into inappropriate tissues (e.g., such as blood vessel walls).

In another embodiment of the invention, each of the first and second plates may form partially cylindrical support surfaces, a portion (or more) of which may be parallel to a longitudinal axis of the expansible implant. A cylindrical (curved)  
10 support surface may spread out the forces that the implant places on tissues.

In another embodiment of the present invention, the opening out of said first and second plates of the implant utilizes one or more supports under the plates. Such a feature allows a ratio of the length of the support surfaces to the length of the implant to be increased to be as close to one (1) as possible (see above).  
15 Furthermore, this feature allows thrust forces to be more evenly distributed under the plate in order to reduce the cantilever.

A filler cement which may be injected in and/or around the implant, so as to aid in compressive load with the implant in bone restoration, include an ionic cement, in particular a phosphocalcic cement, an acrylic cement or a compound of  
20 the latter. Accordingly, the combination of the implant and the cement is not unlike a steel reinforced concrete structure in the construction of buildings.

In another embodiment of the present invention, an expansible implant for bone restoration includes a single plane of expansion intrinsic to the implant. The single plane of expansion corresponds to a bone restoration plane. The implant may  
25 also include first and second opposed plates respectively forming first and a second bearing surfaces for the bone. The first and second plates are positioned to move away from one another according to the single plane of expansion (e.g., at the time of the expansion of the implant). The implant may also include first and second supports for one or more of the first and second bearing surfaces, and are preferably  
30 provided under either or preferably both plates (respectively). The implant may also include means for controlling expansion of the implant. Such means may include a material web provided between each support and a corresponding plate, having a determined thickness.

In other embodiments of the present invention, the means for controlling  
35 expansion controls an expansion value between a minimum thickness of the implant

5 before any expansion of the latter and a maximum thickness of the implant after its maximum expansion.

The implant may also include (preferably) a means for positioning the expansible implant in bone in order to make the expansion plane of the implant correspond substantially with a bone restoration plane. Such means may include an  
10 engagement means (e.g., a threaded engagement) allowing angular orientation of the implant about the longitudinal axis and may include one or more flat surfaces in an end of the implant (for example) for attachment with an implant carrier.

Still another embodiment of the invention is directed to a system for bone restoration and may include at least one expansible implant having a single plane of  
15 expansion for corresponding to a bone restoration plane (one or more implants may be used in a single bone to produce a more symmetrical bone restoration; see Fig. 37). The system may also include a first tube for positioned adjacent an exterior surface of the bone for restoration and a first rod having a threaded end for affixing into a distal end of the interior of the bone (the first rod may be received within the  
20 first tube). The system may also include a second tube for receiving the first tube therein and a third tube for receiving the second tube. The third tube may include one or more engagement members for anchoring the third tube on the exterior surface of the bone. The system may further include a drill for establishing an enlarged opening in the side of the bone, which may be guided by the first rod.  
25 Moreover, the system may further include a medical insertion device for inserting an expansible implant into a patient.

In still yet another embodiment of the invention, a medical insertion device is disclosed for inserting an expansible implant into a patient. The device may include a gripping portion having a central bore, a first tube housed in the central  
30 bore and a threaded rod housed in the first tube which may include a distal end for receiving an implant for insertion into the patient. The device may also include a handle attached to the gripping portion and/or the implant carrier as well as a gauge for determining an expansion of the implant.



Still other features, advantages, embodiments and objects of the present invention will become even more clear with reference to the attached drawings, a brief description of which is set out below, and the following detailed description.

5

## BRIEF DESCRIPTION OF THE FIGURES

Fig. 1A illustrates a perspective view of an embodiment of an expansible implant according to an embodiment of the invention, in a resting position.

Fig. 1B illustrates the example of Fig. 1A, in opened-out/expanded position.

10 Fig. 2A illustrates a side view of another embodiment of an expansible implant according to another embodiment of the invention, in a resting position.

Fig. 2B illustrates the example of Fig. 2A, in opened-out/expanded position.

Fig. 3 illustrates a lateral view of the example according to Fig. 1A.

Fig. 4 illustrates a view in section according to the line I-I of Fig. 3.

Fig. 5 illustrates a view in section according to the line II-II of Fig. 3.

15 Fig. 6 represents an end view according to F of the example according to Fig. 1A.

Fig. 7 illustrates a view from above of the example according to Fig. 1A.

Fig. 8 illustrates a perspective view of a second embodiment of an expansible implant according to another embodiment of the invention, in a resting position.

Fig. 9 illustrates the example of Fig. 8, in opened-out position.

20 Fig. 10 illustrates a lateral view of the example according to Fig. 8.

Fig. 11 illustrates a view in section according to the line III-III of Fig. 10.

Fig. 12 illustrates a view in section according to the line IV-IV of Fig. 10.

Fig. 13 illustrates a view in section according to the line V-V of Fig. 10.

5           Fig. 14 illustrates a view in section according to the line VI-VI of Fig. 10.

          Fig. 15 illustrates an end view according to G of the example according to Fig. 8.

          Fig. 16 illustrates a view from above of the example according to Fig. 8.

          Figs. 17-29 illustrate schematically, the different steps of an embodiment of  
10   a method for bone restoration according to the invention.

          Figs. 30-32 illustrate schematically, steps of another embodiment of a method for bone restoration according to the invention.

          Fig. 33 illustrates a perspective view of an implant carrier device for inserting an implant into the bone of a patient according to another embodiment of  
15   the present invention.

          Fig. 34 illustrates a top view of the implant carrier device of Fig. 33.

          Fig. 35 illustrates an expansion gauge for the implant carrier shown in Figs. 33 and 34.

          Fig. 36 illustrates a chart with expansion values for implants according to  
20   the disclosed embodiments using the implant carrier shown in Figs. 33 and 34.

          Fig. 37 illustrates the use of a pair of implants according to another embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE EMBODIMENTS

          The expansible implant 1 represented in Figs, 1A to 7 (as well as other  
25   embodiments) may include one or more of the following:

- a single determined expansion plane 2, which may be intrinsic to the implant,
- means 3 for positioning the expansible implant in the bone allowing the expansion plane to correspond with a bone restoration plane,

- 5       – means 4 for opening out the expansible implant in the single expansion plane 2,
- means 5 for controlling a determined expansion value, between a minimum thickness A of the implant before any expansion of the latter and a maximum thickness B of the implant after its maximum expansion, and
- 10      – a first 6 and a second 7 opposite plate which are able to form respectively a first 8 and a second 9 support surface in the bone intended to be moved apart one from the other along the single expansion plane 2 during expansion of the implant 1.

As shown in Figs. 1A and IB, implant 1 may include a cylindrical shape  
 15 with a transverse circular exterior section, and can be manufactured of biocompatible material, (for example titanium) into a tubular body using lathe, laser, and/or electro-erosion manufacturing techniques (cast manufacturing may also be used). The implant 1 may also include a first end 20 and a second end 21, each respectfully adopting the shape of a transverse section of the tubular body. The ends  
 20 are preferably intended to be brought towards one another to allow the opening-out/expansion of the implant, as represented in Figs. IB and 2B.

Accordingly, the two ends 20, 21 are connected to each other by a first 22 (which also may be referred to as “upper” arm) and second 23 (which also may be referred to as “lower” arm) rectilinear arms, which are parallel when the implant is  
 25 not opened-out. The arms may be formed longitudinally in the tubular body -- i.e., able to be folded under the first 6 and second 7 opposite plates upon ends 20 and 21 being brought towards one another, which also results in the distancing of first 6 and second 7 opposite plates from the longitudinal axis 10 of the tubular body.

Figs. 2A-2C illustrate an embodiment of the implant which is similar to the  
 30 embodiment disclosed in Figs. 1 A and IB, but with an additional set of supports (e.g., a four bar linkage). More specifically, the implant in Figs. 2A-2B includes supports 12A, 12B, 13A, 13B, 14A, 14B, 15A, and 15B, two pair for each of the upper and lower plates. The additional supports may provide further rigidity for the implant and/or may insure that plates 6 and 7 open-out in a substantially parallel  
 35 and/or even manner.



5           As represented in Figs. 4-5, in order for arms 22 and 23 to open out in a single expansion plane 2 (passing through the longitudinal axis 10 of the tubular body), the arms 22 and 23 are preferably diametrically opposed. In that regard, arms 22, 23 may be formed from a transverse recess 40 of the tubular body, traversing the tubular body throughout, and extending over the length of the tubular body between  
10   the two ends 20 and 21 of the implant 1. As represented in Fig. 5, the arms, 22, 23 connecting the two ends 20 and 21, respectively adopt a transverse section bounded by a circular arc 26 of the exterior surface of the tubular body. Chord 27 defines the circular arc 26 and may be included in the wall 25 to form recess 40. The recess 40 may be symmetrical with respect to the longitudinal axis 10.

15           Each arm 22, 23 may be divided into three successive rigid parts, which may be articulated together in conjunction with the ends 20 and 21 as follows (for example). With respect to the upper arm 22: a first rigid part 28 is connected at one end to end 20 by means of an articulation 29. The other end of rigid part 28 is connected to a first end of a second adjacent, central rigid part 30 by means of an  
20   articulation 31. The second rigid part 30 may be connected at a second end to the third rigid part 32 by means of an articulation 33. The other end of the third rigid part 32 may be connected to end 21 by means of an articulation 34. Preferably, the articulations 29, 31, 33 and 34 may include one degree of freedom in rotation, acting, respectively, about axes which are perpendicular to the expansion plane 2.  
25   Preferably, articulations 29, 31, 33 and 34 are formed by a thinning of the wall forming the arm in the relevant articulation zone, as represented in Figs. 1A-3 (see also, e.g., reference numerals 5 and 81).

          Each arm 22, 23 may open out such that the central rigid part 30 moves away from the longitudinal axis 10 of the implant pushed by the two adjacent rigid  
30   parts 28 and 32, when the ends 20 and 21 of the implant are brought one towards the other. As represented more particularly in Fig. 3, in order to initiate the movement of the arm in the correct direction when the ends 20 and 21 are brought towards the other, it is preferable to establish a suitable rotation couple of the various parts of the arm.

35           Accordingly, the ends of rigid parts 28, 32 of upper arm 22 may be articulated with ends 20 and 21, respectively, via a material web formed on the rigid parts. Other ends of rigid parts 28, 32 may also be articulated with the central rigid part 30 via a material web formed on rigid parts 28, 32. The displacement of the

5 articulations establish a rotation couple on the rigid parts 28 and 32 when a force is applied to bring the ends 20 and 21 together along the longitudinal axis 10 of the implant. This displacement tends to make the rigid part 32 pivot towards the exterior of the implant as a result of moving the central rigid part 30 away from the longitudinal axis 10.

10           The lower arm 23 may be constructed in a similar manner as the upper arm and is preferably symmetrical to the upper arm 22 with respect to a plane which is perpendicular to the expansion plane 2 passing through the longitudinal axis 10.

          Thus, according to some embodiments of the present invention, the articulations between the upper 22 and lower 23 arms and corresponding rigid parts  
15 are preferably formed by weakened zones produced by grooves 81. The grooves define a thin web of material (i.e., the thinness of the material at 31, 33) forming the tubular body, the thickness of which may be determined by the depth of the grooves 81 (as represented in the figures) in order to allow plastic deformation of the material without breaking. Specifically, according to one embodiment, the rigid  
20 parts 28 and 32 of the upper arm 22, and their symmetrical ones on the lower arm 23, can adopt a position, termed extreme expansion, in which the intended rigid parts are perpendicular to the longitudinal axis 10 of the implant 1 upon the ends 20 and 21 being brought towards one another (the latter being opened up until its maximum expansion capacity), resulting in plastic deformation of the corresponding  
25 material. The width of the grooves 81 are preferably pre-determined to allow a clearance of the parts of the upper and lower arms and also to impart a suitable radius of curvature to the webs in order to ensure plastic deformation without rupture of the material.

          The first 6 and second 7 opposite plates may be formed in the upper 22 and  
30 lower 23 arms. With respect to the upper arm 22, for example, plate 6 may be formed by the central rigid part 30 and by material extensions (rigid parts 28 and 32) extending out both sides thereof. In order to produce the rigid plate 6, end parts 28 and 32 are separated from the upper arm 22 using a pair of transverse slots 35 and 36 which extend longitudinally over the length each respective end part (see Figs. 3-4).  
35 Articulations 31 and 33 and rigid parts 28 and 32 form, respectively, a first 12 and a second 13 support (Fig. 1B) for the first 6 plate. The same applies to the second plate 7 by symmetry.



5           Hence, according to the illustrated embodiment, the first 6 and second 7 plates may comprise respectively a first 16, 18 and a second 17, 19 cantilever wing, the respective attachment zones of which are situated at the level of the first 12, 14 and second 13, 15 supports. As represented in Figs. 1A-B, the first 16, 18 and second 17, 19 cantilever wings may include a length corresponding substantially to  
10 the maximum displacement value of one of the first 6 or second 7 plates in the single expansion plane 2.

          The first 6 and second 7 plates form first 8 and second 9 support surfaces, respectively, each having a length which may be substantially equal to the length of the implant and which may be displaced perpendicularly to the longitudinal axis 10  
15 during expansion. According to one embodiment of the invention, since the implant 1 is formed in a tubular body, the first 6 and second 7 plates form, respectively, curved support surfaces, which are preferably parallel to the longitudinal axis 10.

          The means 3 for positioning the expansible implant in a bone to enable the expansion plane 2 to correspond with a bone restoration plane, may include an  
20 engagement means which allows for an angular orientation of the implant about longitudinal axis 10. For example, such means may include flat surfaces 37, 38 which are formed on the cylindrical surface with a circular section of end 20, which may allow for rotational engagement of the implant 1. The means 4 for opening out the expansible implant in a single expansion plane 2, may include rigid parts 28 and  
25 32 of upper arm 22 and the corresponding symmetrical rigid parts on the lower arm 23, allowing opening out of the first 6 and second 7 plates.

          An implant carrier 71 (see Fig. 23) may be used to allow the ends 20 and 21 of the implant to be brought together when placed within the bone. The implant carrier 71, by supporting end 20 of the implant, for example, allows the end 21 to be  
30 pulled toward end 20, or vice-versa (e.g., end 21 being supported and end 20 being pushed toward end 21). To that end, the distal end 21, for example, comprises an opening distal orifice 39 threaded along the longitudinal axis 10 in order to allow the engagement of the implant carrier 71, which includes a corresponding threaded portion. The proximal end 20 may include a bore 80 along the longitudinal axis 10  
35 in order to allow the passage of a core of the implant carrier 71 to pass to the distal end 21.



5 A control means may be provided by the implant carrier which may include a millimetric control means for bringing ends 20 and 21 together, preferably by means of screw-thread engagement, allowing the expansion to be stopped at any moment as a function of requirements. On the other hand, the control means 5 provided by the articulations of the arms 22 and 23, more specifically, by the 10 thickness of the material webs (e.g., 31, 33) defining each arm which, deforming in the plastic region, allow the expansion to substantially preserve a determined opening-up position of the arms, apart from elastic shrinkage which is negligible in practice.

The expansion of the plates 6 and 7 of the implant, and their stabilisation 15 once opened up, can be achieved through adaptation of plates 6 and 7 to the bone geometry by the plates. While in some embodiments of the invention the plates 6 and 7 are opened-out in a parallel arrangement, other embodiments of the invention allow plates 6 and 7 of the implant to be opened-out in a non-parallel displacement, if necessary (e.g., as a function of the bone anatomy). For example, the expansion of 20 plates 6 and 7 may be non-parallel if the lengths of individual support arms are different. For example, if supports 12 and 14 are longer than supports 13 and 15 (see Figs. 1A-2B), opening out the implant will force plates 6 and 7 to progressively angle away from each other. In Figs. 1A-2B, this would result that plates 6 and 7 at end 21 to be further apart one another than at end 20. As one of ordinary skill in the 25 art will appreciate, depending upon the configuration, only one respective support need be lengthened/shortened, in order to obtain a particular angle.

Similarly, as shown in Figs. 2A-2C, when the four bar linkage comprising supports 12A, 12B, 13A, 13B, 14A, 14B, 15A, 15B, as shown, are equal lengths (i.e., length of 12A = length of 13A, length of 12B = length of 13B, etc.), a 30 parallelogram then results upon expansion of the implant (parallelism is insured between segments AD and BC; see Fig. 2C). By modifying the lengths of L1 and L2, the four bar linkage will not result in a parallelogram upon expansion, but rather an angle between plate 6 and 7 occurs. The angle formed may also be dependent on how close ends 20 and 21 are drawn near to each other. As the implant is opened- 35 out, the angle progressively increases.

Figs. 8-16 relate to a second embodiment of an expansible implant 101, the elements of which are functionally similar to the corresponding elements of the implant embodiment illustrated in Figs. 1-7. Moreover, the corresponding features in

5 Figs. 8-16 relating to the embodiment illustrated in Figs. 1-7 include the same reference numerals, respectively, with the addition of the number 100 and therefore will not be described further.

The represented implant 101 differs from the implant 1 by the absence of the wing portion on the plates 106 and 107, as represented more particularly in Fig. 9.

10 Implant 101 includes a deformable parallelogram system 141 on one of the rigid parts 128 or 132 of each of the arms 122 (upper) and 123 (lower). In the illustrated example, the parallelogram system is represented on rigid part 128 of upper arm 122, connected to the end 120 and the corresponding system on lower arm 123. The parallelogram systems may be used to ensure displacement of the plates of each of

15 the arms 122 and 123, parallel to longitudinal axis 110 of the implant. As represented in the figures, the rigid part 128 of the arm 122 (similarly on corresponding arm 123) is split, as are articulations 131 and 129 (respectively) over the central part 130 and over the end 120 of the implant in order to form a parallelogram which is deformable during displacement of the corresponding plate.

20 The articulations of the deformable parallelogram 141 may be produced in the same manner as the other articulations 131, 133, 134 of the arm 122, as represented in Figs. 8-16. The disclosed geometry as explained above and represented in Figs. 11-14, establishes force couples on the various parts 129, 130, 132 of the arm. This allows for the desired displacements when bringing together

25 ends 120 and 121 of the implant 101.

In order to obtain a deformable parallelogram 141, the rigid part 128 of the arm is preferably divided into three longitudinal levers: two lateral levers 142 and a central lever 143, which form two sides of the deformable parallelogram 141. The two remaining sides of the parallelogram may be formed by an extension 144 of the

30 central part of the arm 122, placed in an axis of extension of the central lever 143, and by a double extension 145 of the end 120, extending parallel to the longitudinal axis 110 of the implant and placed in the axis of extension of the two lateral levers 142 (see Fig. 8).

It is worth noting that arms 122 and 123 may be symmetrical with respect to

35 a plane which is substantially perpendicular to the plane of expansion 102 passing through the longitudinal axis 110 of the implant 101 in order to obtain, during the



5 expansion of the implant, the displacement of the two plates 106 and 107 in a manner parallel to the longitudinal axis 110.

#### Bone Restoration Examples

A first example of a method for human bone restoration according to one embodiment of the present invention using an expansible implant will now be  
10 described with reference to Figs. 17-29. It concerns, more particularly, a method for bone restoration of a vertebra via a posterolateral route, with fracture reduction. Accordingly, the method may include one or more (and preferably all) of the following steps. One of skill in the art will appreciate that the implant according to so embodiments of the present invention pushes through/divides tissues in the interior  
15 of the bone so that the bearing surfaces of the implant preferably come into contact with the bone tissue for restoration.

An expansible implant, expansible (preferably) in a single determined, expansion plane 2 (intrinsic to the implant) is introduced into a vertebra 60, the shape of which is to be restored. To effect this operation, a rod/pin 61 (e.g.,  
20 Kirschner pin type) is placed percutaneously via the posterolateral route so that the threaded end 62 can be affixed (e.g., screwed) into the cortical bone 63 opposite the cortical bone 64 which is traversed by the pin (Fig. 17). The pin 61 is received in a first dilation tube 65 until an end of the first tube 65 contacts (e.g., maybe supported) the exterior surface of the cortical bone 64 (Fig. 18).

25 The first dilation tube 65 is received by a second dilation tube 66, until the end of the second tube 66 comes into contact (e.g., supported by) the exterior surface of the cortical bone 64 (Fig. 19). The second dilation tube is further received by a third dilation tube 67, which comes into contact (e.g. is supported) on the exterior surface of the cortical bone 64 (Fig. 20). Teeth 68 on the end of the third dilation  
30 tube 67 anchor the tube in the cortical bone 64.

The first 65 and second 66 dilation tubes, as shown in Fig. 21, are then removed, leaving only the pin 61 surrounded by tube 67, which are separated from one another by tubular spacer 68. The proximal cortical bone 64 and cancellous bone 70 is then pierced by means of a drill 69 (for example) guided by the pin 61, as  
35 represented in Fig. 22. In one embodiment, the cancellous bone is pierced as far as the distal third (approximately), then the drill 69 may be withdrawn (the pin 61 may be withdrawn as well).



5           A proximal end of the implant 1 is removably attached to a distal end of a hollow core (preferably) implant carrier 71 which is then introduced into the core of tube 67, as represented in Fig. 23. The implant may be removably affixed to the implant carrier via threaded engagement (for example). Within the core of the implant carrier 71, a rod 72 (See also Fig. 33, reference numeral 3316) having a  
10   distal end which includes an engagement means to engage the distal end of the implant (and which may also include an expanded proximal end, larger than a diameter of the rod) may be inserted. Similar to the affixation of the implant to the implant carrier, the engagement means of the rod to the implant may be via threaded engagement.

15           The implant carrier 71, as shown in Fig. 33, includes a handling means 3310 for controlled movement of the rod relative to the implant carrier (for example). The handling means may comprise a gripping block 3312, having a central bore through which the implant carrier 71 is positioned and is held in place at least rotationally, but preferably rotationally and linearly. In that regard, a proximal end of the  
20   gripping member and the proximal end of the implant carrier are preferably flush. A handle 3314, according to one embodiment of the invention, may be attached to the proximal end of either or both of the gripping member and the implant carrier, but is preferably free to rotate relative thereto in either or both of the clockwise and counter-clockwise directions. In still another embodiment of the invention, the  
25   handle may not be attached to either or both of the gripping block and implant carrier. The handle may include a center opening which preferably includes internal screw threads of a predetermined thread pitch.

          The rod 3316, which is received within the implant carrier, preferably includes external threads corresponding in thread pitch to that of handle 3314. A  
30   locking device slides relative to the gripping block and may include a pin 3321 which frictionally interferes with the rod 3316, to lock the rod in place (i.e., no rotational movement).

          The threads of the rod are preferably provided at least along a majority of the length rod. According to one embodiment of the invention, the rod, implant carrier,  
35   gripping block and handle may be pre-assembled. One would insert the threaded distal

end of the rod into an opening in the center of the proximal end of the implant, where it then may be received in the correspondingly threaded portion in the center of the distal end of the implant. The distal end (i.e., the location of the implant) of the assembly of the implant with the implant carrier/handling means may then be inserted into dilation tube  
5 67.

Fig. 34 illustrates another view of the implant carrier, and includes a gauge 3320 which may be used to indicate the amount of expansion of the implant (e.g., a determination on the rotation amount of the rod 3316). The gauge may comprise a window to the rod 3316. As show in Fig. 35, according to one embodiment of the  
10 invention, the portion of the rod that is visible may not include threads. Rather, this section of the rod may include markings 3322 which indicate a percentage of expansion. Additional markings 3324 provided adjacent the window allow a user to gauge the percentage of expansion from the relative movement between the two markings.

Depending upon the predetermined thread pitch and direction of the thread of the  
15 rod 3316, rotation of the handle moves the rod 3316 relative to the implant carrier linearly in a direction. Preferably, the threads are provided on the rod such that clockwise rotation of the handle moves the rod outward away from an area in which the implant is to expand (the implantation area). For example, for an M5 thread, a pitch of 0.8 mm may be used. However, one of skill in the art will appreciate that a thread pitch of between about 0.5  
20 mm and about 1.0 mm (for example) may be used. Fig. 36 is a chart illustrating a no-load expansion of an implant according to one of the embodiments of the invention by the number of turns of the rod for three particular sizes of implants.

Accordingly, in view of the above embodiment, once the implant is positioned within the dilation tube and slid down therein, so that it is placed into the interior of the  
25 vertebra 60. The implant is preferably positioned such that the single expansion plane 2 corresponds to the desired bone restoration plane (Fig. 24). The position of the implant may be verified using any known imaging techniques, including, for example, X-ray and ultrasound.

The handle 3314 is then rotated to "pull" the rod away from the implantation area.  
30 Since the proximal end of the implant is butted up against the implant carrier, and pulling



5 on the rod causes the distal end of the implant to move toward the proximal end (or  
visa-versa). This results in the ends of the implant drawing towards each other  
which opens out the implant. More specifically, opposite plates 6 and 7 are opened  
out, advantageously forming, respectively, a first 8 and a second 9 support surface  
in the vertebra 60, which surfaces may be continuous over their length which may  
10 be substantially equal to the length of the implant 1 (Fig. 25). In the course of the  
expansion, control of the reduction of the fracture thanks to the millimetric control  
means, and after having obtained the desired expansion, for example, of a  
determined value between a minimum thickness of the implant before any  
expansion of the latter and a maximum thickness of the implant after its maximum  
15 expansion, then freeing of the implant carrier 71 by unscrewing it from the implant  
1, then extraction of the tube 67, as represented in FIG. 26, with the implant in  
opened-out position remaining in place in the vertebra 60.

Accordingly, the expansion of the implant in the vertebra is achieved by  
support under the plates allowing the thrust force to be distributed over the length of  
20 the plates under the latter. Thus a sufficient length of the plates may be provided  
while limiting an excessive dimensioning of the thickness of the latter in order to  
resist flexion. It will be appreciated by those of ordinary skill in the art that the  
implant according to some embodiments of the invention adopt a ratio of a spatial  
requirement in length (unexpanded) to length of elevated plate which is extremely  
25 optimised, allowing a preferable use of the limited intra-osseous spaces with a view  
to fracture reduction, for example.

The rod 3316 may also include, according to one of the embodiments of the  
invention, a disengagement means, which may comprise an internal hex on the  
proximal end 3318 of the rod. This may allow one to disengage the rod from the  
30 implant once the implant has been opened out. Alternatively, where the handle is not  
attached to the gripping block and/or implant carrier, the handle could be counter-  
rotated (i.e., rotated such that the rod does not move in a direction away from the  
implant) such that it travels away from the flush portion of the gripping block and  
implant carrier, such that it engages the proximal end of the rod. Further counter-  
35 rotation of the handle (after opening out of the implant) causes the rod to rotate in  
the same counter-rotation as the handle, thereby causing the rod to disengage from  
the implant. Depending upon the determined thread pitch, such disengagement can



5 occur in any number of rotations (e.g., less or more than one rotation). See also Fig.  
26

Preferably, after the rod has been removed, a filling material 74 is injected around the implant. The filling material may comprise, for example, an ionic cement, in particular, a phosphocalcic cement, an acrylic cement or a compound of  
10 the latter, with a view to filling in and around the implant. To accomplish this, a needle of the injector 73 is slid down tube 67 until the end of the needle reaches the distal orifice 39 of the implant 1 (Fig. 27). The filling material is then injected via the needle. Continued injection in a retrograde manner may be done up to a proximal orifice in cortical bone 64 of the vertebra 60 (Fig. 28). The needle of the injector  
15 may then be withdrawn from tube 67 (Fig. 29).

A second example of a method according to an embodiment of the invention for restoration of human bone anatomy, will now be described with references to Figs. 30-32. This example generally concerns a method for bone restoration of a vertebra by a transpedicular route, with fracture reduction.

20 The second example is similar to the first and differs from the latter by the penetration route of the implant into the vertebra 60, which is now accomplished in a transpedicular manner (Fig. 30) instead of the posterolateral route used in the first method. As a result, only some steps of the second method have been represented in Figs. 30-32 in order to show the different route used for the introduction of the  
25 implant 1 into the vertebra. For Figs. 30 to 32, elements identical to those of the first method example have the same numerical references, and those figures correspond respectively to the steps of Figs. 24, 25 and 28 of the first method example. Concerning the step represented in Fig. 32, the latter differs slightly from Fig. 28 by the position of the needle of the injector 73, closer to the distal end of the implant in  
30 Fig. 32.

It will thus be seen that the invention attains the objects made apparent from the preceding description. Since certain changes may be made without departing from the scope of the present invention, it is intended that all matter contained in the above description or shown in the accompanying drawings be interpreted as  
35 illustrative and not in a literal sense (and thus, not limiting). Practitioners of the art will realize that the method, device and system configurations depicted and described herein are examples of multiple possible system configurations that fall within the scope of the current invention.

## Claims:

1. An expandible implant for bone restoration comprising:  
  
a single plane of expansion intrinsic to the implant, wherein upon the single plane of expansion corresponds to a bone restoration plane;  
  
first and second opposed plates respectively forming first and a second bearing surfaces for the bone, wherein the first and second plates intended to move away one from the other according to the single plane of expansion at the time of the expansion of the implant;  
  
first and second implant ends configured to be brought towards one another upon a force being applied thereto resulting in the first and second opposed plates moving away from one another along the plane of expansion;  
  
first and second supports for each of the first and second bearing surfaces, located under each plate respectively; and  
  
means for controlling expansion of the implant, the means including a material web provided between each support and a corresponding plate, having a determined thickness which controls expansion of the implant.
2. The expandible implant according to claim 1, further including a groove positioned adjacent each material web having a determined width to allow a clearance between each support and a respective plate.
3. The expandible implant according to claim 1, wherein each support is substantially equal in length to one another.
4. The expandible implant according to claim 1, wherein at least one first support of at least one of the plate is shorter in length than a corresponding second support, such that upon expansion of the implant, the first and second plates move at an angle to one another.
5. The expandible implant according to claims 1, wherein the first and second supports comprise a pair of first and second supports.



6. The expansible implant according to claim 1, wherein the means for controlling expansion of the implant control expansion enabling the implant to expand and retain any determined expansion value between a minimum thickness of the implant before any expansion and a maximum thickness of the implant after its maximum expansion.
7. An expansible implant for bone restoration comprising:
  - a longitudinal axis;
  - a single plane of expansion;
  - at least one plate forming a bearing surface for bone;
  - a first end;
  - a second end, wherein the first and second ends are configured to be brought towards one another to expand the implant to which the at least one plate is directed away from the longitudinal axis upon a force being applied to the ends of the implant;
  - at least one support for at least one plate; and
  - a first zone of material provided between a first end of the at least one support and the at least one plate, wherein the first zone plastically deforms during expansion of the implant for controlling the expansion of the implant.
8. The expansible implant according to claim 7, wherein the first zone of material includes a thickness that is less than the thickness of the at least one support.
9. The implant according to claim 7, further comprising a second zone of material that plastically deforms during expansion of the implant, wherein the second zone of material is provided between a second end of the at least one support and the first end of the implant.
10. The implant according to claim 9, wherein the second zone of material includes a thickness that is less than the thickness of the at least one support.

11. The implant according to claim 7, further comprising a second zone of material that plastically deforms during expansion of the implant, wherein the second zone of material is provided between a second end of the at least one support and the first end of the implant.
12. The implant according to claim 11, wherein the second zone of material includes a thickness that is less than the thickness of the at least one support.
13. The implant according to claim 7, wherein the first zone of material is arranged to project out from the end of the support substantially to a first side of the support.
14. The implant according to claim 11, wherein the second zone of material is arranged to project out from the end of the support substantially to a second side of the support.
15. The implant according to claim 7, wherein the at least one plate comprises two opposed plates respectively forming first and second bearing surfaces for the bone upon expansion of the implant, each plate being directed away from the longitudinal axis of the implant according to the single plane of expansion.
16. An expansible implant comprising:
  - a longitudinal axis;
  - at least one plate forming a bearing surface;
  - a first end;
  - a second end, wherein the first and second ends are configured to be brought towards one another along the longitudinal axis to expand the implant by directing the at least one plate away from the longitudinal axis upon a force being applied to the ends of the implant;
  - at least one support for the at least one plate; and
  - a zone of material provided between the at least one support and the at least one plate plastically deforms during expansion of the implant for controlling the expansion of the implant.



17. The expansible implant according to claim 16, wherein the controlled expansion substantially preserves the implant at any expanded value upon cessation of the longitudinal force.
18. The expansible implant according to claim 17, wherein the expanded value includes any expansion value of the implant up to a maximum thickness of the implant after maximum expansion.
19. The expansible implant according to claim 16, wherein the controlled expansion substantially preserves the implant at any expanded value such that upon cessation of the longitudinal force, expansion of the implant ceases at a determined expanded value and the controlled expansion substantially preserves the implant at the determined expanded value produced as a result of the applied force.
20. The expansible implant according to claim 19, wherein the implant is configured to further expand upon re-applying a longitudinal force.
21. The expansible implant according to claim 16, wherein the longitudinal force is applied to at least one end of the implant.
22. The expansible implant according to claim 16, wherein the longitudinal force is applied to both ends of the implant.
23. The expansible implant according to claim 16, wherein the longitudinal force is a compression force.
24. The expansible implant according to claim 16, wherein the longitudinal force is generated external to the implant.
25. An expansible implant for bone restoration comprising:
  - a single plane of expansion intrinsic to the implant, wherein the single plane of expansion corresponds to a bone restoration plane;
  - first and second opposed plates respectively forming first and a second bearing surfaces for the bone, wherein the first and second plates move away from one another

according to the single plane of expansion at the time of the expansion of the implant;

first and second implant ends substantially aligned along a longitudinal axis of the implant, wherein the first implant end includes an opening for allowing engagement of the implant with an implant carrier, and wherein the first and second implant ends configured to be brought towards one another upon a force being applied thereto resulting in the first and second opposed plates moving away from one another;

at least one pair of first and second supports, wherein each support of a pair of supports includes a first end connected to the first or second plate and a second end connected to the first or second implant ends; and

a first material web provided between each respective support and the corresponding plate the support is connected to, and

a second material web provided between each respective support and the corresponding implant end the support is connected to, wherein

each material web plastically deforms during expansion of the implant to control expansion of the implant, and wherein each material web comprises a reduced thickness portion of a respective support.

26. An expansible implant for bone restoration comprising:

a single plane of expansion;

a longitudinal axis;

at least one plate forming a bearing surface for bone, wherein upon expansion of the implant, the plate is directed away from the implant according to the single plane of expansion at the time of the expansion of the implant;

first and second implant ends substantially aligned along the longitudinal axis of the implant, wherein the first implant end includes an opening for allowing



engagement of the implant with an implant carrier, and wherein the first and second implant ends are configured to be brought towards one another upon a force being applied thereto resulting in the at least one plate moving away from the longitudinal axis;

at least one support connected to at least one plate and to at least one implant end; and

a zone of material provided between the at least one support and at least one of the at least one plate and the at least one implant end, wherein

the zone of material plastically deforms during expansion of the implant for controlling the expansion of the implant and wherein the zone of material comprises a reduced thickness portion of a respective support.

27. An expansible implant comprising:

a longitudinal axis;

at least one plate forming a bearing surface, wherein upon expansion of the implant, the plate is directed away from the longitudinal axis of the implant;

first and second implant ends substantially aligned along the longitudinal axis of the implant, wherein the first implant end includes an opening for allowing engagement of the implant with an implant carrier, and wherein the first and second implant ends are configured to be brought towards one another upon a force being applied thereto resulting in the at least one plate moving away from the longitudinal axis;

at least one support connected to at least one plate and to at least one implant end; and

a zone of material provided between the at least one support and at least one of the at least one plate and the at least one implant end, wherein

the zone of material plastically deforms during expansion of the implant for controlling the expansion of the implant and wherein the zone of material comprises a reduced thickness portion of a respective support.

28. An expansible implant comprising:

a longitudinal axis;

at least one plate forming a bearing surface, wherein upon expansion of the implant the plate is directed away from the longitudinal axis of the implant;

first and second implant ends substantially aligned along the longitudinal axis of the implant, wherein the first implant end includes an opening for allowing engagement of the implant with an implant carrier, and wherein the first and second implant ends are configured to be brought towards one another upon a force being applied thereto resulting in the at least one plate moving away from the longitudinal axis;

at least one support connected to at least one plate and to at least one implant end; and

a zone of material provided between the at least one support and at least one of the at least one plate and the at least one implant end, wherein the zone of material comprises a reduced thickness portion of a respective support.



1/14

FIG. 1A





FIG. 1B



2/14

FIG. 2A




FIG. 2B










FIG. 2C







3/14


**FIG. 3****FIG. 4****FIG. 5****FIG. 6****FIG. 7**

4/14


**FIG. 8****FIG. 9**




5/14

**FIG. 10****FIG. 11**


III-III

**FIG. 12**




IV-IV

**FIG. 13**

V-V

**FIG. 14**

VI-VI

**FIG. 15****FIG. 16**

6/14

FIG. 17




FIG. 18





FIG. 19





7/14

FIG. 20




FIG. 21





FIG. 22



8/14

FIG. 23





FIG. 24





9/14

FIG. 25





FIG. 26



10/14

FIG. 27




FIG. 28





FIG. 29





11/14

FIG. 30




FIG. 31





FIG. 32



12/14

FIG. 33





FIG. 37





13/14

FIG. 34






FIG. 35



14/14

FIG. 36



— Implant L=20mm  
- - - - Implant L=25mm  
- . - . - . Implant L=30mm

