

(51) International Patent Classification:
C07D 307/48 (2006.01)

(21) International Application Number:

PCT/US2012/037206

(22) International Filing Date:

10 May 2012 (10.05.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/489,498 24 May 2011 (24.05.2011) US
13/228,813 9 September 2011 (09.09.2011) US

(71) Applicant: **EASTMAN CHEMICAL COMPANY**
[US/US]; 200 South Wilcox Drive, Kingsport, TN 37660 (US).

(72) Inventors: **SHAIKH, Ashfaq**; 2601 John Dennis Hwy, Apt. 509, Kingsport, TN 37660 (US). **JANKA, Mesfin Ejerssa**; 2459 Wildwood Drive, Kingsport, TN 37660 (US). **LANGE, David Milton**; 128 Sugarfield Lane, Blountville, TN 37617 (US). **MORROW, Michael Charles**; 1704 Cooks Valley Road, Kingsport, TN 37664 (US). **BOWERS, Bradford Russell**; 1285 Robertson Road, Chuckey, TN 37641 (US). **PARKER, Kenny Randolph**; 599 Tyne Gray Road, Afton, TN 37616 (US). **PARTIN, Lee Reynolds**; 101 Partridge Place, Kingsport, TN 37663 (US). **JENKINS, Jason Christopher**; 4536 Chickasaw Road, Kingsport, TN 37664 (US). **MOODY, Paula**; 3322 Pine Timbers Drive, Johnson City, TN 37604

(US). **SHANKS, Thomas Elbert**; 360 Rangewood Road, Piney Flats, TN 37686 (US). **SUMNER, Charles Edwan, Jr.**; 4280 Orebank Road, Kingsport, TN 37664 (US).

(74) Agent: **OWEN, Steven A.**; P.O. Box 511, Kingsport, TN 37662-5075 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: AN OXIDATION PROCESS TO PRODUCE A CRUDE AND/OR PURIFIED CARBOXYLIC ACID PRODUCT




Fig. 1.

(57) Abstract: Disclosed is an oxidation process to produce a crude carboxylic acid product carboxylic acid product. The process comprises oxidizing a feed stream comprising at least one oxidizable compound to generate a crude carboxylic acid slurry comprising furan-2,5-dicarboxylic acid (FDCA) and compositions thereof. Also disclosed is a process to produce a dry purified carboxylic acid product by utilizing various purification methods on the crude carboxylic acid.

AN OXIDATION PROCESS TO PRODUCE A CRUDE AND/OR PURIFIED CARBOXYLIC ACID PRODUCT

5 **FIELD OF THE INVENTION**

The present invention relates to a process to produce a carboxylic acid composition. The process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream in the presence of an oxidizing gas stream, solvent stream, and at least one
10 catalyst system.

More particularly, the present invention relates to a process to produce a carboxylic acid composition comprising furan-2,5-dicarboxylic acid (FDCA) and compositions thereof. The process comprises oxidizing 5-hydroxymethyl)furfural in the presence of oxygen, a
15 saturated organic acid solvent having from 2-6 carbon atoms, and a catalyst system at a temperature of about 100°C to about 220°C to produce the carboxylic acid composition comprising furan-2,5-dicarboxylic acid.

20 **BACKGROUND OF THE INVENTION**

Aromatic dicarboxylic acids, such as terephthalic acid and isophthalic acid, are used to produce a variety of polyester products. Important examples of which are poly (ethylene terephthalate) and its copolymers. These aromatic dicarboxylic acids are synthesized by the
25 catalytic oxidation of the corresponding dialkyl aromatic compounds which are obtained from fossil fuels, which is disclosed in U.S. Patent Application 2006/0205977 A1), which is herein incorporated by reference to the extent it does not contradict the statements herein.

There is a growing interest in the use of renewable resources as
30 feed stocks for the chemical industry mainly due to the progressive reduction of fossil reserves and their related environmental impacts. Furan-2,5-dicarboxylic acid (FDCA) is a versatile intermediate

- 2 -

considered as a promising closest *biobased* alternative to terephthalic acid and isophthalic acid. Like aromatic diacids, FDCA can be condensed with diols such as ethylene glycol to make polyester resins similar to polyethylene terephthalate (PET) (Gandini, A.; Silvestre, A. J.; Neto, C. P.; Sousa, A. F.; Gomes, M. *J. Poly. Sci. A* **2009**, 47, 295.). Therefore, there is a need in the chemical industry for an efficient process to produce carboxylic acid compositions, especially FDCA. A high yield process (minimum of 90% FDCA yield) to produce a dry, purified FDCA product is provided herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates different embodiments of the invention wherein a process to produce a dried purified carboxylic acid **710** is provided.

Figure 2 illustrates an embodiment of the invention, showing the GC chromatogram of the carboxylic acid composition **110** that has been dried.

Figure 3 illustrates an embodiment of the invention, showing a ^1H NMR of the carboxylic acid composition **110** that has been dried.

Figure 4 illustrates an embodiment of the invention, showing a $^{13}\text{C}\{^1\text{H}\}$ NMR of the carboxylic acid composition **110** that has been dried.

Figure 5 illustrates an embodiment of the invention, showing the effects of temperature, pressure, cobalt and bromine concentrations have on the FDCA yield in the carboxylic acid composition **110**.

Figure 6 illustrates an embodiment of the invention, Effect of temperature on yield using an oxidizable raw material stream **30** comprising 5-AMF. The + symbol represents that Co is 2000 ppm and Br is 3000 ppm. The x symbol represents that Co is 2500 ppm and Br is 2500 ppm.

Figure 7 illustrates an embodiment of the invention, Effect of temperature on yield using an oxidizable raw material stream **30** comprising 5-EMF. The + symbol represents that Co is 2000 ppm and Br

is 3000 ppm. The x symbol represents that Co is 2500 ppm and Br is 2500 ppm.

DETAILED DESCRIPTION

5 It should be understood that the following is not intended to be an exclusive list of defined terms. Other definitions may be provided in the foregoing description, such as, for example, when accompanying the use of a defined term in context.

 As used herein, the terms “a,” “an,” and “the” mean one or more.

10 As used herein, the term “and/or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself or any combination of two or more of the listed items can be employed. For example, if a composition is described as containing components A, B, and/or C, the composition can contain A alone; B
15 alone; C alone; A and B in combination; A and C in combination, B and C in combination; or A, B, and C in combination.

 As used herein, the terms “comprising,” “comprises,” and “comprise” are open-ended transition terms used to transition from a subject recited before the term to one or more elements recited after the
20 term, where the element or elements listed after the transition term are not necessarily the only elements that make up the subject.

 As used herein, the terms “having,” “has,” and “have” have the same open-ended meaning as “comprising,” “comprises,” and “comprise” provided above.

25 As used herein, the terms “including,” “includes,” and “include” have the same open-ended meaning as “comprising,” “comprises,” and “comprise” provided above.

 The present description uses numerical ranges to quantify certain parameters relating to the invention. It should be understood that when
30 numerical ranges are provided, such ranges are to be construed as providing literal support for claim limitations that only recite the lower value of the range as well as claim limitations that only recite the upper

value of the range. For example, a disclosed numerical range of 10 to 100 provides literal support for a claim reciting "greater than 10" (with no upper bounds) and a claim reciting "less than 100" (with no lower bounds).

5 The present description uses specific numerical values to quantify certain parameters relating to the invention, where the specific numerical values are not expressly part of a numerical range. It should be understood that each specific numerical value provided herein is to be construed as providing literal support for a broad, intermediate, and
10 narrow range. The broad range associated with each specific numerical value is the numerical value plus and minus 60 percent of the numerical value, rounded to two significant digits. The intermediate range associated with each specific numerical value is the numerical value plus and minus 30 percent of the numerical value, rounded to two
15 significant digits. The narrow range associated with each specific numerical value is the numerical value plus and minus 15 percent of the numerical value, rounded to two significant digits. For example, if the specification describes a specific temperature of 62 °F, such a description provides literal support for a broad numerical range of 25 °F
20 to 99 °F (62 °F +/- 37 °F), an intermediate numerical range of 43 °F to 81 °F (62 °F +/- 19 °F), and a narrow numerical range of 53 °F to 71 °F (62 °F +/- 9 °F). These broad, intermediate, and narrow numerical ranges should be applied not only to the specific values, but should also be applied to differences between these specific values. Thus, if the
25 specification describes a first pressure of 110 psia and a second pressure of 48 psia (a difference of 62 psi), the broad, intermediate, and narrow ranges for the pressure difference between these two streams would be 25 to 99 psi, 43 to 81 psi, and 53 to 71 psi, respectively

 In one embodiment of the invention, a process is provided to
30 produce carboxylic acid composition and/or dry purified carboxylic acid **710** comprising furan-2,5-dicarboxylic acid (FDCA). Embodiments of the process are represented in **Figure 1**. The process comprises oxidizing

- 5 -

at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system. The oxidizable raw material stream **30** comprises at least one oxidizable compound suitable to produce a carboxylic acid composition **110** comprising FDCA. The amount of FDCA in the carboxylic acid composition **110** can range from greater than 10 by weight percent in the carboxylic acid composition **110**, greater than 20 by weight percent in the carboxylic acid composition **110**, greater than 30 by weight percent in the carboxylic acid composition **110**. The carboxylic acid composition **110** comprises FDCA and solvent.

In another embodiment of the invention, the process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system. The oxidizable raw material stream **30** comprises at least one oxidizable compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), 5-alkyl furfurals (5-R''-furfural, where R'' = alkyl, cycloalkyl and aryl), mixed feedstocks of 5-HMF and 5-HMF esters, mixed feedstocks of 5-HMF and 5-HMF ethers, mixed feedstocks of 5-HMF and 5-alkyl furfurals to generate a carboxylic acid composition comprising FDCA. The process can optionally include removing impurities from the carboxylic acid composition **110** in a liquid displacement zone **225** to form a low impurity slurry stream **210**. The low impurity slurry stream **210** can be further treated in a secondary oxidation zone **335** to produce a secondary oxidation slurry stream **310** which can be routed to a crystallization zone **425** to form a crystallized slurry stream **410**. The crystallized slurry stream **410** is cooled in a cooling zone **430** and the cooled crystallized slurry stream **510** can be routed to a solid-liquid separation zone **625** to generate a purified wet cake stream **610** comprising FDCA that is dried

- 6 -

in a drying zone **725** to generate a dried, purified carboxylic acid **710** comprising purified FDCA.


In one embodiment of the invention, a process is provided to produce a dried, purified carboxylic acid **710** comprising dried, purified furan-2,5-dicarboxylic acid (FDCA) and comprises the following steps:

Step (a) comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system in a primary oxidation zone **125** which comprises at least one primary oxidizer reactor to produce a carboxylic acid composition **110** comprising furan-2,5-dicarboxylic(FDCA); wherein the oxidizable raw material stream **30** comprises at least one oxidizable compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), 5-alkyl furfurals (5-R''-furfural, where R'' = alkyl, cycloalkyl and aryl), mixed feedstocks of 5-HMF and 5-HMF esters, mixed feedstocks of 5-HMF and 5-HMF ethers, and mixed feedstocks of 5-HMF and 5-alkyl furfurals. Structures for the various oxidizable raw material compounds are outlined below:

25


- 7 -

Preferred 5-HMF Derivative Feeds



The 5-HMF or its derivatives are oxidized with elemental O₂ in a multi-step reactions, eqs 1 and 2, to form FDCA with 5-formyl furan-2-carboxylic acid (FFCA) as a key intermediate.

5



In one embodiment of this invention, streams routed to the primary oxidation zone **125** comprises an oxidizing gas stream **10** comprising oxygen and a solvent stream **20** comprising solvent, an oxidizable raw material stream **30**, and a catalyst system. Oxidizable raw material stream 30 comprises a continuous liquid phase. In another embodiment of the invention, the oxidizable raw material stream **30**, the oxidizing gas stream **10**, the solvent stream **20** and the catalyst system can be fed to the primary oxidization zone **125** as separate and

individual streams or combined in any combination prior to entering the primary oxidation zone **125** wherein said feed streams may enter at a single location or in multiple locations in the primary oxidization zone **125**.

5 The carboxylic acid composition **110** comprises FDCA and FFCA. In another embodiment the FFCA in the carboxylic acid composition **110** ranges from about 0.1 wt% (weight percent) to about 4 wt% or 0.1 wt% to about 0.5 wt%, or 0.1wt% to about 1wt%. In another embodiment of the invention the carboxylic acid composition **110** comprises FDCA and
10 FFCA and at least one of 2,5-diformylfuran in an amount ranging from 0 wt% to about 0.2 wt%, levulinic acid in an amount ranging from 0 wt% to 0.5 wt%, succinic acid in an amount ranging from 0 wt% to 0.5 wt% and acetoxo acetic acid in an amount ranging from 0 wt% to 0.5 wt%.
In another embodiment of the invention the carboxylic acid composition
15 **110** comprises FDCA, FFCA and EFCA. In other embodiment of the invention the EFCA in the carboxylic acid composition **110** in an range from about 0.05 wt% to 4 wt%, or about 1 wt% to 2 wt%.

The catalyst system comprises at least one catalyst suitable for oxidation. Any catalyst known in the art capable of oxidizing the
20 oxidizable compound can be utilized. Example of suitable catalysts comprise at least one selected from, but are not limited to, cobalt, bromine and manganese compounds, which are soluble in the selected oxidation solvent. In another embodiment of the invention, the catalyst system comprises cobalt, manganese and bromine wherein the weight
25 ratio of cobalt to manganese in the reaction mixture is from about 10 to about 400 and the weight ratio of cobalt to bromine is from about 0.7 to about 3.5.

The oxidizing gas stream comprises oxygen. Examples include, but are not limited to, air and purified oxygen. The amount of oxygen in
30 the primary oxidation zone ranges from about 5 mole % to 45 mole %, 5 mole % to 60 mole % 5 mole % to 80 mole %.

Suitable solvents include water and the aliphatic solvents. In an embodiment of the invention, the solvents are aliphatic carboxylic acids which include, but are not limited to, aqueous solutions of C₂ to C₆ monocarboxylic acids, e.g., acetic acid, propionic acid, n-butyric acid, isobutyric acid, n-valeric acid, trimethylacetic acid, caprioic acid, and mixtures thereof. In another embodiment of the invention, the solvent is volatile under the oxidation reaction conditions to allow it to be taken as an off-gas from the oxidation reactor. In yet another embodiment of the invention the solvent selected is also one in which the catalyst composition is soluble under the reaction conditions.

The most common solvent used for the oxidation is an aqueous acetic acid solution, typically having a concentration of 80 to 99 wt. %. In especially preferred embodiments, the solvent comprises a mixture of water and acetic acid which has a water content of 0% to about 15% by weight. Additionally, a portion of the solvent feed to the primary oxidation reactor may be obtained from a recycle stream obtained by displacing about 80 to 90% of the mother liquor taken from the crude reaction mixture stream discharged from the primary oxidation reactor with fresh, wet acetic acid containing about 0 to 15% water.

Suitable solvents include, but are not limited to, aliphatic mono-carboxylic acids, preferably containing 2 to 6 carbon atoms and mixtures thereof and mixtures of these compounds with water. Examples of aliphatic mono-carboxylic acids, include, but are not limited to acetic acid.

Generally, the oxidation temperature can vary from about 100°C to about 220°C and from about 110°C to about 160°C.

In another embodiment of the invention, a process is provided to produce furan-2,5-dicarboxylic acid (FDCA) in high yields by liquid phase oxidation that minimizes solvent and starting material loss through carbon burn. The process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst

- 10 -

system in a primary oxidation zone **125**; wherein the oxidizable compound is at least one selected from the group consisting of $\text{H}(\text{C}=\text{O})\text{-R}(\text{C}=\text{O})\text{H}$, $\text{HOH}_2\text{C-R}(\text{C}=\text{O})\text{H}$, and 5-(hydroxymethyl)furfural (5-HMF). The oxidizable compound can be oxidized in a solvent comprising acetic acid with or without the presence of water with oxygen in the presence of a catalyst system comprising cobalt, manganese and bromine, wherein the weight ratio of cobalt to manganese in the reaction mixture is from about 10 to about 400 and the weight ratio of cobalt to bromine is from about 0.7 to about 3.5. Such a catalyst system with improved Co:Mn ratio can lead to high yield of FDCA. In this process, the oxidation temperature can vary from about 100°C to about 220°C, or another range from about 110°C to about 160°C, which can minimize carbon burn. The cobalt concentration of the catalyst can range from about 1000 ppm to about 6000 ppm, and the amount of manganese from about 2 ppm to about 600 ppm, and the amount of bromine from about 300 ppm to about 4500 ppm with respect to the total weight of the liquid in the reaction medium of the primary oxidation zone **125**. As used herein, process temperature is the temperature of the reaction mixture within the primary oxidation zone where liquid is present as the continuous phase. The primary oxidizer reactor will typically be characterized by a lower section where gas bubbles are dispersed in a continuous liquid phase. Solids can also be present in the lower section. In the upper section of the primary oxidizer, gas is in the continuous phase and entrained liquid drops can also be present.

In various embodiments of the invention, the catalyst compositions employed in the processes of the invention comprise cobalt atoms, manganese atoms, and bromine atoms, supplied by any suitable means, as further described below. The catalyst composition is typically soluble in the solvent under reaction conditions, or it is soluble in the reactants fed to the oxidation zone. Preferably, the catalyst composition is soluble in the solvent at 40°C. and 1 atm, and is soluble in the solvent under the reaction conditions.

5 The cobalt atoms may be provided in ionic form as inorganic cobalt salts, such as cobalt bromide, cobalt nitrate, or cobalt chloride, or organic cobalt compounds such as cobalt salts of aliphatic or aromatic acids having 2-22 carbon atoms, including cobalt acetate, cobalt octanoate, cobalt benzoate, cobalt acetylacetonate, and cobalt naphthalate.

10 The oxidation state of cobalt when added as a compound to the reaction mixture is not limited, and includes both the +2 and +3 oxidation states.

15 The manganese atoms may be provided as one or more inorganic manganese salts, such as manganese borates, manganese halides, manganese nitrates, or organometallic manganese compounds such as the manganese salts of lower aliphatic carboxylic acids, including manganese acetate, and manganese salts of beta-diketonates, including manganese acetylacetonate.

20 The bromine component may be added as elemental bromine, in combined form, or as an anion. Suitable sources of bromine include hydrobromic acid, sodium bromide, ammonium bromide, potassium bromide, and tetrabromoethane. Hydrobromic acid, or sodium bromide may be preferred bromine sources.

25 In another embodiment of the invention, a process is provided for producing furan-2,5-dicarboxylic acid (FDCA) in high yields by liquid phase oxidation that minimizes solvent and starting material loss through carbon burn. The process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system in a primary oxidation zone **125**; wherein the oxidizable compound is selected from the group consisting of 5-

30

- 12 -

(acetoxymethyl)furfural (5-AMF), 5-(ethoxymethyl)furfural (5-EMF), 5-methyl furfural (5-MF); wherein the solvent stream 20 comprises acetic acid with or without the presence of water; wherein the catalyst system comprising cobalt, manganese and bromine, wherein the weight ratio of cobalt to manganese in the reaction mixture ranges from about 10 to about 400 and the weight ratio of cobalt to bromine is from about 0.7 to about 3.5. The catalyst system with improved Co:Mn ratio can lead to high yield of FDCA. In this process, the oxidation temperature can vary from about 100 °C to about 220 °C, or from about 110 °C to about 160 °C to minimize carbon burn. The cobalt concentration in the catalyst system can range from about 500 ppm to about 6000 ppm, and the amount of manganese from about 2 ppm to about 600 ppm and the amount of bromine from about 300 ppm to about 4500 ppm with respect to the total weight of the liquid in the reaction medium. Mixed feedstocks of 5-AMF and 5-HMF or 5-EMF and 5-HMF or 5-MF and 5-HMF or 5-AMF, 5-EMF and 5-HMF, with varying ratios of the components can be used and similar results can be obtained.

In another embodiment of the invention, a process is provided for producing furan-2,5-dicarboxylic acid (FDCA) in high yields by liquid phase oxidation that minimizes solvent and starting material loss through carbon burn. The process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system in a primary oxidation zone **125**; wherein said oxidizable compound is 5-(hydroxymethyl)furfural (5-HMF); wherein said solvent stream comprises acetic acid with or without the presence of water; wherein said catalyst system comprising cobalt, manganese and bromine, wherein the weight ratio of cobalt to manganese in the reaction mixture is from about 10 to about 400. In this process, the temperature can vary from about 100°C to about 220°C, from about 105°C to about 180°C, and from about 110°C to about 160°C. The cobalt concentration of the catalyst system can range from about 1000 ppm to about 6000

ppm, and the amount of manganese can range from about 2 ppm to about 600 ppm, and the amount of bromine can range from about 300 ppm to about 4500 ppm with respect to the total weight of the liquid in the reaction medium.

5 In another embodiment of the invention, the process comprises oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system in a primary oxidation zone **125**; wherein said oxidizable compound is 5-(hydroxymethyl)furfural (5-HMF);
10 wherein said solvent stream comprises a saturated organic acid having from 2-6 carbon atoms with or without the presence of water at a temperature of 100°C to 220°C to produce a dicarboxylic acid composition; wherein the primary oxidation zone **125** comprises at least one primary oxidation reactor and wherein the catalyst system
15 comprises cobalt in a range from about 500 ppm by weight to about 6000 ppm by weight with respect to the weight of the liquid in the reaction medium, manganese in an amount ranging from about 2 ppm by weight to about 600 ppm by weight with respect to the weight of the liquid in the reaction medium and bromine in an amount ranging from
20 about 300 ppm by weight to about 4500 ppm by weight with respect to the weight of the liquid in the reaction medium.

 In another embodiment of the invention, when the oxidizable raw material stream **30** comprises 5-HMF, then the cobalt to manganese ratio by weight is at least 10:1, 15:1, 20:1, 25:1, 30:1, 40:1 50:1, 60:1,
25 or 400 to 1.

 In another embodiment of the invention, when the oxidizable material stream **30** comprises at least one oxidizable compound selected from the group consisting of 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), 5-alkyl furfurals (5-R''-furfural, where R'' = alkyl, cycloalkyl and aryl), mixed feedstocks of 5-HMF and 5-HMF esters, mixed feedstocks of 5-HMF and 5-HMF ethers,
30

- 14 -

and mixed feed-stocks of 5-HMF and 5-alkyl furfurals, the cobalt to manganese ratio by weight of the catalyst system is at least 1:1, 10:1, 20:1, 50:1, 100:1, or 400:1.

5 In another embodiment of this invention, furan-2,5-dicarboxylic acid (FDCA) can be obtained by liquid phase oxidation of 5-(hydroxymethyl)furfural (5-HMF), 5-(acetoxymethyl)furfural (5-AMF) and 5-(ethoxymethyl)furfural (5-EMF) with molecular oxygen using Co/Mn/Br catalyst system in acetic acid solvent. After the oxidation of 5-HMF/5-AMF/5-EMF in presence of acetic acid, the FDCA precipitates out of
10 solution. After filtration, washing with acetic acid and then with water, and drying, solids were obtained with a minimum of 90%, 92%, 94%, 96% FDCA content by weight.

In another embodiment of the invention, FDCA is obtained by liquid phase oxidation of 5-HMF, 5-AMF and 5-EMF with molecular
15 oxygen using Co/Mn/Br catalyst system in acetic acid solvent. After the oxidation of 5-HMF/5-AMF/5-EMF in acetic acid, the FDCA precipitates out of solution. After filtration, washing with acetic acid and then with water, and drying, solids were obtained with a minimum of 96% FDCA content and a maximum b* of 15, 16, 17, 18, 19, or 20.

20 The b* is one of the three-color attributes measured on a spectroscopic reflectance-based instrument. The color can be measured by any device known in the art. A Hunter Ultrascan XE instrument is typically the measuring device. Positive readings signify the degree of yellow (or absorbance of blue), while negative readings signify the
25 degree of blue (or absorbance of yellow).

In another embodiment of the invention, a process is provided for producing furan-2,5-dicarboxylic acid (FDCA) in minimum yields of 80% or 85% or 90% or greater by liquid phase oxidation that minimizes solvent and starting material loss through carbon burn. As used herein,
30 yield is defined as mass of FDCA obtained divided by the theoretical amount of FDCA that should be produced based on the amount of raw material use. For example, if one mole or 126.11 grams of 5-HMF are

- 15 -

oxidized, it would theoretically generate one mole or 156.01 grams of FDCA. If for example, the actual amount of FDCA formed is only 150 grams, the yield for this reaction is calculated to be = $(150/156.01)$ times 100, which equals a yield of 96%. The same calculation applies for oxidation reaction conducted using 5-HMF derivatives or mixed feeds.

In another embodiment of this invention, a process is provided comprising oxidizing at least one oxidizable compound in an oxidizable raw material stream **30** in the presence of an oxidizing gas stream **10**, solvent stream **20**, and at least one catalyst system in a primary oxidation zone **125**; wherein said oxidizable compound is selected from the group consisting of $\text{H}(\text{C}=\text{O})\text{-R}(\text{C}=\text{O})\text{H}$, $\text{HOH}_2\text{C-R}(\text{C}=\text{O})\text{H}$, 5-(hydroxymethyl)furfural (5-HMF); wherein said solvent stream comprises acetic acid with or without the presence of water; wherein said catalyst system comprises cobalt, manganese and bromine, wherein the weight ratio of cobalt to manganese in the reaction mixture is from about 10 to about 400 and the weight ratio of cobalt to bromine is from about 0.7 to about 3.5. Such a catalyst system with improved Co:Mn and Co:Br ratio can lead to high yield of FDCA (minimum of 90%), decrease in the formation of impurities (measured by b^*) causing color in the downstream polymerization process while keeping the amount of CO and CO_2 in the off-gas at a minimum.

The temperature in the primary oxidation zone can range from about 100 °C to about 220 °C, and can range from about 110 °C to about 160 °C or can range from about 105 °C to about 180 °C or about 100 °C to about 200 °C, or about 100 °C to about 190 °C. One advantage of the disclosed primary oxidation conditions is low carbon burn as illustrated in Table 1. Oxidizer off gas stream **120** is routed to the oxidizer off gas treatment zone 825 to generate an inert gas stream **810**, liquid stream **820** comprising water, and a recovered solvent stream **830** comprising condensed solvent. In one embodiment, at least a portion of recovered solvent stream **830** is routed to wash feed stream **620** and the combined stream is routed to the solid-liquid separation zone **625** for the purpose

- 16 -

of washing the solids present in the solid-liquid separation zone **625**. In one embodiment, the inert gas stream **810** can be vented to the atmosphere. In another embodiment, at least a portion of the inert gas stream **810** can be used as an inert gas in the process for inerting vessels and or used for conveying gas for solids in the process.

In another embodiment of the invention, the composition of the liquid phase within the primary oxidizer can have a pH from about -4.0 to about 1.0 or the feedstock pH is from about -1.8 to about 1.0, or the feedstock pH is from about -1.5 to about 1.0.

It should be understood that steps (b)- (g) are optional and only one possible embodiment of a process to purified the carboxylic acid composition.

Step (b) comprises routing the crude carboxylic composition **110** and fresh solvent stream **220** to a liquid displacement zone **225** to produce a displaced mother liquor stream **230** and low impurity slurry stream **210** comprising FDCA. The displaced mother liquor stream **230** comprises solvent and soluble matter dissolved in the solvent comprising dissolved impurities and dissolved catalyst. In various embodiments of the invention, from about 5% to about 99%, from about 30% to about 90%, and most preferably from about 50 to about 85% of mother liquor present in the carboxylic acid composition **110** is displaced in the liquid displacement zone **225** resulting in dissolved matter comprising impurities present in the displaced mother liquor not going forward in the process. Sufficient fresh solvent is fed to the liquid displacement zone **225** that becomes mixed with solids present resulting in a low impurity slurry stream **210** being pumpable with weight % solids ranging from 1% to 50%, 10% to 40%, and preferably the weight % solids in stream **210** will range from 25% to 38%.

The liquid displacement zone may be a single unit operation or multiple unit operations. In one embodiment of the invention, the liquid displacement zone **225** may be any solid-liquid separation device

- 17 -

capable of generating an isolated wet cake from a feed slurry and then mixing the isolated wet cake with fresh solvent in a separate mixing device to generate the low impurity slurry stream **210**. Examples of suitable solid-liquid separation devices include, but are not limited to, a continuous pressure drum filter, solid bowl centrifuges including, but not limited to, decanter and disc stack centrifuges, and batch pressure filters including, but not limited to, candle and leaf filters. The preferred solid-liquid separation device for this application is a continuous pressure drum filter. The solid-liquid separator is operated at temperatures between about 30 degrees C. to about 200 degrees C., preferably 80 degrees C. to about 170.degree. C. The solid-liquid separator in the liquid displacement zone **225** may be operated in continuous or batch mode, although it will be appreciated that for commercial processes, the continuous mode is preferred. Alternatively, a portion of the mother liquor in stream **110** is displaced with fresh liquor stream **220** in a single device to form the low impurity slurry stream **210** without forming an isolated wet cake.

In one embodiment, from 5% to 100% by weight of the displaced mother liquor stream **230** is routed to a purge zone **235** wherein a portion of the impurities present in stream **230** are isolated and exit the process as purge stream **920**, wherein a portion is 5% by weight or greater. Recovered solvent stream **910** comprises solvent and catalyst isolated from stream **230** and is recycled to the process. In one embodiment, recovered solvent stream **910** is recycled to the primary oxidation zone **125** and contains greater than 30% of the catalyst that entered the purge zone **235** in stream **230**. In another embodiment, stream **910** is recycled to the primary oxidation zone **125** and contains greater than 50 weight %, contains greater than 70 weight %, and preferably greater than 90 weight % of the catalyst that enters the purge zone **235** in stream **230** on a continuous or batch basis.

In another embodiment of this invention, a portion up to 100% of the carboxylic acid composition **110** may be routed directly to a

secondary oxidation zone **335** without being subjected to the liquid displacement zone **225**. In another embodiment of the invention, up to 100% of the feed to the purge zone **235** may be a mother liquor stream **630** generated in a solid-liquid separation zone **625** which also produces the purified wet cake stream **610**.

In yet another embodiment, up to 100% of the feed to the purge zone **235** may be mother liquor generated in a secondary liquid displacement zone located at some location downstream of the secondary oxidation zone **325**. A secondary liquid displacement zone is not shown in Figure 1, and it comprises equipment like that described for the liquid displacement zone **225** located after the primary oxidation zone **125**, and must be located after the secondary oxidation zone **335**.

Step (c) comprises oxidizing the low impurity slurry stream **210** in a secondary oxidation zone **335** to form a purified slurry stream **310**. In one embodiment of the invention, the low impurity slurry stream **210** is routed to a secondary oxidation zone **335** where it is heated to between about 115 degrees C. and about 220 degrees C., and preferably between about 120 degrees C. to about 200 degrees C. and further oxidized with an oxidizing gas, such as air, fed by line **320** to produce a purified slurry stream **310**. The secondary oxidation zone comprises at least one oxidation reactor vessel. In one embodiment, the secondary oxidation zone can be one or more oxidation vessels. When the carboxylic acid in low impurity slurry stream **210** is FDCA, the secondary oxidation zone is operated at a temperature ranging from about 115 degrees C. to about 220 degrees C., preferably between about 120 degrees C. to about 200 degrees C., and stream **210** is further oxidized with an oxidizing gas stream fed by line **320** to produce a purified slurry stream **310**.

Generally, oxidation in the secondary oxidation zone **335** is at a higher temperature than the oxidation in the primary oxidation zone **125** to enhance the impurity removal. In one embodiment, the secondary

oxidation zone **335** is operated at about 30°C, 20°C, and preferably 10°C higher temperature than the oxidation temperature in the primary oxidation zone **125** to enhance the impurity removal. The secondary oxidation zone **335** can be heated directly with solvent vapor, or steam
5 via stream **320** or indirectly by any means known in the art.

Additional purification of the low impurity slurry stream **210** is accomplished in the secondary oxidation zone by a mechanism involving recrystallization or crystal growth and oxidation of impurities and intermediates including FFCA. One of the functions of the secondary
10 oxidation zone is to convert FFCA to FDCA. FFCA is considered monofunctional relative to a polyester condensation reaction because it contains only one carboxylic acid. FFCA is present in the carboxylic acid composition stream **110** and the low impurity slurry stream **210**. FFCA is generated in the primary oxidation zone **125** because the reaction of 5-
15 HMF to FFCA can be about eight times faster than the reaction of FFCA to the desired di-functional product FDCA. Additional air or molecular oxygen may be fed in stream **320** to the secondary oxidation zone **335** in an amount necessary to oxidize a substantial portion of the partially oxidized products such as FFCA in the stream **210** to the corresponding
20 carboxylic acid FDCA. Generally, at least 70% by weight of the FFCA present in the low impurity slurry stream **210** is converted to FDCA in the secondary oxidation zone **335**. Preferably, at least 80% by weight of the FFCA present in the low impurity slurry stream **210** is converted to FDCA in the secondary oxidation zone **335**, and most preferably, at least
25 90% by weight of the FFCA present in the low impurity slurry stream **210** is converted to FDCA in the secondary oxidation zone **335**. Significant concentrations of monofunctional molecules like FFCA in the dried, purified FDCA product are particularly detrimental to polymerization processes as they may act as chain terminators during the polyester
30 condensation reaction.

The amount of oxygen fed in the secondary oxidation zone **335** in controlled to limit the burning of organic molecules to CO₂. The amount

- 20 -

of oxygen in stream **330** is monitored and used to control the amount of oxygen fed in stream **320**. Another function of the secondary oxidation zone **335** is to dissolve and recrystallize solids present in the low impurity slurry stream **210** fed to the secondary oxidation zone. At least
5 10% by weight, 25% by weight, 50% by weight, and preferably at least 85% by weight of solid impurities and oxidation by-products in stream **210** feed to the secondary oxidation zone **335** go into solution as the FDCA particles are dissolved and re-crystallized in the secondary oxidation zone **335**. Off gas from the secondary oxidation zone is
10 withdrawn via line **330** and fed to a recovery system where the solvent is removed from the off gas comprising volatile organic compounds (VOCs). VOCs including methyl bromide may be treated, for example by incineration in a catalytic oxidation unit. The purified slurry stream **310** generated in the secondary oxidation zone is routed to the crystallization
15 zone **425**.

Step (d) comprises crystallizing the secondary oxidation slurry **310** in a crystallization zone **425** to form a crystallized slurry stream **410**. Generally, the crystallization zone **425** comprises at least one
20 crystallizer. Vapor from the crystallization zone can be condensed in at least one condenser and returned to the crystallization zone **425** or routed away from crystallization zone **425**. Optionally, the liquid from the condenser or vapor product from the crystallization zone can be recycled, or it can be withdrawn or sent to an energy recovery device.
25 In addition, the crystallizer off gas is removed via line **420** and can be routed to a recovery system where the solvent is removed, and crystallizer off gas comprising VOCs may be treated, for example, by incineration in a catalytic oxidation unit. When the carboxylic acid is FDCA, the purified slurry stream **310** from the secondary oxidation
30 zone **335** is fed to a crystallization zone **425** comprising at least one crystallizer where it is cooled to a temperature between about 40 degrees C. to about 175 degrees C. to form a crystallized slurry

- 21 -

stream **410**, preferably to a temperature between about 50 degrees C. to about 170 degrees C., and most preferably from about 60 degrees C. to about 165 degrees C.

5 The crystallized slurry stream **410** is then routed to a cooling zone **430** to generate a cooled crystallized slurry stream **510**. The cooling of the crystallized slurry stream **410** can be accomplished by any means known in the art. Typically, the cooling zone **430** comprises a flash tank. The temperature of stream **510** can range from 35 °C to 160 °C, 45 °C to 120 °C, and preferably from 55 °C to 95 °C.

10 In another embodiment, a portion of up to 100% of the secondary oxidation slurry stream **310** is routed directly to the cooling zone **425**, thus the portion is not subjected to a crystallization zone **430**. In yet another embodiment, a portion of up to 100% of the crystallized slurry stream **410** is routed directly to a secondary liquid displacement zone which is not illustrated in Figure 1. Up to 100% of the slurry effluent comprising FDCA from a secondary liquid displacement zone can be routed to the solid-liquid separation zone **625** and or routed directly to the cooling zone **430**. The function of the secondary liquid displacement zone is to displace a portion of solvent in the crystallized slurry stream **410** with fresh solvent and or water wherein a portion must be greater than 5 weight percent. The secondary liquid displacement zone is separate and distinct from the liquid displacement zone **225** located after the primary oxidation zone **125**. The same type of equipment may be used for both the primary and secondary liquid displacement zones. In yet another embodiment, crystallized slurry stream **410** can be routed directly to the solid-liquid separation zone **625** without being first processed in the cooling zone **430**.

25 **Step (e)** comprises isolating, washing, and dewatering solids present in the cooled, crystallized slurry stream **510** in the solid-liquid separation zone **625**. These functions may be accomplished in a single solid-liquid separation device or multiple solid-liquid separation

30

devices. The solid-liquid separation zone **625** comprises at least one solid-liquid separation device capable of separating solids and liquids, washing solids with a wash solvent stream **620**, and reducing the % moisture in the washed solids to less than 30 weight %, less than 25 weight %, less than 20 weight% , less than 15 weight %, and preferably less than 10 weight %.

Equipment suitable for the solid liquid separation zone **625** can typically be comprised of, but not limited to, the following types of devices: centrifuges, cyclones, rotary drum filter, belt filters, pressure leaf filters, candle filters, etc. The preferred solid liquid separation device for the solid liquid separation zone **625** is a rotary pressure drum filter. The temperature of the cooled, crystallized slurry steam **510** which is routed to the solid-liquid separation zone **625** can range from 50°C to 140°C, 70°C to 120°C, and is preferably from 75°C to 95°C. The wash solvent stream **620** comprises a liquid suitable for displacing and washing mother liquor from the solids.

In one embodiment of the invention, a suitable wash solvent comprises acetic acid and water. In another embodiment, a suitable solvent comprises water up to 100% water. The temperature of the wash solvent can range from 20°C to 135°C, 40°C and 110°C, and preferably from 50°C to 90°C. The amount of wash solvent used is defined as the wash ratio and equals the mass of wash divided by the mass of solids on a batch or continuous basis. The wash ratio can range from about 0.3 to about 5, about 0.4 to about 4, and preferably from about 0.5 to 3.

After solids are washed in the solid liquid separation zone, they are dewatered. Dewatering involves reducing the mass of moisture present with the solids to less than 30% by weight, less than 25% by weight, less than 20% by weight, less than 15% by weight, and most preferably less than 10% by weight resulting in the generation of a purified wet cake stream **610**. In one embodiment, dewatering is accomplished in a filter by passing a gas stream through the solids to

- 23 -

displace free liquid after the solids have been washed with a wash solvent. In another embodiment, dewatering is achieved by centrifugal forces in a perforated bowl or solid bowl centrifuge. Stream **630** generated in the solid-liquid separation zone **625** is a mother liquor stream comprising oxidation solvent, catalyst, and some impurities and oxidation byproducts. In one embodiment, a portion of stream **630** is routed to a purge zone **235** and a portion is routed back to the primary oxidation zone **125** wherein a portion is at least 5 weight %. Wash liquor stream **640** is also generated in the solid-liquid separation zone **625** and comprises a portion of the mother liquor present in stream **510** and wash solvent wherein the ratio of mother liquor mass to wash solvent mass is less than 3 and preferably less than 2.

Step (f) comprises drying the purified wet cake stream **610** in a drying zone **725** to generate a dry purified carboxylic acid **710** and a vapor stream **720**. In one embodiment, vapor stream **720** comprises wash solvent vapor. In another embodiment, vapor stream **720** comprises oxidation solvent and wash solvent. The drying zone **725** comprises at least one dryer and can be accomplished by any means known in the art that is capable of evaporating at least 10% of the volatiles remaining in the purified wet cake stream **610** to produce the dried, purified carboxylic acid **710** comprising purified FDCA and a vapor stream **720**. For example, indirect contact dryers include, but are not limited to, a rotary steam tube dryer, a Single Shaft Porcupine ^{RTM} dryer, and a Bepex Solidaire ^{RTM} dryer. Direct contact dryers include, but are not limited to, a fluid bed dryer and drying in a convey line can be used for drying to produce stream **710**. The dried, purified carboxylic acid **710** comprising purified FDCA can be a carboxylic acid composition with less than 8% moisture, preferably less than 5% moisture, and more preferably less than 1% moisture, and even more preferably less than 0.5%, and yet more preferably less than 0.1%. In another embodiment of this invention, if the liquid portion of the purified wet cake stream **610**

- 24 -

comprises water and contains less than 0.1 weight % acetic acid, less than 500 ppm wt acetic acid, and preferably less than 200 ppm wt, the stream **610** can be fed directly to a polymerization zone without first being dried.

5 In one embodiment of the invention, a vacuum system can be utilized to draw vapor stream **720** from the drying zone **725**. If a vacuum system is used in this fashion, the pressure of stream **720** at the dryer outlet can range from about 760 mmHg to about 400 mmHg, from about 760 mmHg to about 600 mmHg, from about 760 mmHg to about 700
10 mmHg, from about 760 mmHg to about 720 mmHg, and from about 760 mmHg to about 740 mmHg wherein pressure is measured in mmHg above absolute vacuum. The contents of the conduit between solid-liquid separation zone **625** and drying zone **725** utilized to transfer the purified wet cake stream **610** comprises wet cake stream and gas
15 wherein gas is the continuous phase. The pressure at the exit of the solid liquid separation zone **625** can be close to that of the pressure where vapor stream **720** exits the drying zone **725**, wherein close is defined as within 2 psig, within 0.8 psig, and preferably within 0.4 psig.

 In an embodiment of the invention, the dried, purified carboxylic
20 acid **710** has a b^* less than about 9.0. In another embodiment of the invention, the b^* color of the dried, purified carboxylic acid **710** is less than about 6.0. In another embodiment of the invention, the b^* color of the dried, purified carboxylic acid **710** is less than about 5.0. In another
25 embodiment of the invention, the b^* color of the dried, purified carboxylic acid **710** is less than about 4.0. In another embodiment of the invention, the b^* color of the dried, purified carboxylic acid **710** is less than about 3. The b^* color is one of the three-color attributes measured on a spectroscopic reflectance-based instrument. A Hunter Ultrascan XE
30 instrument in reflectance mode is typically the measuring device. Positive readings signify the degree of yellow (or absorbance of blue), while negative readings signify the degree of blue (or absorbance of yellow).

- 25 -

It should be appreciated that the process zones previously described can be utilized in any other logical order to produce the dried, purified carboxylic acid **710**. It should also be appreciated that when the process zones are reordered that the process conditions may change. It is also understood that all percent values are weight percents.

Step (g) is an optionally step comprising decolorizing the FDCA in this process or an esterified FDCA with a diol stream via hydrogenation. In one embodiment, the diol stream comprises ethylene glycol. In another embodiment, the diol stream comprises isomers of cyclohexane diol, preferably the 1-4 cyclohexane diol isomer. The decolorizing of the FDCA in this process or an esterified FDCA can be accomplished by any means known in the art and is not limited to hydrogenation. However, for example, in one embodiment of the invention, the decolorizing can be accomplished by reacting a carboxylic acid that has undergone esterification treatment, for example with ethylene glycol, with molecular hydrogen in the presence of a hydrogenation catalyst in a reactor zone to produce a decolorized carboxylic acid solution or a decolorized ester product.

For the reactor zone, there are no special limitations in the form or construction thereof, subject to an arrangement that allows supply of hydrogen to effect intimate contact of the carboxylic acid or ester product with the catalyst in the reactor zone. Typically, the hydrogenation catalyst is usually a single Group VIII metal or combination of Group VIII metals. Preferably, the catalyst is selected from a group consisting of palladium, ruthenium, rhodium and combination thereof. The reactor zone comprises a hydrogenation reactor that operates at a temperature and pressure sufficient to hydrogenate a portion of the characteristically yellow compounds to colorless derivatives.

Since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit this invention to the exact process and operations illustrated and described above, and accordingly

all suitable modifications and equivalents may be resorted to, falling within the scope of the invention

Examples:

5

This invention can be further illustrated by the following examples of embodiments thereof, although it will be understood that these examples are included merely for the purposes of illustration and are not intended to limit the scope of the invention unless otherwise specifically indicated.

10

Examples Set 1

In Examples 1a-3d, glacial acetic acid and the catalyst components in concentrations described in **Tables 1, 2 and 3** were transferred to a 300 mL titanium autoclave equipped with a high pressure condenser, a baffle and an Isco pump. Cobalt, manganese and ionic bromine were provided as cobalt (II) acetate tetrahydrate, manganese (II) acetate and sodium bromide and/or aqueous hydrobromic acid respectively. The autoclave was pressurized with approximately 50 psig of nitrogen and the homogeneous mixture was heated to the desired temperature in a closed system (i.e., with no gas flow) with stirring. At reaction temperature, an air flow of 1500 sccm was introduced at the bottom of the solution and the reaction pressure was adjusted to the desired pressure. A solution of 5-HMF/5-AMF/5-EMF in acetic acid was fed to the mixture at a rate of 0.833 mL/min via a high pressure Isco pump (this is t=0 for the reaction time). After 30 seconds from the start of substrate feeding, 1.0 g of peracetic acid in 5.0 mL of acetic acid was introduced using a blow-case to start the reaction. The feed was stopped after 1 h and the reaction continued for an additional hour at the same conditions of air flow, temperature and pressure. After the reaction time was completed, the air flow was stopped and the autoclave was cooled to room temperature and depressurized. The heterogeneous mixture was filtered to isolate the crude FDCA. The mass of the filtrate was recorded.

- 27 -

The crude FDCA was washed with 60 mL of acetic acid two times and then twice with 100 mL of DI water. The washed crude FDCA was oven dried at 110 °C under vacuum overnight and then weighed. The solid and the filtrate were analyzed by Gas Chromatography using BSTFA derivatization method.

The Off-gas was analyzed for CO and CO₂ by ND-1R (ABB, Advanced Optima) and O₂ by a paramagnetism detection system (Servomex, 1440 Model).

Analytical

Gas Chromatographic Method Process samples were analyzed using a Shimadzu gas chromatograph Model 2010 (or equivalent) equipped with a split/heated injector (300°C) and a flame ionization detector (300°C). A capillary column (60 meter x 0.32 mm ID) coated with (6% cyanopropylphenyl)-methylpolysiloxane at 1.0 µm film thickness (such as DB-1301 or equivalent) was employed. Helium was used as the carrier gas with an initial column head pressure of 29.5 psi and an initial column flow of 3.93 mL/minute while the carrier gas linear velocity of 45 cm/second was maintained constant throughout the entire oven temperature program. The column temperature was programmed as follows: The initial oven temperature was set at 80 °C and was held for 6 minutes, the oven was ramped up to 150 °C at 4°C/minute and was held at 150 °C for 0 minute, the oven was ramped up to 240 °C at 10°C/minute and was held at 240 °C for 5 minutes, then the oven was ramped up to 290 °C at 10°C/minute and was held at 290 °C for 17.5 minutes (the total run time was 60 mins). 1.0-µl of the prepared sample solution was injected with a split ratio of 40:1. EZ-Chrom Elite chromatography data system software was used for data acquisition and data processing. The sample preparation was done by weighing 0.1 g (accurate to 0.1 mg) of sample in a GC vial and adding 200.0 µl ISTD solution (1% by volume of decane in pyridine) and 1000 µl of BSTFA (N, O-bis(trimethylsilyl) trifluoroacetamide) with 1% TMSCl

- 28 -

(trimethylchlorosilane) to the GC vial. The content was heated at 80 °C for 30 minutes to ensure complete derivatization. 1.0- μ l of this prepared sample solution was injected for GC analysis.


- Color measurement.** 1) Assemble the Carver Press die as instructed in the directions---place the die on the base and place the bottom 40 mm cylinder polished side face-up.
- 2) Place a 40 mm plastic cup (Chemplex Plasticup, 39.7 x 6.4 mm) into the die.
- 3) Fill the cup with the sample to be analyzed. The exact amount of sample added is not important.
- 4) Place the top 40 mm cylinder polished side face-down on the sample.
- 5) Insert the plunger into the die. No "tilt" should be exhibited in the assembled die.
- 6) Place the die into the Carver Press, making sure that it is near the center of the lower platen. Close the safety door.
- 7) Raise the die until the upper platen makes contact with the plunger. Apply > 20,000 lbs pressure. Then allow the die to remain under pressure for approximately 3 minutes (exact time not critical).
- 8) Release the pressure and lower the lower platen holding the die.
- 9) Disassemble the die and remove the cup. Place the cup into a labeled plastic bag (Nasco Whirl-Pak 4 oz).
- 10) Using a HunterLab Colorquest XE colorimeter, create the following method (Hunterlab EasyQuest QC software, version 3.6.2 or later)
- Mode: RSIN-LAV (Reflectance Specular Included-Large Area View)
- Measurements:
- CIE L* a* b*
- CIE X Y Z
- 11) Standardize the instrument as prompted by the software using the light trap accessory and the certified white tile accessory pressed against the reflectance port.

- 29 -

- 12) Run a green tile standard using the certified white tile and compare the CIE X, Y, and Z values obtained against the certified values of the tile. The values obtained should be ± 0.15 units on each scale of the stated values.
- 5 13) Analyze the sample in the bag by pressing it against the reflectance port and obtaining the spectrum and L^* , a^* , b^* values. Obtain duplicate readings and average the values for the report.


Interpretation of Results:

- 10 During the oxidation of 5-HMF to FDCA the alcohol site (ArCH_2OH) was converted into carboxylic acid (ArCOOH) mainly via aldehyde (ArCHO), eq 3. Examples 1a, and 1b (**Table-1**) which use catalyst systems consisting of cobalt, manganese and aqueous hydrobromic acid source produced about 90 % yield of FDCA with >
- 15 98 % purity of crude FDCA solid and with a b^* of about 6. The crude FDCA solid also contains 5-Formylfuran-2-carboxylic acid (FFCA), only the hydroxymethyl groups are oxidized to carboxylic acid groups, due to incomplete oxidation.




- Oxidation of 5-AMF, which contains an oxidizable ester and aldehydes moieties, produced FDCA, FFCA, and acetic acid, eq 4.
- 25 Examples 2a to 2b (**Table-2**) demonstrate that a minimum of 99% purity FDCA solid with a b^* of about 7 or less can be achieved using cobalt, manganese and aqueous hydrobromic acid catalyst system.

- 30 -



Oxidation of 5-EMF, which contains an oxidizable ether and aldehyde moieties, produced FDCA, FFCA, 5-(ethoxycarbonyl)furan-2-carboxylic acid (EFCA) and acetic acid, eq 5. Examples 3a to 3d (Table-3) show that a minimum of 96% purity FDCA solid with a b* of about 6 or less can be achieved using cobalt, manganese and aqueous hydrobromic acid catalyst system.



10

It is very important to note that **in a continuous process** under the same conditions as described in this invention report (which was conducted as a batch process) **even higher purity** of crude FDCA is expected due to efficient mixing, relatively low concentrations of reactive intermediates, and other reasons familiar to those skilled in the art.

Table 1. Results from semi-batch reactions performed as described above using 5-HMF feed.*

Example	Co conc (ppm)	Mn conc (ppm)	Br conc (ppm)	Temp (°C)	yield of FDCA (%)	yield of FFCA (%)	Solid Composition		
							FDCA	FFCA	b*
1a	2000	93.3	3000	132	89.4	0.58	99.20	0.81	5.845
1b	2000	93.3	3000	132	88.6	0.8	98.67	0.77	6.175

*P = 130 psig.

25

Table 2. Results from semi-batch reactions performed as described above using 5-AMF feed.*

Example	Co conc (ppm)	Mn conc (ppm)	Br conc (ppm)	Temp (°C)	yield of FDCA (%)	yield of FFCA (%)	Solid Composition		
							FDCA	FFCA	b*
2a	2500	116.8	2500	130	88.2	0.25	99.71	0.25	4.4
2b	2000	93.5	3000	130	90.2	0.16	99.44	0.16	6.8

*P= 130 psig.

Table 3. Results from semi-batch reactions performed as described above using EMF feed.*

Example	Co conc (ppm)	Mn conc (ppm)	Br conc (ppm)	Temp (°C)	yield of FDCA (%)	yield of FFCA (%)	yield of EFCA (%)	Solid Composition			
								FDCA	FFCA	EFCA	b*
3a	2500	116.8	2500	130	89.0	0.02	0.23	99.04	0.02	0.02	3.97
3b	2500	116.8	2500	130	87.4	0.42	1.31	98.08	0.42	0.04	2.74
3c	2000	93.5	3000	130	88.0	0.09	0.43	99.20	0.09	0.05	5.845
3d	2000	93.5	3000	105	86.0	2.92	1.40	96.22	2.90	0.15	0.98

*P = 130 psig.

Examples Set 2

Air oxidation of 5-HMF using cobalt, manganese and ionic bromine catalysts system in acetic acid solvent were conducted. After reaction the heterogeneous mixture was filtered to isolate the crude FDCA. The crude FDCA was washed with acetic acid two times and then twice with DI water. The washed crude FDCA was oven dried at 110 °C under vacuum overnight. The solid and the filtrate were analyzed by Gas Chromatography using BSTFA derivatization method. b* of the solid was measured using a Hunter Ultrascan XE instrument. As shown in **Table 4** we have discovered conditions that to generate yields of FDCA up to 89.4%, b* < 6, and low carbon burn (<0.0006 mol/min CO+CO₂)

Table 4. Results from semi-batch reactions.*

Example	Bromide source	Co conc (ppm)	Mn conc (ppm)	Br conc (ppm)	yield of FDCA (%)	yield of FFCA (%)	CO (total mol)	CO ₂ (total mol)	CO _x (mol/min)	pH before reaction	color (b*)
4a	solid NaBr	2000	93.3	3000	81.6	0.81	0.013	0.078	0.000758	-0.12	13.91
4b	solid NaBr	2000	93.3	3000	82.6	0.87	0.013	0.092	0.000875	-0.12	14.14
4c	aqueous HBr	2000	93.3	3000	89.4	0.58	0.003	0.061	0.000533	-1.03	5.845
4d	aqueous HBr	2000	93.3	3000	88.6	0.8	0.0037	0.061	0.000539	-1.03	6.175

*P= 130 psig, CO_x (mol/min) = CO (mol/min) + CO₂ (mol/min).

Examples set 3

10 In Examples 5a-5h, glacial acetic acid and the catalyst components in concentrations described in **Table-5** were transferred to a 300 mL titanium autoclave equipped with a high pressure condenser, a baffle and an Isco pump. Cobalt, manganese and ionic bromine were provided as cobalt (II) acetate tetrahydrate, manganese (II) acetate and sodium bromide and/or aqueous hydrobromic acid respectively. The autoclave was pressurized with approximately 50 psig of nitrogen and then the homogeneous mixture was heated to the desired temperature in a closed system (i.e., with no gas flow) with stirring. At reaction temperature, an air flow of 1500 sccm was introduced at the bottom of the solution and the reaction pressure was adjusted to the desired pressure. A solution of 5-HMF in acetic acid was fed to the mixture at a rate of 0.833 mL/min via a high pressure Isco pump (this is t=0 for the reaction time). After 30 seconds from the start of 5-HMF feeding, 1.0 g of peracetic acid in 5.0 mL of acetic acid was introduced using a blow-case to start the reaction. The feed was stopped after 1 h and the reaction continued for 1 more hour at the same conditions of air flow, temperature and pressure. After the reaction time was completed the air flow was stopped and the autoclave was cooled to room temperature and depressurized. The heterogeneous mixture was filtered to isolate the crude FDCA. The mass of the filtrate was recorded. The crude FDCA was washed with 60 mL of acetic acid two times and then twice with 100 mL of DI water. The washed crude FDCA was oven dried at 110 °C under vacuum overnight and then weighed. The solid and the

- 33 -

filtrate were analyzed by Gas Chromatography using BSTFA derivatization method.

The Off-gas was analyzed for CO and CO₂ by ND-1R (ABB, Advanced Optima) and O₂ by a paramagnetism detection system (Servomex, 1440 Model).

Analytical

Gas Chromatographic Method Process samples were analyzed using a Shimadzu gas chromatograph Model 2010 (or equivalent) equipped with a split/heated injector (300°C) and a flame ionization detector (300°C). A capillary column (60 meter x 0.32 mm ID) coated with (6% cyanopropylphenyl)-methylpolysiloxane at 1.0 µm film thickness (such as DB-1301 or equivalent) was employed. Helium was used as the carrier gas with an initial column head pressure of 29.5 psi and an initial column flow of 3.93 mL/minute while the carrier gas linear velocity of 45 cm/second was maintained constant throughout the entire oven temperature program. The column temperature was programmed as follows: The initial oven temperature was set at 80°C and was held for 6 minutes, the oven was ramped up to 150°C at 4°C/minute and was held at 150 for 0 minute, the oven was ramped up to 240°C at 10°C/minute and was held at 240 for 5 minutes, then the oven was ramped up to 290°C at 10°C/minute and was held at 290 for 17.5 minutes (the total run time was 60 mins). 1.0-µl of the prepared sample solution was injected with a split ratio of 40:1. EZ-Chrom Elite chromatography data system software was used for data acquisition and data processing. The sample preparation was done by weighing 0.1 g (accurate to 0.1 mg) of sample in a GC vial and adding 200.0 µl ISTD solution (1% by volume of decane in pyridine) and 1000 µl of BSTFA (*N*, *O*-bis(trimethylsilyl) trifluoroacetamide) with 1% TMSCl (trimethylchlorosilane) to the GC vial. The content was heated at 80°C for 30 minutes to ensure

- 34 -

complete derivatization. 1.0- μ l of this prepared sample solution was injected for GC analysis.

pH measurement. The electrode for determining non-aqueous pH and millivolts was a Schott N6480-eth series electrode. The LiCl/EtOH filling solution was replaced with (Et)₄N⁺ Br⁻/ethylene glycol. The electrode response was monitored by Multi-T 2.2 software through a Jensen Systems cdv-70 series Sensolab interface box. The buffers (pH 4 and 7) were purchased from VWR, and the (Et)₄N⁺ Br⁻/ethylene glycol filling solution was from Metrohm.

To perform the pH measurements, a non-aqueous electrode was initially calibrated using aqueous buffers of 4 and 7 allowing the electrode to equilibrate with each for two to three minutes before calibrating at the respective level. Once the electrode was calibrated within 97.5% of 59.2 millivolts slope, the samples were portioned (~15 mL) into smaller vials with mini-Teflon stir bars. The samples were then placed on a stir plate, and the electrode was lowered into the sample. The depth of the electrode was set to where the sample covered about half of the junction slide. Once the sample and electrode was ready, the sample was measured for non-aqueous pH over a period of three minutes. The time was sufficient for equilibration between the electrode and the sample. Between each sample measurement, the electrode was rinsed with Millipore-grade water and wiped with a Kimwipe. The results were recorded in non-aqueous pH units. The millivolts results were also recorded.

Color measurement. 1) Assemble the Carver Press die as instructed in the directions---place the die on the base and place the bottom 40 mm cylinder polished side face-up.

2) Place a 40 mm plastic cup (Chemplex Plasticup, 39.7 x 6.4 mm) into the die.

3) Fill the cup with the sample to be analyzed. The exact amount of sample added is not important.

- 35 -


- 4) Place the top 40 mm cylinder polished side face-down on the sample.
- 5) Insert the plunger into the die. No "tilt" should be exhibited in the assembled die.
- 5 6) Place the die into the Carver Press, making sure that it is near the center of the lower platen. Close the safety door.
- 7) Raise the die until the upper platen makes contact with the plunger. Apply > 20,000 lbs pressure. Then allow the die to remain under pressure for approximately 3 minutes (exact time not critical).
- 10 8) Release the pressure and lower the lower platen holding the die.
- 9) Disassemble the die and remove the cup. Place the cup into a labeled plastic bag (Nasco Whirl-Pak 4 oz).
- 10) Using a HunterLab Colorquest XE colorimeter, create the following method (Hunterlab EasyQuest QC software, version 3.6.2 or later)
- 15 Mode: RSIN-LAV (**R**eflectance **S**pecular **I**ncluded-**L**arge **A**rea **V**iew)
Measurements:
CIE L* a* b*
CIE X Y Z
- 20 11) Standardize the instrument as prompted by the software using the light trap accessory and the certified white tile accessory pressed against the reflectance port.
- 12) Run a green tile standard using the certified white tile and compare the CIE X, Y, and Z values obtained against the certified values of the tile. The values obtained should be ± 0.15 units on each scale of the
- 25 stated values.
- 13) Analyze the sample in the bag by pressing it against the reflectance port and obtaining the spectrum and L*, a*, b* values. Obtain duplicate readings and average the values for the report.

30 Interpretation of Results:

Examples 5c, 5d, 5e and 5f (**Table-5**) which use catalyst systems consisting of cobalt, manganese and aqueous hydrobromic acid or

- 36 -

aqueous hydrobromic acid and sodium bromide as a bromide source produced about 90 % yield of FDCA, minimum colored impurities (measured by b^*) and a minimum level of CO and CO₂ (CO_x, mol/min) in the off-gas. One of the reasons for the differences in activity between hydrobromide and sodium bromide, in **a single batch reaction**, is due to faster oxidation of HBr by Mn(III), eq 6, than sodium bromide (it is about 22 times faster: Jiao, X. J.; Espenson, J. H. *Inorg. Chem.* **2000**, 39, 1549). The activity of hydrobromic acid or sodium bromide reaction mediums can be increased by addition of a strong Brønsted acid (such as triflic acid, HCl, etc.).



Comparative examples 5g and 5h show the inhibiting effect of excess manganese. Therefore it is desirable to limit the amount of manganese, during the oxidation process, to achieve high yield of FDCA.

It is very important to note that **in a continuous process** under the same conditions as described in this invention report (conducted as a batch process) **higher than 90% yield** of FDCA expected due to efficient supply of oxygen and mixing.

Table 5 Results from semi-batch reactions performed as described above.*

Example	Bromide source	Co conc (ppm)	Mn conc (ppm)	Br conc (ppm)	yield of FDCA (%)	yield of FFCA (%)	CO (total mol)	CO ₂ (total mol)	CO _x (mol/min)	pH, before reaction	color (b^*)
5a	solid NaBr	2000	93.3	3000	81.6	0.81	0.013	0.078	0.000758	-0.12	13.91
5b	solid NaBr	2000	93.3	3000	82.6	0.87	0.013	0.092	0.000875	-0.12	14.14
5c	aqueous HBr	2000	93.3	3000	89.4	0.58	0.003	0.061	0.000533	-1.03	5.845
5d	aqueous HBr	2000	93.3	3000	88.6	0.8	0.0037	0.061	0.000539	-1.03	6.175
5e	aqueous HBr + solid NaBr	2000	93.3	3000	91.7	0.96	0.008	0.07	0.000650	-0.63	8.185
5f	aqueous HBr + solid NaBr	2000	93.3	3000	90.2	0.87	0.008	0.072	0.000667	-0.63	7.96
5g	aqueous HBr	2000	2000	3000	79.4	1.08	0.009	0.072	0.000675	-0.84	6.21
5h	aqueous HBr	2000	2000	3000	80.5	1.32	0.009	0.071	0.000667	-0.84	6.31

- 37 -

* T= 132 C, P = 130 psig. $\text{CO}_x \text{ (mol/min)} = \text{CO (mol/min)} + \text{CO}_2 \text{ (mol/min)}$.
FFCA = 5-Formylfuran-2-carboxylic acid.

5 Example Set 4

In Examples 1-34, 72, 73, 85, 86, 91, 92 and 93 glacial acetic acid and the catalyst components in concentrations described in the **Tables 6** and **7** were transferred to a 300 mL titanium autoclave equipped with a high pressure condenser, a baffle and an Isco pump. Cobalt, manganese and ionic bromine were provided as cobalt (II) acetate tetrahydrate, manganese (II) acetate and sodium bromide/aqueous hydrobromic acid respectively. The autoclave was pressurized with approximately 50 psig of nitrogen and then the homogeneous mixture was heated to the desired temperature in a closed system (i.e., with no gas flow) with stirring. At reaction temperature, an air flow of 1500 sccm was introduced at the bottom of the solution and the reaction pressure was adjusted to the desired pressure. A solution of 5-HMF in acetic acid was fed to the mixture at a rate of 0.833 mL/min via a high pressure Isco pump (this is t=0 for the reaction time). After 30 seconds from the start of 5-HMF feeding, 1.0 g of peracetic acid in 5.0 mL of acetic acid was introduced using a blow-case to start the reaction. The feed was stopped after 1 h and the reaction continued for 1 more hour at the same conditions of air flow, temperature and pressure. After the reaction time was completed the air flow was stopped and the autoclave was cooled to room temperature and depressurized. The heterogeneous mixture was filtered to isolate the crude FDCA. The mass of the filtrate was recorded. The crude FDCA was washed with 60 mL of acetic acid two times and then twice with 100 mL of DI water. The washed crude FDCA was oven dried at 110 °C under vacuum overnight and then weighed. The solid and the filtrate were analyzed by Gas Chromatography using BSTFA derivatization method. A typical GC-chromatogram for isolated crude FDCA sample is shown in **Figure 2**. The purity of this solid was confirmed by NMR spectroscopy, **Figures 3** and **4**.

- 38 -

The Off-gas was analyzed for CO and CO₂ by ND-1R (ABB, Advanced Optima) and O₂ by a paramagnetism detection system (Servomex, 1440 Model).

5 **Analytical**

Gas Chromatographic Method Process sample was analyzed using a Shimadzu gas chromatograph Model 2010 (or equivalent) equipped with a split/heated injector (300°C) and a flame ionization detector (300°C). A capillary column (60 meter x 0.32mm ID) coated with (6% cyanopropylphenyl)-methylpolysiloxane at 1.0 µm film thickness (such as DB-1301 or equivalent) was employed. Helium was used as the carrier gas with an initial column head pressure of 29.5 psi and an initial column flow of 3.93 ml/minute while the carrier gas linear velocity of 45 cm/second was maintained constant throughout the entire oven temperature program. The column temperature was programmed as follows: The initial oven temperature was set at 80°C and was held for 6 minutes, the oven was ramped up to 150°C at 4°C/minute and was held at 150 for 0 minute, the oven was ramped up to 240°C at 10°C/minute and was held at 240 for 5 minute, then the oven was ramped up to 290°C at 10°C/minute and was held at 290 for 17.5 minutes (the total run time was 60mins). 1.0-µl of the prepared sample solution was injected with a split ratio of 40:1. EZ-Chrom Elite chromatography data system software was used for data acquisition and data processing. The sample preparation was done by weighing 0.1g (accurate to 0.1mg) of sample in a GC vial and adding 200.0µl ISTD solution (1% by volume of decane in pyridine) and 1000 µl of BSTFA (N, O-bis(trimethylsilyl) trifluoroacetamide) with 1% TMSCl (trimethylchlorosilane) to the GC vial. The content was heated at 80°C for 30 minutes to ensure complete derivatization. 1.0-µl of this prepared sample solution was injected for GC analysis.

Interpretation of Results:

Experiments 1-34, **Table 6**, were conducted by varying temperature, pressure and levels of cobalt and bromine concentrations to determine optimum conditions and catalyst compositions that produces very high yield of FDCA with minimum amount of carbon burn. In this invention, the weight ratio of cobalt to manganese was deliberately kept very high (i.e. 21) in all the reactions to avoid the inhibiting effect of excess manganese especially below 160 °C.

As can be seen from **Figure 5**, under the reaction conditions investigated in this invention the factor that has the most impact on the yield of FDCA is temperature. It is also important to note that the yield increases with increasing cobalt and bromine concentrations.

The data presented in **Table 6** was used to develop a theoretical polynomial model to predict FDCA yield under different conditions, eq -7. Examples of predicted FDCA yields using this model is given in **Table 7**. Experiments No 72, 73, 85, and 86, **Table 7**, were conducted under the predicted conditions. As can be seen from the results they agree well with the predicted values within experimental error.

$$\begin{aligned} \% \text{ yield of FDCA} = & -91.469 + 2.83 \cdot T - 0.01 \cdot P - 0.02 \cdot [\text{Co}] + 0.003 \cdot [\text{Br}] \\ & - 0.01 \cdot T^2 + 3.9 \cdot 10^{-6} \cdot [\text{Co}]^2 \quad \text{-----} \quad (7) \end{aligned}$$

Examples 91-93, **Table 8**, were conducted under the US patent applications (US2003/0055271 A1) conditions using our set-up. As can be seen from **Tables 6, 7 and 8**, the patent application conditions gave much inferior yield of FDCA than the current invention.

Table 6 Results from semi-batch reactions performed as described above.

*Cobalt to manganese weight ratio = 21 for all experiments

Run	A: Temperature deg. C	B: Pressure psi	C: Cobalt Conc ppm	D: Br Conc ppm	% conversion	% yield of FDCA	% yield of FFCA	CO (total mol)	CO ₂ (total mol)	CO ₂ (mol/min)
1	130	200	4000	1500	99.26	75.7	1.1	0.011	0.088	0.00083
2	155	450	3000	2250	99.1	67.3	0.08	0.032	0.163	0.00163
3	180	200	4000	3000	100	68.7	0.037	0.049	0.161	0.00175
4	180	700	2000	3000	98.57	57.3	0.0049	0.044	0.17	0.00178
5	180	200	2000	1500	94.47	48.3	0.96	0.044	0.125	0.00141
6	155	450	3000	2250	99.07	67.2	0.07	0.031	0.158	0.00158
7	130	700	4000	3000	100	78	0.34	0.017	0.183	0.00167
8	130	200	2000	3000	97.11	82.1	1.1	0.012	0.095	0.00089
9	180	700	4000	1500	99.5	53	0.02	0.053	0.148	0.00168
10	155	450	3000	2250	99.38	70.9	0.148	0.032	0.16	0.00160
11	130	700	2000	1500	99.84	68	0.79	0.024	0.168	0.00160
12	180	200	4000	1500	99.26	53.3	0.003	0.061	0.185	0.00205
13	155	450	3000	2250	100	70	0.2	0.03	0.158	0.00157
14	130	200	2000	1500	96.2	74.6	1.49	0.015	0.093	0.00090
15	130	200	4000	3000	99.57	85.3	0.7	0.009	0.083	0.00077
16	130	700	4000	1500	99.9	73.9	0.87	0.018	0.129	0.00123
17	155	450	3000	2250	100	71.2	0.1	0.03	0.159	0.00158
18	130	700	2000	3000	99.89	70.3	0.54	0.02	0.13	0.00125
19	180	200	2000	3000	99.5	58.4	0.464	0.058	0.0193	0.00064
20	180	700	2000	1500	100	54.3	0.55	0.053	0.175	0.00190
21	155	450	3000	2250	100	58.5	0.089	0.029	0.155	0.00153
22	180	700	4000	3000	100	60	0.025	0.048	0.158	0.00172
23	200	450	3000	2250	100	23	0	0.158	0.284	0.00368
24	200	450	3000	2250	100	23.8	0	0.156	0.266	0.00352
25	155	450	3000	2250	99.69	66.2	0.143	0.028	0.154	0.00152
26	155	50	3000	2250	99.05	79	0.075	0.019	0.109	0.00107
27	155	450	3000	1500	98.14	67.4	0.18	0.032	0.15	0.00152
28	155	950	3000	2250	99.94	62.8	0.118	0.034	0.164	0.00165
29	155	450	3000	2250	99.81	68.9	0.093	0.027	0.152	0.00149
30	105	450	3000	2250	97.12	66.9	3.56	0.013	0.099	0.00093
31	155	450	4000	2250	99.92	66.4	0.06	0.032	0.158	0.00158
32	155	450	3000	3750	100	68.8	0.178	0.026	0.151	0.00148
33	155	450	3000	2250	99.76	72	0.1	0.027	0.154	0.00151
34	155	450	2000	2250	99.89	70.3	0.54	0.02	0.13	0.00125

Table 7. Predicted yields of FDCA. 72, 73, 74, 85 and 86 are experimental results.*

	Number	Temperature	Pressure	Cobalt Conc	Br Conc	yield of FDCA	yield of FFCA
5	35	139	50	3999	3000	85.1504	0.447749
	36	139	50	4000	2981	85.0945	0.442835
	37	138	70	4000	3000	85.0502	0.469564
	38	138	74	4000	3000	85.0244	0.473723
	39	138	63	3988	3000	84.9913	0.463436
10	40	139	50	3999	2948	84.976	0.435265
	41	139	50	4000	2938	84.9472	0.432597
	42	139	50	3981	2973	84.9129	0.443582
	43	138	51	3951	2999	84.7494	0.455411
	44	138	50	3935	2999	84.629	0.455856
15	45	138	50	3917	3000	84.4874	0.458526
	46	138	53	3917	3000	84.4716	0.461423
	47	138	50	4000	2777	84.3976	0.406641
	48	138	50	3905	2998	84.3893	0.45981
	49	137	50	3881	3000	84.2031	0.463274
20	50	139	50	3886	3000	84.1187	0.428238
	51	137	50	4000	2596	83.7624	0.395897
	52	137	50	3992	2606	83.724	0.39788
	53	136	50	3804	3000	83.6075	0.473555
	54	136	51	3780	3000	83.4262	0.477259
25	55	137	227	3994	3000	83.3911	0.433817
	56	137	50	4000	2386	82.9936	0.394841
	57	135	50	3694	2946	82.6042	0.479136
	58	135	50	4000	2166	82.2022	0.446345
	59	136	50	4000	2152	82.1354	0.433632
30	60	131	61	2000	3000	81.8774	1.49331
	61	131	59	2002	2993	81.8506	1.4836
	62	131	59	2000	2986	81.8418	1.48296
	63	131	55	2026	3000	81.7822	1.4441
	64	130	83	2000	3000	81.5573	1.48713
35	65	132	50	2074	3000	81.5533	1.34737
	66	130	91	2000	3000	81.4703	1.47787
	67	130	89	2000	3000	81.4632	1.4882
	68	132	50	2103	3000	81.3982	1.28915
	69	131	50	2005	2833	81.2848	1.37298
40	70	139	51	4000	1973	81.2207	0.327309
	71	132	130	2000	3000	81.1875	1.33938
	72. Experimental result.*	132	130	2000	3000	81.5	0.79
	73. Experimental result.*	132	130	2000	3000	81.6	0.81
	74. Experimental result.*	132	130	2000	3000	81.6	0.81
45	75	132	50	2144	3000	81.1813	1.21129
	76	131	50	2146	2993	81.1115	1.22154
	77	132	50	2160	3000	81.1035	1.18214
	78	132	50	2001	2739	81.0004	1.30911
	79	132	50	2000	2681	80.7904	1.28011
50	80	133	50	2228	2993	80.7581	1.06473
	81	133	52	2000	2563	80.3266	1.22742
	82	133	50	2000	2484	80.0491	1.2075
	83	130	51	3136	3000	79.8341	0.591352
	84	133	50	4000	1542	79.8127	0.750216
55	85	135	50	3066	3000	79.7967	0.503153
	85 . Experimental result.*	135	50	3066	3000	85.3	0.86
	86 . Experimental result.*	135	50	3066	3000	83.2	0.96
	87	134	50	4000	1527	79.7531	0.668935
	88	135	206	2262	3000	78.9815	0.792438
60	89	132	50	2000	2052	78.3528	1.25619
	90	137	627	2000	3000	75.8366	0.489432

*Cobalt to Manganese weight ratio = 21 for all experiments.

Table 8. Reactions conducted using the patent application (US20030055271A1) conditions.^a

Run	A:Temperature	B:Pressure	C:Cobalt Conc	D:Br Conc	% conversion	%yield of FDCA	%yield of FFCA	CO (total mol)	CO ₂ (total mol)	CO _x (mol/min)
5 patent (US2003/0055271A1)	125	950	406	1102		44.7	24			
91 ^b	125	950	406	1102	98.42	40.1	23	0.03	0.128	0.00132
patent (US2003/0055271A1)	100	950	406	1102		44.8	3.3			
92 ^b	100	950	406	1102	60.51	0.5	4.4	0.005	0.028	0.00028
93 ^b	100	950	406	1102	64.33	0.9	2.7	0.005	0.031	0.00030

10 ^aCobalt to Manganese ratio = 1. ^bUnknown peaks in the GC.

Examples Set 5

15

20

25

30

In Examples 9a-11b, glacial acetic acid and the catalyst components in concentrations described in **Tables 9, 10 and 11** were transferred to a 300 mL titanium autoclave equipped with a high pressure condenser, a baffle and an Isco pump. Cobalt, manganese and ionic bromine were provided as cobalt (II) acetate tetrahydrate, manganese (II) acetate and aqueous hydrobromic acid respectively. The autoclave was pressurized with approximately 50 psig of nitrogen and the homogeneous mixture was heated to the desired temperature in a closed system (i.e., with no gas flow) with stirring. At reaction temperature, an air flow of 1500 sccm was introduced at the bottom of the solution and the reaction pressure was adjusted to the desired pressure. A solution of 5-MF/5-AMF/5-EMF in acetic acid was fed to the mixture at a rate of 0.833 mL/min via a high pressure Isco pump (this is t=0 for the reaction time). After 30 seconds from the start of substrate feeding, 1.0 g of peracetic acid in 5.0 mL of acetic acid was introduced using a blow-case to start the reaction. The feed was stopped after 1 h and the reaction continued for an additional hour at the same conditions of air flow, temperature and pressure. After the reaction time was

completed, the air flow was stopped and the autoclave was cooled to room temperature and depressurized. The heterogeneous mixture was filtered to isolate the crude FDCA. The mass of the filtrate was recorded. The crude FDCA was washed with 60 mL of acetic acid two times and
5 then twice with 100 mL of DI water. The washed crude FDCA was oven dried at 110 °C under vacuum overnight and then weighed. The solid and the filtrate were analyzed by Gas Chromatography using BSTFA derivatization method.

The off-gas was analyzed for CO and CO₂ by ND-1R (ABB,
10 Advanced Optima) and O₂ by a paramagnetism detection system (Servomex, 1440 Model).

Analytical

Gas Chromatographic Method Process samples were analyzed using a Shimadzu gas chromatograph Model 2010 (or equivalent)
15 equipped with a split/heated injector (300°C) and a flame ionization detector (300°C). A capillary column (60 meter x 0.32 mm ID) coated with (6% cyanopropylphenyl)-methylpolysiloxane at 1.0 µm film thickness (such as DB-1301 or equivalent) was employed. Helium was used as the carrier gas with an initial column head pressure of 29.5 psi
20 and an initial column flow of 3.93 mL/minute while the carrier gas linear velocity of 45 cm/second was maintained constant throughout the entire oven temperature program. The column temperature was programmed as follows: The initial oven temperature was set at 80 °C and was held for 6 minutes, the oven was ramped up to 150 °C at 4°C/minute and was
25 held at 150 °C for 0 minute, the oven was ramped up to 240 °C at 10°C/minute and was held at 240 °C for 5 minutes, then the oven was ramped up to 290 °C at 10°C/minute and was held at 290 °C for 17.5 minutes (the total run time was 60 mins). 1.0-µl of the prepared sample solution was injected with a split ratio of 40:1. EZ-Chrom Elite
30 chromatography data system software was used for data acquisition and data processing. The sample preparation was done by weighing 0.1 g

- 44 -

(accurate to 0.1 mg) of sample in a GC vial and adding 200.0 μ l ISTD solution (1% by volume of decane in pyridine) and 1000 μ l of BSTFA (*N*, *O*-bis(trimethylsilyl) trifluoroacetamide) with 1% TMSCl (trimethylchlorosilane) to the GC vial. The content was heated at 80 $^{\circ}$ C for 30 minutes to ensure complete derivatization. 1.0- μ l of this prepared sample solution was injected for GC analysis.

Interpretation of Results:

5-AMF feed studies:

Oxidation of 5-AMF, which contains an oxidizable ester and aldehydes moieties, produced FDCA, FFCA, and acetic acid, eq 8. Experiments 9a-9k, **Table 9**, were conducted by varying temperature, and levels of cobalt and bromine concentrations to determine optimum conditions and catalyst compositions that produces very high yield of FDCA with minimum amount of carbon burn. In this invention, the weight ratio of cobalt to manganese was deliberately kept very high (i.e. 21) in all the reactions to avoid the inhibiting effect of excess manganese especially below 160 $^{\circ}$ C. Further discussion on mechanism of initiation and inhibition by Mn(II) in oxidation can be found in Zakharov, I. V. *Kinetics and Catalysis* **1998**, 39, 485; and Jiao, X. J.; Espenson, J. H. *Inorg. Chem.* **2000**, 39, 1549.




Table 9. Results from semi-batch reactions performed as described above using 5-AMF feed.*

	Factor 1	Factor 2	Factor 3	Factor 4	Response 1	Response 2
Run	Temperature (°C)	Pressure (psig)	Cobalt conc (ppmw)	Br conc (ppmw)	% yield of FDCA	% yield of FFCA
9a	180	130	2500	2500	44.6	0.25
9b	130	130	2500	2500	88.2	0.25
9c	155	130	2000	3000	67.6	0.026
9d	130	130	2000	3000	90.2	0.16
9e	155	130	2500	2500	64.52	0.35
9f	180	130	2000	3000	49.5	0.15
9g	105	130	2000	3000	64.8	1.8
9h	180	130	2000	3000	42.3	0.007
9i	180	130	2500	2500	40.9	0.06
9j	130	130	2000	3000	86.9	0.79
9k	130	130	2500	2500	88.5	0.71

* Cobalt to Manganese weight ratio = 21 for all experiments


As can be seen from **Figure 6**, under the reaction conditions investigated, in this invention, the factor that has the most impact on the yield of FDCA is temperature. It is also important to note that the yield can increase with increasing cobalt and bromine concentrations.

It is important to note that the same yield and selectivity can be obtained with mixed 5-HMF and 5-AMF feed-stocks with varying ratios of the two components.

5-EMF Feed study:

Oxidation of 5-EMF, which contains an oxidizable ether and aldehyde moieties, produced FDCA, FFCA, 5-(ethoxycarbonyl)furan-2-carboxylic acid (EFCA) and acetic acid, eq 9.

- 46 -



Experiments 10a-10k, **Table 10**, were conducted by varying temperature, and levels of cobalt and bromine concentrations to determine optimum conditions and catalyst compositions that produces very high yield of FDCA with minimum amount of carbon burn. Similar to the 5-AMF oxidation described above the weight ratio of cobalt to manganese was deliberately kept very high (i.e. 21) in all the reactions to avoid the inhibiting effect of excess manganese especially below 160 °C.

Table 10. Results from semi-batch reactions performed as described above using 5-EMF feed.*

	Factor 1	Factor 2	Factor 3	Factor 4	Response 1	Response 2	Response 3
Run	Temperature (°C)	Pressure (psig)	Cobalt conc (ppmw)	Br conc (ppmw)	% yield of FDCA	% yield of FFCA	% yield of EFCA
10a	180	130	2500	2500	52.3	0.031	0.117
10b	130	130	2500	2500	88.8	0.02	0.225
10c	155	130	2000	3000	57.5	0.058	0.28
10d	130	130	2000	3000	87.97	0.09	0.43
10e	155	130	2500	2500	64.52	0.35	0.47
10f	180	130	2000	3000	49.5	0.15	0.23
10g	105	130	2000	3000	86	2.92	1.4
10h	180	130	2000	3000	50.9	0.096	0.24
10i	180	130	2500	2500	48.9	0.4	0.61
10j	130	130	2000	3000	87.5	0.4	1.22
10k	130	130	2500	2500	87.4	0.42	1.3

* Cobalt to Manganese weight ratio = 21 for all experiments

As can be seen from **Figure 7**, under the reaction conditions investigated in this invention the factor that has the most impact on the yield of FDCA is temperature. It is important to note that the same yield and selectivity can be obtained with mixed 5-HMF and 5-EMF feed-stocks with varying ratios of the two components.

5-MF Feed study:

Oxidation of 5-MF, which contains an oxidizable methyl and aldehydesmoieties, produced FDCA, and FFCA eq 10. Experiments 11a and 11b, **Table 11**, demonstrate that moderate yield of FDCA with high purity can be obtained using 5-MF as a feed stock.




Table 11. Results from semi-batch reactions performed as described above using 5-MF feed.*

	Factor 1	Factor 2	Factor 3	Factor 4	Response 1	Response 2	Response 3
Run	Temperature (°C)	Pressure (psig)	Cobalt Conc (ppmw)	Br Conc (ppmw)	%conversion	%yield of FDCA	%yield of FFCA
		psi	ppm	ppm			
11a	130	130	2000	3000	100	61.3	0.082
11b	130	400	2500	2500	100	61.8	0.083

* Cobalt to Manganese weight ratio = 21.

It is very important to note that **in a continuous process** under the same conditions as described in this invention report (which was conducted as a batch process) with different feed stock **even higher yields** of crude FDCA is expected due to efficient mixing, relatively low concentrations of reactive intermediates, and other reasons familiar to those skilled in the art.

CLAIMS NOT LIMITED TO DISCLOSED EMBODIMENTS

The preferred forms of the invention described above are to be used as illustration only, and should not be used in a limiting sense to interpret the scope of the present invention. Modifications to the exemplary embodiments, set forth above, could be readily made by those skilled in the art without departing from the spirit of the present invention.

The inventors hereby state their intent to rely on the Doctrine of Equivalents to determine and assess the reasonably fair scope of the present invention as it pertains to any apparatus not materially departing from but outside the literal scope of the invention as set forth in the following claims.

We Claim:

1. A process to produce a purified slurry stream comprising furan-2,5-dicarboxylic acid (FDCA), said process comprising:

(a) oxidizing in an primary oxidation zone an oxidizable compound in a oxidizable raw material stream in the presence of a solvent stream, an oxidizing gas stream, and a catalyst system, wherein said an oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), 5-alkyl furfurals (5-R''-furfural, where R'' = alkyl, cycloalkyl and aryl), mixed feedstocks of 5-HMF and 5-HMF esters, mixed feedstocks of 5-HMF and 5-HMF ethers, and mixed feedstocks of 5-HMF and 5-alkyl furfurals to produce a caboxylic acid composition comprising furan-2,5-dicarboxylic acid (FDCA);

(b) optionally, routing said carboxylic acid composition to a liquid displacement zone to produce a displaced mother liquid stream and a low impurity slurry stream;

(c) routing said low impurity slurry stream to a secondary oxidation zone to form a purified slurry stream; wherein said purified slurry stream comprises FDCA.

2. A process according to claim 1 wherein said displaced mother liquid stream is routed to a purge zone to generate a recovered solvent stream comprising solvent and catalyst.

- 50 -

3. A process according to claim 1 wherein said oxidizing is accomplished in the presence of a catalyst system at a temperature of about 100°C to about 220°C to produce said carboxylic acid composition; wherein said primary oxidation zone comprises at least one oxidation reactor and wherein said carboxylic acid composition comprises furan-2,5-dicarboxylic acid; wherein said catalyst system comprises cobalt, manganese and bromine; and wherein the yield of furan-2,5-dicarboxylic acid (FDCA) is greater than 60%.

4. A process according to claim 1 wherein an offgas from said primary oxidation zone is routed to an oxidizer offgas treatment zone.

5. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 70%.

6. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 80%.

7. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 90%.

- 51 -

8. A process to produce a purified slurry stream comprising FDCA, said process comprising:

- (a) oxidizing in an primary oxidation zone an oxidizable compound in the presence of a solvent stream, an oxidizing gas stream, and a catalyst system, wherein said oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), 5-alkyl furfurals (5-R''-furfural, where R'' = alkyl, cycloalkyl and aryl), mixed feedstocks of 5-HMF and 5-HMF esters, mixed feedstocks of 5-HMF and 5-HMF ethers, and mixed feedstocks of 5-HMF and 5-alkyl furfurals to produce a carboxylic acid composition comprising furan-2,5-dicarboxylic acid(FDCA);
- (b) optionally, routing said carboxylic acid composition to a liquid displacement zone to produce a displaced mother liquid stream and a low impurity slurry stream;
- (c) routing said low impurity slurry stream to a secondary oxidation zone to form a purified slurry stream; wherein said purified slurry stream comprises FDCA.

9. A process according to claim 1 wherein said displaced mother liquid stream is routed to a purge zone to generate a recovered solvent stream comprising solvent and catalyst.

10. A process according to claim 1 wherein said oxidizing is accomplished in the presence of a catalyst system at a temperature of about 100°C to about 220°C to produce said carboxylic acid composition; wherein said primary oxidation zone comprises at least one

- 52 -

oxidation reactor and wherein said carboxylic acid composition comprises furan-2,5-dicarboxylic acid; wherein said catalyst system comprises cobalt, manganese and bromine; and wherein the yield of furan-2,5-dicarboxylic acid (FDCA) is greater than 60%.

11. A process according to claim 1 wherein an offgas from said primary oxidation zone is routed to an oxidizer offgas treatment zone.

12. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), and 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 70%.

13. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), and 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 80%.

14. A process according to claim 1 wherein said oxidizable raw material stream comprises at least one compound selected from the group consisting of 5-(hydroxymethyl)furfural (5-HMF), 5-HMF esters (5-R(CO)OCH₂-furfural where R = alkyl, cycloalkyl and aryl), and 5-HMF ethers (5-R'OCH₂-furfural, where R' = alkyl, cycloalkyl and aryl), and wherein the yield of furan-2,5-dicarboxylic acid is greater than 90%.

- 53 -

15. A process according to claim 8 further comprising routing said displaced mother liquor to a purge zone.




Fig. 1.





Fig. 2.

Fig. 3.



4/6




Fig. 4.






Fig. 5.

6/6

*Fig. 6.**Fig. 7.*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2012/037206

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - C07D 307/48 (2012.01)

USPC - 549/483

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - C07D 307/46, 48, 50; C08G 8/06 (2012.01)

USPC - 508/184; 549/483, 485, 489, 490, 503; 552/301

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

MicroPatent, Google Patent, WIPO, Public PatFT and AppFT

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2010/132740 A2 (SANBORN) 18 November 2010 (18.11.2010) entire document	1-3, 5-10, 12-15
--		
Y		4, 11
Y	US 2,797,197 A (THOMPSON et al) 25 June 1957 (25.06.1957) entire document	4, 11

☐ Further documents are listed in the continuation of Box C.


* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 July 2012

Date of mailing of the international search report

27 JUL 2012

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774