



US 20170291181A1

(19) **United States**(12) **Patent Application Publication**  
**Wright**(10) **Pub. No.: US 2017/0291181 A1**(43) **Pub. Date: Oct. 12, 2017**(54) **ELECTROSTATIC FLUID DELIVERY  
SYSTEM****Publication Classification**(71) Applicant: **Victory Innovations Company**, Poway,  
CA (US)(72) Inventor: **Clifford Wright**, Poway, CA (US)(73) Assignee: **Victory Innovations Company**, Poway,  
CA (US)(51) **Int. Cl.****B05B 5/025** (2006.01)**B05B 5/10** (2006.01)**A61M 11/00** (2006.01)(52) **U.S. Cl.**CPC ..... **B05B 5/0255** (2013.01); **A61M 11/00**  
(2013.01); **B05B 5/10** (2013.01)(21) Appl. No.: **15/507,456**(22) PCT Filed: **Sep. 4, 2015**(86) PCT No.: **PCT/US2015/048573**


§ 371 (c)(1),

(2) Date: **Feb. 28, 2017****Related U.S. Application Data**(60) Provisional application No. 62/046,140, filed on Sep.  
4, 2014.

(57)

**ABSTRACT**

An electrostatic fluid delivery system is configured to deliver fluid, such as a disinfectant fluid, onto a surface by electrically charging the fluid and forming the fluid into a mist, fog, plume, or spray that can be directed onto a surface, such as a surface to be cleaned. The system atomizes the fluid using a high-pressure fluid stream and passes the fluid through an electrode of a nozzle assembly to charge droplets of the atomized fluid.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 5




FIG. 7




FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24



## ELECTROSTATIC FLUID DELIVERY SYSTEM

### REFERENCE TO PRIORITY DOCUMENT

[0001] This application claims priority to co-pending U.S. Provisional Patent Application Ser. No. 62/046,140 entitled "ELECTROSTATIC FLUID DELIVERY SYSTEM DEVICE" and filed Sep. 4, 2014. Priority to the aforementioned filing date is claimed and the provisional patent application is incorporated herein by reference in its entirety.

### BACKGROUND

[0002] Infectious disease is too often acquired in places that should be safe, such as ambulances, hospitals, schools, restaurants, hotels, athletic facilities, and other public areas. These places are traditionally cleaned by spraying a fluid disinfectant onto surfaces and wiping down the surface with a cloth. Unfortunately such cleaning methods have been shown to be ineffective.

[0003] An improved mechanism for spraying down surfaces uses an electrostatic delivery system that sprays an electrically charged fluid, such as a disinfectant, onto surfaces. In an electrostatic delivery system, a fluid such as chemical solution is atomized by a high-pressure air stream as it passes through an electrode inside a nozzle. Negatively charged particles are thereby induced onto droplet surfaces of the solution to form electric field charge within the spray plume of the solution.

[0004] The electrostatic charge causes the fluid to cling to a surface to increase the likelihood that the disinfectant will cover and clean the surface. However, existing electrostatic delivery systems are unwieldy and inconvenient due to the power requirements of such systems. They are typically tethered to an electric cord or powered by air compressor or natural gas, which makes the system heavy. In addition, they are expensive. Cost and cording remain the two main obstacles to widespread adoption. In many cases existing corded products prohibit or restrict their use in applications where an extension cord is cumbersome, inconvenient, slow, and in some cases creating a safety concern by introducing a potentially dangerous tripping hazard.

[0005] In view of the foregoing, there is a need for improved electrostatic fluid delivery system.

### SUMMARY

[0006] Disclosed herein is an electrostatic fluid delivery system that is configured to deliver fluid, such as a disinfectant fluid, onto a surface by electrically charging the fluid and forming the fluid into a mist, fog, plume, or spray that can be directed onto a surface, such as a surface to be cleaned. The system atomizes the fluid using a high-pressure air (or other gas) stream and passes the fluid through an electrode inside a nozzle assembly to charge, such as negatively charge, droplets of the atomized fluid. The system uses a unique nozzle design that is configured to optimally atomize the fluid into various sized droplets. In addition, the system is powered by a DC power system rather than an AC system to eliminate cumbersome power cords. In an embodiment, the DC power system includes a lithium ion battery. The device can electrically or positively charge a liquid or gas.

[0007] In one aspect, there is disclosed an electrostatic sprayer device, comprising: a housing; an electrostatic mod-

ule inside the housing; a reservoir having a cavity adapted to contain a fluid; at least one nozzle fluidly connected to the reservoir wherein the nozzles emit fluid in a direction along a flow pathway; a pump that propels fluid from the reservoir to the at least one nozzle; a direct current battery that powers at least one of the electrostatic module and the pump; an electrode assembly that electrostatically charges the fluid, wherein the electrode assembly is at least one of: (1) a first electrode assembly formed of a plurality electrodes electrically attached to the electrostatic module, wherein each electrode emits ions along an axis that is parallel to the flow pathway of the fluid emitted from the nozzle such that the plurality electrodes form a static electrical field through which the fluid passes; and (2) a second electrode assembly formed of a tube that fluidly through which fluid flows from the reservoir toward the at least one nozzle, wherein at least a conductive portion of the tube is electrically attached to the electrostatic module, and wherein the conductive portion of the tube physically contacts the fluid as it flows through the tube and applies an electrical charge to the fluid.

[0008] Other features and advantages should be apparent from the following description of various embodiments, which illustrate, by way of example, the principles of the disclosure.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 shows a perspective view of an electrostatic fogger device.

[0010] FIG. 2 shows an exploded view of the device of FIG. 1.

[0011] FIG. 3 shows an enlarged view of a nozzle assembly of the device.

[0012] FIG. 4 shows a close up view of a nozzle surrounded by a charging ring.

[0013] FIGS. 5 and 6 show a backpack style fogger.

[0014] FIG. 7 shows an embodiment of a handheld fogger.

[0015] FIG. 8 shows another embodiment of a handheld fogger.

[0016] FIG. 9 shows another embodiment of an electrostatic fogger device.

[0017] FIG. 10 shows the device of FIG. 9 with a portion of an outer housing removed.

[0018] FIG. 11 shows a nozzle assembly of the device.

[0019] FIG. 12 shows a nozzle assembly of the device with a nozzle tool attached thereto.

[0020] FIG. 13 shows a nozzle housing of the nozzle assembly.

[0021] FIG. 14 shows a nozzle component with nozzles.

[0022] FIG. 15 shows an electrode assembly.

[0023] FIG. 16 shows an electrode.

[0024] FIG. 17 shows a perspective view of the nozzle tool.

[0025] FIG. 18 shows an enlarged view of a handle region of the system.

[0026] FIG. 19 shows an enlarged view of a handle region of the system with a portion of the outer housing removed.

[0027] FIG. 20 shows an interior of a cap of a liquid or fluid reservoir of the system.

[0028] FIG. 21 shows a perspective view of the reservoir.

[0029] FIG. 22 shows a perspective view of the system with the reservoir removed.

[0030] FIG. 23 shows an exemplary embodiment of the pump of the system.

[0031] FIG. 24 shows an ion tube isolator that provides a positive or negative electrical charge to fluid flowing the tube isolator via direct contact with the fluid,

#### DETAILED DESCRIPTION

[0032] Before the present subject matter is further described, it is to be understood that this subject matter described herein is not limited to particular embodiments described, as such may of course vary. It is also to be understood that the terminology used herein is for the purpose of describing a particular embodiment or embodiments only, and is not intended to be limiting. Unless defined otherwise, all technical terms used herein have the same meaning as commonly understood by one skilled in the art to which this subject matter belongs.

[0033] Disclosed herein is an electrostatic fluid delivery system that is configured to deliver fluid, such as a disinfectant fluid, onto a surface by electrically charging the fluid and forming the fluid into a mist, fog, plume, or spray that can be directed onto a surface, such as a surface to be cleaned. The system atomizes the fluid using a high-pressure air (or other gas) stream and passes the fluid through an electrode inside a nozzle assembly to charge, such as negatively charge, droplets of the atomized fluid. The system uses a unique nozzle design that is configured to optimally atomize the fluid into various sized droplets. In addition, the system is powered by a DC power system rather than an AC system to eliminate cumbersome power cords. In an embodiment, the DC power system includes a lithium ion battery. The device can electrically or positively charge a liquid or gas.

[0034] The system is configured to electrostatically charge the atomized fluid via direct charging, induction charging, indirect charging, or any combinations thereof. In the case of direct charging, fluid flows through an electrically conductive tube or other conduit that is electrostatically charged such that the fluid contacts the tube and is charged by direct contact with the tube, as describe below. For induction or indirect charging, the fluid is passed through a medium, such as air, that has been electrostatically charged by one or more electrodes or pins that create a static electric field through which the fluid passes to receive a charge. The electrode may or may not be in the fluid stream. In an embodiment, the fluid is charged through both direct contact with the charged tube and by flowing the fluid through a medium such as air that has been charged with electrodes such as, for example, described herein.

[0035] FIG. 1 shows a perspective view of an electrostatic fluid delivery system 105 that is configured to electrically charge and atomize a fluid for spraying onto a surface. The system 105 includes a housing 110 that is sized and shaped to be held by a user. The housing 110 has an ergonomic shape that can be easily grasped and held but it should be appreciated that the size and shape of the housing can vary. In an embodiment, one or more vents or openings are positioned in the outer housing to provide communication between an inside of the outer housing and the outside such as for venting.

[0036] The system 105 may have one or more actuators or controls 120 that can be actuated by a user to activate and operate the system. A fluid expelling region 175 is located at a front of the housing 110 and has an opening through which atomized fluid is expelled. The system 105 also includes a reservoir 125 that defines a chamber in which fluid can be

stored. The chamber of the reservoir 125 communicates internally with a nozzle assembly 205 (FIG. 2) for supplying fluid to be electrically charged and atomized by the nozzle assembly, as described more fully below.

[0037] FIG. 2 shows the system 105 in an exploded state. The housing is formed of multiple pieces that connect to contain an inner region in which is housed a fan 200. The fan 200 is powered by a battery, such as a lithium ion battery. An electrical circuit board converts the DC power to AC power for powering the fan. The system may include a stator coupled to the battery as well as a protection circuit module (PCM).

[0038] The fan 200 (or a pump) operates to blow fluid (gas or liquid) toward a nozzle assembly 205 in the fluid expelling region 175 of the system. The nozzle assembly 205 atomizes and expels fluid in a spray. As the fan blows air toward the nozzle assembly, it creates a pressure differential that sucks fluid from the reservoir 125 into the nozzle assembly 205 where it is atomized and expelled as a result of the fan 200 blowing air therethrough. It should be appreciated that other mechanisms can be used to blow air or to blow or otherwise propel liquid from the reservoir. In an embodiment, a piston pump is used to deliver air pressure to the nozzle tip. A piston pump can pull from the reservoir tank to push fluid or pressurize straight to the nozzle tip. For a smaller footprint embodiment (such as the embodiments of FIGS. 7 and 8) a Pneumatics Micro Pump can act as a solenoid pulling fluid by a magnetic movement. The device can also include a pump that pulls a vacuum in the reservoir or fluid tank to cause fluid to flow out of the reservoir toward the nozzles(s).

[0039] FIG. 3 shows an enlarged view of the nozzle assembly, which includes an annular housing 305 having a central opening in which is positioned a nozzle 310. The housing 305 has a conically or frustoconically shaped surface that can be curved or straight. The surface is shaped such that fluid from the nozzle 310 bounces back and forth along the surface to form a turbulent flow that atomizes the fluid. In an embodiment, the fluid is atomized to droplets in the range of 5 microns to 40 microns in size. The nozzle 310 is mechanically coupled to a drive assembly 315 that moves the nozzle 310 relative to the housing to control the size of the droplets. In this manner, the user can move the nozzle back and forth to achieve a desired plume profile.

[0040] FIG. 4 shows an enlarged view of the nozzle 310. The tip of the nozzle 310 is positioned centrally within a charge ring 405 that is positioned within the housing 305 (FIG. 3) in the assembled device. The charge ring 405 is positioned as such (deep inside the housing) to reduce the likelihood of a user touching the charged ring. The charge ring 405 is grounded and also electrically connected to a power source for achieving a positive voltage on the charge ring 405 during use. As the nozzle 310 expels the atomized fluid through the charge ring 405, it positively charges the fluid. In this manner, the electrically charged plume of fluid will cling to surfaces that it is sprayed upon.

[0041] With reference still to FIG. 4, the nozzle 310 has a series of openings through which fluid is expelled. The openings communicate with an internal lumen of a tube 410 through which fluid flows from the reservoir 125 (FIG. 1). The openings are arranged in a unique spatial pattern comprised of four openings with each opening positioned 90 degrees away from an adjacent opening so as to form a cross pattern. The openings can vary in size. In an embodiment,

the openings are 0.063 inches in diameter. As mentioned, the nozzle can be connected to a drive assembly that varies the position of the nozzle to control the plume profile.

**[0042]** The electrostatic fluid delivery system may vary in size and shape. FIGS. 5 and 6 show a backpack embodiment **405** that is configured to be worn on the back of user. The system includes a fluid tank **410** that is removably mounted to a frame **412** such that the tank **410** can be interchanged with another tank. The frame **412** is connected to a harness **420** or other support for mounting on a user's back, as shown in FIG. 6. The tank **410** is fluidly connected to a handheld nozzle **415** through which a plume of electrically charged fluid is expelled. The backpack embodiment can include any component of the other systems described herein, including the electrostatic configurations and removable reservoir.

**[0043]** In addition, FIG. 7 shows another handheld embodiment **705** having a reservoir at a bottom of the device. FIG. 8 shows an embodiment **805** that has a hand pump that can be pumped to generate a pressure differential that expels a plume of fluid out of the device.

**[0044]** FIG. 9 shows another embodiment of the system **105**. As in the previous embodiment, the system **105** has an outer housing **110** that forms a handle that can ergonomically be grasped by a single hand of a user. The system **105** includes at least one actuator that can be actuated to turn on and also turn off an internal pump, as well as a second actuator for turning on and off an electrostatics charger for expelling a plume of electrostatically charged fluid from a fluid expelling region **175** of the system **105**. The system **105** has a removable reservoir **125** for storing fluid to be expelled.

**[0045]** The system **105** ejects high voltage ions to the air by means of a plurality of (such as three or more) sharp, detachable high voltage ion discharge electrodes or pins of a predetermined spacing (such as at 120° spacing) from each other on a rim of a nozzle holder (described below with reference to FIG. 14). The high voltage ion discharge electrodes are each positioned along an axis that is in parallel to an axis of a spray nozzle so that the spray and ions are emitted in the same direction and along a parallel axis and therefore the droplets in the spray are surrounded and covered by ion stream and can be efficiently charged when they meet the ion stream. The electrodes thus emit, propel, or otherwise send out ions or charge in a direction parallel to the direct of fluid flow or an average direction of fluid flow from the nozzles.

**[0046]** FIG. 10 shows the system **105** with a portion of the outer housing **110** removed to show internal components of the system **105**. The system **105** includes a pump **1005** that is powered by a battery **1010**. The pump **1005** is fluidly coupled to fluid within the reservoir **125** such that the pump can cause a pressure differential to draw fluid from the reservoir and into a nozzle assembly **1015**, which is described in detail below. The system **105** further includes an electrostatic module that is electrically connected to an electrostatic ring, as described below. The electrostatic module in an example embodiment is a 12 kV electrostatic module and it is configured to electrostatically charge an item, such as the electrodes, ring, and/or tube described below.

**[0047]** In an embodiment, a light **1017** is positioned at a front end of the system **105** in the fluid-expelling region **175** such that the light aims light toward the direction where fluid is expelled. The light may be an LED light, for example. The

light can automatically illuminate when any portion of the system is activated. In an example embodiment, LED light has 100 lumens with the light being directly focused on the path of the liquid that is being sprayed out of the sprayer nozzle. The light can be in multiple colors to allow the user to illuminate florescent antimicrobial solutions (infrared light). In another embodiment the light is black light. At least a portion of the light or electrical components of the light may be insulated from contact with the electrically charged field.

**[0048]** FIG. 11 shows a perspective view of the nozzle assembly **1015**, which includes a nozzle housing **1105** having an internal cavity that removably contains a nozzle holder or nozzle component **1110** in which one or more nozzles **1115** are positioned. An annular electrostatic ring **1120** is mounted on a forward edge of the nozzle housing **1105**. The electrostatic ring **1120** forms an opening through which fluid is expelled from the reservoir and through at least one of the nozzles by virtue of the pump creating a pressure differential. An insulator element, such as a rubber ring **1125** is positioned on the electrostatic ring **1120** to electrically shield it from the outer housing **110** of the system.

**[0049]** There is a metal contact on the high voltage electrostatic ring **1120** that is exposed at a rear part of the electrostatic ring **1120**. A high voltage wire from the electrostatic module is soldered or otherwise electrically connected to this metal contact. The soldering point and adjacent exposed metal is completely sealed by epoxy or other insulator to avoid oxidation and leakage of ions from the electrodes. A ground wire from electrostatic module is connected to ground plate. As discussed, the ground wire is embedded in the handle of the sprayer so that it is in contact with the operator during operation. This serves as electrical return loop to complete an electrical circuit. The electrostatic ring is electrically charged so that it transfers the charge to the electrodes that are electrically connected to the ring. In another embodiment, the electrodes themselves are individually connected to the electrostatic module.

**[0050]** As shown in FIG. 12, the system **105** also includes a nozzle tool **1205** that removably and mechanically couples to the nozzle assembly for manipulating the nozzle component **1110**. The nozzle tool **1205** is sized and shaped to be inserted into a front opening in the nozzle housing **1105**. When inserted into the nozzle housing **1105**, the nozzle tool **1205** mechanically couples to the nozzle component **1110** in a manner that permits the nozzle tool **1205** to lock and/or move the nozzle component **1110** relative to the nozzle housing **1105**, as described more fully below.

**[0051]** In an embodiment, the tool **1205** couples to and removes nozzle component by a counter clock turn and by pushing in until nozzle component decouples and can be removed. In this regard, pushing the nozzle component deeper into the housing using the tool causes a threaded portion of the nozzle component to engage a threaded nut or bolt of the housing that secures the nozzle component to the housing. The user can then unthread the nozzle tool and remove it from the housing.

**[0052]** The tool **1205** can also be used to adjust the three-way nozzle by turning it in a desired rotational direction. The user can select three different spray patterns by turning the nozzle component so that a desired nozzle fluidly couples to the reservoir. In this regard, a portion of the tool mechanically attaches to the nozzle component so that it can

apply force to the nozzle component and rotate it until a desired nozzle is in a position that is fluidly coupled to a fluid stream from the reservoir. The system may include a mechanism, such as spring and ball, that provides a noise (such as a clicking sound) when a nozzle is in a position to spray fluid.

**[0053]** FIG. 17 shows a perspective view of the nozzle tool 1205. The nozzle tool 1205 is sized and shaped to be grasped by a user. It includes a coupler region 1705 that can be removably coupled to a drive device, such as a wrench, or grasped by a user. In an embodiment, the coupler region 1705 is hexagonal shaped so that it can be mechanically coupled to a wrench including a socket wrench. The nozzle tool 1205 includes a cavity or seat 1710 that is size and shaped to receive the outer portion of the nozzle component. For example, the seat 1710 can have a shape that complements and receives the shape of the nozzle component 1110. The nozzle tool 1205 also includes at least one opening 1715 that interlocks with a complementary-shaped protrusion 1405 (FIG. 14) on the nozzle component 1110.

**[0054]** FIG. 13 shows a perspective view of the nozzle housing 1105 without the nozzle component 1110 mounted therein. The nozzle housing 1105 has an elongated, cylindrical shape and defines an internal cavity 1305 sized to removably receive the nozzle component 1110. The electrostatic ring 1120 is mounted at the front edge of the nozzle housing 1105 with the rubber ring 1125 positioned in a seat within the electrostatic ring 1120. The rubber ring 1125 insulates a set of three electrode assemblies 1310 that are mounted on the electrostatic ring 1120 in a predetermined position and orientation. The electrode assemblies 1310 are arranged around the opening of the nozzle housing 1105 around the nozzles of the nozzle component 1110 when it is positioned in the nozzle housing 1105. In an embodiment, the electrode assemblies 1310 are positioned at 120 degree increments around the electrostatic ring 1120.

**[0055]** The electrostatic ring 1120 includes the three electrodes (which may be made of stainless steel for example) that are electrically isolated by a rubber washer and rubber threaded cap, as described below. The electrostatic ring 1120 that holds electrodes is metal and is built inside of the nozzle housing. The electric static ring is isolated inside a nozzle housing that acts as a protective barrier. The electrostatic ring 1120 contains three internal threaded holes that accept the three electrodes. A rubber washer is inserted between the electrostatic ring 1120 and an insulator on each electrode. The rubber washer aids in tightening of the electrode to the electrostatic ring 1120 and also assists in avoiding leakage of ions from the electrode. The whole electrostatic ring 1120 is isolated inside the nozzle housing so that it acts a protective barrier.

**[0056]** The ring, when properly mounted, forms a safety gap between the discharge electrodes and the outer housing so as to minimize static leakage through the housing. The rubber ring isolates the nozzle housing from causing a charge to the sprayer housing. The rubber ring also isolates the nozzle housing from main body of the sprayer to prevent water from penetrating to a main body of the sprayer.

**[0057]** A hose coupler 1320 is located at an end of the nozzle housing and is configured to be coupled to a house or other conduit that communicates with the reservoir. The hose coupler 132 defines an internal passageway that communicates with the nozzles 1115 for feeding fluid from the reservoir to the nozzles 1115.

**[0058]** FIG. 14 shows the nozzle component 1110, which is sized and shaped to be removably positioned within the cavity 1305 of the nozzle housing 1105. The nozzle component 1110 houses one or more nozzles 1115, each of which is configured to deliver fluid in a predetermined plume or spray pattern. The nozzle component 1110 includes one or more protrusions 1405 or other structural elements that are sized and shaped to receive complementary structures on the nozzle tool 1205, as described below. Note that the electrostatic ring 1120 with the electrode assemblies 1310 is positioned around the nozzles 1115 with the electrodes of the assemblies 1310 being aligned along an axis that is parallel with an axis of the nozzles.

**[0059]** Any of a variety of nozzle types can be used to achieve a desired flow pattern. There are now described some non-limiting examples of electrodes. In an embodiment, the electrodes include three example types as follows:

**[0060]** (1) A nozzle that provides a cone-shaped spray, with a flow rate of 0.23 L/min, 45° @3.5 bar, SMD=113 um, inner orifice=0.65 mm;

**[0061]** (2) A nozzle that provides a cone-shaped spray, with a flow rate of 0.369 L/min, 60° @3.5 bar, SMD=84 um, inner orifice=0.58 mm;

**[0062]** (3) A nozzle that provides a fan-shaped spray, with a flow rate of 0.42 L/min, 60° @3.5 bar, SMD=100 um, inner orifice=1.00 mm.

**[0063]** It should be appreciated that the aforementioned nozzles are just examples and that variances are within the scope of this disclosure.

**[0064]** FIG. 15 shows an electrode assembly 1310, which includes a high voltage ion discharge electrode 1510 (or pin) and an insulation element 1520 positioned over the electrode or pin 1510. The insulation element 1520 is sized and shaped so that it covers substantially all of the electrode 1510 and exposes only a front portion of the electrode 1510 in the form of a frontward facing conical tip that is aligned along an axis. FIG. 16 shows the electrode 1510 (sometimes referred to as a pin) without the insulation element 1520. Each high voltage ion discharge electrode in the system has the same structure shown in FIG. 15, a metal pin that is overmolded with plastic at the middle of the pin. Each metal pin has one sharp spike at one end and external screw thread at the other end. The insulation element, which can be plastic, at the middle of pin is for easy gripping during installation and removal, although the pins are not necessarily removable. The plastic is also used to insulate the pin and prevent it from releasing ions from body of pin. The electrode assembly can also be a set of electrode assemblies of the type shown in FIG. 15.

**[0065]** Thus, each electrode assembly 1310 includes an insulator element 1520 that can be formed of a rubber washer that covers a middle section of the electrode, and rubber boot that covers a front section except for a front most, sharpened tip. The rubber washer and a plastic or rubber cap (or boot) isolates the electrode and protects the electrode from static leakage such that only the sharpened tip is exposed and/or uninsulated.

**[0066]** Each high voltage ion discharge electrode is to be screwed into an internal screw thread on the high voltage ring 1120 coupled to the nozzle component 1110. Except for its sharp spike at the end, each high voltage ion discharge electrode is completely covered and concealed by the insulator element after it is installed to the high voltage ring 1120.

[0067] FIG. 18 shows an enlarged view of a handle region of the housing 110. The handle region is ergonomically sized and shaped to be grasped by a single hand of a user. A trigger 1805 or other actuator, such as a knob, switch, etc., is ergonomically positioned so that a user can actuate the trigger with his or her finger when the other fingers are wrapped around a post 1810 of the handle region. A ground wire 1815 or other structure 1815 is embedded into the handle region, such as in the post 1810. The ground wire 1815 is positioned so that it will electrically contact the user's hand when the user grasps the post 1810 during use of the device. In an embodiment, the ground wire is made of copper and is a copper strip of material that contacts the user's hand when the user grasps the device although other materials, such as stainless steel, may be used.

[0068] FIG. 19 shows the handle region with a portion of the outer housing 110 removed to show internal components of the device particularly with respect to the reservoir 125, which is a container that encloses an interior cavity that contains fluid. The reservoir is removably attached to the housing 110 and includes a guide surface 1907 that slides into the housing 110. In an embodiment, the guide surface 1907 defines one or more inclined guide projections that interact with the outer housing 110 to properly guide the reservoir 125 into the housing 110.

[0069] With reference still to FIG. 19, a first detachment mechanism 1905, such as a ring attached to a biased or tensions structure such as a pin, and a second detachment mechanism 1920, such as a rotatable wheel or cap 1921, that can be collectively actuated by a user to enable detachment and locking reattachment of the reservoir 125 to the outer housing. FIG. 20 shows a view of the portion of the cap 1921 that communicates with and covers the interior cavity of the reservoir 125. A one-way valve 2003, such as a duckbill valve, is positioned in the cap 1921 and provides a vent for fluid to enter into the interior of the reservoir from atmosphere as the pump of the system pulls a vacuum in the reservoir.

[0070] FIG. 21 shows the reservoir 125, which includes an opening 2005 that provides access to the interior cavity of the reservoir 125. The opening 2005 is defined by a neck 2010 having one or more flanges or threads. The neck 2010 sealingly engages the first detachment mechanism 1905 and the second detachment mechanism 1920 of the system for detaching and lockingly attaching the reservoir to the housing.

[0071] FIG. 22 shows the system with the reservoir 125 and a portion of the outer housing removed. As mentioned, the first detachment mechanism 1905 is configured to attach to the reservoir. Specifically, the first detachment mechanism 1905 includes a spring loaded or tensioned structure that is biased toward locking engagement with a seat 2020 (FIG. 21), structure, or opening in the housing of the reservoir. The first detachment mechanism 1905 is biased to automatically engage and lock with the seat 2020 (or other structure) and lock the reservoir 125 to the housing when it is inserted. In this manner, the detachment mechanism 1905 mechanically prevents the reservoir from being removed from the housing unless the user pulls on, disengages, or otherwise releases the first detachment mechanism 1905 from the reservoir. A user can disengage the first detachment mechanism 1905 from the reservoir by pulling on a structure such as a ring or tab of the first detachment mechanism 1905 to release it from the reservoir. Thus the user must pull out the first

detachment mechanism relative to the housing and/or reservoir to release the reservoir from the housing.

[0072] With reference still to FIG. 22, second detachment mechanism 1920 is a rotatable structure such as a wheel with threads that engage the neck 2010 (FIG. 21) or a portion thereof of the reservoir 125. In an embodiment, the wheel of the second detachment mechanism 1920 is rotated (such as by a three quarter turn or other turn range) by a user once the reservoir 125 is attached to the outer housing. Rotation of a knob the second detachment mechanism 1920 lockingly and sealingly engages the opening 2005 of the reservoir to the knob and to internal conduits of the system that fluidly couple the fluid in the reservoir to the nozzles.

[0073] In this regard, an outlet conduit 2115 fluidly communicates with the internal region of the reservoir when the reservoir is attached and lockingly sealed to the housing. The outlet conduit 2115 can be fluidly attached to a pump inlet conduit 2120 of the pump 1005 such as via a hose (not shown). The pump 1005 has an outlet conduit 2125 that can be fluidly attached to the hose coupler 1320 (FIG. 13) of the nozzle assembly. In this manner, the pump can create a pressure differential that draws fluid from the reservoir and drives it to the nozzle assembly.

[0074] In an embodiment, a hose or tube connects the outlet conduit 2125 of the pump 1005 to the hose coupler 1320 of the nozzle assembly. The tube (or other conduit) that connects the pump 1005 to the nozzle assembly may be configured to electrostatically charge fluid flowing through the tube by direct charging between the tube, which is charged, and the fluid that flows through the tube toward the nozzles. This is described in more detail with reference to FIG. 24, which shows an ion tube isolator 2405 that electrically charges fluid flowing from the reservoir or pump and toward the nozzles. The ion tube isolator includes the tube 2410 through which fluid passes as well as a high voltage electrode assembly or module 2415 that is electrically connected to the electrostatic module and that is made of a conductive material such as metal. The module 2415 can include a lead where it can be electrically connected to the electrostatic module such as via a conductive wire.

[0075] In an embodiment the module 2415 is a conductive material, such as metal. In an embodiment only the module 2415 is conductive and the remainder of the tube 2410 is non-conductive and/or is insulated from contact with any other part of the system. The module 2415 may also be surrounded by an insulator that insulates it from contact with any other part of the system. As fluid flows through the tube 2410, the module 2415 directly contacts the fluid as it flows and passes a charge to the fluid through direct contact with the fluid. In this way, the ion tube isolator 2405 electrostatically charges the fluid prior to the fluid passing through the nozzle.

[0076] In an embodiment, the pump 1005 is a direct current (DC) pump. The pump includes a rotary motion motor with a connecting rod that drives a diaphragm in an up and down motion when activated. In the process of the downward movement of the diaphragm, a pump cavity creates a pressure differential such as by pulling a vacuum relative to the interior of the reservoir to suck fluid through the pump inlet conduit 2120 from the reservoir. Upward movement of the diaphragm pushes fluid of the pump cavity press through the pump outlet conduit 2125 toward the hose coupler 1320 of the nozzle assembly via an attachment hose that attaches the pump outlet conduit 2125 to the hose

coupler **1320**. Any mechanical transmission parts and the pump cavity are isolated by the diaphragm within the pump. The diaphragm pump does not need oil for auxiliary lubricating, in the process of transmission, extraction and compression of the fluid. FIG. **23** shows an exemplary embodiment of the pump **1005**, which includes the pump inlet conduit **2120** and the pump outlet conduit **2125**.

[0077] In use, the user grasps the system **105** and powers the pump so that it propels fluid out of the selected nozzle from the reservoir. As mentioned, the user can use the nozzle tool **1205** to both insert and lock the nozzle assembly **1015** to the system. The user can also use the nozzle tool **1205** to rotate the nozzle component and fluidly couple a selected nozzle to the reservoir. Thus the user can select a desired plume profile for the fluid. The system can also be equipped with just a single nozzle. The user also activates the electrostatic module so that the electrodes become charged and form an electrostatic field in the electrode ring. The fluid is propelled from the nozzle through the ring and through the electrostatic field so that the droplets of fluid in the aerosol plume become positively or negatively electrically charged. As mentioned, the electrodes and the nozzle are aligned along a common parallel axis. This directs the liquid or aerosol toward a desired object based on where the user points the nozzles. In an embodiment, the electrodes do not physically contact the fluid propelled through the nozzles. In another embodiment, the electrodes physically contact the fluid propelled through the nozzles.

[0078] While this specification contains many specifics, these should not be construed as limitations on the scope of an invention that is claimed or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or a variation of a sub-combination. Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results.

1. An electrostatic sprayer device, comprising:

a housing;

an electrostatic module inside the housing;

a reservoir having a cavity adapted to contain a fluid;

at least one nozzle fluidly connected to the reservoir wherein the nozzles emit fluid in a direction along a flow pathway;

a pump that propels fluid from the reservoir to the at least one nozzle;

a direct current battery that powers at least one of the electrostatic module and the pump;

an electrode assembly that electrostatically charges the fluid, wherein the electrode assembly is at least one of:

(1) a first electrode assembly formed of a plurality of electrodes electrically attached to the electrostatic module, wherein each electrode emits ions along an

axis that is parallel to the flow pathway of the fluid emitted from the nozzle such that the plurality of electrodes form a static electrical field through which the fluid passes; and

(2) a second electrode assembly formed of a tube that fluidly through which fluid flows from the reservoir toward the at least one nozzle, wherein at least a conductive portion of the tube is electrically attached to the electrostatic module, and wherein the conductive portion of the tube physically contacts the fluid as it flows through the tube and applies an electrical charge to the fluid.

2. A sprayer device as in claim 1, wherein the electrode assembly includes both the first electrode assembly and the second electrode assembly.

3. A sprayer device as in claim 1, wherein the electrode assembly includes only one of the first electrode assembly and the second electrode assembly.

4. A sprayer device as in claim 1, wherein the plurality of electrodes of the first electrode assembly are positioned on a ring through which the flow pathways passes.

5. A sprayer device as in claim 1, wherein the plurality of electrodes includes three electrodes spaced in 120 degree increments about the ring.

6. A sprayer device as in claim 1, wherein each electrode of the first electrode assembly is an elongated pin that extends along an electrode axis that is parallel with a direction along which the at least one nozzle emits fluid.

7. A sprayer device as in claim 1, wherein the at least one nozzle includes three nozzles.

8. A sprayer device as in claim 7, wherein each of the three nozzles are movable so that a user can selectively couple a desired nozzle to the reservoir.

9. A sprayer device as in claim 1, wherein the at least one nozzle is positioned on a nozzle housing, and wherein the nozzle housing and the at least one nozzle is removable from the housing.

10. A sprayer device as in claim 9, further comprising a tool that can remove the nozzle housing.

11. A sprayer device as in claim 10, wherein the at least one nozzle includes three nozzles that are movable so that a user can selectively couple a desired nozzle to the reservoir, and wherein the tool can also move the nozzles.

12. A sprayer device as in claim 1, wherein the housing is sized and shaped to be held in a single hand of a user.

13. A sprayer device as in claim 12, wherein the housing includes a handle and a trigger that is actuated to active the device.

14. A sprayer device as in claim 1, wherein the housing at least partially forms a backpack.

15. A sprayer device as in claim 1, wherein each electrode of the first electrode assembly is an elongated pin, and further comprising an insulator that contacts and covers the pin such that only a tip of the pin is not insulated.

16. A sprayer device as in claim 15, wherein the reservoir is removably from the housing.

17. A sprayer device as in claim 1, wherein the pump pulls a vacuum in the housing to cause fluid to flow from the reservoir to the at least one nozzle.

18. A sprayer device as in claim 1, wherein the housing includes a handle and further comprising a ground wire in the handle, the ground wire positioned so that the ground wire contacts a user's hand when a user grasps the handle.

\* \* \* \* \*