(12) STANDARD PATENT (11) Application No. **AU 2016380695 B2**
(19) AUSTRALIAN PATENT OFFICE

(54) Title
Electronic fall event communication system

(51) International Patent Classification(s)
G08B 21/04 (2006.01) ***G08B 25/08*** (2006.01)

(21) Application No: **2016380695** (22) Date of Filing: **2016.07.12**

(87) WIPO No: **WO17/116501**

(30) Priority Data

(31) Number	(32) Date	(33) Country
62/273,049	**2015.12.30**	**US**

(43) Publication Date: **2017.07.06**
(44) Accepted Journal Date: **2020.01.02**

(71) Applicant(s)
3M Innovative Properties Company

(72) Inventor(s)
Perner, Judd J.

(74) Agent / Attorney
FPA Patent Attorneys Pty Ltd, ANZ Tower 161 Castlereagh Street, Sydney, NSW, 2000, AU

(56) Related Art
GB 2507787 A
US 20150223705 A1
US 20130135097 A1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
6 July 2017 (06.07.2017)

WIPO | PCT

(10) International Publication Number
WO 2017/116501 A1

(51) International Patent Classification:
G08B 21/04 (2006.01) *G08B 25/08* (2006.01)

(21) International Application Number:
PCT/US2016/041830

(22) International Filing Date:
12 July 2016 (12.07.2016)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
62/273,049 30 December 2015 (30.12.2015) US

(71) Applicant: **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; P.O. Box 33427, St. Paul, Minnesota 55133-3427 (US).

(72) Inventor: **PERNER, Judd J**; P.O. Box 33427, St. Paul, Minnesota 55133-3427 (US).

(74) Agent: **SANNES, Robin A**; Dicke, Billig & Czaja, PLLC, Fifth Street Towers, Suite 2250, 100 S. Fifth Street, Minneapolis, Minnesota 55402 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

— *with international search report (Art. 21(3))*

(54) Title: ELECTRONIC FALL EVENT COMMUNICATION SYSTEM




FIG. 1

(57) Abstract: The fall event detection and communication system includes at least one fall detect node and a personal communication application. The at least one fall detect node is to be implemented as part of a fall protection system. The at least one fall detect node includes at least one detection element and a node transmitter. The at least one detection element is to generate an activation signal upon a condition that indicates a fall event has occurred. The node transmitter is to transmit at least one fall detect signal upon receiving the activation signal from the at least one detection element. The personal communication application is stored in a personal communication device. The personal communication application is to cause the personal communication device to monitor for the fall detect signal and cause the personal communication device to communicate with a remote communication device upon determination that a fall event has occurred.

WO 2017/116501 A1

2016380695 23 Aug 2019

ELECTRONIC FALL EVENT COMMUNICATION SYSTEM

BACKGROUND

[0001] Fall protection is critical for occupational health and safety of workers required to work at heights. Unlike other types of hazards a worker is exposed to such as electrical or mechanical hazards, gravitational potential energy is a universal hazard that affects every organization that requires work done at heights. To combat the dangers associated with working at heights, fall protection equipment manufacturers have developed devices to safely arrest a fall of a worker during a fall event. Although these devices generally perform as intended and safely arrest a worker's fall, there is still potential for harm to come to the worker if the worker is not rescued in a timely manner. This situation is especially relevant when the worker is working alone in a remote location.

[0002] For the reasons stated above and for other reasons stated below which will become apparent to those skilled in the art upon reading and understanding the present specification, there is a need in the art for an effective and efficient way to communicate a fall event to a third party.

[0002a] Reference to any prior art in the specification is not an acknowledgment or suggestion that this prior art forms part of the common general knowledge in any jurisdiction or that this prior art could reasonably be expected to be understood, regarded as relevant, and/or combined with other pieces of prior art by a skilled person in the art.

SUMMARY OF INVENTION

[0003] The above-mentioned problems of current systems are addressed by embodiments of the present disclosure and will be understood by reading and studying the following specification. The following summary is made by way of example and not by way of limitation. It is merely provided to aid the reader in understanding some of the aspects of the disclosure.

[0004] In accordance with a first aspect, the present invention provides a system comprising: a fall protection harness configured with a fall detect node, wherein the fall protection harness is configured to be worn by a worker and arrest a fall of the worker during a fall event, and wherein the fall detect node is configured to transmit a first fall

2016380695 23 Aug 2019

detect signal in response to the fall of the worker; a personal communication device comprising one or more computer processors configured to: configure the fall detect node with the personal communication device via short-range wireless communication at a time when the worker dons the fall protection harness; in response to receiving the first fall detect signal via short-range wireless communication based on the fall of the worker, determine an amount of time during which the personal communication device receives at least the first fall detect signal; and in response to determining that the amount of time during which the personal communication device receives at least the first fall detect signal is greater than or equal to a configured time in the personal communication device, send, via wireless communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.

[0005] In accordance with a second aspect, the present invention provides a computing device comprising: a memory; and one or more computer processors, wherein the memory comprises instructions that when executed by the one or more computer processors cause the one or more computer processors to: configure a fall detect node with the computing device via short-range wireless communication at a time when a worker dons a fall protection harness, wherein the fall protection harness is configured with the fall detect node, wherein the fall protection harness is configured to be worn by the worker and arrest a fall of the worker during a fall event, and wherein the fall detect node is configured to transmit a first fall detect signal in response to the fall of the worker; in response to receiving the first fall detect signal via short-range wireless communication based on the worker, determine an amount of time during which the computing device receives at least the first fall detect signal; and in response to determining that the amount of time during which the computing device receives at least the first fall detect signal is greater than or equal to configured time in the computing device, send, via wireless communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.

[0006] In accordance with a third aspect, the present invention provides a fall detect node, configured for a fall protection harness worn by a worker to arrest a fall of the

2016380695 23 Aug 2019

worker, wherein the fall detect node comprises: at least one detection element configured to generate a fall detect signal in response to the fall of the worker; a transmitter configured to transmit the fall detect signal in response to the fall of the worker; and a controller configured to: configure a fall detect node with a computing device via short-range wireless communication at a time when the worker dons the fall protection harness, wherein the fall protection harness is configured with the fall detect node; in response to receiving the first fall detect signal from the at least one detection element, transmit, via the transmitter using short-range wireless communication, the first fall detect signal to be computing device to cause the computing device to in response to determining that an amount of time during which the computing device receives at least the first fall detect signal is greater than or equal to a configured time in the computing device, send, via wireless communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.

[0006a] As used herein, except where the context requires otherwise, the term "comprise" and variations of the term, such as "comprising", "comprises" and "comprised", are not intended to exclude further additives, components, integers or steps.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The present disclosure can be more easily understood and further advantages and uses thereof will be more readily apparent, when considered in view of the detailed description and the following figures in which:

[0008] Figure 1 is a block diagram of a fall event detection and communication system;

[0009] Figure 2 is an application flow diagram of one embodiment of the present disclosure; and

[0010] Figure 3 is an application flow diagram for another embodiment of the present disclosure.

[0011] In accordance with common practice, the various described features are not drawn to scale but are drawn to emphasize specific features relevant to the present disclosure. Reference characters denote like elements throughout Figures and text.

DETAILED DESCRIPTION

[0012] In the following detailed description, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration specific embodiments in which the disclosure may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the disclosure, and it is to be understood that other embodiments may be utilized and that changes may be made without departing from the spirit and scope of the present disclosure. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present disclosure is defined only by the claims and equivalents thereof.

[0013] Embodiments of the present disclosure provide a fall event detection and communication system. An example of a fall event detection and communication system 100 is illustrated in Figure 1. The fall event detection and communication system 100 in this embodiment includes at least one fall detect node 200a, 200b or 200c, a personal communication device 300 and a remote communication device 400.Each fall detect node 200a, 200b and 200c in this embodiment includes a least one detection element 230a, 230b or 230c, a transmitter 220 and a power supply 215. The fall detect nodes 200a, 200b and 200c are implemented as part of a fall protection system that is used by a user while working at heights. Examples of the implementation of at least one fall detect node 200a, 200b or 200c are described below.

[0014] As discussed above, the fall detect node 200a, 200b or 200c, in the embodiment of Figure 1 includes at least one detection element 230a, 230b or 230c, a transmitter 220 and a power supply 215. The at least one of the detection elements 230a, 230b or 230c is used to detect a fall event. Each detection element 230a, 230b and 230c is in communication with the transmitter 220. Examples of detection elements 230a, 230b and 230c include, but are not limited to, switches or sensors that detect conditions that indicate a fall event has occurred. For example, in one embodiment, one of the detection

elements 230a, 230b or 230c is a pressure switch such as a spring loaded switch that is activated when a select weight is applied. In another embodiment, one of the detection elements 230a, 230b or 230c is an accelerometer sensor. Once at least one of the detection elements 230a, 230b or 230c detects a fall event, a respective activation signal 231a, 231b and 231c is sent to the transmitter 220. Upon receiving the activation signal, the transmitter 220 of the respective fall detect node 200a, 200b or 200c, powered by the power supply 215, transmits a fall detect signal 221a, 221b or 221c. In one embodiment, the fall detect signal 221a, 221b and 221c is a short range communication signal, such as but not limited to, a Bluetooth signal. A Bluetooth signal is a wireless signal using a Bluetooth wireless technology standard for exchanging data over short distances. The Bluetooth standard uses short-wavelength UHF radio waves.

[0015] In an alternative embodiment, at least one of the fall detect nodes 200a, 200b or 200c further includes a node memory 218 in which a node application 216 is stored. This embodiment also includes a node controller 210 to implement the node application 216 and a node clock 250. In an embodiment, the node controller 210 using instructions stored in the application 216 controls the transmitter 220 to transmit the fall detect signal 221a, 221b or 221c only after a select period of time has passed, determined with the use of the clock 250, in which one of the detection elements 230a, 230b or 230c has continuously detected a fall event. Although only three fall detection nodes 200a, 200b and 200c and three detection elements 230a, 230b and 230c per each fall detection node 200a, 200b and 200c is illustrated in Figure 1, any number of fall detection nodes having at least one detection element could be used and the present disclosure is not limited to only three fall detection nodes 200a, 200b and 200c and three detection elements 230a, 230b and 230c per each fall detection node 200a, 200b and 200c.

[0016] The personal communication device 300 includes a near receiver 330 to receive the fall detect signal from the transmitter 220 of the fall detect node 200a, 200b and 200c. In one embodiment, the personal communication device 300 is a cellular phone. However, any type of personal communication device that can receive the fall detect signal can be used. For example, with the Bluetooth standard being used as the near communication standard, a cell phone with a receiver that communicates with the Bluetooth standard can be used. The personal communication device 300 in the embodiment of Figure 1 also includes a personal communication controller 310 such as a

processor, a personal communication clock 350, an input/output 315, a personal communication memory 318 and a transceiver 340.

[0017] The personal communication controller 310 controls operation of the personal communication device. Instructions implemented by the personal communication controller 310 to operate the personal communication device 300 are stored in the memory 318. Also illustrated in Figure 1 in the personal communication device 300 is a personal communication application 320 that is also stored in the personal communication memory 318. The personal communication application 320 is a specific set of instructions implemented by the personal communication controller 310 for a specific purpose as described below. The personal communication controller 310 implements the application instructions when the application is activated by the user through the input/output 315 of the device 300. The personal communication clock 350 in this embodiment is used, among other reasons, to count the time the personal communication device 300 is receiving a fall detect signal 221a, 221b or 221c from the fall detect node 200a, 200b or 200c.

[0018] The transceiver 340 is used by the personal communication device 300 to send and receive signals over long distances. In the cellular phone example, the transceiver 340 would send and receive signals over a cellular network to a remote communication device 400. The remote communication device 400 could be another cell phone or land line that is located remote to the personal communication device 300. Through the personal communication transceiver 340 of the personal communication device 300, a fall alarm message 341 is sent to a remote transceiver 420 of the remote communication device 400 in embodiments. Moreover, in one embodiment, the personnel communication device 300 includes one or more detection elements 317a and 317b. Similar to the detection elements 230a, 230b and 230c in the fall detection node 200a, 200b and 200c, detection elements 317a and 317b can be used to detect fall events. An example of a detection element 317a and 317b is an accelerometer. However, other types of detection elements can be used in the personal communication device.

[0019] Referring to Figure 2, an application flow diagram 500 of one embodiment is illustrated. The process starts by the user getting prepared for working at a height (502). In one embodiment, this would include implementing a fall protection system. For

example, implementing fall protection system may include donning a safety harness and configuring the application 320 in the personal communication device 300 (504). The configuration may include providing a communication number to call if a fall event is detected, how long a fall detect signal 221a, 221b or 221c needs to be observed from the fall detect node 200a, 200b or 200c before a fall alarm message 341 is sent to the remote communication device 400, the type of fall alarm message 341 to send and content of the fall alarm message 341, etc. Once the application 320 is configured (504), the application 320 is activated on the personal communication device 300 (506). The personal communication device is then attached to the user who is going to be working at heights (508). The user then works at heights (510).

[0020] While the user is working at heights, the personal communication device 300 monitors for a fall detect signal 221a, 221b or 221c (512) pursuant to the directions set out by the application 320. If no fall detect signal 221a, 221b or 221c is detected (514), the process continues at (512). If a fall detect signal 221a, 221b or 221c is detected (514), in one embedment, the controller 310 of the personal communication device 300 starts a timer (516) (tracks time using the clock 350) pursuant to the instructions of the application 320. The controller 310 counts the time the near receiver 330 in this embodiment is receiving the fall detect signal 221a, 221b or 221c (518). If the continuous time receiving a fall detect signal 221a, 221b and 221c is less than the time configured in the application (520), the process continues back at (512) monitoring for a fall detect signal 221a, 221b or 221c. If the continuous time receiving fall detect signal 221a, 221c or 221c is equal or greater than the time configured in the application (520), the controller 310 of the personal communication device 300 activates the transceiver 340 to send a fall alarm message 341 to the remote communication device 400 (522).

[0021] Based on the received fall alarm message 341, rescue personal will be sent to rescue the fallen user. An example of a period of time configured in the application is a time that is more than 10 seconds and an example of a weight used by a fall detect node 200a, 200b or 200c to send the fall detect signal 221a, 221b or 221c is 130 lbs or more. In another embodiment, as discussed above, at least one of the fall detect nodes 200a, 200b or 200c is equipped to determine the continuous time its respective detection element 230a, 230b or 230c has detected a fall event. In this embodiment, a respective fall detect signal 221a, 221b or 221c will only be sent after the period of time has been confirmed.

Further in this embodiment, the controller 310 of the personal communication device, pursuant to the instructions stored in the application 320, sends the fall alarm message 341 as soon as the respective fall detect signal 221a, 221b or 221c is detected.

[0022] Figure 3 illustrates an application flow diagram 530 of another embodiment. In this embodiment, at least two different detection elements are used when initiating a fall alarm message 341. For example, the at least two different detection elements may be selected among detection elements 230a, 230b, 230c, 317a and 317b. The process starts by the user getting prepared for working at a height (532). In one embodiment this would be done by implementing a fall protection system. Implementing the fall protection system may include donning a safety harness and configuring the application 320 in the personal communication device 300 (534). The configuration may include providing a communication number to call if a fall event is detected, the number of different signals from different detection elements 230a, 230b, 230c, 317a, 317b that are needed for a determination and verification of a fall event, how long a fall detect signal 221a, 221b and 221c needs to be observed from a detection element 230a, 230b, 230c, 317a and 317b before a fall alarm message 341 is sent to the remote communication device 400, type of fall alarm message 341 to send and content of fall alarm message 341, etc. Once the application 320 is configured (534), the application 320 is activated on the personal communication device 300 (536). The personal communication device is then attached to the user who is going to be working at heights (538). The user then works at heights (540).

[0023] While the user is working at heights, the personal communication device 300 monitors for fall detect signals (542), (552) and (556) pursuant to instructions set out by the application 320. The fall detect signals could be fall detect signals 221a, 221b, 221c. Moreover, the fall detect signals may come from detection elements 317a and 317b. Although the application flow diagram 530 indicates three different types of fall detect signals as used in this example, such as fall detect signals 221a, 221b and 221c from three different detection elements 230a, 230b and 230c, any number of different types of detection elements can be used.

[0024] In the application flow diagram 530 of Figure 3, a personal communication device 300 monitors for a first fall detect signal, such as fall detect signal 221a from the

first detection element 230a. In this embodiment, when a first fall detect signal 221a is detected (544), a timer is started (546). The controller 310 counts the time the near receiver 330 in this embodiment is receiving the fall detect signal 221a (548). If the continuous time receiving the fall detect signal 221a is less than the time configured in the application (550), the process continues back at (542) monitoring for the fall detect signal 221a. If the continuous time receiving the fall detect signal 221a is equal or greater than the time configured in the application (550), the controller 310 in this embodiment confirms if at least one other fall detect signal has been detected (560). For example, communication device 300 monitors for a second fall detect signal, such as fall detect signal 231b from the second detection element 230b at (552) and a third fall detect signal, such as fall detect signal 231c from the third detection element 230c at (556).

[0025] As stated above, in this embodiment, if two or more fall detect signals 221a, 221b and 221c are detected (544), (554) and (558), the fall alarm message 341 is sent to the remote communication device 400 (562). Hence, this embodiment allows for the confirmation of a fall event by requiring at least two independent fall detect systems to detect a fall event simultaneously. This cuts down on false fall detection events. For example, one detection element 230a may be a sensor that measures a load, while detection element 230b is a switch that is activated when a certain amount of force is applied and detection element 230c may be an accelerometer. Moreover, as discussed above, the personal communication device may include detection elements 317a and 317b (such as, but not limited to, accelerometer and/or decelerometer) that can also be used alone or in conjunction with detection elements 230a, 230b and 230c in the fall detect node 200a, 200b and 200c to detect and confirm fall events. Moreover, in another embodiment, at least one fall detect node 200a, 200b or 200c is equipped to count periods of time a fall event is detected by a detection element 230a, 230b, and 230c. In this embodiment, the personal communication controller 310 is configured to recognize that a fall event has been detected as soon as a fall detect signal 221a, 221b or 221c from the respective at least one node 200a, 200b and 200c is detected. The controller 310 in this embodiment would wait for at least one other fall detect signal for verification until a fall alarm message is sent.

[0026] Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that any arrangement, which is

calculated to achieve the same purpose, may be substituted for the specific embodiments shown. This application is intended to cover any adaptations or variations of the present disclosure. Therefore, it is manifestly intended that this disclosure be limited only by the claims and the equivalents thereof.

2016380695 23 Aug 2019

CLAIMS

1. A system comprising:

a fall protection harness configured with a fall detect node, wherein the fall protection harness is configured to be worn by a worker and arrest a fall of the worker during a fall event, and wherein the fall detect node is configured to transmit a first fall detect signal in response to the fall of the worker;

a personal communication device comprising one or more computer processors configured to:

configure the fall detect node with the personal communication device via short-range wireless communication at a time when the worker dons the fall protection harness;

in response to receiving the first fall detect signal via short-range wireless communication based on the fall of the worker, determine an amount of time during which the personal communication device receives at least the first fall detect signal; and

in response to determining that the amount of time during which the personal communication device receives at least the first fall detect signal is greater than or equal to a configured time in the personal communication device, send, via wireless communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.

2. The system of claim 1:

wherein the fall detect node comprises a plurality of detection elements;

wherein the personal communication device is configured to receive, from the plurality of detection elements, a plurality of fall detect signals comprising at least the first fall detect signal; and

wherein the personal communication device is configured to send the fall alarm message to a remote communication device in response to a determination by the personal

2016380695 23 Aug 2019

communication device that at least the plurality of fall detect signals are received from the fall detect node.

3. The system of claim 2:

wherein the personal communication device is configured to send the fall alarm message to a remote communication device in response to a determination by the personal communication device that at least the plurality of fall detect signals are received from the fall detect node for the amount of time that is greater than or equal to the configured time in the personal communication device.

4. The system of claim 2:

wherein the personal communication device is configured to send the fall alarm message to the remote communication device in response to a determination by the personal communication device that the plurality of fall detect signals comprising at least the first fall detect signal are received by the personal communication device at the same time.

5. The system of claim 2:

wherein the personal communication device is configured to send the fall alarm message to the remote communication device in response to a determination by the personal communication device that a second fall detect signal in the plurality of fall detect signals was received by the personal communication device after waiting for both the first fall detect signal and the second fall detect signal, wherein the first fall detect signal was received prior to the second fall detect signal.

6. The system of claim 2, wherein the plurality of detection elements comprises two or more of an accelerometer, a switch that is activated in response to a certain amount of applied force, or a sensor that measures a load.

7. The system of claim 2, wherein the configured time in the personal communication device is at least 10 seconds.

2016380695 23 Aug 2019

8. The system of claim 1, wherein the personal communication device is configured to send the fall alarm message to the remote communication device in response to a determination by the personal communication device that the plurality of fall detect signals comprises a second fall detect signal that is generated based at least in part on a determination by the fall detect node that a weight detected by the fall detect node is greater than a configured weight at the personal communication device.

9. A computing device comprising:

a memory; and

one or more computer processors, wherein the memory comprises instructions that when executed by the one or more computer processors cause the one or more computer processors to:

configure a fall detect node with the computing device via short-range wireless communication at a time when a worker dons a fall protection harness, wherein the fall protection harness is configured with the fall detect node, wherein the fall protection harness is configured to be worn by the worker and arrest a fall of the worker during a fall event, and wherein the fall detect node is configured to transmit a first fall detect signal in response to the fall of the worker;

in response to receiving the first fall detect signal via short-range wireless communication based on the fall of the worker, determine an amount of time during which the computing device receives at least the first fall detect signal; and

in response to determining that the amount of time during which the computing device receives at least the first fall detect signal is greater than or equal to a configured time in the computing device, send, via wireless communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.

10. The computing device of claim 9:

2016380695 23 Aug 2019

wherein fall detect node comprises a plurality of detection elements;

wherein the memory comprises instructions that when executed cause the one or more computer processors to:

receive, from the plurality of detection elements, a plurality of fall detect signals comprising at least the first fall detect signal; and

send the fall alarm message to a remote communication device in response to a determination by the computing device that at least the plurality of fall detect signals are received from the fall detect node.

11. The computing device of claim 10, wherein the memory comprises instructions that when executed cause the one or more computer processors to:

send the fall alarm message to a remote communication device in response to a determination by the computing device that at least the plurality of fall detect signals are received from the fall detect node for the amount of time that is greater than or equal to the configured time in the computing device.

12. The computing device of claim 10:

wherein the computing device is configured to send the fall alarm message to the remote communication device in response to a determination by the computing device that the plurality of fall detect signals comprising at least the first fall detect signal are received by the computing device at the same time.

13. The computing device of claim 10:

wherein the computing device is configured to send the fall alarm message to the remote communication device in response to a determination by the computing device that a second fall detect signal in the plurality of fall detect signals was received by the computing device after waiting for both the first fall detect signal and the second fall detect signal, wherein the first fall detect signal was received prior to the second fall detect signal.

2016380695 23 Aug 2019

14. The computing device of claim 10, wherein the plurality of detection elements comprises two or more of an accelerometer, a switch that is activated in response to a certain amount of applied force, or a sensor that measures a load.

15. The computing device of claim 10, wherein the configured time in the computing device is at least 10 seconds.

16. The computing device of claim 9, wherein the computing device is configured to send the fall alarm message to the remote communication device in response to a determination by the computing device that the plurality of fall detect signals comprises a second fall detect signal that is generated based at least in part on a determination by the fall detect node that a weight detected by the fall detect node is greater than a configured weight at the computing device.

17. A fall detect node, configured for a fall protection harness worn by a worker to arrest a fall of the worker, wherein the fall detect node comprises:

at least one detection element configured to generate a fall detect signal in response to the fall of the worker;

a transmitter configured to transmit the fall detect signal in response to the fall of the worker; and

a controller configured to:

configure a fall detect node with a computing device via short-range wireless communication at a time when the worker dons the fall protection harness, wherein the fall protection harness is configured with the fall detect node;

in response to receiving the first fall detect signal from the at least one detection element, transmit, via the transmitter using short-range wireless communication, the first fall detect signal to the computing device to cause the computing device to in response to determining that an amount of time during which the computing device receives at least the first fall detect signal is greater than or equal to a configured time in the computing device, send, via wireless

2016380695 23 Aug 2019

communication that is different than the short-range wireless communication, a fall alarm message to a remote communication device that is configured to perform at least one operation based at least in part on at least one of a type or content of the fall alarm message.



100
PERSONAL COMMUNICATION DEVICE
300
CONTROLLER 310
CLOCK 350
MEMORY 318
APPLICATION 320
DETECTION ELEMENT 317a
317b
NEAR RECEIVER 330
TRANSCEIVER 340
INPUT/ OUTPUT 315
341
TRANSCEIVER 420
REMOTE COMMUNICATION DEVICE
400
200a
200b
200c
FALL DETECT NODE
POWER SUPPLY 215
CONTR 210
CLOCK 250
MEMORY 218
APPLICATION 216
221a
221b
221c
TRANSMITTER 220
231a
231b
231c
DETECTION ELEMENT 230a
230b
230c

FIG. 1



PREPARE TO START WORKING AT HEIGHT 502
CONFIGURE APPLICATION IN PERSONAL COMMUNICATION DEVICE 504
ACTIVATE APPLICATION 506
ATTACH PERSONAL COMMUNICATION DEVICE TO USER 508
WORK AT HEIGHT 510
MONITOR FOR FALL DETECT SIGNAL 512
SIGNAL DETECTED? 514
NO
YES
START TIMER 516
COUNT TIME RECEIVING FALL EVENT TRANSMISSION 518
TIME REC. => THAN SELECT TIME 520
NO
YES
SEND SIGNAL TO REMOTE COMMUNICATION DEVICE 522
500

FIG. 2



PREPARE TO START WORKING AT HEIGHT 532
CONFIGURE APPLICATION IN PERSONAL COMMUNICATION DEVICE 534
ACTIVATE APPLICATION 536
ATTACH PERSONNEL COMMUNICATION DEVICE TO USER 538
WORK AT HEIGHT 540
MONITOR FOR FIRST FALL DETECT SIGNAL 542
SIGNAL DETECTED? 544
NO
YES
START TIMER 546
COUNT TIME RECEIVING FALL EVENT TRANSMISSION 548
TIME REC. => THAN SELECT TIME 550
NO
YES
MONITOR FOR SECOND FALL DETECT SIGNAL 552
SIGNAL DETECTED? 554
NO
YES
MONITOR FOR THIRD FALL DETECT SIGNAL 556
SIGNAL DETECTED? 558
NO
YES
TWO OR MORE SIGNALS DETECTED? 560
NO
YES
SEND SIGNAL TO REMOTE COMMUNICATION DEVICE 562
530

FIG. 3