



US006434910B1

(12) **United States Patent**
Deane

(10) **Patent No.:** **US 6,434,910 B1**
(45) **Date of Patent:** **Aug. 20, 2002**

(54) **RUBBER CORE SPACER WITH CENTRAL CORD**

(75) Inventor: **Robert J. Deane**, Toronto (CA)

(73) Assignee: **AFG Industries, Inc.**, Kingsport, TN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/421,504**

(22) Filed: **Oct. 20, 1999**

Related U.S. Application Data

(60) Provisional application No. 60/115,953, filed on Jan. 14, 1999.

(51) **Int. Cl.⁷** **E04C 2/54**

(52) **U.S. Cl.** **52/786.13**

(58) **Field of Search** 52/309.7, 309.15, 52/309.16, 786.11, 786.13; 428/34

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,399,294 A * 8/1968 Thieben 52/759.13 X
3,573,149 A * 3/1971 Tibble et al. 52/786.13 X

3,965,638 A * 6/1976 Newman 52/786.13
4,658,553 A * 4/1987 Shinagawa
4,720,950 A * 1/1988 Bayer et al. 52/786.13 X
5,260,112 A 11/1993 Grether et al.
5,466,534 A 11/1995 Newby
5,806,272 A 9/1998 Lafond 52/786.13
5,851,609 A * 12/1998 Baratuci et al. 428/34

FOREIGN PATENT DOCUMENTS

DE 1534834 * 7/1969 52/786.13

* cited by examiner


Primary Examiner—Peter R. Brown

(74) *Attorney, Agent, or Firm*—Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

(57) **ABSTRACT**

Two glass panes are separated by a so-called core spacer made of either EPDM rubber or another solid rubber material with a centrally positioned fiberglass cord extending longitudinally therethrough for imparting strength to the core spacer. The EPDM rubber formulation is chemically compatible with hot melt butyl which is used as an adhesive between the solid rubber and the glass panes. The fiberglass cord is nonstretchable so that the core spacer does not deform or break apart when the core spacer is either initially manufactured or later placed between the two glass panes.

11 Claims, 6 Drawing Sheets






FIG. 1




FIG. 3




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 4e




FIG. 4f




FIG. 4g




FIG. 4h




FIG. 4i




FIG. 5




FIG. 6

RUBBER CORE SPACER WITH CENTRAL CORD

CROSS REFERENCE TO RELATED APPLICATION

This application claims priority from U.S. Provisional Patent Application Ser. No. 60/115,953 filed on Jan. 14, 1999.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to an insulated glass assembly and, in particular, to core spacers separating glass panes.

2. Description of the Related Art

Insulating glass is usually made of at least two panes adhered together along their edges by a core spacer. In the prior art, there are several types of core spacers manufactured from synthetic foam which is soft and easily compressed. Exemplary is the spacer shown in U.S. Pat. No. 5,806,272 which was issued to Lafond on Sep. 15, 1998.

However, such foam core spacers have minimal stability because of their easy compressibility. Furthermore, such foam spacers are readily stretched longitudinally, thus allowing them to be deformed or broken apart before, during or after installation in a window frame.

Another disadvantage of foam core spacers is that they often interact chemically with hot melt butyl, thus causing a stain discoloration which is unacceptable aesthetically. Such a chemical reaction further frequently causes a variety of other problems, like a change in adhesion strength, a shrinkage of the foam spacer, or an expansion thereof. Whenever a shrinkage occurs, the spacer tends to pull away from the corners where the glass panes are joined together. Likewise, if an expansion occurs, the foam spacer becomes misshapen and appears unattractive.

SUMMARY OF THE INVENTION

A solid EPDM rubber core spacer is provided with a centrally positioned, nonstretchable cord made of fiberglass or similar material for imparting strength thereto. Furthermore, the EPDM rubber formulation is chemically compatible with hot melt butyl which is used as an adhesive and as a moisture vapor barrier. Although there are many differences between the hot melt butyls manufactured by different companies, it is important to formulate an EPDM rubber which ensures chemical compatibility.

A key advantage of the present invention is improved stability over foam core spacers when in compression during oven pressing, packing, shipping, and installing in windows. In each situation, the solid rubber core spacer undergoes significantly less compression than the foam of the prior art spacers.

Another advantage of the present invention is the incorporation of the fiberglass cord into the rubber core spacer so that no stretching of the spacer occurs during initial manufacture, spacer assembly, coiling of the spacer, and application of the finished spacer between two glass panes. Also, heating and cooling of the spacer does not result in any deformation or breakage of the spacer when in use because of the presence of the continuous nonstretchable fiberglass cord incorporated therein. Of course, in the real world, everything can be stretched to a breaking point if a powerful enough pulling force is exerted. In that sense, the fiberglass cord is nonstretchable under normal conditions of use.

A further advantage of the present invention is that the chemical composition of the EPDM rubber in the core spacer is such that it does not react, other than in a minimally inconsequential way, with hot melt butyl. Thus, this feature of the present invention prevents a chemical reaction that could cause a stain discoloration, a change of adhesion strength, shrinkage, expansion or any other disadvantage inherent in the prior art foam core spacers whenever a chemical reaction takes place.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a first embodiment of the present invention.

FIG. 2 is a side elevational view of the first embodiment.

FIG. 3 is an exploded side elevational view of a second embodiment.

FIG. 4a is a side elevational view of a third embodiment.

FIG. 4b is a side elevational view of a fourth embodiment.

FIG. 4c is a side elevational view of a fifth embodiment.

FIG. 4d is a side elevational view of a sixth embodiment.

FIG. 4e is a side elevational view of a seventh embodiment.

FIG. 4f is a side elevational view of an eighth embodiment.

FIG. 4g is a side elevational view of a ninth embodiment.

FIG. 4h is a side elevational view of a tenth embodiment.

FIG. 4i is a side elevational view of an eleventh embodiment.

FIG. 5 is an exploded side elevational view of a twelfth embodiment.

FIG. 6 is a perspective view of the first embodiment.

DETAILED DESCRIPTION OF THE INVENTION

In FIG. 1, a first embodiment of a rubber core spacer **10**, noncircular in shape, is shown with a top side **12**, a bottom side **14**, a short side **16**, a long side **18**, and two diagonally cut corners **20** and **22**. A centrally positioned fiberglass cord **24** is embedded in the rubber core spacer **10** when the latter is manufactured. The preferred rubber formulation for the spacer **10** is an ethylene propylene diene monomer (EPDM) polymer with fillers. However, other solid rubber materials may be suitable.

The height H varies according to the width selected for the spacer **10**. Thus, the height H may range from as little as one quarter to three quarters of an inch or greater.

The cord **24** is cylindrical in shape and has a diameter of at least 0.01 inch which is sufficient for the cord **24** to be effective inside the spacer **10**. However, the preferred diameter is 0.02 inch.

In FIG. 2, a first hot butyl melt adhesive **26** is applied around the three sides **12**, **14**, **16** and the corners **20** and **22** of the core spacer **10**, although it is sufficient to be applied around only the top side **12** and the bottom side **14**. This first adhesive **26** sticks the core spacer **10** between a top glass pane **32** and a bottom glass pane **34**. After the first adhesive **26** is positioned, a desiccant **38** is arranged adjacent to the core spacer **10** and is spaced between the panes **32** and **34** by a second hot butyl melt adhesive **28** which is applied around at least two sides and preferably three sides of the desiccant **38** to hold the desiccant **38** between the panes **32** and **34**. This desiccant **38** is a drying agent intended to absorb any moisture between the panes **32** and **34** and is

open on one side **40** to the space separating the panes **32** and **34**. Desiccants are well known in the prior art and many types may be suitable.

In FIG. **3**, a second embodiment is shown in an exploded view in which the desiccant **38** has cut corners **46** and **48** to help the second adhesive **28** hold a vapor barrier **30** in place between the core spacer **10** and the desiccant **38**. The vapor barrier **30** may be a metallized plastic film embedded at both ends in the second adhesive **28**. The core spacer **10** remains in the same position, surrounded on all sides, except for the long side **18**, by the first adhesive **26**. The two panes **32** and **34**, as in the first embodiment seen in FIGS. **1** and **2**, are held apart by the core spacer **10** while the desiccant **38** absorbs any moisture in the space therebetween.

In FIG. **4a**, a third embodiment is shown in which the spacer **10** has its corners **20a** and **22a** cut longer than the corners **20** and **22** seen in the first embodiment of FIGS. **1** and **2**.

In FIG. **4b**, a fourth embodiment is shown in which corners **20b** and **22b** of the spacer **10** come to a point **16b** instead of to the side **16**, as seen in the first embodiment of FIGS. **1-2**.

FIGS. **4c** through **4g** show further embodiments in which patterns are cut into the top side **12** and the bottom side **14** of the spacer **10** to form voids for a purpose to be described.

In FIG. **4c**, a fifth embodiment is shown in which the spacer **10** has triangular indentations **12c** and **14c** in the top side **12** and the bottom side **14**, respectively.

In FIG. **4d**, a sixth embodiment is shown in which the spacer **10** has a plurality of serrated teeth **12d** and **14d** in the top side **12** and the bottom side **14**, respectively.

In FIG. **4e**, a seventh embodiment is shown in which the spacer **10** has scalloped recesses **12e** and **14e** in the top side **12** and the bottom side **14**, respectively.

In FIG. **4f**, an eighth embodiment is shown in which the spacer **10** has deep grooves **12f** and **14f** in the top side **12** and the bottom side **14**, respectively.

In FIG. **4g**, a ninth embodiment is shown in which the spacer **10** has a plurality of shallow channels **12g** and **14g** in the top side **12** and the bottom side **14**, respectively.

In FIG. **4h**, a tenth embodiment is shown in which the spacer **10** has wide depressions **12h** and **14h** in the top side **12** and the bottom side **14**, respectively. However, unlike the embodiments shown in FIGS. **4a** through **4g**, the spacer **10** in FIG. **4h** does not have any cut diagonal corners.

The purpose of the indentations **12c** and **14c** in FIG. **4c**, the teeth **12d** and **14d** in FIG. **4d**, the recesses **12e** and **14e** in FIG. **4e**, the grooves **12f** and **14f** in FIG. **4f**, the channels **12g** and **14g** in FIG. **4g**, and the depressions **12h** and **14h** in FIG. **4h**, is to allow the first adhesive **26** illustrated in FIGS. **1-3** to fill the voids therein so that the adhesive **26** sticks better to the spacer **10** and to the glass panes **32** and **34** of FIGS. **1-3**.

In FIG. **4i**, an eleventh embodiment is shown in which the spacer **10** has a rectangular cross section through which the cord **24** is centrally positioned. Note that there are no diagonally cut corners and no indentations.

In FIG. **5**, a twelfth embodiment is shown in which a third hot melt butyl adhesive **50** is used between the first adhesive **26** and the vapor barrier **30** to orient the vapor barrier **30** at both ends perpendicular to the glass panes **32** and **34**. The amount of the second adhesive **28** used is less than the amount used in the second embodiment of FIG. **3**. The third adhesive **50** may be uncured silicone or urethane.

Also, instead of the diagonally cut corners **46** and **48** of FIG. **3**, the twelfth embodiment in FIG. **5** has smaller square

cut corners **46a** and **48a** so that the desiccant **38** is left with a top surface **54** and a bottom surface **56** which provide additional frictional engagement with the top glass pane **32** and the bottom glass pane **34**, respectively. In this twelfth embodiment, the six-sided spacer **10** is the same size as the spacer **10** shown in the first and second embodiments of FIGS. **1-3**.

When heat is applied to cure the third adhesive **50**, the entire assembly of FIG. **5** has more structural integrity because the cured third adhesive **50** attaches itself firmly to the second adhesive **26**, the metallized vapor barrier **30**, and both glass panes **32** and **34**.

In FIG. **6**, the first embodiment of FIGS. **1** and **2** is shown in place, without the second adhesive **28** and the desiccant **38**, for ease of illustration. The spacer **10** is adhered at its top side **12** to the top glass pane **32** and also is adhered at its bottom side **14** to the bottom glass pane **34**. The pair of glass panes **32** and **34** are parallel to each other but are separated by an interior space **52** to form an entire insulated glass assembly. The spacer **10** extends around the entire periphery between the panes **32** and **34** in an airtight manner. At a 90° corner **42**, either the spacer **10** is flexed, thus causing some curvature in the corner **42**, or the spacer **10** is cut, thus allowing a sharp 90° corner **42** to be formed. In the latter case, an exterior corner void is back-filled with the adhesive **26**, as shown in the embodiments of FIGS. **2, 3** and **5**. Note that it is necessary to cut only the spacer **10** and not any other materials, such as the second adhesive **28** and the desiccant **38** in FIG. **2** or the same two materials and the vapor barrier **30** in FIG. **3**, or the three last listed materials and the adhesive **50** in FIG. **5**. Consequently, the nonstretchable fiberglass cord **24** running therethrough allows the spacer **10** to maintain its structural integrity. Thus, the entire insulated glass assembly is kept intact so that no moisture enters the interior space **52** between the panes **32** and **34**.

The above-described embodiments are not limiting, but can be modified in various ways within the scope and spirit of the present invention.

What is claimed is:

1. An insulated assembly having an interior space, comprising:
 - a pair of parallel panes separated by the interior space;
 - a core spacer with a single, nonheating, centrally positioned, nonstretchable cord embedded therein so that the core spacer is not stretchable; and
 - a first adhesive applied around at least two sides of the core spacer for sticking the core spacer between the pair of parallel panes;
 wherein the spacer and the cord extend around a periphery and go around corners between the panes in an airtight manner to form the insulated assembly; and
 - wherein the cord has a diameter no greater than about 10% of a width of the core spacer.
2. An insulated assembly, according to claim 1, wherein: said core spacer has a height between one quarter and three quarters of an inch and said cord has a diameter of at least 0.01 inch.
3. An insulated assembly according to claim 1, wherein: said parallel panes are flat sheets; said core spacer is noncircular in shape; and said cord is cylindrical in shape.
4. An insulated assembly, according to claim 3, wherein: said flat sheets are made of glass; said core spacer is made of rubber; and said cord is made of fiberglass.
5. An insulated assembly, according to claim 1, further comprising:
 - a desiccant arranged adjacent to the core spacer and spaced between the pair of parallel panes; and

5

a second adhesive applied around at least two sides of the desiccant to hold the desiccant between the pair of parallel panes.

6. An insulated assembly, according to claim 5, further comprising:

a vapor barrier held in place between the core spacer and the desiccant.

7. An insulated assembly, according to claim 6, further comprising:

a third adhesive applied between the first adhesive and the vapor barrier to orient the vapor barrier at both ends perpendicular to the pair of parallel panes.

6

8. An insulated assembly, according to claim 1, wherein: said core spacer is six-sided in shape with a top side, a bottom side, two other sides, and at least two cut corners.

9. An insulated assembly, according to claim 8, wherein: said top side and said bottom side of the core spacer have a pattern cut therein to form voids.

10. An insulated assembly, according to claim 9, wherein: said pattern is a plurality of shallow channels.

11. An insulated assembly, according to claim 1, wherein: said cord has its diameter no greater than about 0.02 inch.

* * * * *