

(19) (KR)
 (12) (B1)

(51) 。 Int. Cl. ⁶
 C23C 2/34 (45) 2001 10 24
 (11) 10 - 0297475
 (24) 2001 05 22

(21) 10 - 1994 - 0001186 (65) 1994 - 0018475
 (22) 1994 01 24 (43) 1994 08 18

(30) 08/008,105 1993 01 25 (US)

(73) 45043 703

(72) 4571

108

290

506

640

(74)

(54)

(66) (34A),
 (68) , (70) , (50,52) 가
 (64) , (74) (72) ,

1

[]

(Induction Heated Meniscus Coating Ve
ssel)

[]

1 가 ,

2 1

3

4 1

5 4 .

六

20 : 34, 34A, 34B :

38 : 46 :

50, 52 : 64 :

66 : 68 :

70 : 72 :

74 : 76, 78

[]

(meniscus coating)

가

가

(hot dip coating)

2 m

가

가

4,557,953 (steel)
(snout)

1991 12 4

07/803,278

가

가

가

가

가

, 가

가
가

가

가

가

가

가

가

, ,
(shallow vessel)

가

$$3 \quad . \quad 1 \quad , \\ 3 \quad . \quad . \quad (34) \\ A) \quad (58) \quad \text{가} \quad (58) \\ . \quad (62) \\ (\text{clcd. } 60)$$

[1]

4 5

가

304

, 2 cm

22 cm, 가 20 cm,

3 mm

4

5 cm, 가 22 cm, 가 14 mm
가 25 mm
50 61

460

가

(DC)

, 7

500

3.75 6.97 kW

, 가 435 , 510

[2]

838

, 13 cm

가

10 m/

1

(20)

/

465

가

500

7.23 kW

1

500

, 25 mm

(57)

1.

,
+,

, 가 가 , 가

가

2.

1 ,

3.

1 ,

4.

3 ,

5.

3 ,

6.

1 ,

가

7.

1 ,

가

8.

7 ,

9.

8 ,

10.

1 ,

11.

1 ,

12.

1

13.

1

가

14.

1

가

15.

16.

가 가 ,

가

, , 가

가

;

,

,

,

↗

,

17.

16

,

18.

17

,

,

19.

17

,


,

20.


16

,


20 mm




2



3





5

