



(22) Date de dépôt/Filing Date: 2003/05/02

(41) Mise à la disp. pub./Open to Public Insp.: 2003/11/20

(45) Date de délivrance/Issue Date: 2014/09/02

(62) Demande originale/Original Application: 2 484 222

(30) Priorité/Priority: 2002/05/06 (US60/378,901)

(51) Cl.Int./Int.Cl. *H04W 52/02* (2009.01),
H04B 7/005 (2006.01), *H04W 56/00* (2009.01)


(72) Inventeurs/Inventors:
GOLDBERG, STEVEN JEFFREY, US;
TERRY, STEPHEN E., US

(73) Propriétaire/Owner:
INTERDIGITAL TECHNOLOGY CORPORATION, US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : SYNCHRONISATION POUR ALLONGER LA DUREE DE VIE D'ACCUMULATEURS

(54) Title: SYNCHRONIZATION FOR EXTENDING BATTERY LIFE



(57) Abrégé/Abstract:

The present invention discloses a method and system for efficiently supporting data calls to WTRUs in systems that also support telephony. Various types of data is transmitted on a known schedule which is tightly synchronized to a predetermined time frame. The WTRUs synchronize their wake-up periods to search for data at times when data may or will actually be transmitted to them.

ABSTRACT

The present invention discloses a method and system for efficiently supporting data calls to WTRUs in systems that also support telephony. Various types of data is transmitted on a known schedule which is tightly synchronized to a predetermined time frame. The WTRUs synchronize their wake-up periods to search for data at times when data may or will actually be transmitted to them.

- 1 -

SYNCHRONIZATION FOR EXTENDING BATTERY LIFE

This application is a division of Canadian Patent Application Serial Number 2,484,222 filed internationally on May 2, 2003, and entered nationally in
5 Canada on November 4, 2004.

FIELD OF INVENTION

The present invention relates to the field of wireless communications. More specifically, the present invention relates to the optimization of power resources of
10 wireless devices within wireless communications systems.

BACKGROUND

The more often a battery operated device, such as a wireless transmit/receive unit (WTRU), looks for possible data being sent to it, the more
15 power the device consumes. In networks and devices that support not only telephony, but also data transmission, the manner in which the devices look for messages from the network varies, depending on whether the device is looking for incoming phone calls or incoming data transmissions.

With respect to telephony, users are accustomed to terrestrial networks
20 wherein a ringing sound is heard almost immediately after a particular telephone number is dialed. To meet this expectation in wireless environments, a WTRU must frequently scan the network to minimize the delay in establishing a connection as perceived by a person placing a phone call. That is, the WTRU must frequently scan the network for incoming calls to minimize the time
25 between when the network sends a calling signal or message and when the receiving WTRU actually checks for the calling signal.

This arrangement is quite suitable for telephony, but is inefficient for data transmission. With respect to data transmission, the strict requirements necessary for ensuring a near-instantaneous response to a call are not required.
30 Longer delays are generally tolerated when transmitting data to WTRUs such as pagers and similar devices, for example. However, it is generally expected, that

- 2 -

such devices respond to a message indicating that there is an incoming data transmission "in real time." Therefore, the network must also be scanned rather frequently in some cases when dealing with data transmission, but even in such situations the frequency with which the network must be scanned is less than
5 when dealing with telephony.

The amount of delay that is acceptable varies according to the type of data being transmitted and user preference. For example, longer delays are tolerated where information is infrequently updated, such as traffic or weather data. In the case of a pager, a reasonable response time could be evaluated in
10 terms of an anticipated time delay for the user to respond to a paged message.

In the case of multiple network transmissions (i.e. stock quotes, sport scores, etc.), some users want information occasionally updated so that they may have longer battery life. Other users have less concern for battery life and simply want data updated rapidly. Examples of users wishing frequent updates
15 would be people desiring immediate information updates and people whose WTRU is connected to an external power supply. In the case of stock quotes, for example, there are casual watchers, and those who desire immediate notification of changes. Thus, if the user would expect to respond to a message quickly, the response time should ideally be fairly quick, but still much greater
20 than the necessary response time for a WTRU becoming aware of an incoming telephone call.

It would therefore be desirable to have a method and system for efficiently supporting data transmissions as well as telephony.

25 SUMMARY

A wireless network permits WTRUs to operate in a quiescent mode of operation according to a synchronization schedule. Synchronization information is provided to the WTRUs to inform them of when they may be in a quiescent mode and when they need to wake up and retrieve data.

According to a first broad aspect of the present disclosure there is disclosed a method for use in a wireless transmit/receive unit (WTRU) operable in a

- 3 -

wireless network wherein data is provided in frames and each frame includes a plurality of physical slots, the method comprising: receiving a frame including a synchronization schedule from a base station, the synchronization schedule indicating at least one physical slot that includes data intended for the WTRU; 5 receiving data during the at least one physical slot identified as including data intended for the WTRU; and operating in a quiescent state during at least one physical slot not identified as including data intended for the WTRU.

According to another aspect, there is provided a method for use in a wireless transmit/receive unit (WTRU). The method comprises receiving, from a base 10 station, a frame including a synchronization schedule, wherein the frame includes a plurality of time slots and the synchronization schedule indicates at least one of the plurality of time slots that includes data intended for the WTRU. The method includes receiving data during the at least one of the plurality of time slots indicated as including data intended for the WTRU and operating in a quiescent state during at 15 least one of the plurality of time slots not indicated as including data intended for the WTRU.

According to another aspect there is provided a wireless transmit/receive unit (WTRU) comprising a receiver configured to receive, from a base station, a synchronization schedule, wherein data is received in frames and each frame 20 includes a plurality of time slots. The synchronization schedule indicates, for at least one frame, at least one of the plurality of time slots of the at least one frame that includes data intended for the WTRU. The WTRU includes a processor configured to activate the WTRU for receipt of data during the at least one of the plurality of time slots indicated as including data intended for the WTRU, and to operate the 25 WTRU in a quiescent state during at least one of the plurality of time slots not indicated as including data intended for the WTRU.

According to another aspect there is provided a method for use in a wireless transmit/receive unit (WTRU). The method comprises receiving a synchronization

- 3a -

schedule from a base station wherein data is received in frames and each frame includes a plurality of time slots and the synchronization schedule indicates, for each frame, which of the plurality of time slots include data intended for the WTRU. The method includes receiving data during each of the plurality of time slots indicated in the synchronization schedule as including data intended for the WTRU and entering a quiescent state during each of the plurality of time slots not indicated in the synchronization schedule as including data intended for the WTRU.

BRIEF DESCRIPTION OF THE DRAWING(S)

Figure 1 is a diagram showing a wireless communication network.

Figure 2 is a data diagram showing a frame structure used in an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

According to the present invention, synchronization information is provided to wireless transmit/receive units (WTRUs) to inform them of when they may be in a quiescent mode (i.e. when they may be asleep) and when they need to wake up and retrieve data. For purposes of describing the invention, a WTRU may have a transmit-only, a receive-only or a transmit-and-receive capability. That is, a WTRU may be any type of device capable of receiving and/or transmitting data in a wireless environment.

Referring now to Figure 1, a representation of a network is shown wherein one or more base stations 21 communicate with a plurality of WTRUs, such as WTRU 22 which will be referred to when describing the invention. The WTRU 22, as explained, can be any of a number of devices supported by the network. Examples include user equipment (UE), cellphone, pager, Blackberry (TM) device, computer with a modem connection or any other device that is capable of operating in a wireless environment. The base station 21 is controlled by a radio network

- 3b -

controller (RNC) 25 which performs various network supervisory and communications functions. The base station 21 includes signal processing circuitry 31 and an RF stage 32, which includes a transmit function. Signals from

the base station 21 are transmitted to the WTRUs within its cell or transmission area, as represented by antennas 33, 34. The WTRU 22 has an RF stage 37 and a signal processing stage 38. A receive function is provided by the WTRU's RF stage 37 in order to receive signals transmitted by the base station 21. In the case of two-way devices, the RF stages 32 and 37 have both transmit and receive functions, permitting the WTRU 22 to transmit data in an uplink and receive data in a downlink. While transmitting requires significantly greater power than receiving, issues of quiescent operation primarily affect the downlink, so the receiver function of the WTRU 22 is significant.

In accordance with the present invention, the WTRU 22 uses its signal processing circuitry 38 in order to control when the RF stage 37 is receiving signals from the base station 21. This allows the operation of the receive function of the WTRU 22 to be active primarily during times when signals are expected to include data intended for that particular WTRU 22. During at least some of the time when signals are not intended for that particular WTRU 22, the WTRU goes quiescent, meaning that most reception and signal processing by the WTRU 22 is turned off.

Regardless of the manner in which data is being transmitted from the network, the WTRUs are preferably synchronized so that they may wake up and go sleep to maximize battery life and satisfy user preferences. The synchronization information provided to the WTRUs is provided in accordance with the manner in which data is being delivered from the network. That is, regardless of the manner in which data is being transmitted from the network, synchronization information is provided to WTRUs so that they are aware of when they need to be awake and when they may go to sleep.

As known to those skilled in the art, data may be provided from the network to WTRUs in a variety of ways, as desired. In one embodiment, data may be transmitted in the form of scheduled transmissions. In this case, the network transmits various types of broadcast or multicast data on a known schedule that is tightly synchronized to a time frame known by both the transmitting WTRU and the receiving WTRU(s). The WTRUs can then

synchronize their wake-ups to search occurrences when data may or will be transmitted. To implement this embodiment in 3rd generation cellular networks, scheduling information can either be provided by a common control channel such as the Broadcast Common Control Channel (BCCH) signaling or a Dedicated
5 Control Channel (DCCH) signaling. Where BCCH signaling is used, scheduling (i.e. synchronization) information may be signaled for all broadcast and multicast services. If DCCH signaling is used, only scheduling of services that are specific to a receiving WTRU will be signaled.

In another embodiment, data may be transmitted in the form of multiple
10 network transmissions. That is, as mentioned, some users want information updated only occasionally in favor of longer battery life whereas others want data updated rapidly without regard for battery life. Therefore, in this embodiment, data is transmitted (even where there is no data change) at a rate that is consistent with a user's preference for the frequency of updates versus battery
15 life. By transmitting data at a rapid by synchronized pace (i.e. the highest available rate desired by a user) and repeating the transmissions even when there is no data change, individual receiving WTRUs can wake up and search for data at different time intervals, according to user preference. This satisfies the needs of both groups of users (as well as those in between) by providing an
20 adjustable degree of settings.

Since the amount of delay that is acceptable varies according to the particular user application, it is likely that any tradeoff between delay and power consumption would have different optimums for different users. Therefore latency (i.e. delay time) may be optimized based on usage, as low latency conflicts
25 with low power consumption. This becomes particularly significant during times when the WTRU is not in active use.

To implement this embodiment in 3rd generation cellular networks, once a receiving WTRU is aware of scheduled broadcast or multicast transmissions, the receiving WTRU can then acquire the service (i.e. the scheduled broadcast or
30 multicast transmissions) transmitted on either the Forward Access Channel (FACH) or the Downlink Shared Channel (DSCH) on an as needed basis. The

network will transmit the broadcast or multicast data in either Radio Link Control Transparent or Unacknowledged Mode, which allows the receiving WTRU to determine if reception is needed autonomously without requiring interaction or causing errors to be perceived in the network.

5 A modification to the embodiment where multiple network transmissions are provided is to transmit only until certain WTRUs in the network's range acknowledge receipt. This modification has the advantage of terminating the transmission when it is no longer necessary while also providing some robustness to the transmission of the information for appropriately enabled devices. This
10 modification has the disadvantage of requiring uplink transmissions from WTRUs and may not be suitable for a large number of WTRUs. With respect to implementation in 3rd generation cellular networks, there are several network acknowledgement alternatives. For example, where there is a single receiving WTRU, Radio Link Control Acknowledged mode provides an automatic repeat
15 request mechanism for assured delivery. When there are multiple receiving WTRUs, layer 3 acknowledgements can either be provided by Radio Resource Control signaling within the Access Stratum, or by transparent data transfer of Non Access Stratum signaling.

 In another embodiment, the network simply transmits the fact that there is
20 a message awaiting delivery. That is, rather than sending the message all the time, in some instances it is more efficient to just notify the WTRUs that a message for them exists. In 3rd generation cellular networks the availability of the message is identified by a common control channel, such as the BCCH. Those WTRUs that want the message will then request its transmission from the
25 network. The request for the message may either be for the particular message or registration with the multicast service for reception of one or more messages associated with that service. This approach is suitable when only a small number of WTRUs are expected to request the actual message, while many WTRUs may want the actual ability to do so. This situation may arise, for example, where
30 there is only limited information in the initial transmission informing WTRUs of a message's existence. In 3rd generation cellular networks, the receiving WTRU

- 7 -

will generate a request for the service with either layer Access Stratum or Non Access Stratum signaling. The network will then either signal broadcast scheduling information or establish a dedicated radio bearer for transmission of the service. That is, the network with knowledge of the number of WTRUs
5 requesting the message or service of multiple messages determines the most efficient method of transmission. If there are a large number of recipients, scheduling of information will be signaled on a common control channel. This information will identify a common channel such as the FACH or DSCH, and the time of transmission for reception of the service. If there are a small number of
10 WTRUs requesting the message or service a dedicated channel will be established to each requesting or registered WTRU associated with this message or service.

Referring now to Figure 2, a signal frame diagram including a sequence of transmissions transmitted by a base station to multiple WTRUs is shown. As mentioned, the delivery of transmissions is synchronized so that messages
15 directed to a particular WTRU or group of WTRUs associated with that message or service is delivered when that particular WTRU or group of WTRUs associated with that message or service is awake looking for data. To accomplish this, in one embodiment, the transmissions are divided into frames 54 wherein seventy two (72) frames 54 make up a superframe, as shown in Figure 2. For simplicity in
20 describing the invention, portions of two superframes 51, 52 are shown. It should be noted, however, that superframes 51, 52 are part of a repeating series of superframes, each having seventy two (72) frames. It should also be noted that a superframe having 72 frames is provided purely by way of example, as other multiframe sequences are possible.

25 The frames 54 are divided into time slots 56, as shown in an expanded view 71E of frame 71. The time slots 56 within each frame, such as frame 71, include transmission packets designated, for example, zero (0) through (14). Each time slot 56 may include data intended for one or more devices. By way of example, slot 6 includes data for WTRU 101 and slot 12 includes data for WTRUs 102 and
30 103.

WTRUs 101 through 103 preferably synchronize their reception so that they are able to receive data during their respective allocated time period. The use of fixed time periods for data reception means that, once a WTRU is provided with its synchronization information (i.e. information related to the particular time sequence of signals intended for that WTRU), the WTRU may synchronize with that time sequence and remain asleep (i.e. quiescent) for a portion of a superframe. This results in reduced power consumption because a WTRU in a quiescent state has most or all of its RF reception circuits turned off. The WTRU, preferably, has most of its signal processing circuits turned off as well. In this embodiment, the reduction in power consumption approximately corresponds to the number of frames that are ignored.

Once synchronized, WTRUs 101 through 103 wake up only in their respective slot, radio frame or multiframe associated with the particular interleaving period known as the transmission time interval (TTI). From the network perspective, for each superframe, the network will wait for frame 71, slot 6 before transmitting data to WTRU 101.

It should be noted that WTRUs may wake up at other times (i.e. other than their designated slots), if needed. For example, it may be necessary to wake up for certain common signals. Additionally, the network and WTRUs may be adapted so that a special "wake up" signal is transmitted from the network to a particular WTRU or group of WTRUs where it is necessary for the WTRU(s) to wake up and receive data outside of their designated slot.

It should be noted that the division of transmissions into superframes, frames, and slots may be varied as desired. For example, in the discussion above, it is assumed that a WTRU will wake up at least every superframe and look for data in at least one slot of at least one frame. However, as mentioned, data transmissions may be provided to users as desired so as to satisfy user preferences for battery life and frequency of data renewal. Therefore, the timing of a particular synchronization scheme may similarly be varied. By way of example, it is possible to create a synchronization schedule between network data delivery and a WTRU's receipt thereof wherein more than one superframe passes

- 9 -

between WTRU wake up periods within which a WTRU wakes up and looks for a message at its assigned frame and slot.

While the present invention has been described in terms of the preferred embodiment, other variations which are within the scope of the invention as
5 outlined in the claims below will be apparent to those skilled in the art.

CLAIMS

1. A wireless transmit/receive unit (WTRU) comprising:
a receiver configured to receive synchronization information indicating at least one time slot of a frame that contains data intended for the WTRU;
a plurality of signal processing components; and
a processor configured to control the plurality of signal processing components, to receive data during the at least one time slot of the frame that contains data intended for the WTRU, and to operate in a quiescent mode wherein at least one signal processing component is powered down during at least one time slot of the frame that does not contain data intended for the WTRU.
2. The WTRU of claim 1, wherein the at least one time slot of the frame contains data for multiple WTRUs.
3. The WTRU of claim 1, wherein the frame includes data intended for a plurality of WTRUs.
4. The WTRU of claim 1, wherein the synchronization information includes synchronization information for multiple WTRUs.
5. The WTRU of claim 1, wherein the synchronization information indicates at least one time slot that contains data for a plurality of WTRUs.
6. The WTRU of claim 1, wherein the synchronization information and the at least one time slot that contains data intended for the WTRU are in a same frame.
7. The WTRU of claim 1, wherein the synchronization information includes synchronization information for multiple frames.
8. The WTRU of claim 1, wherein the frame is a unicast frame.

- 11 -

9. The WTRU of claim 1, wherein the frame is a multicast frame.
10. The WTRU of claim 1, wherein the synchronization information is received in a first frame and the data intended for the WTRU is received in a second frame.
11. The WTRU of claim 1, wherein the synchronization information is received from a base station.
12. The WTRU of claim 1, wherein the receiver is a Code Division Multiple Access (CDMA) receiver.
13. A method for use in a wireless transmit/receive unit (WTRU) comprising a plurality of signal processing components, the method comprising:
 - receiving synchronization information indicating at least one time slot of a frame that contains data intended for the WTRU;
 - powering down one of the plurality of signal processing components during at least one time slot of the frame that does not contain data intended for the WTRU; and
 - receiving data during the at least one time slot of the frame that contains data intended for the WTRU.
14. The method of claim 13, wherein the at least one time slot of the frame contains data for multiple WTRUs.
15. The method of claim 13, wherein the frame includes data intended for a plurality of WTRUs.
16. The method of claim 13, wherein the synchronization information includes synchronization information for multiple WTRUs.
17. The method of claim 13, wherein the synchronization information indicates at least one time slot that contains data for a plurality of WTRUs.

- 12 -

18. The method of claim 13, wherein the synchronization information and the at least one time slot that contains data intended for the WTRU are in a same frame.

19. The method of claim 13, wherein the synchronization information includes synchronization information for multiple frames.



20. The method of claim 13, wherein the frame is a unicast frame.

21. The method of claim 13, wherein the frame is a multicast frame.

22. The method of claim 13, wherein the synchronization information is received in a first frame and the data intended for the WTRU is received in a second frame.

23. The method of claim 13, wherein the synchronization information is received from a base station.

24. The method of claim 13, wherein the WTRU is a Code Division Multiple Access (CDMA) WTRU.

**FIG. 1****FIG. 2**

