

1 563 038

(21) Application No. 50991/77 (22) Filed 7 Dec. 1977 (19)
 (31) Convention Application No. 748833 (32) Filed 9 Dec. 1976 in
 (33) United States of America (US)
 (44) Complete Specification Published 19 Mar. 1980
 (51) INT. CL.³ H02K 3/00 1/12 15/04
 (52) Index at Acceptance
 H2A DP
 B3A 188



(54) PEN RECORDER DRIVING MECHANISM

5 (71) We, GOULD INC., a corporation organized under the laws of the State of Delaware, United States of America, of 10 Gould Center, Rolling Meadows, Illinois 60008, United States of America, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed to be particularly described in and by the following statement:-The invention pertains generally to pen recording apparatus used in making visual records of an electrical input parameter and is more particularly directed to driving mechanisms for such recorders.

10 15 In the past pen recorders have been equipped with driving mechanisms for the pen assemblies which include a coil assembly rotatably mounted within a stator assembly. The stator assembly is generally provided with a permanent magnet arrangement coupled through an air gap to a highly permeable flux path. The coil assembly rotates in the air gap due to an electrical signal applied to a driving coil. The amount of rotation or deflection is functionally related to the amplitude of the electrical signal applied. A recorder pen or stylus is physically attached to the coil assembly to record the deflection associated with the amplitude of the signal as a visual trace on a recording medium, such as chart paper or the like.

20 25 30 These driving mechanisms for pen recorders, normally called "penmotors" are usually designed to include a low inertia coil assembly. These coil assemblies are generally self-supporting or frameless because low coil inertia is a prerequisite for a high speed recording operation.

35 40 45 The frameless coil assembly further includes a through shaft on which to mount the coil for rotation. It has been found that the presence of a one-piece shaft extending lengthwise through the core magnet and mechanically attached to supporting mem-

bers of the coil structure greatly enhances the structural rigidity of the coil assembly, such that it will not be deformed as a result of stresses incurred during normal operation. This is important to ensure that undesired extraneous mechanical deflections will not occur to affect the accuracy and the stability of the overall drive system.

50 55 Examples of advantageous penmotors having a centrally mounted axial shaft through a core magnet or a permeable core and the coil assembly are found in U.S. Patent 3,088,788 issued to A.D. Brown Jr. et al and U.S. Patent 3,550,156 issued to A.R. Thompson.

60 65 70 75 However, the through shaft construction does present certain difficulties for manufacturing the coil assembly. The coil windings are usually wound first and the shaft inserted through the coil by parting the windings. Partition of the windings must be accomplished with care as the insulation on the wire can be easily damaged causing a failure of the mechanism at a future date. Such a delicate operation is time consuming and adds unnecessarily to the expense of manufacturing penmotors. It has been suggested previously that the coils be wound already partitioned but experience had shown that the coil assembly cannot readily be wound in this manner.

80 85 Another disadvantage with through shaft construction is that the axial shaft must be located through the core. This through shaft mounting requires further processing of the core to provide a centrally located aperture for the placement of the axial shaft. An aperture of this sort will degrade the performance of a core magnet as it interferes with the domain orientation and poling of the magnet. Such a degradation of the magnetic field will reduce the torque the penmotor can provide to deflect the coil assembly.

90 The assembly of the through shaft and a

5	core magnet are also matters of concern. The through shaft construction necessitates that the coil assembly be assembled around the core magnet and that the delicate coil to shaft bonding and partition process be performed at this state.	70
10	This adds complexity to the already difficult manufacture. Moreover, it is relatively difficult to maintain nearly precise concentricity between the coil assembly and the core magnet since the coil assembly must have clearance around the core magnet and the through shaft must rotate with clearance in the core magnet aperture without binding.	75
15	The lack of precision tolerances stemming from the non concentricity introduced during assembly can cause other effects such as a long air gap. The shorter an air gap is made, the higher the flux density that can be maintained within the gap which can contribute significantly to the torque generated by the motor. Also, if the gap can be shortened, a more efficient heat transfer between the coil assembly and the outside shell will occur to improve performance.	80
20	The invention provides a penrecorder driving mechanism which substantially solves many of the problems found in the prior art. Included in the driving mechanism is a coil assembly without a through shaft. The elimination of the through shaft obviates the difficult assembly and construction problems heretofore encountered in penmotors.	85
25	According to the present invention there is provided a pen recorder driving mechanism having a rotatable coil assembly located within an air gap between a centrally positioned inner core magnet and highly permeable outer shell, the coil assembly comprising a laminated coil frame of a shape to rotate in said air gap around the core magnet, said coil frame having an inner frame on which a multiplicity of coil turns are wound and an outer frame on said inner frame and coil-turns, and first and second coaxial half shafts attached to said coil frame such that said coil frame is located coaxially between said first and second half shafts to define a longitudinal rotational axis for said assembly.	90
30	The present invention furthermore provides a method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder comprising forming a generally ring shaped outer frame member; forming a generally ring shaped inner frame member, winding a multiplicity of coil turns on said inner frame member; securing said inner frame member including said coil turns together with said outer frame member to form a laminated coil frame; shaping said coil frame into a generally rectangular closed loop having a pair of side legs	95
35	adjoined by a top transverse leg and bottom transverse leg; securing rotational mounting means including half shafts on said top transverse leg and on said bottom transverse leg to define the rotational axis of the assembly; and providing said coil turns with external terminal leads for carrying electrical signals to drive said coil assembly.	100
40	Features and advantages of the invention will be more fully understood and appreciated upon reference to the following detailed description of a preferred embodiment of the invention, given with reference to the accompanying drawings wherein:	105
45	<i>Figure 1</i> is a perspective view, partially in section, of a pen recorder system constructed in accordance with the invention illustrating a driving mechanism in detail;	110
50	<i>Figure 2</i> is a top view of the pen recorder driving mechanism illustrated in <i>Figure 1</i> ;	115
55	<i>Figure 3</i> is a cross sectional view of the driving mechanism taken along section line 3-3 in <i>Figure 1</i> ;	120
60	<i>Figure 4</i> is a cross sectional view of the coil assembly for the driving mechanism taken along section line 4-4 in <i>Figure 2</i> .	125
65	<i>Figure 5</i> is a perspective assembly drawing of the coil windings with the inner and outer support frames for the coil assembly illustrated in <i>Figure 4</i> ;	130
	<i>Figure 6</i> is a perspective view of a forming tool used to stretch the coil frame illustrated in <i>Figure 5</i> into a complex shape;	
	<i>Figure 7</i> is a side view of the coil frame illustrated in <i>Figure 5</i> and the forming tool illustrated in <i>Figure 6</i> in an unstretched configuration;	
	<i>Figure 8</i> is a cross sectional side view of an end piece and half shaft for the coil assembly illustrated in <i>Figure 4</i> before forming;	
	<i>Figure 9</i> is a cross sectional side view of the end piece and half shaft illustrated in <i>Figure 8</i> after forming;	
	<i>Figure 10</i> is a perspective assembly drawing of the joining of the end pieces and half shafts illustrated in <i>Figure 10</i> to the coil frame illustrated in <i>Figure 4</i> ; and	
	<i>Figure 11</i> is a representative flow diagram of the sequence of steps used to manufacture the coil assembly illustrated in <i>Figure 3</i> .	
	In the drawings the convention that identical reference numerals indicate the same structure throughout the different views is maintained.	
	With reference now to the first illustration, <i>Figure 1</i> , there is shown a pen recorder system including a driving mechanism 10 constructed in accordance with the invention. The driving mechanism 10 has a coil assembly 12 mounted for rotation within a substantially annular outer shell 14. Coaxially positioned within the outer shell 14 and aligned with the axis of rotation of coil assembly 12 is a solid cylindrically shaped inner core magnet 16.	

Generally, the coil assembly 12 rotates or deflects in response to electrical signals applied via terminal leads 17. The current flowing through the windings of the coil assembly 12 in response to the electrical signals will coat with the magnetic flux developed between the outer shell 14, and inner core magnet 16 to produce a torque on the coil assembly proportional to the current. 5

In a conventional manner, the deflection of the coil assembly 12 is used to drive a recording apparatus such as a pen assembly 18. The pen assembly 18 is connected to the coil assembly 12 at the vertical upper half shaft 19 and effectuates the lateral crossings of a pen 20 on a transversely moving record medium 22 such as chart paper or the like. Thus as the record medium is passed over a positioning roller 24 from a supply roll 26 in the direction of the arrow, a visual trace representative of the electrical signal applied to the terminal leads 17 is recorded on the medium 22 by the pen 20. 10

A transducer 21, connected to the coil assembly 12 through a transducer arm 25, and lower half shaft 23 is used to provide a feedback position signal indicative of the pen position. 15

The terminal leads 17 and transducer leads 15 can be connected to an electrical control circuit (not shown) which will provide the electrical signals to the coil assembly from a driving amplifier in a conventional manner. Usually, an input signal representative of a physical quantity such as pressure, temperature, resistance, etc. will be combined with the feedback signals developed by the transducer 21, a velocity source, and other compensating signals to form the controlling signal to the driving amplifier. Preferably, the coil assembly 12 has an internally wound driving coil. Further, the driving mechanism 10 may include a bucking coil and or velocity coil for compensation as is known in the art. 20

The pen assembly 18 and an electrical control circuit adapted to drive a pen motor of this type with a position feedback signal transducer similar to that indicated at 21, detailed descriptions of which are not needed for an understanding of the invention, are more fully described in the before referenced U.S. Patent 3,281,688 issued to Brown et al. 25

Turning now to Figure 2, the positioning of the coil assembly 12 between the inner core magnet 16 and the outer shell 14 is illustrated. The upper portion of the driving mechanism 10 has been removed for clarity in the description. 30

The outer shell 14 formed of a highly permeable material has a cylindrical bore passing therethrough defined by an inner surface 29. Concentrically mounted within the bore of the outer shell 14 and precisely positioned by arcuately shaped spacer shoes 28 and 30 is the cylindrical inner core magnet 16. 35

The spacer shoes 28, 30 extend longitudinally the length of magnet 16 and are provided with deformable fins on their outer periphery which abuts the inner surface 29. Preferably the spacer shoes 28, 30 are manufactured from a heat conducting and nonmagnetic material such as aluminum. The fins deform during the mounting of the magnet 16 to take up excess tolerances. 40

Attached to the inner core magnet 16 by an epoxy adhesive or other conventional method is a pair of arcuately shaped pole shoes 32, 34. The pole shoes are centered on the opposing north, south pole orientations of the cylindrical inner core magnet 16 which is poled in the direction of a transverse axis. The pole shoes are preferably formed of a highly permeable material and extend longitudinally the length of the inner core magnet 16. 45

The pole shoes provide a means for easily mounting the inner core magnet 16 within the center of the coil assembly 12 which has arcuate side legs of the same general shape as an air gap 44. The greater clearance of the circumference of the magnet 16 not covered by the pole shoes is used for centering the magnet within the coil assembly 12. The inner core magnet 16 and pole shoes 32,34 are then rotated one quarter turn to align the poles and pole shoes of the magnet within the coil assembly 12. The combination of the coil assembly 12 and inner core magnet 16 are then positioned by the spacer shoes 28, 30 to form the precision air gap 44. During mounting the core magnet is bonded to the spacer shoes 28, 30 to fix its position within the bore. 50

Alternatively, the inner core magnet 16 could have straight edged cut outs on either side of the North, South poles to provide clearance for mounting within the coil assembly 12 instead of the pole shoes provided. Of course, with such a configuration the spacer shoes 28, 30 would have a flat inner edge machined for aligning the core magnet concentric to the inner bore. The pole shoe configuration is preferred as it permits magnetic alignment of the magnet 16 more easily than does the cut out method. 55

The air gap 44 can be shorter than air gaps usually found in pen motor driving mechanism because, according to the invention, the coil assembly can be reproducibly manufactured to closer tolerances and the necessary clearance heretofore used is reduced. Also, the elimination of the through shaft permits concentric alignment and a reduction of clearance between the coil assembly 12, the inner bore of the shell 14, and the core 60

70 75 80 85 90 95 100 105 110 115 120 125 130

magnet 16.

Normally, in penmotors such as described in Brown et al having a through shaft, air gaps on the order of 80 mils with a flux density of 4000-5000 gauss have been common. In the driving mechanism 10 an air gap on the order of 35 mils with a flux density of approximately 8000 gauss can be generated using a solid cylindrical core magnet of a permalloy, Alnico 5, and a highly permeable outer shell 14 of soft magnetic material. In an air gap of this dimension, the coil assembly 12 will be preferably no greater than 20-22 mils in thickness and the remainder clearance.

The coil assembly 12 can be freely deflected in the air gap 44 along the pole shoes in the directions of the arrows. At the outwardly extents of the deflection arcs are set of soft plastics rod shaped bumpers 36, 38, 40, 42 to protect the coil assembly from any destructive over excursions.

The short precision air gap 44 of this configuration produces the further advantage of having increased heat dissipation from the coil assembly. In the configuration described the heat produced by the current flowing through coil assembly windings is efficiently transferred to the inner core and outer shell via the narrow air gap. Long air gaps provide excessive insulation in the form of a thick air layer and may allow a temperature rise in a coil assembly and secondarily increase resistance and power loss. The small clearances of the present coil assembly 12 result in excellent heat transfer between the assembly and the outer shell 14 whereby a temperature increase as low as 3°C/watt has been achieved.

There has been shown above a preferred configuration for the driving mechanism 10 where a central core magnet without an aperture is coupled magnetically through the air gap 44 to a highly permeable outer shell. Alternatively, the central cylindrical portion can be used as a highly permeable flux path with the outer shell having arcuately shaped magnetic poles.

As is illustrated in Figure 3, the air gap 44 extends longitudinally the length of the inner core magnet 16 and pole shoe 32, 34 to the inner face of the shell 14. The concentric positioning of the coil assembly 12 within the air gap 44 and round the core magnet 16 is ensured by a lower bushing 54 and upper mounting bearing 52 which journal the lower half shaft 23 and upper half shaft 19 respectively of the coil assembly for rotation.

The outer race of the ball bearing 52 is press fitted into an aperture drilled through a generally disc shaped upper casing cap 46. The bushing 54 is located in an aperture bored coaxially therewith in a lower casing 48. The casing caps 46, 48 are positioned

coaxially with the inner bore of the shell 14 by having generally annular shaped raised portions 64, 66 respectively extending into the bore.

The upper rim of bushing 54 supports a thrust washer 56 on which the coil assembly 12 rotates while the lower rim of the bushing rests on the surface of a cylindrical relieved section of a generally disc shaped support sleeve 62. The outer flange of the support sleeve 62 is provided with a spacer ring 60 to position its lower surface evenly with that of a mounting plate 58. The transducer 21 is mounted on the plate 58 and support sleeve 62.

The half shafts of the coil assembly 12 extend through the upper and lower casing caps 46, 48 to permit motive attachments thereto. The upper half shaft 19 which drives the pen assembly 18 (shown in phantom) fits into the bore of a pen assembly mounting housing 50 which mounts into a circular recess in the upper casing cap 46. The lower half shaft protrudes from the bushing 54 through an opening in the support sleeve 62 to drive the transducer arm 25. The transducer arm 25 pinned to the shaft 23 swings freely within the field of the transducer core lamination to produce the position feedback signal.

The lower half shaft 23 importantly acts as a conduit for the terminal leads 17 from the windings of the coil assembly. The leads are shielded in this manner and are not exposed to extensive twisting or flexure which may cause their breakage. Moreover, the electrical leads are less likely to bind or become entangled between any moving surface of the rotating coil assembly and adjacent structure.

With more particularity the coil assembly 12 includes an integrally formed generally rectangular or square coil frame 70 having an upper transverse leg 72 and a lower transverse leg 74 connected on either end by the longitudinally extending side legs 76, 78. The side legs are substantially arcuate in shape and of similar curvature to the air gap 44 in which they rotate. The laminar construction and shape of side leg 78 is more clearly illustrated in cross section in Figure 2.

The transverse legs 72, 74 have a similar arcuate curvature to the side legs 76, 78 but as will be more fully explained hereinafter, the curvature is directed inwardly to the coil frame 70 as opposed to the outwardly directed curvature of the transverse legs.

As can be seen more clearly in the cross sectional view of Figure 4, the coil frame 70 has a laminar construction comprising an inner frame 80, a plurality of windings 82 forming preferably the driving coil and a velocity coil, if used, and an outer frame 84. These three laminations are held together

with a bonding material to form the coil frame 70 in the compound shape hereinafter described. Overlaying the transverse legs 72, 74 are a top end piece 86 and a bottom end piece 88. Each end piece, for example 86, has an arcuate curvature that is opposite to that of the transverse leg associated therewith and a pair of laterally extending tabs 90 and 92 which are fixed to corresponding tabs 94 and 96 of the inner frame 80 by welding, soldering, or the like.

The interspaces formed by the oppositely directed curvatures of the transverse legs and the end pieces are filled with a bonding material 98 which further rigidifies the composite structure of the coil frame and end pieces in a laminar form similar to the coil frame. On the end pieces are welded tubular half shafts 19, 23 defining the longitudinal rotational axis for the coil assembly 70. The insulated electrical leads 17 are brought from the windings 82 via the inner bore of the half shaft 23 and an aperture in the bottom end piece 88.

The method for making the coil assemble 12 will now be broadly outlined with reference to the flow chart of steps in Figure 11. Initially, the inner frame 80 and the outer frame 84 are each formed into a ring shape. Then the windings 82 of the driving coil and a velocity coil if used, are wound on the inner ring frame 80 and have an application of bonding material applied to them. Before the bonding material is cured the outer frame 84, inner frame 80, and windings 82 are assembled into a laminar ring structure and subsequently shaped by a forming tool 120 into the generally rectangular or square coil frame 70. Subsequently, the end pieces 86, 88 are formed and attached to the half shafts 19, 23. At this time the coil frame 70 is attached to the end pieces 86, 88. In an additional step bonding material is used to fill the interspaces between the end pieces and the coil frame. Finally, the coil assembly 12 is cured to allow the bonding material to harden and rigidify the structure.

The individual method steps for forming the coil assembly 12 will now be more particularly described. The formation of the coil frame 70 will be better illustrated by reference to Figure 5. The outer frame 84 is constructed of a flexible strip 110 which is bent into ring 111 by attaching its ends together by electrical welding or the like. Preferably, the material is a nonmagnetic strip of stainless steel approximately .002 inches in thickness. The outer frame 84 includes a notch 112 which later provides access to the windings 82 on the inner frame 80.

The inner frame 80 is similarly formed into a ring 113 by the adjoining of the two ends of a generally flat flexible strip 114 by electrical welds or the like. The strip 114

preferably is also formed of nonmagnetic stainless steel of approximately .002 in thickness. The strip 114 has been cut out to leave tabs, such as tabs 94, 96 remaining.

The driving coil and the optional velocity coil windings 82 are now wound on the inner frame 80 in a conventional manner. To facilitate the winding process the tabs 94, 96 can be bent slightly upwards to form a channel for guiding the windings 82. The inner frame 80 can be stretched by a ring arbor to a stop to bend the tabs upwardly and for assuring its dimension. For a driving coil with a resistance of 10 ohms, which will normally match the impedance of a conventional driving amplifier, it is preferred to use two layers of Isonel insulated 32 gauge annealed copper wire approximately 18 mils thick overall. The velocity coil can be wound as is conventional to match the characteristics of the control circuitry.

When the driving and velocity coils have been wound, the inner frame 80 has an application of bonding material 116 applied. The bonding material is applied to saturate the windings and preferably is an epoxy adhesive with the trade name of Stycast 1217 Registered Trade Mark made by Emerson & Cummings of Canton, Massachusetts.

The bonding material 116 can also be any one of a number of adhesive agents which rigidify upon the application of heat, pressure, time or other process steps. The bonding material should flow easily to provide a thin but saturating covering of the windings. The function of the bonding material is to hold the laminations of the coil frame together rigidly after setting up without deformation under moderate temperatures and the invention is not limited to using any one bonding material.

The assembly of the coil frame 70 is completed after the winding step by positioning the outer frame 84 over the inner frame 80, windings 82 and bonding material to form a slip fit. This step provides a laminar ring shaped structure which can be stretched into the final generally rectangular or square form of the coil frame 70.

In Figure 6 a specially shaped forming tool 120 is used for stretching the coil frame 70 after it is assembled into the laminar ring of the inner frame, windings and outer frame. The forming tool 120 comprises four mateable section blocks 122, 124, 126, 128 that together generally form a right parallelepiped. The blocks 122, 124, 126, 128 have semi-circular inner faces 132, 134, 136, 138 which when joined provide a central mounting aperture. The tool 120 is provided in four blocks to clear the inner bore of the laminar ring 70 before stretching.

On each block, for example block 128, is a convex forming face 140 and a concave

70

75

80

85

90

95

100

105

110

115

120

125

130

5 forming face 142 of substantially identical but reverse radius of curvature. These faces when the blocks are assembled together and placed within the laminar ring (formed as explained in Figure 5) are expanded outwardly by a four jaw chuck equally in the direction of the arrows, as illustrated in Figure 7, to stretch the ring into the generally rectangular or square concave-convex shape for coil frame 70 illustrated in Figure 10. 70

10 By having the working surfaces of the section blocks of equivalent curvature the side legs 76, 78 of the coil frame 70 are formed precisely to the arcuate curvature and clearance of size of the air gap by the convex faces while the transverse legs 72, 74 are formed into equivalent channels for after filling with a bonding material by the 20 concave faces. The tool 120 is expanded to a stop which accurately dimensions the coil frame 70. It is the ability to precisely determine the final dimensions of the coil frame 70 which provides many of the advantages for the driving mechanism 10 previously mentioned. 75

15 The equivalent curvature further permits the windings on the inner frame to remain substantially the same length during the coil formation as equal strains are applied to the frame legs during the stretching process. 80

20 It is seen preferably that the inner and outer frames are of stainless steel. Other metals and materials that may be shaped or formed in the manner illustrated and that are relatively light and thin in lamination can be used for the inner and outer frames. Further, the shape of the coil assembly need not be limited to the generally rectangular 25 or square forming tool shown as the forming tool's shape can be changed to provide a coil frame that will fit a multiplicity of different shaped air gaps. Also, the forming tool may be heated to facilitate the forming process if the material of the inner and outer frame is thermally formable. 85

30 Still further, the working faces of the tool are not necessarily limited to the preferred curvatures described but may be changed in order to enhance any of the advantages 90 herebefore described.

35 Each end piece 86, 88 is formed identically and is attached to a half shaft by the steps illustrated in Figures 8 and 9. Initially an 40 end piece in the form of a flat strip 144 is center punched and has a rod 146 with a wedge shaped tool end 148 passed through the punch. The half shaft 100 is held coaxial with the punch against the strip as the rod 45 146 is pulled through the inner bore of the half shaft. By additionally holding the edges 156 of the plate 144 stationary while the tool end 148 forms a flashing 150 within the half shaft 100, the rod 146 will shape the center 50 shaft into a curvature 154. The curvature 154 is designed to be the same arcuate shape as the legs of the coil frame 70. While positioned by the flashing 150 the half shaft 100 can be braced to the end piece at 152. Preferably, the end pieces are formed from strips of .006" thick stainless steel. As described above, other materials may be used for the end pieces. Also, the end pieces may be formed by other processes such as stamping or the like. 95

55 The final assembly step in the manufacture of the coil assembly 12 is illustrated in Figure 11 where the tabs of end piece 86 are joined to the tabs of the upper transverse leg of the coil frame 70 and the tabs of end piece 88 are joined to the tabs of the lower transverse leg of the coil frame 70. The juncture may be formed by electrical welds or other conventional techniques. Prior to the juncture of the end piece 88 to the coil frame the terminal leads 17 may be soldered or joined to the windings 82 through the notch (shown dotted) and brought out through the inner bore of half shaft 23. 100

60 The end pieces have a curvature oppositely directed to the concave channel like curvature of the coil frame 70 and thus form an interspace that is filled by a bonding material 117 to form a frame-epoxy-frame lamination similar to the coil frame. As previously described, the coil assembly 12 is subsequently cured by heating it for a predetermined time to set the epoxy. 105

65 Preferably, the bonding material 117 is Stycast 1095, Registered Trade Mark, a filled epoxy bonding agent produced by Emerson & Cummings of Canton, Massachusetts. The filler is a low density material (glass beads) which reduces the weight of the bonding material in the interspaces. The bonding material 117 can however, be the equivalents before mentioned, for the bonding material 116. 110

70 In this manner, the invention provides a laminar coil assembly 12 which is precisely dimensioned to obtain the advantages discussed. Further, the laminar structure is torsionally and structurally rigid without a through shaft. Since this strength is provided by the light laminar construction, the effect of the coil frame inertia on the response time of the coil assembly is negligible. In the preferred embodiment the coil frame 70 adds less than one-third to the total 75 of the inertia of the windings while additionally protecting them from damage. 115

75 While the preferred embodiment of the invention has been disclosed, it will be understood that various modifications obvious to one skilled in the art can be made thereto without departing from the scope of the invention as defined by the appended claims. 120

80 **WHAT WE CLAIM IS:-**

85 1. A pen recorder driving mechanism 130

having a rotatable coil assembly located within an air gap between a centrally positioned inner core magnet and a highly permeable outer shell, the coil assembly comprising a laminated coil frame of a shape to rotate in said air gap around the core magnet, said coil frame having an inner frame on which a multiplicity of coil turns are wound and an outer frame on said inner frame and coil-turns, and first and second coaxial half shafts attached to said coil frame such that said coil frame is located coaxially between said first and second half shafts to define a longitudinal rotational axis for said assembly. 70

2. A pen recorder driving mechanism as defined in claim 1 wherein said laminated coil frame further included a bonding material which holds said inner frame, said coil turns, and said outer frame rigidly together. 75

3. A pen recorder driving mechanism as defined in claim 1 or 2 wherein said laminated coil frame is substantially a closed loop around said inner core magnet and has a first side leg extending through said air gap at one pole of said inner core magnet and a second side leg oppositely located in the air gap at the other pole and extending therethrough, said first side leg and said second side leg being joined at each end into said loop by laterally directed transverse legs. 80

4. A pen recorder driving mechanism as defined in claim 3 wherein said air gap of the driving mechanism is substantially arcuate in shape and said legs of the coil frame are convexly formed to fit with clearance in said gap. 85

5. A pen recorder driving mechanism as defined in claim 4 wherein said transverse legs of said frame are concave with respect to said side legs. 90

6. A pen recorder driving mechanism as defined in claim 5 wherein the curvature of the side legs is equal to the curvature of the transverse legs. 95

7. A pen recorder driving mechanism as defined in any preceding claim including end piece means connecting said half shafts to said coil frame, said end piece means comprising laminar end piece members extending along said transverse legs, said half shafts being mounted perpendicularly on said end piece members. 100

8. A pen recorder driving mechanism as defined in claim 7 wherein at least one of said half shafts is hollow and said outer frame has a notch for allowing external electrical terminal leads to the coil turns to pass therethrough; said end piece further having an aperture for the passage of said electrical connections, thereby providing a protected passage way for the electrical terminal leads of the coil by way of the interior of said hollow half shaft. 105

9. A pen recorder driving mechanism as defined in claim 1 wherein: said laminated coil frame is adequately proximate to the outer shell inner core magnet as to allow for heat transfer from the coil assembly to the outer shell. 110

10. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder comprising forming a generally ring shaped outer frame member, forming a generally ring shaped inner frame member; winding a multiplicity of coil turns on said inner frame member; securing said inner frame member including said coil turns together with said outer frame member to form a laminated coil frame; shaping said coil frame into a generally rectangular closed loop having a pair of side legs adjoined by a top transverse leg and bottom transverse leg; securing rotational mounting means including half shafts on said top transverse leg and on said bottom transverse leg to define the rotational axis of the assembly; and providing said coil turns with external terminal leads for carrying electrical signals to drive said coil assembly. 115

11. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as is defined in claim 10 wherein said step of forming a generally ring shaped outer frame member includes the step of bending an outer frame strip of flexible material into a circular ring and adjoining the ends of said strip while it is still bent into the ring shape thereby forming the initial configuration of said outer frame. 120

12. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as is defined in claim 11 wherein said step of forming a generally ring shaped outer frame member includes notching the strip to provide the outer frame with an opening for passing the windings on the inner frame through. 125

13. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as is defined in claim 10, 11 or 12 wherein said step of forming a generally ring shaped inner frame includes the step of bending a thin inner frame strip of flexible material into a circular ring and adjoining the ends of said strip while it is still bent into the ring shape thereby forming the initial configuration of said inner frame member. 130

14. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as is defined in claim 13 wherein said step of forming a generally ring shaped inner frame includes forming tab sections on both sides of said inner frame strip for attaching said rotational mounting means to said coil assembly. 130

15. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 10

wherein said step of winding a multiplicity of coil turns on said inner frame member includes winding a driving coil and a velocity coil together on said inner frame.

5 16. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 10 wherein said step of securing said inner frame member and said outer frame member includes saturating the windings or said inner frame with a bonding material and assembling said outer frame over said windings and inner frame to form a laminar ring structure.

10 17. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 16 wherein the securing together of said inner frame member and said outer frame member includes stretching the laminar ring structure by a ring arbor.

15 18. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 17 wherein the step of shaping the coil frame includes providing a expandable forming tool in the general configuration of a right parallelepiped having side leg forming faces and transverse leg forming faces; placing said forming tool within the coil frame; and expanding said forming tool against the coil frame such that the forming faces stretch the coil frame into a generally rectangular closed loop defined by the shape of the forming tool.

20 19. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 18 wherein the step of shaping the coil frame includes: providing said side leg forming faces with a convex curvature; providing said transverse leg forming faces with an equivalent concave curvature; whereby said expanding step stretches the coil turns on the frame equally and produces the generally rectangular closed loop configuration with the coil turns substantially the same length.

25 20. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder as defined in claim 18 wherein the securing of said rotational mounting means to the coil frame includes steps of: forming end piece means with an arcuate cross section of substantially equivalent curvature as said transverse leg, said curvature being convex with respect to said transverse leg; attaching a half shaft to each end piece means; fixing one of said end piece means to the upper transverse leg of said coil frame and the other to the bottom transverse leg with the convex curvature of the end pieces oppositely deposited to the concave curvatures of said transverse legs thereby forming an interspace therebetween

30 and filling the interspaces between said end piece means and said transverse legs with bonding material.

35 21. A pen recorder driving mechanism substantially is hereinbefore described with reference to the accompanying drawings.

40 22. A method of manufacturing a laminated coil assembly for the driving mechanism of a pen recorder, substantially as hereinbefore described with reference to the accompanying drawings.

45 23. A laminated coil assembly for the driving mechanism of a pen recorder, substantially as herein described with reference to the accompanying drawings.

50 70

75 75

80 80

85 85

A.A. THORNTON & CO.,
Chartered Patent Agents,
Northumberland House,
303/306 High Holborn,
London, WC1V 7LE.

Printed for Her Majesty's Stationery Office,
by Croydon Printing Company Limited, Croydon, Surrey, 1980.
Published by The Patent Office, 25 Southampton Buildings,
London, WC2A 1AY, from which copies may be obtained.




FIG. 1




FIG. 2




FIG. 3





FIG. 4






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11