



## (51) International Patent Classification:

*H04W 36/08* (2009.01)      *H04W 12/08* (2009.01)*H04W 36/14* (2009.01)      *H04W 84/12* (2009.01)*H04W 12/04* (2009.01)      *H04W 88/06* (2009.01)*H04W 12/06* (2009.01)

## (21) International Application Number:

PCT/FI2017/050298

## (22) International Filing Date:

20 April 2017 (20.04.2017)

## (25) Filing Language:

English

## (26) Publication Language:

English

## (30) Priority Data:

62/329,531      29 April 2016 (29.04.2016)      US

(71) Applicant: NOKIA TECHNOLOGIES OY [FI/FI];  
Karaportti 3, 02610 Espoo (FI).(72) Inventors: LASELVA, Daniela; Septembervej 1 A, 9270  
Klarup (DK). KOVACS, Istvan Zsolt; Mågevej 17, 9000  
Aalborg (DK).(74) Agent: NOKIA TECHNOLOGIES OY et al.; Ari Aarnio,  
IPR Department, Karakaari 7, 02610 Espoo (FI).(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,  
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,  
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,  
HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR,  
KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,  
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,  
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,  
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

## (54) Title: SECURITY KEY USAGE ACROSS HANDOVER THAT KEEPS THE SAME WIRELESS TERMINATION




FIG. 1

(57) **Abstract:** A user equipment (UE) has both cellular and non-cellular links. The network sends it a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over the cellular link to a target access node without changing a wireless termination (WT) that is connected with the UE via the non-cellular link. The network uses that key to maintain the non-cellular link with the UE after the cellular link handover. From the UE's perspective it uses that key to authenticate its non-cellular link prior to the cellular link handover, but this handover does not change the WT which communicates with the UE via the non-cellular link so the UE can, only in response to receiving a first indication associated with the handover, use that same key to maintain that non-cellular link after the handover.



**(84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

— *of inventorship (Rule 4.17(iv))*

**Published:**

— *with international search report (Art. 21(3))*

## SECURITY KEY USAGE ACROSS HANDOVER THAT KEEPS THE SAME WIRELESS TERMINATION

### TECHNOLOGICAL FIELD:

5 [0001] The described invention relates to wireless communications, and more particularly to ciphering/encryption keys used in wireless communications when a user equipment (UE) hands over from a source access node to a target access node but maintains the same wireless termination (WT), for example in a LTE-WLAN aggregation (LWA) radio environment.

### 10 BACKGROUND:

[0002] Generally when a user equipment (UE) in a connected state moves from one cellular access node such as an eNB to another, new security/encryption keys are used after the changeover. At the same time, more ubiquitous wireless local area networks WLANs in combination with the public's increasing awareness of communications security has driven  
15 greatly improved security for IEEE 802.11 type radio access technologies. Future implementations of the LTE cellular radio access technology are to include LTE-WLAN aggregation (LWA) in which a cellular eNB can route some of the traffic (PDCP PDUs) for a given UE's bearer to a WLAN access point (AP) to which the UE has a simultaneous connection. In LWA there is a wireless termination (WT) which is a logical node that  
20 terminates the Xw interface and is in control of one or more WLAN APs, so a given UE's WLAN connection can hand over from one AP to another without the UE changing its WT, depending on the APs involved. Similarly, in LWA it is also possible for the UE's cellular connection to hand over from one eNB to another without changing its WT; this can occur even when the UE's WLAN connection is also handed over to another AP so long as the  
25 source and target APs are under the same WT.

[0003] With respect to LWA in Rel-13 of LTE, at the eNB handover the LWA configuration of the source eNB is released and the UE should release any existing encryption keys it has. This is because the relevant encryption keys, including the key S-  
30  $K_{WT}$  which is a WLAN security key used for the cellular link, are based on the eNB-specific key  $K_{eNB}$  which in this handover case would be associated with the source eNB that the UE is no longer associated to after the hand over. The target eNB would then send a brand new

LWA configuration with its own  $K_{eNB}$  to the UE after the handover. If the target eNB wishes to use eNB-based WLAN authentication it would have to include a parameter called *WT counter* as part of the new LWA configuration it gives to the UE since this is used along with the parameter  $K_{eNB}$  to derive the key  $S-K_{WT}$  that is also used for WLAN authentication (in this regard it functions similar to the IEEE pairwise master key PMK). The UE will then compute the key  $S-K_{WT}$  based on the  $K_{eNB}$  of the target eNB, and also based on the *WT counter* parameter in the new LWA configuration the target eNB signals to the UE. The same applies to the packet data convergence protocol (PDCP) encryption keys since the PDCP ciphering key also changes upon handover based on the eNB-specific value  $K_{eNB}$ . The PDCP ciphering key enables the WT and AP to send to the UE packets that are forwarded to the WT from the eNB.

[0004] While the above eNB-based WLAN authentication method that is defined in the Rel-13 LWA specifications of LTE is intended to be faster than legacy authentication methods based on EAP/AKA 802.1x/AAA (and may in fact be faster), the invention herein can improve that speed of authentication even further as set forth below. While LWA is the specifically described example the broader teachings herein are not limited only to the LWA radio technology environment. For example, the development of 5G cellular radio access technologies is expected to have a cellular-WLAN integration for simultaneously serving a given UE and it is certain to include robust security features to which these teachings can be applied; or these teachings can be implemented with other integrations of different radio access technologies (RATs).

#### SUMMARY:

[0005] According to a first aspect of these teachings there is provided a method comprising: sending to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link; and using at least one key of the first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT.

[0006] According to a second aspect of these teachings there is provided a computer readable memory storing computer program instructions that, when executed by one or more processors, cause a wireless network to send to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link; and further to use at least one key of the first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT.

[0007] According to a third aspect of these teachings there is provided an apparatus for communicating, the apparatus comprising at least one memory storing computer program instructions and at least one processor. The at least one memory with the computer program instructions is configured with the at least one processor to cause the apparatus to send to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link; and to use at least one key of the first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT.

[0008] According to a fourth aspect of these teachings there is provided an apparatus for communicating, the apparatus comprising at least communication means and authentication means. The communications means are for sending to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link. The authentication means is for using at least one key of the first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT. In a particular embodiment the communication means and the authentication means are embodied as a radio and at least one memory storing computer program instructions and at least one processor.

[0009] According to a fifth aspect of these teachings there is provided a method for operating a user equipment (UE), and in this aspect the method comprises: using at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node; handing over the cellular link from the source access node to the target access node without changing a WT in communication with the UE via the non-cellular link; and only in response to the UE receiving a first indication associated with the hand over, the UE using the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

[0010] According to a sixth aspect of these teachings there is provided a computer readable memory storing computer program instructions that, when executed by one or more processors, cause a user equipment to use at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node; to hand over the cellular link from the source access node to the target access node without changing a WT in communication with the UE via the non-cellular link; and only in response to the UE receiving a first indication associated with the hand over, to cause the UE to use the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

[0011] According to a seventh aspect of these teachings there is provided an apparatus for communicating that comprises at least one memory storing computer program instructions and at least one processor. In this aspect the at least one memory with the computer program instructions is configured with the at least one processor to cause a user equipment to use at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node; to hand over the cellular link from the source access node to the target access node without changing a WT in communication with the UE via the non-cellular link; and only in response to the UE receiving a first indication associated with the hand over, to cause the UE to use the at least one key of the first set of security keys to

maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

[0012] According to an eighth aspect of these teachings there is provided an apparatus for communicating that comprises at least authentication means and communication means. In this aspect the apparatus may be a user equipment or the apparatus may be certain components of or for a user equipment. The authentication means is for using at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node. The communication means is for handing over the cellular link from the source access node to the target access node without changing a WT in communication with the UE via the non-cellular link. And the authentication means is further for, only in response to the UE receiving a first indication associated with the hand over, using the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT. In a particular embodiment the authentication means and communication means are embodied as at least one memory storing computer program instructions and at least one processor and a radio.

[0013] These and other aspects are detailed further below with particularity.

#### BRIEF DESCRIPTION OF THE DRAWINGS:

[0014] FIG. 1 is a schematic diagram of a radio environment in which these teachings may be practiced to advantage, namely a LWA radio environment in which a UE hands over from source to target eNBs without changing its WLAN wireless termination.

[0015] FIG. 2 is a schematic diagram showing some of the logical entities in an eNB and PDCP PDU ciphering keys that the eNB provides to the WLAN AP (via the WT) according to certain embodiments of these teachings.

[0016] FIG. 3 is a process flow diagram showing certain features of an example embodiment.

[0017] FIG. 4 is a high level schematic block diagram showing further components of the access nodes shown at FIG. 1 as well as a UE, all of which are suitable for practicing certain aspects of these teachings.

5 DETAILED DESCRIPTION:

[0018] The description below assumes LWA radio technology environment for clarity of explanation, but it will be apparent that these LWA specific examples are readily extendable to more general radio environments in which the UE's bearer is handed over from a source access node that uses one security key or set of keys to a target access node that uses a  
10 different security key or set of keys for packet ciphering/deciphering and/or link authentication.

[0019] Specific to LWA, a new work item for "enhanced LWA" has been approved by the RAN2 in March 2016 [see specifically document RP-160600 by Intel Corp, Qualcomm, Inc.,  
15 and China Telecom entitled "New Work Item on Enhanced LWA"; 3GPP TSG RAN Meeting #71; Gotenborg, Sweden; 7-10 March 2016]. One objective there is mobility optimizations such as intra and inter eNB handovers without a WT change which is satisfied by certain embodiments described herein.

20 [0020] Consider more specifics of the REL. 13 LWA security features. The eNB (specifically, the master eNB or MeNB in LWA parlance) is in charge of creating and updating the master key used for WLAN security (for example, for authentication and encryption). Unless specified otherwise, eNB as used in the examples below refers to a MeNB. 3GPP TS 33.401 and TS 36.331 set forth the following specific procedures  
25 concerning the encryption master key S-K<sub>WT</sub>:

- The eNB derives the master key S-K<sub>WT</sub> based on K<sub>eNB</sub> and WT Counter;
- The eNB sends S-K<sub>WT</sub> to the WT via a secure Xw interface, and then the WT makes it available to APs/ACs which belong to the UE's WLAN mobility set (this is configured for the UE in the LWA configuration);
- 30 • The UE derives the same S-K<sub>WT</sub> key autonomously (also based on based K<sub>eNB</sub> and on WT Counter that the UE receives from its eNB);



- The master key  $S\text{-}K_{WT}$  is then used by the UE as the Pairwise Master Key (PMK) for a 4-way handshake as defined in IEEE 802.11 specifications (for example, 802.11ax, 802.11ad, 802.11ay, etc.).

- 5 [0021] In Rel-13, the eNB can update  $S\text{-}K_{WT}$  by incrementing the WT Counter (in this regard it is considered a refresh parameter) and computing a new  $S\text{-}K_{WT}$ . Also, at any handover event the LWA data radio bearer (DRB, as opposed to a signaling radio bearer SRB) connection between the UE and the WT (via the AP if the WT and AP are not co-located) is released and the UE shall delete the  $S\text{-}K_{WT}$  and further keys derived based on it.
- 10 But there are unresolved questions for how security is to be handled for enhanced LWA (eLWA) in Rel-14 as set forth in document R2-163147 by RAN WG2 entitled “LS on key change during HO for eLWA (3GPP TSG RAN WG2 #93bis; Dubrovnik, Croatia; 11-15 April 2016).
- 15 [0022] Specifically, if the UE performs a handover and  $K_{eNB}$  is changed while the UE remains connected to WLAN associated with the same WT, is it acceptable for the UE to retain the existing  $S\text{-}K_{WT}$  after handover? Also, if it is necessary for the UE to replace the key with a new  $S\text{-}K_{WT}$  derived from the new  $K_{eNB}$ , then RAN2 would like SA3 to consider feasible solutions for Rel-14 eLWA potentially allowing the UE to remain associated with
- 20 the WLAN after intra/inter-eNB handover.

- [0023] In Rel-13 LWA as mentioned above, at the eNB handover the LWA configuration of the source eNB is released and the UE should release any existing  $S\text{-}K_{WT}$  key. But the cellular link to the source eNB is broken before that link is established with the target eNB,
- 25 and so the unintended result of releasing the existing  $S\text{-}K_{WT}$  key without being able to compute a new one would lead to the UE not being able to authenticate with the WLAN AP. Any data packets that are buffered at the WT/AP would need to be discarded after the LWA configuration is released at the UE since such a release would result in termination of the WLAN link that was earlier aggregated to the LTE source eNB. The target eNB would have
- 30 to send a brand new LWA configuration to the UE after the handover. If the target eNB wishes to use eNB-based WLAN authentication it would have to include the *WT counter* parameter as part of the configuration. The UE will then compute the  $S\text{-}K_{WT}$  key based on

the  $K_{eNB}$  parameter of the target eNB and the signaled *WT counter* but by then the WLAN link may have already been terminated due to lack of authentication, absent the advantages of these teachings. The same applies to the PDCP encryption keys since the PDCP ciphering key (for packet encryption/decryption) also changes upon handover based on the current

5  $K_{eNB}$  parameter which is eNB-specific.

[0024] In one aspect of these teachings the security solution for Rel-13 LWA is updated to retain the existing  $S-K_{WT}$  and PDCP keys (which pre-handover are derived based on the  $K_{eNB}$  of the source eNB) after the handover to the target eNB when this handover occurs without a change to the UE's WT. Relatedly these teachings also address how and when to enforce the use of the new  $S-K_{WT}$  and/or PDCP keys (which post-handover are based on the  $K_{eNB}$  of the target eNB).

[0025] While the LTE link undergoes a handover this implies a short data interruption (sometimes referred to as a break-before-make approach since the link to the source eNB is broken slightly before the link to the target eNB is made). But during this short data interruption the WLAN link (same WT-UE) can be maintained and the UE that is configured with LWA can still be served data over its WLAN link during the eNB handover so long as there is no change to the UE's WLAN WT during the cellular handover. In this scenario there is no interruption of the data link to/from the UE because the WLAN link remains connected. But as mentioned above, in the Rel-13 security procedures deleting the existing  $S-K_{WT}$  upon the cellular link hand over may make the WLAN link not usable for some time period for data (except without encryption which is not allowed in LWA specifications). Apart from the key generation itself the relevant security procedures entail a 4-way authentication handshake (which proves the participants have the key but does not actually involve exchanging that key) so in wireless communication terms this time period is not negligible. As detailed herein, retaining that  $S-K_{WT}$  key can keep the LWA WLAN link intact across the break-before-make cellular link hand over because then this handshake will remain valid.

[0026] Retaining the existing/pre-handover  $S-K_{WT}$  and PDCP keys after the handover to the target eNB means for example that the packets from the source eNB that may be buffered

at the WT/AP will not need to be discarded at the cellular handover event; they could still be delivered to the UE via the WT over the intact WLAN link and still be correctly decoded by the UE even after the cellular handover is complete.

5 [0027] If it were otherwise and the WT would not be able to deliver those buffered packets, the source eNB would need to be much more conservative about routing data to the WLAN AP immediately prior to and during the cellular handover, which would generate inefficiencies in the data throughput.

10 [0028] FIG. 1 is a schematic diagram of a UE 10 in a LWA environment and handing over from a source eNB 20S to a target eNB 20T without changing its WT 40 to which it is connected via a WLAN AP 50-2. In this case there is also one other WLAN 50-1 within the mobility set that is configured for the UE but that AP 50-2 is not relevant for this example. For completeness FIG. 1 also shows a serving gateway (S-GW) 60 that also handles  
15 functions of the mobility management entity (MME), which is connected to the eNBs 20S, 20T via a S1 interface.

[0029] The X2 interface goes between the two eNBs 20S, 20T. User and control plane interfaces between the WT 40 and these eNBs 20S, 20T are marked as XW-u and XW-c,  
20 respectively. The UE 10 has a connection with the AP 50-2 using 802.11 radio access technology, and its connection with the eNBs 20S, 20T uses LTE technology (shown as a Uu interface for user data). In the break-before-make cellular handover, the UE's Uu interface with the source eNB 20S is broken before it establishes a new Uu interface with the target eNB 20T, but across this break the 802.11 link with the WT 40 via a single AP 50-  
25 2 as shown remains viable for the LWA networking arrangement to send data to and receive data from the UE 10.

[0030] The UE 10 is configured by its source cell 20S with a LWA configuration, which includes the  $K_{\text{eNB}}$  parameter specific to that source eNB 20S. Conventionally that LWA  
30 configuration would be automatically deleted by the UE 10 at the hand over. In embodiments of these teachings it is not automatically deleted. When handing over the target eNB 20T gives the UE 10 a new LWA configuration, which may be an entirely new

LWA configuration or only an update to its existing one. This LWA configuration from the target eNB 20T indicates to the UE 10 whether or not it should keep the set of security keys (the parameter  $K_{eNB}$  is used to generate  $S-K_{WT}$  which is used for both ciphering and authentication, and also to generate the PDCP encryption keys  $K_{UPenc}$ ) that the UE used prior to the handover. For example, if the LWA configuration from the target eNB 20T includes the *WT counter* parameter for the target eNB this indicates the UE 10 should follow conventional practice by deleting its existing set of ciphering keys and derive new ones using that parameter (and  $K_{eNB}$ ). If instead the LWA configuration from the target eNB 20T does not include the *WT counter* parameter this indicates the UE 10 should retain its existing set of security keys and continue to use them even after the handover. In this example the indication to retain the ciphering keys is implicit in the absence of the *WT counter* parameter from the target eNB 20T. Where this implicit indication is present, the target eNB 20T will later signal the UE 10 to delete those existing ciphering keys and derive a new set, and for example this later signaling can be an explicit indication in that the target eNB 20T sends to the UE 10 a *WT counter* parameter sometime after the handover is completed. In another embodiment the  $S-K_{WT}$  key is retained in order to maintain the non-cellular LWA WLAN link across the hand over of the LWA cellular link but the ciphering key or keys for the PDCP PDUs ( $K_{UPenc}$  for user-plane encryption) is not retained once the cellular link to the source eNB is broken.

[0031] In either case, data and UE context forwarding from the source cell 20S to the target cell 20T is supported at the eNB handover, as it was conventionally. And as has been discussed for eLWA in Rel-14 the UE can still be provisioned with an indication of the PDCP key used for ciphering a given packet as shown in FIG. 2. In this case provisioning of the PDCP key indication is done by the LWA AP 20L functionality of the eNB 20 which informs it to the WLAN AP 50 over the Xw interface and the WLAN AP provisions this PDCP key indication to the UE 10 over the WLAN/802.11 radio access technology link that remains intact across the cellular handover. The UE is expected to instantiate the PDCP protocol entity 20P associated to the target eNB 20T while maintaining the similar PDCP entity 20P associated to the source eNB 20S for the same bearer. In the FIG. 2 depiction there is one LWA bearer for this UE, of which the data sent on the cellular portion is shown

as being sent on RB1 and the data sent on the non-cellular portion is shown as being sent on RB2.

[0032] eNB based WLAN authentication for LWA is defined in 3GPP TS 36.331 as follows:

#### 22A.1.x WLAN Authentication

For a UE supporting LWA, WLAN authentication is performed as follows:

If WT Counter is included in LWA Configuration in the RRC Connection Reconfiguration message, the UE shall start using the S-K<sub>WT</sub> derived using the WT Counter value and K<sub>eNB</sub> as PMK as specified in TS 33.401 subclause G [22] and TS 36.331 subclause 5.6.14.2 [16]. For a UE already authenticated with WLAN, configuration of a new PMK triggers refreshing the IEEE 802.11 security using the new PMK.


If WT Counter is not included in LWA Configuration in the RRC Connection Reconfiguration message:

- if WT Counter has not been previously configured for the UE, the UE which is not already authenticated with a WLAN in the WLAN mobility set shall use authentication methods specified in TS 33.402 subclause 6 [yy];
- if WT Counter has been previously configured for the UE, the UE which is not already authenticated with a WLAN in the WLAN mobility set shall keep using the S-K<sub>WT</sub> previously derived using the WT Counter value and K<sub>eNB</sub> as PMK as specified in TS 33.401 subclause G [22] and TS 36.331 subclause 5.6.14.2 [16];
- the UE which is already authenticated with a WLAN in the WLAN mobility set continues using the previously configured authentication method and is not required to refresh IEEE 802.11 security.

[0033] Derivation of the security key is defined in 3GPP TS 33.401 as follows:

#### **G.2.4.2 Security key derivation**

The UE and MeNB shall derive the security key S-K<sub>WT</sub> of the target WT as defined in Annex A.16 of the present specification.



## G.2.5 Security key update

### G.2.5.1 Security key update triggers

The system supports update of the S-K<sub>WT</sub>. The MeNB may update the S-K<sub>WT</sub> for any reason by using the S-K<sub>WT</sub> update procedure defined in clause G.2. 5.2 of the current specification. If the MeNB re-keys its currently active K<sub>eNB</sub> in an AS security context, the MeNB shall update any S-K<sub>WT</sub> associated with that AS security context.

### G.2.5.2 Security key update procedures

If the MeNB receives a request for S-K<sub>WT</sub> update from the WT or decides on its own to perform S-K<sub>WT</sub> update (see clause G.2.5.1), the MeNB shall increment the WT Counter and compute a fresh S-K<sub>WT</sub>, as defined in clause G.2.4. Then the MeNB shall perform a WT Modification procedure to deliver the fresh S-K<sub>WT</sub> to the WT. The MeNB shall provide the value of the WT Counter used in the derivation of the S-K<sub>WT</sub> to the UE in an integrity protected RRC message. The UE shall derive the S-K<sub>WT</sub> as described in clause G.2.4. Whenever the UE or WT start using a fresh S-K<sub>WT</sub> as PMK they shall refresh the IEEE 802.11 security.

## G.2.6 Handover procedures

During S1 and X2 handover, the LWA DRB connection between the UE and the WT is released, the UE shall delete the S-K<sub>WT</sub> and further keys derived based on it.

[0034] According to embodiments of these teachings, during and for a period of time after a eNB handover without a WT change for a UE configured with LWA, at least one key of a first set of security keys (for example, the existing authentication key S-K<sub>WT</sub> and / or the PDCP ciphering keys which for purposes herein the ciphering key(s) are also considered de-ciphering keys) are maintained with an implicit indication. In the above example this implicit indication is a lack of a *WT counter* parameter in the LWA configuration (update/delta) that is sent to the UE 10 by the target eNB 20T immediately after the handover. Further, the existing S-K<sub>WT</sub> and PDCP ciphering keys are released with an explicit

indication from the target eNB, and in one example this explicit indication is the first provisioning of a new *WT counter* parameter, via dedicated radio resource control (RRC) signaling from the target eNB 20T to the UE 10 at or after the handover command if the LWA configuration was maintained. In Rel-13 the WT does not signal any buffer status report/indication to the target eNB across the cellular handover but in this specific embodiment it does, and such a dedicated RRC message may be triggered by at least the WT signaling of such a buffer status indication related to the PDCP PDUs that are routed from the source eNB 20S to the given UE's bearer.

[0035] In order to enable this more smoothly it is preferable that during preparations for the cellular handover there is a certain information exchange from the source eNB 20S to the target eNB 20T. This information can assist the target eNB 20T to determine if and how to maintain the current LWA configuration with this UE 10.

[0036] More specifically and referring to FIG. 1, during the handover preparation of a given UE 10 the source eNB 20S exchanges over the X2 interface with the target eNB 20T certain LWA specific information including the following.

- Whether the UE 10 had a running LWA configuration for one or more bearers prior the handover event. The purpose of this is to establish whether to maintain the LWA configuration at the handover configuration.
- Used WT 40 and/or UE-specific WLAN Mobility set which the UE 10 was configured in the source eNB 20S. The purpose of this is to determine whether the LWA configuration after handover could be maintained with the same WT 40.
- Whether the UE 10 was using eNB-assisted WLAN authentication. This enables the target eNB 120T to determine whether the WT 40/AP 50-1/UE 10 are using a valid S-K<sub>WT</sub>.

[0037] Additionally, during and after eNB handover without a WT change, and until indicated by the target eNB 20T, the UE 10 and WT 40/AP 50-1 retain the existing S-K<sub>WT</sub> (which is based on the K<sub>eNB</sub> of the source eNB 20S). This differs from conventional practice that would have the UE 10 and WT 40/AP 50-1 release the existing S-K<sub>WT</sub> at the hand over

event. During this time, the UE 10 can remain connected to the same WT 40 and receive PDCP PDUs over the WLAN connection (WT-to-UE) using the  $S-K_{WT}$  from the source eNB 20S. This enables the source eNB 20S to keep forwarding PDUs to the WT 40 for the UE's bearer prior to and during the handover because the WT 40 will still be capable of sending those forwarded PDUs that are buffered at the WT 40/AP 50-1 even after the handover. Absent this feature conventional practice would need to discard those (or send them un-encrypted which is not a suitable option).

[0038] From the UE perspective, the UE 10 will use the existing PDCP encryption key and PDCP entity 20P associated to the source eNB 20S, as opposed to conventional practice where the UE 10 would release it at the hand over event. During this time, the UE 10 should maintain the PDCP entity 20P associated to the source eNB 20S and forward the received (LWA) PDCP PDUs over the WLAN link to that same PDCP entity 20P. Note that in parallel also the PDCP entity 20P associated to the target eNB 20T should be created to allow LTE transmissions. This particular feature of the invention avoids the need for any indication of which PDCP keys are used, which would otherwise be necessary. This is because the PDCP encryption key being used is coupled one-to-one to the  $S-K_{WT}$  key that is retained for a time after the handover; this coupling is by means of using the same  $K_{eNB}$ .

[0039] At the establishment of the Xw-u interface between the target eNB 20T and the WT 40 for the handed over UE's bearer (see FIG. 1), the target eNB 20T can configure the WT 40 to report the buffer status indication related to the PDCP PDUs that were routed from the source eNB 20S to a given UE's bearer. In one embodiment the target eNB 20T requests periodic updates for this buffer status indication (for example, buffer size in bytes), or in another embodiment the target eNB 20T can request event-based updates (for example, the number of PDUs in the WT's buffer for this UE's bearer falls below a pre-defined threshold). In either case identification of the UE 10 at the WT 40 in such a buffer status indication could in one example be based on the UE's media access control (MAC) address, and/or it could be based on one of the UE's 3GPP identifiers.

[0040] The WT 40 thus provides to the target eNB 20T, if and as requested, the buffer status indication for the handed over UE 10 as well as any of the LWA bearers.



[0041] Based on this buffer status indication (for example, once the buffer status indication indicates the WT's relevant buffer is empty) the target eNB 20T then provides the new *WT Counter* to the UE 10 via dedicated RRC signaling. At the same time the target eNB 20T can send the related new S-K<sub>WT</sub> key to the WT 40, where this new S-K<sub>WT</sub> key is generated from the target eNB's K<sub>eNB</sub> and the *WT counter* parameter that the target eNB 20T just signaled to the UE 10.

[0042] In another implementation, the new S-K<sub>WT</sub> key could be send to the WT 40 during the initial WT addition, but in this case the WT will normally propagate it forward to the APs 50-1, 50-2 in the mobility set only at a given time. The target eNB 20T can indicate this given time to the WT 40 implicitly, such as based on the buffer status indication (for example, the indication is implicit once the buffer fulfils a certain threshold, e.g. runs empty). Or the target eNB 20T can indicate this given time to the WT 40 explicitly, for example based on an indication from the target eNB 20T such as provisioning of the key. For example, in one embodiment the target eNB 20T can send the new S-K<sub>WT</sub> to the WT 40 when the IPsec tunnel is established but the WT 40 does not immediately distribute it to the APs 50-1, 50-2 of the mobility set; the WT 40 does so only after its buffer for the handed over UE is empty of packets from the source eNB 20S.

[0043] In the above example embodiment the first reception of the *WT counter* at the UE 10 after the cellular handover indicates implicitly that:

- a) the UE should compute a new S-K<sub>WT</sub> based on target eNB's K<sub>eNB</sub> and
- b) the UE should delete the PDCP entity 20P associated to the source eNB 20S and start using the entity 20P associated to the target eNB 20T.

[0044] The target eNB 20T could start routing data traffic (PDCP) PDUs to the WT 40 at any time if the WT 40 is capable of buffering, until the WT 40 provides the new S-K<sub>WT</sub> to the APs 50-1, 50-2 in the UE's mobility set, or alternatively only after the new S-K<sub>WT</sub> has been distributed by the WT 40 to the APs 50-1, 50-2 in the UE's mobility set.

[0045] FIG. 3 is a process flow diagram that shows certain features of non-limiting embodiments of these teachings from the perspective of the network. Firstly there is some pre-handover information sent from the source eNB 20S to the target eNB 20T which are summarized at block 302 and detailed further above. Then at block 304 the network sends to the UE 10 a first indication to maintain using a first set of security keys that are generated from a parameter that is specific for a source access node such as a source eNB 20S after the UE 10 hands over a cellular link to a target access node such as the target eNB 20T without changing a WT 40 with which the UE 10 is connected via a non-cellular link. Block 306 has (the WT via its AP) using at least one key of that same first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT. The non-cellular link is the WLAN link between the UE 10 and the AP 50-1 in the above example where the UE 10 and the WLAN 50-1/WT 40 use the key  $S\text{-}K_{WT}$  for authenticating the non-cellular link and the key  $K_{UPenc}$  for ciphering the PDCP PDUs that are sent and received on the non-cellular link (both of these keys are among the first set of security keys since they are both generated using  $K_{eNB}$  which is specific to the source eNB); the UE remains connected over this WLAN link from the time when the source access node sends the first indication through at least the time when the target access node sends the second indication.

[0046] Block 304 summarizes a few further details from the various examples detailed further above. In one embodiment the first indication remains valid until a second indication is sent to the UE, after which the at least one key of the first set of security keys is no longer valid for maintaining the non-cellular link. In one specific example the first indication is implicit from an absence of signaling by the target eNB 20T a pre-defined parameter in a LTE-WLAN Aggregation (LWA) configuration for the UE, such as for example absence of the WT counter parameter where the LWA configuration is signaled to the UE via a dedicated RRC message. In the above examples the second indication is an explicit one, for example a new value for the WT counter parameter sent from the target eNB 20T in dedicated RRC signaling to the UE 10. In the more specific examples above: a) the parameter specific to the source access node is  $K_{eNB}$ , and b) the first set of security keys include at least: b1) the at least one key which is an authentication key  $S\text{-}K_{WT}$  derived from  $K_{eNB}$  and WT

counter, and b2) at least one ciphering key derived from  $K_{eNB}$  and WT counter for encrypting and decrypting PDCP PDUs communicated with the UE over the non-cellular link.

[0047] Not specifically repeated in FIG. 3 but detailed further above, the target eNB's sending of the second indication to the UE may be triggered by the target eNB's receiving from the WT 40 a buffer status indication related to packets routed from the source access node 20S to a bearer allocated to the UE 10 that remains valid across the hand over, such as the bearer on the WLAN radio link.

[0048] To the extent FIG. 3 may be considered to represent a method, the source access node and the target access node (as well as the WLAN WT) may coordinate in performing the method in that the source access node may inform the target access node, prior to the hand over, that the UE is using eNB-assisted WLAN authentication. The target access node then uses this information to determine validity of at least one key of the first set of security keys. FIG. 3 may also represent actions performed by a wireless network when executing by one or more processors computer program instructions that are stored on a computer readable memory.

[0049] Actions from the perspective of the UE 10 are similar to those above from the network perspective. For example, the UE would in some embodiments use at least one key of a first set of security keys that are generated using a parameter that is specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node. In from the above examples this non-cellular link is the WLAN link between the UE through the WLAN AP 50-1 to the WT 40. Then the UE hands over the cellular link from the source access node to the target access node, without changing a WT that remains in communication with the UE across the hand over via the non-cellular link. From the UE's perspective, only in response to the UE receiving a first indication associated with the hand over does the UE use the at least one key of the first set of ciphering keys to maintain the non-cellular link after the UE hands over the cellular link to the target access node without changing the WT. Further details correspond to those summarized from the network's perspective.

[0050] For all of the above examples the non-cellular link can change from one AP to another and still be maintained so long as both those APs are in the same mobility set; if not that would entail a change to the UE's WT. Assuming in FIG. 1 that AP 50-1 and AP 50-2 are both in the same mobility set, then while performing the cellular hand over from the source eNB 20S to the target eNB 20T the non-cellular link can be maintained, consistent with the above examples, whether the UE's non-cellular link is directly to AP 50-1 throughout or whether that non-cellular link changes from AP 50-1 to AP 50-2 because in either case the UE's WT, and hence its WLAN authentication and ciphering keys, do not change.

[0051] FIG. 4 is a schematic diagram illustrating some further components in addition to those already shown and described for the eNB 9source 20S or target 20T), and further components of the UE 10. In the wireless system a wireless (LWA) network is adapted for communication over a wireless link 11 such as the described cellular bearer and WLAN bearer with an apparatus such as a mobile communication device which may be referred to as a UE 10, via cellular 20S/20T and WLAN 50-1/50-2 radio network access nodes. The network may include a network control element (MME, see FIG. 1) that may include mobility management entity/serving gateway (MME/S-GW) functionality, and which provides connectivity with a further network such as a telephone network and/or a data communications network (e.g., the internet).

[0052] The UE 10 includes a controller, such as a computer or a data processor (DP) 10D, a computer-readable memory medium embodied as a memory (MEM) 10B that stores a program of computer instructions (PROG) 10C, one or more buffers, and a suitable wireless interface, such as radio frequency (RF) transmitter/receiver combination 10D for bidirectional wireless communications with the various access nodes 20S/20T/50-1/50-2 via one or more antennas.

[0053] The wireless link between the UE 10 and the source/target eNBs 20S/20T can use LTE RAT while that with the APs 50-1/50-2 can use WLAN RAT. Further, the UE 10 includes a galvanic or other portable power supply not shown specifically.

[0054] Each of the source/target eNBs 20S/20T as well as the APs 50-1/50-2 also includes a controller, such as a computer or a data processor (DP) 20A, a computer-readable memory medium embodied as a memory (MEM) 20B that stores a program of computer instructions (PROG) 20C as well as the variously described buffers, and a suitable wireless interface, such as RF transmitter/receiver combination 20D for communication with the UE 10 (as well as other UEs) via one or more antennas. The source/target eNBs 20S/20T are coupled via a data/control path (not shown) to the MME and this path may be implemented as an interface. The source/target eNBs 20S/20T are also coupled to one another, and possibly to further eNBs, via another data/control path, which may be implemented in the LTE radio access technology as an X2 interface with both user plane (X-U) and control plane (X-C) instances. The APs 50-1/50-2 are coupled to the eNBs 20S/20T via a WT 40 that has similar functionality though not necessarily the radios; the WT 40 may or may not be co-located with a given AP.

[0055] At least one of the PROGs 10C/20C is assumed to include program instructions that, when executed by the associated DP 10A/20A, enable the device to operate in accordance with exemplary embodiments of this invention as detailed above. That is, various exemplary embodiments of this invention may be implemented at least in part by computer software executable by the DP 10A of the UE 10; by the DP 20A of the source/target eNBs 20S/20T and/or WT 40 and/or APs 50-1/50-2, or by hardware or by a combination of software and hardware (and firmware).

[0056] In various exemplary embodiments the UE 10 and/or the access nodes 20S/20T/50-1/50-2 may also include dedicated processors, for example a RRC module, a radio-frequency (RF) front end, and the like. There may also be one or more modules that is/are constructed so as to operate in accordance with various exemplary embodiments of these teachings.

[0057] The computer readable MEMs 10B/20B may be of any type suitable to the local technical environment and may be implemented using any one or more suitable data storage technology, such as semiconductor based memory devices, flash memory, magnetic memory devices and systems, optical memory devices and systems, fixed memory and removable memory, electromagnetic, infrared, or semiconductor systems. Following is a non-

exhaustive list of more specific examples of the computer readable storage medium/memory: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any  
5 suitable combination of the foregoing.

[0058] The DPs 10A/20A may be of any type suitable to the local technical environment, and may include one or more of general purpose computers, special purpose computers,  
10 microprocessors, digital signal processors (DSPs) and processors based on a multicore processor architecture, as non-limiting examples. The wireless interfaces (e.g., the radios 10D/20D) may be of any type suitable to the local technical environment and may be implemented using any suitable communication technology such as individual transmitters, receivers, transceivers or a combination of such components.

[0059] In general, the various embodiments of the UE 10 can include, but are not limited to, smart phones, machine-to-machine (M2M) communication devices, cellular telephones, personal digital assistants (PDAs) having wireless communication capabilities, portable  
15 computers having wireless communication capabilities, image capture devices such as digital cameras having wireless communication capabilities, gaming devices having wireless communication capabilities, music storage and playback appliances having wireless communication capabilities, Internet appliances permitting wireless Internet access and browsing, as well as portable units or terminals that incorporate combinations of such  
20 functions. Any of these may be embodied as a hand-portable device, a wearable device, a device that is implanted in whole or in part, a vehicle-mounted communication device, and the like.

[0060] It should be understood that the foregoing description is only illustrative. Various alternatives and modifications can be devised by those skilled in the art. For example,  
30 features recited in the various dependent claims could be combined with each other in any suitable combination(s). In addition, features from different embodiments described above could be selectively combined into an embodiment that is not specifically detailed herein as

separate from the others. Accordingly, the description is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

[0061] Below are certain acronyms used herein:

5	3GPP	third generation partnership project
	AC	(WLAN) access controller
	AP	(WLAN) access point
	eNB	enhanced node B (LTE base station)
	ID	identifier
10	IPSec	Internet protocol security
	IW	interworking
	LTE	long term evolution (4G cellular)
	LWA	LTE – WLAN aggregation
	LWIP	LTE-WLAN radio level integration via IPsec tunneling
15	MAC	media access control
	MME	mobility management entity
	PDCCP	packet data convergence protocol
	PDU	packet data unit/protocol data unit
	RAN	radio access network
20	RLC	radio link control
	RRC	radio resource control
	S-GW	serving gateway
	UE	user equipment
	WLAN	wireless local area network
25	WT	WLAN Termination

CLAIMS:

What is claimed is:

1. A method comprising:
  - 5 sending to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link; and
  - 10 using at least one key of the first set of security keys to maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT.
2. The method according to claim 1, wherein the first indication remains valid until a second indication is sent to the UE, after which the at least one key of the first set of  
15 security keys is no longer valid for maintaining the non-cellular link.
3. The method according to claim 2, wherein the first indication is implicit from an absence of signaling a pre-defined parameter in a LTE-WLAN Aggregation (LWA) configuration for the UE.  
20
4. The method according to any of claim 3, wherein the second indication is explicit and indicates a new value for a WT counter parameter which is the pre-defined parameter.
5. The method according to any of claims 2-4, wherein sending of the second  
25 indication to the UE is triggered by the target access node receiving from the WT a buffer status indication related to packets routed from the source access node to a bearer allocated to the UE that remains valid across the hand over.
6. A computer readable memory storing computer program instructions that, when  
30 executed by one or more processors, cause a wireless network to perform the method according to any of claims 1-5.



7. An apparatus for communicating, the apparatus comprising:  
at least one memory storing computer program instructions; and  
at least one processor;

wherein the at least one memory with the computer program instructions is configured with

- 5 the at least one processor to cause the apparatus to at least:

send to a user equipment (UE) a first indication to maintain using a first set of  
security keys generated from a parameter specific to a source access node after  
the UE hands over a cellular link to a target access node without changing a  
wireless termination (WT) with which the UE is connected via a non-cellular  
10 link; and

use at least one key of the first set of security keys to maintain the non-cellular  
link with the UE after the UE hands over the cellular link to the target access  
node without changing the WT.

- 15 8. The apparatus according to claim 7, wherein the first indication remains valid until  
a second indication is sent to the UE, after which the at least one key of the first set of  
security keys is no longer valid for maintaining the non-cellular link.

9. The apparatus according to claim 8, wherein the first indication is implicit from an  
20 absence of signaling a pre-defined parameter in a LTE-WLAN Aggregation (LWA)  
configuration for the UE.

10. The apparatus according to claim 9, wherein:

the pre-defined parameter is a WT counter,

- 25 the LWA configuration is signaled to the UE via a dedicated radio resource control  
(RRC) message,

the parameter specific to the source access node is  $K_{eNB}$ , and

the first set of security keys include at least:

the at least one key which is an authentication key  $S-K_{WT}$  derived from  $K_{eNB}$   
30 and WT counter, and

at least one ciphering key derived from  $K_{eNB}$  and WT counter for encrypting and decrypting PDCP PDUs communicated with the UE over the non-cellular link.

- 5 11. The apparatus according to any of claims 8-10, wherein the second indication is explicit.
12. The apparatus according to claim 11, wherein the explicit second indication is a new value for the WT counter parameter.
- 10 13. The apparatus according to any of claims 8-12, wherein sending of the second indication to the UE is triggered by the target access node receiving from the WT a buffer status indication related to packets routed from the source access node to a bearer allocated to the UE that remains valid across the hand over.
- 15 14. The apparatus according to any of claims 8-13, wherein:  
the first indication is sent by the source and/or the target access node;  
the second indication is sent by the target access node; and  
the source access node and the target access node coordinate in performing the  
20 method by the source access node informing the target access node, prior to the hand over, that the UE is using eNB-assisted WLAN authentication, which the target access node uses to determine validity of at least one key of the first set of security keys.
- 25 15. An apparatus comprising:  
communication means for sending to a user equipment (UE) a first indication to maintain using a first set of security keys generated from a parameter specific to a source access node after the UE hands over a cellular link to a target access node without changing a wireless termination (WT) with which the UE is connected via a non-cellular link; and  
authentication means for using at least one key of the first set of security keys to  
30 maintain the non-cellular link with the UE after the UE hands over the cellular link to the target access node without changing the WT.

16. A method for operating a user equipment (UE), the method comprising:  
using at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the UE handing over a cellular link to a target access node;

5 handing over the cellular link from the source access node to the target access node without changing a wireless termination (WT) in communication with the UE via the non-cellular link; and

only in response to the UE receiving a first indication associated with the hand over, the UE using the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

17. The method according to claim 16, wherein the first indication remains valid until a second indication is received at the UE, after which the at least one key of the first set of security keys is no longer valid for maintaining the non-cellular link.

18. The method according to claim 17, wherein the first indication is implicit from an absence of a pre-defined parameter in a LTE-WLAN Aggregation (LWA) configuration that is received at the UE.

19. The method according to any of claims 17-18, wherein:  
the first indication is received from the source access node and/or the target access node;  
the second indication is received from the target access node; and  
during the method the UE is using eNB-assisted WLAN authentication.

20. A computer readable memory storing computer program instructions that, when executed by one or more processors, cause a user equipment to perform the method according to any of claims 16-19.

21. An apparatus for communicating, the apparatus comprising:  
at least one memory storing computer program instructions; and  
at least one processor;

wherein the at least one memory with the computer program instructions is configured with the at least one processor to cause a user equipment (UE) to at least:

use at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate a non-cellular link prior to the

5 UE handing over a cellular link to a target access node;

hand over the cellular link from the source access node to the target access node without changing a wireless termination (WT) in communication with the UE via the non-cellular link; and

10 only in response to the UE receiving a first indication associated with the hand over, use the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

22. The apparatus according to claim 21, wherein the first indication remains valid  
15 until a second indication is received at the UE, after which the at least one key of the first set of security keys is no longer valid for maintaining the non-cellular link.

23. The apparatus according to claim 22, wherein the first indication is implicit from an absence of a pre-defined parameter in a LTE-WLAN Aggregation (LWA) configuration  
20 that is received at the UE.

24. The apparatus according to claim 23, wherein:  
the pre-defined parameter is a WT counter,  
the LWA configuration is received at the UE via a dedicated radio resource control  
25 (RRC) message,  
the parameter specific to the source access node is  $K_{eNB}$ , and  
the first set of security keys include at least:

the at least one key which is an authentication key  $S-K_{WT}$  derived from  $K_{eNB}$  and WT counter, and

30 at least one ciphering key derived from  $K_{eNB}$  and WT counter for encrypting and decrypting PDCP PDUs communicated with the UE over the non-cellular link.


25. The apparatus according to any of claims 22-24, wherein the second indication is explicit.

5 26. The apparatus according to claim 25, wherein the explicit second indication is a new value for the WT counter parameter.

27. The apparatus according to any of claims 22-26, wherein:  
the first indication is received from the source access node and/or the target access  
10 node;  
the second indication is received from the target access node; and  
during the method the UE is using eNB-assisted WLAN authentication.

28. An apparatus comprising:  
15 authentication means for using at least one key of a first set of security keys generated from a parameter specific to a source access node to authenticate for a user equipment (UE) a non-cellular link prior to the UE handing over a cellular link to a target access node; and  
communication means for handing over the cellular link from the source access node to the target access node without changing a wireless termination (WT) in communication  
20 with the UE via the non-cellular link;  
wherein the authentication means if further for, only in response to the UE receiving a first indication associated with the hand over, using the at least one key of the first set of security keys to maintain the non-cellular link after the UE hands over to the target access node without changing the WT.

25



2/3




FIG.2




FIG.4




FIG.3



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI2017/050298

**A. CLASSIFICATION OF SUBJECT MATTER**

See extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC: H04W

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
FI, SE, NO, DK

Electronic data base consulted during the international search (name of data base, and, where practicable, search terms used)

EPODOC, WPIAP, EPO-Internal full-text databases, XP3GPP, XPAIP, XPESP, XPETSI, XPI3E, XPIEE, XPIETF, XPIPCOM

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ERICSSON Mobility optimizations for eLWA. In: 3GPP Draft; R2-16279 3rd Generation Partnership Project (3GPP), Mobile Competence Centre ; 650, route des Lucioles ; F-06921 Sophia-Antipolis Cedex ; France: 2016-04-02, the whole document	1-28
A	WO 2016036296 A1 (ERICSSON TELEFON AB L M [SE]) 10 March 2016 (10.03.2016)	1-28
A	WO 2014035619 A1 (QUALCOMM INC [US]) 06 March 2014 (06.03.2014)	1-28
A	US 2014293970 A1 (DAMNJANOVIC JELENA [US] et al.) 02 October 2014 (02.10.2014)	1-28

☒ Further documents are listed in the continuation of Box C.
☒ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search  
26 June 2017 (26.06.2017)Date of mailing of the international search report  
29 June 2017 (29.06.2017)Name and mailing address of the ISA/FI  
Finnish Patent and Registration Office  
P.O. Box 1160, FI-00101 HELSINKI, Finland  
Facsimile No. +358 29 509 5328Authorized officer  
Tapio Ikäheimo  
Telephone No. +358 29 509 5000

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI2017/050298

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	ITRI Inter eNB Handover without WT Change to Keep LWA Active. In: 3GPP Draft; R2-166480 3rd Generation Partnership Project (3GPP), Mobile Competence Centre ; 650, route des Lucioles ; F-06921 Sophia-Antipolis Cedex ; France: 2016-10-09,	1, 6, 7, 15, 16, 20, 21, 28

**INTERNATIONAL SEARCH REPORT**  
**Information on Patent Family Members**

International application No.  
PCT/FI2017/050298

Patent document cited in search report	Publication date	Patent family members(s)	Publication date
WO 2016036296 A1	10/03/2016	None	
.....			
WO 2014035619 A1	06/03/2014	CN 104584642 A	29/04/2015
		EP 2891368 A1	08/07/2015
		IN 145MUN2015 A	16/10/2015
		US 2014064068 A1	06/03/2014
.....			
US 2014293970 A1	02/10/2014	US 9474067 B2	18/10/2016
		WO 2014160763 A1	02/10/2014
.....			

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI2017/050298

CLASSIFICATION OF SUBJECT MATTER

IPC

**H04W 36/08** (2009.01)

**H04W 36/14** (2009.01)

**H04W 12/04** (2009.01)

**H04W 12/06** (2009.01)

**H04W 12/08** (2009.01)

**H04W 84/12** (2009.01)

**H04W 88/06** (2009.01)