



US011814232B2

(12) **United States Patent**
Seiler et al.

(10) **Patent No.:** **US 11,814,232 B2**

(45) **Date of Patent:** **Nov. 14, 2023**

(54) **CARTRIDGE, METHOD OF MANUFACTURING A CARTRIDGE, DISPENSING ASSEMBLY AND METHOD OF ASSEMBLING A DISPENSING ASSEMBLY**

(71) Applicant: **medmix Switzerland AG**, Haag (CH)

(72) Inventors: **Philipp Seiler**, Au (CH); **Tobias Bodenmüller**, Eriskirch (DE); **Richard Lavelanet**, Balgach (CH)

(73) Assignee: **MEDMIX SWITZERLAND AG**, Haag (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 256 days.

(21) Appl. No.: **17/281,774**

(22) PCT Filed: **Aug. 2, 2019**

(86) PCT No.: **PCT/EP2019/070895**

§ 371 (c)(1),

(2) Date: **Mar. 31, 2021**

(87) PCT Pub. No.: **WO2020/069784**

PCT Pub. Date: **Apr. 9, 2020**

(65) **Prior Publication Data**

US 2021/0394989 A1 Dec. 23, 2021

(30) **Foreign Application Priority Data**

Oct. 2, 2018 (EP) 18198353

Apr. 12, 2019 (EP) 19168895

(51) **Int. Cl.**

B65D 81/32 (2006.01)

B01F 35/52 (2022.01)

(Continued)

(52) **U.S. Cl.**

CPC **B65D 81/3261** (2013.01); **B01F 35/522** (2022.01); **B05C 17/00513** (2013.01); **B05C 17/00553** (2013.01); **B65D 83/0072** (2013.01)

(58) **Field of Classification Search**

CPC **B65D 81/3261**; **B65D 83/0072**; **B65D 35/242**; **B65D 35/10**; **B65D 47/06**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,275,193 A 9/1966 Barr

3,467,283 A 9/1969 Kinnavy

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 058 657 B1 5/2003

EP 266 844 B1 1/2007

(Continued)

OTHER PUBLICATIONS

International Search Report dated Jan. 9, 2020 in corresponding International Patent Application No. PCT EP2019/070895, filed Aug. 2, 2019.


Primary Examiner — Rafael A Ortiz

(74) *Attorney, Agent, or Firm* — GLOBAL IP COUNSELORS, LLP

(57) **ABSTRACT**

A cartridge for a material to be dispensed includes a rigid head part having a dispensing outlet and a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end that is connected to the head part. The head part has an outer circumferential surface, and an inner surface of the front end of the flexible film is sealingly and non-releasably connected to the outer circumferential surface of the head part.

40 Claims, 7 Drawing Sheets



(51)	Int. Cl. B05C 17/005 (2006.01) B65D 83/00 (2006.01)	10,071,837 B2 9/2018 Franca et al. 10,124,521 B2 11/2018 Geiger 10,442,582 B1 10/2019 Ekkert 10,486,880 B2 11/2019 Franca et al.
(58)	Field of Classification Search CPC . B65D 81/32; B01F 35/522; B05C 17/00513; B05C 17/00553 USPC 206/219; 222/92 See application file for complete search history.	2002/0170926 A1* 11/2002 Horner B05C 17/0052 222/326 2004/0000562 A1 1/2004 Gantner 2005/0109796 A1 5/2005 Bourque et al. 2005/0138792 A1 6/2005 Black et al. 2006/0006194 A1 1/2006 Niggemyer et al. 2006/0021996 A1 2/2006 Scott et al. 2006/0144854 A1 7/2006 Clemens et al. 2006/0188314 A1 8/2006 Hunter et al. 2010/0108709 A1* 5/2010 Frey B05C 17/00583 222/105 2011/0220679 A1* 9/2011 Mamiye B65D 81/325 220/276 2014/0174037 A1 6/2014 Frey 2015/0147430 A1 5/2015 Dzikowicz et al. 2016/0045928 A1 2/2016 Frey 2017/0072426 A1 3/2017 Frey 2018/0169693 A1 6/2018 Frey 2018/0280235 A1 10/2018 Franca et al. 2019/0015865 A1 1/2019 Ludwig et al.
(56)	References Cited U.S. PATENT DOCUMENTS	
	3,905,517 A 9/1975 Friedrich et al. 3,979,025 A 9/1976 Friedrich et al. 4,233,725 A 11/1980 Burger 4,687,663 A 8/1987 Schaeffer 5,002,523 A 3/1991 Cho 5,184,757 A 2/1993 Giannuzzi 5,305,920 A 4/1994 Reiboldt et al. 5,360,146 A 11/1994 Ikushima 5,409,143 A 4/1995 Sigel et al. 5,593,066 A * 1/1997 Konuma B65D 83/0072 222/326 5,647,510 A * 7/1997 Keller B05C 17/00513 222/105 6,129,244 A 10/2000 Horth 6,237,307 B1 5/2001 Zentmyer et al. 6,334,548 B1 1/2002 Ichikawa et al. 6,860,406 B2 3/2005 Kobetsky et al. 6,971,787 B2 12/2005 Botrie et al. 7,137,531 B2 11/2006 Arghyris et al. 7,144,170 B2 12/2006 Parks et al. 7,445,135 B2 11/2008 Miyata et al. 7,815,384 B2 10/2010 Parks et al. 8,276,755 B2 10/2012 Matsumura et al. 8,313,006 B2 11/2012 Willner et al. 8,690,012 B2 4/2014 Stoeckli et al. 9,132,944 B2 9/2015 Schick 9,238,544 B2 1/2016 Schulz et al. 9,517,488 B2 12/2016 Frey 9,968,959 B2 5/2018 Frey	
		FOREIGN PATENT DOCUMENTS
		EP 284 163 B1 3/2008 EP 2 322 449 B1 6/2012 EP 2927156 A1 * 10/2015 B05C 17/00553 EP 3 195 941 A1 7/2017 EP 3 263 483 A1 1/2018 FR 2 820 127 A1 8/2002 GB 2305160 A * 4/1997 B05C 17/00513 JP H03133748 A 6/1991 JP H06336254 A 12/1994 JP 2001-225853 A 8/2001 JP 3624132 B2 3/2005 JP 4248694 B2 4/2009 WO WO-2005095225 A1 * 10/2005 B01F 13/002 WO 2009/113502 A1 9/2009 WO WO-2009113502 A1 * 9/2009 B29C 45/1418

* cited by examiner






Fig. 1









Fig.7





Fig.8







Fig.10

Fig.11




Fig.12




Fig. 14A




Fig. 14B





Fig. 14C



**CARTRIDGE, METHOD OF
MANUFACTURING A CARTRIDGE,
DISPENSING ASSEMBLY AND METHOD OF
ASSEMBLING A DISPENSING ASSEMBLY**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a U.S. National Stage application of International Application No. PCT/EP2019/070895, filed Aug. 2, 2019, which claims priority to European Patent Application No. 18198353.7, filed Oct. 2, 2018 and European Patent Application No. 19168895.1, filed Apr. 12, 2019, the contents of each of which are hereby incorporated herein by reference.

BACKGROUND

Field of the Invention

The present invention relates to a cartridge for a material to be dispensed comprising a rigid head part having a dispensing outlet and a flexible film forming a cartridge wall, with the film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end that is connected to the head part, wherein the head part has an outer circumferential surface, and wherein an inner surface of the front end of the film is sealingly and non-releasably connected to the outer circumferential surface of the head part. The invention further relates to a method of manufacturing a cartridge, to a dispensing assembly, and to a method of assembling a dispensing assembly comprising such a cartridge.

Background Information

In the industrial sector, in the construction industry, for example of buildings, and also in the dental sector, cartridges are frequently used to store flowable liquid, frequently pasty or viscous to highly viscous substances and to dispense them for the respective application as required. Examples for such substances are joint sealing compounds, compounds for chemical dowels or chemical anchors, adhesives, pastes or impression materials in the dental sector. These cartridges are usually produced from plastic and are manufactured in an injection molding process.

A distinction is made between single-component systems in which the material to be dispensed is only made of one component and two-component or multicomponent systems in which at least two different components are stored in separate chambers of the same cartridge or in separate cartridges, wherein the components are intimately mixed at dispensing by a dynamic or static mixing apparatus. Examples for this are two-component adhesives or chemical dowels which only harden after the mixing of the two components. Two-component systems are in particular also used in the industrial sector for paints which are often used to generate functional protective layers such as for corrosion protection.

SUMMARY

For reasons of environmental protection, film cartridges are increasingly being used.

In contrast to regular cartridges which are completely produced from plastic in an injection molding process, at

least parts of film cartridges are designed as a film. Usually the cartridge wall(s) bounding the cartridge chamber(s) is/are made of a film which is connected to a head part made of rigid material, e.g. plastic, comprising the dispensing outlet. This has several advantages. On the one hand, the unfilled film cartridges can be stored and transported in a collapsed state from the cartridge manufacturers to the manufacturers of the filling materials (media) who then take care of the filling of the empty cartridges. Only after being filled the film cartridge is in its expanded state which is comparable in size to a regular non-collapsible cartridge. This means that the necessary space for storage and for transportation can be reduced, since the collapsed cartridges have a reduced size in comparison to regular non-collapsible cartridges.

On the other hand, once the cartridges have been used, i.e. reduced to the collapsed state by dispensing the filling material, the cartridges are significantly reduced in size and weight in comparison to regular cartridges so that the cost of disposal is also reduced. In any case the carbon footprint associated with the film cartridges is reduced in comparison to plastic cartridges that are completely formed in an injection molding process.

U.S. Pat. No. 5,593,066 discloses film cartridges in which the film is attached to the head part of the cartridges. During the manufacture of such a film cartridge with an injection molded head, one has to place a cylindrical film over a core that is part of a mold. The attachment of the film at the head part can be problematic and if not carried out correctly leads to a detachment of the film from the head part.

It has been determined that during the manufacture of a film cartridge with an injection molded head, one has to sealingly attach a film to the rigid head part. For this, a required length or size of the film has to be cut from a larger film piece or film roll. If this cut or trimmed film is attached to the head part, a cutting area of the film where the film was cut can pose a problem: as a result of the cut, individual fiber-like or hair-like film parts of the film could become loose or detached from the main surface of the film in the cutting area of the film. The connection of the head part with a section of the film which includes such a cutting area could thus lead to a leak or faulty attachment in the region of the parts of the film comprising such a cutting area. Further prior art is known from EP 3 263 483 A1.

For this reason it is an object of the invention to enhance the connection between the film and the cartridge so that a cartridge can be produced in a more reliable manner. It is a further object of the invention to reduce the number of rejected cartridges due to detached injection molded heads. It is yet a further object of the present invention to propose a cartridge of the initially named kind and a method of manufacturing such a cartridge by which the total manufacturing costs can be reduced.

This object is satisfied by a cartridge having the features disclosed herein.

Such a cartridge for a material to be dispensed comprises a rigid head part having a dispensing outlet and a flexible film forming a cartridge wall, with the film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end that is connected to the head part, wherein the head part has an outer circumferential surface, the outer circumferential surface comprising formations, wherein an inner surface the front end of the film is sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations present at the outer circumferential surface of the head part.

Sealingly and non-releasably connected in the present disclosure means that there will be no leakage of the cartridge contents during storage or use and that the cartridge will not detach from the head piece during normal storage and use conditions.

It has been found that better sealing and non-releasable connections can generally be obtained between materials having similar or compatible compositional properties, such as polyolefins with polyolefins, particularly PE with PE or PP with PP, or polyamides with polyamides, such as Nylon 6 or Nylon 66 with themselves or with each other, and/or through the use of surface roughening, surface modification treatments such as corona discharge to increase the surface energy and/or to introduce polar groups, primers and/or adhesives into the respective composition.

In addition to application testing, other test methods include measurements of sealing via qualitative means or measures such as pressing air-filled cartridges under water and inspecting for bubbles or more quantitative methods such as leak gas detectors, vacuum burst or creep tests and seal strength measurements, and measurements of bond strength include measurements of tensile, peel or stripping strength.

Furthermore, it is desirable that the connection does not release during storage and especially use and, for example, is capable of withstanding pressures of at least 5 Bar and preferably of up to 55 bar, i.e. the pressures that may arise on dispensing material from the cartridge chamber.

In this connection it should be noted that the application filed by the present applicant at the European Patent Office on the same date as the present application and having the attorney reference S14046PEP and the application DE202018105661.1 filed at the German Patent and Trademark Office are respectively hereby incorporated by reference.

By injection molding the head part to an inner surface of the film, the mechanical properties of the bond can be improved. It has, for example, been found that on use with a multi-layer film, the innermost layer of the film should be the thickest layer of the film for reasons of stability and hence in the region where the bond is formed between the innermost surface and the head part, the most material is present leading to an improved bond in comparison to films that attach to an inner surface of a head part.

Such formations typically form additional fixation elements or means and, in particular comprise protrusions, ribs, pins, hooks, webs, notches, recesses and/or grooves, and are arranged at the outer circumferential surface of the head part in order to enhance the bond between the film and the head part.

The provision of such formations also enables the film forming the cartridge wall to be actively deformed at the respective formation to collect any slack present in the film to ensure that those parts of the inner surface of the film that should be attached to the outer circumferential surface of the head part are attached to the head part. By attaching the inner surface in this way no air pockets arise between the film and the head part. Such air pockets lead to faulty connections and hence to the rejected cartridges.

Moreover, through the use of such formations variances in a diameter of the film can be compensated by the film's property to elongate to a certain degree under strain.

The dimensions of the formations should namely be chosen such that all the slack can be collected even at the largest possible film diameter and such that the strain on films having the smallest possible diameter does not lead to a damage of the film.

It should be noted that the above cartridge can be filled both using front filling and back filling techniques.

It should further be noted that due to the injection molding of the head part such that the film is connected at the outer circumferential surface in contrast to the inner circumferential surface also avoids problems of connecting a film which arise as a result of cutting the film, such as individual fiber-like or hair-like film parts of the film, as these are no longer present in the direct vicinity of a material stored within the cartridge, but at an outer surface of the head part and so do not come into direct contact with the material.

It should be noted in this connection that U.S. Pat. No. 5,593,066 does not disclose the use of such formations nor the problems leading to the requirement of use of such formations.

In this connection it should further be noted that a flexible film bag is a film bag that can be folded together in the empty state, e.g. in the manner of a concertina, and that after filling and a possible dispensing of the components present therein can be unfolded and refolded without the film bag being damaged or becoming limited in its function.

Further benefits and advantageous embodiments of the invention will become apparent from the dependent claims, from the description and from the accompanying drawings.

The formations can comprise grooves formed in the outer circumferential surface of the head part. Grooves can be formed in a comparatively simple manner through the use of inserts and enable the film forming the cartridge wall to be stretched during the manufacturing process so that as little as possible slack is present in the film in order to attach the film to the head part.

The grooves can extend in parallel to the longitudinal direction of the cartridge. Such grooves have found to be beneficial for the attachment of the film to the head part.

The grooves can have a triangular-like shape in a cross-section thereof, i.e. in a side view of the cartridge, in particular with a base of the triangle forming the groove being spaced apart furthest from the dispensing outlet and optionally forming a bottom end of the head part. By forming the grooves in a triangular manner both stresses and strains can be introduced into the film ensuring an improved attachment of the film at the head part. Film bags attached at these grooves appear to have diamond shaped grooves in the outer surface of the film due to the possible interaction between the mold in which the head part is formed and the materials used.

The formations can comprise a ring recess that is formed in the outer circumferential surface and that circumferentially extends around the outer circumferential surface perpendicular to the longitudinal direction of the cartridge. Like the grooves the recess can ensure that stresses and strains are introduced into the film to ensure an improved attachment of the film at the head part. By arranging the recess perpendicular to the grooves the stresses and strains introduced into the film act in a direction perpendicular to the grooves, so that the film is stressed and strained in two dimensions further enhancing the connection between the film and the head part.

The ring recess can extend through the grooves, especially wherein the ring recess extends through the base of the grooves, with the recess respectively the base forming the bottom end of the head part and a middle part of the grooves present in the film forming the cartridge wall. By arranging the recess about a geometric center of the grooves the film can be stressed and strained in an ideal manner in two dimensions. It should be noted in this connection that the middle part of the grooves comprises the geometric center

5

and at most 40% of a length of the diamond-shaped groove in a direction in parallel to the longitudinal direction centered about the geometric center.

The ring recess can have an L-shaped cross-section in the longitudinal direction, with a short limb of the L in particular being arranged perpendicular to the longitudinal direction of the cartridge and/or the long limb of the L being arranged inclined to the longitudinal direction of the cartridge and optionally also to the short limb of the L. Such a ring recess is found to be beneficial for a correct attachment and alignment of the film at the head part. In this connection it should be noted that the short limb of the L can coincide with the base respectively the bottom end of the head part.

The formations can comprise one or more wave-like structures formed in the outer circumferential surface, optionally wherein the wave-like structures can extend perpendicular to the longitudinal direction of the cartridge. Such wave like structures can be used to introduce stresses and strains into the film in two-dimensions which is found to be beneficial for a correct attachment and alignment of the film at the head part.

The wave-like structures can comprise between 2 and 5 valleys and/or between 2 and 5 peaks. This number of peaks and valleys is found to be beneficial for the attachment of the film to the head part. Including fewer or more peaks and valleys can hinder the process of attaching the film to the head part.

Some of the valleys can have a greater depth than other ones of the valleys of the wave-like structure. Additionally or alternatively, some of the peaks can have a greater height than other ones of the peaks of the wave-like structure. In this way variations in the stresses and strains introduced into the film can be varied to ensure that as little as possible slack remains in the film while not stressing film bags of smaller diameter.

One wave-like structure can be formed between directly adjacent grooves. This arrangement has been found to be beneficial during the attachment of the film to the head part.

The formations can comprise one or more ribs projecting from the outer circumferential surface, with each rib, preferably extending perpendicular to the longitudinal direction of the cartridge and in particular being arranged between directly adjacent grooves. The ribs can introduce point like stresses and strains into the film as desired.

The cartridge wall can be received in a support sleeve, with the outer circumferential surface having the formations being arranged within the sleeve and the one or more ribs forming a press-fit and/or interference fit type of connection with an inner surface of the sleeve. Thus, the ribs can fulfill two functions, namely the correct attachment of the film at the head part and also the correct attachment of the cartridge in a sleeve which is required for a correct placement of the cartridge in a dispenser.

The head part can comprise a collar, with the collar surrounding the dispensing outlet in a radially outer region of the head part, extending in the longitudinal direction and defining at least regionally the outer circumferential surface of the head part to which the film is connected, optionally wherein the collar is received in the sleeve. Such a collar improves the amount of surface area available at the head part for connecting the film to the head part.

The collar can be formed radially inwardly of an outermost part of the head part, with a ledge being formed between the outermost part of the head part and the outer circumferential surface of the head part present at the collar. This design has found to be practical in use of the cartridge with a sleeve.

6

The inner surface of the film can be attached to the outer circumferential surface of the head part, wherein a front end of the film can extend beyond the outer circumferential surface of the head part, optionally such that it is connected to the ledge and possibly also to the outermost part of the head part. In this way the attachment of the film at the head part can be further improved.

The cartridge chamber can be filled with a material, for example, with a material selected from the group of members consisting of topical medications, medical fluids, wound care fluids, cosmetic and/or skin care preparations, dental fluids, veterinary fluids, adhesive fluids, disinfectant fluids, protective fluids, paints and combinations of the foregoing.

Such fluids and hence the cartridge can therefore be expediently used in the treatment of target areas such as the nose (e.g. anti-histaminic creams etc.), ears, teeth (e.g. molds for implants or buccal applications (e.g. aphtas, gum treatment, mouth sores etc.), eyes (e.g. the precise deposition of drugs on eyelids (e.g. chalazion, infection, anti-inflammatory, antibiotics etc.), lips (e.g. herpes), mouth, skin (e.g. anti-fungal, dark spot, acne, warts, psoriasis, skin cancer treatment, tattoo removal drugs, wound healing, scar treatment, stain removal, anti-itch applications etc.), other dermatological applications (e.g. skin nails (for example anti-fungal applications, or strengthening formulas etc.) or cytological applications.

Alternatively the fluids and hence the cartridge can also be used in an industrial sector both for the production of products as well as for the repair and maintenance of existing products, e.g. in the building industry, the automotive industry, the aerospace industry, in the energy sector, e.g. for windturbines, etc. The dispensing assembly can, for example, be used for the dispensing of construction material, sealants, bonding material, adhesives, paints, coatings and/or protective coatings.

In this connection it should be noted that the cartridge can be a one-component cartridge comprising one cartridge chamber. Alternatively the cartridge can be a two-component cartridge comprising two cartridge chambers, with a respective chamber being provided e.g. for a hardener and the other one for a corresponding binder material. In this way the design presented herein can be used for a plethora of types of cartridges and applications.

Optionally each cartridge chamber of a two-component cartridge can be bounded by an own head part comprising a chamber outlet for the respective cartridge chamber, in particular with the head parts either being integrally formed or separately formed, with the separately formed head parts preferably being connectable to one another and/or connected to one another, e.g. via the chamber outlets; and/or with the chamber outlets together forming the dispensing outlet. This further illustrates the applicability of the current design for use with film cartridges.

The dispensing outlet can project from the rigid head part in a direction opposed to the direction of extent of the flexible film forming the at least one cartridge wall. In this way e.g. a mixing tip can be attached to the dispensing outlet in a facile manner.

The film can be a multi-layer film comprising at least two, three, four, five or more layers. Such films enable a longer storage life of the components stored in the cartridge in comparison to films made of only one material.

In this connection it should be noted that if the film bag comprises a fin seal rather than an overlap seal, the number of components of a multi-component film can be reduced,

since the outer layer does not have to have a material common to the inner layer. The same is true for an extruded film bag.

Bulges can be present in an internal end face of the head part comprising the dispensing outlet. These bulges form channels through which a material of the head part may flow during the injection molding process and aid in the attachment of the film forming the cartridge wall.

In this connection the head part can have a Shore D hardness selected in the range of 40 to 99. Preferably the Shore D hardness of the head part lies in the range of 40 to 60.

The head part can comprise polyethylene, polypropylene, polyamide, polyethylenterephthalate or polybutylenterephthalate. The head part can for example comprise polyamide in the form of PA-6 (perlon) or PA-66 (nylon). Polyamide has the advantage that it has a good mechanical stability and is thus suitable for the head part.

Polyethylenterephthalats (PET) can also be used for the head part. PET can namely be processed in a facile manner and has a good chemical resistance.

In accordance with an embodiment the head part is made of a high density PE (HDPE). High density polyethylene (HDPE) has a density in the range of 930 kg/m³ to 970 kg/m³ auf.

One can also consider forming the head part and/or the film bag of a material that has been recycled, for example recycled by 100%, such as HDPE, green PE (e.g. made of sugar cane) and PP.

Alternatively, the material of the head part and/or of the film bag can comprise a compound which is formed by a mixture of green PE with normal PE, a mixture of green PE and recycled PE, or a mixture of normal PE with green PE and recycled PE. Also compounds comprising recycled PP, partially recycled PP and/or normal PP can be used in injection molding processes of the head part and/or as the material of the cartridge wall. The use of such recycled materials leads to a more environmentally friendly cartridge.

The head part and/or the film bag can additionally be reinforced with further material such as through the use of fibers, such as natural fibers, wood fibers, cellulose fibers, hemp fibers, cork fibers, fibers from sun flower seeds, grass fibers, bamboo fibers, flax or carbon fibers.

By way of example, PP, TPE, TPS can each be injection molded together with cork fibers. PE, PP, PLA, PPS, and/or PBAT can be used in injection molding processes together with wood or natural fibers. PA, PE and/or PP can be injection molded together with a wide range of natural fibers. PP and/or PE can be injection molded together with fibers from sun flower seeds. PE, PP, and/or PLA can be injection molded together with fibers grass fibers, flax. It is also possible to injection mold thermoplastic materials not only with one kind of fiber but a mixture of types of fibers.

The cartridge can be a single component cartridge having only one cartridge chamber bound by the flexible film forming the cartridge wall. Such a cartridge can expediently store single component mastic materials, sealants and the like.

A second film can be attached to the head part to cover an internal end face of the head part, optionally with the second film bridging an outlet passage leading from the cartridge chamber to an end of the dispensing outlet. Such a second film can prevent diffusion of components present in the material stored in the cartridge via the end face.

Such cartridges can be filled both using front filling techniques and back filling techniques, with the cartridge having a second film that also extends so as to cover the

passage of the dispensing outlet generally only being able to be used in backfilling applications.

In this connection it has been noted that at least one of the head part, the second film and the cartridge wall, such as the first film or a solid cartridge wall, can also be a 3D printed component.

In this connection it should further be noted that 3D printing refers to a process in which material is joined or solidified under computer control to create a three-dimensional object, with material being complied to form the desired object. In some embodiments, a computer can refer to a smart phone, a tablet, a printer motherboard, a processor/computer in the printer, or any other device with a processor or an electronic controller. The material for the at least one of the head part, the second film and the cartridge wall can be any material, such as liquid molecules or powder grains that are capable of being fused together to form the respective component having the desired properties. In some embodiments, the at least one of the head part, the second film and the cartridge wall can be printed from one or more materials such as PA12, polypropylene, and/or glass filled polyamide. However, the material can be any suitable material or materials.

The film forming the film bag can be a multilayer film having at least two layers formed from different materials. In the preferred choice the film is a five-layer film comprising a sandwich structure in which the outer layer is formed of PE (20 to 40 μm thickness) which is connected to a layer of PA (10 to 20 μm) via a tie layer (1.5 to 2.5 μm). The PA layer in turn is connected via a further tie layer (1.5 to 2.5 μm) to an aluminum or aluminum alloy layer (5 to 10 μm). The aluminum or aluminum alloy layer is in turn connected to a further PA layer (10 to 20 μm) via a further tie layer (1.5 to 2.5 μm) which is then connected to an inner layer corresponding to the inner surface 42, via a via a further tie layer (1.5 to 2.5 μm) with the inner layer having a thickness selected in the range of 45 to 100 μm .

The film forming the film bag can be a three-layer film comprising a sandwich structure in which the first layer is formed of polyethylene (PE) (20 to 40 μm thickness), which is connected to a second layer of aluminum (Al) or of an aluminum alloy (Al alloy) (7 to 12 μm thickness) via a tie layer (1.5 to 2.5 μm thickness). The Al or AL alloy layer is in turn connected to a third PET layer (12 to 15 μm thickness) via a further tie layer (1.5 to 2.5 μm thickness).

The film forming the film bag can be a four-layer film comprising a sandwich structure in which the first layer is formed of PE (20 to 40 μm thickness), which is connected to a second layer of aluminum (Al) or of an aluminum alloy (Al alloy) (7 to 12 μm thickness) via a tie layer (1.5 to 2.5 μm thickness). The Al or AL alloy layer is in turn connected to a third layer of PA (10 to 20 μm thickness) via a tie layer (1.5 to 2.5 μm thickness). The third layer of PA is in turn connected to a fourth layer of PE (15 to 30 μm thickness) via a further tie layer (1.5 to 2.5 μm thickness).

It should be noted that the respective tie layers are not considered to be individual layers of a multi-layered film, they are merely present to ensure a bond is formed between the individual layers.

The materials of the film can differ from the above mentioned materials as can their respective thicknesses. It should be noted in this connection that the films typically have a thickness selected in the range of 40 to 200 μm , in particular of 70 to 180, in particular of 120 to 170 μm .

According to a further aspect the present invention relates to a cartridge for a material to be dispensed comprising a rigid head part having a dispensing outlet and a flexible film

9

forming a cartridge wall, with the film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end that is connected to the head part, wherein the head part has an outer circumferential surface, wherein an inner surface of the front end of the film is sealingly and non-releasably connected to the outer circumferential surface of the head part, wherein bulges are present in an internal end face of the head part comprising the dispensing outlet.

According to a further aspect the present invention relates to a dispensing assembly having a cartridge comprising one or more cartridge chambers, the one or more cartridge chambers being filled with a respective material and having the sleeve into which the respective cartridge chamber is inserted, the dispensing assembly optionally further comprising a dispenser and/or a mixing tip. Using such a dispensing assembly one can dispense the desired materials in a facile manner.

According to a further aspect the present invention relates to a method of assembling a dispensing assembly having a cartridge comprising one or more cartridge chambers, a sleeve and optionally a dispenser, the method comprising the steps of:

inserting the one or more cartridge chambers into a respective sleeve;

fixing the one or more cartridge chambers in the respective sleeve by at least one of a press fit and an interference fit between some of the formations present at the respective cartridge chamber and an inner surface of the respective sleeve; and optionally inserted the cartridge and the sleeve into the dispenser.

The advantages associated with the cartridge can beneficially be exploited in such a method.

According to a further aspect the present invention relates to a method of manufacturing a cartridge according to any of the preceding claims, the method comprising the steps of:

placing the film on a core of a mold; introducing inserts into the mold which represent a shape of the formations directly adjacent to the film; and injection molding the head part in a head space of the mold to form the head part with its outer circumferential surface having the formations and to sealingly and non-releasably bond the front end of the film to the outer circumferential surface of the head part.

In this way a cartridge having the advantages discussed in the foregoing can be produced in a facile, cost-effective and reproducible manner.

BRIEF DESCRIPTION OF DRAWINGS

The invention will be explained in more detail hereinafter with reference to the drawings.

FIG. 1 is a perspective view of a first type of cartridge;

FIG. 2 is a side view of the cartridge of FIG. 1;

FIG. 3 is an enlarged sectional view of section A of FIG. 2;

FIG. 4 is an enlarged sectional view of section B of FIG. 2;

FIG. 5 is a schematic sectional view showing a first type of seam;

FIG. 6 is a schematic sectional view showing a second type of seam;

FIG. 7 is a perspective view of a dispensing assembly;

FIG. 8 is an enlarged sectional view of section C of FIG. 7;

FIG. 9 is a side view of a further cartridge;

10

FIG. 10 is an enlarged sectional view of section D of FIG. 9;

FIG. 11 is an enlarged sectional view of section E of FIG. 9;

FIG. 12 is a perspective view from below of a head part;

FIG. 13 is a schematic sectional view through a further type of cartridge; and

FIGS. 14A to 14C are schematic sectional views of various types of head parts of single component cartridges, with a respective second film being attached to the head part.

DETAILED DESCRIPTION

In the following, the same reference numerals will be used for parts having the same or equivalent function. Any statements made having regard to the direction of a component are made relative to the position shown in the drawing and can naturally vary in the actual position of application.

FIG. 1 shows a two-component cartridge 10 configured to store and dispense two materials M, M' from respective cartridge chambers 12, 12'. The two-component cartridge 10 comprises a rigid head part 14 having a dispensing outlet 16 and a flexible film 18, 18' forming a respective cartridge wall 20, 20' for each cartridge chamber 12, 12'. The film 18, 18' bounds the cartridge chamber 12, 12' and extends at least partially in a longitudinal direction A of the cartridge 10. The film 18, 18' having a front end 22, 22' that is connected to the head part 14.

The head part 14 has an outer circumferential surface 24 (see e.g. FIG. 3). The outer circumferential surface comprises formations 26. The front end 22, 22' of the film 18, 18' is sealingly and non-releasably connected to the outer circumferential surface 24 of the head part and to the formations 26 present at the outer circumferential surface 24 of the head part 14.

The formations 26 comprise grooves 28 formed in the outer circumferential surface 24 of the head part 14. The grooves 28 extend in parallel to the longitudinal direction A of the cartridge 10. In a side view of the cartridge 10, see e.g. FIG. 2, or in the perspective view of FIG. 1, the grooves 28 have a triangular-like shape (see FIG. 12) in a cross-section thereof. During the process of attaching the film 18, 18' to the grooves 28 this results in diamond-shaped grooves 28' being visible in an outer surface 60 of the film 18, 18'. Depending on the shape of the grooves 28' also other shapes can be visible in the outer surface 60 of the film 18, 18'.

A base 28" of a triangle forming the groove 28 forms a bottom end 68 of the head part 14 (see FIG. 12).

A further type of formation 26 formed at the cartridge 10 is a ring recess 30 that is formed in the outer circumferential surface 24 and that circumferentially extends around the outer circumferential surface 24 perpendicular to the longitudinal direction A of the cartridge 10.

A further type of formation 26 formed at the cartridge 10 is a wave-like structure 32 formed in the outer circumferential surface 24. The respective wave-like structure 32 extends perpendicular to the longitudinal direction A of the cartridge 10.

A further type of formation 26 formed at the cartridge 10 is a rib 34 projecting from the outer circumferential surface 24. In the examples shown the ribs 34, each extend perpendicular to the longitudinal direction A of the cartridge 10 and are arranged between directly adjacent grooves 28. Other arrangements of the ribs 34, for example grooves 28

arranged in parallel to the longitudinal direction A or more than one per pair of ribs 34 arranged between adjacent grooves 28 are possible.

It should be noted that the ribs 34 project further from the outer circumferential surface 24 than the respective wave-like structure 32.

It should further be noted that the respective groove 28 projects further into the outer circumferential surface 24 than most of the recess 30, and that the grooves 28 and the recess 30 optionally project further into the outer circumferential surface 24 than the ribs 34 or wave-like structures 32 project from the outer circumferential surface 24.

Reinforcement ribs 36 are disposed at the side of the head part 14 remote from the cartridge wall 20, 20'. The reinforcement ribs 36 serve the purpose of reinforcing the head part 14 so that this can easily withstand the pressures applied thereon during a dispensing process.

The dispensing outlet 16 is a common outlet which combines a respective chamber outlet 38. Two outlet passages 40, 40' lead from the respective cartridge chamber 12, 12' to an end 42 of the dispensing outlet 16.

The dispensing outlet 16 is, on the one hand, configured to be sealed off by a cap cooperating with a plunger (not shown) in a storage state of the cartridge 10. The dispensing outlet 16 is further configured to cooperate with a mixing tip (not shown) that is typically used to dispense the materials M, M' stored in the cartridge 10 in a dispensing state of the cartridge 10.

FIG. 2 shows a side view of the cartridge of FIG. 1. The dispensing outlet 16 projects from a pedestal 44 that is arranged on the head part 14 and which forms a connection between the two cartridge chambers 12, 12' of the cartridge 10 of FIG. 1. The pedestal 44 serves the purpose of reinforcing the head part 14 in the region of the dispensing outlet 16 so that the dispensing outlet 16 and the head part 14 can easily withstand the pressures applied thereon during a dispensing process.

The Figs. shown herein respectively show a two-component side by side cartridge 10. It should be noted that the head part 14 and the features and methods of attachment of the head part 14 to the respective film 18, 18' can naturally be employed at a one-component cartridge (not shown) comprising only one cartridge chamber 12, or at a coaxial cartridge comprising two cartridge chambers 12, 12' that are coaxially arranged with respect to one another about the longitudinal direction A.

The cartridge 10 shown in the foregoing has a common head part 14 for both chambers 12, 12'. However, it is naturally also possible to form each cartridge chamber 12, 12' of a two-component cartridge 10 with separate head parts that are then connected to another e.g. in a permanent or releasable manner (both not shown), for example in the region of the outlet chambers 38, 38', with the combined chamber outlets 38, 38' then forming the dispensing outlet 16.

FIG. 3 shows an enlarged sectional view of section A of the cartridge 10 of FIG. 2. The head part 14 comprises a collar 46. The collar 46 surrounds the dispensing outlet 16 in a radially outer region of the head part 14 and extends in the longitudinal direction A and defines the outer circumferential surface 24 of the head part 14 to which the film 18, 18' is connected.

The collar 46 is formed radially inwardly of an outermost part 48 of the head part 14. A ledge 50 is formed between the outermost part 48 of the head part 14 and the outer circumferential surface 24 of the head part 14 present at the collar 46.

It should be noted in this connection that a length of the collar 46 in the longitudinal direction A is typically selected in the range of 2 mm to 20 mm, preferably 5 mm to 7 mm.

It should further be noted that a length of the ledge 50 in a direction perpendicular to the longitudinal direction A is typically selected in the range of 0.5 mm to 8 mm, preferably 1 mm to 4 mm.

An inner surface 52 of the film 18 is attached to the outer circumferential surface 24 of the head part 14, to the ledge 50 and also to the outermost part 48 of the head part 14.

In this connection it should be noted that the film 18, 18' can be connected to the outer circumferential surface 24 of the head part 14 by one of injection molding, by gluing, by welding, in particular ultrasonic welding, by shrinking, by clamping and by mounting.

FIG. 3 further shows that the ring recess 30 has an L-shaped cross-section in the longitudinal direction A. A short limb 30' of the L is arranged perpendicular to the longitudinal direction A of the cartridge 10 and the long limb 30'' of the L is arranged inclined to the longitudinal direction A of the cartridge 10 and also to the short limb 30' of the L.

It should be noted in this connection that a length of the short limb 30' perpendicular to the longitudinal direction A is typically selected in the range of 0.3 mm to 7 mm, preferably 0.8 mm to 4 mm. It should further be noted that the short limb 30' can form the bottom end 54 (see FIG. 12).

It should further be noted that a length of the long limb 30'' is typically selected in the range of 1 mm to 12 mm, preferably 2 mm to 8 mm.

It should further be noted that a height of the rib 34 projecting from the outermost surface 24 is typically selected in the range of 0.05 to 3 mm, preferably in the range of 0.15 to 1.5 mm. A length of the rib 34 perpendicular to the longitudinal direction A is typically selected in the range 0.1 to 4 mm, in particular 0.2 to 2 mm.

The respective wave-like structure 32 can comprise between 2 and 5 valleys 32'' and between 2 and 5 peaks 32', with a respective peak having a height typically selected in the range of 0.05 to 2 mm, preferably in the range of 0.1 to 1 mm. The respective valley 32'' is either formed in a plane coinciding with the outer circumferential surface 24 or has a depth of up to 3 mm, preferably of up to 0.5 mm.

It should be noted in this connection that some of the valleys 32'' can have a greater depth than other ones of the valleys 32'' of the wave-like structure 32. It should further be noted that some of the peaks 32' can have a greater height than other ones of the peaks 32' of the wave-like structure 32. The wave-like structure 32 is generally formed between directly adjacent grooves 28.

The ring recess 30 intersects the grooves 28' present in the film 18, 18', but has a lesser depth than that of the grooves 28'. In this connection it should be noted that the grooves 28 can extend over a height of the collar 46, with the diamond-like grooves 28' extending further beyond the bottom end 68. The ring recess 30 is arranged to extend through a middle part of the grooves 28.

The grooves 28 typically have a length selected in the range of 2 mm to 20 mm, preferably 5 mm to 7 mm; and/or has a depth a depth from the outer circumferential surface 24 typically selected in the range of 0.4 mm to 5 mm, preferably 0.5 mm to 2 mm.

The diamond-like grooves 28' typically have a length selected in the range of 2 mm to 30 mm, preferably 10 mm to 14 mm;

FIG. 4 shows an enlarged sectional view of section B of the cartridge 10 of FIG. 2. The film 18, 18' also at this side of the cartridge chamber 12, 12' extends beyond an internal

13

end face 54 of the head part 14 comprising the respective chamber outlet 38, 38'. It should be noted in this connection that a respective second film 56, 56' is attached to the head part 14 to cover the end face 54. The second film 56, 56' is arranged to at least partially, in particular almost completely or completely cover the end face 54.

The second film 56, 56' is arranged to prevent a diffusion of the material M, M' stored in the cartridge chamber 12, 12' through the end face 54 of the head part 14.

The properties of the second film 56, 56' can be selected identical to the properties of the film 18, 18' forming the cartridge wall 20, 20', the film 56, 56' can be selected from a material which bonds to the material of a rear surface 54' forming the end face 54 of the head 14 part, preferably the material of the second film 56, 56' and the material of the rear surface 54' of the head part 14 are identical.

FIG. 5 shows a schematic sectional view of the film 18, 18' taken perpendicular to the longitudinal direction A. The cartridge wall 20, 20' comprises a connection seam 58 extending in the longitudinal direction A over a length of the cartridge wall 20, 20'. The connection seam 58 comprising overlapping regions of the film. FIG. 5 shows a first type of seam 58. The connection seam 58 comprises a part of the inner surface 52 of the film 18, 18' adjacent to a first longitudinal edge of the film 18, 18' which is connected, in particular bonded, to a part of the outer surface 60 of the film 18, 18' adjacent to an opposite second longitudinal edge of the film 18, 18'. Such a seam 58 is commonly known as an overlap seam 58.

FIG. 6 shows a schematic sectional view of a further type of film 18, 18' taken perpendicular to the longitudinal direction A similar to the drawing shown in FIG. 5. FIG. 6 shows a second type of seam 58'. The connection seam 58' comprises a part of the inner surface 52 of the film 18, 18' adjacent to a first longitudinal edge of the film 18, 18' which is connected, in particular bonded, to a part of the inner surface 52 of the film 18, 18' adjacent to an opposite second longitudinal edge of the film 18, 18'. Such a seam 58' is commonly known as a fin seal 58'.

In this connection it should be noted that a closure seam (not shown) can be disposed at a rear end of the film 18, 18'. The closure seam then runs traverse to the longitudinal direction A and connects two regions of the inner surface 42 of the film 18, 18' to close the rear end of the cartridge chamber 12, 12' in a seal tight manner.

FIG. 7 shows a perspective view of a dispensing assembly 62. The dispensing assembly 62 comprising the two-component cartridge 10, with the one or more cartridges 10 being filled with a respective material M, M' and a respective 64 sleeve into which the respective cartridge chamber 12, 12' is inserted. The cartridge walls 20, 20' are received in the support sleeves 64.

FIG. 8 shows an enlarged sectional view of section C of the dispensing assembly 62. The collar 46 is received in the sleeve 64 as is the outer circumferential surface 24 having the formations 26 arranged within the sleeve 64 and the one or more ribs 34 forming a press-fit and/or interference fit type of connection with an inner surface 66 (see FIG. 8) of the sleeve 64.

On assembling the dispensing assembly 62, the cartridge 10, respectively the cartridge chambers 12, 12' are inserted into the respective sleeve 64. The cartridge 10 is fixed to the respective sleeve 64 by at least one of a press fit and an interference fit between some of the formations 26 present at the respective cartridge 10 and the inner surface 66 of the respective sleeve 64.

14

In this connection it should be noted that the sleeve can be made from plastic, e.g. PE or PA or from a metal, e.g. aluminum or an aluminum alloy, for example in an extrusion process or an injection molding process.

FIG. 9 shows a side view of a further cartridge 10. The cartridge 10 of FIG. 9 is also a two-component cartridge 10. The difference between the cartridge 10 of FIG. 9 and the one shown e.g. in FIG. 1 lies in the attachment of the film 18, 18' to the head part 14.

FIG. 10 shows an enlarged sectional view of section D of the cartridge 10 of FIG. 9. The inner surface of the film 18 is attached to the outer circumferential surface 24 of the head part 14. The front end 22 of the film 18 extends beyond the outer circumferential surface 24 of the head part 14 and such that it projects partly along the ledge 50. The front end 22 of the film 18 does not project over the complete length of the ledge 50 or over the outermost part 48 of the head part 14 as is the case for the cartridge 10 of FIGS. 1 to 4.

FIG. 11 shows an enlarged sectional view of section E of FIG. 9 which is similar to the drawing shown in FIG. 4. Like in FIG. 10 the front end 22, 22' of the film 18, 18' does not project over the complete length of the ledge 50 or over the outermost part 48 of the head part 14 as is the case for the cartridge 10 of FIGS. 1 to 4.

FIG. 12 shows a perspective view from below of the head part 14. The grooves 28 are seen which taper from a bottom end 68 of the head part towards the ledge 50 in the manner of a triangle. On injection molding the head part 14 to the film 18, 18' this structure aids in the formation of the diamond shaped grooves 28' that are visible e.g. in FIG. 1 in the outer surface 60 of the film 18, 18'.

FIG. 12 further shows the presence of a plurality of bulges 70 that are present in the internal end face 54 of the head part 14 comprising the chamber outlets 38, 38'. The respective bulges 70 connect with two of the grooves 28. The bulges 70 are formed by passages present in the core (not shown) of the injection mold and are the passages via which the material of the head part 14 is injected into the injection mold. Through the provision of such passages and the presence of the bulges 70, the attachment of the film 18, 18' to the head part can be improved as the flow of material in the mold can be positively influenced thereby.

In this connection it should be noted that it is preferred if there is one bulge 70 per pair of grooves 28. It is further preferred if the plurality of grooves intersect at one point of intersection 72, with the point of intersection 72 forming the inlet position of the flow of material into the injection mold.

FIG. 13 shows a schematic sectional view through the film 18, 18' of a further type of cartridge 10. The film 18, 18' is a blown extruded film 18, 18' that does not comprise a longitudinal seam in contrast to the examples shown in FIGS. 5 and 6.

On forming the cartridges 10 discussed in the foregoing a film 18, 18' is placed on a core of a mold (not shown). Not shown inserts are then introduced into the mold. The inserts comprises structures which correspond to a shape of the formations 26 directly adjacent to the film 18, 18'. Once the mold is closed the head part 14 is injection molding in a head space of the mold to form the head part 14 with its outer circumferential surface 24 having the formations 26 to sealingly and non-releasably bond the front end 22, 22' of the film 18, 18' to at least the outer circumferential surface 24 of the head part 14.

In this connection it should be noted that the films 18, 18' discussed in the foregoing can comprise the inner surface 52 and the outer surface 60. It is the inner surface 52 that is connected to the outer circumferential surface 24 of the head

part **14**. The connection preferably being formed by a bond produced in an injection molding process to form an integral connection structure.

The film **18, 18'** is preferably a multilayer film having at least two layers formed from different materials. In the preferred choice the film is a five layer film comprising a sandwich structure in which the outer layer is formed of PE (20 to 40 μm thickness) which is connected to a layer of PA (10 to 20 μm) via a tie layer (1.5 to 2.5 μm). The PA layer in turn is connected via a further tie layer (1.5 to 2.5 μm) to an aluminum or aluminum alloy layer (5 to 10 μm). The aluminum or aluminum alloy layer is in turn connected to a further PA layer (10 to 20 μm) via a further tie layer (1.5 to 2.5 μm) which is then connected to an inner layer corresponding to the inner surface **42**, via a further tie layer (1.5 to 2.5 μm) with the inner layer having a thickness selected in the range of 45 to 100 μm .

It should be noted that the respective tie layers are not considered to be individual layers of a multi-layered film, they are merely present to ensure a bond is formed between the individual layers.

The materials of the film **18, 18'** can differ and from the above mentioned materials as can their respective thicknesses. It should be noted in this connection that the films **18, 18'** typically have a thickness selected in the range of 70 to 200 μm , in particular of 120 to 170 μm .

The head part **14** typically comprises plastic and in particular consists of plastic with at least the part of the film **18, 18'** that is connected to the head part **14** also comprising plastic and in particular consisting of plastic.

Generally speaking the plastic of the head part **14** and the plastic of the part of the film **18, 18'** being connected to the head part **14** are selected from plastics which bond and are preferably the same so that the strongest possible bond is formed there between. The head part **14** is beneficially produced by injection molding as this permits a facile, reproducible, fast and cost-effective manufacture of the cartridges.

It should further be noted that the cartridge wall **20, 20'** can be formed from a blown extruded film sleeve.

It should also be noted that the material of the inner layer **52** and the material of the outer layer **60** can be identical or that the material of the inner layer **52** and the material of the outer layer **60** can be different from one another.

It should also be noted that the thickness of the inner layer **52** and the thickness of the outer layer **60** can be identical or that the thickness of the inner layer **52** is greater than the thickness of the outer layer **60**.

It should be noted in this connection that the front end **22, 22'** of the film **18, 18'** can be clamped between the outer circumferential surface **24** of the head part **14** and an inner surface of a clamping member (not shown), in particular a clamping ring, surrounding the outer circumferential surface **24** of the head part **14**. Such a clamping ring is used to support the attachment of the film **18, 18'** at the head part **14**.

FIGS. **14A** to **14C** show schematic sectional views of various types of head parts **14** of single component cartridges **1**, with respective second films **56** being attached to the head part **14**. The connection of the first film **18** at the collar **46** can take place in the same manner as described in the foregoing.

FIG. **14A** shows a first type of single component cartridge **10**, the dispensing outlet **16** of which has an outer thread **74** extending over a cylindrically shaped portion of the dispensing outlet **16** that extends from the head part **14** to the

front end **76** of the dispensing outlet **16**. Mixing tips, outlets and caps can be connected to the single component cartridge **10** via the outer thread **74**.

The front end **76** comprises a sealed front end **76'** at its very end. Thus in the storage state of the cartridge **10**, the chamber outlet **38** is sealed off at the end **42** of the passage **40**. The sealed front end **76'** like the dispensing outlet **16** is made from the same material as the head part **14**. Such a sealed front end **76'** is expediently used in backfilling applications.

In order to use such a single component cartridge **10**, the front end **76** is typically separated from the dispensing outlet **16**, typically by cutting the sealed front end **76'** away from the front end **76**.

In order to prevent the outer thread **74** from becoming damaged on cutting away the sealed front end **76'**, the sealed front end **76'** is presently formed at a V-shaped portion and is typically cut at the shanks of the V-shape. Naturally other shapes of the sealed front end **76'**, such as a dome shaped end, a trapezoidal shaped end etc. are possible.

FIG. **14B** shows a further type of single component cartridge **10** in which the second film **56** extends over the complete end face **54** of the head part **14** and thereby bridges the passage **40** of the chamber outlet **38**. Also this design is suited to backfilling operations, since the chamber outlet **38** is sealed off in this way. In contrast to the design shown in FIG. **14A**, the chamber outlet **38** is open even in the storage state of the cartridge **10**.

In order to use the cartridge **10**, the second film **56** has to be pierced. The tool (not shown) used to pierce the second film **56** can either be a separate tool, or it can be arranged at a mixer or outlet (also not shown) that is connected to the cartridge **10** via the outer thread and that then comprises some form of piercing member that projects through the passage **40** and that is configured to engage the second film **56**.

The type of single component cartridge **10** shown in FIG. **14C** comprises a cap **78** that is arranged at the front end **76** via the outer thread **74** and a corresponding inner thread **84**. In order to seal the front end **76**, the cap comprises an annular projection **80** projecting into the passage **40**. In some instances a seal **82** can be arranged on an outer surface of the annular projection **80** in order to seal between the cap **78** and the front end **76**. The cartridge **10** shown in FIG. **14C** can be used in both front and back filling applications, but is generally used in front filling applications.

The invention claimed is:

1. A cartridge for a material to be dispensed comprising: a rigid head part having a dispensing outlet; and

a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end connected to the head part, the head part having an outer circumferential surface comprising formations, and an inner surface of the front end of the flexible film being sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations at the outer circumferential surface of the head part,

the formations comprising grooves formed in the outer circumferential surface of the head part, and comprising a ring recess formed in the outer circumferential surface and that circumferentially extends around the outer circumferential surface perpendicular to the longitudinal direction of the cartridge, and the ring recess extending through the grooves.

17

2. The cartridge of claim 1, wherein the grooves extend parallel to the longitudinal direction of the cartridge.
3. The cartridge of claim 1, wherein the grooves have a triangular-like shape in a cross-section thereof.
4. The cartridge of claim 3 wherein a base of the triangle forming the groove is spaced apart furthest from the dispensing outlet.
5. The cartridge of claim 1, wherein the ring recess extends through a base of the grooves, with the base forming a bottom end of the head part.
6. The cartridge in accordance with claim 1, wherein the ring recess has an L-shaped cross-section in the longitudinal direction.
7. The cartridge of claim 6, wherein a short limb of the L is arranged perpendicular to the longitudinal direction of the cartridge.
8. The cartridge of claim 6, wherein a long limb of the L is arranged inclined to the longitudinal direction of the cartridge.
9. The cartridge of claim 7, wherein the long limb of the L is arranged inclined to the longitudinal direction of the cartridge and also to the short limb of the L.
10. The cartridge of claim 7, wherein the short limb of the L forms a bottom end of the head part.
11. The cartridge of claim 1, wherein the formations comprise one or more wave-like structures formed in the outer circumferential surface.
12. The cartridge of claim 11, wherein the wave-like structures extend perpendicular to the longitudinal direction of the cartridge.
13. The cartridge of claim 11, wherein the wave-like structures comprise at least one of between 2 and 5 valleys and between 2 and 5 peaks.
14. The cartridge of claim 11, wherein the formations comprise grooves formed in the outer circumferential surface of the head part, and one wave-like structure of the one or more wave-like structures is formed between directly adjacent grooves of the grooves.
15. The cartridge in accordance with claim 1, wherein the formations comprise one or more ribs projecting from the outer circumferential surface.
16. The cartridge of claim 15, wherein each rib of the one or more ribs extends perpendicular to the longitudinal direction of the cartridge.
17. The cartridge of claim 15, wherein the formations comprise grooves formed in the outer circumferential surface of the head part, and each rib of the one or more ribs is arranged between directly adjacent grooves of the grooves.
18. The cartridge in accordance with claim 15, wherein the cartridge wall received in a support sleeve, with the outer circumferential surface having the formations arranged within the sleeve and the one or more ribs forming at least one of a press-fit and an interference fit type of connection with an inner surface of the sleeve.
19. The cartridge of claim 1, wherein the head part comprises a collar, with the collar surrounding the dispensing outlet in a radially outer region of the head part, extending in the longitudinal direction and defining at least regionally the outer circumferential surface of the head part to which the flexible film is connected.
20. The cartridge of claim 19, wherein the collar is formed radially inwardly of an outermost part of the head part, with a ledge formed between the outermost part of the head part and the outer circumferential surface of the head part present at the collar.

18

21. The cartridge of claim 1, wherein the inner surface of the flexible film is attached to the outer circumferential surface of the head part, and a front end of the flexible film extends beyond the outer circumferential surface of the head part.
22. The cartridge of claim 1, wherein the cartridge chamber is filled with the material.
23. The cartridge of claim 1, wherein the cartridge is a one-component cartridge comprising one cartridge chamber.
24. The cartridge of claim 1, wherein the cartridge is a two-component cartridge comprising two cartridge chambers.
25. The cartridge of claim 24, wherein the two cartridge chambers include a first cartridge chamber and a second cartridge chamber, and the rigid head part is a first rigid head part and the cartridge includes a second rigid head part, the first and second cartridge chamber being bounded by the first rigid head part and the second rigid head part, respectively, and the dispensing outlet comprising a first chamber outlet and a second chamber outlet for the first cartridge chamber and the second cartridge chamber, respectively.
26. The cartridge of claim 25, wherein the first and second rigid head parts are either integrally formed or separately formed.
27. The cartridge of claim 26, wherein the first and second rigid head parts are separately formed and at least one of connectable to one another and connected to one another.
28. The cartridge of claim 1, wherein the dispensing outlet projects from the rigid head part in an opposite direction to a direction of extent of the flexible film forming the cartridge wall.
29. The cartridge of claim 1, wherein the flexible film is a multi-layer film comprising at least two, three four, five or more layers.
30. The cartridge of claim 1, wherein the cartridge is a single component cartridge having only one cartridge chamber bound by the flexible film forming the cartridge wall.
31. The cartridge of claim 1, wherein a second film is attached to the head part to cover an internal end face of the head part.
32. The cartridge of claim 31, wherein the second film bridges an outlet passage leading from the cartridge chamber to an end of the dispensing outlet.
33. A cartridge for a material to be dispensed, comprising: a rigid head part having a dispensing outlet and a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end connected to the head part, the head part having an outer circumferential surface comprising formations, and an inner surface of the front end of the flexible film being sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations at the outer circumferential surface of the head part, the formations comprising one or more wave-like structures formed in the outer circumferential surface, the wave-like structures comprising at least one of between 2 and 5 valleys and between 2 and 5

peaks, and some of the valleys have a greater depth than other ones of the valleys of the wave-like structure.

- 34. A cartridge for a material to be dispensed, comprising:
 - a rigid head part having a dispensing outlet and
 - a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end connected to the head part, the head part having an outer circumferential surface comprising formations, and an inner surface of the front end of the flexible film being sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations at the outer circumferential surface of the head part, the formations comprising one or more wave-like structures formed in the outer circumferential surface, the wave-like structures comprising at least one of between 2 and 5 valleys and between 2 and 5 peaks, and some of the peaks have a greater height than other ones of the peaks of the wave-like structure.
- 35. A cartridge for a material to be dispensed comprising:
 - a rigid head part having a dispensing outlet and comprising a collar; and
 - a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end connected to the head part, the head part having an outer circumferential surface comprising formations, and an inner surface of the front end of the flexible film being sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations at the outer circumferential surface of the head part, the formations comprising one or more ribs projecting from the outer circumferential surface, and the collar surrounding the dispensing outlet in a radially outer region of the head part, extending in the longitudinal direction and defining at least regionally the outer circumferential surface of the head part to which the flexible film is connected, the collar being received in a sleeve.
- 36. A cartridge for a material to be dispensed comprising:
 - a rigid head part having a dispensing outlet; and
 - a flexible film forming a cartridge wall, with the flexible film bounding a cartridge chamber for the material to be dispensed, extending at least partially in a longitudinal direction of the cartridge and having a front end

connected to the head part, the head part having an outer circumferential surface comprising formations, and an inner surface of the front end of the flexible film being sealingly and non-releasably connected to the outer circumferential surface of the head part and to the formations at the outer circumferential surface of the head part, the head part comprising a collar, with the collar surrounding the dispensing outlet in a radially outer region of the head part, extending in the longitudinal direction and defining at least regionally the outer circumferential surface of the head part to which the flexible film is connected, the collar formed radially inwardly of an outermost part of the head part, with a ledge formed between the outermost part of the head part and the outer circumferential surface of the head part present at the collar, and a front end of the flexible film extending beyond the outer circumferential surface of the head part such that the front end of the flexible film is connected to at least one of the ledge and the outermost part of the head part.

- 37. A dispensing assembly comprising:
 - the cartridge in accordance with claim 1, the cartridge chamber being filled with the material; and
 - a sleeve into which the cartridge is capable of being inserted.
- 38. A method of assembling a dispensing assembly comprising the cartridge in accordance with claim 1 and a sleeve, the method comprising:
 - inserting the cartridge chamber into the sleeve; and
 - fixing the cartridge chamber in the sleeve by at least one of a press fit and an interference fit between some of the formations disposed at the cartridge chamber and an inner surface of the sleeve.
- 39. The method of claim 38, the dispensing assembly further having a dispenser.
- 40. A method of manufacturing a cartridge according to claim 1, the method comprising:
 - placing the flexible film on a core of a mold;
 - introducing inserts into the mold which represent a shape of the formations directly adjacent to the flexible film; and
 - injection molding the head part in a head space of the mold to form the head part with the outer circumferential surface having the formations and to sealingly and non-releasably bond a front end of the flexible film to at least the outer circumferential surface of the head part.

* * * * *