



(86) Date de dépôt PCT/PCT Filing Date: 2008/06/30
(87) Date publication PCT/PCT Publication Date: 2009/01/08
(85) Entrée phase nationale/National Entry: 2009/12/29
(86) N° demande PCT/PCT Application No.: JP 2008/062243
(87) N° publication PCT/PCT Publication No.: 2009/005159
(30) Priorités/Priorities: 2007/06/29 (JP2007-172742);
2008/06/20 (JP2008-162311)

(51) Cl.Int./Int.Cl. *G03G 21/18* (2006.01)

(71) Demandeur/Applicant:
CANON KABUSHIKI KAISHA, JP

(72) Inventeurs/Inventors:
TOBA, SHINJIRO, JP;
YOSHIMURA, AKIRA, JP;
NITTANI, SUSUMU, JP

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : APPAREIL DE FORMATION D'IMAGE ELECTROPHOTOGRAPHIQUE DE CARTOUCHE DE TRAITEMENT
(54) Title: PROCESS CARTRIDGE AND ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS




FIG. 6

(57) Abrégé/Abstract:

A process cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, includes an electrophotographic photosensitive drum; developing roller for developing an electrostatic latent image formed on the

(57) **Abrégé(suite)/Abstract(continued):**

electrophotographic photosensitive drum; drum frame supporting the electrophotographic photosensitive drum; a developing frame supporting the developing roller, the developing frame is movable relative to the drum frame and is capable of taking a contacting position in which the developing roller is in contact with the electrophotographic photosensitive drum; and a force receiving device including a first force receiving portion for receiving a first external force and a second force receiving portion for receiving a second external force, wherein the second force receiving portion is movable relative to the developing frame, wherein the second force receiving portion is placed in a stand-by position retracted from an operating position by the first force receiving portion receiving the first external force, and is movable from the stand-by position to the operating position for moving the developing frame from the contacting position to the spacing position, wherein a distance through which the second force receiving portion moves from the stand-by position to the operating position is larger than a distance through which the first force receiving portion is moved by the first external force.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
8 January 2009 (08.01.2009)

PCT

(10) International Publication Number
WO 2009/005159 A4(51) International Patent Classification:
G03G 21/18 (2006.01)(21) International Application Number:
PCT/JP2008/062243

(22) International Filing Date: 30 June 2008 (30.06.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2007-172742 29 June 2007 (29.06.2007) JP
2008-162311 20 June 2008 (20.06.2008) JP(71) Applicant (for all designated States except US): **CANON KABUSHIKI KAISHA** [JP/JP]; 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TOBA, Shinjiro** [JP/JP]; c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, 146-8501 (JP).
YOSHIMURA, Akira [JP/JP]; c/o CANON KABUSHIKIKAISHA, 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, 146-8501 (JP). **NIITANI, Susumu** [JP/JP]; c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, 146-8501 (JP).(74) Agent: **YAMADA, Ryuichi**; TOKO International Patent Office, Toranomom Sugai Bldg. 2F, 18-16, Toranomom 3-chome, Minato-ku, Tokyo 1050001 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PROCESS CARTRIDGE ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS




FIG. 6

(57) Abstract: A process cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, includes an electrophotographic photosensitive drum; developing roller for developing an electrostatic latent image formed on the electrophotographic photosensitive drum; drum frame supporting the electrophotographic photosensitive drum; a developing frame supporting the developing roller, the developing frame is movable relative to the drum frame and is capable of taking a contacting position in which the developing roller is in contact with the electrophotographic photosensitive drum; and a force receiving device including a first force receiving portion for receiving a first external force and a second force receiving portion for receiving a second external force, wherein the second force receiving portion is movable relative to the developing frame, wherein the second force receiving portion is placed in a stand-by position retracted from an operating position by the first force receiving portion receiving the first external force, and is movable from the stand-by position to the operating position for moving the developing frame from the contacting position to the spacing position, wherein a distance through which the second force receiving portion moves from the stand-by position to the operating position is larger than a distance through which the first force receiving portion is moved by the first external force.

WO 2009/005159 A4



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,
NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Date of publication of the amended claims and statement:

19 March 2009

Published:

- *with international search report*
- *with amended claims and statement*

DESCRIPTION

PROCESS CARTRIDGE

AND

5 ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS

[TECHNICAL FIELD]

The present invention relates to a process cartridge made up of an electrophotographic
10 photosensitive drum and a development roller (which processes photosensitive drum), in particular, a process cartridge, the electrophotographic photosensitive drum and development roller of which can be placed in contact with, or separated from, each
15 other. The present invention also relates to an electrophotographic image forming apparatus employing the above described process cartridge.

[BACKGROUND ART]

20 In recent years, a process cartridge system has come to be widely used in the field of an image forming apparatus which uses an electrophotographic image forming process. A process cartridge system is one of the electrophotographic image forming systems.
25 It uses a cartridge in which an electrophotographic photosensitive drum, and a development roller, that is, a roller for processing an electrophotographic

photosensitive drum, are integrally disposed to make them removably mountable in the main assembly of an image forming apparatus. Thus, the employment of a process cartridge system makes it possible for a user
5 to maintain an electrophotographic image forming apparatus without relying on a service person. This is why a process cartridge system has come to be widely used in the field of an electrophotographic image forming apparatus.

10 A process cartridge is structured so that its development roller is kept pressured toward its electrophotographic photosensitive drum with the application of a preset amount of pressure, in order to keep the development roller in contact with the
15 photosensitive drum when forming an image. In a case of a so-called contact development method, that is, a development method which places a development roller in contact with a photosensitive drum to develop a latent image on the photosensitive drum, the elastic
20 layer of the development roller is kept pressed upon the peripheral surface of the photosensitive drum so that a preset amount of contact pressure is maintained between the peripheral surface of the development roller and that of the photosensitive drum.

25 Therefore, if a process cartridge is left unused in the main assembly of an image forming apparatus for a substantial length of time, the elastic layer of the

development roller sometimes deforms. Thus, if an image forming apparatus in which a process cartridge has been left unused for a substantial length of time is used for the first time thereafter, it is possible
5 that a latent image will be nonuniformly developed. Further, in the case of a so-called contact development method, a development roller is in contact with a photosensitive drum during development. Therefore, developer sometimes transfers from a
10 development roller onto the points of the peripheral surface of a photosensitive drum, to which developer is not supposed to adhere. Further, not only do a photosensitive drum and a development roller rotate in contact with each other during development, but also,
15 during processes other than development. Therefore, a so-called contact development method exacerbates the deterioration of a photosensitive drum, a development roller, and developer.

One of the solutions to the above described
20 problem is proposed in Japanese Laid-open Patent Application 2003-167499. According to this patent application, an image forming apparatus is provided with a mechanism which acts on a process cartridge to keep an electrophotographic photosensitive drum and a
25 development roller separated from each other when an image is not actually being formed (Patent Document 1).

In the case of the image forming apparatus

proposed in Patent Document 1, its main assembly is structured so that four process cartridges are removably mountable in the main assembly. Each cartridge is made up of a photosensitive member unit
5 and a development unit. The photosensitive member unit has a photosensitive member. The development unit supports a development unit, and is connected to the photosensitive member unit so that it can be rotationally moved relative to the photosensitive
10 member unit. Further, the main assembly of the image forming apparatus is provided with a separation plate, whereas the process cartridge is provided with a force receiving portion. As the separation plate is moved, the force receiving portion receives the force from
15 the separation plate, causing the development unit to move relative to the photosensitive member unit. As a result, the development roller, which was in contact with the photosensitive drum, separates from the photosensitive drum.

20 According to the prior art, the force receiving portion, that is, the portion which catches the force for separating a development roller and a photosensitive member from each other, remains projecting beyond the external contour of the
25 development unit. Therefore, it is liable to be damaged while a user handles a process cartridge, or a process cartridge is conveyed alone. Further, the

presence of the above described force receiving
portion has been one of the major problems which arose
when studies were made to reduce in size a process
cartridge structured so that its electrophotographic
5 photosensitive member and development roller can be
placed in contact with, or separated from, each other,
and also, when studies were made to reduce in size the
main assembly of an image forming apparatus in which
such a process cartridge as the one described above is
10 removably mountable.

[DISCLOSURE OF THE INVENTION]

The primary object of the present invention is to
provide a process cartridge, the electrophotographic
15 photosensitive drum and development roller of which
can be placed in contact with, or separated from, each
other, and which is significantly smaller in size than
a counterpart in accordance with the prior art, and
also, to provide an electrophotographic image forming
20 apparatus which is compatible with a process cartridge
in accordance with the present invention, is removably
mountable and is significantly smaller in size than a
counterpart in accordance with the prior art.

Another object of the present invention is to
25 provide a process cartridge, the electrophotographic
photosensitive member and development roller of which
can be placed in contact with, or separated from, each

other, and the development unit moving force receiving
portion of which is significantly less liable to be
damaged while the process cartridge is handled by a
user, or transported alone, than a counterpart in
5 accordance with the prior art.

These and other objects, features, and advantages
of the present invention will become more apparent
upon consideration of the following description of the
10 preferred embodiments of the present invention, taken
in conjunction with the accompanying drawings.

[BRIEF DESCRIPTION OF THE DRAWINGS]

Figure 1 is a schematic sectional view of the
15 electrophotographic image forming apparatus in the
first embodiment of the present invention, showing the
general structure of the apparatus.

Figure 2 is a schematic sectional view of the
process cartridge in the first embodiment of the
20 present invention.

Figure 3 is also a schematic sectional view of
the electrophotographic image forming apparatus in the
first embodiment of the present invention, showing the
general structure of the apparatus.

25 Figure 4 is another schematic sectional view of
the electrophotographic image forming apparatus in the
first embodiment of the present invention, showing how

the process cartridges therein are replaced.

Figure 5 is a schematic sectional view of one of the process cartridges, and its adjacencies, in the electrophotographic image forming apparatus in the first embodiment of the present invention, at a plane perpendicular to the axial line of the photosensitive drum.

Figure 6 is a schematic sectional view of the process cartridge in the first embodiment of the process cartridge, showing the movement of the structural components of the cartridge, which is related to the mounting of the process cartridge into the apparatus main assembly.

Figure 7 is a schematic side view (as seen from the side from which it receives cartridge driving force) of the process cartridge in the first embodiment of the present invention, which is being mounted into the apparatus main assembly, showing the movement the structural components of the cartridge, which is related to the mounting of the process cartridge into the apparatus main assembly.

Figure 8 is also a schematic sectional view (as seen from the side from which it receives cartridge driving force) of the process cartridge in the first embodiment of the present invention, which is being mounted into the apparatus main assembly, showing the movement of the structural components of the cartridge,

which is related to the mounting of the process cartridge into the apparatus main assembly.

Figure 9 is an exploded perspective view of the process cartridge in the first embodiment of the present invention.

Figure 10(a) is a perspective view of the process cartridge in the first embodiment of the present invention, as seen from the side from which the cartridge is driven, and Figure 10(b) is a perspective view of the process cartridge in the first embodiment of the present invention, as seen from the side opposite from the side from which the cartridge is driven.

Figure 11 is a perspective view of the process cartridge in the first embodiment of the present invention, as seen from the side from which the cartridge is driven.

Figure 12 is a schematic drawing of the process cartridge in the second embodiment of the process cartridge, showing the movement of the structural components of the cartridge.

Figure 13 is an exploded perspective view of the process cartridge in the second embodiment of the present invention.

Figure 14 is a schematic drawing of the process cartridge in the third embodiment of the process cartridge, showing the movement of the structural

components of the cartridge, which is related to the mounting of the process cartridge into the apparatus main assembly.

Figure 15 is an exploded perspective view of the process cartridge in the third embodiment of the present invention.

Figure 16 is a schematic drawing of the cartridge tray guiding hole of the electrophotographic image forming apparatus in the first embodiment of the present invention.

Figure 17 is a partially cutaway perspective view of the electrophotographic image forming apparatus in the first embodiment of the present invention.

Figure 18 is a schematic drawing of the pressing member, and the components related to the operation of the pressing member, in the first embodiment of the present invention, showing the movement of the pressing member.

Figure 19 is a schematic drawing of the force applying first member, and the components related to the operation of the force applying first member, in the first embodiment of the present invention, showing the operation of the force applying first member.

Figure 20 is a perspective view of the force receiving apparatus of the process cartridge in the first embodiment of the present invention.

Figure 21 is a schematic drawing of the process

cartridge in the first embodiment of the present invention, the force receiving second member of which has been just been moved by the force applying second member of the cartridge.

5

[BEST MODE FOR CARRYING OUT THE INVENTION]

(Embodiment 1)

Next, referring to Figures 1 - 4, the process cartridges and electrophotographic image forming apparatuses in this preferred embodiment of the present invention will be described.

Figure 1 is a schematic sectional view of the electrophotographic image forming apparatus 100 (which hereafter will be referred to simply as apparatus main assembly), in which multiple (four) process cartridges 50y, 50m, 50c, and 50k (which hereafter may be referred to simply as cartridges 50) which have been removably mounted. The multiple (four) cartridges 50 store yellow, magenta, cyan, and black toners (developers), one for one. Figure 2 is a schematic sectional view of the cartridge itself. Figures 3 and 4 are schematic sectional drawings of the electrophotographic image forming apparatus in this embodiment, which are for showing how the any cartridge or cartridges 50 are removed from the main assembly of the image forming apparatus.

25

{General Structure of Electrophotographic Image

Forming Apparatus}

The electrophotographic image forming apparatus in this embodiment is structured to carry out the following image forming operation. Referring to Figure 5 1, first, the uniformly charged area of the peripheral surface of each of the electrophotographic photosensitive drums (which hereafter will be referred to as photosensitive drums) 30y, 30m, 30c, and 30k is scanned by a beam of laser light 11 projected by a 10 laser scanner 10, with which the apparatus main assembly 100 is provided, while being modulated with pictorial signals. As a result, an electrostatic latent image is effected on the peripheral surface of each photosensitive drum 30. This electrostatic latent 15 image is developed by a development roller 42, into a visible image; an image is formed of toner (developer) on the peripheral surface of the photosensitive drum 30. In other words, yellow, magenta, cyan, and black toner images are formed on the photosensitive drums 20 30y, 30m, 30c, and 30k, respectively. Then, these toner images are sequentially transferred by the voltages applied to transfer rollers 18y, 18m, 18c, and 18k, onto a transfer belt 19 supported and stretched by rollers 20 - 22. Thereafter, the toner 25 images on the transfer belt 19 are transferred by a transfer roller 3, onto a sheet of recording medium P delivered by a recording medium conveyance roller 1 as

a recording medium conveying means. Then, the recording medium P is conveyed to a fixation unit 6 made up of a driver roller, and a fixation roller having an internal heater. In the fixation unit 6, heat and pressure is applied to the recording medium P and the toner images thereon. As a result, the toner images on the recording medium P are fixed to the recording medium P. Then, the recording medium P is discharged onto a delivery tray 9 by a pair of discharge rollers 7.

{General Structure of Process Cartridge}

Next, referring to Figures 1, 2 and 10, the cartridges 50 in this embodiment will be described. The multiple (four) cartridges 50 in this embodiment are the same in structure although they are different in the color of the toner T they store. Thus, the structure of the cartridges 50 will be described with reference to the cartridge 50y.

The cartridge 50y is provided with a photosensitive drum 30, and processing means which process the photosensitive drum 30. The processing means in this embodiment are a charge roller 32 which is the charging means for charging the photosensitive drum 30, a development roller 42 which is the developing means for developing a latent image formed on the photosensitive drum 30, a blade 33 which is the cleaning means for removing the residual toner

remaining on the peripheral surface of the photosensitive drum 30, etc. The cartridge 50y is made up of a drum unit 31 and a development unit 41.

{Structure of Drum Unit}

5 Referring to Figures 2 and 10, the drum unit 31 includes the abovementioned photosensitive drum 30, charge roller 32, and blade 33. It also includes a waste toner storing portion 35, a drum unit main frame 34, and lateral covers 36 and 37 (which hereafter will
10 be referred to simply as cover). Referring to Figure 9, one of the lengthwise end portions of the photosensitive drum 30 is rotatably supported by the supporting portion 36b of the cover 36, whereas the other lengthwise end of the photosensitive drum 30 is
15 rotatably supported by the supporting portion 37b of the cover 37 as shown in Figures 10(a) and 10(b). The covers 36 and 37 are attached to the lengthwise ends of the drum unit main frame 34. Next, referring to Figure 10(b), the lengthwise end portion of the
20 photosensitive drum 30, which is supported by the cover 36, is provided with a coupling member 30a for transmitting driving force to the photosensitive drum 30. The coupling member 30a engages with a first coupling member 105 of the apparatus main assembly 100,
25 shown in Figures 4 and 7, as the cartridge 50y is mounted into the apparatus main assembly 100. Thus, as driving force is transmitted from a motor (unshown)

with which the apparatus main assembly 100 is provided,
to the coupling member 30a, the photosensitive drum 30
rotates in the direction indicated by an arrow mark U
in Figure 2. The charge roller 32 is supported by the
5 drum unit main frame 34 so that it is rotated in
contact with the photosensitive drum 30 by the
rotation of the photosensitive drum 30. The blade 33
is supported also by the drum unit main frame 34 so
that it remains in contact with the peripheral surface
10 of the photosensitive drum 30 with the presence of a
preset amount of pressure between the blade 33 and the
peripheral surface of the photosensitive drum 30. The
covers 36 and 37 are provided with holes 36a (Figure
9) and 37a (Figures 10(b)) for supporting the
15 development unit 40 in such a manner that the
development unit 40 is rotationally movable relative
to the drum unit 31.

{Structure of Development Unit}

Referring to Figures 2 and 9, the development
20 unit 41 has the abovementioned development roller 42.
It also has a development blade 43, a development unit
main frame 48, a bearing unit 45, and a pair of
lateral covers 46. The development unit main frame 48
has a toner storage portion 49 in which the toner to
25 be supplied to the development roller 42 is stored. It
supports the development blade 34 which regulates the
thickness to which toner is coated on the peripheral

surface of the development roller 42. Referring to Figure 9, the bearing unit 45 is firmly attached to one of the lengthwise end portions of the development unit main frame 48. It rotatably supports the development roller 42, one of the lengthwise end portions of which has a development roller gear 69. Further, the bearing unit 45 is provided with an idler gear 68, which transmits driving force from a coupling member 67 to the development roller gear 69. The cover 46 is securely attached to the outward side of the bearing unit 45, in terms of the lengthwise direction of the bearing unit 45, in a manner to cover the coupling member 67 and idler gear 68. Further, the cover 46 is provided with a cylindrical portion 46b, which protrudes outward from the outward surface of the cover 46. The coupling member 67 is exposed through the hollow of the cylindrical portion 46b. The apparatus main assembly 100 and process cartridge 50y are structured so that as the process cartridge 50y is mounted into the apparatus main assembly 100, the coupling member 67 engages with the second coupling 106 of the apparatus main assembly 100, which is shown in Figure 17, transmitting thereby driving force from the motor (unshown) with which the apparatus main assembly 100 is provided, to the process cartridge 50y.

{Connection of Development Unit to Drum Unit}

Referring to Figures 9 - 11, the development unit

41 and drum unit 31 are connected in the following manner: First, at one end of the process cartridge 50y, the cylindrical portion 46b is fitted into the supporting hole 36a. At the other end, a projection 5 48b which projects from the development unit main frame 48 is fitted into the supporting hole 37a. As a result, the development unit 41 is connected to the drum unit 31 in such a manner that the development unit 41 is rotationally movable relative to the drum 10 unit 31. Next, referring to Figure 2, the development unit 41 is kept pressured by a pair of compression springs 95, which are elastic members, in the direction to be rotated about the axial line of the cylindrical portion 46b so that the development roller 15 42 is kept in contact with the photosensitive drum 30. That is, the development unit 41 is kept pressed by the resiliency of the compression springs 95 in the direction indicated by a narrow mark G, generating a moment H which acts in the direction to rotate the 20 development unit 41 about the cylindrical portion 46b and projection 48b. Thus, the development roller 42 is kept in contact with the photosensitive drum 30 with the presence of the preset amount of contact pressure between the development roller 42 and photosensitive 25 drum 30. The position in which the development unit 41 is when it is kept in contact with the photosensitive drum 30 is referred to as "contact position".

Referring to Figure 10(a), the compression spring 95 in this embodiment is located on the opposite side from one of the lengthwise end portions, where the coupling member 30a of the photosensitive drum 30, and
5 the coupling member 67 which transmits driving force to the development roller gear 69, are located.
{Force Receiving Apparatus}

Referring to Figure 2, the cartridge 50y is provided with a force receiving apparatus 90 for
10 placing the development roller 42 and photosensitive drum 30 in contact with each other, or separating them from each other, in the apparatus main assembly 100.

Referring to Figures 6 and 8, which are schematic side views of the cartridge 50y, the cover 36 of which
15 has been removed, as seen from the side from which the cartridge 50y is driven, the force receiving apparatus 90 is made up of a force receiving first member 71 and a force receiving second member 70. Until the cartridge 50y begins to be positioned relative to the
20 apparatus main assembly 100 in a preset manner, the force receiving second member 70 remains in its standby position, that is, the position in which the force receiving second member 70 does not project beyond the external contour of the cartridge 50y, as
25 shown in Figure 10(a). As the cartridge 50y is advanced into the apparatus main assembly 100 in the direction indicated by an arrow mark Z2 (shown in

Figure 1) by a cartridge tray 13 (which will be described later), the cartridge 50y is positioned in the apparatus main assembly 100 by a cartridge positioning portion 101a of the apparatus main assembly 100. As the cartridge 50y is pressed against the cartridge positioning portion 101a, the force receiving first member 71 is pressed upward by a projection 180 (force receiving first member pressing member) of the apparatus main assembly 100, which will be described later. That is, the force receiving first member 71 receives a first external force from the projection 180. As a result, the force receiving portion 70 is moved out of its standby position, projecting outward of the cartridge 50y beyond the external contour of the cartridge 50y, as shown in Figure 11.

Next, referring to Figures 6, 7, and 9, while the cartridge 50y is kept in its accurate positioned (image forming position) in the apparatus main assembly 100 by the positioning portion 101a, the force receiving first member 71 is below the force receiving second member 70. The force receiving first and second members 71 and 70 are in connection with each other. More specifically, the force receiving second member 70 is rotatably supported by its rotational axle 70b, and is provided with an elongated hole 70a. The top end portion (in drawings) of the

force receiving first portion 71 is provided with a projection (connective pin), which is fitted in the elongated hole of the force receiving second member 70. Thus, as force is applied to the force receiving second member 70 by the force receiving first member 71, more specifically, the projection (connective pin) of the force receiving first member, which is in the elongated hole 70a of the force receiving second member 70, the force receiving first member 70 is rotationally moved about its rotational axle 70b.

Referring to Figure 7, since the elongated hole 70a is located between the rotational axle 70b and the force catching surface 70c, a distance h_2 by which the force receiving second member 70 moves can be made greater than a distance h_1 (Figure 7) by which the force receiving first member 71 moves, by properly setting the leverage ratio of the force receiving second member 70. Here, the distances by which the force receiving first and second members 71 and 70 move are the distances measured in terms of the vertical direction, that is, the direction parallel to the direction in which the force receiving member 71 is moved toward the force applying member 60 (which will be described later). That is, with the employment of the above described structural arrangement, the distance h_2 by which the force receiving second member 70 moves can be increased without increasing the

projection 180 in the distance by which it projects,
making it thereby possible to reduce in size the
apparatus main assembly 100 shown in Figure 1.

Incidentally, the force receiving apparatus is movably
5 supported by the cover 46.

{Cartridge Tray of Electrophotographic Image Forming
Apparatus Main Assembly}

Next, the cartridge tray 13, which is in the form
of a drawer, will be described.

10 Referring to Figure 4, the cartridge tray 13 is
attached to the apparatus main assembly 100 in such a
manner that, in practical terms, it can be
horizontally and linearly moved relative to the
apparatus main assembly 100. That is, the cartridge
15 tray 13 can be pushed into, or pulled out of, the
apparatus main assembly 100 in the direction indicated
by an arrow mark Z2 or Z1, respectively. The apparatus
main assembly 100 is structured so that the cartridge
tray 13 can be locked in the innermost position (image
20 forming position, shown in Figure 1, in the apparatus
main assembly 100), and the outermost position
(cartridge replacement position: cartridge mounting or
removing position), shown in Figure 4, which is the
farthest position to which the cartridge tray 13 can
25 be pulled out). The cartridge 50 is mounted into the
cartridge tray 13 by an operator in the direction
indicated by an arrow mark C, which is virtually

parallel to the direction of gravity, as shown in Figure 4. The cartridge tray 13 is structured so that as the cartridges 50 are mounted into the cartridge tray 13, the cartridges 50 become arranged in tandem, in the direction parallel to the direction in which the cartridge tray 13 is movable, with their lengthwise direction (which is parallel to axial lines of photosensitive drum 30 and development roller 42) being perpendicular to the moving direction of the cartridge tray 13. As the cartridge tray 13 is pushed into the apparatus main assembly 100, the cartridges 50 in the cartridge tray 13 enter the apparatus main assembly 100, with the presence of a preset amount of gap f2 (Figure 5) between the photosensitive drum 30 in each cartridge 50, and an intermediary transfer belt 19 located below the cartridge path. Then, as the cartridge tray 13 is moved into its innermost position in the apparatus main assembly 100, each cartridge 50 is positioned in the apparatus main assembly 100 by the cartridge positioning portion 101a provided in the apparatus main assembly 100 (Figures 5 and 7). The cartridge positioning operation will be described later in detail. A user is to close a door 12 after pushing the cartridge tray 13 all the way into the apparatus main assembly 100. Closing the door 12 ensures that each cartridge 50 is properly mounted into the apparatus main assembly 100. Therefore, in

terms of operability, this structural arrangement for the apparatus main assembly 100 and cartridges 50 is superior to the structural arrangement of an electrophotographic image forming apparatus in accordance with the prior art, which requires the cartridges 50 to be individually mounted into the apparatus main assembly 100 by a user.

Next, referring to Figures 1, 3, 4, and 17, the operation of the cartridge tray 13 will be described. Figure 17 does not show the cartridges 50, in order to make it easier to understand the operation of the cartridge tray 13.

The cartridge tray 13 is supported by a pair of tray supporting members 14 in such a manner that the cartridge tray 13 can be pulled out of the apparatus main assembly 100 while remaining supported by the tray supporting members 14. The tray supporting members 14 are moved by the movement of the door 12, which can be opened or closed by an operator (user). The door 12 is attached to the apparatus main assembly 100 so that it can be rotationally moved about its rotational axis 12a. The door 12 is rotationally movable between a position (shut position) in which it completely covers an opening 80, as shown in Figure 1, and a position (open position) in which it fully exposes the opening 80 as shown in Figure 3.

When it is necessary to take out any cartridge or

cartridge 50 in the apparatus main assembly 100, the door 12 is to be rotationally moved from the shut position to the open position. As the door 12 is rotationally moved, a pair of projections 15

5 (connective pins) with which the door 12 is provided moves in the clockwise direction about the rotational axis 12a, while moving in a pair of elongated holes 14c, one for one, with which the tray supporting member 14 is provided, from the bottom end of the

10 elongated hole 14c toward the top end of the elongated hole 14c, as shown in Figure 3. As a result, the tray supporting members 14 are moved by the projections 15 in the direction indicated by the arrow mark Z1. As the tray supporting members 14 are moved in the

15 abovementioned direction, the projections 14d1 and 14d2, which project from each of the tray supporting members 14 are guided by the guiding holes 107 with which the apparatus main assembly 100 is provided, as shown in Figure 4. Referring to Figure 16, each

20 guiding hole 107 has three sections, that is, two horizontal sections 107a1 and 107a3, and one diagonal section 107a2. The diagonal section 107a2 extends diagonally upward from the horizontal section 107a1 to the horizontal section 107a3. Therefore, as the door 12

25 is moved from the shut position, shown in Figure 1, to the open position, shown in Figure 3, the projections 14d 1 and 14d 2 are guided by the guiding hole 107,

sequentially through the horizontal portion 107a1,
diagonal portion 107a2, and horizontal portion 107a3.
Thus, the tray supporting members 14 are first moved
in the direction indicated by the arrow mark Z1, and
5 then, are moved in the direction indicated by an arrow
mark Y1, that is, direction to move away from the
transfer belt 19. With the tray supporting members 14
moved all the way in the direction indicated by the
arrow mark Y1, the cartridge tray 13 can be pulled out
10 of the apparatus main assembly 100 through the opening
80 in the direction indicated by the arrow mark Z1, as
shown in Figure 4. Figure 17 is a partially cutaway
perspective view of the image forming apparatus after
the cartridge tray 13 has been pulled out of the
15 apparatus main assembly 100 to its outermost position.

Next, the case in which any cartridge or
cartridges 50 are mounted into the apparatus main
assembly 100 will be described. Referring to Figure 4,
the cartridge tray 13 is to be pushed into the
20 apparatus main assembly 100 in the direction of the
arrow mark Z2 through the opening 80, with the door 12
kept in the open position. Thereafter, the door 12 is
to be moved into the shut position as shown in Figure
2. As the door 12 is moved, each of the projection 15
25 of the door 12 moves in the counterclockwise direction
about the rotational axis 12a, while moving in the
corresponding elongated hole 14c of the tray

supporting member 14, toward the bottom end 14c2 of
the elongated hole 14c, as shown in Figure 1. Thus,
the tray supporting member 14 is moved in the
direction of the arrow mark Z2 by the pair of
5 projections 15. Therefore, as the door 12 is moved
into the shut position as shown in Figure 1, the
projections 14d1 and 14d2 (Figure 4) are guided by the
horizontal portion 107a1, diagonal portion 107a2, and
horizontal portion 107a3, in the listed order, as
10 shown in Figure 16. Therefore, the tray supporting
members 14 move, first, in the direction of the arrow
mark Z2, and then, in the direction of the arrow mark
Y2, that is, the direction to move closer to the
transfer belt 19, as shown in Figure 1.

15 {Positioning of Process Cartridge Relative to
Electrophotographic Image Forming Apparatus Main
Assembly}

Next, referring to Figures 5, 17, and the
positioning of the cartridge 50 in the apparatus main
20 assembly 100 will be described. Referring to Figure 17,
the apparatus main assembly 100 is provided with
multiple pairs (four pairs in this embodiment) of
cartridge positioning portions 101a for positioning a
cartridge 50 relative to the apparatus main assembly
25 100. That is, each cartridge compartment of the
cartridge tray 13 is provided with a pair of cartridge
positioning portions 101a, which are located at the

lengthwise ends of the corresponding compartment, one for one, in terms of the direction parallel to the lengthwise direction of the cartridge 50, in a manner to sandwich the transfer belt 19. Referring to Figures 5 18(a) and 18(b), there are pressing members 61 (61y, 61m, 61c, and 61k) above each of the tray supporting members 14. Each pressing member 61 is provided with a hole 61d, through which a pressing member supporting shaft 55, with which the apparatus main assembly 100 10 is provided, is put to rotatably support the pressing member 61.

Referring again to Figures 18(a) and 18(b), as the door 12 is moved from the open position to the shut position (in X direction), the pressing member 61 15 is moved in the direction indicated by an arrow mark Z, pressing thereby on the top surface of the drum unit main frame 34 as shown in Figure 20. Therefore, the cartridge 50y is pressed in the direction indicated by an arrow mark P in Figure 7, causing the cartridge 20 positioning portion 31b, with which the drum unit 31y is provided, to come into contact with the cartridge positioning portion 101a of the apparatus main assembly 100. As a result, the cartridge 50y is properly positioned in the apparatus main assembly 100. 25 Similarly, the cartridges 50m, 50c, and 50k are properly positioned in the apparatus main assembly 100.

Further, as the cartridge 50 is made to descend

toward the positioning portion 101a by the movement of the door 12, the projection 180 of the apparatus main assembly 100 comes into contact with the force receiving portion 71c of the force receiving first member 71, which is in the bottom portion of the cartridge 50. That is, the force receiving member 71 receives force from the projection 180, from the bottom side of the cartridge 50. In comparison, when the door 12 is moved from the shut position to the open position (Y direction), the pressing member 61 moves in the direction indicated by an arrow mark J. As a result, the pressing member 61 separates from the top surface of the drum unit main frame 34 as shown in Figure 5.

{Development Roller Separating Mechanism of Electrophotographic Image Forming Apparatus Main Assembly}

Next, the operation of the force applying first portion 60 will be described.

Referring to Figures 1, 3 and 19, in terms of the vertical direction of the apparatus main assembly 100, the force applying member 60 is positioned so that after the proper positioning of the cartridge 50, the force applying member 60 is above the cartridge 50. In terms of the axial line of the photosensitive drum 30, the force applying member 60 is positioned so that it is enabled to come into contact with the force

receiving second member 70 which is at the
corresponding lengthwise ends of the cartridge 50.

Driving force is transmitted from a motor 110
(mechanical power source) with which the apparatus
5 main assembly 100 is provided, to a gear 112 through a
gear 111. As the driving force is transmitted to the
gear 112, the gear 112 rotates in the direction
indicated by an arrow mark L, rotating thereby the cam
portion 112a, which is integral with the gear 112, in
10 the arrow L direction. The cam portion 112a is in
contact with the moving force receiving portion 60b,
with which the force applying member 60 is provided.
Therefore, as the cam portion 112a rotates, the moving
force receiving member 60 is moved in the direction
15 indicated by an arrow mark E or B.

Referring to Figure 19(a), as the force applying
member 60 moves in the direction indicated by the
arrow mark E, a rib 60y of the force applying member
60 separates from the force receiving second member 70,
20 as shown in Figure 7, allowing thereby the development
roller 42 to come into contact with the photosensitive
drum 30. This position of the development unit 41,
which allows the development roller 42 to remain in
contact with the photosensitive drum 30, will be
25 referred to as the contact position.

Referring to Figure 19(b), as the force applying
member 60 is moved in the direction indicated by the

arrow mark B, the rib 60y comes into contact with the force receiving second member 70, subjecting the force receiving second member 70 to external force (second external force) through the rib 60y. Therefore, the development unit 41 is rotated (rotationally moved) about the cylindrical portion 46b (rotational axle), separating thereby the development roller 42 from the photosensitive drum 30. This position of the development unit 41, which keeps the development roller 42 separated from the photosensitive drum 30, will be referred to as the separation position.

Similarly, the force applying member 60 is positioned above the path of the cartridge 50, through which the cartridge 50 is moved into the apparatus main assembly 100 by the cartridge tray 13. The force receiving second member 70 is attached to the cartridge 50 in such a manner that until the cartridge 50 is moved into the apparatus main assembly 100, the force receiving second member 70 remains in its standby position (Figure 5). Therefore, the force applying member 60 can be positioned significantly closer to the cartridge path, without allowing the force applying member 60 and cartridge 50 to interfere with each other during the mounting of the cartridge 50, compared to the force applying member of an image forming apparatus in accordance with the prior art, making it possible to minimize wasted space, making it

thereby possible to significantly reduce the cartridge 50y in terms of its dimension in terms of its lengthwise direction (axial direction of photosensitive drum 30) as well as the vertical direction of the apparatus main assembly 100. The detailed description of the force applying member 60 will be given later.

{Description of Mounting of Process Cartridge into Electrophotographic Image Forming Apparatus Main Assembly, and Operation of Force Receiving Apparatus}

Next, the operational sequence from the beginning of the mounting of the cartridge 50 into the apparatus main assembly 100, to the separation of the development roller 42 from the photosensitive drum 30, will be described.

Referring to Figure 4, after the cartridge tray 13 is pulled out of the apparatus main assembly 100 to its outermost position, each cartridge 50 can be mounted into, or removed from, the cartridge tray 13 in the vertical direction, which is indicated by the arrow mark C.

After the mounting of the cartridge(s) 50 into the cartridge tray 13, the cartridge tray 13 is to be moved into the apparatus main assembly 100 in the direction indicated by the arrow Z2, through the opening 80. That is, in this embodiment, each cartridge 50 is horizontally moved into the apparatus

main assembly 100, from the direction which is intersectional (roughly perpendicular) to the axial line of the photosensitive drum 30.

Referring to Figure 3, the cartridge 50y is mounted in the downstream end of the cartridge tray 13 in terms of the direction in which the cartridge tray 13 is moved into the apparatus main assembly 100. That is, the cartridge 50y moves below the ribs 60k 60c, and 60m of the force applying member 60 from upstream to downstream.

If the apparatus main assembly 100 and cartridge 50y are structured so that the force receiving second member 70 remains projecting when the cartridge 50y is moved into the apparatus main assembly 100, the pressing member 61 and force applying member 60 must be positioned significantly higher than they are positioned in this embodiment. In this embodiment, however, the apparatus main assembly 100 and cartridge 50y are structured so that the force receiving second member 70 remains in the above described standby position when the cartridge 50y is moved into the apparatus main assembly 100. Therefore, the pressing member 61 and force applying member 60 can be positioned as closely as possible, without taking into consideration the distance by which the force receiving second member 70 projects beyond the external contour of the cartridge 50y. In other words,

the pressing member 61 and force applying member 60 can be positioned significantly closer to the path of the cartridge 50y, making it possible to reduce the cartridge 50y in dimension in terms of the direction parallel to the vertical direction of the apparatus main assembly 100, compared to the counterparts of a process cartridge in accordance with the prior art. Further, referring to Figure 20, in terms of the direction parallel to the axial line of the drum 30, the force receiving apparatus 90, pressing member 61, and force applying member 60 overlap, making it possible to reduce thereby the cartridge 50y in dimension in terms of the lengthwise direction of the cartridge 50y.

Next, referring to Figure 5, the image forming apparatus in this embodiment is structured to ensure that when the cartridge tray 13 is moved into the apparatus main assembly 100, there remain a gap f1 between the force applying member 60 and force receiving second member 70, and a gap f2 between photosensitive drum 30 and transfer belt 19. Therefore, the cartridge 50 and apparatus main assembly 100 do not interfere with each other when the cartridge 50 is moved into the apparatus main assembly 100.

After the cartridge tray 13 is pushed all the way into the apparatus main assembly 100, the door 12 is to be moved into the shut position as shown in Figures

1 and 18(b). As the door 12 is moved into the shut position, the tray supporting members 14 are moved toward the transfer belt 19 (direction indicated by arrow mark Y2). Hereafter, the vertical component of this movement of the tray supporting members 14 in the direction indicated by the arrow mark Y2 will be referred to as a distance f2. As the tray supporting members 14 are moved in the direction indicated by the arrow mark Y2, the cartridges 50 are moved toward the transfer belt 19 by the movement of the tray supporting members 14, causing thereby the peripheral surface of the photosensitive drum 30 in each cartridge 50 to come into contact with the surface of the transfer belt 19. By the time the peripheral surface of the photosensitive drum 30 comes into contact with the surface of the transfer belt 19, the gap f1 between the force receiving apparatus 90 and force applying member 60 widens to the sum of the gaps f1 and f2, as shown in Figure 5.

Further, as the door 12 is moved into the shut position, the pressing member 61 is moved by the movement of the door 12, pressing thereby on the top surface of the drum unit main frame 34. Therefore, the cartridge positioning portion 31b of each cartridge 50 is placed in contact with the cartridge positioning portion 101a of the apparatus main assembly 100. Consequently, each cartridge 50 is properly positioned

relative to the apparatus main assembly 100, as shown in Figure 7.

Further, a shaft 36d, shown in Figure 10, with which the cover 36 of each cartridge 50 is provided, engages with the cartridge rotation stopping portion 13a (Figure 17), with which the cartridge tray 13 is provided. Therefore, the cartridge 50 is prevented from moving further in the direction indicated by an arrow mark a in Figure 1, in the apparatus main assembly 100.

Next, referring to Figure 6, the home position of the force applying member 60 in this embodiment is made to be where the force applying member 60 keeps the development roller 42 separated from the photosensitive drum 30. This is for the following reason. That is, while the image forming apparatus is not used for image formation after the mounting of the cartridges 50, each cartridge 50 remains in the state shown in Figure 8. That is, the force applying member 60 has moved in the direction indicated by the arrow mark B, and the force receiving second member 70 has been moved by the rib 60y as far as it can be moved. While the cartridge 50 is in this state, the photosensitive drum 30 and development roller 42 remain separated from each other. It is in this state, shown in Figure 8, in which the photosensitive drum 30 and development roller 42 remain separated from each

other, that the cartridge 50 is removed from the apparatus main assembly 100. Thus, when the cartridge 50 is mounted into the apparatus main assembly 100 next time, the force applying member 60 is in the position shown in Figure 8. Therefore, as the cartridge 50 is mounted, the force receiving second member 70 comes into contact with the rib 60y, because the force receiving second member 70 is out of its standby position, as shown in Figure 6. Thus, the force receiving first portion 71 is provided with an elastic portion 71b, which is formed as an integral part of the force receiving first portion 71, as shown in Figure 6. Therefore, as the contact between the force receiving second member 70 and rib 60y begins to interfere with the inward movement of the cartridge 50, the elastic portion 71b gives in (is compressed), preventing thereby the force receiving apparatus 90 from being damaged.

As the force applying member 60, which is in the state shown in Figure 6, is moved in the direction indicated by an arrow mark E as shown in Figure 7, the force receiving second member 70 projects outward farther from the cartridge 50y, entering thereby the path of the rib 60y. This position of the force receiving second member 70, that is, the position in which the force receiving second member 70 is in the path of the rib 60y, will be referred to as the

outermost position (active position). That is, when the force receiving second member 70 is in its outermost position, the distance of the projection of the force receiving second member 70 is greater than that when the force receiving second member 70 is in the abovementioned standby position, which is obvious. In order for the force receiving second member 70 to engage with the force applying member 60, the distance of the projection of the force receiving second member 70 at the outermost position must be greater than the sum of the gaps f_1 and f_2 . Further, the action of the force applying member 60 is triggered in a period between the completion of the mounting of the cartridges 50 into the apparatus main assembly 100 and the starting of an image forming operation.

Next, referring to Figure 8, as the force applying member 60 is moved in the direction indicated by the arrow mark B, the lateral surface 70c, which is the force receiving second portion of the force receiving second portion 70, receives external force (second external force) through the rib 60y3, since the force receiving second member 70 (lateral surface 70c) is in the path of the force applying member 60. Therefore, the development unit 41 is rotationally moved about its rotational axis 46b (shaft), causing thereby the development roller 42 to separate by a gap α from the photosensitive drum 30. It is in its

outermost position that the force receiving second member 70 receives the external force (second external force) from the force applying member 60. Therefore, this structural arrangement is greater in the distance
5 between the force applying member 60 and the rotational axis 46b of the development unit 41 than a structural arrangement which moves the force applying member toward the process cartridge to separate the development roller from the photosensitive drum.
10 Therefore, the employment of this structural arrangement makes it possible to reduce the amount of torque necessary to separate the development roller 42 from the photosensitive drum 30.

In this embodiment, the elastic portion 71b is an
15 integral part of the force receiving first member 71. However, as long as it is enabled to absorb the force applied to the force receiving first member 70 by the abovementioned change in the position of the cartridge 50, it may be formed as a part of another component,
20 or as an independent component. For example, the force applied to the force receiving first member 71 by the change in the position of the cartridge 50 may be absorbed by placing an absorbing member independent from the force receiving second and first members 70
25 and 71, between the force receiving second and first members 70 and 71, or by forming the force receiving second member of an elastic material so that the above

described force can be absorbed by the deformation of the force receiving second member 71 itself.

Before the starting of an image forming operation, the force applying member 60 is moved in the direction indicated by the arrow mark E to place the development roller 42 in contact with the photosensitive drum 30. As the force applying member 60 is moved in the abovementioned direction, the force receiving second member 70 stops receiving force from the rib 60y, as shown in Figure 7. Therefore, the development roller 42 is placed in contact with the photosensitive drum 30 by the resiliency of the compression springs 95 provided between the development unit 41 and drum unit 31, readying thereby the process cartridge 50 for image formation. It is before the development roller 42 comes into contact with the photosensitive drum 30 that the photosensitive drum 30 begins to be rotated, and the development roller 42 begins to be rotated, by the driving force which the cartridge 50 receives from the apparatus main assembly 100 through the coupling portion 67. This is for the following reason. That is, referring to Figure 10(a), the coupling portion 67 is made coaxial with the cylindrical portion 46b so that even when the development unit 41 moves about the cylindrical portion 46b, the coupling portion 67 does not change in position. That is, in this embodiment, it is before the development roller 42 is placed in

contact with the photosensitive drum 30 that the development roller 42 and photosensitive drum 30 begin to be rotated. This arrangement makes it possible to minimize the difference in peripheral velocity between the photosensitive drum 30 and development roller 42 when the development roller 42 comes into contact with the photosensitive drum 30. Therefore, it can minimize the amount of the wear that occurs to the photosensitive drum 30 and development roller 42 when the two come into contact with each other. After the completion of the image forming operation, the development roller 42 is separated from the photosensitive drum 30 by moving the force applying member 60 in the direction indicated by the arrow mark B as described above. It is after the separation of the development roller 42 from the photosensitive drum 30 that the development roller 42 and photosensitive drum 30 are stopped. Thus, this arrangement minimizes the difference in the peripheral velocity between the development roller 42 and photosensitive drum 30, which occurs when the two become separated. Therefore, it minimizes the amount by which the development roller 42 and photosensitive drum 30 wear when they are separated from each other. Consequently, this arrangement improves an image forming apparatus in image quality.

Next, the operation for removing the cartridge 50

from the apparatus main assembly 100 will be described.

First, the door 12 is to be moved from its shut position to the open position. As the door 12 is moved, the tray supporting members 14 are raised in the
5 direction to separate from the transfer belt 19 as shown in Figures 3 and 4. Therefore, the cartridges 50 are moved upward, causing the photosensitive drum 30 in each cartridge 50 to separate from the transfer belt 19. Further, the pressing member 61 is rotated in
10 the direction indicated by the arrow mark J in Figure 5, being separated from the drum unit 31, as described above. Thus, the force receiving first member 71 separates from the projection 180, being thereby deprived of the force to keep the force receiving
15 second member 70 projecting beyond the external contour of the development unit 41.

As for the force receiving second member 70, its slant surface 70y2 comes into contact with the slant surface 60y2 of the force applying 60, as shown in
20 Figure 21. Thus, the force receiving second member 70 is rotationally moved about its rotational axis 70a, back into its standby position (inaction position), by the component of the force to which the slant surface 70y2 is subjected as the cartridge 50 (cartridge tray
25 13) is pulled out. Incidentally, a spring may be employed, as in another embodiment of the present invention, as the means for generating the force for

returning the force receiving second member into its standby position. That is, the first embodiment, in which the abovementioned spring is not employed, was presented as the embodiment which is smallest in the components count.

As described above, in this embodiment, the apparatus main assembly 100 and cartridge 50 are structured so that as the door 12 is moved into its shut position after the cartridge 50 is mounted into the apparatus main assembly 100, the force receiving second member 70 for moving the development unit 41 projects beyond the outward surface of the development unit 41. Therefore, the cartridge 50 in this embodiment is significantly smaller in height than a cartridge (50) in accordance with the prior art.

Further, the force receiving second member 70 remains in its standby position while the cartridge 50 is mounted. Therefore, the space necessary, in the apparatus main assembly 100 in this embodiment, for the movement of the cartridge(s) 50 does not need to be as large as that in the main assembly of an image forming apparatus in accordance with the prior art. That is, the present invention makes it possible to reduce the opening 80 in size, and also, makes it possible to place the force applying member 60 significantly closer to the path of the cartridge 50 than the prior art, making it thereby possible to

reduce the apparatus main assembly 100 in vertical dimension. Further, the force receiving apparatus 90, pressing member 61, and force applying member 60 are positioned so that they overlap in terms of the
5 direction parallel to the axial line of the drum, as shown in Figure 20, making it possible to reduce the cartridge in its lengthwise dimension.

Further, when the cartridge 50 is handled by a user, or is transported alone, the force receiving
10 second member 70 remains in its standby position, being therefore unlikely to be damaged.

In this embodiment, the apparatus main assembly 100 is structured so that its projection 180 is below the path of the cartridge 50. However, as long as the
15 projection 180 comes into contact with the force receiving first member 71 while the cartridge 50 is mounted into the apparatus main assembly 100, it does not matter where the projection 180 is positioned. Moreover, the shape of the projection 180 is optional,
20 as long as the projection 180 is enabled to move the force receiving portion 71c by coming into contact with the force receiving portion 71c. In other words, the force receiving portion 71c may be a stationary projection which projects from the cover 46. However,
25 if the force receiving portion 71c is made stationary, the force receiving portion 71c must be adjusted in height to prevent the force receiving portion 71c from

coming into contact with the apparatus main assembly 100 while the cartridge 50y is mounted into the apparatus main assembly 100.

(Embodiment 2)

5 Next, referring to Figures 12 and 13, another preferred embodiment of the present invention will be described. In this embodiment, the cartridge 50 is provided with a first lever 471, a second lever 470, and a gear 472. The first lever 471 has a force
10 receiving first portion 471c. The second lever 470 has a force receiving second portion 470c, and meshes with the gear 472. This structural arrangement can move the second lever by a greater distance than the distance by which the first lever is moved.

15 The gear 472 is a step gear made up of a portion (first portion) which engages with the first lever 471 and is $n1$ in tooth count, and a portion (second portion) which engages with the second lever 470 and is $n2$ in tooth count. Thus, it is possible to amplify
20 the distance by which the first level 471 is moved by making the tooth count $n2$ of the second portion of the gear 472 greater than the tooth count $n1$ of the first portion of the gear 472 ($n2 > n1$). To concretely described the operation of the force receiving
25 apparatus in this embodiment, referring to Figure 12(a), while the cartridge 50 is inserted into the apparatus main assembly 100, the second lever 470

remains within the cartridge 50. Then, when the cartridge 50 is properly positioned relative to the apparatus main assembly 100 by the cartridge positioning portion 101a, the force receiving first portion 471c begins to receive external force (first external force) from the projection 180, being thereby moved upward as indicated by an arrow mark F2. As the force receiving first portion 471c moves upward as indicated by the arrow mark F2, the gear 472 is rotated, and this rotation of the gear 472 causes the second lever 470 to move upward. Thus, immediately after the cartridge 50 is properly positioned by the cartridge positioning portion 101a, the second lever 470 is in its outermost position as shown in Figure 12(b). When the second lever 470 is in its outermost position, the force receiving portion 470c of the lever 470 receives the external force (second external force) from the rib 60y3 in the same manner as the force receiving second portion 70c of the force receiving second member 70 receives external force from the rib 60y3 in the first embodiment.

Further, in this structural arrangement, a coil spring 473 is provided to ensure that the second lever 470 always returns to its standby position. The reason therefor is as follows: It is assumed that from the standpoint of apparatus design, it is difficult to ensure that the component of the force which the slant

surface 60y1 receives is large enough to return the force receiving portion 470c to its original position (for example, if the amount of the force necessary to pull cartridges (cartridge tray) increases). In other words, the provision of the coil spring 473 is not
5 mandatory, as it is not in the first embodiment.

This embodiment, however, will be described with reference to a case where the coil spring 473 is provided. In this case, unless the resiliency of the coil spring 473 is smaller than the resilience of the
10 elastic portion 471b which is an integral part of the lever 471, the force receiving first member 470 is not allowed to move. Therefore, all that is necessary is to set the relationship between a force F1 which is generated by the coil spring 473, and a force F2 which
15 is generated by the elastic member 471b, to be $F1 < F2$.

In this embodiment, the cartridge 450 is designed to be assembled in the following manner: First, the gear 472 is rotatably supported by the cover 446 which
20 is firmly attached to the bearing unit 445, and then, the second lever 470 and first lever 471 are attached so that the two levers mesh with the corresponding portions of the gear 472. The shape of the apparatus main assembly in this embodiment is the same as that
25 of the apparatus main assembly in the first embodiment. Therefore, the force receiving portion which is necessary to place the development roller in contact

with the photosensitive drum, or separating the development roller from the photosensitive drum, is the tip 470c of the second lever 470. Otherwise, this embodiment is the same as the first embodiment.

5 As described above, the force receiving apparatus in this embodiment is the same in effectiveness as that in the first embodiment. In this embodiment, however, the distance by which the second lever is moved can be easily changed by changing the gear ratio
10 between the first and second portions of the gear 472.

Also in this embodiment, when the cartridge tray is pulled out, the force receiving member 470 comes into contact with the slant surface 60y2. Then, as the cartridge tray is pulled out further, the force
15 receiving second member 470 is pushed back into the development unit, and stored therein, by being moved in the direction indicated by an arrow mark F2 by the slanted surface 60y2. Therefore, the provision of the return spring 473 is not mandatory.

20 (Embodiment 3)

Next, referring to Figures 14 and 15, the third embodiment of the present invention will be described with reference to a case where the force receiving first member belongs to a drum unit 531. First, the
25 method for assembling the cartridge in this embodiment will be described. The cartridge in this embodiment is designed so that a force receiving first member 571

belongs to a drum unit 531. A force receiving second member 570 and a connective rod 574 are attached to a cover 546. Then, the cover 536 is joined with a bearing member 545. Lastly, the development unit 541
5 and drum unit 531 are connected by the cover 536 to complete the cartridge 550.

To describe in more detail the cartridge 550 in this embodiment with reference to Figures 14 and 15, first, referring to Figure 14, a projection 5180 of
10 the apparatus main assembly is located so that it opposes the drum unit. Thus, the force receiving first member 571 is placed in the drum unit 531.

The drum unit is provided with the force receiving first member 571, which has a force
15 receiving first portion 571c and is movable. Further, the drum unit is provided with a rod 571 and a connective rod 574. The connective rod 574 is rotationally movable about the rotational axis 574a while remaining in contact with the rod 571. The
20 development unit is provided with a force receiving second member 570, which has an elongated hole 570b and is rotationally movable about a rotational axis 570a. Further, the opposite lengthwise end of the connective rod 574 from the rod 571 is provided with a
25 projection (connective pin) which fits in the elongated hole of the force receiving second member 570.

When the cartridge 550 is properly positioned relative to the apparatus main assembly 101 by the cartridge positioning portion 101a, the force receiving first portion 571c begins to receive
5 external force (first external force) from the projection 5180. Therefore, the force receiving first member 571 begins to be moved in the direction indicated by an arrow mark I as shown in Figure 14(b), causing the connective rod 574 to rotationally move in
10 the direction (clockwise direction) indicated by an arrow mark m. Thus, the force receiving second member 570 is rotationally moved about the rotational axis 570a in the direction to move the opposite end portion of the 570 from the elongated hole 570b, arcuately
15 upward, as indicated by an arrow mark n. Since the curvature of the elongated hole 570b is such that while the development roller is not in contact with the photosensitive drum, the center of the curvature of the elongated hole 570b coincides with the
20 rotational axis of the development unit 541. Therefore, while the development unit 541 is separated from the drum unit 531, the connective rod 574 is subjected to no load. Also in this embodiment, a return spring (573) is provided. However, the return spring 573 may
25 be eliminated by a design change.

Also in this embodiment, the distance by which the force receiving second member is moved can be made

greater than the distance by which the force receiving first member is moved, by properly selecting the leverage ratio of the connective rod.

Further, in this embodiment, when the cartridge tray is pulled out, the force receiving member 570 comes into contact with the slant surface 60y2 as does the force receiving first member 70 in the first embodiment. Then, as the cartridge tray is pulled out further, the force receiving second member 570 is pushed back into the development unit 541 to be stored therein, by being moved in the direction opposite from the direction indicated by the arrow mark n. Therefore, the provision of the return spring 573 is not mandatory.

15

[INDUSTRIAL APPLICABILITY]

According to the present invention, it is possible to reduce in size a process cartridge, the electrophotographic photosensitive drum and development roller of which can be placed in contact with, or separated from, each other. It is also possible to reduce in size an electrophotographic image forming apparatus which employs the abovementioned process cartridge. Further, it is possible to structure an electrophotographic image forming apparatus so that its force receiving apparatus for separating the development roller from

25

the electrophotographic photosensitive drum is unlikely to be damaged while the abovementioned process is handled by a user, or is transported alone.

While the invention has been described with
5 reference to the structures disclosed herein, it is not confined to the details set forth, and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

AMENDED CLAIMS**received by the International Bureau on 27 January 2009 (27.01.2009)**

1. A process cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, comprising:
- an electrophotographic photosensitive drum;
 - a developing roller for developing an electrostatic latent image formed on said electrophotographic photosensitive drum;
 - 10 a drum frame supporting said electrophotographic photosensitive drum;
 - a developing frame supporting said developing roller, said developing frame is movable relative to said drum frame and is capable of taking a contacting position in which said developing roller is in contact with said electrophotographic photosensitive drum and a spacing position in which said developing roller is spaced from said electrophotographic photosensitive drum; and
 - 20 a force receiving device including a first force receiving portion for receiving a first external force and a second force receiving portion for receiving a second external force, wherein said second force receiving portion is movable relative to said developing frame, wherein said second force receiving portion is placed in a stand-by position retracted from an operating position by said first force
- 25

receiving portion receiving the first external force,
and is movable from the stand-by position to the
operating position for moving said developing frame
from the contacting position to the spacing position,
5 wherein a distance through which said second force
receiving portion moves from the stand-by position to
the operating position is larger than a distance
through which said first force receiving portion is
moved by the first external force.

10

2. A process cartridge according to Claim 1,
wherein said force receiving device includes a first
lever member provided with said first force receiving
portion, a rotatable gear member engaging with said
15 first lever member, and a second lever member provided
with said second force receiving portion and movable
through engagement with said gear member.

3. A process cartridge according to Claim 1,
20 wherein said force receiving device includes a lever
member rotatable about a rotation axis, and is
provided at one end portion with said first force
receiving portion and is provided at the other end
portion with said second force receiving portion.

25

4. A process cartridge according to Claim 1,
wherein said first force receiving portion is provided

on said drum frame.

5. A process cartridge according to Claim 1,
wherein said force receiving device is provided on
5 said developing frame.

6. A process cartridge according to Claim 1,
wherein said first force receiving portion contacts
the main assembly of the apparatus and receives the
10 first external force when said process cartridge is
mounted to the main assembly of the apparatus.

7. A process cartridge according to Claim 1,
15 wherein said second force receiving portion receives
the second external force from a force applying means
provided movably in the main assembly of the apparatus
when said process cartridge is mounted to the main
assembly of the apparatus.

20

8. A process cartridge according to Claim 6,
wherein said first force receiving portion receives
the first external force at a lower side of said
process cartridge by contacting to said first force
25 receiving portion.

9. A process cartridge according to Claim 1,

wherein said first force receiving portion is disposed below said second force receiving portion in the state in which said process cartridge is mounted in place in the main assembly of the apparatus.

5

10. A process cartridge according to Claim 1, wherein said process cartridge is detachably mountable to said main assembly of the apparatus through an opening provided in the main assembly of the electrophotographic image forming apparatus in a substantially horizontal direction crossing with an axial direction of said electrophotographic photosensitive drum.

15 11. A process cartridge according to Claim 1, wherein the main assembly of the apparatus includes a drawer member movable between an inside mounting position and a retracted position in which said process cartridge is mountable thereon.

20

12. A process cartridge according to Claim 1, wherein said force receiving member permits, in the stand-by position, said process cartridge to enter the main assembly of the apparatus, and is moved to the operating position from the stand-by position when said process cartridge is mounted to the main assembly of the apparatus.

25

13. A process cartridge according to Claim 1,
wherein said drum frame and said developing frame
rotatable relative to each other about a rotation axis,
5 and said force receiving member is more remote from
the rotation axis in the operating position than in
the stand-by position.

14. A process cartridge according to Claim 7,
10 wherein a moving distance of said second force
receiving portion is larger than that of said first
force receiving portion in a direction toward a force
applying member.

15 15. A process cartridge according to Claim 1,
wherein said drum frame supports rotatably said
photosensitive drum by way of a covering member.

16. A process cartridge according to Claim 1,
20 wherein said developing frame supports rotatably said
developing roller by way of a bearing.

17. An electrophotographic image forming apparatus
for forming an image on a recording material, said
25 apparatus comprising:

- (i) a movable force applying member;
- (ii) a main assembly contact portion;

(iii) mounting means;

(iv) a process cartridge mounted demountably to
said mounting means, said process cartridge including,
an electrophotographic photosensitive drum,

5 a developing roller for developing an
electrostatic latent image formed on said
electrophotographic photosensitive drum,

a drum frame supporting said
electrophotographic photosensitive drum,

10 a developing frame supporting said developing
roller, said developing frame is movable relative to
said drum frame and is capable of taking a contacting
position in which said developing roller is in contact
with said electrophotographic photosensitive drum and
15 a spacing position in which said developing roller is
spaced from said electrophotographic photosensitive
drum,

a force receiving device including a first
force receiving portion for receiving a first external
20 force when said process cartridge is mounted to the
main assembly of the apparatus of said
electrophotographic image forming apparatus, and a
second force receiving portion for receiving a second
external force when the force applying member moves,
25 wherein said second force receiving portion is movable
relative to said developing frame, wherein said second
force receiving portion is placed in a stand-by

position retracted from an operating position by said first force receiving portion receiving the first external force, and is movable from the stand-by position to the operating position for moving said developing frame from the contacting position to the spacing position, wherein a distance through which said second force receiving portion moves from the stand-by position to the operating position is larger than a distance through which said first force receiving portion is moved by the first external force; and

(vi) feeding means for feeding the recording material.

18. An apparatus according to Claim 17, wherein said first force receiving portion receives the first external force at a lower side of said process cartridge by contacting to said first force receiving portion.

19. An apparatus according to Claim 17, wherein said process cartridge is detachably mountable to said main assembly of the apparatus through an opening provided in the main assembly of the electrophotographic image forming apparatus in a substantially horizontal direction crossing with an axial direction of said electrophotographic

photosensitive drum.

20. An apparatus according to Claim 17, wherein
the main assembly of the apparatus includes a drawer
5 member movable between an inside mounting position and
a retracted position in which said process cartridge
is mountable thereon.

21. An apparatus according to Claim 17, wherein
10 said force receiving member permits, in the stand-by
position, said process cartridge to enter the main
assembly of the apparatus, and is moved to the
operating position from the stand-by position when
said process cartridge is mounted to the main assembly
15 of the apparatus.

1/21




FIG. 1

2/21




FIG. 2

3/21




FIG. 3

4/21





FIG. 4

5/21

**FIG. 5**

6/21




FIG. 6

7/21




FIG. 7

8/21.




FIG.8

9/21





FIG. 9

10/21

**FIG.10**

11/21




FIG. 11

12/21




FIG. 12

13/21




FIG.13




FIG. 14

15/21





FIG.15

16/21

**FIG.16**

17/21





FIG. 17

18/21

(a)



(b)




FIG.18

19/21




FIG.19

20/21




FIG. 20

21/21




FIG. 21




FIG. 6