



(51) International Patent Classification:
H04W 56/00 (2009.01) *H04W 64/00* (2009.01)
G01S 1/00 (2006.01)

(21) International Application Number:
PCT/IB2009/007733

(22) International Filing Date:
11 December 2009 (11.12.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/340,548 19 December 2008 (19.12.2008) US

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HALIVAARA, Ismo, Kullervo** [FI/FI]; Ihaistenkatu 4, FIN-33400 Tampere (FI). **WIROLA, Lauri, Aarne, Johannes** [FI/FI];

Vestonkatu 67 F 19, FIN-33580 Tampere (FI). **SYRJÄRINNE, Jari, Tapani** [FI/FI]; Aakkulankatu 4 B 8, FIN-33700 Tampere (FI).


(74) Common Representative: **NOKIA CORPORATION**; C/O Nokia Inc., 6021 connection Drive, MS 2-5-520, Attn: IP Docketing, Irving, TX 75039 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,

[Continued on next page]

(54) Title: SYNCHRONIZATION INDICATION IN NETWORKS



(57) Abstract: Systems and methods provide a network's synchronization status to a terminal when the terminal receives a transmission from the network. This network synchronization status can be indicated in accordance with various methods including, but not limited to the following: with a status flag in a network message; in a network capability indication; in a network's positioning capability indication; cell/network time relation information; in a time relation information of different Radio Access Technologies; and implicitly with another parameter and/or by a request for a certain measurement. When the network's synchronization status is determined, accurate time information/time assistance data can be maintained at the terminal.

Figure 1



TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

SYNCHRONIZATION INDICATION IN NETWORKS

FIELD

Various embodiments relate generally to positioning technologies for location-based services. More particularly, various embodiments relate to obtaining accurate time information at a terminal.

BACKGROUND

This section is intended to provide a background or context to various embodiments that are recited in the claims. The description herein may include concepts that could be pursued, but are not necessarily ones that have been previously conceived or pursued. Therefore, unless otherwise indicated herein, what is described in this section is not prior art to the description and claims in this application and is not admitted to be prior art by inclusion in this section.

Location services based on the location of mobile devices are becoming increasingly widespread. Assistance data for assisted navigation systems, such as global navigation satellite systems (GNSS), have been specified and standardized for cellular systems, e.g., global positioning systems (GPS), European Galileo, and Russian Global Navigation Satellite System (GLONASS). An exemplary GNSS can comprise a network of satellites that broadcasts navigation signals including time and distance data. GNSS receivers pick up these broadcasted navigation signals and calculate a precise global location based thereon. Other examples of GNSS include, but are not limited to, satellite-based augmentation systems (SBAS), local area augmentation systems (LAAS), quasi-zenith satellite systems (QZSS), and hybrid receivers.

The delivery of such assistance data can be built on top of cellular system-specific control plane protocols including, e.g., the radio resource location services protocol (RRLP) for GSM networks, the radio resource control (RRC) protocol of layer 3 in wideband code division multiple access (WCDMA) networks, and IS-801 for Code Division Multiple Access (CDMA) networks, standardized in the 3rd Generation Partnership Project (3GPP) and 3GPP2 standards. In addition, the control plane protocols also support Radio Access Network (RAN)-specific positioning methods. Examples include Enhanced Observed Time Difference (EOTD) in RRLP and Idle Period DownLink – Observed Time Difference Of Arrival (IPDL-OTDOA). It should be noted that assistance data as described herein, can refer to GNSS assistance containing, but not limited to, navigation models, time assistance, reference location, atmosphere models, differential corrections, sensor assistance and acquisition assistance. The assistance data can also include e.g. position information, high-accuracy position information, multi-frequency multi-GNSS measurement data, computationally-generated measurements, sensor measurements, route information and waypoint information.

As described above, assistance data may include, amongst other data, navigation models for the satellites, reference location and reference time. Whether the reference location and time are accurate or not has a major impact on performance and thus, information regarding GNSS time is crucial in solving the GNSS receiver's position. Keeping accurate time in, e.g., an Assisted GNSS (AGNSS) terminal/receiver (where time information is provided as assistance data) requires, for example, either an accurate and expensive oscillator, power-consuming miniature atomic clock, frequent connection to the satellites, or frequent requests of the time assistance from the network. Frequent connections to, e.g., satellites and/or a network, are power-consuming and thus degrade the user experience.

In technical terms, accurate time assistance together with reference position allows for the prediction of a code phase and Doppler frequency search space for spread spectrum satellite broadcasts. Having a small search window improves sensitivity contributing to Time-To-First-Fix (TTFF) and availability. Both aspects are important from the customer-satisfaction point-of-view.

It should be noted that other assistance data, such as ephemerides, have a lifetime of several hours. Therefore, the need to update such information needs is relatively rare. However, with conventional oscillators, time can be kept sufficiently accurate in a terminal on the order of only tens of minutes. Hence, it would be beneficial to be able to maintain an accurate time relation in a terminal by some other system or method.

When a mobile terminal is operating in a network that is synchronized to GNSS time, it can use this information to maintain accurate time even when moving from one cell to another within the same network. However, in networks that may be either synchronous or asynchronous, such as Evolved Universal Mobile Telecommunications System Terrestrial Radio Access Network (E-UTRAN), the terminal does not know about the network's synchronization status and cannot utilize this potential. In certain synchronized networks, such as IS-95/2000 and WiMAX, synchronization is a feature that is defined in the standard. That is, time transfer is an intrinsic feature of, e.g., the IS-95/2000 system, where the 3GPP RRLP and 3GPP RRC define the time assistance for control using cell frame timings. In addition, IS-95 is directly synchronized to GPS time, so accurate GPS time is readily available from every cell, making the maintenance of accurate time in the handsets unnecessary. Hence the information is available to the terminal in the design phase. Moreover, these networks also broadcast the GPS time information.

Open Mobile Alliance secure user plane location (OMA SUPL) protocol does the same in the user plane, where a reference time is given in the form of a difference between the GNSS time and the cell frame timing of the serving base station. In IP-networks, clocks can be synchronized using protocols specifically designed for this purpose. Additionally, certain systems enable AGNSS receiver time assistance over IP/an IP network connection by utilizing different combinations of at least one of the following: a time transfer protocol; a time server; a GNSS-

receiver for obtaining the relationships between the time-server's time and the GNSS time scales; a time server synched to a specified GNSS time; a service providing differences between GNSS time scales; and user plane assistance protocols for transferring the relationship(s) from a server to a terminal.

5

SUMMARY

One exemplary embodiment relates to a method of providing network synchronization status to a terminal comprising receiving a transmission from a network. The method further comprises determining a synchronization status of the network from the transmission, where

10

accurate time is maintained based on the synchronization status of the network.

Another exemplary embodiment relates to an apparatus comprising an electronic device. The electronic device is configured to receive a transmission from a network. The electronic device is further configured to determine a synchronization status of the network from the transmission, where accurate time is maintained by the electronic device based on the

15

synchronization status of the network.

These and other advantages and features of various embodiments of the present invention, together with the organization and manner of operation thereof, will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, wherein like elements have like numerals throughout the several drawings described below.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are described by referring to the attached drawings, in which:

Figure 1 is a flow chart illustrating exemplary processes performed for maintaining accurate timing in a terminal via a network synchronization status transmitted during a network

25

transmission in accordance with various embodiments;

Figure 2 is an overview diagram of a system within which various embodiments may be implemented;

Figure 3 is a perspective view of an electronic device that can be used in conjunction with the implementation of various embodiments; and

30

Figure 4 is a schematic representation of the circuitry which may be included in the electronic device of Figure 3.

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS

The availability of assistance data, e.g., time information, described above can greatly affect GNSS receiver performance. For example, in scenarios where good signal conditions exist, approximately 30 seconds are typically needed for a GPS receiver to extract a copy of a navigation message from a signal broadcasted by a satellite. Therefore, if no valid copy (e.g.,

35

from a previous session) of a navigation model is available, at least 18 seconds (a theoretical minimum, although 30 seconds is a more typical value) elapse before the satellite can be used in position calculations. With regard to Assisted GPS (AGPS) receivers, a cellular network sends a receiver a copy of a navigation message. Therefore, the receiver need not extract navigation data from the satellite broadcast, but rather can obtain it directly from the network. TTFF can be reduced to 10 seconds or less (as opposed to the 30 seconds required for conventional GPS systems). This reduction in TTFF is crucial in scenarios when, for example, positioning an emergency call is required. Additionally, this reduction in TTFF can improve the user experience in various use cases.

Various embodiments provide a network's synchronization status to a terminal when the terminal receives a transmission from the network in question. This network synchronization status can be indicated utilizing various methods including, but not limited to the following: with a status flag in a (system) message from the network; in a network capability indication; in a network's positioning capability indication; in GNSS time, i.e., cell/network time relation information; in a time relation information of different Radio Access Technologies (RATs); and/or implicitly with another parameter and/or by a request for a certain measurement (e.g., certain assistance data that is only provided in a synchronized network or OTDOA measurement that is only requested in a synchronized network). Additionally, it should be noted that the transmission can be either a broadcast transmission or point-to-point signalling.

For example and with regard to the aforementioned RATs, "pseudo-synchronization" can be achieved between networks. That is, if the terminal obtains network synchronization status information of a first network, e.g., a 3GPP Long-Term Evolution (LTE) network, and consequently, maintains accurate time, this information can be used to "pseudo-synchronize" the LTE network with another network. Hence, a multi-mode receiver that supports, e.g., LTE and Global System for Mobile Communications (GSM) communication standards/technologies, can use the LTE network synchronization status information to indirectly relate the asynchronous GSM cells to an accurate time reference. Therefore, the benefits of a first network's synchronization status information can be extended to one or more other networks.

When the network's synchronization status is determined, accurate time information/time assistance data can be maintained at the terminal. Thus, the terminal, e.g., an AGNSS receiver, can predict the code phases and the Doppler frequencies for spread spectrum satellite broadcasts. That is, the satellite signals in view (i.e., above horizon) and hence, the receiver can find the satellite signals very quickly because of the reduced code and frequency search space. Accurate reference location and time information avoid scenarios such as when the AGNSS receiver may only be able to calculate which satellites are above the horizon and should be searched, where when either the reference location or time is unavailable, the other may become obsolete and the AGNSS receiver is required to do a full-sky search.

Figure 1 illustrates exemplary processes performed for providing time information in a network transmission in accordance with various embodiments. At 100, a transmission is received from a network at a terminal. At 110, the synchronization status of the network is determined from the transmission. At 120, the synchronization status of the network is utilized to maintain accurate time at the terminal.

Maintaining accurate time in a terminal in accordance with various embodiments results in fewer assistance data requests (i.e., less traffic in the network), as well as improved location experience due to faster location determination, e.g., in cases where a terminal does not need to request additional assistance data from the network. Moreover, sensitivity and therefore availability are improved, if accurate time assistance is available. Additionally and assuming very accurate synchronization, using network-based measurements in hybrid (GNSS+network measurement) positioning becomes possible, where the network-based measurements can be either OTDOA or time-of-arrival (TOA)-type measurements, for example. Further still, savings in a terminal's power consumption can also be realized because the terminal is able to determine the location of a user of the terminal in a substantially shorter time than is conventionally possible.

Figure 2 shows a system 10 in which various embodiments can be utilized, comprising multiple communication devices that can communicate through one or more networks. The system 10 may comprise any combination of wired or wireless networks including, but not limited to, a mobile telephone network, a wireless Local Area Network (LAN), a Bluetooth personal area network, an Ethernet LAN, a token ring LAN, a wide area network, the Internet, etc. The system 10 may include both wired and wireless communication devices.

For exemplification, the system 10 shown in Figure 2 includes a mobile telephone network 11 and the Internet 28. Connectivity to the Internet 28 may include, but is not limited to, long range wireless connections, short range wireless connections, and various wired connections including, but not limited to, telephone lines, cable lines, power lines, and the like.

The exemplary communication devices of the system 10 may include, but are not limited to, an electronic device 12 in the form of a mobile telephone, a combination personal digital assistant (PDA) and mobile telephone 14, a PDA 16, an integrated messaging device (IMD) 18, a desktop computer 20, a notebook computer 22, etc. The communication devices may be stationary or mobile as when carried by an individual who is moving. The communication devices may also be located in a mode of transportation including, but not limited to, an automobile, a truck, a taxi, a bus, a train, a boat, an airplane, a bicycle, a motorcycle, etc. Some or all of the communication devices may send and receive calls and messages and communicate with service providers through a wireless connection 25 to a base station 24. The base station 24 may be connected to a network server 26 that allows communication between the mobile

telephone network 11 and the Internet 28. The system 10 may include additional communication devices and communication devices of different types.

The communication devices may communicate using various transmission technologies including, but not limited to, Code Division Multiple Access (CDMA), GSM, Universal Mobile Telecommunications System (UMTS), Time Division Multiple Access (TDMA), Frequency Division Multiple Access (FDMA), Transmission Control Protocol/Internet Protocol (TCP/IP), Short Messaging Service (SMS), Multimedia Messaging Service (MMS), e-mail, Instant Messaging Service (IMS), Bluetooth, IEEE 802.11, IEEE 802.16, LTE, etc. A communication device involved in implementing various embodiments may communicate using various media including, but not limited to, radio, infrared, laser, cable connection, and the like.

Figures 3 and 4 show one representative electronic device 12 within which various embodiments may be implemented. It should be understood, however, that various embodiments are not intended to be limited to one particular type of device. The electronic device 12 of Figures 3 and 4 includes a housing 30, a display 32 in the form of a liquid crystal display, a keypad 34, a microphone 36, an ear-piece 38, a battery 40, an infrared port 42, an antenna 44, a smart card 46 in the form of a UICC according to one embodiment, a card reader 48, radio interface circuitry 52, codec circuitry 54, a controller 56 and a memory 58. Individual circuits and elements are all of a type well known in the art, for example in the Nokia range of mobile telephones.

Various embodiments described herein are described in the general context of method steps or processes, which may be implemented in one embodiment by a computer program product, embodied in a computer-readable medium, including computer-executable instructions, such as program code, executed by computers in networked environments. A computer-readable medium may include removable and non-removable storage devices including, but not limited to, Read Only Memory (ROM), Random Access Memory (RAM), compact discs (CDs), digital versatile discs (DVD), etc. Generally, program modules may include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Computer-executable instructions, associated data structures, and program modules represent examples of program code for executing steps of the methods disclosed herein. The particular sequence of such executable instructions or associated data structures represents examples of corresponding acts for implementing the functions described in such steps or processes.

Various embodiments may be implemented in software, hardware, application logic or a combination of software, hardware and application logic. The software, application logic and/or hardware may reside, for example, on a chipset, a mobile device, a desktop, a laptop or a server. Software and web implementations of various embodiments can be accomplished with standard programming techniques with rule-based logic and other logic to accomplish various database searching steps or processes, correlation steps or processes, comparison steps or processes and

decision steps or processes. Various embodiments may also be fully or partially implemented within network elements or modules. It should be noted that the words “component” and “module,” as used herein and in the following claims, is intended to encompass implementations using one or more lines of software code, and/or hardware implementations, and/or equipment for receiving manual inputs.

Individual and specific structures described in the foregoing examples should be understood as constituting representative structure of means for performing specific functions described in the following the claims, although limitations in the claims should not be interpreted as constituting “means plus function” limitations in the event that the term “means” is not used therein. Additionally, the use of the term “step” in the foregoing description should not be used to construe any specific limitation in the claims as constituting a “step plus function” limitation. To the extent that individual references, including issued patents, patent applications, and non-patent publications, are described or otherwise mentioned herein, such references are not intended and should not be interpreted as limiting the scope of the following claims.

The foregoing description of embodiments has been presented for purposes of illustration and description. The foregoing description is not intended to be exhaustive or to limit embodiments to the precise form disclosed, and modifications and variations are possible in light of the above teachings or may be acquired from practice of various embodiments. The embodiments discussed herein were chosen and described in order to explain the principles and the nature of various embodiments and its practical application to enable one skilled in the art to utilize various embodiments and with various modifications as are suited to the particular use contemplated. The features of the embodiments described herein may be combined in all possible combinations of methods, apparatus, modules, systems, and computer program products.

WHAT IS CLAIMED IS:

1. A method, comprising:
receiving a transmission from a network;
determining a synchronization status of the network from the transmission; and
maintaining accurate time based on the synchronization status of the network.
2. The method according to claim 1, wherein the network comprises at least one of a synchronous and asynchronous network.
3. The method according to claim 1 or 2, wherein the network is a terrestrial communication network.
4. The method according to any of claims 1 to 3, wherein the synchronization status of the network is indicated in the transmission via a status flag, and wherein the transmission comprises a network message.
5. The method according to any of claims 1 to 3, wherein the synchronization status of the network is deduced in a terminal from a status flag in the transmission, and wherein the transmission comprises a network message.
6. The method according to any of claims 1 to 5, wherein the synchronization status of the network is indicated in the transmission via a network capability indication.
7. The method according to any of claims 1 to 5, wherein the synchronization status of the network is indicated in the transmission via a network positioning capability indication.
8. The method according to any of claims 1 to 5, wherein the synchronization status of the network is indicated in the transmission via at least one of cell and network global navigation satellite systems time relation information.
9. The method according to any of claims 1 to 5, wherein the synchronization status of the network is indicated in the transmission via time relation information associated with different radio access technologies.

10. The method according to claim 9 further comprising, utilizing the synchronization status of the network to enable “pseudo-synchronization” of the accurate time between the network and a second network, wherein the network operates using a first radio access technology and the second network operates using a second radio access technology.

11. The method according to any of claims 1 to 10, wherein the synchronization status of the network is indicated in the transmission implicitly with at least one of a parameter and a measurement request.

12. The method according to claim 11, wherein the parameter request comprises a request for assistance data, and wherein the network comprises a synchronized network.

13. The method according to claim 11, wherein the measurement request comprises a request for one of an observed time difference of arrival and a time of arrival, and wherein the network comprises a synchronized network.

14. The method according to any of claims 1 to 13, wherein the transmission comprises one of a broadcast transmission and a point-to-point signaling transmission.

15. A computer program product, embodied on a computer-readable medium, comprising computer code configured to cause an apparatus to perform the processes according to any of claims 1 to 14.

16. An apparatus, comprising:
at least one processor; and
at least one memory including computer program code
the at least one memory and the computer program code configured to, with the at least one processor, cause the apparatus to perform at least the following:
receive a transmission from a network;
determine a synchronization status of the network from the transmission; and
maintain accurate time based on the synchronization status of the network.

17. The apparatus according to claim 16, wherein the apparatus comprises a global navigation satellite systems receiver.

18. The apparatus according to claim 16 or 17, wherein the network comprises at least one of a synchronous and asynchronous network.

19. The apparatus according to any of claims 16 to 18, wherein the network is a terrestrial communication network.

20. The apparatus according to any of claims 16 to 19, wherein the synchronization status of the network is indicated in the transmission via a status flag, and wherein the transmission comprises a network message.

21. The apparatus according to any of claims 16 to 19, wherein the synchronization status of the network is deduced in said apparatus from a status flag in the transmission, and wherein the transmission comprises a network message.

22. The apparatus according to any of claims 16 to 21, wherein the synchronization status of the network is indicated in the transmission via a network capability indication.

23. The apparatus according to any of claims 16 to 21, wherein the synchronization status of the network is indicated in the transmission via a network positioning capability indication.

24. The apparatus according to any of claims 16 to 21, wherein the synchronization status of the network is indicated in the transmission via at least one of cell and network global navigation satellite systems time relation information.

25. The apparatus according to any of claims 16 to 21, wherein the synchronization status of the network is indicated in the transmission via time relation information associated with different radio access technologies.

26. The apparatus according to claim 25, wherein the electronic device is further configured to utilize the synchronization status of the network to enable "pseudo-synchronization" of the accurate time between the network and a second network, wherein the network operates using a first radio access technology and the second network operates using a second radio access technology.

27. The apparatus according to any of claims 16 to 26, wherein the synchronization status of the network is indicated in the transmission implicitly with at least one of a parameter and a measurement request.

28. The apparatus according to claim 27, wherein the parameter request comprises a request for assistance data, and wherein the network comprises a synchronized network.

29. The apparatus according to claim 27, wherein the measurement request comprises a request for one of an observed time difference of arrival and a time of arrival, and wherein the network comprises a synchronized network.

30. The apparatus according to any of claims 16 to 29, wherein the transmission comprises one of a broadcast transmission and a point-to-point signaling transmission.

31. The apparatus according to any of claims 16 to 30, wherein the apparatus is a mobile terminal.

32. An apparatus, comprising:
means for receiving a transmission from a network;
means for determining a synchronization status of the network from the transmission; and
means for maintaining accurate time based on the synchronization status of the network.




Figure 1




Figure 2




Figure 3




Figure 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB2009/007733

A. CLASSIFICATION OF SUBJECT MATTER

IPC: see extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: H04W, H04L, H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	J Syrjärinne and L. Wirola. Setting a New Standard: Assisting GNSS receivers That Use Wireless Networks. InsideGNSS, Vol 1, No. 7, pp 26-31, (2006) http://www.insidegnss.com/auto/1006%20New%20Standard.pdf Whole document --	1-32
Y	WO 2008013404 A1 (ELECTRONICS ABD TELECOMMUNICATIONS RESEARCH INSTITUTE), 31 January 2008 (31.01.2008), page 60, line 14 - page 62, line 21 --	1-32
Y	WO 2008058162 A2 (QUALCOMM INCORPORATED), 15 May 2008 (15.05.2008), paragraphs (0014)-(0037) --	1-32

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 April 2010

Date of mailing of the international search report

30-04-2010

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Per Karlsson / MRO

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB2009/007733

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5353332 A (A.K. RATH ET AL), 4 October 1994 (04.10.1994), column 6, line 4 - column 9, line 12, claims 1-5, abstract, Table 1 --	1-32
A	3GPP TS 44.031 V8.1.0 (2008-12) (available 2008-15-15); 3rd Generation Partnership Project; Technical Specification Group GSM/EDGE Radio Access Network; Location Services (LCS); Mobile Station (MS) - Serving Mobile Location Centre (SMLC) Radio Resource LCS Protocol (RRLP) (Release 8) http://www.3gpp.org/ftp/Specs/html-info/44031.htm Section 2.2-2.3a, 4.1-4.7 --	1-32
A	3GPP TS 25.331 V8.4.0 (2008-09)(available 2008-09-23); 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Radio Resource Control (RRC); Protocol Specification (Release 8) http://www.3gpp.org/ftp/Specs/html-info/25331.htm Section 8.6.7.19-8.6.7.19.7.11 --	1-32
P,Y	WO 2009026557 A2 (QUALCOMM INCORPORATED), 26 February 2009 (26.02.2009), figure 3, claims 1-4, abstract, paragraphs (0006)-(0009) -- -----	1-32

International patent classification (IPC)**H04W 56/00** (2009.01)**G01S 1/00** (2006.01)**H04W 64/00** (2009.01)**Download your patent documents at www.prv.se**

The cited patent documents can be downloaded:

- From "Cited documents" found under our online services at www.prv.se (English version)
- From "Anförda dokument" found under "e-tjänster" at www.prv.se (Swedish version)

Use the application number as username. The password is **RTZFSOWLNO**.

Paper copies can be ordered at a cost of 50 SEK per copy from PRV InterPat (telephone number 08-782 28 85).

Cited literature, if any, will be enclosed in paper form.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/IB2009/007733

WO	2008013404	A1	31/01/2008	NONE		
WO	2008058162	A2	15/05/2008	AU	2007316361 A	15/05/2008
				CA	2667166 A	15/05/2008
				CN	101536351 A	16/09/2009
				EP	2095528 A	02/09/2009
				KR	20090081013 A	27/07/2009
				NO	20092158 A	30/07/2009
				US	20100093363 A	15/04/2010
US	5353332	A	04/10/1994	SG	52648 A	28/09/1998
WO	2009026557	A2	26/02/2009	AU	2008288790 A	26/02/2009
				CA	2695013 A	26/02/2009
				US	20090052430 A	26/02/2009