

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 451 786 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:

10.09.1997 Bulletin 1997/37

(51) Int Cl.⁶: **D01F 6/62, D01F 6/70**

(21) Application number: **91105606.7**

(22) Date of filing: **09.04.1991**

(54) **Water-soluble fiber and a method for manufacture thereof**

Wasserlösliche Faser und Verfahren zu ihrer Herstellung

Fibre soluble dans l'eau et méthode pour sa fabrication

(84) Designated Contracting States:
DE

(30) Priority: **13.04.1990 JP 98087/90**

(43) Date of publication of application:
16.10.1991 Bulletin 1991/42

(73) Proprietor: **DAI-ICHI KOGYO SEIYAKU CO., LTD.**
Shimogyo-ku Kyoto (JP)

(72) Inventors:
• **Fujita, Takeshi**
Uji-city, Kyoto (JP)

• **Isoda, Chuzo**
Uji-city, Kyoto (JP)
• **Pu, Sejin**
Ukyo-ku, Kyoto (JP)

(74) Representative:
Strehl Schübel-Hopf Groening & Partner
Maximilianstrasse 54
80538 München (DE)

(56) References cited:
EP-A- 0 089 038 **BE-A- 899 831**

EP 0 451 786 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

The present invention relates to water-soluble fiber and a method for manufacture thereof.

Among the water-soluble fibers heretofore known is polyvinyl alcohol fiber which is generally fabricated into a twisted yarn, woven fabric or non-woven fabric and put to use in a diversity of applications. For example, it has been used for provisional reinforcing or adhesion in a variety of industrial processes.

However, polyvinyl alcohol fiber is not readily soluble in water and requires heating to at least about 80°C for dissolution, thus being poor in workability. Moreover, when exposed to a temperature over 100°C, it undergoes crosslinking so that dissolution is often made difficult.

SUMMARY OF THE INVENTION

The object of the present invention is to provide a water-soluble fiber which is tough and readily soluble in water at ambient temperature and does not suffer losses in water solubility on exposure to heat and a method for manufacturing the fiber.

The present invention is directed to a water-soluble fiber composed of a high molecular compound with a weight average molecular weight of not less than 10,000, which high molecular compound is obtainable by reacting a polyalkylene oxide compound, which is obtainable by addition polymerization of an ethylene oxide-containing alkylene oxide and an organic compound containing two active hydrogen atoms, with a polycarboxylic acid, an anhydride thereof, or a lower alkyl ester thereof, or a diisocyanate compound.

The manufacture of said water-soluble fiber comprises spinning said high molecular compound.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The polyalkylene oxide compound as a major starting material for the high molecular compound of the present invention is preferably a compound having a weight average molecular weight of not less than 100 and can be prepared by addition polymerization of an ethylene oxide-containing alkylene oxide and an organic compound containing two active hydrogen atoms.

The organic compound containing two active hydrogen atoms includes, *inter alia*, ethylene glycol, propylene glycol, polyethylene glycol, polypropylene glycol, polytetramethylene glycol, 1,6-hexanediol, bisphenol A, aniline and so on.

The ethylene oxide-containing alkylene oxide includes, *inter alia*, ethylene oxide and mixtures of ethylene oxide with propylene oxide, butylene oxide, styrene oxide, α -olefin oxides, glycidyl ethers and so on.

The addition reaction of such an alkylene oxide can be carried out in the known manner, and the mode of addition polymerization of ethylene oxide and other alkylene oxides may be optionally random or block.

The polycarboxylic acid, anhydride thereof, or lower alkyl ester thereof, which is reacted with said polyalkylene oxide compound, include, *inter alia*, phthalic acid, isophthalic acid, terephthalic acid, sebacic acid, dimer acid, pyromellitic acid, etc., anhydrides thereof, and methyl esters, dimethyl esters, diethyl esters, etc. thereof. The preferred are dimethyl terephthalate, dimethyl phthalate, dimethyl isophthalate, dimethyl sebacate, pyromellitic anhydride and so on.

The polyester-forming reaction between said polyalkylene oxide compound and said polycarboxylic acid, anhydride thereof or lower alkyl ester thereof is preferably conducted at 120-250°C and 10^{-2} - 10^3 Pa.

The diisocyanate to be reacted with said polyalkylene oxide compound includes, *inter alia*, tolylene diisocyanate, diphenylmethane diisocyanate, hexamethylene diisocyanate, isophorone diisocyanate, xylylene diisocyanate, 4,4'-methylene-bis-(cyclohexyl isocyanate) and so on.

The urethane-forming reaction between said polyalkylene oxide compound and said diisocyanate is conducted by mixing the starting compounds in an NCO/OH ratio of, for example, 1.5 through 0.5 and heating the mixture at 80 to 150°C for 1 to 5 hours.

The weight average molecular weight of the high molecular compound according to the present invention is not less than 10,000. If the molecular weight is less than 10,000, the fiber will not be sufficiently high in mechanical strength, giving rise to yarn breakage in the spinning process.

This high molecular compound can be processed into fiber by any known relevant technique such as melt-spinning, dry spinning, wet-spinning, etc., although the melt-spinning process is preferred if only from economic points of view.

In the melt-spinning process, the high molecular compound is melted at 50-200°C in a nitrogen gas atmosphere and extruded from the conventional spinning nozzle.

In this process, such additives as a plasticizer, lubricant, stabilizer, colorant, filler, etc. can be added. According to the intended application, a perfume, fungicide, agrochemical, fertilizer, etc. can also be incorporated.

The water-soluble fiber as spun has large elongation. For example, the elongation of a fiber with a diameter of 10 μ m to 5 mm is approximately 500 to 3,000 percent.

After spinning, the fiber may be treated with a sizing or bundling agent in the hydrocarbon series or stretched. When it is stretched in a draw ratio of 5 to 30, its tensile strength is remarkably increased. The stretching may be performed concurrently with spinning.

The fiber thus obtained is subjected to various

processings such as twisting and cutting. The fiber can also be constructed into mixed fabrics with other fibers.

The water-soluble fiber according to the present invention is not only high in elongation and tensile strength but is readily soluble in water. Moreover, this water solubility is not appreciably affected by heating. Therefore, as processed into a thread or yarn or a web, the fiber remains tough and self-supporting in application and, yet, can be completely dissolved out swiftly as needed. In this and other ways, this material can contribute to rationalization of various industrial processes.

The following examples and comparative examples are further illustrative of the invention, it being to be understood, however, that the invention is by no means limited thereof but limited only by the claims appended hereto.

Example 1

One hundred parts (parts by weight; the same applies hereinafter) of polyethylene glycol (weight average molecular weight 10,000) and 2.2 parts of dimethyl terephthalate were used to give a polyester compound with a weight average molecular weight of 130,000 (hereinafter referred to as high molecular compound A).

This high molecular compound A was fed to a melt-spinning apparatus, where it was melted at 120°C in a nitrogen gas atmosphere and extruded through a spinning nozzle at a rate of 50 m/min, rapidly cooled under tension and taken up. A plain-weave fabric was then constructed using a thread-like bundle of ten filaments.

When put in water, this plain-weave fabric disappeared in 15 seconds. On the other hand, the same plain-weave fabric was locally heat-sealed (120°C, 1.5 seconds) to provide a firm local bond. When this fabric was put in water, the whole fabric inclusive of the bond disappeared in 18 seconds.

Example 2

One-hundred parts of a polyalkylene oxide compound (weight average molecular weight 20,000) prepared by block polymerization of ethylene oxide (85%), propylene oxide (15%) and bisphenol A was mixed with 0.84 part of hexamethylene diisocyanate and a small amount of dibutyltin dilaurate and the mixture was heated at 100°C to give a high molecular compound with a weight average molecular weight of 250,000.

This compound was extruded in the same manner as Example 1, cut to 2-3 mm and processed into a nonwoven fabric. Using this nonwoven fabric as a filter, a used vacuum pump oil (containing 0.5% of water) was purified. As a result, the water content was reduced to 0.02% and the oil came clear. This purified oil could be reused with full competence.

Comparative Example 1

When a plain-weave fabric of polyvinyl alcohol fiber was put in hot water at 80°C, it disappeared in about 10 seconds. In water at 25°C, however, the fabric swelled as its surface was wetted but remained to be dissolved completely as yet even after one hour. On the other hand, the same plain-weave fabric with a heat-sealed local bond remained partially undissolved even in hot water at 80°C.

Example 3

The high molecular compound A synthesized in Example 1 was fed to a melt-spinning apparatus, where it was melted at 120°C and extruded from a 1 mm (dia.) spinning nozzle at a take-up rate of 30 m/min. The resulting monofilament had a diameter of 40 µm and a tensile strength of 200 bar.

This fiber could be stretched in a draw ratio of 13 at 20°C and the stretched fiber had a diameter of 12 µm and a tensile strength of 390 bar.

At 50°C, the fiber could be stretched in a draw ratio of 20 to give a filament with a diameter of 9 µm. The tensile strength of this filament was 550 bar.

Comparative Example 2

A wet-spun polyvinyl alcohol filament with a diameter of 40 µm could be stretched only to twice its initial length at 20°C. The stretched filament had a diameter of 28 µm and a tensile strength of 500 bar.

It is, thus, apparent that in the case of the water-soluble fiber according to the present invention, its large elongation permits stretching into finer fiber even if the filament as spun is not so fine. Moreover, spinning troubles such as yarn breakage can be prevented in accordance with the invention.

Claims

1. A water-soluble fiber composed of a high molecular compound with a weight average molecular weight of not less than 10,000, which high molecular compound is obtainable by reacting a polyalkylene oxide compound, which is obtainable by addition polymerization of an ethylene oxide-containing alkylene oxide and an organic compound containing two active hydrogen atoms, with a polycarboxylic acid, an anhydride thereof, a lower alkyl ester thereof, or a diisocyanate.
2. A water-soluble fiber according to claim 1 which has an elongation of 500 to 3,000 percent.
3. A method of manufacturing a water-soluble fiber which comprises spinning a high molecular com-

pound with a weight average molecular weight of not less than 10,000, which high molecular compound is obtainable by reacting a polyalkylene oxide compound, which is obtainable by addition polymerization of an ethylene oxide-containing alkylene oxide and an organic compound containing two active hydrogen atoms, with a polycarboxylic acid, an anhydride thereof, a lower alkyl ester thereof, or a diisocyanate.

4. A method of manufacturing a water-soluble fiber according to claim 3 wherein the fiber as spun or in the course of spinning is stretched in a draw ratio of 5 to 30.

Patentansprüche

1. Wasserlösliche Faser aus einer hochmolekularen Verbindung mit einem Gewichtsmittel des Molekulargewichts von nicht weniger als 10 000, wobei die hochmolekulare Verbindung durch Umsetzen einer Polyalkylenoxidverbindung, die durch Additionspolymerisation eines Ethylenoxid enthaltenden Alkylenoxids erhältlich ist, und einer organischen Verbindung mit zwei aktiven Wasserstoffatomen mit einer Polycarbonsäure, deren Anhydrid, deren niederen Alkylester oder einem Isocyanat erhältlich ist.
2. Wasserlösliche Faser gemäß Anspruch 1, die eine Dehnung von 500 bis 3000 % hat.
3. Verfahren zur Herstellung einer wasserlöslichen Faser, welches das Verspinnen einer hochmolekularen Verbindung mit einem Gewichtsmittel des Molekulargewichts von nicht weniger als 10 000 umfaßt, wobei die hochmolekulare Verbindung durch Umsetzen einer Polyalkylenoxidverbindung, die durch Additionspolymerisation eines Ethylenoxid enthaltenden Alkylenoxids erhältlich ist, und einer organischen Verbindung mit zwei aktiven Wasserstoffatomen mit einer Polycarbonsäure, deren Anhydrid, deren niederen Alkylester oder einem Isocyanat erhältlich ist.
4. Verfahren zur Herstellung einer wasserlöslichen Faser gemäß Anspruch 3, wobei die gerade versponnene Faser oder die Faser im Verlauf des Verspinnens in einem Verstreckungsverhältnis von 5 bis 30 verstreckt wird.

obtenu en faisant réagir un composé oxyde de polyalkylène, susceptible d'être obtenu par polymérisation d'addition d'un oxyde alkylène contenant de l'oxyde d'éthylène, et d'un composé organique ayant deux atomes d'hydrogène actifs, avec un acide polycarboxylique, un anhydride correspondant, ou un alkyle ester inférieur correspondant ou un diisocyanate.

2. Fibre soluble dans l'eau selon la revendication 1 qui a une elongation de 500 à 3 000 %.
3. Procédé pour la préparation d'une fibre soluble dans l'eau qui consiste à filer un composé de haut poids moléculaire ayant un poids moléculaire moyen en poids n'excédant pas 10 000, ce composé à haut poids moléculaire pouvant être obtenu par réaction d'un composé d'oxyde de polyalkylène obtenu par polymérisation d'addition d'un oxyde alkylène contenant de l'oxyde d'éthylène et d'un composé organique ayant deux atomes d'hydrogène actif, avec un acide polycarboxylique, un anhydride correspondant ou un ester d'alkyle inférieur correspondant ou un diisocyanate.
4. Procédé de préparation d'une fibre soluble dans l'eau selon la revendication 3 dans laquelle la fibre telle que filée ou en cours de filature est étirée dans un rapport d'étirage de 5 à 30.

Revendications

1. Fibre soluble dans l'eau constituée d'un composé de haut poids moléculaire ayant un poids moléculaire moyen en poids n'excédant pas 10 000, ce composé de haut poids moléculaire pouvant être