




(86) **Date de dépôt PCT/PCT Filing Date:** 2012/12/19
(87) **Date publication PCT/PCT Publication Date:** 2013/06/27
(45) **Date de délivrance/Issue Date:** 2016/02/02
(85) **Entrée phase nationale/National Entry:** 2014/06/18
(86) **N° demande PCT/PCT Application No.:** US 2012/070626
(87) **N° publication PCT/PCT Publication No.:** 2013/096453
(30) **Priorité/Priority:** 2011/12/19 (US13/330,592)

(51) **Cl.Int./Int.Cl.** **A61F 9/007** (2006.01),
A61F 2/14 (2006.01)
(72) **Inventeurs/Inventors:**
WARDLE, JOHN, US;
SCHIEBER, ANDREW T., US
(73) **Propriétaire/Owner:**
IVANTIS, INC., US
(74) **Agent:** BORDEN LADNER GERVAIS LLP

(54) **Titre : POSE D'IMPLANTS OCULAIRES DANS L'OEIL**
(54) **Title: DELIVERING OCULAR IMPLANTS INTO THE EYE**



(57) **Abrégé/Abstract:**

A method of deploying an ocular implant into Schlemm's canal of an eye. The method includes the steps of inserting a distal end of a cannula through a cornea of the eye and into an anterior chamber of the eye, the cannula having a distal opening extending from the distal end and through a side wall; placing the distal opening of the cannula into fluid communication with Schlemm's canal; advancing the ocular implant distally through the cannula with a delivery tool engaged with the ocular implant, a proximal portion of the ocular implant engaging the delivery tool proximal to a distal portion of the delivery tool; and disengaging the ocular implant and the delivery tool when the proximal portion of the ocular implant reaches the cannula distal opening. The invention also includes a system for practicing the method.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau

(43) International Publication Date
27 June 2013 (27.06.2013)



(10) International Publication Number
WO 2013/096453 A1

(51) International Patent Classification:

A61F 2/14 (2006.01)

(21) International Application Number:

PCT/US2012/070626

(22) International Filing Date:

19 December 2012 (19.12.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/330,592 19 December 2011 (19.12.2011) US

(71) Applicant: **IVANTIS, INC.** [US/US]; 38 Discovery, Suite 150, Irvine, CA 92618 (US).

(72) Inventors: **WARDLE, John**; 38 Discovery, Suite 150, Irvine, CA 92618 (US). **SCHIEBER, Andrew, T.**; 38 Discovery, Suite 150, Irvine, CA 92618 (US).

(74) Agents: **THOMAS, Justin** et al.; Shay Glenn LLP, 2755 Campus Drive, Suite 210, San Mateo, CA 94403 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: DELIVERING OCULAR IMPLANTS INTO THE EYE




FIG. 1

(57) Abstract: A method of deploying an ocular implant into Schlemm's canal of an eye. The method includes the steps of inserting a distal end of a cannula through a cornea of the eye and into an anterior chamber of the eye, the cannula having a distal opening extending from the distal end and through a side wall; placing the distal opening of the cannula into fluid communication with Schlemm's canal; advancing the ocular implant distally through the cannula with a delivery tool engaged with the ocular implant, a proximal portion of the ocular implant engaging the delivery tool proximal to a distal portion of the delivery tool; and disengaging the ocular implant and the delivery tool when the proximal portion of the ocular implant reaches the cannula distal opening. The invention also includes a system for practicing the method.

DELIVERING OCULAR IMPLANTS INTO THE EYE

FIELD

5 [0002] The present invention relates generally to the medical devices and treatments for the eye. More particularly, the present invention relates to systems, devices and methods for delivering ocular implants into the eye for treating glaucoma.

BACKGROUND

10 [0003] According to a draft report by The National Eye Institute (NEI) at The United States National Institutes of Health (NIH), glaucoma is now the leading cause of irreversible blindness worldwide and the second leading cause of blindness, behind cataract, in the world. Thus, the NEI draft report concludes, "it is critical that significant emphasis and resources continue to be devoted to determining the pathophysiology and management of this disease."
15 Glaucoma researchers have found a strong correlation between high intraocular pressure and glaucoma. For this reason, eye care professionals routinely screen patients for glaucoma by measuring intraocular pressure using a device known as a tonometer. Many modern tonometers make this measurement by blowing a sudden puff of air against the outer surface of the eye.

20 [0004] The eye can be conceptualized as a ball filled with fluid. There are two types of fluid inside the eye. The cavity behind the lens is filled with a viscous fluid known as vitreous humor. The cavities in front of the lens are filled with a fluid known as aqueous humor. Whenever a person views an object, he or she is viewing that object through both the vitreous humor and the aqueous humor.

25 [0005] Whenever a person views an object, he or she is also viewing that object through the cornea and the lens of the eye. In order to be transparent, the cornea and the lens can include no blood vessels. Accordingly, no blood flows through the cornea and the lens to provide nutrition

to these tissues and to remove wastes from these tissues. Instead, these functions are performed by the aqueous humor. A continuous flow of aqueous humor through the eye provides nutrition to portions of the eye (e.g., the cornea and the lens) that have no blood vessels. This flow of aqueous humor also removes waste from these tissues.

5 [0007] Aqueous humor is produced by an organ known as the ciliary body. The ciliary body includes epithelial cells that continuously secrete aqueous humor. In a healthy eye, a stream of aqueous humor flows out of the anterior chamber of the eye through the trabecular meshwork and into Schlemm's canal as new aqueous humor is secreted by the epithelial cells of the ciliary body. This excess aqueous humor enters the venous blood stream from Schlemm's canal and is
10 carried along with the venous blood leaving the eye.

[0008] When the natural drainage mechanisms of the eye stop functioning properly, the pressure inside the eye begins to rise. Researchers have theorized prolonged exposure to high intraocular pressure causes damage to the optic nerve that transmits sensory information from the eye to the brain. This damage to the optic nerve results in loss of peripheral vision. As
15 glaucoma progresses, more and more of the visual field is lost until the patient is completely blind.

[0009] In addition to drug treatments, a variety of surgical treatments for glaucoma have been performed. For example, shunts were implanted to direct aqueous humor from the anterior chamber to the extraocular vein (Lee and Scheppens, "Aqueous-venous shunt and intraocular pressure," Investigative Ophthalmology (Feb. 1966)). Other early glaucoma treatment implants
20 led from the anterior chamber to a sub-conjunctival bleb (e.g., US 4,968,296 and US 5,180,362). Still others were shunts leading from the anterior chamber to a point just inside Schlemm's canal (Spiegel et al., "Schlemm's canal implant: a new method to lower intraocular pressure in patients with POAG?" Ophthalmic Surgery and Lasers (June 1999); US 6,450,984; US 6,450,984).

25

SUMMARY OF THE DISCLOSURE

[00010] One aspect of the invention provides a method of deploying an ocular implant into Schlemm's canal of an eye. In some embodiments, the method includes the steps of inserting a distal end of a cannula through a cornea of the eye and into an anterior chamber of the eye, the
30 cannula having a distal opening extending from the distal end and through a side wall; placing the distal opening of the cannula into fluid communication with Schlemm's canal; advancing the ocular implant distally through the cannula with a delivery tool engaged with the ocular implant, a proximal portion of the ocular implant engaging the delivery tool proximal to a distal portion of the delivery tool; and disengaging the ocular implant and the delivery tool when the proximal
35 portion of the ocular implant reaches the cannula distal opening.

[00011] In some embodiments, the disengaging step includes the step of separating the distal portion of the delivery tool and the ocular implant from each other when the distal portion of the delivery tool passes through the distal opening of the cannula. In some such embodiments, the separating step is performed before the distal portion of the delivery tool reaches the distal end of the cannula. The separating step may include the step of maintaining contact between the ocular implant and the cannula and moving the distal portion of the delivery tool away from the cannula. In embodiments in which the distal portion of the delivery tool has an at-rest shape (such as, e.g., a curve having a smaller radius of curvature than a distal portion of the cannula), the separating step may also include the step of permitting the distal portion of the delivery tool to assume its at-rest shape.

[00012] In some embodiments, the inserting step includes the step of placing the distal end of the cannula in Schlemm's canal and a portion of the cannula distal opening outside of Schlemm's canal, the disengaging step including the step of disengaging the ocular implant and the delivery tool while the proximal portion of the ocular implant is disposed outside of Schlemm's canal. The disengaging step may also include the step of disengaging the ocular implant and the delivery tool while the proximal portion of the ocular implant is disposed inside the anterior chamber of the eye.

[00013] Some embodiments include the step of, after the disengaging step: re-engaging the delivery tool and the ocular implant; moving the delivery tool and the ocular implant in a proximal direction to withdraw at least a portion of the ocular implant from Schlemm's canal; advancing the ocular implant and delivery tool distally into Schlemm's canal; and disengaging the ocular implant and the delivery tool.

[00014] The method's disengaging step may also include the step of disengaging an interlocking portion of the delivery tool from a complementary interlocking portion of the ocular implant.

[00015] Another aspect of the invention provides a system with a cannula having a side wall defining a passageway, the cannula including an opening extending through a distal end and the side wall, the opening fluidly communicating with the passageway; an ocular implant disposed inside the passageway defined by the cannula; a delivery tool having a distal interlocking portion engaging a complementary interlocking portion of the ocular implant to form a mechanically interlocking connection when the interlocking portion of the delivery tool is proximal to the trough portion of the cannula.

[00016] In some embodiments, the distal interlocking portion of the delivery tool has an at-rest shape different from the shape of the cannula (such as, e.g., a curve having a smaller radius of curvature than a radius of curvature of the cannula), the cannula side wall preventing the

delivery tool from assuming its at-rest shape when the interlocking portion of the delivery tool is proximal to the trough portion of the cannula.

[00017] In some embodiments, the system also has a cannula subassembly including the cannula and a delivery tool subassembly including the delivery tool, the delivery tool subassembly and the cannula subassembly engaging one another at a keyed interface, the keyed interface being configured to permit the delivery tool to slide along the passageway defined by the cannula, and the keyed interface being configured to prohibit rotation of the delivery tool subassembly relative to the cannula subassembly so that a predetermined orientation between the delivery tool and the cannula is maintained.

[00018] In some embodiments, the delivery tool subassembly includes a rotating rack gear defining a shaped hole having a predetermined shape in lateral cross-section and the cannula subassembly including a shaped portion configured to cooperate with the shaped hole of the rotating rack gear so that the delivery tool is free to slide along the passageway defined by the cannula and rotation of the delivery tool relative to the cannula is prohibited.

[00019] In some embodiments, the opening extending through the distal end and the side wall of the cannula is dimensioned and positioned such that, when the ocular implant reaches a predefined location along the passageway, the delivery tool will move toward an undeformed shape in which the interlocking portion of the delivery tool disengages the complementary interlocking portion of the ocular implant to release the ocular implant. The delivery tool may also have a cannula wall engagement surface diametrically opposite the interlocking portion and a reduced diameter portion proximal to the interlocking portion.

[00020] In some embodiments, the mechanically interlocking connection is configured to preclude axial and/or movement of the ocular implant relative to the delivery tool. The mechanically interlocking connection may include a peak of the delivery tool that is received in a valley of the ocular implant or a peak of the ocular implant that is received in a valley of the delivery tool.

[00021] In some embodiments, the system also includes a motion control mechanism configured to be operated from a location outside of the eye to move the delivery tool and the ocular implant along the passageway defined by the cannula.

[00022] In some embodiments, a system configured to deliver an ocular implant into Schlemm's canal of an eye is provided, comprising a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion, and a delivery tool slidably insertable into the lumen of the cannula, the delivery tool having a distal interlocking portion configured to mechanically interlock with a proximal

interlocking portion of the ocular implant, the delivery tool being biased to bend radially through the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

[00023] In one embodiment, the delivery tool further comprises a ribbon portion proximal to the distal interlocking portion that is biased to assume a curved resting shape when no external forces are acting thereon.

[00024] In some embodiments, the ribbon portion is sized and configured to track along the widest part of an interior of the lumen of the cannula.

[00025] In other embodiments, a thickness of the ribbon portion is selected so as to enable the ribbon portion to preferentially bend along a preferential bending plane.

[00026] In alternative embodiments, the delivery tool is oriented within the cannula so that the preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula.

[00027] In some embodiments, the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than an inner diameter of the lumen of the cannula so that the distal interlocking portion can form a mechanically interlocking connection with the proximal interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

[00028] In another embodiment, the distal trough portion has a trough depth greater than a height of the ocular implant so that a distal end of the ocular implant will travel between an inner surface of the distal trough portion and tissue stretched over the distal trough portion as the ocular implant is advanced.

[00029] In alternative embodiments, the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

[00030] In one embodiment, the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the cannula.

[00031] In another embodiment, an ocular implant and delivery system, comprising an ocular implant sized and configured to be implanted inside Schlemm's canal of an eye, the ocular implant comprising a proximal interlocking portion, a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion, and a delivery tool slidably insertable into the lumen of the cannula, the delivery tool having a distal interlocking portion configured to mechanically interlock with the proximal interlocking portion of the ocular implant, the delivery tool being biased to bend radially through

the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

[00032] In one embodiment, the delivery tool further comprises a ribbon portion proximal to the distal interlocking portion that is biased to assume a curved resting shape when no external forces are acting thereon.

[00033] In some embodiments, the ribbon portion is sized and configured to track along the widest part of an interior of the lumen of the cannula.

[00034] In other embodiments, a thickness of the ribbon portion is selected so as to enable the ribbon portion to preferentially bend along a preferential bending plane.

[00035] In alternative embodiments, the delivery tool is oriented within the cannula so that the preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula.

[00036] In some embodiments, the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than an inner diameter of the lumen of the cannula so that the distal interlocking portion can form a mechanically interlocking connection with the proximal interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

[00037] In another embodiment, the distal trough portion has a trough depth greater than a height of the ocular implant so that a distal end of the ocular implant will travel between an inner surface of the distal trough portion and tissue stretched over the distal trough portion as the ocular implant is advanced.

[00038] In alternative embodiments, the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

[00039] In one embodiment, the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the cannula.

[00040] A system for delivering an ocular implant into Schlemm's canal of an eye, the ocular implant comprising a wall having a wall thickness is also provided, the system comprising a cannula comprising a cannula wall, the cannula wall including first portion and a second portion, both portions of the cannula wall extending along a longitudinal center axis having a curved portion, the first portion of the cannula wall being disposed on a radially inward side of the longitudinal center axis and the second portion of the cannula wall being disposed on radially outward side of the longitudinal center axis, the cannula wall defining a trough opening through the first portion of the cannula wall and a lumen extending from the trough to a proximal end of the cannula, the cannula wall being sized and configured so that the trough and the lumen define

a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the cannula is inside Schlemm's canal of the eye, a delivery tool extending into the lumen of the cannula, the delivery tool comprising a proximal portion, a distal interlocking portion, and a ribbon portion extending between the proximal portion and the distal interlocking portion, the distal interlocking portion of the delivery tool forming a mechanically interlocking connection with a complementary interlocking portion of the ocular implant when disposed in the lumen of the cannula, and the distal interlocking portion of the delivery tool moving through the trough opening of the cannula when the distal interlocking portion of the delivery tool reaches a predetermine location along the pathway so that the mechanically interlocking connection is broken.

[00041] In some embodiments, the ribbon portion of the delivery tool is biased to assume a curved resting shape when no external forces are acting thereon, the ribbon portion the delivery tool moves toward the curved resting shape when the delivery tool reaches the predetermined location along the pathway, and the interlocking portion of the delivery tool disengages the complementary interlocking portion of the ocular implant when the delivery tool is free to move toward the curved resting shape.

[00042] In other embodiments, the ribbon portion has an outer diameter and a thickness extending between a first major side of the ribbon portion and a second major side of the ribbon portion, and the outer diameter of the ribbon portion is only slightly smaller than the inner diameter of the cannula so that the ribbon portion tracks along the widest part of the cannula lumen and so that support provided by the cannula wall makes it less likely that ribbon portion will buckle.

[00043] In another embodiment, the outer diameter of the ribbon portion is smaller than the inner diameter of the cannula by a clearance value. In one embodiment, the clearance value is less than two times the wall thickness of the ocular implant. In other embodiments, the clearance value is between about 0.0005 inches and about 0.0010 inches.

[00044] In some embodiments, the thickness of the ribbon portion is selected so that the ribbon portion preferentially bends along a preferential bending plane. In another embodiment, an aspect ratio of the diameter to the thickness is selected so that the ribbon portion preferentially bends along a preferential bending plane.

[00045] In some embodiments, the delivery tool is oriented within the cannula so that a preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula, the curvature plane being defined by the central axis of the cannula.

[00046] In some embodiments, the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than the inner diameter of the cannula

so that the distal interlocking portion can form a mechanically interlocking connection with the complimentary interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

[00047] In some embodiments, the outer diameter of both the ocular implant and the distal interlocking portion of the delivery tool is smaller than the inner diameter of the cannula by a clearance value. In another embodiment, the clearance value is less than two times the wall thickness of the ocular implant. In another embodiment, the clearance value is between about 0.0005 inches and about 0.0010 inches.

[00048] In some embodiments, the trough opening has a width that is substantially equal to an inner diameter of the cannula and both the ribbon portion and the distal interlocking portion of the delivery tool have an outer diameter slightly smaller than the inner diameter of the cannula so that so that a distal portion of the delivery tool can pass through the trough opening when the delivery tool reaches the predetermined location along the pathway defined by the cannula.

[00049] In another embodiment, the outer diameter of both the ribbon portion and the distal interlocking portion of the delivery tool is smaller than the inner diameter of the cannula by a clearance value. In some embodiments, the clearance value is less than two times the wall thickness of the ocular implant. In other embodiments, the clearance value is between about 0.0005 inches and about 0.0010 inches.

[00050] In one embodiment, the trough has a trough depth greater than a height of the implant so that the distal end of the ocular implant will travel between an inner surface of the cannula and tissue stretched over the trough as the ocular implant is advanced along the path defined by the lumen and the trough.

[00051] In other embodiments, the trough is symmetrical about a curvature plane of the cannula so that the cannula can be used by both left handed users and right handed users in substantially the same way.

[00052] In an additional embodiment, the curved portion of the longitudinal central axis of the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

[00053] In some embodiments, the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the curved portion of the longitudinal central axis of the cannula.

[00054] In another embodiment, a delivery tool subassembly and a cannula subassembly of the system engage one another at a keyed interface, the keyed interface being configured to permit the delivery tool to slide along the passageway defined by the cannula and the keyed interface being configured to prohibit rotation of the delivery tool subassembly relative to the

cannula subassembly so that a coplanar relationship between a bending plane of the ribbon portion and a curvature plane of the cannula is maintained.

[00055] In one embodiment, the distal interlocking portion of the delivery tool engages the complementary interlocking portion of the ocular implant to form a mechanically interlocking connection when the distal interlocking portion of the delivery tool is disposed in the lumen of the cannula.

[00056] In another embodiment, the cannula wall holds the ribbon portion of the delivery tool in a deformed shape when the distal interlocking portion of the delivery tool is disposed in the lumen of the cannula.

[00057] A cannula for delivering an ocular implant into Schlemm's canal of an eye, the ocular implant having an implant height is provided, the cannula comprising a body comprising a first side and a second side, both sides of the body extending along a longitudinal center axis having a curved portion, the first side of the body being disposed on a radially inward side of the longitudinal center axis and the second side of the body being disposed on radially outward side of the longitudinal center axis, a tapered distal tip extending distally from the second side of the body, the body defining a trough that opens through the first side of the body and a lumen that extends from the trough to a proximal end of the body, the body being sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the tapered distal tip is inside Schlemm's canal of the eye, the tapered distal tip being shaped and configured to stretch Schlemm's canal tissues over a portion of the trough as the tapered distal tip is advanced into Schlemm's canal, and the trough having a trough depth greater than the implant height so that the distal end of the ocular implant will travel between an inner surface of the cannula and the tissue stretched over the trough as the ocular implant is advanced along the path defined by the lumen and the trough.

[00058] In some embodiments, the curved portion of the longitudinal central axis defines a curvature plane.

[00059] In other embodiments, the trough is symmetrical about the curvature plane. In an additional embodiment, the distal tip is symmetrical about the curvature plane.

[00060] In some embodiments, the trough comprises a first trough edge, a second trough edge, and an intermediate portion extending between the first trough edge and the second trough edge, the intermediate portion having a semi-circular transverse cross-sectional shape.

[00061] In another embodiment, the tip portion comprises a first leading edge, a second leading edge, and a semi-circular transverse cross-section extending between the first leading edge and the second leading edge.

[00062] In one embodiment, a tip chord extending between the first leading edge and the second leading edge has a chord length that increases as the tip portion extends proximally from a distal point thereof.

5 [00063] In some embodiments, the first leading edge has a first length and the second leading edge has a second length that is substantially equal to the first length.

[00064] In other embodiments, the first leading edge and the second leading edge extend between an inside surface of the body and an outside surface of the body.

[00065] In another embodiment, the inside surface of the body comprises a concave surface and the outside surface of the body comprises a convex surface.

10 [00066] In some embodiments, the first leading edge and the second leading edge both distally converge toward the distal point so that the tapered distal tip is generally V-shaped when viewed in plan.

[00067] In an additional embodiment, the distal point of the tip portion is sufficiently blunt to slide along the outer major wall of Schlemm's canal without cutting scleral tissue underlying the
15 outer major wall of Schlemm's canal.

[00068] In some embodiments, at least a portion of the body is tubular.

[00069] In another embodiment, a curved portion of the body is shaped and dimensioned to be received inside the anterior chamber while a tubular portion of the body is extending through an incision in the dome shaped wall and the distal point of the body is inside Schlemm's canal.

20 [00070] In some embodiments, the curved portion of the longitudinal central axis has a radius of curvature that is substantially constant along a length thereof.

[00071] In another embodiment, the curved portion of the longitudinal central axis has a radius of curvature that varies along a length thereof.

[00072] In another embodiment, the curved portion of the longitudinal central axis has a
25 radius of curvature that is smaller than a radius of curvature of the ocular implant.

[00073] In some embodiments, the body has a curved portion extending to the distal tip.

[00074] In some embodiments, the curved portion of the body has an angular span greater than 90 degrees.

[00075] In another embodiment, the curved portion of the body has an angular span of about
30 140.

[00076] In an additional embodiment, the trough depth extends between an inner surface of the body and a chord extending between a first trough edge and a second trough edge.

[00076a] In one aspect, there is provided a method of deploying an ocular implant into Schlemm's canal of an eye, comprising: inserting a distal end of a curved distal portion of a cannula through a cornea of the eye and into an anterior chamber of the eye, the cannula comprising a distal opening and a trough extending from the distal end and through a side wall; placing the distal opening of the cannula into fluid communication with Schlemm's canal; advancing the ocular implant distally through the cannula with a delivery tool engaged with the ocular implant, a proximal portion of the ocular implant engaging the delivery tool proximal to a distal portion of the delivery tool, the delivery tool having a curved at-rest shape with a smaller radius of curvature than the radius of curvature of the distal portion of the cannula; and disengaging the ocular implant and the delivery tool when the proximal portion of the ocular implant reaches the cannula distal opening by permitting the delivery tool to move toward its at-rest shape.

[00076b] In another aspect, there is provided a system comprising: a cannula having a side wall defining a passageway, the cannula having a curved distal portion extending between a distal end and a proximal portion along a radius of curvature, the cannula including an opening extending through the distal end and the side wall to form a trough portion, the opening fluidly communicating with the passageway; an ocular implant disposed inside the passageway defined by the cannula; and a delivery tool having a distal interlocking portion engaging a complementary interlocking portion of the ocular implant to form a mechanically interlocking connection when the interlocking portion of the delivery tool is proximal to the trough portion of the cannula, the delivery tool distal interlocking portion having a curved at-rest shape having a smaller radius of curvature than the radius of curvature of the cannula distal portion, the cannula side wall preventing the delivery tool distal interlocking portion from assuming its at-rest shape when the delivery tool distal interlocking portion is proximal to the trough portion of the cannula.

[00076c] In another aspect, there is provided a system configured to deliver an ocular implant into Schlemm's canal of an eye, comprising: a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion; and a delivery tool slidably insertable into the lumen of the cannula, the

delivery tool having a distal interlocking portion configured to mechanically interlock with a proximal interlocking portion of the ocular implant, the delivery tool being biased to bend radially through the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

[00076d] In another aspect, there is provided an ocular implant and delivery system, comprising: an ocular implant sized and configured to be implanted inside Schlemm's canal of an eye, the ocular implant comprising a proximal interlocking portion; a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion; and a delivery tool slidably insertable into the lumen of the cannula, the delivery tool having a distal interlocking portion configured to mechanically interlock with the proximal interlocking portion of the ocular implant, the delivery tool being biased to bend radially through the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

[00076e] In another aspect, there is provided a system for delivering an ocular implant into Schlemm's canal of an eye, the ocular implant comprising a wall having a wall thickness, the system comprising: a cannula comprising a cannula wall, the cannula wall including first portion and a second portion, both portions of the cannula wall extending along a longitudinal center axis having a curved portion, the first portion of the cannula wall being disposed on a radially inward side of the longitudinal center axis and the second portion of the cannula wall being disposed on radially outward side of the longitudinal center axis; the cannula wall defining a trough opening through the first portion of the cannula wall and a lumen extending from the trough to a proximal end of the cannula, the cannula wall being sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the cannula is inside Schlemm's canal of the eye; a delivery tool extending into the lumen of the cannula, the delivery tool comprising a proximal portion, a distal interlocking portion, and a ribbon portion extending between the proximal portion and the distal interlocking portion; the distal

interlocking portion of the delivery tool forming a mechanically interlocking connection with a complementary interlocking portion of the ocular implant when disposed in the lumen of the cannula; and the distal interlocking portion of the delivery tool moving through the trough opening of the cannula when the distal interlocking portion of the delivery tool reaches a
 5 predetermine location along the pathway so that the mechanically interlocking connection is broken.

[00076f] In another aspect, there is provided a cannula for delivering an ocular implant into Schlemm's canal of an eye, the ocular implant having an implant height, the cannula comprising: a body comprising a first side and a second side, both sides of the body extending
 10 along a longitudinal center axis having a curved portion, the first side of the body being disposed on a radially inward side of the longitudinal center axis and the second side of the body being disposed on radially outward side of the longitudinal center axis; a tapered distal tip extending distally from the second side of the body; the body defining a trough that opens through the first side of the body and a lumen that extends from the trough to a proximal end
 15 of the body, the body being sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the tapered distal tip is inside Schlemm's canal of the eye; the tapered distal tip being shaped and configured to stretch Schlemm's canal tissues over a portion of the trough as the tapered distal tip is advanced into Schlemm's canal; and the trough having a
 20 trough depth greater than the implant height so that the distal end of the ocular implant will travel between an inner surface of the cannula and the tissue stretched over the trough as the ocular implant is advanced along the path defined by the lumen and the trough.

[00076g] In another aspect, there is provided a method of delivering an ocular implant into Schlemm's canal of an eye, the method comprising: inserting a distal end of a cannula
 25 into Schlemm's canal so that Schlemm's canal wall tissue extends over a trough portion of the cannula; and advancing the ocular implant distally through a cannula lumen into the trough portion of the cannula below the Schlemm's canal wall tissue and further distally into Schlemm's canal, the ocular implant having a height less than a depth of the trough portion.

BRIEF DESCRIPTION OF THE DRAWINGS

[00077] Figure 1 is a stylized representation of a medical procedure in accordance with this detailed description.

5 [00078] Figure 2 is an enlarged perspective view further illustrating the delivery system and the eye shown in Figure 1.

[00079] Figure 3 is a stylized perspective view illustrating the anatomy of an eye.

[00080] Figure 4 is a stylized perspective view showing Schlemm's canal and an iris of the eye shown in the previous figure.

10 [00081] Figure 5 is an enlarged cross-sectional view further illustrating Schlemm's canal SC shown in the previous figure.

[00082] Figure 6A is a perspective view showing a delivery system including an ocular implant and a cannula defining a passageway that is dimensioned to slidably receive the ocular implant.

15 [00083] Figure 6B is an enlarged detail view further illustrating the ocular implant and the cannula 108 shown in Figure 6A.

[00084] Figure 7 is a perspective view further illustrating delivery system 100 shown in Figure 6.

[00085] Figure 8 is an exploded view illustrating various elements of a delivery system in accordance with the detailed description.

20 [00086] Figure 8A is an end view of the rotating rack gear shown in Figure 8.

[00087] Figure 9 is an exploded perspective view further illustrating the delivery tool subassembly shown in the exploded perspective view of Figure 8.

[00088] Figure 10 is an exploded perspective view further illustrating the cannula subassembly shown in the exploded perspective view of Figure 8.

25 [00089] Figure 11 is a cross-sectional view showing an assembly including both the delivery tool subassembly and the cannula subassembly shown in the exploded perspective view of Figure 8.

[00090] Figure 12 is a perspective view of a cannula in accordance with the detailed description.

30 [00091] Figure 13 is a perspective view of an assembly including the cannula shown in Figure 12 and an ocular implant that is resting in a passageway defined by the cannula.

[00092] Figure 14 is a stylized perspective view including the assembly shown in Figure 13.

[00093] Figure 15 is an enlarged perspective view showing a portion of the cannula shown in the assembly of Figure 14.

[00094] Figure 16 is an additional perspective view showing the ocular implant and the cannula shown in the previous Figure.

[00095] Figure 17 is an additional perspective view showing the ocular implant and the cannula shown in Figure 16.

5 [00096] Figure 18 is an additional perspective view showing the ocular implant and the cannula shown in Figures 16 and 17.

[00097] Figure 19 is a perspective view of Schlemm's canal after the cannula shown in Figure 18 has been withdrawn leaving an inlet portion of the ocular implant in the anterior chamber of the eye and the remainder of ocular implant in Schlemm's canal.

10 [00098] Figures 20A - Figure 20H are a series of stylized plan views illustrating example methods in accordance with the detailed description and associated apparatus used while performing those methods.

[00099] Figure 21 is a perspective view showing a delivery tool subassembly 370 that may be part of a delivery system (e.g., the delivery system shown in Figure 8).

15 [000100] Figure 22A is a stylized plan view further illustrating the delivery tool shown in Figure 21. Figure 22B is an additional stylized plan view illustrating the cannula, ocular implant, and delivery tool shown in Figure 22A.

[000101] Figure 23 is a stylized plan view showing a delivery system including an ocular implant disposed in a passageway defined by a cannula.

20 [000102] Figure 24A is a stylized plan view further illustrating the cannula shown in Figure 23. Figure 24B is an additional stylized plan view illustrating the cannula, ocular implant, and delivery tool shown in Figure 24A.

[000103] Figure 25A is a perspective view showing a delivery tool subassembly that may be part of a delivery system (e.g., the delivery system shown in Figure 8). Figure 25B is a
25 perspective view of the distal end of the delivery tool of this embodiment.

[000104] Figure 26A is a stylized perspective view showing a cannula having a distal portion positioned so as to extend through the wall of Schlemm's canal. An ocular implant is shown extending out a distal opening of the cannula and into Schlemm's canal. Figure 26B is an additional perspective view showing the ocular implant and the cannula shown in Figure 26A.

30 [000105] Figure 27A is a top view showing a cannula and a delivery tool.

[000106] Figure 27B is a cross-sectional view of cannula taken along section line B-B shown in Figure 27A.

[000107] Figure 27C, Figure 27D and Figure 27E are cross-sectional views of delivery tool shown in the previous figure.

[000108] Figure 27F is a cross-sectional view of an ocular implant taken along section line F-F shown in Figure 27A.

[000109] Figure 27G is an isometric view showing a distal portion of the delivery tool.

5 [000110] Figure 27H is a perspective view of an assembly including a cannula, delivery tool and ocular implant.

[000111] Figure 27I is a cross-sectional view of a cannula and delivery tool taken along section line i-i shown in Figure 27H.

[000112] Figure 27J is a perspective view showing an assembly including a cannula and a distal portion of a delivery tool.

10 [000113] Figure 28 is a perspective view of a cannula.

[000114] Figure 29A and Figure 29B are plan views of the cannula shown in the previous figure.

[000115] Figure 30A is an additional top view of the cannula shown in the previous figure.

15 [000116] Figure 30B is a stylized cross-sectional view taken along cutting plane B-B shown in Figure 30A.

[000117] Figure 31 is a cross-sectional view further illustrating the cannula shown in the previous figure.

[000118] Figure 32 is perspective view further illustrating the anatomy of the eye.

20 [000119] Figure 33 is a perspective view showing selected structures from the eye shown in the previous figure.

[000120] Figure 34 is an additional perspective view of the ocular structures shown in the previous figure.

[000121] Figure 35 is an additional perspective view showing the ocular implant and cannula shown in the previous figure.

25 [000122] Figure 36 is an additional stylized perspective view showing the ocular implant and cannula.

[000123] Figure 37 is an additional stylized perspective view showing the ocular implant and cannula.

[000124] Figure 38A is a plan view showing a delivery system housing held in a left hand LH.

30 [000125] Figure 38B is a plan view showing a delivery system housing held in a right hand RH.

DETAILED DESCRIPTION

[000126] The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are

not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

[000127] Figure 1 is a stylized representation of a medical procedure in accordance with this detailed description. In the procedure of Figure 1, a physician is treating an eye 20 of a patient P. In the procedure of Figure 1, the physician is holding a hand piece of a delivery system 70 in his or her right hand RH. The physician's left hand (not shown) may be used to hold the handle H of a gonio lens 23. Alternatively, some physicians may prefer holding the delivery system hand piece in the left hand and the gonio lens handle H in the right hand RH.

[000128] During the procedure illustrated in Figure 1, the physician may view the interior of the anterior chamber using gonio lens 23 and a microscope 25. Detail A of Figure 1 is a stylized simulation of the image viewed by the physician. A distal portion of a cannula 72 is visible in Detail A. A shadow-like line indicates the location of Schlemm's canal SC which is lying under various tissues (e.g., the trabecular meshwork) that surround the anterior chamber. A distal opening 74 of cannula 72 is positioned near Schlemm's canal SC of eye 20.

[000129] Methods in accordance with this detailed description may include the step of advancing the distal end of cannula 72 through the cornea of eye 20 so that a distal portion of cannula 72 is disposed in the anterior chamber of the eye. Cannula 72 may then be used to access Schlemm's canal of the eye, for example, by piercing the wall of Schlemm's canal with the distal end of cannula 72. Distal opening 74 of cannula 72 may be placed in fluid communication with a lumen defined by Schlemm's canal. The ocular implant may be advanced out of distal opening 74 and into Schlemm's canal. Insertion of the ocular implant into Schlemm's canal may facilitate the flow of aqueous humor out of the anterior chamber of the eye.

[000130] Figure 2 is an enlarged perspective view further illustrating delivery system 50 and eye 20 shown in the previous figure. In Figure 2, cannula 56 of delivery system 50 is shown extending through a cornea 26 of eye 20. A distal portion of cannula 56 is disposed inside the anterior chamber defined by cornea 26 of eye 20. In the embodiment of Figure 2, cannula 56 is configured so that a distal opening 58 of cannula 56 can be placed in fluid communication with Schlemm's canal.

[000131] In the embodiment of Figure 2, an ocular implant is disposed in a passageway defined by cannula 56. Delivery system 50 includes a mechanism that is capable of advancing and retracting the ocular implant along the length of cannula 56. The ocular implant may be placed in Schlemm's canal of eye 20 by advancing the ocular implant through the distal opening of cannula 56 while the distal opening is in fluid communication with Schlemm's canal.

[000132] Figure 3 is a stylized perspective view illustrating a portion of eye 20 discussed above. Eye 20 includes an iris 30 defining a pupil 32. In Figure 3, eye 20 is illustrated in a cross-sectional view created by a cutting plane passing through the center of pupil 32. Eye 20 can be conceptualized as a fluid filled ball having two chambers. Sclera 34 of eye 20 surrounds a posterior chamber PC filled with a viscous fluid known as vitreous humor. Cornea 36 of eye 20 encloses an anterior chamber AC that is filled with a fluid known as aqueous humor. The cornea 36 meets the sclera 34 at a limbus 38 of eye 20. A lens 40 of eye 20 is located between anterior chamber AC and posterior chamber PC. Lens 40 is held in place by a number of ciliary zonules 42.

[000133] Whenever a person views an object, he or she is viewing that object through the cornea, the aqueous humor, and the lens of the eye. In order to be transparent, the cornea and the lens can include no blood vessels. Accordingly, no blood flows through the cornea and the lens to provide nutrition to these tissues and to remove wastes from these tissues. Instead, these functions are performed by the aqueous humor. A continuous flow of aqueous humor through the eye provides nutrition to portions of the eye (e.g., the cornea and the lens) that have no blood vessels. This flow of aqueous humor also removes waste from these tissues.

[000134] Aqueous humor is produced by an organ known as the ciliary body. The ciliary body includes epithelial cells that continuously secrete aqueous humor. In a healthy eye, a stream of aqueous humor flows out of the eye as new aqueous humor is secreted by the epithelial cells of the ciliary body. This excess aqueous humor enters the blood stream and is carried away by venous blood leaving the eye.

[000135] Schlemm's canal SC is a tube-like structure that encircles iris 30. Two laterally cut ends of Schlemm's canal SC are visible in the cross-sectional view of Figure 3. In a healthy eye, aqueous humor flows out of anterior chamber AC and into Schlemm's canal SC. Aqueous humor exits Schlemm's canal SC and flows into a number of collector channels. After leaving Schlemm's canal SC, aqueous humor is absorbed into the venous blood stream and carried out of the eye.

[000136] Figure 4 is a stylized perspective view showing Schlemm's canal SC and iris 30 of eye 20 shown in the previous figure. In Figure 4, Schlemm's canal SC is shown encircling iris 30. With reference to Figure 4, it will be appreciated that Schlemm's canal SC may overhang iris 30 slightly. Iris 30 defines a pupil 32. In the embodiment of Figure 4, Schlemm's canal SC and iris 30 are shown in cross-section, with a cutting plane passing through the center of pupil 32.

[000137] The shape of Schlemm's canal SC is somewhat irregular, and can vary from patient to patient. The shape of Schlemm's canal SC may be conceptualized as a cylindrical-tube that has

been partially flattened. With reference to Figure 4, it will be appreciated that Schlemm's canal SC has a first major side 50, a second major side 52, a first minor side 54, and a second minor side 56.

[000138] Schlemm's canal SC forms a ring around iris 30 with pupil 32 disposed in the center of that ring. With reference to Figure 4, it will be appreciated that first major side 50 is on the outside of the ring formed by Schlemm's canal SC and second major side 52 is on the inside of the ring formed by Schlemm's canal SC. Accordingly, first major side 50 may be referred to as an outer major side of Schlemm's canal SC and second major side 52 may be referred to as an inner major side of Schlemm's canal SC. With reference to Figure 4, it will be appreciated that first major side 50 is further from pupil 32 than second major side 52. The outer major wall of Schlemm's canal is supported by scleral tissue of the eye. Elevated pressure inside the eye of a patient suffering from glaucoma may cause the inside major wall of Schlemm's canal to be pressed against the outer major wall of the canal.

[000139] Figure 5 is an enlarged cross-sectional view further illustrating Schlemm's canal SC shown in the previous figure. With reference to Figure 5, Schlemm's canal SC comprises a wall W defining a lumen 58. The shape of Schlemm's canal SC is somewhat irregular and can vary from patient to patient. The shape of Schlemm's canal SC may be conceptualized as a cylindrical-tube that has been partially flattened. The cross-sectional shape of lumen 58 may be compared to the shape of an ellipse. A major axis 60 and a minor axis 62 of lumen 58 are illustrated with dashed lines in Figure 5.

[000140] The length of major axis 60 and minor axis 62 can vary from patient to patient. The length of minor axis 62 is between one and thirty micrometers in most patients. The length of major axis 60 is between one hundred and fifty micrometers and three hundred and fifty micrometers in most patients.

[000141] With reference to Figure 5, Schlemm's canal SC comprises a first major side 50, a second major side 52, a first minor side 54, and a second minor side 56. In the embodiment of Figure 5, first major side 50 is longer than both first minor side 54 and second minor side 56. Also in the embodiment of Figure 5, second major side 52 is longer than both first minor side 54 and second minor side 56.

[000142] Figure 6A is a perspective view showing a delivery system 100 including an ocular implant 150 and a cannula 108 defining a passageway that is dimensioned to slidably receive ocular implant 150. Delivery system 100 may be used to advance ocular implant 150 into a target location in the eye of a patient. Examples of target locations that may be suitable in some applications include areas in and around Schlemm's canal, the trabecular meshwork, the

suprachoroidal space, and the anterior chamber of the eye. Figure 6B is an enlarged detail view further illustrating ocular implant 150 and cannula 108 of delivery system 100.

[000143] Delivery system 100 of Figure 6A is capable of controlling the advancement and retraction of ocular implant 150 within cannula 108. Ocular implant 150 may be placed in a target location (e.g., Schlemm's canal) by advancing the ocular implant through a distal opening 132 of cannula 108 while the distal opening is in fluid communication with Schlemm's canal. In the embodiment of Figure 6A, ocular implant 150 has been advanced through distal opening 132 of cannula 108 for purposes of illustration.

[000144] Delivery system 100 of Figure 6A includes a housing 102, a sleeve 104, and an end cap 110. A tracking wheel 106 extends through a wall of housing 102 in Figure 6A. Tracking wheel 106 is part of a mechanism that is capable of advancing and retracting a delivery tool 152 of delivery system 100. The delivery tool 152 extends through a distal opening of cannula 108 of Figure 6B. Rotating the tracking wheel will cause delivery tool 152 to move in an axial direction along a passageway defined by cannula 108. The axial direction may be in a distal direction D or a proximal direction P.

[000145] In the embodiment of Figure 6A, housing 102 is configured to be gripped with one hand while providing control over the axial advancement and retraction of ocular implant via tracking wheel 106. The housing of delivery system 100 results in an advantageous ergonomic relationship of the fingers relative to the hand. This design provides a configuration that will allow a user, such as a physician, to stabilize the device using part of the hand, while leaving the middle or index finger free move independently from the remainder of the hand. The middle or index finger is free to move independently to rotate the wheel for advancing and/or retract the ocular implant.

[000146] Figure 6B is an enlarged detail view further illustrating ocular implant 150 and a cannula 108 of delivery system 100. Cannula 108 comprises a generally tubular member 198 having proximal portion 140, a distal end 134, and a distal portion 144 extending between distal end 134 and proximal portion 140. In the embodiment of Figure 6, distal portion 144 is curved. In some useful embodiments, distal portion 144 is dimensioned and configured to be received in the anterior chamber of the eye.

[000147] Figure 6B shows delivery tool 152 of delivery system 100 extending through distal opening 132 of cannula 108. Delivery tool 152 includes an interlocking portion 160 that is configured to form a connection with a complementary interlocking portion 162 of ocular implant 150, as explained in more detail below. In the embodiment of Figure 6, rotating the tracking wheel will cause delivery tool 152 and ocular implant 150 to move along a path defined by cannula 108. Cannula 108 is sized and configured so that the distal end of cannula 108 can be

advanced through the trabecular meshwork of the eye and into Schlemm's canal. Positioning cannula 108 in this way places distal opening 132 in fluid communication with Schlemm's canal. Ocular implant 150 may be placed in Schlemm's canal by advancing the ocular implant through distal opening 132 of cannula 108 while the distal opening is in fluid communication with

5 Schlemm's canal. The distal portion of the cannula may include a cutting portion configured to cut through the trabecular meshwork and the wall of Schlemm's canal, such as by providing distal end 134 with a sharp edge adapted to cut through such tissue.

[000148] Figure 7 is a perspective view further illustrating delivery system 100 shown in the previous figure. In Figure 7, a portion of housing 102 has been removed for purposes of

10 illustration. Delivery system 100 includes a delivery tool subassembly 170 and a cannula subassembly 180. Delivery tool subassembly 170 includes rotating rack gear 120 and a delivery tool (not shown). In the embodiment of Figure 7, the delivery tool extends into a passageway defined by a cannula 108. Cannula 108 can be seen extending beyond sleeve 104 in Figure 7. Cannula subassembly 180 includes cannula 108, a hub 172, and an extension tube (not shown).

15 In the embodiment of Figure 7, the extension tube of cannula subassembly 180 is disposed inside a lumen defined by rotating rack gear 120.

[000149] Delivery system 100 includes a mechanism 166 that controls the movement of delivery tool subassembly 170. Mechanism 166 includes a number of components that are located inside housing 102, including tracking wheel 106, an idler gear 122, and the rotating rack gear 120. In the embodiment of Figure 7, tracking wheel 106 and idler gear 122 are both

20 rotatably supported by housing 102. Gear teeth on tracking wheel 106 engage gear teeth on idler gear 122, which in turn engage gear teeth on the rotating rack gear 120. Rotating tracking wheel 106 in a counter clockwise direction CCW causes idler gear 122 to rotate in a clockwise direction CW, which in turn causes the rotating rack gear 120 to move in a distal direction D.

25 Rotating tracking wheel 106 in a clockwise direction CW causes idler gear 122 to rotate in a counter clockwise direction CCW, which in turn causes the rotating rack gear 120 to move in a proximal direction P. In other embodiments, the idler gear may be eliminated from the device, which would cause counter-clockwise movement of the tracking wheel to move the rack gear proximally.

30 [000150] In the embodiment of Figure 7, a sleeve 104 is fixed to cannula subassembly 180. Sleeve 104 may be rotated by the user to change the orientation of cannula 108 with respect to housing 102. The sleeve 104 may include gripping features, such as grooves (as shown), a rubber coating, or other frictional surfaces to facilitate this use. In some applications, correct alignment between the cannula and iris is advantageous to ensure that the core tube and/or ocular

35 implant is advanced at the correct trajectory relative to Schlemm's canal or other anatomy in the

eye into which the ocular implant is to be implanted. The device is configured in a manner that keeps the ocular implant aligned within the device during rotation. Selected groups of components are keyed together to ensure that they rotate as a single body while simultaneously allowing axial movement of the ocular implant. In the embodiment of Figure 7, cannula subassembly 180 and delivery tool subassembly 170 rotate in unison with sleeve 104 relative to housing 102.

[000151] In the embodiment of Figure 7, rotating rack gear 120 is configured to rotate with sleeve 104 while maintaining the ability to move axially in the distal and proximal directions before, during, and after rotation. As the rotating rack gear 120 moves distally and/or proximally, it causes corresponding movement of the delivery tool relative to cannula 108. This movement is transferred to ocular implant 150 when delivery tool 152 is coupled to ocular implant 150. Delivery tool subassembly 170 and cannula subassembly 180 engage one another in a keyed arrangement, as described in more detail below. This keyed arrangement causes delivery tool subassembly 170 and cannula subassembly 180 to maintain a constant rotational orientation relative to each other while, at the same time, allowing delivery tool subassembly 170 to translate in a distal direction D and a proximal direction P relative to cannula subassembly 180.

[000152] Figure 8 is an exploded view illustrating various elements of delivery system 100. Cannula subassembly 180 includes a hub 172 and an extension tube 174 that are both fixed to cannula 108. Extension tube 174 includes a shaped portion 175 that is dimensioned and shaped to fit within a shaped through hole 177 (shown in Figures 8A and 11) within by rotating rack gear 120. This keyed arrangement causes delivery tool subassembly 170 and cannula subassembly 180 to maintain a constant rotational orientation relative to each other while, at the same time, allowing delivery tool subassembly 170 to translate in a distal direction D and a proximal direction P relative to cannula subassembly 180.

[000153] In some embodiments, delivery tool 152 is formed from shape memory material (such as, e.g., nitinol), and at least a portion of delivery tool 152 assumes a curved at-rest shape when no external forces are acting on it. Delivery tool 152 can be urged to assume a straightened shape, for example, by inserting delivery tool 152 through a straight portion of the passageway defined by cannula 108. When the delivery tool is confined, such as within cannula 108, the interlocking portion can engage the complementary interlocking portion to join the delivery tool and ocular implant together, and allow the delivery tool and ocular implant to move together through the cannula 108, as described in more detail below.

[000154] Delivery system 100 also includes an O-ring 126 disposed between sleeve and 104 and housing 102. O-ring 126 can provide friction and/or resistance between sleeve 104 and

housing 102. This friction and/or resistance may be useful, for example, to hold the sleeve 104 in a desired orientation. A noseplug 105 snaps into the distal end of the delivery system.

[000155] Figure 9 is an exploded perspective view of delivery tool subassembly 170 shown in the previous figure. Delivery tool subassembly 170 comprises a delivery tool 152, a rotating rack gear 120, and a spacer 176. Delivery tool 152 includes a shaped proximal portion 156, a curved distal portion 153, a distal cannula engagement surface 161 and a reduced diameter portion 163 proximal to the distal cannula engagement surface 161. Spacer 176 is interposed between rotating rack gear 120 and shaped proximal portion 156 of delivery tool 152 to hold delivery tool 152 and rotating rack gear 120 in a generally co-axial arrangement when delivery tool subassembly 170 is in an assembled state, as shown in Figure 11. Distal cannula engagement surface 161 is adapted to slide along an inside surface of the cannula wall while the delivery tool 152 is engaged to ocular implant 150. Curved distal portion 153 of delivery tool 152 has an at rest curve that is greater (i.e., has a smaller radius of curvature) than the curved portion 144 of cannula 108.

[000156] Figure 10 is an exploded perspective view of cannula subassembly 180. Cannula subassembly 180 comprises cannula 108, extension tube 174 and hub 172. In the embodiment of Figure 10, cannula 108 defines a passageway 138 that is dimensioned to slidably receive an ocular implant and the delivery tool shown in the previous figure. At the same time, extension tube 174 of cannula subassembly 180 may be received inside a lumen defined by the rotating rack gear shown in the previous figure.

[000157] Extension tube 174 includes a shaped portion 175 that is dimensioned and shaped to fit within a shaped through hole defined by rotating rack gear 120, as shown below in Figure 11. This keyed arrangement causes delivery tool subassembly 170 and cannula subassembly 180 to maintain a constant rotational orientation relative to each other while, at the same time, allowing delivery tool subassembly 170 to translate in a distal direction D and a proximal direction P relative to cannula subassembly 180.

[000158] Figure 11 is a cross-sectional view showing an assembly including delivery tool subassembly 170 and cannula subassembly 180 discussed above. Delivery tool subassembly 170 includes a delivery tool 152, a rotating rack gear 120 and a spacer 176. In the cross-sectional view of Figure 11, a shaped portion 156 of delivery tool 152 can be seen extending into a slot 123 extending from a central portion 181 a through hole 177 formed in rotating rack gear 120. (Figure 8A shows an end view of rotating rack gear 120 and through hole 177.) In the embodiment of Figure 11, an interlocking portion 160 of delivery tool 152 is disposed in angular alignment with shaped portion 156. Spacer 176 is interposed between rotating rack gear 120 and delivery tool 152. In the exemplary embodiment of Figure 11, spacer 176 is shaped and

dimensioned to hold delivery tool 152 and rotating rack gear in a generally co-axial arrangement. This arrangement creates an advantageous oriented relationship of interlocking portion 160 with respect to the distal opening 132 of cannula 108 and ensures that interlocking portion 160 is unimpeded and readily disengages itself from the implant when it exits and flexes through distal opening 132. In the exemplary embodiment of Figure 11, spacer 176 and rotating rack gear 120 are fixed to each other at a weld joint 178. Weld joint 178 may be formed, for example, using a laser welding process.

[000159] Cannula subassembly 180 includes cannula 108, a hub 172, and an extension tube 174. Extension tube 174 is disposed about cannula 108. Extension tube 174 and cannula 108 may be fixed to one another, for example, using a laser spot welding process. Hub 172 is fixed to an outer surface portion of extension tube 174 in the embodiment of Figure 11. In Figure 11, extension tube 174 of cannula subassembly 180 can be seen extending into a shaped through-hole defined by rotating rack gear 120 of delivery tool assembly 170.

[000160] In Figure 11, delivery tool 152 can be seen extending into a passageway 138 defined by a cannula 108 of cannula subassembly 180. Passageway 138 defined by cannula 108 is sized to slidably enclose delivery tool 152 and an ocular implant that is coupled to delivery tool 152. Delivery tool 152 is configured to form a connection with the ocular implant, so that distal movement of the delivery tool can cause distal movement of the ocular implant within cannula 108. Delivery tool 152 may be used to advance the ocular implant through a distal opening 132 of cannula 108 in order to deliver the ocular implant into the eye. The assembly of Figure 11 may be rotated by the user to change the orientation of the curved portion of cannula 108 with respect to the housing of the delivery system. The keyed relationship between delivery tool subassembly 170 and cannula subassembly 180 assures that the rotational orientation between cannula 108 and the ocular implant/delivery tool stays constant while at the same time, allowing ocular implant/delivery tool to translate in a distal direction D and a proximal direction P relative to cannula 108.

[000161] Figure 12 is a perspective view of a cannula 108 in accordance with the present detailed description. Cannula 108 of Figure 12 comprises a generally tubular member 198 having a central axis 196. Generally tubular member 198 of Figure 12 comprises a proximal portion 140, a distal end 134, and a distal portion 144 extending between distal end 134 and proximal portion 140. A distal opening surface 142 surrounds a distal opening 132 extending through the distal end and through a side wall of cannula 108. A beveled edge 165 is disposed at the distal end of distal opening surface 142, extending from the distal end 134 to a proximal extent 167 of beveled edge 165. Tubular member 198 defines distal opening 132, a proximal

opening 136, and a passageway 138 extending between proximal opening 136 and distal opening 132.

[000162] In the embodiment of Figure 12, proximal portion 140 of cannula 108 is substantially straight, distal portion 144 of cannula 108 is curved, and central axis 196 defines a curvature plane 148. Curvature plane 148 may be referred to as a plane of curvature. Curvature plane 148 divides cannula 108 into a first portion PA and a second portion PB. In the embodiment of Figure 12, second portion PB is substantially a mirror image of first portion PA. In Figure 12, distal portion 144 is shown extending between distal end 134 and proximal portion 140 with no intervening elements. In the embodiment of Figure 12, distal portion 144 is curved along its entire length.

[000163] A method in accordance with this detailed description may include the step of advancing the distal end 134 of cannula 108 through the cornea of a human eye so that distal end 134 is disposed in the anterior chamber of the eye. Cannula 108 may then be used to access Schlemm's canal of the eye, for example, by piercing the wall of Schlemm's canal with the distal end 134 of cannula 108. The beveled edge 165 may be inserted into Schlemm's canal to place at least part of distal opening 132 of cannula 108 in communication with Schlemm's canal, as discussed in more detail below. The ocular implant may be advanced out of a distal port of the cannula and into Schlemm's canal.

[000164] In the embodiment of Figure 12, distal portion 144 of cannula 108 defines a trough 154. In some useful embodiments, trough 154 is configured to receive the entire external cross section of an ocular implant as the ocular implant is being advanced into Schlemm's canal. When this is the case, trough 154 may have a depth dimension that is deeper than a width of the ocular implant. This cannula configuration advantageously prevents the ocular implant from intersecting the layers of the trabecular meshwork as the ocular implant is advanced into Schlemm's canal. Trough 154 may also be configured to allow the proximal portion of the ocular implant to be released from the delivery tool, as discussed below.

[000165] Figure 13 is a perspective view of an assembly including cannula 108 shown in the previous figure. For purposes of illustration, cannula 108 is cross-sectionally illustrated in Figure 13. In Figure 13, an ocular implant 150 can be seen resting in a passageway 138 defined by cannula 108. With reference to Figure 13, it will be appreciated that distal portion 144 of cannula 108 is curved so that central axis 196 of cannula 108 defines a curvature plane 148. With reference to Figure 13, it will be appreciated that curvature plane 148 divides cannula 108 into a first portion and a second portion PB. Only second portion PB of cannula 108 is shown in the illustrative embodiment of Figure 13.

[000166] Figure 14 is a stylized perspective view including the assembly shown in the previous figure. In the embodiment of Figure 14, a distal portion of cannula 108 is shown extending through the wall of Schlemm's canal SC. The distal tip of cannula 108 may include a sharp portion configured for cutting and/or pierced the trabecular meshwork and the wall of Schlemm's canal so that the passageway defined by the cannula can be placed in fluid communication with the lumen defined by Schlemm's canal. With the passageway of the cannula placed in fluid communication with the lumen of Schlemm's canal, ocular implant 150 can be advanced out of the distal opening of the cannula and into Schlemm's canal. In Figure 14, a distal portion of ocular implant 150 can be seen through distal opening 132 of cannula 108.

[000167] For purposes of illustration, a hypothetical window W is cut through the wall of cannula 108 in Figure 14. An interlocking portion 160 of a delivery tool 152 and a complementary interlocking portion 162 of ocular implant 150 are visible through window W. In the embodiment of Figure 14, interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 are engaging each other so that a proximal end 149 of ocular implant 150 is proximal to the distal end 151 of delivery tool 152. Surface 161 of delivery tool 152 rests against the wall of cannula 108 to prevent interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 from disengaging one another. When they are connected in this fashion, delivery tool 152 and ocular implant 150 move together as the delivery tool is advanced and retracted relative to cannula 108 by the delivery system mechanism.

[000168] Figure 15 is an enlarged perspective view showing a portion of cannula 108 shown in the previous figure. In some useful embodiments, cannula 108 is curved to achieve substantially tangential entry into Schlemm's canal SC. In the embodiment of Figure 15, cannula 108 is contacting an outer major wall of Schlemm's canal SC at a point of tangency PT. Also in the embodiment of Figure 15, a curved distal portion of cannula 108 is dimensioned to be disposed within the anterior chamber of the eye.

[000169] As shown in Figure 15, the distal tip 134 and beveled edge of the cannula 108 have been inserted into Schlemm's canal up to the proximal extent 167 of beveled edge 165. In this position, ocular implant 150 can be seen extending into trough 154. In some useful embodiments, the ocular implant has a radius of curvature that is larger than the radius of curvature of the cannula. This arrangement ensures that the ocular implant will track along trough 154 as the ocular implant is urged in a distal direction by delivery system 100.

[000170] Figure 16 is an additional perspective view showing ocular implant 150 and cannula 108 shown in the previous figure. By comparing Figure 16 with the previous figure, it will be appreciated that ocular implant 150 has been advanced in a distal direction D while cannula 108

has remained stationary so that a distal portion of ocular implant 150 is disposed inside Schlemm's canal SC. Trough 154 opens into an elongate opening 132 defined by edge 142 at the distal portion of cannula 108. In the embodiment of Figure 16, the elongate opening defined by the cannula provides direct visualization of the ocular implant as it is advanced into

5 Schlemm's canal. A configuration allowing direct visualization of the ocular implant has a number of clinical advantages. During a medical procedure, it is often difficult to monitor the progress of the implant by viewing the implant through the trabecular meshwork. For example, blood reflux may push blood into Schlemm's canal obstructing a physician's view the portion of the implant that has entered Schlemm's canal. With reference to Figure 16, ocular implant 150
10 tracks along trough 154 as it is advanced distally along cannula 108. The trough opening allows the physician to monitor the progress of the implant by viewing the implant structures as they advance through the trough prior to entering Schlemm's canal. The trough opening also allows the physician to identify the position of the proximal end of the ocular implant with respect to the incision made by the cannula to access Schlemm's canal.

15 [000171] Figure 17 is an additional stylized perspective view showing ocular implant 150 and cannula 108. In the embodiment of Figure 17, the interlocking portions 160 and 162 of the delivery tool 152 and ocular implant 150, respectively, can be seen entering the distal opening 132 defined by cannula 108. As shown, ocular implant 150 has been advanced in a distal direction D (relative to the embodiment shown in the previous figure) so that more of ocular
20 implant 150 is disposed inside Schlemm's canal SC. Surface 161 opposite interlocking portion 160 of delivery tool 152 still rests against the inner wall of cannula 108 to keep the delivery tool interlocked with ocular implant 150.

[000172] Figure 18 is an additional stylized perspective view showing ocular implant 150 and cannula 108. As shown in Figure 18, the ocular implant 150 and delivery tool 152 have
25 advanced further distally so that delivery tool surface 161 and part of the reduced diameter portion 163 have now passed into opening 132, thereby permitting the delivery tool curved portion 153 to move toward its curved at-rest shape so that the delivery tool engagement surface 160 disengages and moves away from its complementary engagement surface 162 on the ocular implant 150.

30 [000173] In some useful embodiments, the delivery tool may be colored to provide visual differentiation from the implant. After the disengaging from the ocular implant, cannula 108 and delivery tool 152 can be withdrawn from Schlemm's canal SC leaving the ocular implant 150 in the fully deployed position shown in Figure 18. After delivery of ocular implant 150 is complete, the delivery tool and the cannula may be removed from the eye, leaving at least a
35 distal portion of the ocular implant in Schlemm's canal.

[000174] Figure 19 is a perspective view of Schlemm's canal SC after the cannula (seen in the previous figure) has been withdrawn leaving an inlet portion of ocular implant 150 in the anterior chamber of the eye and the remainder of ocular implant 150 in Schlemm's canal. The presence of ocular implant 150 in Schlemm's canal may facilitate the flow of aqueous humor out of the anterior chamber. This flow may include axial flow along Schlemm's canal, flow from the anterior chamber into Schlemm's canal, and flow leaving Schlemm's canal via outlets communicating with Schlemm's canal. When in place within the eye, ocular implant 150 will support the trabecular meshwork and Schlemm's canal tissue and will provide for improved communication between the anterior chamber and Schlemm's canal (via the trabecular meshwork) and between pockets or compartments along Schlemm's canal.

[000175] Figures 20A - Figure 20H are a series of stylized plan views illustrating example methods in accordance with this detailed description and associated apparatus used while performing those methods. In Figure 20A, a distal portion of cannula 108 is shown extending through the wall of Schlemm's canal SC. In the embodiment of Figure 20A, cannula 108 includes a sharp portion at its distal end 134 configured for cutting and/or pierced the trabecular meshwork and the wall of Schlemm's canal SC. In the embodiment of Figure 20A, the distal end of cannula 108 has been advanced through the trabecular meshwork and the wall of Schlemm's canal SC and a passageway defined by cannula 108 has been placed in fluid communication with the lumen defined by Schlemm's canal SC.

[000176] Figure 20B is an additional stylized plan view showing cannula 108 shown in the previous figure. In the embodiment of Figure 20B, an ocular implant 150 has been advanced out of a distal opening of cannula 108 and into Schlemm's canal SC. In Figure 20B, a distal portion of ocular implant 150 is shown residing in a lumen defined by Schlemm's canal.

[000177] Figure 20C is an additional stylized plan view showing ocular implant 150 and cannula 108. In the embodiment of Figure 20C, an interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 are both disposed near a trough portion of cannula 108. Ocular implant 150 has been advanced in a distal direction D (relative to the embodiment shown in the previous figure) so that more of ocular implant 150 is disposed inside Schlemm's canal SC. In Figure 20C, ocular implant is shown residing in a fully deployed position. As shown in Figure 20C, interlocking portion 160 of delivery tool 152 has disengaged from complementary interlocking portion 162 of ocular implant 150.

[000178] In the embodiment of Figure 20C, distal opening 132 defined by cannula 108 is shaped and dimensioned so as to allow interlocking portion 160 of delivery tool 152 to extend therethrough when ocular implant 150 reaches the fully deployed position shown in Figure 20C.

When surface 161 has entered opening 132, a distal portion of delivery tool 152 is free to flex

radially inward toward a curved, at-rest shape extending through distal opening 132 when ocular implant 150 reaches the fully deployed position shown in Figure 20C to disengage from the ocular implant.

[000179] Figure 20D is a plan view of Schlemm's canal SC after cannula 108 has been moved away from ocular implant 150. After moving cannula 108 away from ocular implant 150, a physician may visually inspect the present location of the ocular implant to determine whether that location is acceptable. If the physician determines that the present location is unacceptable, the physician may use the systems and methods described herein to recapture and reposition the ocular implant. The figures described below illustrate exemplary methods and apparatus for recapturing and repositioning the ocular implant.

[000180] In the embodiment of Figure 20E, cannula 108 has been positioned so that the complementary interlocking portion 162 of ocular implant 150 is disposed between cannula 108 and the interlocking portion 160 of delivery tool 152. Further distal movement of cannula 108 will cause delivery tool surface 161 to re-engage with the inner wall of cannula 108, thereby moving the interlocking portion 160 of the delivery tool into re-engagement with the ocular implant. The delivery tool and ocular implant can thereafter be moved proximally, possibly together with the cannula, to reposition the implant for subsequent redeployment.

[000181] Figure 20F is an additional stylized plan view showing ocular implant 150 and cannula 108 shown in the previous figure. By comparing Figure 20F with the previous figure, it will be appreciated that delivery tool 152 and ocular implant 150 have been moved in a proximal direction P so that a portion of ocular implant 150 has been withdrawn from Schlemm's canal SC. In the embodiment of Figure 20F, the complementary interlocking portion of ocular implant 150 and the interlocking portion of delivery tool 152 have both been drawn into the passageway defined by cannula 108. Also in the embodiment of Figure 20F, the side wall of cannula 108 is holding the distal portion of delivery tool 152 in a deformed shape with the interlocking portion of delivery tool 152 engaging the complementary interlocking portion of ocular implant 150.

[000182] Figure 20G is an additional stylized plan view showing ocular implant 150 and cannula 108 shown in the previous figure. In the embodiment of Figure 20G, ocular implant 150 has been advanced out of a distal opening of cannula 108 and into Schlemm's canal SC. In Figure 20G, a distal part of ocular implant 150 is shown residing in a lumen defined by Schlemm's canal. In the embodiment of Figure 20G, interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 are both once again located near a trough portion of cannula 108. In Figure 20G, ocular implant is shown residing in a second fully deployed position. In the embodiment of Figure 20G, the delivery tool 152 has once again disengaged from ocular implant 150 by permitting interlocking portion 160 of

delivery tool 152 to move away from complementary interlocking portion 162 of ocular implant 150

[000183] Figure 20H is a stylized plan view showing ocular implant 150 and Schlemm's canal SC after the cannula (seen in the previous figure) has been withdrawn leaving an inlet portion of ocular implant 150 in the anterior chamber of the eye and the remainder of ocular implant 150 in Schlemm's canal. When in place within the eye, ocular implant 150 will support the trabecular meshwork and Schlemm's canal tissue and will provide for improved communication between the anterior chamber and Schlemm's canal (via the trabecular meshwork) and between pockets or compartments along Schlemm's canal. Accordingly, the presence of ocular implant 150 in Schlemm's canal will facilitate the flow of aqueous humor out of the anterior chamber.

[000184] With reference to the figures described above, it will be appreciated that methods in accordance with the present detailed description may be used to position at least a distal portion of an implant in Schlemm's canal of an eye. In some cases, a proximal inlet portion of the ocular implant may be left in the anterior chamber. An exemplary method in accordance with the present detailed description may include the step of advancing a distal end of a cannula through a cornea of the eye so that a distal portion of the cannula is disposed in the anterior chamber of the eye. The cannula may be used to access Schlemm's canal, for example, by cutting and/or piercing the wall of Schlemm's canal with a distal portion of the cannula. A distal opening of the cannula may be placed in fluid communication with Schlemm's canal. The distal end of the ocular implant may be advanced through the distal opening of the cannula and into Schlemm's canal.

[000185] After delivering an ocular implant into Schlemm's canal, a physician may visually inspect the present location of the ocular implant to determine whether that location is acceptable. If the physician determines that the present location is unacceptable, the physician may use the systems and methods described herein to recapture and redeliver the ocular implant. Recapturing and redelivering the ocular implant may include the steps of forming a second connection between the delivery tool and the ocular implant and moving the delivery tool and the ocular implant in a proximal direction so that at least a portion of the ocular implant is withdrawn from Schlemm's canal. A distal part of the ocular implant may be advanced into Schlemm's canal while the ocular implant is coupled to the delivery tool at the second connection. The second connection may be selectively broken to release the ocular implant from the delivery system while the distal part of the ocular implant is disposed in Schlemm's canal.

[000186] Figure 21 is a perspective view showing a delivery tool subassembly 370 that may be part of a delivery system (e.g., delivery system 100 shown in Figure 8). Delivery tool subassembly 370 of Figure 21 comprises a rotating rack gear 320 that is fixed to a delivery tool

352. Delivery tool 352 includes an interlocking portion 360 and a curved distal portion 353. Curved distal portion 353 of delivery tool 352 is biased to assume the curved at-rest shape shown in Figure 21 when no external forces are acting on it. Curved distal portion 353 of delivery tool 352 may be urged to assume a straightened shape, for example, when it is disposed in a straight portion of a passageway defined by a cannula. Optional cut-outs 351 may be formed in the wall of delivery tool 352 to reduce friction during tool advancement by reducing the bending force. The cannula wall may also hold interlocking portion 360 of delivery tool 352 into engagement with a complementary interlocking portion of an ocular implant to form a mechanically interlocking connection.

10 [000187] Figure 22A is a stylized plan view showing delivery tool 352 shown in the previous figure. In the embodiment of Figure 22A, delivery tool 352 is extending into a passageway 338 defined by a cannula 308. A distal portion of cannula 308 defines a trough 354 that communicates with the passageway 338 defined by the wall of cannula 308. Trough 354 opens out the distal end of cannula 308. Trough 354 also opens into an elongate opening 332 defined
15 by the edge 342 of the cannula wall.

[000188] In Figure 22A, cannula 308 is illustrated in partial cross section. Interlocking portion 360 of delivery tool 352 and a complementary interlocking portion 362 of an ocular implant 350 are visible in Figure 22A. In the embodiment of Figure 22A, interlocking portion 360 of delivery tool 352 and complementary interlocking portion 362 of ocular implant 350 are
20 engaging each other to form a mechanically interlocking connection such that the implant's interlocking portion 362 is proximal to the delivery tool's interlocking portion 360. The delivery tool 352 and ocular implant 350 may be selectively disengaged when interlocking portion 360 of delivery tool 352 is allowed to move away from and disengage complementary interlocking portion 362 of ocular implant 350. In the embodiment of Figure 22, the wall of cannula 308 is
25 preventing interlocking portion 360 of delivery tool 352 from moving away from and disengaging complementary interlocking portion 362 of ocular implant 350. A surface 363 of delivery tool 352 can be seen contacting the wall of cannula 308 at a point S in Figure 22.

[000189] In Figure 22A, interlocking portion 360 of delivery tool 352 is shown disposed within cannula passageway 338 at a location proximal of trough 354 and distal opening 332. In some
30 useful embodiments, opening 332 is dimensioned and positioned such that, when the ocular implant reaches a predefined location along the passageway, the distal portion of delivery tool 352 will be free to move toward a curved at-rest shape. When the delivery tool assumes a curved shape, the interlocking portion of the delivery tool moves away from and disengages the complementary interlocking portion of the ocular implant. In this way, delivery tool 352 and

ocular implant 350 may be selectively disengaged as delivery tool 352 is moved distally along the passageway defined by the cannula from a starting location proximal of opening 332.

[000190] Figure 22B is an additional stylized plan view illustrating cannula 308, ocular implant 350, and delivery tool 352 shown in the previous figure. By comparing Figure 22B with Figure 22A, it will be appreciated that delivery tool 352 has been advanced in a distal direction D so that delivery tool 352 is extending through opening 332 and ocular implant 350 is outside of cannula passageway 338. In the embodiment of Figure 22B, interlocking portion 360 has moved away from complementary interlocking portion 362 and ocular implant 350 and delivery tool 352 have disengaged.

[000191] Figure 23 is a stylized plan view showing a delivery system 500 including an ocular implant 550 disposed in a passageway 538 defined by a cannula 508. Figure 23 includes an enlarged detail view V illustrating a portion of cannula 508. For purposes of illustration, a hypothetical window W is cut through the wall of cannula 508 in Figure 23. An interlocking portion 560 of a delivery tool 552 and a complementary interlocking portion 562 of ocular implant 550 are visible through window W. In the embodiment of Figure 23, interlocking portion 560 of delivery tool 552 and complementary interlocking portion 562 of ocular implant 550 are engaging each other to form a mechanically interlocking connection. When delivery tool 552 is confined, such as within cannula passageway 538, it can be held in mechanically interlocking engagement with ocular implant 550 so that these elements move together through passageway 538 of cannula 508. An optional ring 561 proximal to interlocking portion 560 and to the proximal end of implant 550 maintains the spacing between interlocking portion 560 and interlocking portion 562 so that they can be more easily disengaged. The wall of cannula 508 prevents interlocking portion 560 of delivery tool 552 and complementary interlocking portion 562 of ocular implant 550 from disengaging one another in the embodiment of Figure 23. A surface 565 of delivery tool 552 can be seen contacting the wall of cannula 508 at a point S in Figure 23.

[000192] Delivery system 500 of Figure 23 may be used to advance ocular implant 550 into a target location in the eye of a patient. Delivery system 500 includes a housing 502 and a tracking wheel 506 that can be seen extending through the wall of housing 502 in Figure 23.

Tracking wheel 506 is part of a mechanism that is capable of advancing and retracting delivery tool 552 of delivery system 500. Rotating tracking wheel 506 will cause delivery tool 552 to move in an axial direction along a passageway 538 defined by cannula 508. The axial direction may be in a distal direction D or a proximal direction P. Ocular implant 550 moves along with delivery tool 552 as it is advanced and retracted relative to cannula 508 by the delivery system mechanism.

[000193] In the embodiment of Figure 23, housing 502 is configured to be gripped with one hand while providing control over the axial advancement and retraction of the ocular implant via tracking wheel 506. The design of housing 502 results in an advantageous ergonomic relationship of the fingers relative to the hand. This design provides a configuration that will allow a user, such as a physician, to stabilize the device using part of the hand, while leaving the middle or index finger free move independently from the remainder of the hand. The middle or index finger is free to move independently to rotate tracking wheel 506 of delivery system 500 for advancing and/or retracting delivery tool 552.

[000194] Figure 24A is a stylized plan view further illustrating cannula 508 shown in the previous figure. A distal portion of cannula 508 defines a trough 554 that communicates with a passageway 538 defined by the wall of cannula 508. Trough 554 opens out the distal end of cannula 508. Trough 554 also opens into an elongate opening 532 defined by the edge 542 of the cannula wall. An ocular implant 550 and a portion of a delivery tool 552 are disposed within cannula passageway 538. A distal portion of delivery tool 552 is biased to assume a curved at-rest shape when no external forces are acting on it. In the embodiment of Figure 24A, the distal portion of delivery tool 552 is disposed in a straight portion of the cannula passageway 538 so that it is urged to assume a straightened shape.

[000195] Figure 24B is an additional stylized plan view illustrating cannula 508, ocular implant 550, and delivery tool 552 shown in the previous figure. In figure 24B, delivery tool 552 is shown extending through opening 532 and ocular implant 550 is shown in a location outside of cannula passageway 538. In Figure 24B, a gap can be seen between interlocking portion 560 of delivery tool 552 and a complementary interlocking portion 562 of ocular implant 550 in figure 24B. Accordingly, it will be appreciated that ocular implant 550 and delivery tool 552 have disengaged. In the embodiment of Figure 24B, the distal portion of delivery tool 552 has flexed through distal opening 532 as it has assumed a curved shape.

[000196] Reference is now made to both Figure 24A and Figure 24B which may be collectively referred to as Figure 24. In the embodiment of Figure 24A, the distal end of delivery tool 552 is disposed within cannula passageway 538 at a location proximal of trough 554 and distal opening 532. In the embodiment of Figure 24B, delivery tool 552 has been advanced in a distal direction D so that delivery tool 552 is extending through opening 532. Opening 532 is dimensioned and positioned such that, when the ocular implant reaches a predefined location along the passageway, the distal portion of delivery tool 552 will be free to move toward a curved at-rest shape. When the delivery tool assumes a curved shape, the interlocking portion of the delivery tool moves away from and disengages the complementary interlocking portion of the ocular implant. In this way, delivery tool 552 and ocular implant 550 may be selectively

disengaged as delivery tool 552 is moved distally along passageway 538 from the position shown in Figure 24A to the position shown in Figure 24B.

[000197] Figure 25A is a perspective view showing a delivery tool subassembly 770 that may be part of a delivery system (e.g., delivery system 100 shown in Figure 8). Delivery tool

5 subassembly 770 of Figure 25A comprises a rotating rack gear 720 that is fixed to a delivery tool 752 formed as a flat ribbon. Figure 25B is enlarged perspective view showing a distal portion of delivery tool 752. Figure 25A and Figure 25B may be collectively referred to as Figure 25.

Delivery tool 752 of Figure 25 includes an interlocking portion 760 and a curved distal portion 753. Curved distal portion 753 of delivery tool 752 is biased to assume the curved at-rest shape shown in Figure 25 when no external forces are acting on it. Curved distal portion 753 of delivery tool 752 may be urged to assume a straightened shape, for example, when it is disposed in a straight portion of a passageway defined by a cannula. The cannula wall may also hold interlocking portion 760 of delivery tool 752 into engagement with a complementary interlocking portion of an ocular implant to form a mechanically interlocking connection.

15 [000198] Figure 26A is a stylized perspective view showing a cannula 708 having a distal portion positioned so as to extend through the wall of Schlemm's canal SC. The distal tip of cannula 708 may include a sharp portion configured for cutting and/or pierced the trabecular meshwork and the wall of Schlemm's canal so that a passageway 738 defined by the cannula can be placed in fluid communication with the lumen defined by Schlemm's canal. With the

20 passageway of the cannula placed in fluid communication with the lumen of Schlemm's canal, an ocular implant 750 can be advanced out of the distal opening of the cannula and into Schlemm's canal. Insertion of the ocular implant into Schlemm's canal may facilitate the flow of aqueous humor out of the anterior chamber of the eye.

[000199] In Figure 26A, delivery tool 752 is shown extending out of passageway 738 defined by a cannula 708. A surface 767 of delivery tool 752 rests against an inner wall surface of cannula 708 to keep delivery tool 752 interlocked with ocular implant 750. A distal portion of cannula 708 defines a trough 754 that communicates with passageway 738 defined by the cannula wall. Trough 754 opens out the distal end of cannula 708. Trough 754 also opens into an elongate opening 732 defined by the edge 742 of the cannula wall.

30 [000200] Figure 26B is an additional perspective view showing ocular implant 750 and cannula 708 shown in the previous figure. By comparing Figure 26B with the previous figure, it will be appreciated that ocular implant 750 and delivery tool 752 have advanced further distally so that part of delivery tool surface 767 and part of distal curved portion 753 have now passed through opening 732, thereby permitting the distal tool portion to move toward its curved at-rest shape so

that the delivery tool interlocking portion 760 disengages and moves away from its complementary interlocking portion 762 on the ocular implant 750.

[000201] Reference is now made to both Figure 26A and Figure 26B which may be collectively referred to as Figure 26. In the embodiment of Figure 26, ocular implant 750 tracks along trough 754 as it is advanced distally along cannula 708. The trough opening allows the physician to monitor the progress of the implant by viewing the implant structures as they advance through the trough prior to entering Schlemm's canal. The trough opening also allows the physician to identify the position of the proximal end of the ocular implant with respect to the incision made by the cannula to access Schlemm's canal. Additionally, the trough opening allows the physician to see when the delivery tool is going to release the implant to monitor when he or she will lose the ability to retract the implant.

[000202] Figure 27A is a top view showing a cannula 108 and a delivery tool 152. Cannula 108 and delivery tool 152 may form part of a delivery system for delivering an ocular implant 150 in the eye of a patient. The delivery tool 152 and/or the ocular implant can comprise an elastic or bendable material configured to assume a pre-determined shape, such as a shape memory material, for example. As shown in Figure 27A, body 182 of cannula 108 comprises a first side 183 and a second side 184 that extend along opposite sides of a longitudinal center axis 196. Longitudinal center axis 196 includes a curved portion 185 having a radius RA. In Figure 27A, radius RA can be seen extending from a curvature center point CP to longitudinal center axis 196.

[000203] Delivery tool 152 comprises a proximal portion 153, a distal interlocking portion 160, and a ribbon portion 163 that extends between proximal portion 153 and distal interlocking portion 160. In the embodiment of Figure 27A, no external forces are acting on delivery tool 152 and ribbon portion 163 is free to assume a predetermined or unbiased and undeformed shape. In some embodiments, the predetermined shape can comprise a curved resting shape. With reference to Figure 27A, delivery tool 152 has a radius of curvature RC when it is free to assume the undeformed shape. Radius RC can be seen extending from curvature center point CP to a longitudinal axis LC of delivery tool 152 in Figure 27A. With reference to Figure 27A, the radius RC of delivery tool 152 is smaller than the radius RA of cannula 108. As will be described in more detail below, the ocular implant 150 can be configured to engage the delivery tool 150 within a passageway of the cannula. In some useful embodiments, a trough portion 189 of distal opening 132 of cannula 108 is dimensioned and positioned such that, when ocular implant 150 reaches a predefined location along the passageway of the cannula, the distal portion of delivery tool 152 will be free to move toward a curved at-rest shape to release the ocular implant.

[000204] In the embodiment of Figure 27A, no external forces are acting on the ocular implant and ocular implant 150 is free to assume an undeformed shape. With reference to Figure 27A, ocular implant 150 has a radius of curvature RB when it is free to assume the undeformed shape. Radius RB of ocular implant 150 can be seen extending from a curvature center point CP to a longitudinal axis LA of ocular implant 150 in Figure 27A. Ocular implant 150 may comprise, for example, the ocular implant disclosed in US Patent Publ. No. 2011/0009958.

[000205] With reference to Figure 27A, the radius RA of cannula 108 is smaller than the radius RB of ocular implant 150. This arrangement allows the elastic behavior of the ocular implant to bias the ocular implant against an inner surface of cannula 108 as the distal end of ocular implant 150 travels through trough 186 of the cannula. Biasing the ocular implant against the inner surface of the trough helps assure that the distal end of the ocular implant travels between the inner surface of the trough and tissue covering a portion of the distal opening 132. This arrangement also helps assure that the distal end of the ocular implant follows the path defined by trough 186 as it is advanced in a distal direction through the cannula.

[000206] Ocular implant 150, delivery tool 152 and cannula 108 may be fabricated from various biocompatible materials possessing the necessary structural and mechanical attributes. Both metallic and non-metallic materials may be suitable. Examples of metallic materials include stainless steel, tantalum, gold, titanium, and nickel-titanium alloys known in the art as Nitinol. Nitinol is commercially available from Memry Technologies (Brookfield, Conn.), TiNi Alloy Company (San Leandro, Calif.), and Shape Memory Applications (Sunnyvale, Calif.). Nitinol is one advantageous material for ocular implant 150 and delivery tool 152 due to its super elastic properties. Stainless Steel can be used for cannula 108 due to its mechanical strength and ability to maintain its shape and cause ocular implant 150 and delivery tool 152 to conform within it.

[000207] Figure 27B is a cross-sectional view of cannula 108 taken along section line B-B shown in Figure 27A. As shown in Figure 27B, cannula 108 has an inner diameter D1. Cannula 108 of Figure 27B defines a lumen 187. In some embodiments, the cannula defines a trough and a lumen that define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the cannula is inside Schlemm's canal of the eye. An ocular implant can be delivered into Schlemm's canal by advancing the ocular implant along the pathway defined by the lumen and the trough.

[000208] Figure 27C, Figure 27D and Figure 27E are cross-sectional views of delivery tool 152 shown in the previous figure. These section views correspond to section lines shown in Figure 27A. More particularly, Figure 27C, Figure 27D and Figure 27E correspond to section line C-C, D-D, and E-E, respectively. Figures 27A through 27 F may be collectively referred to as Figure

27. In the embodiment of Figure 27, proximal portion 153, distal interlocking portion 160, and ribbon portion 163 of delivery tool 152 can all have an outer diameter D2. In some useful embodiments, delivery tool 152 is fabricated by removing material from a wire having a generally cylindrical shape. As shown in Figure 27D, ribbon portion 163 of delivery tool 152 has a thickness T that extends between a first major side 112 of ribbon portion 163 and a second major side 114 of ribbon portion 163.

[000209] In some embodiments, the outer diameter of the ribbon portion can be only slightly smaller than the inner diameter of the cannula so that the ribbon portion tracks along the widest part of the cannula lumen and so that support provided by the cannula wall makes it less likely that ribbon portion will buckle. The outer diameter of the ribbon portion may be designed to be smaller than the inner diameter of the cannula by a selected clearance value. In some useful embodiments, the clearance value is less than two times the wall thickness of the ocular implant. In some embodiments, a clearance value can be between about 0.0005 inches and about 0.0010 inches.

[000210] Figure 27F is a cross-sectional view of an ocular implant 150 taken along section line F-F shown in Figure 27A. With reference to Figure 27, it will be appreciated that ocular implant 150 and distal interlocking portion 160 of delivery tool 152 both have an outer diameter D2. In some useful embodiments, the ocular implant and the distal interlocking portion of the delivery tool have an outer diameter designed to provide a carefully selected clearance between those elements and the inner diameter of the cannula. The clearance is large enough to allow the delivery tool and the ocular implant to slide along the lumen of the cannula. At the same time, the clearance is small enough to prevent unintentional release of the ocular implant, for example, when the complimentary interlocking portion of the ocular implant climbs over the interlocking portion of the delivery tool. The clearance is also small enough to reduce the likelihood that the ocular implant will become jammed, for example, when the wall of the ocular implant becomes lodged between the delivery tool and the inner diameter of the cannula. In some embodiments, the clearance value is less than two times the wall thickness of the ocular implant.

[000211] Figure 27G is an isometric view showing a distal portion of delivery tool 152. Delivery tool 152 comprises a proximal portion (not shown), a distal interlocking portion 160, and a ribbon portion 163 that extends between the proximal portion and distal interlocking portion 160. In the embodiment of Figure 27A, no external forces are acting on delivery tool 152. As shown in Figure 27G, ribbon portion 163 of delivery tool 152 can be biased to assume a curved resting shape when no external forces are acting on it (e.g., external forces from an interior surface of the cannula).

[000212] Ribbon portion 163 of delivery tool 152 has an outer diameter D2 and a thickness T. As shown in Figure 27G, thickness T extends between a first major side 112 of ribbon portion 163 and a second major side 114 of ribbon portion 163. With reference to Figure 27G, it will be appreciated that outer diameter D2 is greater than thickness T. In some useful embodiments, an aspect ratio of outer diameter to thickness is also selected so that the ribbon portion preferentially bends along a preferential bending plane. In the embodiment of Figure 27G, the thickness of the ribbon portion is selected so that the ribbon portion preferentially bends along a preferential bending plane PBP.

[000213] In some delivery system designs, the delivery tool is oriented within the cannula so that a preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula. This coplanar orientation assures that when the ocular implant reaches a predefined location (e.g., the trough portion) along the passageway of the cannula, the distal portion of delivery tool 152 will be free to move toward a curved at-rest shape to release the ocular implant.

[000214] Figure 27H is a perspective view of an assembly including cannula 108, delivery tool 152 and ocular implant 150. For purposes of illustration, a hypothetical window W is cut through the wall of cannula 108 in Figure 27H. By comparing Figure 27H with the previous figure, it can be seen how cannula 108 prevents ribbon portion 163 of delivery tool 152 from assuming its curved at rest shape when the ribbon portion of delivery tool 152 is inside the lumen of the cannula.

[000215] An interlocking portion 160 of a delivery tool 152 and a complementary interlocking portion 162 of ocular implant 150 are visible through window W. In the embodiment of Figure 27H, interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 are engaging each other so that a proximal end 149 of ocular implant 150 is proximal to the distal end 151 of delivery tool 152. Surface 161 of delivery tool 152 rests against the wall of cannula 108 to prevent interlocking portion 160 of delivery tool 152 and complementary interlocking portion 162 of ocular implant 150 from disengaging one another. When they are connected in this fashion, delivery tool 152 and ocular implant 150 move together as the delivery tool is advanced and retracted relative to cannula 108 by the delivery system mechanism.

[000216] In some embodiments, the ocular implant and the distal interlocking portion of the delivery tool have an outer diameter designed to provide a carefully selected clearance between those elements and the inner diameter of the cannula. The clearance is large enough to allow the delivery tool and the ocular implant to slide along the lumen of the cannula. At the same time, the clearance is small enough to prevent unintentional release of the ocular implant, for example, when the complimentary interlocking portion of the ocular implant climbs over the interlocking

portion of the delivery tool. The clearance is also small enough to reduce the likelihood that the ocular implant will become jammed, for example, when the wall of the ocular implant becomes lodged between the delivery tool and the inner diameter of the cannula. In some useful embodiments, the clearance value is less than two times the wall thickness of the ocular implant.

5 [000217] Figure 27I is a cross-sectional view of cannula 108 and delivery tool 152 taken along section line i-i shown in Figure 27H. Ribbon portion 163 of delivery tool 152 has an outer diameter D2 and a thickness T. As shown in Figure 27I, thickness T extends between a first major side 112 of ribbon portion 163 and a second major side 114 of ribbon portion 163. As shown in Figure 27I, cannula 108 has an inner diameter D1. In some useful embodiments, the
10 outer diameter of the ribbon portion is only slightly smaller than the inner diameter of the cannula so that the ribbon portion tracks along the widest part of the cannula lumen and so that support provided by the cannula wall makes it less likely that ribbon portion will buckle. The outer diameter of the ribbon portion may be designed to be smaller than the inner diameter of the cannula by a selected clearance value.

15 [000218] Figure 27J is a perspective view showing an assembly including a cannula 108 and a distal portion of a delivery tool 152. In the embodiment of Figure 27J, delivery tool 152 is assuming a somewhat curved shape in which the distal portion of the delivery tool extends through the trough portion 189 of distal opening 132. In the embodiment of Figure 27J, trough portion 189 begins having a width equal to the inner diameter of cannula 108 at a point P. In
20 some embodiments, the trough opening has a width that is substantially equal to an inner diameter of the cannula and both the ribbon portion and the distal interlocking portion of the delivery tool have an outer diameter slightly smaller than the inner diameter of the cannula so that so that a distal portion of the delivery tool can pass through the trough opening when the delivery tool reaches the predetermined location along the pathway defined by the cannula.
25 When the distal interlocking portion of the delivery tool reaches the point P where the full trough width starts it is free to flex radially towards the trough opening through the distal opening of the cannula. The outer diameter of both the ribbon portion and the distal interlocking portion of the delivery tool may be designed to be smaller than the inner diameter of the cannula by a selected clearance value.

30 [000219] Figure 28 is a perspective view of a cannula 108 in accordance with the present detailed description. Cannula 108 of Figure 28 comprises a body 182 having a first side 183 and a second side 184. In Figure 28, first side 183 and second side 184 can be seen extending along opposite sides of a longitudinal center axis 196 of cannula 108. Longitudinal center axis 196 includes a curved portion 185. In the embodiment of Figure 28, first side 183 is disposed on a
35 radially inward side of curved portion 185 of longitudinal center axis 196. Second side 184 is

disposed on a radially outward side of curved portion 185 of longitudinal center axis 196 in the embodiment of Figure 28.

[000220] Body 182 of Figure 28 includes a trough 186 that opens through first side 183. The trough 186 can define an open groove portion of the cannula. Body 182 also defines a lumen 187 that extends from trough 186 to a proximal opening 136 of body 182. In some embodiments, the body is sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the cannula is inside Schlemm's canal of the eye. An ocular implant can be delivered into Schlemm's canal by advancing the ocular implant along the pathway defined by the lumen and the trough. Examples of ocular implants that may be delivered through the cannula of this invention may be found, e.g., in US Patent No. 7,740,604; US Patent Publ. No. 2009/0082860; US Patent Publ. No. 2009/0082862; US Patent Publ. No. 2009/0227934; and US Patent Publ. No. 2011/0009958.

[000221] Trough 186 comprises a first trough edge 188A, a second trough edge 188B, and an intermediate wall extending between first trough edge 188A and second trough edge 188B. In the embodiment of Figure 28, the intermediate wall has a generally semi-circular transverse cross-sectional shape. A trough portion 189 of distal opening 132 extends between first trough edge 188A and second trough edge 188B opposite the intermediate wall.

[000222] In some useful embodiments, trough 186 is configured to receive the entire external cross section of an ocular implant as the ocular implant is being advanced into Schlemm's canal. When this is the case, trough 186 may have a depth dimension that is deeper than a height of the ocular implant. This cannula configuration allows the distal end of the ocular implant to be advanced under tissue that is covering the trough.

[000223] Cannula 108 and trough 186 include a tapered distal tip 190 extending distally from second side 184 of body 182. Tapered distal tip 190 comprises a first leading edge 192A, a second leading edge 192B, and an intermediate wall extending between first leading edge 192A and second leading edge 192B. In the embodiment of Figure 28, the intermediate wall has a generally semi-circular transverse cross-sectional shape. First leading edge 192A and second leading edge 192B both distally converge toward a distal point 193 of tapered distal tip 190. In some useful embodiments, distal point 193 of tapered distal tip 190 is sufficiently blunt to slide along the outer major wall of Schlemm's canal without cutting the scleral tissue underlying the outer major wall of Schlemm's canal. A distal opening 132 extends between first leading edge 192A and second leading edge 192B of tapered distal tip 190 opposite the intermediate wall.

[000224] First leading edge 192A of tapered distal tip 190 meets first trough edge 188A at a first apex AA. Second leading edge 192B of tapered distal tip 190 meets second trough edge

188B at a second apex AB. During a delivery procedure, tapered distal tip 190 may be inserted into Schlemm's canal until first apex AA and second apex AB are aligned with the incision made to enter Schlemm's canal. It is an important aspect of this design that the apex points, the length of the trough opening 189 and the curve profile of the delivery tool are all configured to enable the delivery system to automatically deploy the ocular implant in the correct position when first apex AA and a second apex AB are aligned with the incision.

[000225] After the cannula is positioned properly in Schlemm's canal, the delivery tool can be advanced along the lumen of the cannula. When the distal interlocking portion of the delivery tool reaches the point where the full trough width starts, the delivery tool is free to flex radially towards the trough opening through the distal opening of the cannula. The ocular implant is automatically released from the delivery system as the distal interlocking portion of the delivery tool moves away from the trough of the cannula and away from the ocular implant. Automatically releasing the ocular implant from the delivery system causes the inlet portion of the ocular implant to be consistently placed in the correct position with respect to Schlemm's canal.

Automatically placing the inlet of the ocular implant in the correct location eliminates any need to adjust the position of the ocular implant after deployment. Automatically placing the inlet of the ocular implant in the correct location also eliminates any possibility of inserting the inlet portion of the ocular implant into Schlemm's canal. The automatic placement of the inlet of the ocular implant is particularly beneficial when the physician's view of the ocular implant is obstructed at the time of release. The physician's view may be obstructed, for example, by blood reflux.

[000226] Figure 29A and Figure 29B are plan views of cannula 108 shown in the previous figure. Figure 29A and Figure 29B may be collectively referred to as Figure 29. The plan views of Figure 29 were created using a technique known in the field of engineering drawing as multiview projection. In engineering drawing it is customary to refer to multiview projections using terms such as front view, top view, and side view and the like. In accordance with this convention, Figure 29A may be referred to as a top view of cannula 108 and Figure 29B may be referred to as a side view of cannula 108. The terms top view, side view, and bottom view are used herein as a convenient method for differentiating between the views shown in Figure 29. It will be appreciated that cannula 108 shown in Figure 29 may assume various orientations without deviating from the spirit and scope of this detailed description. Accordingly, the terms top view, side view, and bottom view should not be interpreted to limit the scope of the invention recited in the attached claims.

[000227] As shown in Figure 29A, body 182 of cannula 108 comprises a first side 183 and a second side 184 that extend along opposite sides of a longitudinal center axis 196. Longitudinal

center axis 196 includes a curved portion 185. In the embodiment of figure 29, first side 183 is disposed on a radially inward side of curved portion 185 of longitudinal center axis 196. Second side 184 is disposed on a radially outward side of curved portion 185 of longitudinal center axis 196 in the embodiment of figure 29.

5 [000228] As shown in Figure 29B, body 182 of cannula 108 includes a trough 186 that opens through first side 183. Trough 186 comprises a first trough edge 188A, a second trough edge 188B, and a trough portion 189 of distal opening 132 extending between first trough edge 188A and second trough edge 188B. The cannula body 182 also defines a lumen 187 that fluidly communicates with trough 186 and extends to a proximal end of body 182. In some useful
10 embodiments, the body is sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point 193 of the tapered distal tip 190 is inside Schlemm's canal of the eye.

[000229] As shown in Figure 29B, cannula 108 includes a tapered distal tip 190 extending distally from second side 184 of body 182. Tapered distal tip 190 comprises a first leading edge
15 192A and a second leading edge 192B. First leading edge 192A and second leading edge 192B both distally converge toward a distal point 193 of tapered distal tip 190. In some embodiments, distal point 193 of tapered distal tip 190 is sufficiently blunt to slide along the outer major wall of Schlemm's canal without cutting the scleral tissue underlying the outer major wall of Schlemm's canal. A distal opening 132 of cannula 108 extends between first leading edge 192A
20 and second leading edge 192B of tapered distal tip 190.

[000230] First leading edge 192A of tapered distal tip 190 meets first trough edge 188A at a first apex AA. Second leading edge 192B of tapered distal tip 190 meets second trough edge 188B at a second apex AB. During a delivery procedure, tapered distal tip 190 may be inserted into Schlemm's canal until first apex AA and second apex AB are aligned with the incision made
25 to enter Schlemm's canal. Aligning the apex points with the incision enables a delivery system in accordance with this detailed description to automatically deploy the ocular implant in the correct position.

[000231] Figure 30A is an additional top view of cannula 108 shown in the previous figure. In Figure 30A, the distal point 193 of cannula 108 is shown having been advanced into and residing
30 inside Schlemm's canal SC of a human eye. Schlemm's canal SC and various surrounding tissues are schematically illustrated in Figure 30A. Schlemm's canal SC comprises a wall W that extends between scleral tissue 34 and the trabecular meshwork TM. As shown in Figure 30A, a tissue tent 197 has been formed by lifting an inner portion of wall W away from an outer portion of wall W. Tissue tent 197 comprises tissues of Schlemm's canal wall W and trabecular
35 meshwork TM that can be seen covering a portion of distal opening 132 in Figure 30A.

[000232] With reference to Figure 30A, the distal tip of cannula 108 has been inserted into Schlemm's canal SC up to the apex A of the distal tip at which tissue tent 197 intersects the trough portion 189 of distal opening 132. In some embodiments, the tapered distal tip 190 of cannula 108 is shaped and configured to lift and/or stretch trabecular meshwork TM and wall W over a portion of distal opening 132 as distal point 193 is advanced into Schlemm's canal. With reference to Figure 30A, trough portion 189 of distal opening 132 is not covered by wall W and trabecular meshwork TM. The uncovered portion of distal opening 132 may allow a physician to see an ocular implant as it advances through trough 186.

[000233] Figure 30B is a stylized cross-sectional view taken along cutting plane B-B shown in Figure 30A. The picture plane of Figure 30B extends laterally across Schlemm's canal SC and trabecular meshwork TM of an eye 20. Additional ocular anatomy is shown in figure 30B to provide context and increase understanding. Eye 20 includes an iris 30 that defines a pupil 32 of the eye. Schlemm's canal SC may be conceptualized as a tube-like structure disposed between scleral tissue 34 and trabecular meshwork TM. Together, Schlemm's canal SC and trabecular meshwork TM extend along an outer edge of anterior chamber AC and encircle iris 30. As shown in Figure 30B, Schlemm's canal wall W and trabecular meshwork TM are covering a portion of trough 186 of cannula 108. In Figure 30B, trabecular meshwork TM is shown stretching between Schwalbe's line 6 and a scleral spur 4 of eye 20.

[000234] Figure 31 is a cross-sectional view further illustrating cannula 108 shown in the previous figure. In the cross-sectional view of Figure 31, an ocular implant 150 can be seen advancing into trough 186 of cannula 108. The distal point 193 of tapered distal tip 190 is positioned inside Schlemm's canal SC of a human eye. In Figure 31, tissues of Schlemm's canal wall W and trabecular meshwork TM can be seen extending over a distal portion of distal opening 132.

[000235] With reference to Figure 31, trough 186 has a depth greater than the height of ocular implant 150 so that the distal end of the ocular implant will travel between an inner surface S of cannula 108 and the tissue covering the distal portion of distal opening 132 as ocular implant 150 moves in a distal direction D. Distal direction D is illustrated using an arrow in figure 31. This cannula configuration advantageously prevents the ocular implant from intersecting the layers of trabecular meshwork TM and wall W that are covering the distal portion of trough 186.

[000236] As shown in Figure 31, trough 186 opens through a first side 183 of cannula 108. In the embodiment of Figure 31, the length of trough portion 189 of distal opening 132 is selected to ensure correct positioning of the implant upon release and provide direct visualization of the ocular implant as it is advanced into Schlemm's canal SC. An exemplary line of sight used by a hypothetical viewer V is schematically illustrated using a dashed line in Figure 31. A

configuration allowing direct visualization of the ocular implant has a number of clinical advantages. During a medical procedure, it is often difficult to monitor the progress of the implant by viewing the implant through the trabecular meshwork. For example, blood reflux may push blood into Schlemm's canal obstructing a physician's view of the portion of the implant that has entered Schlemm's canal. With reference to Figure 31, ocular implant 150 tracks along trough 186 as it is advanced distally along cannula 108. The trough portion of the distal opening allows the physician to release the implant such that the inlet extends into the AC a defined length; it also allows the user to monitor the progress of the implant by viewing the implant structures as they advance through the trough prior to entering Schlemm's canal. The trough portion of the distal opening also allows the physician to identify the position of the proximal end of the ocular implant with respect to the incision made by the cannula to access Schlemm's canal. Additionally, the trough portion of the distal opening allows the physician to see when the delivery tool is going to release the implant to monitor when he or she will lose the ability to retract the implant.

[000237] With reference to Figure 31, tapered distal tip 190 of cannula 108 has been inserted into Schlemm's canal SC up to the apex A of the distal tip at which tissue tent 197 intersects the trough portion 189 of distal opening 132. During some delivery procedures, the physician's view through trough portion 189 may be obstructed by blood reflux. Accordingly, it is an important aspect of this design that the apex of the tapered distal tip, the length of trough opening 189 and the curved profile of the delivery tool are all configured to enable the delivery system to automatically deploy the ocular implant in the correct position when the apex of the tapered distal tip is aligned with the incision made to access Schlemm's canal. When the distal interlocking portion of the delivery tool reaches to the trough portion of the cannula, it will be free to flex radially towards the trough opening through the distal opening of the cannula. The ocular implant is automatically released from the delivery system as the distal interlocking portion of the delivery tool moves away from the ocular implant. Automatically releasing the ocular implant from the delivery system causes the inlet portion of the ocular implant to be consistently placed in the correct position with respect to Schlemm's canal. Automatically placing the inlet of the ocular implant in the correct location eliminates any need to adjust the position of the ocular implant after deployment. Automatically placing the inlet of the ocular implant in the correct location also eliminates any possibility of inserting the inlet portion of the ocular implant into Schlemm's canal.

[000238] Figure 32 is perspective view further illustrating the anatomy of eye 20. Eye 20 includes a dome-shaped wall that defines and encloses the anterior chamber AC. The dome-shaped wall of the eye comprises a cornea 36 and scleral tissue 34. The scleral tissue 34 meets

the cornea 36 at a limbus of eye 20. The dome shaped wall includes a scleral spur 4 comprising scleral tissue 34. Schlemm's canal SC resides in a shallow depression in the scleral tissue located near scleral spur 4. The trabecular meshwork TM is fixed to scleral spur 4 and extends over Schlemm's canal SC. Together, Schlemm's canal SC, trabecular meshwork TM, and scleral spur 4 encircle anterior chamber AC along the dome shaped wall. Iris 30 of eye 20 is disposed inside the anterior chamber AC. Iris 30 defines a pupil 32. Descemet's membrane 8 is one of the inner-most layers of cornea 36. Descemet's membrane extends across cornea 36 toward Schlemm's canal SC and terminates at Schwalbe's line 6 near the upper edge of Schlemm's canal SC.

10 [000239] Figure 33 is a perspective view showing selected structures from the eye shown in the previous figure. In Figure 33, a distal portion of cannula 108 can be seen residing in the anterior chamber of the eye. One function of cannula 108 is to delivery an ocular implant into Schlemm's canal SC. During a delivery procedure, distal point 193 of tapered distal tip 190 of cannula 108 may be advanced through trabecular meshwork TM and into Schlemm's canal. In
15 some particularly useful methods, taper distal tip 190 is inserted into Schlemm's canal SC up to a first apex AA and a second apex AB of cannula 108. When distal point 193 is disposed in Schlemm's canal, cannula 108 will define a pathway extending from a location outside of the eye to a location inside Schlemm's canal. The ocular implant can be advanced along the pathway defined by cannula 108 inserted into Schlemm's canal.

20 [000240] In some embodiments, cannula 108 includes a curved distal portion that is dimensioned to be received within the anterior chamber of the eye. This curved portion may be configured to provide a pathway entering Schlemm's canal in a substantially tangential direction. When a physician is attempting to insert tapered distal tip 190 of cannula 108 into Schlemm's canal under gonio lens visualization, the physician may refer to anatomical landmarks of the eye.
25 One convenient landmark is scleral spur 4 which has the appearance of a white line encircling the anterior chamber. Another convenient landmark is a pigment line centered on Schlemm's canal SC. An additional convenient landmark is Schwalbe's line 6.

[000241] Figure 34 is an additional perspective view of the ocular structures shown in the previous figure. In the embodiment of Figure 34, the tapered distal tip of cannula 108 has been
30 advanced into Schlemm's canal SC. A tissue tent 197 can be seen arching over a distal portion of cannula 108 in Figure 34. With reference to Figure 34 it will be appreciated that the distal tip of cannula 108 has been inserted into Schlemm's canal SC up to the first apex and the second apex of cannula 108 at which tissue tent 197 intersects the trough portion 189 of distal opening 132. In some useful embodiments, the tapered distal tip of cannula 108 is configured to lift a

portion of Schlemm's canal wall W and trabecular meshwork TM away from the scleral tissue enclosing the anterior chamber of the eye.

[000242] The tissue tent 197 created by cannula 108 may facilitate delivery of an ocular implant 150 into Schlemm's canal SC. In Figure 34, ocular implant 150 can be seen extending from the lumen of cannula 108 into its trough 186. During a delivery procedure, the distal end of ocular implant 150 may be advanced through tissue tent 197 and the distal opening of cannula 108 as it is inserted into Schlemm's canal. It is important to note that maintaining the relationship of the cannula apex A and the Schlemm's canal entry point will enable a delivery system in accordance with this detailed description to automatically and predictably release the implant in the correct location. The predictability of the resulting implant delivery location has far reaching benefits. If the field of view becomes compromised (e.g., filled with blood) during implant delivery and the user has maintained the position of cannula with respect to the Schlemm's canal entry point he or she can deliver ocular implant with a high degree of confidence that the delivery system in accordance with this detailed description will automatically release the ocular implant in the correct location.

[000243] Trough 186 of cannula opens through a first side 183 of the cannula body 182. As shown in Figure 34, a first window WA of ocular implant 150 can be seen through trough portion 189 of distal opening 132. Windows and other structures of ocular implant can be observed through trough portion 189 of distal opening 132 to provide visual feedback regarding the movement of ocular implant 150 during a delivery procedure.

[000244] Figure 35 is an additional perspective view showing ocular implant 150 and cannula 108 shown in the previous figure. When comparing Figure 35 with the previous figure, ocular implant 150 has been advanced in a distal direction D while cannula 108 has remained stationary so the distal end of ocular implant 150 is disposed inside Schlemm's canal SC. Because ocular implant 150 can be seen through trough portion 189 of distal opening 132, it will be appreciated that first window WA is now extending into Schlemm's canal and a second window WA of ocular implant 150 has come into view.

[000245] In the embodiment of Figure 35, trough portion 189 of distal opening 132 has a length selected to provide direct visualization of ocular implant 150 while the first apex and the second apex of cannula 108 are aligned with the incision that provides entry into Schlemm's canal SC. A cannula configuration allowing direct visualization of the ocular implant has a number of clinical advantages. During a medical procedure, it is often difficult to monitor the progress of the implant by viewing the implant through the trabecular meshwork. For example, heavy pigmentation and/or blood reflux may push blood into Schlemm's canal obstructing a physician's view of the portion of the implant that has entered Schlemm's canal. With reference

to Figure 35, ocular implant 150 tracks along trough 186 as it is advanced distally along cannula 108. The trough portion of the distal opening allows the physician to monitor the progress of the implant by viewing the implant structures as they advance through the trough prior to entering Schlemm's canal. The trough portion of the distal opening also allows the physician to identify the position of the proximal end of the ocular implant with respect to the incision made by the cannula to access Schlemm's canal. Additionally, the trough portion of the distal opening allows the physician to see when the delivery tool is going to release the implant to monitor when he or she will lose the ability to retract the implant.

[000246] Figure 36 is an additional stylized perspective view showing ocular implant 150 and cannula 108. In Figure 36, mechanically interlocking portions of ocular implant 150 and a delivery tool 152 can be seen entering trough 186 of cannula 108. As shown in Figure 36, ocular implant 150 has been advanced in a distal direction D (relative to the position shown in the previous figure) so that more of ocular implant 150 is disposed inside Schlemm's canal SC. An outer surface of delivery tool 152 is resting against an inner surface of cannula 108 to keep the delivery tool interlocked with ocular implant 150 in the embodiment of Figure 36.

[000247] Figure 37 is an additional stylized perspective view showing ocular implant 150 and cannula 108. In the embodiment of Figure 37, the connection previously formed between the interlocking portions of delivery tool 152 and ocular implant 150 has been broken, since the distal portion of the delivery tool has been advanced into the trough portion of the cannula and flexed towards the trough opening away from the implant and cannula. With reference to Figure 37, it will be appreciated that a distal portion of delivery tool 152 has moved radially away from ocular implant 150.

[000248] In the embodiment of Figure 37, trough portion 189 of distal opening 132 is shaped and dimensioned so as to allow a distal portion of delivery tool 152 to extend therethrough when ocular implant 150 reaches the fully deployed position shown in Figure 37. With reference to Figure 37, it will be appreciated that when the distal portion of delivery tool 152 reaches the point at which the full trough width begins, it is free to assume a curved, unstressed shape extending through the trough portion 189 of distal opening 132. In this manner, the delivery system releases ocular implant 150 when the ocular implant reaches the fully deployed position.

In some useful embodiments, the delivery tool may be colored to provide visual differentiation from the implant. Flexing radially through the trough opening to assume the curved shape causes the distal portion of delivery tool 152 to disengage from the ocular implant. When the delivery tool disengages from the ocular implant, the connection between these two elements is broken. When the connection is broken, the ocular implant is released from the delivery system. Releasing the ocular implant from the delivery system in this manner causes the inlet portion of

the ocular implant to be consistently placed in the correct position with respect to Schlemm's canal. Placing the inlet of the ocular implant in the correct location using this delivery system eliminates any need to adjust the position of the ocular implant after deployment. This delivery system is particularly beneficial when the physician's view of the ocular implant is obstructed at the time of release. The physician's view may be obstructed, for example, by blood reflux.

[000249] Figure 38A is a plan view showing a delivery system housing 102 held in a left hand LH. Figure 38B is a plan view showing delivery system housing 102 held in a right hand RH. In the embodiment of figure 38A, cannula 108 is disposed in a left handed position. In the embodiment of figure 38B, cannula 108 is disposed in a right handed position. The right handed position and the left handed position are rotated about one hundred and eighty degrees from each other causing trough portion 189 of distal opening 132 of cannula 108 to be visible in both Figure 38A and Figure 38B.

[000250] As shown in Figures 38A-38B, the body of cannula 108 extends along a longitudinal center axis 196. Longitudinal center axis 196 includes a curved portion so that longitudinal center axis 196 defines a curvature plane 148. In some embodiments, trough portion 189 of distal opening 132 is symmetrical about curvature plane 148. A tapered distal tip of cannula 108 is also symmetrical about the curvature plane 148. The symmetrical design of cannula 108 allows both left handed users and right handed users to use the cannula in substantially the same way.

[000251] The scope of the claims should not be limited by particular embodiments set forth herein, but should be construed in a manner consistent with the specification as a whole.

CLAIMS:

1. A system comprising:

a cannula having a side wall defining a passageway, the cannula having a curved distal portion extending between a distal end and a proximal portion along a radius of curvature, the cannula including an opening extending through the distal end and the side wall to form a trough portion, the opening fluidly communicating with the passageway;

an ocular implant disposed inside the passageway defined by the cannula; and

a delivery tool having a distal interlocking portion engaging a complementary interlocking portion of the ocular implant to form a mechanically interlocking connection when the interlocking portion of the delivery tool is proximal to the trough portion of the cannula, the delivery tool distal interlocking portion having a curved at-rest shape having a smaller radius of curvature than the radius of curvature of the cannula distal portion, the cannula side wall preventing the delivery tool distal interlocking portion from assuming its at-rest shape when the delivery tool distal interlocking portion is proximal to the trough portion of the cannula.

2. The system of claim 1, wherein the delivery tool distal interlocking portion at-rest shape is a curve having a smaller radius of curvature than a radius of curvature of the cannula.

3. The system of claim 1, wherein the system comprises a cannula subassembly including the cannula and a delivery tool subassembly including the delivery tool, the delivery tool subassembly and the cannula subassembly engaging one another at a keyed interface, the keyed interface being configured to permit the delivery tool to slide along the passageway defined by the cannula, and the keyed interface being configured to prohibit rotation of the delivery tool subassembly relative to the cannula subassembly so that a predetermined orientation between the delivery tool and the cannula is maintained.

4. The system of claim 1, wherein the delivery tool subassembly includes a rotating rack gear defining a shaped hole having a predetermined shape in lateral cross-section and the

cannula subassembly including a shaped portion configured to cooperate with the shaped hole of the rotating rack gear so that the delivery tool is free to slide along the passageway defined by the cannula and rotation of the delivery tool relative to the cannula is prohibited.

5. The system of claim 1, wherein the delivery tool further comprises a cannula wall engagement surface diametrically opposite the interlocking portion and a reduced diameter portion proximal to the interlocking portion.

6. The system of claim 1, wherein the mechanically interlocking connection is configured to preclude axial movement of the ocular implant relative to the delivery tool.

7. The system of claim 1, wherein the mechanically interlocking connection is configured to preclude rotation of the ocular implant relative to the delivery tool.

8. The system of claim 1, wherein the mechanically interlocking connection comprises a peak of the delivery tool that is received in a valley of the ocular implant.

9. The system of claim 1, wherein the mechanically interlocking connection comprises a peak of the ocular implant that is received in a valley of the delivery tool.

10. The system of claim 1 further comprising a motion control mechanism configured to be operated from a location outside of the eye to move the delivery tool and the ocular implant along the passageway defined by the cannula.

11. A system configured to deliver an ocular implant into Schlemm's canal of an eye, comprising:

a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion; and

a delivery tool slidably insertable into the lumen of the cannula, the delivery tool having a distal interlocking portion configured to mechanically interlock with a proximal interlocking portion of the ocular implant, the delivery tool being biased to bend radially through the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

12. The system of claim 11, wherein the delivery tool further comprises a ribbon portion proximal to the distal interlocking portion that is biased to assume a curved resting shape when no external forces are acting thereon.

13. The system of claim 12, wherein the ribbon portion is sized and configured to track along the widest part of an interior of the lumen of the cannula.

14. The system of claim 12, wherein a thickness of the ribbon portion is selected so as to enable the ribbon portion to preferentially bend along a preferential bending plane.

15. The system of claim 14, wherein the delivery tool is oriented within the cannula so that the preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula.

16. The system of claim 11, wherein the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than an inner diameter of the lumen of the cannula so that the distal interlocking portion can form a mechanically interlocking connection with the proximal interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

17. The system of claim 11, wherein the distal trough portion has a trough depth greater than a height of the ocular implant so that a distal end of the ocular implant will travel

between an inner surface of the distal trough portion and tissue stretched over the distal trough portion as the ocular implant is advanced.

18. The system of claim 11, wherein the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

19. The system of claim 12, wherein the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the cannula.

20. An ocular implant and delivery system, comprising:

an ocular implant sized and configured to be implanted inside Schlemm's canal of an eye, the ocular implant comprising a proximal interlocking portion;

a curved cannula sized and configured to be advanced partially inside Schlemm's canal, the cannula having a distal trough portion which defines an open groove and a lumen extending along a length of the cannula into the distal trough portion; and

a delivery tool slidably insertable into the lumen of the cannula, the delivery tool having a distal interlocking portion configured to mechanically interlock with the proximal interlocking portion of the ocular implant, the delivery tool being biased to bend radially through the open groove of the distal trough portion to disengage from the ocular implant when the distal interlocking portion of the delivery tool is advanced into the distal trough portion of the cannula.

21. The system of claim 20, wherein the delivery tool further comprises a ribbon portion proximal to the distal interlocking portion that is biased to assume a curved resting shape when no external forces are acting thereon.

22. The system of claim 21, wherein the ribbon portion is sized and configured to track along the widest part of an interior of the lumen of the cannula.

23. The system of claim 21, wherein a thickness of the ribbon portion is selected so as to enable the ribbon portion to preferentially bend along a preferential bending plane.

24. The system of claim 23, wherein the delivery tool is oriented within the cannula so that the preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula.

25. The system of claim 20, wherein the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than an inner diameter of the lumen of the cannula so that the distal interlocking portion can form a mechanically interlocking connection with the proximal interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

26. The system of claim 20, wherein the distal trough portion has a trough depth greater than a height of the ocular implant so that a distal end of the ocular implant will travel between an inner surface of the distal trough portion and tissue stretched over the distal trough portion as the ocular implant is advanced.

27. The system of claim 20, wherein the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

28. The system of claim 21, wherein the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the cannula.

29. A system for delivering an ocular implant into Schlemm's canal of an eye, the ocular implant comprising a wall having a wall thickness, the system comprising:

a cannula comprising a cannula wall, the cannula wall including first portion and a second portion, both portions of the cannula wall extending along a longitudinal center axis having a curved portion, the first portion of the cannula wall being disposed on a radially

inward side of the longitudinal center axis and the second portion of the cannula wall being disposed on radially outward side of the longitudinal center axis;

the cannula wall defining a trough opening through the first portion of the cannula wall and a lumen extending from the trough to a proximal end of the cannula, the cannula wall being sized and configured so that the trough and the lumen define a pathway extending from a location outside of the eye to a location inside Schlemm's canal when a distal point of the cannula is inside Schlemm's canal of the eye;

a delivery tool extending into the lumen of the cannula, the delivery tool comprising a proximal portion, a distal interlocking portion, and a ribbon portion extending between the proximal portion and the distal interlocking portion;

the distal interlocking portion of the delivery tool forming a mechanically interlocking connection with a complementary interlocking portion of the ocular implant when disposed in the lumen of the cannula; and

the distal interlocking portion of the delivery tool moving through the trough opening of the cannula when the distal interlocking portion of the delivery tool reaches a predetermine location along the pathway so that the mechanically interlocking connection is broken.

30. The system of claim 29, wherein:

the ribbon portion of the delivery tool is biased to assume a curved resting shape when no external forces are acting thereon;

the ribbon portion the delivery tool moves toward the curved resting shape when the delivery tool reaches the predetermined location along the pathway; and

the interlocking portion of the delivery tool disengages the complementary interlocking portion of the ocular implant when the delivery tool is free to move toward the curved resting shape.

31. The system of claim 29, wherein:

the ribbon portion has an outer diameter and a thickness extending between a first major side of the ribbon portion and a second major side of the ribbon portion; and

the outer diameter of the ribbon portion is only slightly smaller than the inner diameter of the cannula so that the ribbon portion tracks along the widest part of the cannula lumen and so that support provided by the cannula wall makes it less likely that ribbon portion will buckle.

32. The system of claim 31, wherein the outer diameter of the ribbon portion is smaller than the inner diameter of the cannula by a clearance value.

33. The system of claim 32, wherein the clearance value is less than two times the wall thickness of the ocular implant.

34. The system of claim 32, wherein the clearance value is between about 0.0005 inches and about 0.0010 inches.

35. The system of claim 31, wherein the thickness of the ribbon portion is selected so that the ribbon portion preferentially bends along a preferential bending plane.

36. The system of claim 31, wherein an aspect ratio of the diameter to the thickness is selected so that the ribbon portion preferentially bends along a preferential bending plane.

37. The system of claim 31, wherein the delivery tool is oriented within the cannula so that a preferential bending plane of the ribbon portion is co-planar with a curvature plane of the cannula, the curvature plane being defined by the central axis of the cannula.

38. The system of claim 29, wherein the ocular implant and the distal interlocking portion of the delivery tool both have an outer diameter slightly smaller than the inner diameter of the cannula so that the distal interlocking portion can form a mechanically interlocking connection with the complimentary interlocking portion of the ocular implant, the mechanically interlocking connection being configured to prevent jamming and unintentional release of the ocular implant.

39. The system of claim 38, wherein the outer diameter of both the ocular implant and the distal interlocking portion of the delivery tool is smaller than the inner diameter of the cannula by a clearance value.

40. The system of claim 39, wherein the clearance value is less than two times the wall thickness of the ocular implant.

41. The system of claim 39, wherein the clearance value is between about 0.0005 inches and about 0.0010 inches.

42. The system of claim 39, wherein the trough opening has a width that is substantially equal to an inner diameter of the cannula and both the ribbon portion and the distal interlocking portion of the delivery tool have an outer diameter slightly smaller than the inner diameter of the cannula so that so that a distal portion of the delivery tool can pass through the trough opening when the delivery tool reaches the predetermined location along the pathway defined by the cannula.

43. The system of claim 42, wherein the outer diameter of both the ribbon portion and the distal interlocking portion of the delivery tool is smaller than the inner diameter of the cannula by a clearance value.

44. The system of claim 43, wherein the clearance value is less than two times the wall thickness of the ocular implant.

45. The system of claim 44, wherein the clearance value is between about 0.0005 inches and about 0.0010 inches.

46. The system of claim 29, wherein the trough has a trough depth greater than a height of the implant so that the distal end of the ocular implant will travel between an inner surface of

the cannula and tissue stretched over the trough as the ocular implant is advanced along the path defined by the lumen and the trough.

47. The system of claim 29, wherein the trough is symmetrical about a curvature plane of the cannula so that the cannula can be used by both left handed users and right handed users in substantially the same way.

48. The system of claim 29, wherein the curved portion of the longitudinal central axis of the cannula has a radius of curvature that is smaller than a radius of curvature of the ocular implant.

49. The system of claim 29, wherein the ribbon portion of the delivery tool has a resting radius of curvature that is smaller than a radius of curvature of the curved portion of the longitudinal central axis of the cannula.


50. The system of claim 29, wherein a delivery tool subassembly and a cannula subassembly of the system engage one another at a keyed interface, the keyed interface being configured to permit the delivery tool to slide along the passageway defined by the cannula and the keyed interface being configured to prohibit rotation of the delivery tool subassembly relative to the cannula subassembly so that a coplanar relationship between a bending plane of the ribbon portion and a curvature plane of the cannula is maintained.

51. The system of claim 29, wherein the distal interlocking portion of the delivery tool engages the complementary interlocking portion of the ocular implant to form a mechanically interlocking connection when the distal interlocking portion of the delivery tool is disposed in the lumen of the cannula.

52. The system of claim 29, wherein the cannula wall holds the ribbon portion of the delivery tool in a deformed shape when the distal interlocking portion of the delivery tool is disposed in the lumen of the cannula.

53. Use of the system of any one of claims 1 to 52 for deploying or delivering an ocular implant into Schlemm's canal of an eye.

1 / 45



2 / 45




FIG. 2




FIG. 3

4 / 45





FIG. 4

5 / 45






FIG. 6A




FIG. 6B




FIG. 7

8 / 45




FIG. 8

9 / 45






FIG. 8A

10 / 45



11 / 45






FIG. 11




FIG. 13




FIG. 14

16 / 45




FIG. 15

17 / 45




FIG. 16

18 / 45




FIG. 17




FIG. 18

20 / 45




FIG. 19




FIG. 20B




FIG. 20D




FIG. 20A




FIG. 20C




FIG. 20F




FIG. 20H




FIG. 20E








FIG. 20G



23 / 45







25 / 45












FIG. 27A






FIG. 27E




FIG. 27F

FIG. 27B




FIG. 27H




FIG. 27G

32 / 45





FIG. 27i

33 / 45








FIG. 28



36 / 45




FIG. 30A




FIG. 30B




FIG. 31

39 / 45




FIG. 32




FIG. 33

41 / 45




FIG. 34

42 / 45




FIG. 35




FIG. 36

44 / 45




FIG. 37




FIG. 38A




FIG. 38B

