





(22) Date de dépôt/Filing Date: 2007/04/05  
 (41) Mise à la disp. pub./Open to Public Insp.: 2007/10/07  
 (45) Date de délivrance/Issue Date: 2009/06/23  
 (30) Priorité/Priority: 2006/04/07 (US11/278,986)

(51) Cl.Int./Int.Cl. *B65D 47/36* (2006.01),  
*B32B 7/14* (2006.01), *B65D 53/04* (2006.01)  
 (72) Inventeur/Inventor:  
 DRUMMOND, MICHAEL T., US  
 (73) Propriétaire/Owner:  
 SONOCO DEVELOPMENT, INC., US  
 (74) Agent: SIM & MCBURNEY

(54) Titre : OPERCULE POUR CONTENANT  
 (54) Title: MEMBRANE CLOSURE FOR CONTAINER



(57) Abrégé/Abstract:

A membrane closure for a container is provided. The membrane closure includes an integral tab for removing the membrane closure from the container. The closure includes a lower layer, an adhesive layer, and an upper layer. The lower layer is sealed to the body of a container. The upper layer includes a score pattern that defines a tab area and a fixed area. The adhesive layer includes a first adhesive for releasably attaching the tab area to the lower layer and a second adhesive for permanently bonding the fixed area to the lower layer. The membrane closure is removable from the container by pulling on the tab area.

**ABSTRACT OF THE DISCLOSURE**

A membrane closure for a container is provided. The membrane closure includes an integral tab for removing the membrane closure from the container. The closure includes a lower layer, an adhesive layer, and an upper layer. The lower layer is sealed to the body of a container. The upper layer includes a score pattern that defines a tab area and a fixed area. The adhesive layer includes a first adhesive for releasably attaching the tab area to the lower layer and a second adhesive for permanently bonding the fixed area to the lower layer. The membrane closure is removable from the container by pulling on the tab area.

## MEMBRANE CLOSURE FOR CONTAINER

### BACKGROUND OF THE INVENTION

#### 1) Field of the Invention

The present invention relates to membrane-type closures for product containers.

#### 2) Description of Related Art

Conventional containers for snack foods and other products often have a membrane closure sealed to a top rim of the container and an overcap covering the membrane. The container is initially opened by the consumer by removing and discarding the membrane. Typically, the membrane includes an outwardly projecting tab to aid in the removal of the membrane. The overcap is provided to allow the consumer to re-close the container once the membrane is removed.

In addition to re-closing the container, the overcap is beneficial to the manufacturer and packager of the container. For example, the overcap prevents dust, grease, and other containments from collecting on the container's top membrane closure during the manufacturing and packaging operations. Also, the overcap effectively holds down the tab of the membrane closure against the container and reduces the probability of the tab getting caught or damaged on the equipment during the manufacturing and packaging operations.

Specifically, the membrane closure and the tab are usually cut from a membrane web material as a single piece. The membrane closure is sealed to the container with the tab extending horizontally off the side of the container. When the overcap is applied, the skirt of the overcap engages and pushes the tab down and along the side of the container, where the tab is less likely to get caught or damaged.

However, in order to engage and push the tab down, the overcap must overcome the additional material from the tab along the container bead, which adds to the difficulties of the overcap application process. Also, in some applications, an

overcap adds little to no value for the consumer. For example, in a single-serving container the overcap is discarded with the membrane closure after the initial opening because there is no need to use the overcap to reclose the container. In such applications, it would be beneficial to eliminate the overcap. However, as mentioned above, without the overcap the tab of the membrane closure is more likely to interfere with the manufacturing and packaging operations.

Alternative methods of securing or handling the tab have been considered. For example, the tab may be folded back and heat sealed to the rest of the membrane closure or a material may be used for the membrane closure and tab that allows for the tab to be folded into place (i.e., dead fold retention) either against the rest of the membrane closure or along the side of the container. However, these methods add excessive cost or complexity to the operations.

In light of the foregoing there remains a need to provide a sealable membrane closure for containers that alleviates the need of an overcap to prevent the collection of contaminants onto the membrane closure or to secure the removal means of the membrane closure, i.e. the tab, into a safer position. As always, it would be beneficial for such a membrane closure to be cost-effective and simple to produce.

#### BRIEF SUMMARY OF THE INVENTION

The present invention addresses one or more of the above needs by providing a membrane closure for a container. The membrane closure includes an integral tab for removing at least a portion of the membrane closure from the container. The tab does not extend beyond the container and, thus, minimizes the likelihood of the tab interfering with or being damaged by the manufacturing and packaging operations. Moreover, the tab is releasably secured to the rest of the membrane closure by an adhesive. The adhesive further reduces the likelihood of the tab interfering with the manufacturing and packaging operation. Also, because of the adhesive a particular amount of force is required to start the opening feature, i.e. the tab, of the container, which is preferred by many consumers. The membrane closure may also include a material for the outer or top surface of the membrane closure that does not readily soil, which adds to the aesthetics and cleanliness of the container.

According to one embodiment, the membrane closure includes a lower layer, an upper layer, and an adhesive layer. The upper layer has a score pattern that defines

a first area and a second area. More specifically, the first area forms a tab. The adhesive layer has a first adhesive for attaching the first area to the lower layer and a second adhesive for attaching the second area to the lower layer. The second adhesive is stronger than the first adhesive.

The score pattern may be symmetric or non-symmetric. For example, the score pattern may include two opposite and symmetric lines of weakening that diverge from a common inner point and extend outwardly toward an outer periphery of the membrane closure. Each line of weakening may include an end portion that extends along or away from the outer periphery. Each line of weakening may include a slit portion and a perforated portion.

The first adhesive may be a pressure-sensitive adhesive or low bond-strength adhesive. The second adhesive may be a laminating adhesive or a high bond-strength adhesive. The lower layer may include a barrier material for serving as a barrier to the passage of liquids and gasses and the upper layer may include a top surface formed from a material not readily soiled. Also, the adhesive layer may include an adhesive-free region.

In another aspect, the present invention may provide a container having the membrane closure as described above. The structure and type of the container may vary. For example, the container may be a paperboard container or a molded plastic container. The container includes a body that defines an interior for storing products and an opening into the interior. The lower layer of the membrane closure includes a bottom surface and a top surface. The bottom surface is sealed to the body by a seam. The membrane closure is removable from the container substantially along the seam by pulling the first tab area.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

Figure 1 is a perspective view of a container with a membrane closure according to an embodiment of the present invention;

Figure 2 is a cross-sectional view of the container and membrane closure in Figure 1 taken along line 2-2;

Figure 3 is a partial perspective view of the container and membrane closure of Figure 1 illustrating the separation of the tab away from the lower layer of the membrane closure;

Figure 4 is a partial perspective view of the container and membrane closure of Figure 1 illustrating the membrane closure being removed from the container via the tab of the membrane closure;

Figure 5 is a perspective view of the container and membrane according to another embodiment of the present invention; and

Figure 6 is a cross-sectional view of the container and membrane closure in Figure 5 taken along line 5-5.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention now will be described more fully hereinafter with reference to the accompanying drawings in which some but not all embodiments of the invention are shown. Indeed, this invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout.

The present invention provides a membrane closure **10** for a container **12**. The membrane closure may be adapted for various containers. For example, the container may be a spirally wound paperboard container or a molded plastic container, as known in the art. For illustrative purpose only, the figures depict a container **12** with a tubular body **14** that extends from a top end **16** to a bottom end **18** and defines an interior **20** for storing one or more products. The tubular body is particularly beneficial for packaging food products such as potato crisps or peanuts. Although illustrated as having a circular cross sectional shape, the cross sectional shape of the container may vary.

The body may include at least one structural body ply and be formed by wrapping a continuous strip of body ply material, such as paperboard, around a mandrel of a desired shape to create the body structure. The body ply strip may be spirally wound around the mandrel or passed through a series of forming elements so as to be wrapped in a convolute shape around the mandrel. At the downstream end of the mandrel, the body structure may be cut into discrete container bodies.

The body may also include an innermost liner ply. The liner ply may be supported or unsupported as described in U.S. Patent No. 6,270,004, which is assigned to the assignee of the present invention and is herein incorporated by reference. In general, the liner prevents liquids from leaking out of the container and prevents liquids from entering the container and contaminating or degrading the products contained within the interior of the container. The liner may also be resistant to the passage of gases, so as to prevent odors of the products in the container from escaping or preventing atmospheric air and/or water vapor from entering the container and possibly spoiling the products. The liner ply may have multiple layers including polymeric layers and barrier layers as described in U.S. Patent Application Publication No. 2003/0038170, which is assigned to the assignee of the present invention and is herein incorporated by reference.

The bottom end **18** of the illustrated container **12** defines a bottom opening (not visible in the figures). The bottom opening may be hermetically closed by any suitable closure **19**, such as a crimped metal end or double seamed end or the like, as known in the art.

The membrane closure **10** of the present invention may be adapted for closing the top opening of the container **12**, which is defined by the top end **16**. According to an embodiment of the present invention, the membrane closure **10** includes a lower layer **22**, an adhesive layer **24**, and an upper layer **26**. The lower layer **22** has a bottom surface **28** facing the container **12** and a top surface **30** facing away from the container **12**. The bottom surface **28** is attached substantially along the top end **16** of the container in order to close and seal the top opening. More specifically, the top end **16** may be rolled outwardly to form a rim **17** or a curl or a bead as known in the art. The rim **17** may provide a sealing surface for attaching or engaging the bottom surface **28** of the lower layer. As shown, the bottom surface **28** may be defined by a heat-sealable portion or coating **32** of the lower layer for heat sealing the lower layer **22** to the rim **17** or an adhesive or other suitable sealant may be applied for sealing the lower layer to the top end.

The lower layer **22**, as well as the rest of the membrane closure **10**, is configured to be removable from the container **12**. For example the attachment of the lower layer **22** to the top rim **17** may define a seam **36** between the membrane closure **10** and the container **12**. The peel strength of the seam **36** is weaker than the ultimate strength of the lower layer **22**. Therefore, after sealing the lower layer **22** to the

container **12**, the lower layer **22** may be peeled from the container **12** substantially along the seam **36**.

The lower layer **22** may also include a barrier material or portion **34** that serves as a barrier to the passage of liquids and/or gasses such as oxygen. For example, the barrier material **34** may be any of the following: aluminum foil, polyethylene terephthalate (PET), modified polyethylene terephthalate, polyethylene naphthalate, polyamide, metallized and silicate coated polyester, metallized and silicate coated polypropylene, metallized polyamide, polyvinylidene chloride, ethylene vinyl alcohol, and mixtures thereof.

The upper layer **26** includes a top surface **38** facing away from the container **12** and a bottom surface **40** facing toward the container **12**. As explained in more detail below, the adhesive layer **24** attaches the bottom surface **40** of the upper layer to the top surface **38** of the lower layer. The upper layer **26** may include a variety of materials. For example purposes only, and not by way of limitation, the upper layer may comprise polyethylene terephthalate, modified polyethylene terephthalate, polyethylene naphthalate, or any other material for providing a top surface that is not readily soiled. The thickness of the upper layer **26** may vary. For example, in one embodiment, 48 gauge PET may be used to form the upper layer.

As illustrated, the upper layer **26**, as well as the lower layer **22**, may be shaped to generally overlie the top end **16** of the container **12** and extend minimally, if at all, beyond the body **14** of the container. In some applications, not extending beyond the container body would be beneficial in that it would reduce the risk of the membrane closure getting snagged, caught, or damaged during the manufacturing and packaging operations. For example, in the illustrated embodiment, the upper layer **26** and the lower layer **22** are generally circular in shape to match the circular shaped top end **16** of the container.

As best seen in Figure 1, the upper layer **26** includes a score pattern **42**. The score pattern **42** defines a first tab area **44** and a second fixed area **46** of the upper layer. The shape and size of the score pattern may vary. In general, the score pattern **42** is adapted for providing or forming a means for removing the membrane closure **10** from the container **12**, referred to herein as a tab. For example, and as illustrated, the score pattern **42** may have a "U" or "V" shape formed by two opposite and symmetric lines of weakening **48**, **49** that diverge from a common inner point **50** or apex and extend outwardly toward an outer periphery **52** of the membrane closure.

Each of the lines of weakening **48, 49** may also include an end portion **58** that extends along the outer periphery **52** for a predetermined distance in an opposite direction from the other line of weakening, as illustrated in Figure 1. In particular, as the end portions **58** of the lines of weakening extend along the outer periphery, they are generally extending in a circular manner and parallel to and inside of the seam between the top end of the container and the membrane closure. The end portions **58** are exaggerated in length in Figure 1. The end portions **158** alternatively can be curved away from the outer periphery **52** as shown in Figure 5. Such end portions **158** help prevent tearing of the upper layer **26** when the tab **44** is pulled. Also, the natural tear properties of the upper layer material may be used to help control the tearing in the upper layer. For example, as stated above, the material of the upper layer may be polyethylene terephthalate, which has a lesser resistance to tearing in one predetermined direction, referred to herein as a tear direction. The tear direction may be aligned with portions of the lines of weakening to promote tearing along the lines. Although the illustrated embodiments depict generally symmetric score patterns and a symmetric membrane closure, it should be understood that other embodiments of the present invention may include non-symmetric score patterns and/or non-symmetric membrane closures.

The lines of weakening **48, 49** may include slits, perforations or other alterations that are intended to weaken the upper layer **26** along the lines **48, 49** such that the upper layer **26** is likely to tear along the lines **48, 49**. For example, the lines **48, 49** may start as a slit near the inner point **50** (or the closed end of the “U” or “V”) of the score pattern and become a series of perforations as the lines extend to the outer periphery **52** (or the open end of the “U” or “V”). The slit near the inner point **50** of the score pattern is intended to allow a user to grasp the first tab area **44** at the apex **50** and then lift the rest of the first tab area **44** of the upper layer away from the lower layer **22**, as shown in Figure 3.

As mentioned, the adhesive layer **24** connects the upper layer **26** to the lower layer **22**. More specifically and as shown in Figure 2, the adhesive layer **24** includes a first adhesive **54** for connecting the first tab area **44** of the upper layer to the lower layer **22** and a second adhesive **56** for connecting the second fixed area **46** of the upper layer to the lower layer **22**. The second adhesive **56** is for substantially holding or fixing the second fixed area **46** of the upper layer to the lower layer **22**, including while the first tab area **44** is being pulled away from the lower layer and while the

membrane closure **10** is lifted away from the container **12**. The second adhesive may be a variety of adhesives, such as a high bond-strength or “permanent” laminating adhesive. One consideration is that the second adhesive **56** is stronger than the first adhesive **54** such that the second fixed area **46** of the upper layer remains substantially fixed to the lower layer **22** while the first tab area **44** is being pulled away from the lower layer **22**. Also, the second adhesive **56** may be effectively stronger than the seam **36** between the membrane closure and the container such that the second fixed area **46** of the upper layer remains substantially fixed to the lower layer **22** while the membrane closure **10** is being pulled away from the container **12**.

One of the features of the present invention is the first adhesive **54** connecting the first tab area **44** of the upper layer to the lower layer **22**. To allow the first tab area **44** to be lifted away from the lower layer **22** with a minimal likelihood of tearing outside of the score pattern **42**, the peel strength of the first adhesive **54** is less than the ultimate strength of the first tab area **44**. The first adhesive may be a variety of adhesives, such as a peelable or low bond-strength adhesive or a pressure-sensitive adhesive. The first adhesive **54** is intended to reduce the likelihood of an inadvertent lifting of the first tab area **44** or the likelihood of the first tab area **44** interfering with or being damaged by the manufacturing and packaging operations. Moreover, consumers prefer that some amount of force is required to start an opening feature of a container. In some applications, a required opening force may reassure a consumer on the integrity of the container.

The membrane closure **10** may be made from a variety of methods. For example purposes only, and not by way of limitation, the adhesives **54**, **56** may be pattern-printed onto one of the layers **22**, **26**, followed by adhesive lamination of the layers to each other. The scoring of the upper layer can be done before or after the lamination step; in either case, the score pattern should be substantially aligned with the adhesive areas.

Figures 3 and 4 provide an illustration of the removal of the membrane closure **10** from the container **12**, according to an embodiment of the present invention. As shown in Figure 3, a user may grab and pull the first tab area **44** near the apex **50** such that some or all of the first tab area **44** is lifted away from the lower layer **22** while the rest of the upper layer, i.e., the second fixed area **46**, remains fixed to the lower layer **22**. The relatively low peel strength of the first adhesive **54** compared to the ultimate strength of the first tab area **44** facilitates the lifting of the first tab area **44** along the

lines of weakening 48, 49 from the inner point 50 toward the outer periphery 52. Although described as lifting, in the applications with perforated portions, the lifting may also include tearing along the weaken lines. The amount of force necessary to lift the first tab area 44 away from the lower layer 22 is generally considered an opening force.

The end of the lines of weakening 48, 49 adjacent the outer periphery 52 stop the lifting of the first tab area 44 such that the further pulling of the first tab area 44 will remove the membrane closure 10 from the container 12 as shown in Figure 4. More particularly, the user provides a pulling force (i.e. the opening force) that is strong enough to overcome the peel strength of the first adhesive 54 that is holding the first tab area 44 to the lower layer 22 and to separate any perforations along the lines of weakening 48, 49. However, once the first tab area 44 is lifted and the ends of the lines of weakening 48, 49 are reached, in order to further lift the first tab area 44 or other portions of the upper layer 26 away from the lower layer 22, the pulling force would have to overcome the second adhesive 56 that is holding the second fixed area 46 of the upper layer to the lower layer 22 or the ultimate strength of the material of the upper layer 26. Furthermore, the lines of weakening 48, 49 near their ends extend generally perpendicular from the general direction of the pulling force which also increases the resistance of tearing more of the upper layer 26. Because the strength of the seam 36 between the lower layer 22 and the top end 16 of the container is effectively weaker than the strength of the second adhesive or the ultimate strength of the membrane closure 10, additional pulling causes the separation of the lower layer 22, and thus the membrane closure 10, from the top end 16 of the container along the seam 36. The force necessary to separate the lower layer 22 from the top end 16 along the seam 36 is generally considered a seal force.

Although the membrane closure is generally described above as being removed from the top end of the container, in some applications, it may be desirable to remove only a portion of the membrane closure from the top end. For example, in applications where the container stores a pourable product, the first tab area may be adapted for removing only a portion of the membrane closure from the top end of the container, such that the removed portion of the membrane closure defines a pourable opening from which to pour the product through.

Also, in other applications, the majority of the lower layer may be torn away from the top end of the container rather than separated along the seam. More

specifically, as stated above, according to one embodiment, the end portions of the first tab area may include perforated portions that extend generally parallel and inside of the seam between the lower layer and top end of the container. Once the first tab area is lifted to the end portions, additional pulling may cause the lower layer to tear between the seam and the end portions due to the strength of the seam, strength of the second adhesive that is located between the end portions and the seam, and the strength of the material of the lower layer. Therefore, a portion of the lower layer may remain affixed to the top end of the container after the removal of the membrane closure.

The membrane closure **10** may also include an adhesive-free region **160** in the first tab area **44** to facilitate initial grasping of the first tab area **44**, as illustrated in the embodiment of Figures 5 and 6. In the adhesive-free region **160**, the upper layer **26** is not adhered to the lower layer **22**. The adhesive-free region **160** preferably is located at the apex **50** of the first tab area **44**.

Many modifications and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

## THAT WHICH IS CLAIMED:

1. A membrane closure comprising:  
a lower layer;  
an upper layer having a score pattern defining a first area and a second area,  
wherein the first area forms a tab;  
an adhesive layer having a first adhesive for attaching the first area to the  
lower layer and a second adhesive layer for attaching the second area to the lower  
layer to, wherein the second adhesive is stronger than the first adhesive.
2. The membrane closure according to Claim 1, wherein the score pattern  
includes two opposite and symmetric lines of weakening that diverge from a common  
inner point and extend outwardly toward an outer periphery of the membrane closure,  
each line of weakening including an end portion adjacent the outer periphery.
3. The membrane closure according to Claim 2, wherein the end portions  
of the lines of weakening extend along the outer periphery for a predetermined  
distance in opposite directions from each other.
4. The membrane closure according to Claim 2, wherein the end portions  
of the lines of weakening extend generally away from the outer periphery.
5. The membrane closure according to Claim 2, wherein each line of  
weakening includes a slit portion and a perforated portion.
6. The membrane closure according to Claim 1, wherein the score pattern  
is non-symmetric.
7. The membrane closure according to Claim 1, wherein the first  
adhesive is a pressure-sensitive adhesive and the second adhesive is a laminating  
adhesive.
8. The membrane closure according to Claim 1, wherein the lower layer  
includes a barrier material for serving as a barrier to the passage of liquids and gasses.

9. The membrane closure according to Claim 1, wherein the upper layer includes a top surface formed from a material not readily soiled.

10. The membrane closure according to Claim 1, wherein the adhesive layer defines an adhesive-free region.

11. A container for storing products, the container comprising:  
a body defining an interior for storing products and an opening into the interior;  
a membrane closure sealed to the body for closing the opening, the membrane closure including:  
a lower layer having a bottom surface and a top surface, wherein the bottom surface is sealed to the body by a seam;  
an upper layer having a score pattern defining a first tab area and a second fixed area;  
an adhesive layer having a first adhesive for attaching the first tab area to the top surface of the lower layer and a second adhesive layer for attaching the second fixed area to the top surface of the lower layer, wherein the second adhesive is stronger than the first adhesive; and  
wherein at least a majority of the membrane closure is removable from the container substantially along the seam by pulling the first tab area.

12. The container according to Claim 11, wherein the container is a paperboard container.

13. The container according to Claim 11, wherein the container is a molded plastic container.

14. The container according to Claim 11, wherein the score pattern includes two opposite and symmetric lines of weakening that diverge from a common inner point and extend outwardly toward an outer periphery of the membrane closure.

15. The container according to Claim 14, wherein each line of weakening includes a slit portion and a perforated portion.

16. The container according to Claim 11, wherein the first adhesive is a pressure-sensitive adhesive and the second adhesive is a laminating adhesive.

17. The container according to Claim 11, wherein the bottom surface of the lower layer includes a heat sealable material for forming the seam between the lower layer and the body.

18. The container according to Claim 11, wherein the lower layer includes a barrier material for serving as a barrier to the passage of liquids and gasses.

19. The container according to Claim 11, wherein the upper layer includes a top surface formed from a material not readily soiled.

20. A membrane closure for a container, the membrane closure comprising:  
a lower layer sealed to the container;  
an upper layer having a score pattern defining a tab area and a fixed area; and  
an adhesive layer having a first adhesive for releasably attaching the tab area to the lower layer and a second adhesive for permanently bonding the fixed area to the lower layer;

wherein at least a portion of the lower layer is removable from the container by pulling the tab area.

21. The membrane closure according to Claim 20, wherein the score pattern has a general V-shape with an open end near an outer periphery of the upper layer and a closed end near an inner point of the upper layer.

22. The membrane closure according to Claim 20, wherein the score pattern includes a slit portion and a perforated portion.

23. The membrane closure according to Claim 20, wherein the score pattern is non-symmetric.




FIG. 1




FIG. 2




FIG 3




FIG 4




FIG. 5




FIG. 6

