



(43) International Publication Date
20 December 2012 (20.12.2012)

(51) International Patent Classification:

A45D 1/04 (2006.01) A45D 1/08 (2006.01)
A45D 1/06 (2006.01) A45D 1/28 (2006.01)

(21) International Application Number:

PCT/AU2012/000686

(22) International Filing Date:

15 June 2012 (15.06.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2011902370 17 June 2011 (17.06.2011) AU

(71) Applicant (for all designated States except US): **WISE-
TYPE INVESTMENTS PTY LTD** [AU/AU]; 3 Barletta
Place, Mindarie, Western Australia 6030 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COCKS, Janet
Elizabeth** [AU/AU]; 3 Barletta Place, Mindarie, Western
Australia 6030 (AU). **VINE, Anne Lynette** [AU/AU]; 16
Collaroy Court, Kallaroo, Western Australia 6025 (AU).
KHOURY, Edward Joseph [AU/AU]; 19 Scouler Way,
Bateman, Western Australia 6150 (AU).

(74) Agent: **HOLLIDAY, Neal Joseph**; c/- Armour IP, PO
Box 67, Burswood, Western Australia 6100 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: HAIR IRON




Fig 1

(57) Abstract: A hair iron (10) comprising first and second side members (12, 14) pivotally connected adjacent first ends (16) thereof. A first heating plate (22) is provided on a first surface (18) of the first side member (12) and a second heating plate (24) is provided on a first surface (18) of the second side member (14) such that moving the first and second side members (12, 14) to a closed position engages a section of hair between the first and second heating plates (22, 24). Second ends (17) of the first and second side members (12, 14) are tapered to aid separating the section of hair by sliding the hair iron (10) longitudinally into the hair. Opposed first and second longitudinal edges (34, 35) of the first surfaces (18) of the first and second side members (12, 14) are each curved such that the first longitudinal edges (34) are concave in shape.

“HAIR IRON”**Field of the Invention**

[001] The present invention relates to a hair iron.

Background to the Invention

[002] Many people wish to treat their hair to either create increased volume or to straighten the hair. For people with relatively fine hair that sits flat against the head, it may be desired to treat the hair to lift the hair away from the head and create the appearance of a fuller head of hair. Crimping irons can be used to add small waves to portions of the hair near the scalp to make the hair stand away from the head and provide increased volume. Crimping irons generally comprise a pair of heated plates that can be pivoted together around sections of hair.

[003] Hair straightening irons for straightening wavy or curly hair comprise a similar construction. That is, a pair of heated plates that can be engaged around sections of hair to heat the hair and straighten it. In the case of straightening irons, the heated plates include a flat surface.

[004] The present invention relates to an improved hair iron construction that may be used for treating the hair, including straightening and volumizing. The construction of the hair iron makes the process of separating and treating sections of the hair easier.

Summary of the Invention

[005] According to one aspect of the present invention there is provided a hair iron comprising:

first and second side members pivotally connected adjacent first ends thereof;
a first heating plate provided on a first surface of the first side member; and

a second heating plate provided on a first surface of the second side member such that moving the first and second side members to a closed position engages a section of hair between the first and second heating plates; wherein second ends of the first and second side members are tapered to aid separating the section of hair by sliding the hair iron longitudinally into the hair and wherein opposed first and second longitudinal edges of the first surfaces of the first and second side members are each curved such that the first longitudinal edges are concave in shape.

[006] Preferably the curves in the first and second longitudinal edges extend from a location between the first and second ends of the first and second arm members to the second ends thereof.

[007] Preferably the first and second longitudinal edges of the first and second arm members are parallel to each other from the first ends thereof to a location between the first and second ends thereof and wherein the curve of the second longitudinal edge is greater than that of the first longitudinal edge from said location between the first and second ends to the second end such that the first and second longitudinal edges approach each other to form a tapered end portion adjacent the second end.

[008] Preferably the first and second side members each include a second side surface which is arcuate in transverse cross section such that each second side surface extends from the first longitudinal edge of the first side surface to the second longitudinal edge of the first side surface.

[009] In a preferred embodiment, the second side surfaces of the first and second side members decrease in height above the respective first side surfaces towards the second end.

[010] In one embodiment, the arcuate shape of the longitudinal cross section of the second side surfaces decrease in size towards the second end such that the tapered end portion decreases in cross sectional size towards the second end.

[011] Each of the heating plates preferably extends along a portion of the length of the respective side member from a location adjacent the second end to a location between the second end and the first end.

[012] In one embodiment, a heat control is provided to control the heat applied to the first and second heating plates. The heat control preferably comprises a dial located on the first side surface of the second side member such that a portion of the periphery thereof extends outwardly beyond the first longitudinal edges of the first and second side members.

[013] In one embodiment, the hair iron further comprises:
a plurality of longitudinal corrugations provided on the first heating plate; and
a plurality of longitudinal corrugations provided on the second heating plate being complementary in shape to the corrugations on the first heating plate such that the first and second side members can be pivoted between a closed position in which the corrugations on the first heating plate engage with the corrugations on the second heating plate and an open position in which the first and second heating plates are separated to receive hair;
wherein moving the first and second side members to the closed position engages the section of hair between the first and second heating plates and crimps the hair adjacent the scalp to create volume.

[014] The corrugations may decrease in amplitude moving in a direction away from a first longitudinal edge towards a second longitudinal edge. Preferably the corrugations define a generally square waveform decreasing in amplitude from the first longitudinal edge towards the second longitudinal edge.

[015] In a further embodiment, upper surfaces of the first and second heating plates are flat to provide for straightening of hair engaged between the heating plates.

Brief Description of the Drawings

[016] The invention will now be described, by way of example, with reference to the following drawings, in which:

[017] Figure 1 is an upper perspective view of a hair iron in accordance with the present invention;

[018] Figure 2a is a side view of the hair iron of Figure 1;

[019] Figure 2b is a cross sectional view of the hair iron of Figure 2a through the line A-A;

[020] Figure 3a is a top view of the hair iron of Figure 1;

[021] Figure 3b is a cross sectional view of the hair iron of Figure 3a through the line B-B;

[022] Figure 4a is an upper perspective view of the heating plates of the hair iron of Figure 1;

[023] Figure 4b is a top view of the heating plates with the shape of the corrugations shown in broken lines;

[024] Figure 4c is a cross sectional view of the heating plates of Figure 4b through the line A-A;

[025] Figure 4d is a cross sectional view of the heating plates of Figure 4b through the line B-B;

[026] Figure 4e is a cross sectional view of the heating plates of Figure 4b through the line C-C;

[027] Figure 5a is a side view of the hair iron of Figure 1;

[028] Figure 5b is a close up view of Detail A of Figure 5a; and

[029] Figure 5c is a top view of the hair iron of Figure 1.

Detailed Description of Preferred Embodiments

[030] Referring to Figures, there is shown a hair iron 10 comprising generally a first side member 12 and a second side member 14. Each of the first and second side members 12 and 14 comprises an elongate member having a first end 16 and a second end 17.

[031] The first and second side members 12 and 14 are pivotally connected to each other adjacent the first ends 16. Each of the first and second side members 12 and 14 includes a first side surface 18. The first side surfaces 18 are generally planar and the first side surface 18 of the first side member 12 is adjacent the first side surface 18 of the second side member 14.

[032] The pivotal connection between the first and second side members 12 and 14 is provided by a hinge mechanism 20 located adjacent the first ends 16 of the first and second side members 12 and 14. The first and second side members 12 and 14 are pivotable between a closed position (as shown in Figure 2), in which the first side surface 18 of the first side member 12 is adjacent and parallel to the first side surface 18 of the second side member 14, and an open configuration in which the first and second side members 12 and 14 are moved away from each other.

[033] The hinge mechanism 20 is located offset slightly from the first ends 16 of the first and second side members 12. The first and second side members 12 and 14 can therefore be pivoted to the open position by pressing together the first and second side members 12 and 14 between the hinge mechanism 20 and the first end 16.

[034] The first end 16 of the first side member 12 is provided with a hook 40 for hanging the heating iron 10. The hook 40 comprises a shaft extending outwardly from the first end 16 of the first side member 12 having a ring on a distal end thereof.

[035] In the embodiment shown, each of the first and second side members 12 and 14 includes a second side surface 19, being opposite the first side surface 18. The second side surfaces 19 are arcuate in transverse cross section such that each second side surface 19 extends from a first longitudinal edge 34 of the first side surface 18 to an opposite second longitudinal edge 35 of the first side surface 18.

[036] The first side member 12 is provided with a first heating plate 22 secured to the first side surface 18 thereof. The second side member 14 is provided with a second heating plate 24 secured to the first side surface 18

thereof. Each of the first and second heating plates 22 and 24 includes a lower surface that is secured to the first side surface 18 of the corresponding side member 12 or 14 and an upper surface 21 that is located remote from the lower surface. The upper surface 21 of the first heating plate 22 is therefore arranged adjacent the upper surface 21 of the second heating plate 24 such that the upper surfaces 21 engage when the first and second side members 12 and 14 move to the closed configuration.

[037] Each of the heating plates 22 and 24 extends along a portion of the length of the associated side member 12 or 14 from a location adjacent the second end 17 to a location adjacent a midpoint of the side member 12 or 14.

[038] In the embodiment shown, the heating iron 10 is constructed as a crimping iron in order to add volume to the hair. The upper surfaces 21 of the first and second heating plates 22 and 24 include longitudinal corrugations 26 along the length thereof. It will be appreciated though that in the case of the heating iron 10 being used for straightening the hair, the upper surfaces 21 of the heating plates 22 and 24 would be flat.

[039] The corrugations 26 in the upper surfaces 21 comprise a plurality of ribs extending parallel to longitudinal axes of the side members 12 and 14. The corrugations 26 in the first heating plate 22 are complementary to the corrugations 26 of the second heating plate 24. That is, when the first heating plate 22 engages with the second heating plate 24 (as best seen in Figures 4c to 4e), the ribs of the first heating plate 22 are received between adjacent pairs of ribs on the second heating plate 24.

[040] The hair iron 10 is provided also with a heating element on each of the first and second side members 12 and 14. The heating elements are provided to apply heat to the heating plates 12 and 14. The heating elements comprise electrical heating elements and a power cord 28 is provided extending from the first end of the second side member 14 to supply power to the heating elements.

[041] A heat control may also be provided to control the operation of the heating elements and thereby the temperature of the heating plates 22 and

24. The heat control in the embodiment shown comprises a dial 30 located on the first side surface 18 of the second side member 14 between the second heating plate 24 and the hinge mechanism 20. The dial 30 is located such that a portion of the periphery thereof extends outwardly beyond the first longitudinal edges 34 of the first and second side members 12 and 14, as best seen in Figure 3a. The dial 30 can therefore be operated while the first and second side members 12 and 14 are in the closed position by turning the dial 30 via the extending portion thereof.

[042] The corrugations 26 are provided on the heating plates 24 such that the amplitude thereof decreases moving in a direction moving away from a first longitudinal edge 32 towards a second longitudinal edge 33. That is, the height of the ribs (and therefore the depth of the grooves between the ribs) decreases towards the second longitudinal edge 33. The first longitudinal edge 32 of the heating plates 22 and 24 is the edge oriented closest to the scalp in use.

[043] The ribs in the embodiment shown are generally square in shape. That is, the corrugations define a generally square waveform decreasing in amplitude from the first longitudinal edge 32 towards the second longitudinal edge 33.

[044] The first and second longitudinal edges of the heating plates 22 and 24 and the first and second longitudinal edges 34 and 35 of the first and second side members 12 are each curved. The first and second side members 12 and 14 are curved such that the first longitudinal edge 34 is concave in shape to conform generally to the curvature of the head. The second longitudinal edge 35 of the first and second side members 12 and 14 is curved to generally follow the curve of the first longitudinal edge 34.

[045] In the embodiment shown, the curves in the first and second longitudinal edges 34 and 35 extend from a location between the first and second ends 16 and 17 of the first and second arm members 12 and 14 to the second ends 17 thereof.

[046] From the first ends 16 of the first and second arm members 12 and 14 to a location between the first and second ends 16 and 17 thereof, the first and second longitudinal edges 34 and 35 are parallel to each other. From said location between the first and second ends 16 and 17, the curve of the second longitudinal edge 35 is greater than that of the first longitudinal edge 34 such that the first and second longitudinal edges 34 and 35 approach each other to form a tapered end portion 21 adjacent the second end 17.

[047] Also, the second side surfaces 19 of the first and second side members 12 and 14 decrease in height above the respective first surfaces 18. That is, the arcuate shape of the longitudinal cross section of the second side surfaces 19 decrease in size along a portion adjacent the second end 17 such that the tapered end portion 21 decreases in cross sectional size towards the second end. That is, the tapered end portion 21 tapers down to a point.

[048] The first and second side members 12 and 14 are also provided with an adjustment mechanism to limit the amount by which the first and second side members 12 and 14 move apart. In the embodiment shown, the adjustment mechanism comprises a peg 36 provided through an aperture in the first side member 12 between the hinge mechanism 20 and the first end 16.

[049] An inner end of the peg 36 extends into a space between the first ends 16 of the first and second side members 12 and 14 such that when the side members 12 and 14 are pivoted towards the open position, the first end 16 of the second member 14 engages with the inner end of the peg 36. The peg 36 includes a threaded outer surface to engage with an internal thread in the aperture such that rotating the peg 36 causes an inner end to move towards or away from the second side member 14 to adjust the amount of movement of the side members 12 and 14 before the engagement with the peg 36.

[050] In use, the hair iron 10 is used to treat sections of the hair for straightening or crimping. The first and second side members 12 and 14 are moved to the open configuration and oriented such that the first longitudinal edge 34 is adjacent and generally parallel to the scalp. The tapered end

portions 21 of the first and second side members 12 and 14 are inserted into the hair and the hair iron 10 is then moved longitudinally such that a section of hair is received between the first and second side members 12 and 14. The tapered end portions 21 provide easier separation of a section of hair for treatment.

[051] The hair iron 10 is moved so that a section of hair is received between the first and second side members 12 and 14 with the hair passing generally transversely between the first and second side members 12 and 14 with the hair iron adjacent the scalp. By moving the first and second side members 12 and 14 to the closed position, the portion of the section of hair between the first and second side members 12 and 14 is clamped between the first and second heating plates 22 and 24.

[052] In the case of heating plates 22 and 24 with corrugations 16, the corrugations 26 crimp the portion of the hairs and this crimp is set into the hair by the applied heat. As the corrugations decrease in size towards the second longitudinal edge 33, the size of the crimp in the hair decreases in a direction away from the scalp. Preferably the first rib on the first heating plate (and consequently the corresponding groove on the second heating plate) is located relatively close to the first longitudinal edge 32 such that the first crimp is placed close to the scalp.

[053] The arrangement of the first and second side members 12 and 14 of the hair iron 10 and the heating plates 22 and 24 allows ease of use for separating sections of the hair and crimps the hair only adjacent the scalp, so the remainder of the hair appears straight. The decreasing of the crimp size away from the scalp provides a useful volumizing effect and square wave type crimp is believed to add a significant amount of volume over a relatively short section of hair.

[054] In the case of use as a straightening iron, the heating iron 10 can engage sections of the hair from closely adjacent the scalp and then be moved outwardly to straighten the hair between the heating plates 22 and 24.

[055] It will be readily apparent to persons skilled in the relevant arts that various modifications and improvements may be made to the foregoing embodiments, in addition to those already described, without departing from the basic inventive concepts of the present invention.

Claims

- 5 1. A hair iron comprising:
first and second side members pivotally connected adjacent first ends thereof;
a first heating plate provided on a first surface of the first side member; and
a second heating plate provided on a first surface of the second side member
such that moving the first and second side members to a closed position
10 engages a section of hair between the first and second heating plates;
wherein second ends of the first and second side members are tapered to aid
separating the section of hair by sliding the hair iron longitudinally into the hair
and wherein opposed first and second longitudinal edges of the first surfaces
of the first and second side members are each curved such that the first
15 longitudinal edges are concave in shape.
2. A hair iron in accordance with claim 1, wherein the curves in the first
and second longitudinal edges extend from a location between the first and
second ends of the first and second arm members to the second ends thereof.
- 20 3. A hair iron in accordance with claim 2, wherein the first and second
longitudinal edges of the first and second arm members are parallel to each
other from the first ends thereof to a location between the first and second
ends thereof and wherein the curve of the second longitudinal edge is greater
than that of the first longitudinal edge from said location between the first and
25 second ends to the second end such that the first and second longitudinal
edges approach each other to form a tapered end portion adjacent the second
end.
4. A hair iron in accordance with claim 3, wherein the first and second
side members each include a second side surface which is arcuate in
30 transverse cross section such that each second side surface extends from the
first longitudinal edge of the first side surface to the second longitudinal edge
of the first side surface.

5. A hair iron in accordance with claim 4, wherein the second side surfaces of the first and second side members decrease in height above the respective first side surfaces towards the second end.

6. A hair iron in accordance with claim 5, wherein the arcuate shape of the longitudinal cross section of the second side surfaces decrease in size towards the second end such that the tapered end portion decreases in cross sectional size towards the second end.

7. A hair iron in accordance with any one of the preceding claims, wherein each of the heating plates extends along a portion of the length of the respective side member from a location adjacent the second end to a location between the second end and the first end.

8. A hair iron in accordance with any one of the preceding claims, wherein a heat control is provided to control the heat applied to the first and second heating plates.

9. A hair iron in accordance with claim 8, wherein the heat control comprises a dial located on the first side surface of the second side member such that a portion of the periphery thereof extends outwardly beyond the first longitudinal edges of the first and second side members.

10. A hair iron in accordance with any one of the preceding claims further comprising:

a plurality of longitudinal corrugations provided on the first heating plate; and a plurality of longitudinal corrugations provided on the second heating plate being complementary in shape to the corrugations on the first heating plate such that the first and second side members can be pivoted between a closed position in which the corrugations on the first heating plate engage with the corrugations on the second heating plate and an open position in which the first and second heating plates are separated to receive hair;

wherein moving the first and second side members to the closed position engages the section of hair between the first and second heating plates and crimps the hair adjacent the scalp to create volume.

11. A heating iron in accordance with claim 10, wherein the corrugations provided on the heating plates decrease in amplitude moving in a direction away from a first longitudinal edge towards a second longitudinal edge.

12. A hair iron in accordance with claim 11, wherein the corrugations define
5 a generally square waveform decreasing in amplitude from the first longitudinal edge towards the second longitudinal edge.

13. A hair iron in accordance with any one of claims 1 to 9, wherein upper surfaces of the first and second heating plates are flat to provide for straightening of hair engaged between the heating plates.




Fig 1







Fig 2a



SECTION A-A

Fig 2b

3 / 5










Fig 4c

Fig 4d

Fig 4e




Fig 5b




Fig 5a




Fig 5c

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2012/000686

A. CLASSIFICATION OF SUBJECT MATTER

A45D 1/04 (2006.01) A45D 1/06 (2006.01) A45D 1/08 (2006.01) A45D 1/28 (2006.01)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC: IPC, ECLA: A45D1/- & Keywords (concave, taper, curve) and like terms; USPC: 132/223, 132/224, 132/225, 132/227, 132/229, 132/232, 132/269 & Keywords (concave, taper, curve) and like terms

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	Documents are listed in the continuation of Box C	



Further documents are listed in the continuation of Box C



See patent family annex

• * "A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier application or patent but published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search
14 August 2012Date of mailing of the international search report
15 August 2012

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
Email address: pct@ipaustalia.gov.au
Facsimile No.: +61 2 6283 7999

Authorized officer

Kate Huang
AUSTRALIAN PATENT OFFICE
(ISO 9001 Quality Certified Service)
Telephone No. 0262832889

INTERNATIONAL SEARCH REPORT		International application No.
C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		PCT/AU2012/000686
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/0022184 A1 (LEE) 20 September 2001 Figures 2-3, 7A-7B	1-13
A	US 2008/0236609 A1 (WONG) 02 October 2008 Figures 1-3, 6, 10-12	1-13
A	JP 2003-250627 A (TAKASHI) 09 September 2003 English abstract - Patent Abstracts of Japan, figures 1-3	1-13
A	WO 2000/002465 A1 (VOLUMASTER AB) 20 January 2000 Figures 1-5	1-13

Form PCT/ISA/210 (fifth sheet) (July 2009)

INTERNATIONAL SEARCH REPORT		International application No.	
Information on patent family members		PCT/AU2012/000686	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
US 2001/0022184 A1	20 Sep 2001	JP 2001269213 A	02 Oct 2001
		KR 20010088269 A	26 Sep 2001
		US 2001022184 A1	20 Sep 2001
		US 6386206 B2	14 May 2002
US 2008/0236609 A1	02 Oct 2008	US 2008236609 A1	02 Oct 2008
JP 2003-250627 A	09 Sep 2003	JP 2003250627 A	09 Sep 2003
		JP 4230707 B2	25 Feb 2009
WO 2000/002465 A1	20 Jan 2000	AU 759567 B2	17 Apr 2003
		AU 4949599 A	01 Feb 2000
		BR 9911947 A	27 Mar 2001
		CA 2335765 A1	20 Jan 2000
		CN 1308497 A	15 Aug 2001
		EP 1094731 A1	02 May 2001
		EP 1094731 B1	29 Sep 2004
		HK 1039260 A1	12 Mar 2004
		JP 2002520076 A	09 Jul 2002
		JP 4279464 B2	17 Jun 2009
		SE 9802484 A	10 Jan 2000
		US 6615847 B1	09 Sep 2003
		WO 0002465 A1	20 Jan 2000
End of Annex			
</			