



(51) International Patent Classification:

B60N 2/00 (2006.01) *B60N 2/70* (2006.01)
B60R 21/015 (2006.01)

(21) International Application Number:

PCT/EP2013/071571

(22) International Filing Date:

16 October 2013 (16.10.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

LU 92 087 22 October 2012 (22.10.2012) LU

(71) Applicant: IEE INTERNATIONAL ELECTRONICS & ENGINEERING S.A. [LU/LU]; Zone Industrielle, L-6468 Echternach (LU).

(72) Inventors: KORDEL, Markus; Trevererstrasse 48, 54295 Trier (DE). JUNGES, Dietmar; Im Acker 6, 54552 Mehren (DE). WEIRES, Konstantin; Hunnenkopfstrasse, 15, 54675 Kruchten (DE). WAMPACH, Manuel; 18, rue Jaques Santer, L-6139 Junglinster (LU).

(74) Agents: BEISSEL, Jean et al.; Office Freylinger S.A., 234, Route d'Arlon, P.O. Box 48, L-8001 Strassen (LU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SEAT OCCUPANCY SENSOR UNIT FOR SEAT WITH SPRING SUSPENSION OR SEAT PAN

Fig. 1



(57) Abstract: A pressure-responsive seat occupancy sensor unit (10) comprises a support plate (12) having a top surface (20) and a bottom surface, a plurality of spacer elements (14) defining an upper surface (18) of the pressure-responsive seat occupancy sensor unit, which upper surface the top surface of the support plate is arranged recessed from, a foam pad (22) disposed between the spacer elements on the support plate, a recess (24) formed in the top surface of the support plate, underneath the foam pad, and a pressure-responsive membrane switch (26) arranged in the recess. The recess has a depth exceeding the thickness of the pressure-responsive membrane switch. The foam pad is configured such that, upon it being compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into the recess and activates the pressure-responsive membrane switch.

SEAT OCCUPANCY SENSOR UNIT FOR SEAT WITH SPRING SUSPENSION OR SEAT PAN

Technical field

[0001] The present invention generally relates to sensing the occupancy state of a vehicle seat. Specifically, the invention relates to a pressure-responsive seat occupancy sensor unit for being placed on the bottom side of a seat cushion; i.e. between the seat cushion and the cushion-supporting means such as, e.g. a seat pan, springs etc.

Background Art

[0002] Seat occupancy sensors are nowadays widely used in automotive vehicles to provide a seat occupancy signal for various appliances, such as, e.g. a seat belt reminder, an auxiliary restraint system (airbag), etc. Seat occupancy sensors exist in a number of variants, e.g. based on capacitive sensing, deformation sensing or pressure (force) sensing. Pressure-sensitive seat occupancy sensors have typically been arranged between the foam body of the seat cushion and the seat cover.

[0003] The possibility of customization and personalization of the vehicle by the customer is a key selling factor of modern cars. This leads to many different variants of car interiors being offered for one car model. With the increasing number of available options, severe constraints arise concerning the implementation of technical equipment in the vehicle. With seat occupancy sensors arranged between the foam body of the seat cushion and the seat cover, every seat design (leather, cloth, sport, comfort, ...) requires specific development effort for the occupant detection system. That induces high development costs and therefore is an unattractive solution for the automotive industry. A problem to be solved is, therefore, to find a sensor solution, which is less influenced by seat design and thus can be used for a greater variety of car seats or even car platforms.

[0004] Document DE 197 52 976 A1 discloses a vehicle seat occupancy sensor in the shape of a film-type pressure sensor. The pressure sensor includes a first carrier film, a spacer and a second carrier film, which are disposed on one another in the manner of a sandwich. Contact elements are arranged on the inner surfaces of the carrier films. An opening in the spacer allows the contact elements to get into contact

with each other when pressure is applied on the sensor. The pressure sensor is arranged inside a cavity on the bottom side of the foam cushion of the vehicle seat. The pressure sensor is supported by a foam block, which closes the cavity and which rests on the seat pan.

[0005] Document DE 20 2010 003 563 U1 discloses a pressure-sensor unit, comprising a film-type pressure sensor. The pressure sensor includes two films maintained at a distance by a spacer material arranged there between. The pressure sensor is disposed on a compressible intermediate layer, which is, in turn arranged on a base plate. Document JP 2011 105278 discloses a seat occupancy sensor comprising a support plate with bearing elements for fixing the support plate on seat cushion suspension springs, wherein the bearing elements define an upper surface from which the top surface of the support plate is recessed. A foam pad carrying a pressure-responsive detector is arranged between the bearing elements on the support plate.

[0006] With pressure sensor units arranged on the B-surface of the seat cushion (i.e. on the side facing away from that on which an occupant may seat himself, between the seat cushion and the support thereof), the seat cushion transfers the pressure from the seating surface to the pressure sensor unit. As a matter of fact, the padding of the seat cushion becomes part of the measurement unit. Whereas the production tolerances of film-type pressure sensors may be controlled such that a uniform activation pressure threshold (i.e. the pressure, at which the films of the pressure sensor get into contact with each other) is achieved for the whole production, important investments would be necessary in the seat manufacturers' production in order to guarantee that the foam of every seat cushion has exactly the same thickness and behaves the same way under pressure, in particular, transfers the same amount of pressure to the pressure-sensor unit.

Technical problem

[0007] It is an object of the present invention to provide a pressure-responsive B-surface seat occupancy sensor unit compatible with the production tolerances of vehicle seats. This object is achieved by the invention as claimed in claim 1.

General Description of the Invention

[0008] A pressure-responsive seat occupancy sensor unit for detecting an occupancy state of a seat, e.g. a vehicle seat, according to a first aspect of the invention is configured for seats wherein the cushion is supported by springs. Such pressure-responsive seat occupancy sensor unit comprises a support plate having a top surface and a bottom surface, a plurality of bearing elements for fixation of the support plate on seat cushion suspension springs, the bearing elements defining an upper surface of the pressure-responsive seat occupancy sensor unit, which upper surface the top surface of the support plate is arranged recessed from, a foam pad disposed between the bearing elements on the support plate, a recess formed in the top surface of the support plate, underneath the foam pad, and a pressure-responsive membrane switch arranged in the recess. The recess has a depth exceeding the thickness of the pressure-responsive membrane switch. The foam pad is configured such that, upon it being compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into the recess and activates the pressure-responsive membrane switch.

[0009] As will be appreciated, due to the depth of the recess greater than the thickness (height) of the pressure-responsive membrane switch, there is an air gap between the pressure-responsive membrane switch and the bottom of the foam pad when the seat is in unloaded condition. The air gap thus prevents a so-called pre-loading of the pressure-responsive membrane switch. Furthermore, if the foam pad deforms due to ageing and begins sinking into the gap, it will not immediately apply a pre-load on the membrane switch. Accordingly, a longer lifetime of the unit may be obtained.

[0010] Preferably, the bearing elements are integrally formed with the support plate. The bearing elements and the support plate can be made from any suitable material. Preferably, however, they are made from injection-molded plastic.

[0011] According to a second aspect of the invention, the pressure-responsive seat occupancy sensor unit is configured for seats wherein the cushion is supported by a seat pan (e.g. made from sheet metal or from plastic). The pressure-responsive seat occupancy sensor unit for detecting an occupancy state of a seat according to the second aspect of the invention comprises a support plate having a top surface and a

bottom surface, a plurality of spacer elements defining an upper surface of the pressure-responsive seat occupancy sensor unit from which upper surface the top surface of the support plate is arranged recessed from, a foam pad disposed between the spacer elements, carried by the support plate, a recess formed in the top surface of the support plate, underneath the foam pad, and a pressure-responsive membrane switch arranged in the recess. The recess has a depth exceeding the thickness of the pressure-responsive membrane switch. The foam pad is configured such that, upon it being compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into the recess and activates the pressure-responsive membrane switch.

[0012] Preferably, the spacer elements are integrally formed with the support plate. The support plate and the spacer elements are preferably made from injection-molded plastic, although other materials may prove suitable.

[0013] The pressure-responsive membrane switch used in accordance with the first or second aspect of the invention advantageously comprises a first carrier film and a second carrier film spaced from each other by a spacer film, the spacer film having therein an opening defining a cell, the pressure-responsive membrane switch comprising at least two electrodes arranged in facing relationship with each other in the cell on the first and the second carrier film, respectively, in such a way that they are brought closer together, possibly into contact with each other, when pressure is applied on the pressure-responsive membrane switch. When a contact between the electrodes on the first and second carrier film is established, one speaks of "activation" of the membrane switch. The minimum amount of pressure at which the contact is established is called the "pressure threshold" or the "activation threshold".

[0014] A further aspect of the invention relates to a vehicle seat, comprising a seat cushion supported by cushion-supporting springs and a pressure-responsive seat occupancy sensor unit according to the first aspect of the invention. The pressure-responsive seat occupancy sensor unit rests on the cushion-supporting springs and is applied by the cushion-supporting springs against the seat cushion.

[0015] Yet a further aspect of the invention relates to a vehicle seat, comprising a seat cushion supported by a cushion-supporting pan and a pressure-responsive seat occupancy sensor unit in accordance with the second aspect of the invention. The

pressure-responsive seat occupancy sensor unit in this case rests on the cushion-supporting pan and is applied by the cushion-supporting pan against the seat cushion.

[0016] When the seat is loaded (by an occupant), the seat foam is compressed and transfers a part of the pressure to the foam pad of the seat occupancy sensor unit. In turn, the foam pad deforms and penetrates into the recess. If the pressure transferred to the pressure-responsive membrane switch exceeds the pressure threshold, the latter is activated and the occupancy of the seat is recognized.

[0017] As will be appreciated, the sensitivity of the seat occupancy sensor unit depends on and may thus be adjusted by at least the following parameters:

- Height and hardness of the foam pad;
- Height of the gap between the foam pad and the pressure-responsive membrane switch;
- Activation threshold of the membrane switch;
- The size (diameter) of the recess in relation to the supported area of the foam pad.

Brief Description of the Drawings

[0018] Preferred embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings in which:

Fig. 1 is a cross sectional view of a pressure-responsive seat occupancy sensor unit according to the first aspect of the invention;

Fig. 2 shows the pressure-responsive seat occupancy sensor unit of Fig. 1 when the seat, which it is arranged in, is occupied;

Fig. 3 is a perspective view of the pressure-responsive seat occupancy sensor unit of Fig. 1 without the foam pad;

Fig. 4 is a perspective view of the pressure-responsive seat occupancy sensor unit of Fig. 1 wherein the foam pad is shown;

Fig. 5 is a cross sectional view of a pressure-responsive seat occupancy sensor unit according to the second aspect of the invention;

Description of Preferred Embodiments

[0019] Figs. 1 to 4 show a pressure-responsive seat occupancy sensor unit 10 for a vehicle seat according to a preferred embodiment of the first aspect of invention. The occupancy sensor unit 10 comprises a support plate 12 which is integrally formed with lateral bearing elements 14, by which the support plate is attached to the cushion-supporting springs 16 of the seat. The bearing elements 14 define an upper surface 18 of the occupancy sensor unit, from which upper surface 18 the top surface 20 of the support plate 12 is arranged recessed. A foam pad 22 is disposed between the bearing elements 14 on the top surface 20 of the support plate 12. A recess 24 formed in the top surface 20 of the support plate 12, underneath the foam pad 22, accommodates a pressure-responsive membrane switch 26. The depth of the recess 24 exceeds the thickness (height) of the membrane switch 26.

[0020] The upper surface 28 of the foam pad 22 is substantially in alignment with the upper surface 18 of the occupancy sensor unit 10. Both surfaces are thus applied against the bottom side (B-surface) of the seat cushion 30. When the seat is loaded (illustrated in Fig. 2 by arrow 32), the seat cushion transfers part of the resulting pressure onto the occupancy sensing unit 10, in particular onto the foam pad 22. The mechanical properties of the foam pad 22 are chosen such that, when the foam pad 22 is compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into the recess 24 in the top surface of the support plate 12 and activates the pressure-responsive membrane switch 26.

[0021] Fig. 3 shows the occupancy sensing unit 10 from a different perspective. The foam pad 22 and the seat cushion are not shown in Fig. 3 for sake of clarity. The lateral bearing elements 14 rest upon the cushion-suspension mat formed by the springs 16 and the cross-ties 34. The support plate 12, which is in recess from the upper surface 18 of the occupancy sensing unit 10 carries a sensor device with two active areas 36, each of which represents a pressure-responsive membrane switch 26. Both switches are electrically linked to a connection tail, which is protected by a hot-melt casing 38. The connection tail serves to interface the sensor device with read-out electronics (such as e.g. a car's onboard computer). Fig. 4 shows the same perspective as Fig. 3, with the foam pad 22 in place.

[0022] Fig. 5 illustrates a preferred embodiment of a seat occupancy sensor unit 10' according to a second variant of the invention, integrated into the seating portion of a vehicle seat 40. The vehicle seat comprises a seat pan 42, which supports the seat cushion 30'. The occupancy sensor unit 10' rests upon the seat pan 42.

[0023] The pressure-responsive seat occupancy sensor unit 10' comprises a support plate 12' a plurality of spacer elements 14' defining an upper surface 18' of the pressure-responsive seat occupancy sensor unit from which upper surface 18' the top surface of the support plate is arranged recessed from. A foam pad 22' is disposed between the spacer elements 14, carried by the support plate 12'. A recess 24' formed in the top surface of the support plate 12', underneath the foam pad 22', accommodates a pressure-responsive membrane switch 26'. The recess 24' has a depth exceeding the thickness of the membrane switch 26'. The foam pad 22' is configured such that, upon it being compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into the recess 24' and activates the membrane switch 26'.

[0024] While specific embodiments have been described in detail, those skilled in the art will appreciate that various modifications and alternatives to those details could be developed in light of the overall teachings of the disclosure. Accordingly, the particular arrangements disclosed are meant to be illustrative only and not limiting as to the scope of the invention, which is to be given the full breadth of the appended claims and any and all equivalents thereof.

Claims

1. Pressure-responsive seat occupancy sensor unit (10) for detecting an occupancy state of a seat, e.g. a vehicle seat, comprising:
a support plate (12) having a top surface and a bottom surface,
a plurality of bearing elements (14) for fixation of said support plate on seat cushion suspension springs (16), said bearing elements defining an upper surface (18) of said pressure-responsive seat occupancy sensor unit, which upper surface said top surface (20) of said support plate is arranged recessed from;
a foam pad (22) disposed between said bearing elements on said support plate;
characterized by a recess (24) formed in said top surface of said support plate, underneath said foam pad; and
a pressure-responsive membrane switch (26) arranged in said recess,
wherein said recess has a depth exceeding the thickness of said pressure-responsive membrane switch.
2. Pressure-responsive seat occupancy sensor unit as claimed in claim 1, wherein said bearing elements are integrally formed with said support plate.
3. Pressure-responsive seat occupancy sensor unit as claimed in claim 2, wherein said support plate and said bearing elements are made of injection-molded plastic.
4. Pressure-responsive seat occupancy sensor unit as claimed in any one of claims 1 to 3, wherein said pressure-responsive membrane switch comprises a first carrier film and a second carrier film spaced from each other by a spacer film, said spacer film having therein an opening defining a cell, said pressure-responsive membrane switch comprising at least two electrodes arranged in facing relationship with each other in said cell on said first and said second carrier film, respectively, in such a way that they are brought closer together, possibly into contact with each other, when pressure is applied on said pressure-responsive membrane switch.
5. Pressure-responsive seat occupancy sensor unit as claimed in any one of claims 1 to 4, wherein said foam pad is configured such that, upon it being compressed

by application of pressure exceeding a certain threshold, it deforms so as to penetrate into said recess and activates said pressure-responsive membrane switch.

6. A vehicle seat, comprising a seat cushion (30) supported by cushion-supporting springs (16) and a pressure-responsive seat occupancy sensor unit (10) as claimed in any one of claims 1 to 5, wherein said pressure-responsive seat occupancy sensor unit rests on said cushion-supporting springs and is applied by said cushion-supporting springs against said seat cushion.
7. Pressure-responsive seat occupancy sensor unit (10') for detecting an occupancy state of a seat (40), e.g. a vehicle seat, comprising:
a support plate (12) having a top surface and a bottom surface,
a plurality of spacer elements (14') defining an upper surface (18') of said pressure-responsive seat occupancy sensor unit from which upper surface said top surface (20') of said support plate is arranged recessed from;
a foam pad (22') disposed between said spacer elements, carried by said support plate;
characterized by a recess (24') formed in said top surface of said support plate, underneath said foam pad; and
a pressure-responsive membrane switch arranged in said recess,
wherein said recess has a depth exceeding the thickness of said pressure-responsive membrane switch.
8. Pressure-responsive seat occupancy sensor unit as claimed in claim 7, wherein said spacer elements are integrally formed with said support plate.
9. Pressure-responsive seat occupancy sensor unit as claimed in claim 8, wherein said support plate and said spacer elements are made of injection-molded plastic.
10. Pressure-responsive seat occupancy sensor unit as claimed in any one of claims 7 to 9, wherein said pressure-responsive membrane switch comprises a first carrier film and a second carrier film spaced from each other by a spacer film, said spacer film having therein an opening defining a cell, said pressure-responsive membrane switch comprising at least two electrodes arranged in facing relationship with each other in said cell on said first and said second

carrier film, respectively, in such a way that they are brought closer together, possibly into contact with each other, when pressure is applied on said pressure-responsive membrane switch.

11. Pressure-responsive seat occupancy sensor unit as claimed in any one of claims 7 to 10, wherein said foam pad is configured such that, upon it being compressed by application of pressure exceeding a certain threshold, it deforms so as to penetrate into said recess and activates said pressure-responsive membrane switch.
12. A vehicle seat (40), comprising a seat cushion (30') supported by a cushion-supporting pan (42) and a pressure-responsive seat occupancy sensor unit (10') as claimed in any one of claims 7 to 11, wherein said pressure-responsive seat occupancy sensor unit rests on said cushion-supporting pan and is applied by said cushion-supporting pan against said seat cushion.

Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2013/071571

A. CLASSIFICATION OF SUBJECT MATTER

INV. B60N2/00 B60R21/015 B60N2/70
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B60N B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2011 105278 A (AISIN SEIKI) 2 June 2011 (2011-06-02) abstract; figures 2,3	1,6,7,12
A	----- EP 2 492 137 A2 (IG BAUERHIN GMBH [DE]) 29 August 2012 (2012-08-29) paragraphs [0042] - [0059]; figures 4,5 -----	1,6,7,12



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 January 2014

Date of mailing of the international search report

20/01/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lotz, Klaus-Dieter

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2013/071571

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 2011105278	A	02-06-2011	NONE	

EP 2492137	A2	29-08-2012	DE 102012003243 A1	30-08-2012
			DE 202011005145 U1	29-06-2012
			EP 2492137 A2	29-08-2012
