




(86) **Date de dépôt PCT/PCT Filing Date:** 2011/08/10
(87) **Date publication PCT/PCT Publication Date:** 2012/03/29
(45) **Date de délivrance/Issue Date:** 2017/07/11
(85) **Entrée phase nationale/National Entry:** 2013/02/21
(86) **N° demande PCT/PCT Application No.:** IB 2011/053563
(87) **N° publication PCT/PCT Publication No.:** 2012/038846
(30) **Priorité/Priority:** 2010/09/20 (VN2-2010-00198)

(51) **Cl.Int./Int.Cl. A47G 9/10** (2006.01),
A61H 1/02 (2006.01)
(72) **Inventeur/Inventor:**
PHAM, LOAN KIM THI, VN
(73) **Propriétaire/Owner:**
PHAM, LOAN KIM THI, VN
(74) **Agent:** MOFFAT & CO.

(54) **Titre : OREILLER CERVICAL POUR LE TRAITEMENT DE MALADIES DE LA COLONNE CERVICALE**
(54) **Title: CERVICAL PILLOW FOR TREATMENT OF CERVICAL SPINE DISEASES**



(57) **Abrégé/Abstract:**

A cervical pillow for treatment of cervical spine diseases includes a padded member made of resilient materials such as foam, rubber, or cotton. The padded member has a rectangular flat bottom side, vertically flat left and right sides, a rounded front side, a



(57) Abrégé(suite)/Abstract(continued):

thin back side, and a wavy top side that has a flat portion connecting to the front side, a slightly concave portion in the middle, and a very convex portion connecting to the back side. The cervical pillow further includes a nearly rectangular solid block made of high-strength materials such as plastic or compressed rubber. This solid block is embedded within the padded member along its back side and under the very convex portion of its top side.

ABSTRACT

A cervical pillow for treatment of cervical spine diseases includes a padded member made of resilient materials such as foam, rubber, or cotton. The padded member has a rectangular flat bottom side, vertically flat left and right sides, a rounded front side, a thin back side, and a wavy top side that has a flat portion connecting to the front side, a slightly concave portion in the middle, and a very convex portion connecting to the back side. The cervical pillow further includes a nearly rectangular solid block made of high-strength materials such as plastic or compressed rubber. This solid block is embedded within the padded member along its back side and under the very convex portion of its top side.

CERVICAL PILLOW FOR TREATMENT OF CERVICAL SPINE DISEASES

FIELD OF THE INVENTION

- 5 The present invention generally relates to a device for treatment of cervical spine diseases and more particularly, to a cervical pillow for treatment of cervical spine diseases.

BACKGROUND OF THE INVENTION

- 10 Most muscles of the body relax completely when they are not being used; however, muscles in the neck have to work non-stop in order to keep the head in its place. The human neck is constantly fighting against gravity. It also has to bend, lift, turn, and twist resulting in the discs and the facet joints to degenerate. As the discs become thinner, the spaces between the vertebrae become narrower. Sustained contraction, hypertonicity,
15 and motion restriction of the atypical and typical cervical vertebrae, C0-C2 and C2-T1, respectively, can lead to headache and neck pain, and more severely, cervical spine diseases including cervical kyphosis, straight cervical spine, and cervical herniated disc. Several attempts have been made to treat these cervical spine diseases, some of which were artificial cervical disc replacement, therapeutic drugs, and chiropractic care.
- 20 However, artificial cervical disc replacement is not for everyone, especially not for those with osteoporosis, joint disease, and allergy to stainless steel. In addition, artificial cervical disc replacement requires a discectomy, which may lead to other complications such as infection, excessive bleeding, and damages to nerves, spinal cord, esophagus or vocal cord. Drugs such as acetaminophen and NSAIDs can reduce neck pain;
25 unfortunately, they are only temporary. In addition to the drugs limited ability to treat cervical spine diseases, they cause liver and kidney damage, gastrointestinal bleeding, and ulcers. Chiropractic care seems to be a safer option of the three treatments. Chiropractors use spinal effective manipulation techniques, such as specific spinal manipulation or instrument-assisted manipulation, to treat patients. However, in the

process of treating patients, there is a risk of putting excessive forces on the patients' spine that may lead to damaging it. On the other hand, if the chiropractors treat the diseases with totally safe thus much less intensive forces, the treatment period is normally very lengthy. The treatment period is even prolonged given the fact that patients can only spend one to two hours a day with the chiropractors. To treat the diseases safely and to shorten the treatment period, it becomes necessary to have a device that can replicate the safe forces applied by the chiropractors, and that is handy enough for patients to use it whenever needed in order to increase the treatment time each day, thus to shorten the treatment period.

10 The Olson patent (US. Pat. No. 5,644,809) describes a pillow for maintaining proper cervical and thoracic spinal alignment of people as they sleep. This pillow, however, does not have the functions for treating cervical spine diseases.

The Chang-Ho patent application (Publication No. WO/2009/148215) describes a pillow for protecting the cervical vertebrae by maintaining proper head and cervical vertebrae height. This pillow, however, does not have the functions for treating cervical spine diseases.

Finally, the Sang-Hyun patent application (Publication No. WO/2007/091863) describes a pillow for supporting a user's head, neck, shoulders and back. The pillow relaxes the joints of bones and muscles when the user lies on the pillow to strengthen the vertebrae, the nervous tissue and blood vessels, thereby preventing various diseases. This pillow, however, also does not have functions of treating cervical spine diseases.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a cervical pillow that treats cervical spine diseases. These diseases include cervical kyphosis, straight cervical spine, and cervical herniated disc.

According to the present invention, a cervical pillow for treatment of cervical spine diseases includes a padded member and a nearly rectangular solid block. Made of resilient materials such as foam, the padded member, whose density is 30-40 kg/m³, comprises a rectangular flat bottom side, vertically flat left and right sides, a rounded

front side, a thin back side, and a wavy top side that has a flat portion connecting to the front side, a slightly concave portion in the middle, and a very convex portion connecting to the back side.

5 The nearly rectangular solid block was made of high strength material. The solid block is inserted inside padded member along its back side and under the very convex portion of its top side. The nearly rectangular solid block comprises two parts: the bell-shaped base and the bell-shaped body. The nearly rectangular solid block is able to tolerate the high pressure without being broken or distorted, with a shape and size similar to those of a person's neck. The pillow is designed in a way that, when a person put the back of his neck on the convex
10 portion and his head on the concave portion of the wavy top side, his cervical lordosis will stay in a clinically normal range.

The very convex portion of the top side together with the solid block create an elevated firm area. When a patient lay down in a supine position in which the occipital region of his head is on the slightly concave portion of the top side and his neck is on the elevated firm
15 area, the elevated firm area is, thanks to its very convex shape, capable of generating a strong but safe reaction force against the gravity forces from the head and body. Obviously, the reaction force is placed on his cervical spine. Given that, the elevated firm area is able to treat cervical spine diseases by gradually adjusting the straight or kyphotic cervical spine back to its natural inward curvature. With the same mechanism, the elevated firm area is
20 also able to treat cervical herniated discs by gradually pushing the discs back into their original places.

As patients can use the pillow by themselves at their home without the help from a doctor, the treatment time each day is increased significantly, therefore the treatment period can be shortened markedly.

The brief description above sets forth rather broadly the more important features of the present invention in order that the detailed description thereof that follows may be better understood, and in order that the present contributions to the art may be better appreciated. There are, of course, additional features of the invention that will be described hereinafter and which will be for the subject matter of the claims appended hereto. Before explaining the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception, upon which disclosure is based, may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the present invention.

15 In a broad aspect, the present invention relates to a cervical pillow for treating cervical spinal diseases comprising two parts, a padded member made of resilient materials such as foam, rubber, or cotton, and a solid block made of high-strength materials, wherein: the padded member has a rectangular flat bottom side, vertically flat left and right sides, a rounded front side, a thin back side, and a wavy top side that has a flat portion connecting to the front side, a slightly concave portion in the middle, and a very convex portion connecting to the back side, the solid block is embedded within the padded member along its back side and under the very convex portion of its top side, the solid block has an upper part and a lower part, the width of the upper part from the front side toward the back side is similar to the width of cervical vertebrae of a patient, the width of the lower part from the front side toward the backside is larger than the width of the upper part for keeping the solid block from tilting always straight and generating feedback vertical force to neck of the patient when a patient put his neck on the convex portion, and a height of solid block is conform so that the vertical force bends the neck forward when a user put his neck on this solid block.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawing wherein:

5 **FIG. 1** is a perspective left-back view of a cervical pillow for treatment of cervical spine diseases according to the invention.

FIG. 2 is a perspective right-back view of the pillow shown in **FIG. 1**

FIG. 3 is a perspective right-front view of the pillow shown in **FIG. 1**

FIG. 4 is a perspective left-back view of the pillow shown in **FIG. 1**

10 **FIG. 5** is a cross-section side view of the pillow shown in **FIG. 4** taken along line A-A

FIG. 6 is a cross-section front view of the pillow shown in **FIG. 4** taken along line B-B

FIG. 7 shows a person in a supine position lying on the pillow shown in **FIG. 1**

FIG. 8 is a cross-section side view of the nearly rectangular solid block of the pillow shown in **FIG. 4** taken along line A-A

DETAILED DESCRIPTION OF THE INVENTION

5 **FIG 1, 2, and 3** show perspective views of a cervical pillow for treatment of cervical spine diseases **100**, which comprises a padded member **101** and a nearly rectangular solid block **200**. Made of resilient materials such as foam, the padded member **101** comprises a rectangular flat bottom side **102**, a vertically flat left side **104**, a vertically flat right side **106**, a rounded front side **107**, a thin back side **103**, and a wavy top side **105** that has a flat
10 portion **105a** connecting to the front side **107** and a slightly concave portion **105b** in the middle and a very convex portion **105c** connecting to the back side **103**.

The nearly rectangular solid block **200** is inserted inside the padded member **101** along its back side **103** and under the very convex portion **105c** of its top side **105**. The nearly rectangular solid block **200** comprises two parts: the bell-shaped base **201** and the bell-shaped body **202**, as shown in **FIG. 8**. The nearly rectangular solid block **200** has the bell-shaped base **201** and the bell-shaped body **202**. The nearly rectangular solid block **200** is able to tolerate the high pressure, without being broken or distorted, with a shape and size similar to those of a person's neck. The pillow **100** is designed in a way that, when a person puts the back of his neck on the convex portion **105c** and his head on the concave portion
15 **105b** of the wavy top side **105**, his cervical lordosis will stay in a clinically normal range of 31 to 40 degrees.

20 The very convex portion **105c** of the top side **105** together with the solid block **200** create an elevated firm area **300**. When a patient lay down in a supine position in which the occipital region of his head is on the slightly concave portion **105b** of the top side

105 and his neck is on the elevated firm area **300** as shown in **FIG. 7**, the elevated firm area **300** is, thanks to its very convex shape, capable of generating a strong but safe reaction force **F3** against the gravity force **F1** from the head and the gravity force **F2** from the body. Obviously, the reaction force **F3** is placed on his cervical spine. Given
5 that, the elevated firm area **300** is able to treat cervical spine diseases by gradually adjusting a straight or kyphotic cervical spine back to its natural inward curvature. With the same mechanism, the elevated firm area **300** is also able to treat cervical herniated discs by gradually pushing the discs back into their original places. In this case, a user needs to place his neck onto the elevated firm area **300** in the manner that the herniated
10 disc is right on the peak of the elevated firm area **300**.

As patients can use the pillow **100** by themselves at their home without the help from a doctor, the treatment time each day is increased significantly, therefore the treatment period can be shortened markedly.

15

20

25

30

CLAIM

What is claimed is:

1. A cervical pillow for treating cervical spinal diseases comprising two parts, a
5 padded member made of resilient materials such as foam, rubber, or cotton, and a solid
block made of high-strength materials, wherein:

the padded member has a rectangular flat bottom side, vertically flat left and right
sides, a rounded front side, a thin back side, and a wavy top side that has a flat portion
10 connecting to the front side, a slightly concave portion in the middle, and a very convex
portion connecting to the back side,

the solid block is embedded within the padded member along its back side and
under the very convex portion of its top side,

15

the solid block has a upper part and a lower part, the width of the upper part from
the front side toward the back side is similar the width of cervical vertebrae of a patient,
the width of the lower part from the front side toward the backside is larger than the width
of the upper part for keeping the solid block from tilting always straight and generating
20 feedback vertical force to neck of the patient when a patient put his neck on the convex
portion, and

a height of solid block is conform so that the vertical force bends the neck forward
when a user put his neck on this solid block.

1/4




FIG. 1




FIG. 2

2/4




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6




FIG. 7

4/4




FIG. 8

