

(86) Date de dépôt PCT/PCT Filing Date: 2004/11/04
(87) Date publication PCT/PCT Publication Date: 2005/05/12
(45) Date de délivrance/Issue Date: 2009/08/11
(85) Entrée phase nationale/National Entry: 2006/05/04
(86) N° demande PCT/PCT Application No.: CA 2004/001935
(87) N° publication PCT/PCT Publication No.: 2005/042901
(30) Priorité/Priority: 2003/11/04 (US60/516,874)


(51) Cl.Int./Int.Cl. *E06B 3/54* (2006.01),
B29C 65/02 (2006.01), *E06B 3/66* (2006.01),
E06B 3/663 (2006.01), *E06B 3/673* (2006.01)

(72) Inventeurs/Inventors:
GLOVER, MICHAEL, CA;
FIELD, STEPHEN, CA

(73) Propriétaire/Owner:
BYSTRONIC SOLUTION CENTRE INC., CA

(74) Agent: SMART & BIGGAR

(54) Titre : PANNEAU ENCADRE ET PROCEDE DE FABRICATION ASSOCIE
(54) Title: A FRAMED PANEL AND RELATED METHOD OF MANUFACTURE



(57) **Abrégé/Abstract:**

A framed panel and related method of manufacture are disclosed. A framed panel unit includes a panel along the edge of which thermoplastic frame members are disposed. The frame members have first and second opposed side walls which define a channel

(57) **Abrégé(suite)/Abstract(continued):**

for receiving the edge of the panel. The channel of each frame member has spacers between the panel and each side wall for spacing the panel from the side walls. Prior to welding together the ends of the frame members, the spacers retain the frame members on the panel. The panel may include multiple opposed sheet members with a spacer between the sheet members spacing them apart, and a reactive thermoplastic sealant material bonding the sheets to the frame members. An associated method of forming a framed panel, frame members for a panel, and a spacer component for use in mounting a panel within a channel of a frame member are also disclosed.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/042901 A1

(51) International Patent Classification⁷: **E06B 3/54**,
3/66, 3/663, 3/673, B29C 65/48, 65/54

[CA/CA]; 44 Dufferin Road, Ottawa, Ontario K1M 2A8 (CA). **FIELD, Stephen** [CA/CA]; 745 Lonsdale Road, Ottawa, Ontario K1K 0J9 (CA).

(21) International Application Number:
PCT/CA2004/001935

(74) Agents: **WALTERS, David, M.** et al.; Smart & Biggar, P.O.Box 2999, Station D, 900-55 Metcalfe Street, Ottawa, Ontario K1P 5Y6 (CA).

(22) International Filing Date:
4 November 2004 (04.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/516,874 4 November 2003 (04.11.2003) US

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US):
BOWMEAD HOLDINGS INC. [CA/CA]; 39 Vaughan Street, Ottawa, Ontario K1M 1W9 (CA).


(72) Inventors; and

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

(75) Inventors/Applicants (for US only): **GLOVER, Michael**

[Continued on next page]

(54) Title: A FRAMED PANEL AND RELATED METHOD OF MANUFACTURE



(57) Abstract: A framed panel and related method of manufacture are disclosed. A framed panel unit includes a panel along the edge of which thermoplastic frame members are disposed. The frame members have first and second opposed side walls which define a channel for receiving the edge of the panel. The channel of each frame member has spacers between the panel and each side wall for spacing the panel from the side walls. Prior to welding together the ends of the frame members, the spacers retain the frame members on the panel. The panel may include multiple opposed sheet members with a spacer between the sheet members spacing them apart, and a reactive thermoplastic sealant material bonding the sheets to the frame members. An associated method of forming a framed panel, frame members for a panel, and a spacer component for use in mounting a panel within a channel of a frame member are also disclosed.

WO 2005/042901 A1

WO 2005/042901 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A Framed Panel and Related Method of Manufacture

Field of the Invention

This invention relates generally to framed panels and fenestration products and more particularly but not
5 limited to products made from thermoplastic profiles welded around an insulating glass unit.

Background of the Invention

To improve manufacturing efficiency and reduce product costs, various attempts have been made in recent
10 years to develop integrated insulating glass / window frame production systems.

One example which is described in a presentation given at InterGlass Metal 97' was developed in Germany by Meeth Fenster. With this production system, the window is
15 fabricated from plastic channel window frame profiles that are assembled around an insulating glass (IG) unit and corner welded using conventional hot plate technology. During the assembly process, the unit is held in position by means of a hot melt butyl adhesive bead that is located
20 centrally in the frame channel. Twin silicone thermosetting glazing sealant beads are then applied in the two gaps either side of the IG unit. After assembly, the windows are stored in a truck container ready for shipping and the truck containers are left parked outside the factory for a few
25 hours while the two-part silicone sealant is cured. For the Meeth production system, there are four main drawbacks. First, because of the butyl adhesive bead, the glazing channel cannot be drained and this creates potential IG durability problems. Second, conventional hot plate welding
30 is a slow process that is complicated by the need for corner

flash removal. Third, the sash frame assemblies cannot be shipped until the two-part thermosetting sealant is fully cured. Fourth, the Meeth production is largely a manual process with manual loading of the individual frame profiles into the welding clamping fixtures and manual application of the sealant beads.

A second example of an integrated IG/window frame system is described in US Patent 5,622,017 issued to Lynn et al. and assigned to the Andersen Corporation. As with the Meeth system, the Andersen window is also fabricated from plastic channel frame profiles that are assembled around an IG unit and corner welded using conventional hot plate technology. In comparison with the Meeth System, the Andersen profile incorporates conventional plastic glazing fins on one side of the channel frame profile. A structural thermosetting sealant is then applied to one side of the unit and the single glazing sealant bead is allowed to cure. Because the IG glass unit is not held in position, the frame subassembly cannot be moved for several hours while waiting for the sealant to cure. In addition, the unit cannot be accurately centered within the channel profile and so the process of sealant application cannot be easily automated.

As described in US Patent 5,902,657 issued to Hanson et al., the channel frame profiles can be joined at the corners using friction welding with a moveable U-shaped metal platen that rapidly moves back and forth melting the plastic at the interface joint. As with conventional hot plate welding, the metal platen is then removed and the matching ends of the framing profiles are then pressured against each other. From a practical perspective, this solution is difficult to implement because as the metal plate is removed, the molten plastic material is also

removed resulting in a poor weld assembly. A further concern is that the IG unit is held in position by the sloped channel walls and as a result there are potential glass breakage problems at the corners.

5 A third example of an integrated IG/window frame system is described in PCT application CA02/000842 by Field et al (See Figures 21-23 therein). Again, the frame assembly is welded using friction welding but instead of using a metal platen, a plastic web is used that is vibrated
10 back and forth using an inverted vibratory welding head. To avoid potential glass breakage problems, the IG unit is isolated from the plastic channel frame profiles using conventional rubber setting blocks. However, because the unit is not firmly held in position and is not accurately
15 centered, the sealant application process cannot easily be automated. In addition, the profiles have to be manually loaded into the clamping fixtures and this slows down the production cycle time.

Summary of the Invention

20 According to one aspect of the present invention, there is provided a framed panel unit comprising a panel; a plurality of thermoplastic frame members disposed along the edge of said panel; each frame member having first and second opposed side walls defining a channel therebetween,
25 the edge of said panel being received within the channel of each frame member; the channel of each frame member having spacer means therein including a first spacer between said panel and said first side wall for spacing said panel from said first side wall and a second spacer between said panel
30 and said second side wall for spacing said panel from said second side wall, and where prior to welding together the

77271-59

ends of said frame profiles, the spacer means positions said panel within said channel and further retains said frame members on the panel.

One arrangement is where at least one of said first and second spacers is positioned below the top of a respective channel wall to provide an open gap at the top of the channel between the panel and the side wall for receiving sealant. In this arrangement, spacers are provided in the channel, either side of the panel to center the panel in the channel and to also hold the panel in position during an assembly process, for example during application of a sealant, e.g. a reactive thermoplastic sealant, to both sides of the panel along a frame member.

In this arrangement, the spacers also resiliently retain the frame members on the panel when the frame members are unconnected so that the frame members can be positioned and held in place on the panel before the frame members are connected together, for example by welding. This also facilitates handling of the unit by allowing the various components to be moved and transferred together as whole between assembly stations in a production process and, in particular, facilitates the transfer and loading of the frame members into a welding apparatus so that this loading process may be automated, rather than manual.

One or both spacers may be formed separately from the frame member, or may be formed integrally therewith. One or both spacers may comprise a discrete protrusion extending into the channel for engaging a portion of the panel adjacent an edge thereof. Either one or each protrusion may have an upper surface which is deflected downwards to engage the surface of the panel so that when

77271-59

the pressure applied to the panel by the protrusion is increased if the frame member is pulled in a direction away from the panel, making it difficult to withdraw the frame member from the panel when installed thereon.

5 When separately formed from the frame members, the first and second spacer may be joined together by a third intermediate spacer which spaces the edge of the panel from the base of the channel. The first, second and third spacers may thereby form a U-shaped insert and the first and
10 second spacers may be hingedly coupled to the third spacer and may be integrally formed therewith. The spacer insert may include locator means for positioning the insert at a predetermined lateral position between the side walls of the channel, which might be particularly useful when, due to
15 manufacturing tolerances, the distance between the side walls of the channel are greater than required to accommodate the width of the insert. In one embodiment, the base of the channel has oppositely sloped upper surfaces which slope transversely of the channel and the locator
20 means includes first and second oppositely sloped lower surfaces of the third spacer which engage the sloped surfaces of the channel to urge the third spacer towards a predetermined position within the channel on applying a force, for example the weight of the panel, to the third
25 spacer towards the base of the channel.

In one embodiment, the frame members are welded together by friction welding, and possibly by means of a weldable junction piece disposed between adjacent ends of the frame members. The junction piece may be a flat planar
30 flange or may also incorporate integral legs that help position the framing members in the assembly process. In one embodiment, the framed panel unit includes a reactive

77271-59

thermoplastic sealant material along the junction between one or both outer surfaces of the panel and the frame member. The sealant material may have a high degree of stiffness (high modulus) to increase the structural strength and rigidity of the framed panel unit. The reactive thermoplastic sealant may for example be polyurethane or silicone based.

As the spacers effectively position and hold the panel in the desired position, relative thereto, the sealant need not have any open time to allow the panel to be repositioned relative to the joined frame members, and no repositioning is required. This allows a warm or hot applied thermoplastic sealant to be used which cools down almost immediately on its application to the panel unit so that once the application process is complete, the unit can be moved almost immediately to the next production stage, if any, for shipment, or for storage, resulting in a fast and more efficient production process. In one embodiment, the sealant may comprise a reactive thermoplastic sealant that may have an open time of 2 seconds or less but which after exposure to moisture chemically cures and bonds to the glass.

According to another aspect of the present invention, there is provided a panel unit comprising first and second opposed sheet members; a spacer between said sheet members spacing said sheet members apart, said spacer comprising a thermoplastic sealant material and being located proximate an edge of the sheet members; a frame member having a channel formed therein, said edge being disposed within said channel; and a reactive thermoplastic sealant material bonding said sheets to said frame member.

77271-59

The provision of a reactive thermoplastic sealant material which structurally bonds the sheets to the frame member allows the perimeter seal and spacer between the sheet members to be simplified and the material used to be considerably reduced. In one embodiment, the perimeter edge seal between the glazing sheets only consists of a thermoplastic sealant spacer.

According to another aspect of the present invention, there is provided a method of forming a framed panel, comprising the steps of: (a) providing a panel to be framed; (b) providing a plurality of frame members for framing said panel, each frame member having a channel formed therein for receiving an edge portion of said panel and resilient means within said channel for spacing the panel from opposed side walls of said channel and for resiliently retaining said panel in said channel; (c) inserting said panel into the channel of each frame member such that said frame members are held on said panel by said resilient means; and (d) joining the ends of adjacent frame members together using a welding process. In one embodiment, the framing members are interconnected by junction pieces prior to transferring the frame/panel subassembly to the welding apparatus.

According to another aspect of the present invention, there is provided a frame member for a panel, comprising first and second opposed side walls defining a channel therebetween for receiving said panel; first and second pre-formed spacers comprising a resilient material inserted in said channel; the first spacer being positioned against said first side wall for spacing one side of said panel therefrom and said second spacer being positioned

77271-59

against said second side wall to space the other side of said panel therefrom.

According to another aspect of the present invention, there is provided a spacer for use in mounting a panel within a channel of a frame member, comprising a base portion for spacing said panel from the base of said channel; two side portions extending from said base portion for spacing said panel from respective side walls of said channel; and protrusions extending from said side portions for engaging opposite faces of said panel and for resiliently retaining said panel in said frame member.

According to another aspect of the present invention, there is provided a frame member comprising first and second opposed sidewalls defining a channel therebetween and protrusions extending from each sidewall into said channel for resiliently retaining a panel therebetween. In one embodiment, the protrusions that extend from each side wall are flexible fins and according to another embodiment, a bulb seal also extends from each side wall and is located at the top of each framing channel member.

According to another aspect of the present invention, there is provided a frame member comprising first and second opposed sidewalls defining a channel therebetween, at least one sidewall having an elongate recess formed therein extending along the channel and positioned below the top of a respective sidewall.

Brief Description of the Drawings

Figure 1 shows an exploded elevation view of U-channel sash frame profiles assembled around an insulating glass panel.

Figure 2 is a vertical cross section perspective corner detail of a U-channel sash frame incorporating a double glazed insulating panel.

Figure 3 is a perspective view of a single corner vibration welding apparatus.

Figure 4A is a plan view of a single corner, vibration welding apparatus with the extrusions installed in the fixtures prior to the welding process.

Figure 4B is a view similar to Figure 4A showing the single corner vibration welding apparatus during the welding process.

Figure 5 shows a cross section sash frame detail of a U-channel sash frame profile incorporating a conventional dual-seal insulating glass panel and where the framing profiles are temporarily held in position by means of folding rubber spacer inserts.

Figure 6A is a perspective view of the folding rubber spacer inserts prior to insertion within the U-channel sash frame profile.

Figure 6B is a perspective detail view of the folding rubber spacer inserts after insertion within the U-channel sash frame profile.

Figure 7A shows a cross section detail of the folding rubber spacer and the perimeter edge of an insulating glass panel just prior to the insertion of the panel into the folding rubber spacer.

Figure 7B is cross section detail of the perimeter edge of an insulating glass panel after the panel has been inserted into the folding rubber spacer.

Figure 8A shows an exploded cross section detail of three window sash frame components, including: (i) bottom perimeter edge of insulating glass panel, (ii) an unfolded rubber spacer insert and (iii) U-channel sash frame profile.

Figure 8B shows a cross section detail of the folding rubber spacer inserted within the U-channel sash frame profile.

Figure 8C shows the insulating glass panel inserted within the U-channel sash frame profile.

Figure 9 shows a cross section detail of the perimeter edge of a single-seal insulating glass panel incorporated within a U-channel sash frame profile.

Figures 10A-10D show schematic plan views of the production process of an integrated IG/window frame assembly.

Figure 10A shows a schematic plan view of the insulating glass panel.

Figure 10B shows a schematic plan view of the insulating glass panel with U-shaped plastic framing profiles loosely assembled around the insulating unit.

Figure 10C shows a plan view of the insulating panel/plastic sash frame subassembly with junction pieces inserted at the corners.

Figure 10D shows a plan view of the completed window sash subassembly.

Figure 11A is a cross section plan view detail of a frame corner assembly where the thermoplastic plastic profiles are vibration welded at the corner using a corner junction piece with a diagonal web and integral legs.

5 Figure 11B is a cross section detail of the frame corner assembly as shown in Figure 11A where the plastic framing profile is ultrasonically spot welded to the integral legs of the corner junction piece.

10 Figure 11C shows a vertical cross-section detail through the hollow profile shown in Figure 11A.

Figures 12A-12E show schematic plan views of a high volume production process of an integrated IG/frame assembly.

15 Figure 12A shows a plan view of the frame profiles assembled around an insulating glass panel.

Figure 12B shows a plan view of the insulating glass panel/frame subassembly.

Figure 12C shows a plan view of the insulating glass panel/frame subassembly suspended below a gantry.

20 Figure 12D shows a plan view of a four headed horizontal friction corner welder with the insulating glass panel/frame assembly dropped into position.

25 Figure 12E shows a plan view of the four headed horizontal friction corner welder with the insulating glass panel/ frame assembly clamped into position just prior to the welding process.

Figure 13 is a vertical cross section of a U-channel sash frame window incorporating a double glazed

insulating panel and thermoplastic U-channel framing profiles with integrally formed flexible fin spacers and glazing bulb seals.

Detailed Description of the Preferred Embodiments

5 Referring to the drawings, **Figure 1** shows an exploded elevation view of a sash window **20** where the U-shaped thermoplastic framing profiles **21** are assembled around an insulating glass panel unit **25**. Typically, the insulating glass panel unit **25** consists of two glass
10 sheets **26,27**, which are shown more clearly in Figure 5, and are separated by a perimeter edge seal. As described in more detail in **Figures 3 to 5**, the end joint surfaces **23,24** of the sash frame profile members **21** are friction welded at the corners using thermoplastic planar flange junction
15 pieces **22**. Folding rubber spacer inserts **30** are used to hold the insulating glass panel **25** in position within the U-shaped channel profile **21**. Prior to the welding process, the folding rubber spacer inserts **30** also retain the framing profiles **21** in position on the insulating glass panel **25**.
20 In addition, the folding rubber spacer inserts **30** also prevent the vibrating junction piece **22** from striking the corners **31** of the insulating glass panel **25** during the welding process. The folding rubber spacer inserts **30** can be made from various resilient materials with one preferred
25 material being EPDM rubber.

Figure 2 shows an exploded perspective corner detail of a U-channel sash frame window **20** incorporating a double glazed insulating panel unit **25**. The ends **23,24** of the plastic framing profiles **21** are miter cut and vibration
30 welded to a plastic planar flange junction piece **22**. The framing profiles **21** can be made from various thermoplastic

materials but generally, the preferred material is polyvinyl chloride (PVC). In order for the junction pieces **22** to strongly bond to the framing profiles **21**, the junction pieces **22** are made from essentially the same type of plastic material as the framing profiles **21**.

Figure 3 shows a top perspective view of a prototype single corner vibration welding apparatus **32**. The apparatus consists of five main components:

1. Vibratory Head

A linear vibratory head **33** that incorporates a top plate **34** which vibrates back and forth very rapidly in a predetermined plane.

2. Junction Piece Holding Fixture

A junction piece holding fixture **35** which is directly attached to the top plate **34** and firmly holds the planar flange junction piece **22** in position.

3. Moveable Framing Fixtures

Two moveable framing fixtures **36** and **37** incorporate clamping devices **38** that firmly hold the framing profiles **21** in position.

4. Control Systems

A control system **39** that regulates the various operating parameters of the vibration welding apparatus **32** including: weld time, hold time, joint pressure, weld depth, amplitude, frequency and voltage.

5. Machine Frame

A machine frame 40 which provides the structure that supports the other components.

Figure 4A shows a plan view of a single corner, vibration welding apparatus 32 in an open position. The linear vibration welding apparatus 32 features a vibratory head 33 that linearly moves back and forth in a pre-determined plane. The vibratory head 33 is similar to the vibratory heads used on commercially available linear vibration welders such as the Branson Mini Welder, but unlike these commercially available products, the vibratory head is turned upside down as this allows for more flexible and easy positioning of the framing profile members 41 and 42 during the frame assembly process. A flat plate 43 is bolted to the top surface of the vibratory head 33. As with standard vibration welders, the vibratory head 33 is bolted to a separate heavy cast iron support (not shown) and isolated from the cast iron support structure (not shown) using rubber mounts. This cast iron support structure is in turn bolted to a machine frame 40 that positions the vibratory head 33 at a convenient working height.

Flat plate metal sheets 44 are bolted to the top surface of the machine frame 40 but this top working surface is separated apart from the vibratory head 33 so that a minimum of vibratory movement is transferred to the machine frame 40. Moveable profile fixtures 36 and 37 are supported on guide rails 45 directly attached to the top table plate 44 and these fixtures hold the framing profiles 41 and 42 in position. The moveable profile fixtures 36 and 37 move over the vibratory head 33 but there is no direct contact except where the framing profiles 41 and 42 contact the junction

piece 22. The moveable fixtures also allow for the miter cut ends 23, 24 of the framing profiles 41 and 42 to be positioned parallel to the planar flange 48 of the junction piece 22.

5 A fixed holding fixture 35 for the junction piece 22 is located so that the planar flange 48 of the junction piece 22 is in a balanced central position. The holding fixture 35 which is directly attached to the top plate 43 of the vibratory head 33, firmly holds the removable tab 49 of
10 the junction piece 22 in position.

Figure 4B shows a plan view of the vibration welding equipment 32 in operation with the miter cut ends 23 and 24 of the framing profiles 41 and 42 being pressured against the planar flange 48 of the junction piece 22. By
15 vibrating the junction piece 22 back and forth and by simultaneously pressuring the framing profiles 41 and 42 against the planar flange 48 of the junction piece 22, friction heat is generated at the two joint interfaces 50 and 51. When a molten state is reached at the two joint
20 interfaces 50 and 51, the vibration is stopped and the perpendicular pressure is then maintained briefly while the molten plastic solidifies to form two welded joints 52 and 53 on either side of the planar flange 48. In order to provide for even weld strength, essentially the same
25 perpendicular engagement force has to be simultaneously applied to each side of the junction piece 22.

 One of the key advantages of vibration corner welding is that by incorporating flash traps or weld beads within the junction piece 22, it is feasible to eliminate
30 the need for mechanical flash removal and as a result, there are substantial equipment cost savings.

Although frame assemblies can be manufactured using a single corner welder, it is more productive if two or more corners are welded simultaneously. The operation of a vertical four head welder is described in PCT Application 5 CA02/00842 by Field et al. As with conventional hot plate welders, the profiles are separately loaded into the holding fixtures and the miter cut corners are welded in either a one stage or two stage operation.

10 With a two stage process, two diagonally opposite corners and are first welded together. For each corner weld, the process is essentially the same as with a single corner vibration welder. Both sets of framing profiles are independently pressurized against the two diagonally opposite junction pieces. The next step is for the other 15 set of diagonally opposite corners to be welded together and the assembled frame is then unloaded.

Because the friction welding process is so fast (3 to 6 seconds), this two stage process does not significantly increase cycle time and compared with 20 simultaneously welding all four corners, the key advantage is that the required movement and control of the heads is greatly simplified.

For a conventional four head, hot plate welder, the overall cycle time is about 2 minutes and this overall 25 cycle time includes: profile loading, corner welding, cool down and frame unloading. In comparison, the overall cycle time for the two-stage vibration welding process is less than 30 seconds and so this represents a significant increase in productivity.

30 Instead of a two stage process, a second option is to simultaneously weld all four corners in one operation.

During the vibration welding process, each head has to move fractionally and because the head movements involved are so small and so complex, the control system for this simultaneous four headed welding operation is very complex
5 and requires very sophisticated software.

A further major advantage of vibration corner welding is that it is feasible to weld around an insulating glass unit. With a four headed welder, the frame profiles are loaded into the framing fixtures and the insulating
10 glass unit is positioned between the four welding heads. The four heads then move centrally into position so that the U-shaped framing profiles overlap the perimeter edge of the insulating glass unit. With the insulating glass unit in position, the miter cut frame profiles are then welded using
15 friction corner welding.

Figure 5 shows a bottom cross section detail of a U-channel sash window **20**. The U-shaped channel sash framing profiles **21** are assembled around a dual seal insulating glass panel unit **25**. The two gaps **57** and **58** between the
20 insulating glass panel unit **25** and the framing profile **21** are filled with glazing sealant material **59** forming glazing beads **54** and **55**. Various glazing sealant materials can be used but one preferred material is a reactive thermoplastic sealant.

25 Compared to conventional two-part thermosetting sealants, the advantage of a reactive thermoplastic sealant is that the one part sealant is warm or hot applied so that after a few seconds cool down, the material develops high green strength allowing the window units to be almost
30 immediately handled. Compared to conventional widow glazing seal application where there is a need for some open time

during the application process, the open time for the reactive thermoplastic sealant materials can be less than two seconds. In addition through a moisture cure process, the reactive thermoplastic material is chemically cured
5 creating a strong adhesive bond between the glass sheets and the framing profiles.

Various types of reactive thermoplastic sealants can be used but one preferred material is a reactive hot melt polyurethane adhesive that is manufactured by National
10 Starch and Chemical Company under the trade name of Purfect Glaze. A second preferred material is a reactive hot melt silicone that is manufactured by Dow Corning under the trade name of Instant Glaze. Compared to the reactive silicone material, the reactive polyurethane material generally
15 provides for higher adhesion strength.

The modulus or stiffness of the Purfect Glaze sealant can be varied and generally, a high modulus material is preferred as this allows for the glass sheets to be firmly bonded to the framing profiles. As a result,
20 structural advantage can be taken of the stiffness of the glass sheets **26,27** so that the structural performance of the framing profiles **21** is enhanced allowing for a reduction in profile size as well as the possible elimination of metal reinforcement that is typically required for large size PVC
25 windows.

With a high modulus, stiff sealant material and because of the high differential expansion between the plastic PVC framing profiles **21** and the glass sheets, **26,27** there is potential for cold temperature glass breakage.
30 However, our experience has shown that even at quite extreme Canadian winter temperatures (ie below -30°C) glass breakage

is not a problem. This is because the plastic PVC material is sufficiently ductile that differential expansion within the plastic profile cross section can be accommodated. As well, the plastic framing profiles **21** are firmly adhered to
5 the perimeter side faces of the glass sheets **26,27** as opposed to the bottom edge where glass breakage problems are accentuated due to glass edge micro cracks created during the glass cutting process.

At cold outside temperatures, a further concern is
10 that there can be IG edge seal failure due to loss of adhesion between the glass sheets **26, 27** and an IG edge spacer. To eliminate this problem, there is a need for the perimeter edge seal to be somewhat flexible and for a conventional dual-seal design. One preferred option is use
15 an inner desiccant-filled PIB/butyl spacer **62** that is backed by outer structural thermosetting sealant **63**. Other IG dual-seal options include: flexible desiccant-filled silicone or EPDM rubber foam spacer (Trade name: Super Spacer) backed by hot melt butyl sealant.

20 Folding rubber spacer inserts **30** are used to accurately center the insulating glass panel unit **25** within the frame profile **21**. These inserts **30** temporarily hold the framing members **21** on the panel unit **25** and also positions the panel **25** in the sash frame subassembly while it is
25 transferred to the sealant gunning application station.

The bottom sides **64** and **65** of the U-channel frame profile are chamfered and this helps position the folding rubber spacer inserts **30** within the sash frame profile **21**. To further help hold the folding rubber spacer inserts **30** in
30 position, the sidewalls of the profile also incorporate inner ledges **66** and **67**. The bottom section of the folding

rubber spacer inserts **30** also incorporate a V-shaped opening that provides for water drainage from the glazing cavity **69**.

To provide for consistent application, the sealant beads **54** and **55**, are produced using robotic application equipment. One option is separately apply each bead using a standard robot and where the sash assembly frame is rotated through 180° degrees after the application of the first bead **54**. A second option is to apply both beads **54** and **55**, simultaneously using automated double-head sealant application equipment that operates in a similar manner to automated sealant gunning equipment used for insulating glass sealing. For double bead application, the sash frame assembly is typically in a vertical position and to ensure that the sealant material does not deform or drip particularly on the top edge, the thermoplastic sealant material needs to have a high viscosity.

Figure 6A shows a perspective view of the folding rubber spacer insert **30** prior to installation within the U-channel profile **21**. The side wall sections **72** and **73** space the IG unit **25** away from the channel walls of the framing profile. The folding rubber spacer insert **30** incorporates V-notches **70** and **71**, that allow the rubber spacer insert to be folded at the corners. The purpose of the V-notches **70** and **71**, is to allow the inserts **30** to be easily installed within the frame profile **21** prior to the insertion of the IG panel **25**. The V-notches **70** and **71** also help the folding rubber spacer insert **30** accommodate dimensional tolerances in the frame profile. The rubber inserts **30** can be made from a variety of different rubber materials with one preferred option being EPDM rubber.

Although a one piece assembly is shown in **Figure 6A**, it can be appreciated by those skilled-in-the-art that the side wall sections could consist of two separate spacers that are individually attached to the side walls of the channel profile. Similarly the bottom section of the folding rubber spacer insert could also consist of a separate spacer that is positioned in the bottom channel of the framing profile.

Figure 6B shows a perspective view of the folding rubber spacer insert **30** with side sections **72** and **73** folded at right angles to the bottom section **74**.

Figure 7A shows an exploded cross section detail of the folding rubber spacer insert **30** and the perimeter edge **75** of an insulating glass unit panel **25** just prior to the insertion of the panel unit **25** into the folding spacer insert **30**.

Figure 7B is a cross section detail of the perimeter edge **75** of an insulating glass panel **25** after the panel has been inserted into the folding rubber spacer insert **30** that is held within a U-channel frame profile (not shown). The side wall sections **72** and **73** of the folding rubber spacer insert **30** incorporate a protrusion or positioning flange **76** that extends beyond the inner wall surfaces **77** of the side walls **72** and **73**. As the panel unit **25** is inserted into the folding rubber spacer **30**, the protrusion **76** is compressed downwards and so as a result, the insulating glass panel **25** is firmly wedged in position and centered within the frame profile **21**.

Figure 8 shows the production steps involved in the fabrication of the integrated IG/ sash frame assembly **20**.

Figure 8A shows an exploded bottom cross section detail of a window sash frame. There are only three components shown: an insulating glass panel **25**, a folding rubber spacer insert **30** and a U-channel sash frame profile **21**. The bottom faces **78** of the rubber spacer insert **30** are coated with a low-friction coating **79** (see dotted line). The low friction coating **79** allows the rubber spacer insert **30** to slide along the U-channel framing profile **21** during the friction corner welding process. The low friction coating **79** is compatible with standard IG sealant materials and one preferred material option is a polyurethane-based coating. In comparison, the top faces **109** of the rubber insert **30** preferably have a high friction coefficient and do not move in position during the friction corner welding process.

Figure 8B shows an exploded bottom cross section detail of a window sash frame with the folding rubber spacer insert **30** inserted within the sash frame profile **21**. The rubber spacer inserts **30** can be inserted manually or alternately, the spacer inserts **30** can be automatically inserted as part of the profile cutting and fabrication process.

Figure 8C shows a bottom cross section detail of a window sash frame **20** with the IG panel unit **25** installed within rubber spacer insert **30** that is held in position within the sash frame profile **21**. The rubber spacer inserts **30** center the IG panel unit **25** in the sash frame **21** and the corners of the frame assembly are then welded using friction corner welding techniques that are described in PCT Application CA02/000842. As well as centering the panel unit **25**, the rubber spacer inserts **30** also help isolate the IG unit **25** from any resonance or vibratory movement during

the welding process. The sash frame assembly is then transported to the automated frame sealing robot (not shown) with the rubber spacer inserts **30** holding the IG unit **25** in position.

5 It should be noted that although the friction corner welding process is carried out with the IG panel unit **25** in either a horizontal or vertical position, the sealant gunning operation is typically carried out with the panel unit **25** in a vertical position. By positioning the IG panel
10 unit **25** in a vertical position, this ensures that the IG panel unit **25** is centered within the frame profile **21** and that there is no compression of the bottom rubber side wall sections **72** and **73**. After the double bead application of the reactive hot melt sealant, the sash frame assembly can
15 be immediately transferred to the next step in the production process which is typically hardware application. As a result through these various improvements in assembly methods, there is a continuous sash frame production process with increased throughput and productivity and no major
20 production bottlenecks or delays.

Although a double glazed panel unit is illustrated in **Figure 8**, it can be appreciated by those skilled-in-the-art that a triple glazed unit could also be used. Alternatively using a different frame profile, the same
25 production method can be used for welding around a single glass sheet and one option is for this single glass sheet would be as the center light of a triple glazed panel unit.

Figure 9 shows a cross section bottom detail of a single seal IG panel unit **80** incorporated within a slim-line
30 U-channel sash frame profile **81**. In contrast to a dual seal IG unit, the perimeter edge seal assembly **82** consists of a

single barrier seal. Various single seal assemblies can be used including: the Intercept™ edge seal product marketed by PPG Inc. and the Swiggle Seal™ product marketed by TruSeal Inc.

5 One preferred single seal design is to use a thermoplastic spacer **83** that is made from desiccant filled butyl and/or polyisobutylene sealant material. The thermoplastic spacer **83** is marketed under the trade name of TPS and is directly applied to the glass using automated
10 sealant gunning equipment manufactured by Bystronic Inc. A key advantage of the TPS spacer is that the material remains somewhat flexible and as a result, the spacer/edge seal assembly can accommodate some degree of glass movement and bowing even at cold temperatures. Typically, the TPS spacer
15 is backed up by a structural thermosetting sealant such as polysulphide or polyurethane sealant (See **Figure 5**). However with integrated IG/sash frame assembly, the glass sheets **26** and **27**, are structurally bonded to the frame profile **81** by means of structural sealant glazing beads **54**,
20 **55** and so as a result, there is no need for an outer structural IG sealant to hold the glass sheets **26** and **27** in position. By eliminating this outer structural sealant, there are material and equipment cost savings and as well, the frame profile size can also be reduced resulting in
25 additional material cost savings. A further production benefit is that there are no delays while waiting for the thermosetting sealant to cure and this provides for continuous sash frame production with the resulting productivity improvements and cost savings.

30 **Figure 10** shows the key production steps for assembling U-channel sash frame profiles **21** around an insulating glass panel unit **25**. **Figure 10A** shows a

schematic plan view of an insulating glass panel unit **25**.

Figure 10B shows a schematic plan view of the insulating glass panel unit **25** with U-shaped plastic framing profiles **21** loosely assembled around the insulating glass panel unit

5 **25**. **Figure 10C** shows a schematic plan view of the insulating glass unit/frame profile sub assembly **87** with corner junction pieces **22** inserted between the cut ends **23** and **24** of the framing profiles **21**. The four corners of the sash frame subassembly **87** are then welded, using methods and
10 techniques disclosed in PCT CA 02/000842 for example.

Figure 10D shows a schematic plan view of the completed sash frame window **20**. As previously explained, the insulating glass panel unit **25** is held in position and centered in the U-shaped frame profile **21** using folding rubber spacer

15 inserts (not shown).

Although the production process is shown in schematic form in **Figure 10**, it can be appreciated by those skilled-in-the-art that the process can be fully automated using four headed production equipment as described in PCT
20 Application CA02/000842. With a conventional, four headed hot plate welder, the overall cycle time is approximately 120 seconds and the time taken to manually load the four plastic profiles into the clamping fixtures is approximately 15 seconds. With four headed friction corner welder, the
25 overall cycle time is less than 30 seconds but the task of manually loading the profiles takes 15 seconds while the actual weld time is less than 2 seconds.

Instead of preloading the profiles into the clamping fixtures of the four headed welder, one option with
30 friction corner welding is to loosely fit the profiles around the insulating glass unit (See **Figure 10B**). The profiles **21** can be temporarily held in place, by the folding

rubber spacer inserts **30** (not shown) allowing the sub assembly of IG unit/frame profiles **87** to be transferred to the four-headed welder. The planar flange junction pieces **22** are then inserted and the corners welded using friction corner welding techniques. (See **Figure 10C**). As a result of pre-assembling the frame profiles **21** around the IG panel unit **25**, the overall cycle time can potentially be reduced to less than fifteen seconds.

Finally, it should be noted that in **Figure 10** although schematic plan views are shown with the insulating glass panel unit **25** in a horizontal position, the various manufacturing operations can also be carried out with the insulating glass panel unit **25** in a vertical position.

Where a thermoplastic sealant spacer is used, the sealant is preferably applied directly onto the perimeter glass edge with the glass sheet in a vertical position. As previously noted, the double bead sealant gunning operation is also carried out with the IG/frame sub assembly in a vertical position and so if all the various assembly operations are consistently carried out with the glass sub assemblies in a vertical position, there are potential productivity improvements and cost savings.

Figures 11A and **11B** show a cut out cross section plan view of a corner frame assembly **89** fabricated from square profile glass fiber filled PVC profile extrusions **90** and **91** and where the profiles **90** and **91** are vibration corner welded at using a junction piece **92** incorporating integral legs **93**.

As shown in **Figure 11A**, the integral legs **93** of the junction piece **92** incorporate an integral spring centering device **94** that simplifies frame assembly. The

planar flange **48** of the junction piece **92** is first vibration welded to the miter cut ends **23** and **24** of the profiles **90** and **91**. Because of the need to accommodate the vibration movement back and forth, the legs **93** only loosely fit within
5 the profile.

As shown in **Figure 11B**, in order to provide for additional support, the plastic framing profiles **90** and **91** are ultrasonically spot welded to the legs **93** of the junction piece **92**. A double tip welding head is typically
10 used creating spot welds **95** and **96**. Because the legs **93** only loosely fit within the profile, the ultrasonic welding process allows the plastic to flow in the gap between the junction piece legs **93** and the profile extrusions **90** and **91** creating an extra strong welded spot bond and reduced
15 material flow on the exterior surface. Because of their complex shape, the junction pieces **92** are typically injection molded and have to be manufactured from essentially the same base thermoplastic resin material as the extruded profiles **90** and **91**.

Figure 11C shows a vertical cross section through the hollow framing profile **91**. The integral legs **93** of the junction piece **92** consist of a rigid flat bar **97** with a central positioning fin **98**. The profile extrusion incorporates a half circular indentation **99** and this allows
20 the positioning fin **98** to be centrally located.
25

Figure 12 shows an alternative high volume production process for welding around an insulating glazing panel unit **25**. **Figure 12A** shows a plan view of an insulating glazing panel unit **25** with U-Channel framing
30 profiles **21** manually assembled around an insulating glazing panel unit **25** and where the profiles **21** are loosely

interconnected by junction pieces **92** that incorporate integral legs **93**. **Figure 12B** shows a plan view of the insulating glass/frame subassembly **100** where the profiles **21** are positioned around the insulating glass panel unit **25** and where the profiles are in part held in position by folding rubber spacer inserts (not shown). **Figure 12C** shows a plan view of the insulating glass/frame subassembly **100** suspended below a gantry **101** and held in position by means of an adjustable clamping mechanisms **102**. **Figure 12D** shows a plan view of four headed horizontal friction corner welder **103** where the insulating glass/frame subassembly **100** is transferred by the gantry **101** and dropped into position in the friction corner welder **103**. The removeable tabs **49** of the junction pieces **92** are located in the junction piece holding fixture **35** that are attached to the vibratory heads **33**. **Figure 12E** shows a plan view of the insulating glass/frame subassembly **100** where the frame profiles **21** are clamped in position in moveable framing fixtures **104** and where the subassembly **100** is squared prior to friction corner welding the four corners **29**. After the welding process, the removable tabs **49** are automatically cut-off and the framing fixture clamps **104** are released. The assembled sash frame window **20** is then moved by the gantry **101** to the next window production operation.

Because with this high volume production process, the framing profiles are not manually placed in the profile fixtures, weld cycle time is substantially reduced to less than fifteen seconds per window unit and this results in a production output of two thousand windows per eight hour shift. It should be noted that although a high volume sash frame production method is described in **Figure 12**, it can be appreciated by those skilled-in-the-art that the same

production methods and apparatus can also be used to manufacture separate window frame assemblies.

Figure 13 shows a bottom cross-section detail of a U-channel sash window profile **21** featuring flexible fin spacers **105** and glazing bulb seal **106**. U-shaped channel profiles **21** are assembled around the insulating glass panel unit **25**. The panel unit **25** is then inserted into the channel frame profile **21**. The double set of flexible fin spacers **105** that are integrally formed with the framing profile **21** are compressed downwards and hold the insulating glass unit **25** in position. Typically, the flexible fins **105** are made from flexible PVC plastic material and are extruded simultaneously with the PVC framing profiles.

The dual seal insulating glass panel unit **25** is supported on a rubber support pad **107** that is positioned centrally in the U-shaped framing profile **21**. The support pad **107** incorporates an opening **108** to allow for water drainage from the glazing cavity **69**. The flexible glazing bulb seal **106** that is also integrally formed with the framing profile **21** prevents rain water run-off from entering the glazing cavity **39**. The use of integrally formed flexible fin spacers and bulb seals does not provide for the same structural performance as the twin sealant bead assembly previously described in **Figure 5**. However for smaller residential windows the use of integrally formed spacers provides for adequate structural performance and with the added advantage of lower equipment, material and labor costs.

77271-59

CLAIMS:

1. A framed panel unit comprising a panel;

a plurality of thermoplastic frame members
5 disposed along the edge of said panel;

each frame member having first and second opposed
side walls defining a channel therebetween, the edge of said
panel being received within the channel of each frame
member;

10 the channel of each frame member having spacer
means therein including a first spacer between said panel
and said first side wall for spacing said panel from said
first side wall and a second spacer between said panel and
said second side wall for spacing said panel from said
15 second side wall and where prior to welding together the
ends of said frame members, said spacer means positions said
panel within said channel and further retains said frame
members on said panel.

20 2. A framed panel unit as claimed in claim 1, wherein
at least one of said first and second spacers includes a
protrusion extending therefrom and engaging a respective
side of said panel for resiliently retaining said frame
member on said panel.

25

3. A framed panel unit as claimed in claim 1 or 2,
wherein said channel of each frame member includes a base

77271-59

between the first and second opposed sidewalls, wherein each spacer means further comprises a third spacer arranged between the edge of said panel and the base of said channel and wherein said first and second spacers are coupled to
5 said third spacer.

4. A framed panel unit as claimed in claim 3, wherein for each spacer means, the first and second spacers are hingedly coupled to said third spacer and the respective
10 junction between each of said first and second spacers and said third spacer is relieved to accommodate folding of said first and second spacers towards said third spacer.

5. A framed panel unit as claimed in claim 3, wherein
15 said third spacer includes locator means for positioning said third spacer at a predetermined lateral position between the side walls of said channel and wherein the base of said channel has first and second oppositely sloped upper surfaces which slope transversely of said channel and said
20 locator means includes first and second oppositely sloped lower surfaces of said third spacer which engage the sloped surfaces of said channel such that said third spacer is urged towards a central position within said channel on applying a force to said third spacer towards the base of
25 said channel.

6. A framed panel unit as claimed in any one of claims 3 to 5, wherein said third spacer includes means for

77271-59

permitting fluid to flow therethrough between adjacent portions of said channel separated by said third spacer.

7. A framed panel unit as claimed in any one of claims 1 to 6, wherein each frame member comprises polyvinyl chloride (PVC) thermoplastic material.

8. A framed panel unit as claimed in any one of claims 1 to 7 further comprising a weldable flange member disposed between and welded to adjacent ends of said frame members.

9. A framed panel unit as claimed in any one of claims 1 to 8, wherein said panel is comprising at least part of sheet glass.

10. A framed panel unit as claimed in claim 9, wherein said panel comprises one of a single sheet of glass, a double glazed insulating glass unit, a triple glazed insulating glass unit, and a centre lite of a triple glazed unit.

11. A framed panel unit as claimed in any one of claims 1 to 10, wherein at least one of said first and second spacers is positioned below the top of a respective

77271-59

channel wall to provide an open gap at the top of said side wall for receiving sealant.

12. A framed panel unit as claimed in claim 11,
5 wherein said sealant material comprises a reactive thermoplastic sealant material.

13. A framed panel unit as claimed in claim 12,
wherein the open time of said reactive sealant is two
10 seconds or less.

14. A framed panel unit as claimed in claim 12 or 13,
wherein said sealant is one of polyurethane based and
silicone based.

15. A framed panel unit as claimed in any one of
claims 11 to 14, wherein said sealant material has a high
modulus.

20 16. A framed panel unit as claimed in any one of
claims 1 to 3, wherein at least one of said first and second
spacers is integrally formed with a respective channel wall.

77271-59

17. A framed panel unit as claimed in claim 1, wherein each said frame member further includes a series of pre-formed inserts between one of said first and second opposed side walls and an outer face of said panel for spacing said outer face of said panel from said side wall to define a gap therebetween for sealant material.

18. A framed panel unit as claimed in claim 17, wherein said inserts comprise a resilient rubber material and said framed panel unit includes friction reducing means between said inserts and said channel to facilitate relative movement between said inserts and each said frame member.

19. A framed panel unit as claimed in claim 18, wherein each of said at least one of said first and second spacers includes one or more protrusions integrally formed with and extending from the other side wall, and wherein said integrally formed protrusions comprise flexible plastic fins.

20

20. A panel unit as claimed in claim 19, wherein said integrally formed protrusions further comprise a flexible bulb seal located at the top of one of said side walls.

21. A method of forming a framed panel, comprising the steps of:

77271-59

(a) providing a panel to be framed;

(b) providing a plurality of frame members for framing said panel, each frame member having a channel formed therein for receiving an edge portion of said panel and resilient means within said channel for spacing the panel from opposed side walls of said channel and for resiliently retaining said panel in said channel;

(c) inserting said panel into the channel of each frame member such that said frame members are held on said panel by said resilient means; and

(d) joining the ends of adjacent frame members together using a welding process.

22. A method as claimed in claim 21, wherein the step of joining comprises forming a plurality of welded joints using a separate welding station for each joint.

23. A method as claimed in claim 22, wherein the step of joining comprises forming said plurality of welded joints substantially simultaneously.

24. A method as claimed in any one of claims 21 to 23, wherein the step of joining comprises

(e) positioning a weldable member between adjacent ends of two frame members; and

77271-59

(f) welding each end to said weldable member by urging said frame members into engagement with said weldable member, and vibrating said weldable member to cause melting of material at the interface of each end and said weldable member.

25. A method as claimed in claim 24 further comprising performing steps (e) and (f) for each joint substantially simultaneously.

26. A method as claimed in claim 24, wherein the frame members are interconnected by junction pieces prior to transferring the assembled frame and panel components to a welding apparatus and wherein said junction piece incorporates integral legs.

27. A method as claimed in any one of claims 21 to 25, comprising permitting said panel to move relative to each frame member for at least part of said joining step.

28. A method as claimed in claim 27, wherein said permitting includes permitting said panel to move in a direction along the channel of each frame member during at least part of said joining step.

77271-59

29. A method as claimed in claim 27 or 28, wherein permitting movement comprises permitting movement of said resilient means relative to said channel.

5 30. A method as claimed in any one of claims 23 to 29, wherein the step of providing a panel comprises providing a panel comprising first and second opposed sheet members and a thermoplastic sealant spacer between said sheet members spacing said sheet members apart, wherein said thermoplastic
10 sealant spacer is the only spacer spacing said sheet members apart.

31. A method as claimed in claim 30, wherein the step of providing said panel comprises the steps of providing
15 said first and second sheet members, forming said thermoplastic spacer and joining said first and second sheet members with said thermoplastic sealant spacer therebetween.

32. A method as claimed in any one of claims 21 to 31,
20 further comprising the step of applying sealant material between said panel and at least a portion of a frame member.

33. A method as claimed in claim 32, wherein said sealant material is applied after said joining step.

77271-59

34. A method as claimed in any one of claims 21 to 31, further comprising the step of applying sealant material for bonding the frame members to the panel to both outwardly facing surfaces of said panel substantially simultaneously.

5

35. A method as claimed in claim 34, comprising applying said sealant material for bonding between said panel and said frame members after said joining step and when said panel is in a substantially upright position.

10

36. A frame member for a panel, comprising first and second opposed side walls defining a channel therebetween for receiving said panel;

first and second pre-formed spacers comprising a resilient material inserted in said channel;

15

the first spacer being positioned against said first side wall for spacing one side of said panel therefrom and said second spacer being positioned against said second side wall to space the other side of said panel therefrom.

20

37. A frame member as claimed in claim 36, wherein said first and second spacers are mounted in said channel such that said spacers are capable of sliding along said channel.

25

77271-59

38. A frame member as claimed in claim 36 or 37 further comprising retaining means for retaining at least one of said first and second spacers in said channel to limit movement of said spacers in a direction transverse to the length of said channel towards the channel opening defined between said opposed side walls.

39. A frame member as claimed in claim 38, wherein said retaining means is arranged to permit movement of said spacers in a direction along said channel.

40. A frame member as claimed in claim 38 or 39, wherein said retaining means for a respective spacer comprises a protrusion extending from a channel side wall into said channel.

41. A frame member as claimed in any one of claims 36 to 40, wherein at least one surface of the channel which engages a spacer and the surface of said spacer which engages said channel is a low friction surface.

42. A frame member as claimed in claim 36, wherein at least one of said first and second spacers has a respective protrusion extending therefrom for engaging a side of said panel.

77271-59

43. A frame member as claimed in claim 42, wherein a respective protrusion extending from a spacer has an upper surface and a lower surface and is arranged to be deflected towards the base of the channel on insertion of the panel in
5 said frame member such that the upper surface of said protrusion engages said panel to retain said panel in said frame member.

44. A frame member as claimed in claim 42 or 43,
10 wherein the upper surface of the protrusion is angled towards the base of said channel prior to deflection by said panel, wherein said first and second spacers are mounted in said channel such that said spacers are capable of sliding along said channel; and

15 retaining means for retaining at least one of said first and second spacers in said channel to limit movement of said spacers in a direction transverse to the length of said channel towards the channel opening defined between said opposed side walls, wherein said retaining means is
20 arranged to permit movement of said spacers in a direction along said channel.

45. A frame member as claimed in any one of claims 36 to 44, comprising a third spacer positioned at the base of
25 said channel for spacing said panel from said base.

77271-59

46. A frame member as claimed in claim 45, wherein said third spacer is coupled to at least one of said first and second spacers.

5 47. A frame member as claimed in claim 46, wherein said third spacer is hingedly coupled to at least one of said first and second spacers.

48. A frame member as claimed in claim 47 wherein the
10 third spacer has first and second side edges and each of said first and second spacers has a lower edge, and at least one of said first and second spacers is hingedly coupled to the third spacer along and between respective adjacent edges.

15

49. A frame member as claimed in claim 48 including biasing means between said third spacer and at least one of said first and second spacers for urging a respective spacer outwardly into engagement with a respective channel wall.

20

50. A frame member as claimed in claim 49 wherein said third spacer has a lower surface which engages the base of said channel and said third spacer includes a formation on its lower surface, and the base of said channel includes a
25 complementary formation to locate said third spacer at a predetermined position between the side walls of said channel when said formations engage.

77271-59

51. A frame member as claimed in claim 50, wherein said third spacer includes oppositely sloped lower surfaces providing said formation and the base of said channel includes complementary oppositely sloped surfaces for
5 engaging said formation.

52. A frame member as claimed in claim 51, wherein the sloped surfaces of said third member slope downwards towards a centre line through said third spacer between opposed
10 sides thereof, and complementary surfaces of the base of said channel slope downwards towards the centre of said channel.

53. A frame member as claimed in claim 52, wherein
15 said third spacer includes means formed therein which allows fluid communication therethrough in a direction along said channel.

54. A spacer for use in mounting a panel within a
20 channel of a frame member, comprising a base portion for spacing said panel from the base of said channel;

two side portions extending from said base portion for spacing said panel from respective side walls of said channel; and

25 protrusions extending from said side portions for engaging opposite faces of said panel and for resiliently retaining said panel in said frame member.

77271-59

55. A spacer as claimed in claim 54, wherein said protrusions extend from upper ends of said side portions.

56. A spacer as claimed in claim 54 or 55, wherein the
5 side portions include respective recesses below said protrusions to allow said protrusions to flex toward said base portion.

57. A spacer as claimed in any one of claims 54 to 56,
10 wherein said protrusions have respective upper surfaces which are directed towards said base portion when said protrusions are in an unstressed condition.

58. A spacer as claimed in any one of claims 54 to 57,
15 wherein said protrusions are formed by respective extensions of said side portions which are folded such that said protrusions extend from said side portions.

59. A spacer as claimed in any one of claims 54 to 58
20 wherein said side portions are hingedly coupled to said base portion.

60. A spacer as claimed in claim 59, wherein said side portions are integrally formed with said base portion and
25 junctions between said base portion and said side portions have a reduced thickness to hingedly couple said portions together.

77271-59

61. A spacer as claimed in claim 60, wherein a region adjacent said junctions of said base portion and said side portions are relieved to accommodate folding of said side portions towards said base portion.

5

62. A spacer as claimed in any one of claims 54 to 61, wherein the surface of the spacer which engages said channel includes means for positioning said spacer within said channel at a predetermined transverse position.

10

63. A spacer as claimed in claim 62, wherein said positioning means comprises oppositely sloped lower surfaces of said base portion.

15 64. A spacer as claimed in claim 63, wherein said oppositely sloped surfaces slope downwards towards an axial centre line through said base portion.

20 65. A spacer as claimed in any one of claims 54 to 64, wherein said base portion includes means for permitting fluid to flow therethrough between adjacent portions of the channel separated by said spacer when inserted in said channel.

25 66. A spacer as claimed in any one of claims 54 to 65, wherein the outer surfaces include a low friction layer or coating.

77271-59

67. A spacer as claimed in any one of claims 54 to 66, wherein the surfaces of said protrusions for engaging said panel are relatively high friction surfaces.

5 68. A spacer as claimed in any one of claims 54 to 67 where said spacer is made from ethylene propylene diene monomer (EPDM) rubber.

69. A framed panel unit as claimed in claim 1, at
10 least one of said side walls of each said frame member having an elongate recess formed therein extending along the channel and positioned below the top of a respective sidewall.


15 70. A framed panel unit as claimed in claim 69, wherein the upper edge of said recess is substantially perpendicular or angled downwardly from the recess towards said channel with respect to a line directed from the base to the top of said channel.

20


71. A framed panel unit as claimed in any one of claims 69 or 70, wherein said channel includes a base having oppositely sloped upper surfaces transverse to said channel.

25 72. A framed panel unit as claimed in claim 1, wherein said spacer means centers said panel within said channel.


1/20

**Figure 1**

2/20

**Figure 2**

3/20

**Figure 3**

4/20




Figure 4A

5/20







Figure 4B



6/20

**Figure 5**




7/20


**Figure 6A****Figure 6B**



8/20

**Figure 7A****Figure 7B**

9/20

**Figure 8A****Figure 8B****Figure 8C**

10/20**Figure 9**

11/20**Figure 10A****Figure 10B**

12/20




Figure 10C








Figure 10D


14/20

**Figure 11B**


15/20**Figure 11C**

16/20


**Figure 12A****Figure 12B**

17/20**Figure 12C**


18/20

**Figure 12D**

19/20

**Figure 12E**

20/20

**Figure 13**

