



US 20160361521A1

(19) **United States**

(12) **Patent Application Publication**
Parodi et al.

(10) **Pub. No.: US 2016/0361521 A1**

(43) **Pub. Date: Dec. 15, 2016**

(54) **GUIDEWIRE WITH ADJUSTABLE STIFFNESS**

filed on Nov. 3, 2009, provisional application No. 60/913,489, filed on Apr. 23, 2007, provisional application No. 61/008,100, filed on Dec. 17, 2007.

(71) Applicant: **CardioGuidance Biomedical, LLC**,
Arlington, VA (US)

(72) Inventors: **Juan Carlos Parodi**, Pinecrest, FL (US); **Peter W. J. Hinchliffe**, Campbell Hall, NY (US); **Henry Lupton**, Oranmore (IE); **Ivan Mooney**, Tuam (IE); **Colin Donohue**, Atheryn (IE)

(21) Appl. No.: **15/183,254**

(22) Filed: **Jun. 15, 2016**

Related U.S. Application Data

(63) Continuation of application No. 13/719,319, filed on Dec. 19, 2012, now Pat. No. 9,387,309, which is a continuation of application No. 12/660,891, filed on Mar. 5, 2010, now Pat. No. 9,387,308, which is a continuation-in-part of application No. 12/082,507, filed on Apr. 11, 2008, now abandoned.


(60) Provisional application No. 61/159,178, filed on Mar. 11, 2009, provisional application No. 61/257,483,

Publication Classification

(51) **Int. Cl.**
A61M 25/09 (2006.01)
(52) **U.S. Cl.**
CPC ... *A61M 25/0905* (2013.01); *A61M 25/09041* (2013.01); *A61M 25/09025* (2013.01); *A61M 2025/0006* (2013.01)

(57) **ABSTRACT**

A medical guidewire system including an inner member having an outer diameter and an outer member having an inner diameter, the inner diameter being larger than the outer diameter. The inner and outer members are relatively slidable to adjust a stiffness of the guidewire system. The lumen of the outer member forms a gap for fluid flow therethrough. A connector to the inner member and a fluid infusion channel communicating with the gap for injection of fluid through the gap to exit a distal portion of the outer member.







FIG. 1B






FIG. 1A




FIG. 2A




FIG. 3




FIG. 4









FIG. 5








FIG. 12





FIG. 11







FIG. 13A






FIG. 13B






FIG. 16






FIG. 17




FIG. 18

FIG. 18A




FIG. 25




FIG. 18B




FIG. 29A








FIG. 31











FIG. 26




FIG. 27





FIG. 28






FIG. 29




FIG. 30

GUIDEWIRE WITH ADJUSTABLE STIFFNESS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 13/719,319 filed Dec. 19, 2012, (now allowed), which is a continuation of pending U.S. patent application Ser. No. 12/660,891 filed Mar. 5, 2010, (now allowed), which claims priority from U.S. provisional patent application No. 61/159,178, filed Mar., 11, 2009 and from U.S. provisional patent application No. 61/257,483, filed Nov. 3, 2009, and is a continuation in part of U.S. patent application Ser. No. 12/082,507, filed Apr. 11, 2008, now abandoned, (which claims priority from provisional application No. 60/913,489, filed Apr. 23, 2007 and provisional application No. 61/008,100, filed Dec. 17, 2007. The entire contents of each of these applications are incorporated herein by reference.

FIELD OF THE INVENTION

[0002] This application relates to a medical guidewire and more particularly to a medical guidewire system with adjustable size and stiffness.

BACKGROUND OF THE INVENTION

[0003] Guidewires are currently being used in medical procedures to guide catheters, sheaths or other devices from a remote site to a surgical site. From a remote part of the body, a guidewire is introduced into an artery or vein. The guidewire is then advanced through the vascular system to the target site where an angiogram, balloon, stent, catheter or other vascular device is to be positioned. The guidewire then functions as a rail for advancement of these devices.

[0004] Currently, a soft small diameter wire, such as a 0.014 wire, is utilized initially to advance in the artery or vein. During advancement, especially through tortuous anatomy, the soft wire may lack the requisite pushability to advance around a curve. Also, due to its softness/flexibility, it may be difficult to advance a catheter over it to perform the surgical, e.g. diagnostic and/or interventional, procedure. In these instances, this flexible wire needs to be exchanged for a stiffer and/or larger wire. To exchange the guidewire, several steps are required. First, an exchange catheter is advanced over the soft wire. Second, the soft wire is removed. Third, the stiffer wire is inserted through the exchange catheter. Fourth, the exchange catheter is removed, leaving the stiffer wire in place. Such wire exchanges are time consuming and require two separate wires and an exchange catheter. Furthermore, these steps also increase risks to the patient such as increased risk of infection and increased chance of damaging the vessel due to the added insertion and removal of the wires through the vascular system as well as possible loss of wire position and critical time loss.

[0005] Even after exchange for the larger wire, sometimes the requisite stiffness and pushability to advance through a curved vessel portion is still lacking and therefore the wire needs to be exchanged for yet an even stiffer wire. This requires an additional wire exchange utilizing the time consuming four step method described above.

[0006] After such exchange for a stiffer wire and advancement around the tortuous portion of the anatomy, a stenosis

or restricted passage of the vessel might be encountered through which the larger wire cannot pass. Thus, yet another catheter exchange could be required, this time exchanging the larger diameter stiffer wire for the smaller diameter softer wire. As a result, multiple guidewire exchanges requiring multiple insertions of the exchange catheter, multiple removals of the already inserted wire, and multiple insertions of a new wire from the remote site may be necessary in a single surgical (diagnostic and/or interventional) procedure. As noted above, this adds undesired time to the surgical procedure, as well as increases the risk of trauma or damage to the vessel and loss of desired wire position.

[0007] In addition, the inventor has found that in some instances where a catheter exchange is required, the surgical procedure cannot even be performed. That is, in some instances, the exchange catheter, which has a larger diameter (typically about 0.040 inches inside diameter) than the stiffer replacement wire because it has a lumen to receive the wire, cannot cross the stenosis. In this case, the guidewire with increased pushability cannot be inserted and advanced to reach the target site, thus not enabling a stent, dilation balloon or other vascular treatment device to be advanced to the surgical site. Consequently, the intraluminal surgical procedure cannot be performed.

[0008] As can be appreciated from the above, in the current procedure, multiple guidewires may be required to achieve desired parameters such as softness to reduce trauma to the vessel during insertion, reduced diameter to enable access through restricted passages in the vessels and facilitate access to the surgical site, stiffness/rigidity to allow pushability and stiffness/rigidity to facilitate passage of a catheter thereover. For example, a gentler more flexible guidewire, such as a 0.014 inch diameter wire, has the small diameter and softness advantage, but lacks the pushability to advance through some tortuous anatomy. The larger diameter guidewire, such as the 0.035 or 0.038 inch diameter guidewire, is more rigid and has better pushability but may be too large for restricted passages. It may also still lack the necessary stiffness, thus requiring an exchange for an extra stiff wire. The extra stiff wire lacks the flexibility and softness. Thus, the user needs to exchange the wires to obtain the requisite pushability, flexibility and stiffness for accessing the diagnostic and/or interventional site.

[0009] Also, exchange sheaths, when used with a 0.014 guidewire, present a relatively large stepped transition from their distal end to the smaller diameter 0.014 guidewire, therefore creating a more traumatic "snow plow" effect during insertion.

[0010] Therefore, it would be advantageous to provide a guidewire system which provides the desired diameter, pushability, flexibility and stiffness without requiring guidewire exchanges and exchange catheters, thereby eliminating the foregoing disadvantages of such exchanges.

[0011] It would also be advantageous if fluid, such as contrast, could be injected through the guidewire system for visualization.

SUMMARY OF THE INVENTION

[0012] The present invention overcomes the problems and deficiencies of the prior art. The present invention provides in one aspect a medical guidewire system comprising a first inner member having a first outer diameter, a second intermediate member having a second outer diameter larger than

the first outer diameter, and a third outer member having a third diameter larger than the second outer diameter. The second member has a longitudinally extending opening to receive the first member for relative sliding movement with respect to the first member and the third outer member has a longitudinally extending opening to receive the second member for relative sliding movement with respect to the first and second member. The second and third members have an interlocking frictional engagement and the first and second members have a clamping engagement.

[0013] In one embodiment, the third member has a third stiffness greater than the first stiffness of the first member, and the second member is movable with respect to the third member to provide the third member with a second stiffness greater than the third stiffness.

[0014] In one embodiment, the first member comprises a solid core material. The first and second members in one embodiment are composed at least in part of shape memory metal. In one embodiment, the second and/or third members comprise hypotubes which can have slots in a sidewall to increase flexibility.

[0015] In one embodiment, the first member includes a slotted member slidable thereon for selected engagement with the second member at a selected position.

[0016] The present invention in another aspect provides a medical guidewire system comprising an inner member having an outer diameter and an outer member having an inner diameter, the inner diameter being larger than the outer diameter. The outer member has a longitudinally extending lumen to receive the inner member. The inner and outer members are relatively slidable to adjust a stiffness of the guidewire system. The lumen of the outer member forms a gap for fluid flow therethrough. A connector has a first end portion connected to the outer member, a second end portion connected to the inner member and a fluid infusion channel communicating with the gap for injection of fluid through the gap to exit a distal portion of the outer member.

[0017] The inner member can be selectively lockable with the outer member. The gap in one embodiment is defined by an annular space between an outer wall of the inner member and an inner wall of the outer member.

[0018] In one embodiment, the connector includes a first clamping member at the first end portion and a second clamping member at the second end portion. A rotatable knob can be provided at each end portion to provide a clamping force on the inner member and on the outer member. The connector can include a side arm for delivering fluid to the lumen of the outer member.

[0019] In one embodiment, the outer member comprises a hypotube having a plurality of slots formed therein.

[0020] In another aspect, the present invention provides a medical guidewire system comprising an inner member having an outer diameter, an outer member having an inner diameter forming a first lumen, and an intermediate member having a second lumen. The inner diameter is larger than the outer diameter. The outer member has a longitudinally extending lumen to receive the intermediate member and the intermediate and outer members are relatively slidable to adjust a stiffness of the guidewire system. The lumen of the intermediate member forms a gap for fluid flow therethrough, and a connector has a first end portion connected to the intermediate member, a second end portion connected to the inner member and a fluid infusion channel communicating with the gap for injection of fluid through the gap to

exit a distal portion of the guidewire system. The connector includes a first clamping member engageable with the intermediate member and a second clamping member engageable with the inner member.

[0021] In one embodiment, the inner wire has a locking member thereon movable by engagement with the intermediate member to a locking position to fix the position of the inner and intermediate members, and the intermediate member has a flared handle portion frictionally engageable with the outer member to fix the position of the outer and intermediate members.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] Preferred embodiment(s) of the present disclosure are described herein with reference to the drawings wherein:

[0023] FIG. 1 is a perspective view of the guidewire system of the present invention showing the intermediate (stiffener) wire and outer wire in the retracted position to expose the inner wire;

[0024] FIG. 1A is an exploded perspective view of the guidewire of FIG. 1;

[0025] FIG. 1B is a longitudinal cross-sectional view of the guidewire of FIG. 1 showing the outer wire and the intermediate stiffener wire in the advanced position;

[0026] FIG. 2 is a perspective view of an alternate embodiment of the guidewire system of the present invention showing the intermediate (stiffener) wire and outer wire in the retracted position to expose the inner wire;

[0027] FIG. 2A is a longitudinal cross-sectional view of the guidewire of FIG. 2 showing the outer wire and the intermediate stiffener wire in the advanced position;

[0028] FIG. 3 is an anatomical view illustrating the guidewire of the present invention being inserted through the femoral artery for subsequent advancement through the vascular system, e.g. to the external carotid artery (the shuttle sheath not shown for clarity);

[0029] FIG. 4 is a longitudinal cross-sectional view of the guidewire of FIG. 1 showing the outer wire and the intermediate stiffener wire in the retracted position to expose the inner wire, corresponding to the position of the wires in FIG. 1;

[0030] FIG. 5 is a longitudinal cross-sectional view of the guidewire of FIG. 1 showing the outer wire in the advanced position and the intermediate stiffener wire in the retracted position;

[0031] FIG. 6 is a perspective view of an alternate embodiment of the guidewire of the present invention having a modified distal tip, and illustrating the outer wire and intermediate stiffener wire in the retracted position to expose the inner wire;

[0032] FIG. 7 is a longitudinal cross-sectional view of the guidewire of FIG. 6 except showing the outer wire in the advanced position and the intermediate wire in the retracted position;

[0033] FIG. 8 is a perspective view of a proximal end of the guidewire of the present invention showing attachment of a conventional extension wire to the inner wire;

[0034] FIG. 9 is an enlarged cross-sectional view taken along line 9-9 of FIG. 8 showing the attachment of the extension wire to the inner wire;

[0035] FIG. 10 is a perspective view of another alternate embodiment of the guidewire system of the present invention, the outer wire shown in the advanced position and the intermediate stiffener wire in the retracted position;

[0036] FIG. 11 is a longitudinal cross-sectional view of the guidewire of FIG. 10 showing the outer wire in the advanced position and the intermediate stiffener wire in the retracted position;

[0037] FIG. 12 is a cross-sectional view of an alternate embodiment of the handle of the inner wire having a threaded engagement for removal from the inner wire;

[0038] FIG. 13 is a perspective view of an alternate embodiment of the guidewire system of the present invention showing the intermediate (stiffener) tube and outer tube in the retracted position to expose the inner wire;

[0039] FIG. 13A is a cross-sectional view taken along line A-A of FIG. 13 showing the distal region of the outer tube (the inner wire removed for clarity);

[0040] FIG. 13B is an exploded perspective view of the guidewire of FIG. 13;

[0041] FIG. 14 is an enlarged view of the guidewire of FIG. 13 showing the handles in the retracted unlocked position;

[0042] FIG. 15 is a perspective view of the inner wire handle of FIG. 14 engaged (interlocked) with the stiffener handle prior to locking;

[0043] FIG. 16 is a perspective view similar to FIG. 15 showing the inner wire handle rotated to lock the inner wire and stiffener;

[0044] FIG. 17 is an enlarged view of the stiffener tube of FIG. 13;

[0045] FIG. 18 is an enlarged view of an alternate embodiment of the stiffener tube;

[0046] FIG. 18A is an enlarged view of an alternate embodiment of the outer tube;

[0047] FIG. 18B is an enlarged view of an alternate embodiment of the outer tube;

[0048] FIG. 19 is an enlarged perspective view of a proximal portion of an alternate embodiment of the guidewire system of the present invention showing the inner wire and stiffener tube in the retracted position;

[0049] FIG. 20 is a perspective view showing the handles of FIG. 19 prior to engagement;

[0050] FIG. 21 is a cross-sectional view of the handle of the inner wire of FIG. 19 prior to attachment to the inner wire;

[0051] FIG. 22 is an enlarged perspective view of a proximal portion of another alternate embodiment of the guidewire system of the present invention showing the inner wire and stiffener in the retracted position;

[0052] FIG. 22A is an enlarged view of the locking member of the inner wire of FIG. 22;

[0053] FIG. 23 is a cross-sectional view illustrating the threaded locking member of the inner wire spaced from the threaded portion of the stiffener collar;

[0054] FIG. 24 is a cross-sectional view of the threaded locking members engaged for rotation to fix the inner wire axially with respect to the stiffener tube; and

[0055] FIG. 25 is a perspective view of a proximal portion of another alternate embodiment of the guidewire system of the present invention showing the inner wire in the retracted position;

[0056] FIG. 26 is a perspective view of another alternate embodiment of the guidewire system of the present invention;

[0057] FIG. 27 is a close up perspective view of the threaded interlock of the intermediate and outer members of FIG. 26;

[0058] FIG. 28 is a close up perspective view of the clamping interlock of the intermediate and inner members of FIG. 26;

[0059] FIG. 29 is a cross-sectional view of an alternate embodiment of the guidewire system of the present invention having a connector for fluid injection;

[0060] FIG. 29A is a perspective view of the inner wire, intermediate and outer tube of FIG. 29;

[0061] FIG. 30 is a cross-sectional view of another alternate embodiment of the guidewire system of the present invention having a connector for fluid injection;

[0062] FIG. 31 is a cross sectional view of the distal portion of the guidewire system of FIG. 30 showing the inner member in an advanced position.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0063] Turning now to the drawings, wherein like reference numerals identify similar or like components throughout the several views, the guidewire system of the present invention is illustrated. The guidewire system comprises a guidewire 10 have three coaxial members, or in some embodiments two coaxial members, movable with respect to one another to adjust the stiffness and size (outer diameter) of the guidewire.

[0064] More specifically, the guidewire system 10 in the embodiment shown in FIGS. 1-5, comprises a small diameter inner member 20, an intermediate stiffener member 30 slidable over the inner member 20, and a larger diameter outer member 40 slidable over the intermediate member 30 and the inner member 20. As used herein, the term “proximal” refers to the part or component of the system closer to the user and the term “distal” refers to the part or component further from the user. The term member as used herein includes a wire, tube or other structure of the inner, intermediate and outer components of the guidewire system.

[0065] The small diameter inner member 20, in a first embodiment, is a wire having a spherical or ball tip 22 either integral or attached thereto. The ball tip 22 provides a blunt atraumatic leading end of the wire to reduce trauma to the vessel during advancement. The ball tip 22 is also preferably dimensioned so it has a larger diameter (transverse dimension) than the diameter of the lumen 42 of the outer wire 40 or at least larger than the diameter of the opening to the lumen 42. Thus, it also acts as a stop to prevent withdrawal of the entire wire 20 through the outer wire 40 and acts as a stop to limit distal movement of the outer wire 40 so it does not extend over the tip 24 so that a blunt tip can remain as the leading edge for the guidewire 10 to provide a smoother passage. This is shown for example in FIG. 2 where the surface 22a of the tip 22 would abut the distalmost end 40a of outer wire 40.

[0066] It should be appreciated that tips other than ball tips can be utilized. For example, FIGS. 6 and 7 show a conical tip 22' of inner wire 20' having a smoother transition and functioning similar to ball tip 22. In all other respects, guidewire 10' of FIG. 6 is identical to the guidewire 10 of FIG. 1. The guidewire 10' is shown in FIG. 6 with the intermediate wire 30' and outer wire 40' retracted to expose the inner wire 22' and shown in FIG. 7 with the outer wire 40' advanced to its distal position.

[0067] Additionally, it should be appreciated that an enlarged tip need not be provided. For example, in the

alternate embodiment of FIG. 2, the distal tip of the inner wire is the same diameter as the portion proximal of the distal tip.

[0068] The inner wire forms the core wire of the system, and is preferably formed of a solid core and can be composed at least in part of a shape memory material such as Nitinol. Non-metallic materials can also be utilized, such as Pebax. The inner wire in one embodiment can have a coil and core combination towards its distal end and is a solid wire towards its proximal end. Other materials such as stainless steel are also contemplated. Preferably, the wire **20** has an outer diameter of about 0.014 inches, although other dimensions are also contemplated. Preferably, the inner wire **20** has a greater degree of flexibility and is softer than the other two wires **30**, **40**. In one embodiment, for example, the coil wire is composed of a stainless steel wire with a platinum coil at a distal tip over a reduced diameter of the stainless steel wire, and has a PTFE coating.

[0069] The stiffener member **30** forms the intermediate wire as it is positioned between the inner wire **20** and outer wire **40**. Stiffener wire **30** can be formed from single or multiple wires wound together, having a lumen **32** with a dimension (diameter) larger than the outer diameter of the wire **20** so it can slide over wire **20** (or wire **20** can slide within it). In a preferred embodiment, the stiffener wire **30** has an outer diameter of about 0.018 inches, although other dimensions are also contemplated. The wire **20** can be formed of a shape memory material such as Nitinol, although other materials, such as stainless steel, are also contemplated. In one embodiment, the stiffener has a stiffness/rigidity greater than the stiffness of the inner wire **20** and outer wire **40**. However, the stiffener can alternatively have a stiffness less than the stiffness of the outer wire/and or inner wire, provided it has sufficient stiffness such that when it is advanced, it stiffens a distal region of the outer wire (and overall guidewire system) by providing a distal region of increased wall thickness due to the combination of stiffener and outer member. That is, in such embodiment, advancement of the stiffener provides a thicker walled and thereby stiffer/more rigid wire.

[0070] The stiffener, in an alternate embodiment, is in the form of a slotted hypotube which is described in more detail below.

[0071] The outer wire **40** has a longitudinally extending opening or lumen **42** with a dimension (diameter) larger than the outer diameter of the intermediate wire **30** so it can slide over wire **30** and smaller wire **20** (or wire **30** can slide within it). In a preferred embodiment, the outer diameter of the wire is between about 0.035 inches to about 0.038 inches, although other dimensions are also contemplated. In one embodiment (not shown) the outer wire **40** is a wound wire wound in one direction. It could be a round wire or a rectangular wire. Alternatively, it can comprise a series of wound or twisted wires. The wire **40** can also have a hydrophilic and/or a PTFE coating. It can also be formed with a coated or uncoated plastic jacket. A safety wire connected to proximal and distal portions of the outer wire could optionally be provided. The outer wire **40** has a stiffness/rigidity greater than the stiffness of the inner wire **20**. In some embodiments, the outer wire can also have a stiffness less than the stiffness/rigidity of the intermediate wire **30** as discussed above.

[0072] In an alternate embodiment, the outer tube is in the form of a slotted hypotube which is described in more detail below.

[0073] In the alternate embodiment of FIGS. 2 and 2A, inner wire **50** does not have an enlarged tip but terminates in a tip **52** of the same diameter. Outer wire **60** has a thicker wall portion at the distal end portion **62** to create a shoulder **62b** and a reduced lumen diameter **62a**. The shoulder **62b** can form a stop to limit distal advancement of the stiffener **70** such that the distalmost end of the stiffener, although extending to a distal region of the outer wire **60**, cannot extend to a distalmost end of the outer wire **60**. The reduced lumen area **62a** creates a tighter fit for the inner wire **20** as it slides more closely around the inner wire **50** to limit entry of material into the lumen of the outer wire **60**. The tighter fit also enables clot to be wiped off the inner wire **50** upon movement with respect to the distal tip **63** of outer wire **60**. The tip **63** also has a smooth shallow taper (similar to the outer wire **40** of FIG. 1) to provide a smoother transition and facilitate advancement over the inner wire **50** in very tight and tortuous anatomy with reduced trauma. Tips with even more gradual tapers could be provided. In all other respects, the guidewire system of FIG. 2 is the same as FIG. 1.

[0074] In one embodiment, the inner wires described herein have a length of about 3.0 m, the intermediate wires or tubes described herein have a length of about 2.36 m to about 2.38 m and the outer wires or tubes described herein have a length of about 2.4 m to about 2.6 m. In another embodiment, the intermediate wires or tubes described herein have a length of about 1m to about 2 m, and preferably about 1.8 m, and the outer wires or tubes described herein have a length of about 1m to about 2 m, and preferably about 1.8 m. It should be understood that these dimensions are provided by way of example and other dimensions are also contemplated.

[0075] It should be appreciated that sliding movement of the wires (or tubes) referred to herein means that either the outside wire (or tube) is moving over the held (stationary) inside wire, the inside wire is moving within the stationary outside wire, or both wires are sliding in opposite directions. For example, the inner wire can be exposed by moving the inner wire distally, moving the outer wire (tube) proximally, or moving both wires in their respective directions. However, it may be preferable that the stiffening wire be advanced or retracted to maintain the advanced position of the guidewire during insertion. The foregoing likewise applies to the use of tubes instead of wires as one or more of the members of the guidewire system.

[0076] The use of the guidewire system will now be described with reference to the embodiment of FIG. 1, it being understood that such use is also applicable to the other embodiments of the present invention described herein utilizing the three members in the form of wires or tubes (or other structures).

[0077] It is also contemplated that a two component guidewire system be provided with an inner member and an outer member slidable with respect to one another to adjust the guidewire diameter and to adjust the guidewire stiffness without the use of a stiffener. The inner member and outer member in such system are lockable to one another. Examples of such embodiments are described below.

[0078] In use, selective positioning of the three wires with respect to one another varies the diameter of the guidewire being advanced through the vascular system and varies the

stiffness of the guidewire. This independent sliding movement of the wires provides an in situ progressive transformation of the soft wire, used to avoid damage to the vessel, into a stiff or rigid wire to provide a rail system for easier catheter advancement thereover and to increase pushability around curved anatomy.

[0079] More specifically, to increase the pushability and stiffness of the guidewire 10, the outer wire 40 is advanced distally over the inner wire 20 from the position of FIG. 4 to the position of FIG. 5 (or the inner wire 20 is retracted to the position of FIG. 5). If further stiffness or enhanced pushability is desired, the intermediate wire 30 is advanced from the retracted position of FIG. 5 to the advanced position of FIG. 1B. Sliding of the wires is controlled by the user at the proximal end.

[0080] Note in the embodiment of FIG. 1B, in the advanced position of the intermediate wire 30, it remains spaced proximally from the distalmost end of the outer wire 40 to reduce trauma to the vessel by ensuring some flexibility of the distalmost tip of the guidewire 10. In one embodiment, in the advanced position, the distalmost end 34 of the intermediate wire 30 is spaced a distance of about 1 centimeter to about 4 centimeters, and preferably from about 1 cm to about 2 cm, from the distalmost end 40a of outer wire 40. Other spaced distances are also contemplated. In the advanced position of the inner wire 20 (FIGS. 1 and 4), it can protrude about 30 cm to about 40 cm from the distalmost end 40a of outer wire 40. In other embodiments, it can protrude from about 5 cm to about 20 cm from the distalmost end 40a of outer wire 40. Other protruding lengths are also contemplated.

[0081] After the guidewire 10 has been stiffened by relative sliding movement of the outer and/or intermediate wire, if a smaller diameter and more flexible guidewire is desired, the inner wire 20 can again be exposed by retraction of the outer wire 40 (and stiffener wire 30) or advancement of the inner wire 20 (or opposite movement of both).

[0082] As can be appreciated, relative movement of the wires can occur repeatedly as desired to enhance advancement of the guidewire 10 through the vascular system to the desired surgical site.

[0083] In an alternate embodiment shown in FIGS. 10 and 11, each of the wires 120, 130 and 140 of guidewire 100 has a handle portion. Handle portions as used herein include integral handles, separate handles attached to the members or a proximal end portion of the member which interlocks with another member. With reference to FIGS. 10 and 11, inner wire 120 has a handle 124 at its proximal end, intermediate stiffener wire 130 has a handle 134 at its proximal end, and outer wire 140 has a handle portion 144 at its proximal end. This facilitates grasping of the wire by the user as well as facilitates torquing of the wire to rotate the distal end. One or more of the handles can include a textured surface (see e.g. handle 144 of FIG. 10) to facilitate gripping.

[0084] The handles can optionally interlock to fix the positioning of the wires with respect to one another. FIG. 11 illustrates one way to interlock the handles. In this embodiment, the engagement regions of the members include an interlocking feature in the form of a taper/recess interlock. More specifically, interlocking is achieved by providing a taper on the distal portion of handles 124 and 134 which frictionally mate with a proximal recess at the proximal end of the mating handle. More specifically, distal tapered region

125 of handle 124 would frictionally engage with the proximal recess 136 of handle 134 and distal tapered region 135 of handle 134 would frictionally engage the proximal recess 146 of handle 144. Thus, when inner wire 120 is moved relative to the outer wire 140, the user does not need to hold it in this advanced (exposed) position as the handle 124 would interlock with handle 134 to fix the inner wire 120 in position. Similarly, when intermediate wire 130 is moved relative to the outer wire 140, the user does not need to hold it in this position as the handle 134 would interlock with handle 144 to fix the inner wire 120 and intermediate wire 130 in position. This interlocking of the handles 134 and 144 could also be used to maintain the spacing between the distalmost ends of the wires 130 and 140 as described above with respect to wires 30 and 40. It could also be used to maintain the distal tip of the inner wire 20 as the leading edge instead of or in addition to utilizing the larger diameter tip, e.g. the ball tip, to achieve this function. The handle for the outer wire is shown as the same dimension of the outer wire so the handle can be considered the proximal portion of the wire.

[0085] FIGS. 13-17 illustrate an alternate embodiment of the guidewire system having alternate engagement regions providing an alternate mechanism for interlocking the members. This system has a stiffener and outer member formed of a tube. The relative stiffness of the inner, intermediate, and outer members can be provided as discussed above.

[0086] More specifically, guidewire 210 has an inner member 220, an intermediate stiffening member 230 and an outer member 240. Stiffener member 230 is in the form of a tube, preferably composed of stainless steel, and has a longitudinally extending lumen 232 (FIG. 17) dimensioned to slidably receive inner wire 220. The stiffener tube 230 in the embodiment illustrated in FIG. 17 has a plurality of slots 234 formed therein (preferably laser cut into the tube) to increase the flexibility of the tube. Each slot in the illustrated embodiment, extends around a portion of the circumference, for less than 360 degrees and preferably less than 180 degrees. Additionally, the slots are staggered such that a solid portion of the tube between the space between slots in one row is adjacent a slotted portion of another row. For ease of understanding, three rows of slots have been numbered in FIG. 17 to illustrate how slot portion 236a of row R2 is adjacent a gap 235b (solid tube portion) between slot portions of row R1 and adjacent gap 237b (solid tube portion) between slot portions of row R3.

[0087] As shown, the axial spacing between the slots in FIG. 17 is substantially equal. However, it is also contemplated that the spacing between the slots can be varied at various portions along the tube to provide areas of different flexibility. For example, in the embodiment of FIG. 18, the slots of tube 230' vary such that slots 2311a at the distal portion of the tube 230' are closer together (have a shorter distance d1) than the slots 2311b of a more proximal portion which have a greater distance d2 between them. This provides more flexibility toward the distal end. Various slot spacing is contemplated. For example, the slots can be varied such that they become progressively further apart in a proximal direction or discrete regions of the tube can have slots of substantially equal spacing, but different than other regions of the tube.

[0088] It is also contemplated, that the slots can be formed in a spiral pattern such as shown in FIG. 18A illustrating an outer tube with slots. The outer tube 240' has spiral or

helically arranged slots **249** formed in the tube, preferably at an angle to the longitudinal axis as shown. The spiral slots, preferably formed by laser cutting, can be interrupted, leaving a solid wall portion **243** between the sets of spiraling slots. The solid wall portions can be evenly spaced as shown to provide similar sets of slots or can be varied to provide sets having different lengths of spiraling slots. Such spiraling slots can also be formed on the intermediate stiffener tube. A heat shrink tube (not shown), made of PET for example, can be positioned over all or a portion of the tube, and preferably over a distal portion and a hydrophilic coating or jacket can be provided over the distal portion, preferably for about 30 cm.

[0089] In the embodiment of FIG. 18B, gaps **262b** (solid tube portion) of slots **260** are radially staggered. The slots **260** are formed in a spiral pattern with the space **263** therebetween (pitch) increased toward a proximal end. Different portions can be of a different constant pitch and/or portions can be of progressively increasing pitch.

[0090] The foregoing slot arrangements can be provided on the stiffener tube and/or the outer tube. It should be appreciated, however, that in alternate embodiments, the stiffener tube and/or outer tube do not have slots.

[0091] Referring back to FIGS. 13-13C, inner wire preferably is a 0.014" wire as described above and outer member **240** is in the form of a tube, preferably of stainless steel. The outer tube **240** can have slots in the various arrangements as described above with respect to the stiffener tube **230** and the distances between slots can be varied in different regions of the tube as described above. The outer tube **240** and stiffener **230** can have the same or different slot arrangements.

[0092] Outer tube **240** has a lumen **242** dimensioned to slidably receive stiffener tube **230**. Outer tube **240** has a distal end portion, best shown in FIG. 13A, having a distal lumen portion **242a** that gradually reduces in diameter, to a diameter **E1** at region **242b**, less than the diameter **E2** at region **242c**. In this manner, diameter **E1** can be close to the outer diameter of the inner wire **230** to reduce any gap between the inner wire **220** and outer tube **240** when the inner wire **220** is extended. The inner wall **241** of outer tube **240** is angled to provide a smooth transition between the two diameters **E1** and **E2** to ease the movement of inner wire **220** through lumen **242** to an extended position.

[0093] Alternatively, a lead in tube, e.g. tube **850** of FIG. 31, can be positioned within the outer tube at a distal end having a reduced diameter portion for the inner member. The lead in tube can be attached to the outer tube by soldering, e.g. solder **860**, or other attachment methods. Solder **860** can have a radiused portion to provide a smooth transition for sliding of the inner wire **820** through outer tube **840**. The lead in tube is shown with the embodiment having a fluid connector (described below), but could also be used in other embodiments described herein.

[0094] In some embodiments, a distal portion of the outer tube can have a PET heat shrink and/or a hydrophilic coating. The PET can have a hydrophilic coating over a distal portion. Proximal of the distal portion a coating such as PTFE can be provided on the outer tube.

[0095] The members in the embodiment of FIGS. 13-16 have engagement regions with an interlocking feature in the form of a rotational pin and slot arrangement. More specifically, inner wire **220** has a handle **221** with an L-shaped slot **228** at its distal end. Pin **233** at the proximal end of handle **231** of stiffener tube **220** engages slot **228**. That is, when the

inner wire **220** is advanced longitudinally, the pin **233** engages the longitudinal region **228a** of slot **228** (see FIG. 15). This also acts as a stop for longitudinal advancement of the inner wire **220**. Once in the slot region **228a**, the inner wire **220** is rotated so that the pin **233** enters the transverse slot region **228b** as shown in FIG. 16, thereby fixing the axial position of the inner wire **220** and stiffener **230**. Similarly, the intermediate tube **230** has an L-shaped slot **238** at the distal end of handle **231**. A proximal pin **245** of outer tube **240** enters the longitudinal slot region **238a** and then upon rotation, enters the transverse region **238b** to fix the stiffener **230** to the outer tube **240**. Pin **245** could also be provided on a handle of outer tube **240**. This interlocking handle also functions as a stop to limit the extent of distal movement of the stiffener tube **230** within outer tube **240**.

[0096] Note as an alternative to the pin/slot arrangement, two locking tabs could be provided as shown in FIG. 25. Mating tabs **292** and **283** of outer tube **290** and of handle **281** of stiffener tube **280**, respectively, interlock upon rotation. Similarly, proximal locking tab **282** of handle **281** of stiffener tube **280** interlocks with tab **272** of handle **271** of inner wire **270**.

[0097] FIGS. 19-21 illustrate another embodiment for interlocking the handles to lock the members to prevent longitudinal movement of the members. The embodiment is similar to the embodiment of FIG. 11. Inner wire **320** has a proximal handle **321** with a distal tapered region **322**. This tapered region **322** is inserted into the opening **333** of proximal handle **331** of stiffener tube **330** to frictionally engage the handles. This interference fit interlocks the handles which thereby interlocks the inner wire **320** and stiffener tube **330** to prevent movement of the inner wire **320** with respect to the stiffener tube **330**. The proximal end of outer tube **340** has an opening **343** dimensioned to matingly receive the distal tapered region **332** of handle **331** of intermediate stiffener tube **330** to lock the stiffener **330** against longitudinal movement with respect to the outer tube **340**.

[0098] The handle **321** of inner wire **320** can include a distal taper **327** to releasably engage the inner wire **320**, as shown in FIG. 21. In this manner, the handle **321** can be removed from the wire **320** to enable removal of the intermediate tube **330** and outer tube **340** from the surgical site by sliding proximally over the wire **320**, leaving wire **320** in place. The proximal end of the handle **321** can include a lumen **328** to engage an extension wire (not shown) to increase the length of the inner wire **320**.

[0099] Alternately, a torque type handle can be used to control the inner wire and can be positioned at a desired portion along the proximal exposed wire and can be configured so as to lock and unlock on the other wires while at the same time engaging the handle of the other wire. FIGS. 22-24 illustrate an example of this showing another alternate embodiment of an engagement region with an interlocking feature. A collet **422** has a distal tapered region with a plurality of slots **423**. A series of external threads **424** threadingly engage internal threads **434** of collar **432**. Collar **432** is attached to a proximal end of the stiffener tube **430**.

[0100] In use, collet **422**, which encircles inner wire **420**, is inserted within the opening **435** of handle or collar **434**. In this position, collet **422** is attached to collar **434** but inner wire **420** can still freely move longitudinally within intermediate stiffener tube **430** and outer tube **440**. If the user decides to fix (lock) the position of the inner wire **420** to

prevent longitudinal movement, handle surface 426, preferably textured to enhance grasping, is gripped and rotated as shown in FIG. 24. This advances the collet 422 further into the collar 432, resulting in the internal taper of the collar compressing the slotted region of the collet 422 to apply a clamping force on the inner wire 420. This clamping force applied by the collet 424 prevents longitudinal movement of the inner wire 420. To free the inner wire 420 for longitudinal movement, the collet 424 is rotated in the opposite direction to retract the collet 424 to allow it to expand to loosen the grip on the inner wire 420. Thus, the inner wire 420 and stiffener tube 430 can be selectively interlocked at a desired axial position of these members. That is, after movement of the members to the desired axial position, the user can rotate the collet to lock the members.

[0101] In the alternate embodiment of FIGS. 26-28, the proximal end 531 of handle 538 of intermediate stiffener tube 530 is dimensioned to receive collapsible slotted member or collet 522 which encircles inner wire 520. More specifically, slotted member 522 has a tapered region 525, progressively decreasing in diameter toward a distal end, and an elongated slot or slots 524 formed therein and extending through the slotted member 522. That is, slot 524 can be formed so it extends through the opposing wall to form an opposing slot, also labeled as slot 524 in FIG. 28 and shown in phantom. The slots 524 are illustratively shown extending substantially longitudinally and equidistantly spaced, but could alternatively extend in other orientations and spacings, and a different number of slots can be provided to achieve the collapsibility and clamping function. Slotted member 522 has a longitudinal opening 523 extending along its length to receive the inner wire 520 therethrough.

[0102] In the normal non-collapsed position, the longitudinal opening 523 of slotted member 522 has a dimension larger than the outer diameter of the inner wire 520 so the inner wire 520 can freely slide therethrough. When it is desired to lock the position of the inner wire 520 with respect to the intermediate or stiffener tube 530, the slotted member 522 is slid over the inner wire 520 and inserted into the opening 527 at the proximal end 531 of handle 538 of intermediate tube 540. Due to the internal diameter of the handle 538, when the slotted member 522 is inserted a sufficient distance, the wall of the handle 538 will apply a clamping force on the slotted member 522, thereby collapsing it around the inner wire 520 to reduce the diameter of the longitudinal opening 523 and provide a clamping force to prevent longitudinal movement of the inner wire 520. Thus, the user can selectively lock the members when desired to fix their axial position. When it is desired to free the inner wire 520 for longitudinal movement, the slotted member 522 is moved in the opposite direction, freeing itself from the confines of the handle 538 to allow it to expand back to its normal position (return the longitudinal opening to its larger diameter) to loosen the grip on the inner wire 520. In a preferred embodiment, the slotted member 522 is made from a superelastic material such as Nitinol to ensure repeated return to the previous configuration after repeated locking (clamping) and unlocking. Other materials are also contemplated. This Nitinol lock 522 can be slid proximally over the inner wire 520 and removed to enable removal of the outer tube 540 and intermediate tube 530 by sliding these tubes proximally over the inner wire 520.

[0103] In a two component system (without a stiffener), the slotted member 522 on the inner member would slide into a proximal portion of the outer tube (similarly dimensioned to handle 538) for clamping and locking of the outer tube and inner member.

[0104] A threaded engagement as shown in FIG. 26 fixes the position of the intermediate stiffener tube 530 and the outer tube 540. More specifically, the proximal end 542 of outer tube 540 has a series of male threads 546. These threads engage the internal female threads 537 on the distal end 536 of the handle 538 attached to or integral with the stiffener tube 530 to interlock the outer tube 540 and stiffener tube 530.

[0105] In all other respects, the guidewire system of FIGS. 26-28 and components and methods of use are the same as that described herein with respect to the other embodiments. The engagement regions (mechanisms for interlocking the members) of FIGS. 26-28 can be used with the various embodiments of the members described herein, including for example the slotted stiffener and outer hypotubes.

[0106] In an alternate embodiment illustrated in FIG. 29A, the proximal end 741 of outer tube 740 is crimped to form a reduced diameter portion and a distal end of intermediate tube 630 is flared out at region 738 to form a handle to be fitted over proximal end 741 to provide frictional (locking) engagement between the intermediate tube 630 and outer tube 740. In one embodiment by way of example, the outer tube can have a diameter of about 0.035 inches and is crimped down to about 0.033 inches and the intermediate tube has an attached tube portion with a flared portion of about 0.035 inches in diameter welded to the proximal end of the intermediate tube. This is described in more detail below, for example with the guidewire system having a fluid connector, but can be used with other systems.

[0107] FIG. 29-31 illustrate alternate embodiments of the guidewire system which enables fluid flow through the distal tip. Referring initially to FIG. 29, the three component guidewire system 600 is similar to the aforescribed embodiments as it includes an inner member 620, an intermediate member (stiffener) 630 and an outer member 740. The intermediate member 630 and/or the outer member 640 are preferably in the form of a hypotube with slots in the form as shown in FIG. 18 or 18B, but other slot arrangements are also contemplated. The three members move with respect to each other in the manner described above to change the stiffness and diameter of the guidewire and therefore for brevity are not repeated herein. Further, the members can interlock in the various ways described above, also for brevity not repeated herein.

[0108] The guidewire system 600 of FIG. 29 differs from the aforescribed guidewire systems in the provision of fluid injection. More specifically, guidewire system 600 includes a connector 700, preferably a Touhy Borst type connector, having a proximal end portion 702 and a distal end portion 704. The proximal end portion 702 includes external threads 706 which mate with internal threads 708 of proximal knob 710. Rotation of proximal knob 710 in a first direction compresses the proximal end portion of the connector 700 which in turn compresses internal collar 712 to apply a clamping force thereon. Internal collar 712 also provides a seal and has an opening to receive inner member 620 therethrough. Thus, rotation of proximal knob 710 in a

first direction clamps the proximal end portion 702 of connector 700 to an intermediate portion of the inner member 620.

[0109] The distal end portion 704 of connector 700 includes external threads 726 which mate with internal threads 728 of distal knob 721. Rotation of distal knob 721 in a first direction compresses the distal end portion of the connector 700 which in turn compresses internal collar 722 to apply a clamping force thereon. Internal collar or seal 722 has an opening to receive a proximal end of intermediate member 630 therethrough. Thus, rotation of distal knob 721 in a first direction clamps the distal end portion 704 of connector 700 to the proximal end of the intermediate member 630. In this manner, the connector 700 is attached to a proximal end of the intermediate member 630.

[0110] The connector 700 includes a side arm 730 in fluid communication with the internal channel 703 of the connector 700. This internal channel 703 is in fluid communication with the proximal opening 632 in intermediate member 630. Consequently, fluid injected through the side arm 730 flows into internal channel 703, through the proximal opening 632 in intermediate member 630 and through the gap 634 defined as the annular space between the inner wall of the intermediate stiffener 630 and the outer wall of the inner member 620. The fluid flows through this gap or lumen, and out the distal end of the outer member 640.

[0111] In an alternate embodiment of the guidewire system illustrated in FIGS. 30 and 31, a two component guidewire system is provided. The two component guidewire system 800 includes an inner member 820 and an outer member 840, preferably in the form of a slotted hypotube similar to hypotube 740. In this simplified construction, relative movement of the inner member 820 and outer member 840 adjusts the diameter of the guidewire and adjusts the stiffness of the guidewire without the use of an intermediate stiffener tube. That is, if a smaller and more flexible guidewire is desired, the inner member, e.g. a 0.014 wire, can be advanced/exposed relative to the outer member 840. If a stiffer guidewire is desired, the outer member 840 is advanced over the inner member 820, while preferably maintaining the position of the inner member 820. This two component system can be utilized with the fluid injection connector and capabilities of FIGS. 30 and 31 as well as with guidewire systems without such connectors. In the two component system, the inner member would lock to the outer member rather than the stiffener (intermediate tube). This can be achieved in the manners described above with respect to the engagement of the inner member and stiffener. For example, a collet or slotted member similar to slotted member 522 of FIG. 28 on the inner member can be clamped by the handle portion of the outer member as it is selectively inserted therein. The slotted member would be approximately sized for such engagement.

[0112] In the embodiment of FIGS. 30 and 31, the two component system 800 has a connector 900 similar to connector 700 of FIG. 29. More specifically, connector 900, preferably a Touhy Borst type connector, has a proximal end portion 902 and a distal end portion 904. The proximal end portion 902 includes external threads 906 which mate with internal threads 908 of proximal knob 910. Rotation of proximal knob 910 in a first direction compresses the proximal end of the connector 900 which in turn compresses internal collar 912 to apply a clamping force thereon. Internal collar 912 also provides a seal and has an opening

to receive inner member 820 therethrough. Thus, rotation of proximal knob 910 in a first direction clamps the proximal end portion 902 of connector 900 to the inner member 820.

[0113] The distal end portion 904 of connector 900 includes external threads 926 which mate with internal threads 928 of distal knob 921. Rotation of distal knob 921 in a first direction compresses the distal end portion 904 of the connector 900 which in turn compresses internal collar 922 to apply a clamping force thereon. Internal collar or seal 922 has an opening to receive outer member 840 therethrough. Thus, rotation of distal knob 921 in a first direction clamps the distal end portion 904 of connector 900 to the outer member 840. In this manner, the connector 900 is attached to a proximal end of the outer member 840.

[0114] The connector 900 includes a side arm 930 in fluid communication with the internal channel 903 of the connector 900. This internal channel 903 is in fluid communication with the proximal opening 842 in outer member 840. Consequently, fluid injected through the side arm 930 flows into internal channel 903, through the proximal opening 842 in outer member 840 and through the gap 844 defined as the annular space between the outer wall of the inner member 820 and the internal wall of the outer member 840. The fluid flows through this gap or lumen space, exiting the distal end of the outer member 840. This provides an increased gap diameter compared to the three component system of FIG. 29 because of the absence of the smaller diameter stiffener tube.

[0115] Various types of fluids can be injected through the guidewire systems. One type of fluid that can be injected is a radiopaque contrast for angiographic visualization. Other types of fluids include but are not limited to embolics and drugs. It is also contemplated that the inner wire can be removed to provide a larger lumen for injection of fluids or materials such as biogluers, microspheres, microbeads and/or embolic coils. Note that with the inner wire removed, proximal knob 910 (or knob 710) can be rotated to clamp further on collar 912 to provide a seal.

[0116] It should also be appreciated that in preferred embodiments, the components (inner, intermediate and outer members) of the guidewire system of FIG. 26, as in the other preferred embodiments of the guidewire systems disclosed herein, do not exceed a diameter of about 0.038 inches, and more preferably do not exceed a diameter of about 0.035 inches.

[0117] In an alternate embodiment shown in FIG. 12, the inner wire handle 124' is removable from inner wire 120' by unscrewing. More specifically, handle 124' is attached to inner wire 120' by a screw thread 121' such that the handle 124' can be unscrewed from inner wire 120. This allows outer wire 140 and intermediate wire 130 to be removed by retraction (proximal movement) over the length of the inner wire 120', thereby leaving only the softer, smaller diameter wire in place.

[0118] A conventional extension wire W can optionally be attached to the inner wire 20 (or other inner wires described herein) by a friction fit as shown in FIGS. 8 and 9. That is, a recessed portion of female taper of inner wire 20 receives a male tapered distal end W1 of extension wire W.

[0119] It is also contemplated that the outer and intermediate wires could be held in place and the inner wire removed and replaced with another 0.014 inches wire, such as a conventional 0.014 wire currently being used for surgical procedures.

[0120] The aforescribed guidewires of the present invention provide a method of adjusting the stiffness and size of a guidewire without full withdrawal of the guidewire from a patient's vascular system. The use will be described in conjunction with guidewire 10, however it should be appreciated that the description is applicable to the other three components guidewire systems discussed herein.

[0121] In one method of use, the guidewire 10 is advanced into the vascular system from a remote site, such as the femoral artery F (see FIG. 3), with the outer wire 40 and stiffener 30 in the retracted position to expose a substantial length of the inner wire 10 to expose a smaller wire diameter as shown in FIGS. 1 and 4. This provides for increased flexibility of the guidewire system and less trauma to the vessel. Note it is also contemplated that the guidewire is inserted from other sites such as the jugular vein or radial artery.

[0122] After initial advancement of the guidewire 10 through the vascular system en route to the target site such as the carotid artery C (FIG. 3), if a tortuous vessel portion or other anatomy is encountered wherein the inner wire 20 lacks the requisite pushability and stiffness, the outer wire 40 is slid in a distal direction over the inner wire 20, while maintaining the position of the inner wire 20, avoiding the need to remove the inner wire 20 from the patient. This creates a stiffer guidewire to increase the pushability of the guidewire system 10 to enable it to advance through the curved vessel portion (see FIG. 5).

[0123] If during advancement, the outer wire 40 lacks the requisite pushability or stiffness to advance through a tortuous vessel portion or other anatomy, the stiffener 30 can be advanced in a distal direction within the outer wire 40 and over the inner wire 20 to increase the overall stiffness of the guidewire 10, as shown in FIG. 1B.

[0124] After advancing through the tortuous vessel, the stiffener 30 can be withdrawn if desired, leaving the more flexible outer wire 40 for advancement.

[0125] If during advancement of the guidewire 10 with outer wire 40 covering the inner wire 20 a restricted passage in the portion of the vessel is encountered such that the vessel lumen dimension is less than the outer diameter of the outer wire 40, the outer wire 40 can be retracted in a proximal direction to expose a substantial length of the inner wire 20. The smaller diameter inner wire 20 can then be used to advance through the restricted passage of the vessel lumen.

[0126] As can be appreciated, the wires can be slid relative to one another (as defined herein) during the advancement of guidewire 10 to the treatment site any number of times as desired to provide the requisite diameter size, flexibility and stiffness.

[0127] Once the treatment site is reached, the stiffener 30 and outer wire 40 can be slid proximally over the inner wire 20 and removed from the patient, e.g. by removing the interlocking component of the inner member, thereby leaving the inner wire 20 in the patient to function as a rail for over the wire catheter and/or device insertion. Alternatively, the guidewire 10 can remain in place with the larger diameter wire 40 functioning as a rail for over the wire catheter and/or device insertion. In certain embodiments, fluid can be injected through the guidewire.

[0128] Although the method of use was described in relation to guidewire 10, the other guidewires disclosed herein would be advanced in a similar fashion. In the

embodiment with a handle, the handle or torquer would be removed if it was desired to remove the outer wire and stiffener.

[0129] Additionally, the method was described above with the guidewire system initially inserted so the inner wire extends from the outer wire. It is also contemplated that if a larger wire is desired for initial insertion, the guidewire system would be inserted with the inner wire retracted. Then the inner wire can be advanced to be exposed if a smaller size or increased pushability is desired.

[0130] The two component system works in a similar fashion except without a stiffener tube, relying on the interaction of the inner member and outer tube for diameter and stiffness/flexibility adjustment.

[0131] While the above description contains many specifics, those specifics should not be construed as limitations on the scope of the disclosure, but merely as exemplifications of preferred embodiments thereof. For example, one or more of the wires can contain a hydrophilic coating. Those skilled in the art will envision many other possible variations that are within the scope and spirit of the disclosure as defined by the claims appended hereto.

1. A guidewire system, comprising:
 - an inner wire member having a first outer diameter and a first stiffness, and
 - an outer tube member having an inner diameter larger than the first outer diameter of the inner wire member, and a lumen for receiving the inner wire member, the outer tube member further having regions of different flexibility along its length, and a stiffness different than the first stiffness of the inner wire member,
 - the inner wire member and outer tube member being independently slideable and selectively lockable in position relative to one another, the inner wire member and outer tube member together functioning as a unitary guidewire structure for guiding a medical device into a patient,
 - wherein the selective sliding or locking of the inner wire member and the outer tube member in relative position to one another affects the overall rigidity and diameter of the guidewire system such that the desired degree of pushability, flexibility or stiffness is achieved as the system is advanced into the patient.
2. The guidewire system of claim 1, wherein the inner wire member comprises a tip.
3. The guidewire system of claim 2, wherein the tip is integral to the inner wire member.
4. The guidewire system of claim 2, wherein the tip is attached to the inner wire member.
5. The guidewire system of claim 2, wherein the tip is selected from one of a coiled tip, a ball tip, a blunt tip, and a conical tip.
6. The guidewire system of claim 1, wherein the outer tube member comprises a wound wire.
7. The guidewire system of claim 6, wherein the wound wire comprises a rectangular wire.
8. The guidewire system of claim 6, wherein the wound wire comprises a round wire.
9. The guidewire system of claim 1, wherein the outer tube member comprises a polymeric portion.
10. The guidewire system of claim 1, wherein the polymeric portion is at a distal portion of the outer tube member.
11. The guidewire system of claim 9, wherein the polymeric portion comprises a polymeric coating.

12. The guidewire system of claim **11**, wherein the polymeric coating comprises a hydrophilic coating.

13. The guidewire system of claim **9**, wherein the polymeric coating comprises a polytetrafluoroethylene or polyethylene terephthalate coating.

14. The guidewire system of claim **12**, further including a hydrophilic coating on the outer tube member.

15. The guidewire system of claim **13**, wherein the polymeric coating comprises a heat shrink coating of polyethylene terephthalate.

16. The guidewire system of claim **15**, further including a hydrophilic coating on the outer tube member.

* * * * *