



US009877729B2

(12) **United States Patent**
Bowman et al.

(10) **Patent No.:** **US 9,877,729 B2**
(45) **Date of Patent:** **Jan. 30, 2018**

(54) **CATHETER SYSTEM**

(2013.01); *A61B 2017/12063* (2013.01); *A61B 2017/12068* (2013.01); *A61B 2017/12077* (2013.01)

(71) Applicant: **MicroVention, Inc.**, Aliso Viejo, CA (US)

(58) **Field of Classification Search**

CPC .. *A61B 2017/0065*; *A61B 2017/12054*; *A61B 2017/12063*; *A61B 2017/12068*; *A61B 2017/12077*

(72) Inventors: **Heath Bowman**, Trabuco Canyon, CA (US); **Hideo Morita**, Irvine, CA (US); **Greg Bak-Boychuk**, San Clemente, CA (US); **Joseph Gulachenski**, Trabuco Canyon, CA (US); **Arnold Tuason**, Claremont, CA (US); **Stacy Faught**, Aliso Viejo, CA (US)

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **MicroVention, Inc.**, Aliso Viejo, CA (US)

4,655,762 A 4/1987 Rogers
6,146,373 A 11/2000 Cragg et al.
6,511,468 B1 1/2003 Cragg et al.
6,524,274 B1 2/2003 Rosenthal et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 287 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **14/578,020**

EP 1516598 A1 3/2005
EP 2676696 A1 12/2013
(Continued)

(22) Filed: **Dec. 19, 2014**

(65) **Prior Publication Data**

US 2015/0173773 A1 Jun. 25, 2015

Related U.S. Application Data

(60) Provisional application No. 61/919,643, filed on Dec. 20, 2013.

WIPO, U.S. International Search Authority, International Search Report and Written Opinion dated Apr. 20, 2015 in International Patent Application No. PCT/US2014/071677, 10 pages.
(Continued)

(51) **Int. Cl.**

A61M 31/00 (2006.01)
A61M 37/00 (2006.01)
A61B 17/12 (2006.01)
A61B 17/00 (2006.01)

Primary Examiner — Rebecca E Eisenberg

(74) *Attorney, Agent, or Firm* — Inskeep IP Group, Inc.


(52) **U.S. Cl.**

CPC *A61B 17/12186* (2013.01); *A61B 17/0057* (2013.01); *A61B 17/12031* (2013.01); *A61B 17/12109* (2013.01); *A61B 17/00491* (2013.01); *A61B 2017/0065* (2013.01); *A61B 2017/00623* (2013.01); *A61B 2017/12054*

(57) **ABSTRACT**

A catheter with one or more heated or detachable sections is described. The catheter may be useful for liquid embolic delivery, where the heated or detachable sections may help free the catheter when stuck to liquid embolic during delivery. An instrumented catheter is also described.

18 Claims, 21 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,558,367 B1 5/2003 Cragg et al.
 6,964,657 B2 11/2005 Cragg et al.
 7,896,899 B2 3/2011 Patterson et al.
 7,976,527 B2 7/2011 Cragg et al.
 8,016,799 B2 9/2011 Nash et al.
 8,048,104 B2 11/2011 Monstadt et al.
 8,066,732 B2 11/2011 Paul et al.
 8,066,733 B2 11/2011 Paul et al.
 8,267,955 B2 9/2012 Patterson et al.
 8,454,649 B2 6/2013 Cragg et al.
 8,480,701 B2 7/2013 Monstadt
 8,597,321 B2 12/2013 Monstadt et al.
 8,845,676 B2 9/2014 Monstadt et al.
 2003/0040733 A1 2/2003 Cragg et al.
 2003/0225365 A1 12/2003 Greff et al.
 2003/0225391 A1 12/2003 Cragg et al.
 2004/0225279 A1 11/2004 Raymond
 2008/0045922 A1 2/2008 Cragg et al.
 2008/0287982 A1 11/2008 Harreld
 2009/0163780 A1 6/2009 Tieu
 2009/0227976 A1 9/2009 Calabria et al.

2009/0264858 A1 10/2009 Nash et al.
 2010/0049165 A1 2/2010 Sutherland et al.
 2011/0092956 A1 4/2011 Soer et al.
 2011/0264073 A1 10/2011 Cragg et al.
 2011/0319928 A1 12/2011 Griffin et al.
 2012/0157854 A1 6/2012 Kurrus et al.
 2013/0184660 A1 7/2013 Swiss et al.
 2013/0204234 A1 8/2013 Cully
 2013/0211443 A1 8/2013 Cragg et al.
 2013/0338643 A1 12/2013 De Silva
 2014/0039459 A1 2/2014 Folk et al.
 2014/0135737 A1 5/2014 Sutherland et al.

FOREIGN PATENT DOCUMENTS

WO WO2006074060 A2 7/2006
 WO WO2012004165 A1 1/2012

OTHER PUBLICATIONS

Bormashenko, E. et al., "Electrically Controlled Membranes Exploiting Cassie-Wenzel Wetting Transitions," *Scientific Reports*, 3:3028, Oct. 23, 2013, pages 5 pages.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26




Figure 27




Figure 28




Figure 29

Figure 30





Figure 31




Figure 32




Figure 33




Figure 34




Figure 35




Figure 36

1

CATHETER SYSTEM

RELATED APPLICATIONS

This application claims priority to U.S. Provisional Application Ser. No. 61/919,643 filed Dec. 20, 2013 entitled Catheter System, which is hereby incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

Intravascular procedures typically use catheters to deliver a therapeutic agent to the treatment site. Sometimes there may be a danger of the catheter getting stuck at the treatment site. One example is during the delivery of liquid embolic. Liquid embolic can be thought of as a type of biocompatible glue that hardens over time and is used to embolize a particular site within the vasculature. During delivery of the liquid embolic, reflux of the embolic back into the catheter or around the catheter can result in the catheter getting stuck in the vasculature. Thus there is a need for catheters designed with ways to safely and easily extricate the catheter when stuck in the vasculature.

SUMMARY OF THE INVENTION

A catheter with heated or detachable sections is described, where the sections help free the catheter if stuck within embolic material deployed within a patient's vasculature. In one embodiment, a heating device is located at a distal end of the catheter so as to allow a physician to heat the catheter and melt any embolic material that may otherwise be trapping the catheter. In another embodiment, a mechanism is provided to selectively detach a distal end of the catheter, should it become stuck within embolic material deployed within a patient's vasculature.

The present invention contemplates use of any of the embodiments as an embolic delivery catheter, a detachable tip balloon catheter, detachable intrasaccular device, rapid-exchange system that can detach while still on a guidewire, a stent system, a closure device, a neck bridge device, and a coil implant.

In one embodiment, a catheter is disclosed having a heater coil near its distal end.

In one embodiment a catheter includes a conductive trace heater.

In another embodiment a catheter includes a conductive trace heater which is used to melt an adhesive connection to detach a detachable section.

In one embodiment an instrumented catheter utilizes conductive traces as circuit elements which connect to an instrument component along the catheter.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via adhesive. A heater coil in the proximate portion can be activated to melt the adhesive and separate the distal portion from the proximal portion.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via a bond material that can degrade when exposed to liquid. Exposure of the bond material can be controlled by an electrically controlled Cassie-Wenzel wetting transition material, a film that melts when a heater coil is activated, or a hydrogel layer that shrinks when electric current is applied.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion

2

via a plurality of tethers or monofilaments. The tethers can be broken by activating one or more heater coils.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via a plurality of piston members. When a nearby heater is activated, the pistons actuate, thereby unlocking a locking mechanism on the catheter.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via a plurality of tethers of monofilaments. The tethers are connected between two shape-changing components that, when heated, change shape and break the tethers.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via a locking mechanism controlled by a temperature sensitive spring member. When heated, the spring member moves, unlocking the locking mechanism, thereby freeing the distal end portion.

In another embodiment, a catheter is disclosed having a distal end portion connected to a proximal catheter portion via a fuse member. When power is applied to the fuse member, the fuse breaks, thereby freeing the distal end portion.

In another embodiment, a method of using a catheter is contemplated. For example, a catheter can be advanced to a treatment site and embolic material can be deployed from the catheter's distal tip. Should the catheter become stuck in the embolic material, the physician can either activate a heater at a distal end of catheter to partially melt the embolic material or activate a detachment mechanism to detach a distal end of the catheter. Finally, the catheter can be removed from the patient.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a heated catheter system.

FIG. 2 illustrates a proximal part of a heated catheter system.

FIG. 3 illustrates a distal part of a heated catheter system, where the system utilizes a heater placed on the outer surface of a catheter.

FIG. 4 illustrates a distal part of another embodiment of a heated catheter system.

FIGS. 5-6 illustrate a detachable catheter section utilizing an adhesive and a heater.

FIG. 7 illustrates another embodiment of a heated catheter system.

FIG. 8 illustrates another embodiment of a catheter having a detachable tip.

FIG. 9 illustrates another embodiment of a catheter having a detachable tip.

FIGS. 10-13 illustrate various components of the detachment system of the catheter of FIG. 9.

FIG. 14 illustrates another embodiment of a catheter having a detachable tip.

FIG. 15 illustrates a heater coil of the detachment system of FIG. 14.

FIG. 16 illustrates another embodiment of a catheter having a detachable tip.

FIGS. 17-18 illustrate another embodiment of a catheter having a detachable tip.

FIG. 19 illustrates a piston member of the detachment system of the catheter from FIGS. 17-18.

FIG. 20 illustrates another embodiment of a catheter having a detachable tip.

FIGS. 21-22 illustrate cross sectional views of the detachment system of FIG. 20.

3

FIG. 23 illustrates another embodiment of a catheter having a detachable tip.

FIGS. 24-33 illustrate various components of the detachment system from the catheter of FIG. 23.

FIG. 34 illustrates another embodiment of a catheter having a detachable tip.

FIGS. 35-36 illustrate another embodiment of a catheter having a detachable tip.

DESCRIPTION OF EMBODIMENTS

For the purposes of the Figures described, items on the left are generally considered to sit proximal relative to items on the right and items on the right, in turn, are considered to sit distal relative to items on the left.

Several of the embodiments described utilize conductive traces. Conductive traces are conductive fluids which can be traced over a device, and can be thought of as a conductive ink. The conductive trace is comprised of fine metallic powders amalgamated within a polymer binder. The adhesive properties of the polymer binder allow the conductive trace to be deposited onto a variety of surfaces. When the traces are drawn in a path it provides a conductive, current carrying flow path. They can be used to transfer current between a source and a receiver, and can be integrated into a circuit having (for example) a positive and negative voltage source. See U.S. Pat. No. 4,485,387, U.S. Pat. No. 7,224,258, U.S. Pat. No. 7,736,592 which are hereby incorporated by reference in their entirety. Deposition techniques such as micro-pen, pad printing, bubble jet, screening processes, or rolled deposition during catheter extrusion can be used to deposit the conductive traces on the catheter surface.

FIG. 1 shows a heated catheter system including a catheter 2, y-connector hub 4 at the proximal end of the system, and heater 6 at the distal end of the system. The system further includes proximal contact 7 and distal contact 8 which are connected to a voltage source 10 which includes a user interface, such as a button 12. In FIG. 1 proximal contact 7 is shown as having a positive charge (hooked up to the positive terminal of the voltage source) while distal contact 8 is shown as having a negative charge (hooked up to the negative terminal of the voltage source).

In another example, the polarity of the contacts can be reversed (i.e. proximal contact 7 connected to the negative terminal and distal contact 8 connected to the positive terminal). The button 12 can be engaged to heat the heater 6 by sending electrical current to said heater. In an alternate configuration, the voltage source 10 can sit directly over the contacts 7, 8, physically on the catheter 2. In this configuration the controller can include corresponding terminals and circuitry to interact with contacts 7, 8 on the catheter.

FIG. 2 shows a cross sectional view of the proximal end of the system shown in FIG. 1. Catheter 2 is comprised of an inner catheter liner 18 (indicated by the thicker line region) and an outer catheter jacket 20. This inner catheter liner 18 may run through the catheter hub 4 and extends through the rest of the catheter 2. Polymer may be used for both liner 18 and jacket 20, such as PTFE for the inner liner 18 while polyether block amide is used for the outer catheter jacket 20.

The positive terminal of the voltage source connects to proximal contact 7. In one example, proximal contact 7 can be made of a conductive, plated hypotube. This hypotube sits over a conductive trace 16 that runs to the distal portion of the catheter. Conductive trace 16 runs on the inner catheter liner 18. The hypotube can be cemented over the

4

trace, and the cement 14 can be comprised of a conductive epoxy. In one example, as described, the hypotube sits directly over trace 16.

In another example (shown in FIG. 2) the hypotube connects to the trace 16 by the conductive epoxy 14 which acts as a conductive bridge between the two elements. In these configurations the hypotube would sit on the inner catheter layer. In an alternate configuration, a duct can be bore through the outer catheter layer and conductive epoxy can be placed in this duct to provide a current supply between the inner catheter layer and outer catheter jacket. The hypotube can then be placed on the outer catheter surface.

Conductive trace 16 runs along inner liner 18 all the way to the distal portion of the catheter. Distal contact 8 may be formed of a conductive trace fixed over the outer jacket 20 of the catheter 2 and is connected to the negative terminal of the voltage source. As shown in the Figure, part of the conductive trace 9 can form a spiral shape, then extend longitudinally along the length of the catheter 2. In one example, this spiral region is about 1 centimeter in length. Where proximal contact 7 has a positive polarity and distal contact 8 has a negative polarity, trace 16 will act to supply current and trace 9 will act to return current.

FIG. 3 shows the distal part of the catheter 2. Conductive trace 16 is located along the inner catheter liner 18 to the distal portion of the catheter 2. For the configuration shown in FIGS. 2 and 3, conductive trace 16 has a positive charge, thus supplying current (though as mentioned earlier the polarity of contacts 7, 8 could be reversed). Conductive trace heater 6 is located over the outer jacket 20 of the catheter 2 in a spiral shape at the distal part of the catheter. The tight spiral configuration promotes heat generation as current passes through, due to the close travel path of the current through the spiral and the increased resistance through this section.

At the end of the spiral/coiled configuration 6, conductive trace 9 extends longitudinally along the catheter 2. Trace 9 extends proximally back to the distal contact 8 shown in FIG. 2. In one example, the trace width 24 of the windings of the heater 6 can be about 0.002" to 0.005". In one example, the heater length 26 can be about 1 to 2 cm. In one example, a current of at least 200 milliamps is desired for the heater coil 6. Trace width, heater length, and conductive material used in the conductive trace are variables which may affect the heater current. In one example, the heater winding width 24 is thinner than the supply and return trace conductors 9 and 16 so that the resistance of heater 6 will be higher than the resistance of the supply and return trace 9 and 16.

To connect conductive trace 16 and heater 6, a duct 22 is bore through the outer catheter jacket 20. Conductive epoxy can be placed through this duct to connect trace 16 to heater 6, thus providing a current path from trace 16 (which sits on the inner catheter liner 18) to heater 6 (which sits on the outer catheter jacket 20). Where proximal contact 7 is positive and distal contact 8 is negative, the current flows from proximal contact 7 to conductive epoxy 14 to conductive trace 16 all the way to the distal portion of the catheter. The current then flows through the conductive epoxy 14, through duct 22 to heater 6, then through conductive trace 9 and back to the distal contact 8.

A user can initiate heating of heater 6 by pressing the button 12 on voltage source 10 to activate an electric pulse. The current pulse will then travel through the system in the manner just specified. In one example the DC electrical pulse from the controller will have a regulated current output

5

and pulse duration (i.e. between 0.5-3 seconds). In one example the pulse duration is tuned such that the transient heating effect at the surface of the catheter heating element 6 does not exceed about 165 degrees F. In another example an alternating current voltage source is used.

Though a voltage source 10 is described, this device can include a controller system which contains a voltage source and impulse mechanism (button 12). U.S. Pat. No. 8,182,506 and US20060200192, which are hereby incorporated by reference in their entirety, describe implant detachment systems utilizing such a controller. The controllers described in those references may be used in the system/systems described in this document. In one example voltage source 10 can use a 9 Volt battery. In another example one or more 3 Volt batteries can be used. In another example multiple 9 Volt batteries can be used. In another example three 3 Volt batteries can be used. The voltage source may sit proximal of catheter hub 4, as a handheld unit for the user. Alternatively the voltage source may sit just distal of the catheter hub, mounted on the catheter. In this configuration the controller can include corresponding terminals and circuitry to interact with contacts 7, 8 on the catheter.

In another embodiment the heater 6 may be a metallic heater coil. A conductive epoxy may be used to connect the heater coil to the conductive trace 9.

FIG. 4 illustrates an embodiment of a heated catheter system that is generally similar to the previously described embodiment of FIGS. 1-3. The conductive trace 16 is located on the inner catheter layer connects to a metallic heater coil 28, which also is located on the inner catheter layer. In one example, conductive epoxy is used to connect element 16 to coil 28. This coil 28 extends along a distal portion of the catheter. Duct 22 is present at the distal portion of coil 28 and is formed from a passage or bore through the outer jacket 20 of the catheter. Trace 9 is located on the outer surface of the jacket 20 and is connected to the coil 28 by conductive epoxy within duct 22. The current path (assuming trace 16 is connected to a positive terminal and trace 9 to a negative terminal) runs from proximal contact 7 to conductive epoxy 14 to conductive trace 16 to coil 28, all elements being on the inner catheter layer. The current then travels through the conductive epoxy in duct 22 to return trace 9 back to the distal contact 8, where trace 9 and distal contact 8 are located on the outer catheter jacket.

In the embodiments presented above, conductive epoxy is described as a bridging mechanism to provide a conductive path between elements, and/or between elements on different layers of the catheter. Other conductive materials besides epoxy may be used.

The heated catheter embodiments presented in FIGS. 1-4 may be useful for situations where the embolic hardens around the external surface of the catheter, thus trapping the catheter within the vasculature. The heater works to melt the embolic thus allowing the catheter to be freed. The heaters discussed could be utilized at multiple places along the length of the catheter as well.

Generally a solid metallic material (i.e. a heater coil) will have a higher operating temperature than a conductive trace, since the conductive trace can only operate as a heater up to the melting point of the trace. The conductive trace, however, takes up less space on the catheter versus a solid hypotube or coil thus reducing the overall profile of the catheter and reducing the stiffness of said catheter compared to a catheter utilizing a solid metallic material. Thus for the embodiment shown in FIG. 3 where the heater is on the outside of the catheter a conductive trace may be sufficient to melt any embolic stuck on the outside of the catheter. For

6

the embodiment in FIG. 4, where the heater is placed on the inner catheter layer, any heat generated must transfer through the outer catheter layer before it can begin to melt the embolic in contact with the catheter. Thus a heater which can reach a higher temperature (i.e. the metallic heater coil) may be desirable.

Many catheter designs utilize coils to provide structural stability to the catheter as it navigates the vasculature. Thus the heater coil embodiments described herein can be utilized in a catheter already utilizing a coil or metallic layer for structural reinforcement. The various circuitry elements (conductive traces and/or conductive hypotubes and the like) can thus be combined with an existing structural coil element to create a heater coil. Similarly, a heater coil could provide heat as well as structural stability to a catheter.

FIGS. 5-6 show another embodiment of a heated catheter 5 which utilizes a distal, detachable tubular section 30 that fits over the distal end of the main body of the catheter 5 and can be disconnected by activation of heater 6. As the heater is activated, the section 30 expands in diameter, breaking the adhesive 32. Preferably, section 30 is connected to a distal end portion of the catheter 5 via adhesive 32. If the distal, detachable section 30 gets stuck during embolic delivery, it can be detached and left within the embolic material in the patient while the remaining portion of the catheter 5 is removed. In one example, the heater 6 utilizes a conductive trace and reaches to a temperature between about 120-160 degrees F. In one example, a metallic heater coil is used as the heater 6. The adhesive 32 ideally has a relatively low melt temperature (e.g., about 120-160 degrees F.).

Another embodiment contemplated would utilize a metallic heater coil for heater 6. A detachable section 30 is included; however, no adhesive is used. Instead, a shrink tube (e.g., cross-link polyolefin) made of very soft material is placed over the heater coil. In one example the durometer for this shrink tube is less than 30 D. Due to the softness of the material it will conform to the surface of the metallic heater coil, and adhere to the coil especially as the coil generates heat.

Detachable section 30 is preferably has a tubular shape that is initially slightly larger than the catheter's diameter. The section 30 is placed over the shrink tube and preferably has a high degree of shape memory. A high degree of shape memory can be imparted to the detachable section by utilizing a high area draw-down ratio. Draw down ratio is the ratio of the cross sectional area of the extruded plastic melt to the cross section area of the final product. A high draw down ratio means a significant difference between the two areas, meaning the final product (the detachable section) will retain a high degree of shape memory, retained from the higher pre-processed cross sectional area. As the detachable section is heated from the underlying heater coil, the detachable section will return to its expanded preset shape memory shape, thus detaching from the coil and shrink tube. In an alternative configuration, no shrink tube is utilized and the detachable section directly overlies the heater coil.

Elements 9 and 16, as in the previous embodiments, can be made of a conductive trace. In one example, trace 9 is on the inner catheter liner surface and trace 16 is on the outer jacket. In another example both traces sit on the inner catheter liner surface. In another example both traces sit on the outer catheter jacket. In one example, these traces sit external of the outer catheter jacket. In another example, one or more of the traces may run through the catheter. Alternatively, conductive plated hypotubes can be used. Alternately, conductive wires can be used. When the heater generates heat, the generated heat will cause the detachable

section to expand (the inner diameter will expand while the length contracts) until it detaches from the heater and shrink tubing overlying the heater. The shrink tubing stays with the heater due to the softness and conformity of the tubing. When detachable section 30 completely detaches the rest of the catheter can be pulled away, thus leaving detachable section 30 with the embolic mass.

FIG. 7 shows another embodiment of a catheter 11 utilizing a coil 28 that acts as both a structural element and a heater. The conductive traces/circuitry described could be utilized with structural coils to create a heater coil which also promotes structural integrity of the catheter. Conductive traces 34, 36 are located on the inner catheter liner 18. For the purpose of example, trace 34 is the supply current (positively polarized) and trace 36 is the return current (negatively polarized). Return trace 36 is insulated by a non-conductive material 38 on top of the trace 36 for most of its length, but leaves exposed a distal portion of the conductive trace 36. Coil 28 is wound over the inner liner 18 and is connected to trace 34, 36. The outer catheter jacket 20 is positioned over the inner layer 18 and coil 28, and the layers are fused together via application of elevated temperatures and compression. The fusing action serves to interconnect the trace to the coil 28, thus eliminating any need for additional electric interconnections.

The coil 28 can act as a heater due to the connection to the traces which are, in turn, connected to a voltage source. The coil 28, being on the inner layer 18 of the catheter 11, provides both structural stability to the catheter and acts as a heater. If the distal portion of the catheter 11 is stuck to an embolic mass, the heater 28 can be activated melting any liquid embolic at the surface of the catheter 11, thus helping to free the catheter 11.

The metallic heater coils discussed herein, in one example, may be made of a highly electrically resistive material to increase the resistance of current as it travels through the coil, thus increasing the coil temperature. Factors such as the desired temperature range would impact material selection. Temperature is an important factor in material selection since one would want a temperature high enough to melt embolic but not high enough to melt the actual polymeric material used in the catheter.

The embodiments described in FIGS. 2-4 and 7 utilize a heating element heating a portion of the catheter to melt embolic and the requisite circuitry (i.e. conductive traces) that can be used to convey current to the heating element. This technology can be used for a number of similar applications. In another embodiment, the conductive traces may be used to ferry current to a sensor (i.e. a temperature sensors or pressure sensor), where said sensor takes the place of the heating element. The conductive traces as described earlier can be used to provide a current flow path to the sensor. Thus one could create an instrumented catheter that is capable of measuring temperature and/or pressure, which has minimal stiffness due to the conductive trace circuit elements.

Several embodiments described utilize conductive traces as circuitry elements. Different embodiments could utilize various conductive elements (conductive hypotubes, wired circuit elements, etc.) to replace these conductive traces. Alternatively, the various conductive elements (conductive hypotubes, wired circuit elements, etc.) could be used in combination with the conductive trace.

FIG. 8 illustrates another embodiment of a catheter 50 having a detachable tip 58. The catheter 50 includes a detachment joint 52 that connects the proximal portion 59 of the catheter 50 with the distal tip portion 58. The detachment

joint 52 is held together with a bond material 54 that can degrade (chemically or otherwise) when exposed to liquid such as blood, contrast, saline, or other commonly injected interventional fluids. For example, the bond material 54 may include a salt such as NaCl or similar salts that can dissociate into solution when exposed to liquid.

In one example, the bond material 54 can be selectively exposed to liquid via an outer electrically controlled membrane 56. When current is applied via electrical wires 60 and 61, the membrane allows fluid to enter the joint 52, allowing the bond material 54 (e.g., NaCl) to go into solution and the distal tip portion 58 to separate from the proximal catheter portion 59. In one example, the outer membrane 56 operates via the Cassie-Wenzel wetting transitions effect, which is described in Bormashenko, Edward, Roman Pogreb, Sagi Batter, and Doron Aurbach. "Electrically Controlled Membranes Exploiting Cassie-Wenzel Wetting Transitions." *Scientific Reports* 3 (2013), the contents of which are hereby incorporated herein by reference.

In another example, outer membrane portion 56 can be a layer of hydrogel that, when an electric current is passed through via wires 60 and 61, causes the hydrogel to give off fluid itself and shrink. Once sufficiently shrunken, the hydrogel will allow fluid from outside the catheter 50 to enter the joint 52 and degrade the bond material 54. In one embodiment, the hydrogel alone is used. In another embodiment, the hydrogel has a permeable film or layer over it.

In another example, the outer membrane 56 may be a thin film that melts or degrades when current from the electrical wires 60 and 61 are applied to it. For example, this film could be composed of a polymer such as polyurethane or polyolefin with a melting point sufficient to melt via activation of the heater.

In alternate embodiments, the inner surface 55 of the joint 52 could be configured to selectively allow passage of fluid (e.g., saline or contrast) from the inner passage 53 to the bond material 54. This selective passage of fluid can be accomplished via any of the mechanisms discussed with regard to outer member 56, and can be used alone or in addition to the outer membrane 56 (i.e., both membranes can selectively allow passage of fluid).

FIGS. 9-13 illustrate various aspects of a catheter 70 having proximal portion 59 and distal portion 58 that is detachable via joint 72. Generally, the joint 72 includes a plurality of heating elements 74 and 75 attached to the proximal portion 59 of the catheter that, when activated, melt adhesive members 84, thereby releasing the distal portion 58.

As best seen in FIG. 10, the adhesive members 84 are located within a groove 82A of a distal ring 82, which is fixed to the distal catheter portion 58. The heating elements 74 and 75 are also positioned in the groove 82A, such that the adhesive members 84 fix or secure the heating elements 74 and 75 to the distal ring 82, thereby maintaining the distal catheter portion 58 with the proximal catheter portion 59.

In one embodiment, the heating elements 74 and 75 form a plurality of generally rectangular shapes, though a variety of different shapes are possible, such as a single square or a plurality of circular loops.

Electrical current is distributed to each of the heating elements 74 and 75 via a distal conductive ring 80 and a proximal conductive ring 76. At least one heating element 75 includes elongated proximal ends that pass entirely through the rings 76 and 80 (as well as the insulating layer 78 located between the rings 76, 80). One of the ends 75A connects to electrical wire 60, while the other end 75A connects to electrical wire 61, allowing the element 75 to be selectively

supplied with power. One of the elongated proximal ends **75A** is in electrical contact with proximal ring **76**, while being insulated from electrical contact with distal ring **80**. The other proximal end **75A** is in electrical contact with distal ring **80**, while being insulated from electrical contact with proximal ring **76**. In this respect, the ends **75A** provide a path for current to and between the rings **76** and **80**.

The remaining heating elements **74** preferably have a first end **74A** that makes electrical contact with only the distal ring **80** and second end **74B** that makes electrical contact with only the proximal ring **76**. As seen in FIGS. **12** and **13**, this arrangement can be accomplished by the first end **74A** having a relatively small length that permits entry into only one of the apertures **80A** of the distal ring **80**, and the second end **74B** having a relatively long length that extends through aperture **80**, through the apertures of the insulating layer **78**, and into one of the apertures **76A** of the proximal ring **76**. Insulating members **81** can be further located on portions of the second end **74B** located within the aperture **80A** of the distal ring **80**, thereby preventing electrical contact that would otherwise prevent current from flowing completely through the heating element **74**.

FIG. **14** illustrates another embodiment of a catheter **90** with a distal portion **58** that detaches from a proximal portion **59**, via joint **92**. The joint **92** is held together by a plurality of tethers or monofilaments **96** located axially and circumferentially around the wall of the catheter **90**. Each tether **96** is anchored under tension to both the distal portion **58** and the proximal portion **59** via anchors **98**. The anchors can be an adhesive, bonding agent, a distinct element that the tether **96** can be tied to, or similar fastening mechanisms.

The tethers **96** are preferably broken by a resistive heater located near each of the tethers **96**. For example, FIGS. **14** and **15** illustrate a resistive heater ring **94** that is composed of a plurality of coiled portions **94A** connected by adjacent curved regions **94B**, so as to form a ring shape. Each of the coiled portions **94A** are preferably coiled around one of the tether members **96**, so as to allow efficient heat transfer to the tether members **96**. Finally, electric wires **60** and **61** selectively apply current to the ring **94**, causing the coils **94A** to heat up and melt or break the tether members **96** and release the distal portion **58** of the catheter **90** from the proximal portion **59**.

FIG. **16** illustrates another embodiment of a catheter **100** having a tip portion **58** that detaches from a proximal portion **59** via an electrolytic joint **102**. Specifically, the joint **102** preferably contains a proximal ring **104** and a distal ring **106** that are in contact with a middle sacrificial anode ring **108**. Electric wire **60** provides positive current to the ring **104**, while negative current is supplied via fluid from within the catheter **100** or through the patient's blood via an electrode in contact with the patient. The rings **104**, **106** and the middle sacrificial anode ring **108** are selected so as to cause rapid galvanic corrosion of the anode ring **108** (i.e., the anode ring **108** acts as an anode and the rings **104**, **106** act as a cathode). Once the anode ring **108** has sufficiently corroded, the distal portion **58** of the catheter (including ring **106**) disconnect from the proximal portion **59**.

FIGS. **17-19** illustrate another embodiment of a catheter **110** having a tip portion **58** that detaches from a proximal portion **59** via mechanical release mechanism. Specifically, the catheter **110** includes one or more pistons **114** having a pin **116** that moves outward to disengage the mechanical release mechanism. In one example, the mechanical release mechanism includes a hook portion **116A** on the distal end of the pin **116** that can be moved from a latched position (FIG. **17**) to an unlatched position (FIG. **18**). However, it

should be understood that a variety of different latching mechanisms can be used with the piston **114**.

FIG. **19** illustrates one possible embodiment of the piston **114** in which a pressure-resistant housing **122** and cap **120** contain a material **124** that expands when heated. The material **124** can be any wax, oil, or similar material with a high enough coefficient of expansion to cause movement of the piston **114**. In another example, the material **124** can be mercury, ethanol, or other materials with relatively high coefficients of expansion. When the heater coil **112** is activated, it heats up the pistons **114**, causing the material **124** to expand within the housing **122**, thereby pushing the pin **116** at least partially out of the housing **122**.

FIGS. **20-22** illustrate another embodiment of a catheter **130** having a tip portion **58** that detaches from a proximal portion **59** via mechanical release mechanism **132**. Specifically, the release mechanism **132** includes a proximal ring **134** and a distal ring **136** that are positioned against each other and are connected or held together via a plurality of tether members or filaments **138**. As best seen in the cross sectional view of the ring in FIG. **21**, the rings **134** and **136** initially have a generally concave shape relative to each other (e.g., forming a cross sectional oval between each other). However, when the rings **134** and **136** are heated, either by direct application of current to the rings or by an adjacent heater coil, the rings **134** and **136** bend in opposite directions to form convex shapes (FIG. **22**). This shape change generally increases the distance of the ends of the rings from each other, where the tether members **138** are connected, thereby fracturing or breaking the tether members **138** and allowing the distal portion **58** of the catheter **130** to be disconnected from the proximal portion **59**.

In one embodiment, the temperature bending behavior of the rings **134** and **136** can be created by using a bi-metal design (i.e., a first metal on a first side of the rings and a second, different metal on the second sides of the rings). In another embodiment, the bending behavior of the rings **134** and **136** can be created by using a material capable of Martensite/Austenite transitions. For example, the rings **134**, **136** can be composed of Nitinol having a relatively high Austenite finish temperature, such that when current is applied to the rings or a heater coil is activated, the rings **134**, **136** transition to their Austenite phase, thereby changing shape, as well.

FIGS. **23-33** illustrate another embodiment of a catheter **140** having a tip portion **58** that detaches from a proximal portion **59** via mechanical release mechanism **142**. The mechanical release mechanism **142** preferably includes a heat-activated spring member **146** that maintains the mechanism **142** in a locked state during normal, operational temperatures (e.g., body temperature), but changes shape when heated, either by direct application of current or via an adjacent heater coil, to cause the mechanism **142** to unlock, thereby releasing the distal tip portion **58**.

In one embodiment, the temperature bending behavior of the spring member **146** can be created by using a bi-metal design (i.e., a first metal on a first side of the spring member **146** and a second, different metal on the second side of the spring **146**). In another embodiment, the shape-changing behavior of the spring member **146** can be created by using a material capable of Martensite/Austenite transitions. For example, the spring member **146** can be composed of Nitinol having a relatively high Austenite finish temperature, such that when current is applied to the spring or a heater coil is activated, the spring member **146** transitions to its Austenite phase, thereby changing shape, as well.

The spring member **146** of the mechanical release mechanism **142** is located on and around a base portion **150**. The spring member **146** is further anchored in place on the base portion **150** by a first elongated anchor member **146A** at one of its ends, extending into aperture **150A** (best seen in FIG. **26**). The spring member **146** also includes a second elongated anchor member **146B** that extends into an aperture within the locking ring **148** (best seen in FIGS. **27** and **28**). In this respect, the spring member **146** maintains the locking ring **148** in a first rotational position relative to the base portion **150** during normal operating temperatures (e.g., body temperature) and rotates the locking ring **148** when heated (via applied current or heater coil).

The base portion **150**, spring member **146**, and locking ring **148** are all preferably contained within an outer housing member **152**, which helps maintain the axial positions of these members relative to each other. As best seen in FIG. **29**, the outer housing member **152** includes a plurality of apertures **152A** which allow passage of locking pins **144A** on the ring **144**.

As best seen in FIGS. **31-33**, the locking pins **144A** pass through apertures **152A** and into slots **148B** on the locking ring **148**. As best seen in FIG. **33**, one end of each of the slots **148B** include an overhanging portion or lip **148C** that is sized and shaped to engage the distal ends of the pins **144A**. Specifically, the distal ends of the locking pins **144A** have an enlarged diameter relative to the remaining, proximal portions, allowing this distal end to catch on the lip **148C** and therefore prevent withdrawal of the pins **144A**. Preferably, the spring member **146** is configured to maintain the locking ring **148** in a rotational position that maintains the lip **148C** over distal end of the locking pins **144A**.

At the opposite end of the slot **148B** is a ramped surface **148A** which assists in pushing the locking pins **144A** out of the slot **148B**. Specifically, the ramp **148A** is inclined towards the ring **144**, such that as the locking ring **148** rotates, the ramp **148A** pushes the locking pins **144A** axially outward of the housing **152**. In this respect, when the spring member **146** is heated, the locking ring **148** rotates to disengage the locking pins **144A** with the lip **148C** and pushes the pins **144A** outward. Since ring **144** and base portion **150** are each attached to either the proximal portion **59** or distal portion **58** of the catheter **140**, unlocking the mechanism **142** separates the distal portion **58**.

Alternately, rotation of the locking ring **144** of the mechanical release mechanism **142** can be performed via a different mechanism. For example, the piston **114** of FIG. **19** could be fixed to the base **150** or housing **152**, as well as the locking ring **144** so as to rotate the ring **144** when heat activates the piston **114**.

FIG. **34** illustrates another embodiment of a catheter **140** having a tip portion **58** that detaches from a proximal portion **59** via fuse release mechanism **142**. Specifically, the portions **58** and **59** can be held together by one or more (e.g., a plurality) of fuse members **162** located near the circumference of the catheter **160**.

The fuse members **162** are preferably connected to a proximal ring **164** and a distal ring **166**. The proximal ring **164** and/or the proximal end of the fuse members **162** are connected to electrical wire **60**, while the distal ring **166** and the distal end of the fuse members **162** are connected to electrical wire **60**. Preferably, the electrical wire **61** includes a disconnecting portion **167** that separates when the distal portion **58** separates from the proximal portion **59**. For example, the wire **61** can terminate with a first electrode surface that physically presses against a second electrode surface that, in turn, is connected to the remaining wire in

the distal portion **58**. Hence, electrical communication is provided to the ring **166**, but the electrodes provide no retaining force on the distal portion **58**.

Preferably, the fuse member **162** is composed of a material that can be fractured or broken without causing enough heat to damage surrounding tissue in a patient (this breaking value is sometimes referred to as the "clearing I^2t " value). In one example, the fuse can be composed of an elongated hypotube of gold plated polyimide material.

FIGS. **35-36** illustrate another embodiment of a catheter **170** having a tip portion **58** that detaches from a proximal portion **59** via fuse release mechanism **172**. Specifically, the portions **58** and **59** can be held together by one or more (e.g., a plurality) of fuse members **172** located near the circumference of the catheter **170**, generally similar to the previously discussed catheter **140**.

The fuse member **172**, best seen in FIG. **36**, includes a proximal capsule member **174** having a fuse member **180** fixed within an interior lumen and a distal capsule member **176** having a fixed loop **182** its distal end. When assembled, the fuse member **180** is positioned through the loop **182**, locking the two capsule members **176** together.

Preferably, the capsules are composed of or coated with an insulating material, such as ceramic, so as to not conduct current. Current is supplied to the fuse member **180** by two electrical contacts **178**, **179**, which are insert molded in place. Contact **178** is connected to wire **61** and one end of the fuse member **180**, while contact **179** is connected to wire **60** and the other end of the fuse member **180**.

As with other embodiments, when detachment is desired, current is applied to wires **60**, **61**, causing the fuse member **180** to break or fracture. With the loop **182** no longer engaged with the fuse member **176**, the distal tip **58** is disconnected from the proximal catheter portion **59**.

While one fuse member **172** is discussed, it should be understood that a plurality of fuse members **172** could also be used around the inner circumference of the catheter **170**. In such an example, the wires **60**, **61** and each of the electrical contacts **178**, **179** could each connect to a proximal or distal conducting ring (similar to those in catheter **140**).

While the previously described embodiments are described with regard to use as an embolic delivery catheter, these designs can also be used for other purposes. For example, detachable tip balloons, detachable intrasaccular devices, rapid-exchange systems that can detach while still on a guidewire, stent systems, closure devices, neck bridge devices, and coil implants. In this regard, the catheter embodiments of this specification may have a tensile strength of at least 1 pound, a burst pressure of at least 500 psi, and the ability to carry fluid with minimal or no leakage at the tip junction. In one embodiment, the previously described catheters include an internal lumen diameter of about 0.013" and an outer diameter wall of about 0.020", however, the described concepts can be used on larger or smaller sized catheters.

While the previously described embodiments have been depicted as using two relatively straight wires to convey electricity to the distal end of the catheter, it should be understood that other embodiments are possible. For example, current can be carried through a plurality of braided reinforcement wires that extend the length of the catheter. Typically, the metal utilized for the reinforcement braid are either stainless steel or Nitinol, but in this scenario, materials with lower resistance are preferred (e.g., gold, silver, or copper). Additionally, these wires can be formed using a cladding process, such as a copper core having a nickel cladding, a stainless steel core having a gold cladding,

13

or a Nitinol core having a silver cladding. These wires could also have an outer layer of electrical insulation, such as polyimide enamel, parylene, or other suitable substance. These wires may be further grouped into positive and negative bundles, where multiple wires are tied together to increase the current carrying ability and decrease the overall electrical resistance.

It should also be understood that the present invention includes methods of using all of the catheter embodiments described in the present specification and drawings. For example, any of the catheter embodiments can be advanced to a treatment site and embolic material can be deployed from the catheter's distal tip. Should the catheter become stuck in the embolic material, the physician can activate either heat a distal end of catheter to partially melt the embolic material or activate a detachment mechanism to detach a distal end of the catheter. Finally, the catheter can be removed from the patient.

What is claimed is:

1. A catheter comprising:
 - a proximal portion;
 - a distal portion; and,
 - a detachment mechanism coupled to a distal end of said proximal portion and a proximal end of said distal portion; said detachment mechanism being selectively activated by a user to release said distal portion from engagement with said proximal portion; the detachment mechanism further comprising one or more heating elements extending from said proximal portion and positioned within a proximally-facing groove of a first ring on said distal portion.
2. The catheter of claim 1, wherein said detachment mechanism comprises:
 - an adhesive fixed to said first ring and said one or more heating elements.
3. The catheter of claim 2, wherein said one or more heating elements are rectangular shaped.
4. The catheter of claim 1, further comprising a second ring and a third ring; said second ring being in electrical contact with a first end of each of said one or more heating elements and said third ring being in electrical contact with a second end of each of said one or more heating elements.
5. The catheter of claim 1 wherein said one or more heating elements are connected to a current supply via a trace path formed via conductive epoxy.
6. The catheter of claim 1, wherein said one or more heating elements are a single, spiral heater coil.
7. A catheter comprising:
 - a proximal portion;
 - a distal portion; and,
 - a detachment mechanism comprising one or more heating elements fixed at a distal end of said proximal portion and extending into a proximally-facing groove of a first ring located on said distal portion; said proximally-facing groove containing heat-melting adhesives maintaining said one or more heating elements within said proximally-facing groove;
 wherein said detachment mechanism is selectively activated by a user to melt said adhesives and release said distal portion from engagement with said proximal portion.
8. The catheter of claim 7, wherein said one or more heating elements are a plurality of heating elements.
9. The catheter of claim 8, further comprising a distal conductive ring and a proximal conductive ring, both of which are selectively supplied with electrical current; wherein each of said plurality of heating elements are

14

electrically connected to said distal conductive ring and to said proximal conductive ring.

10. The catheter of claim 9, wherein said proximally-facing groove extends circumferentially around said distal portion.

11. The catheter of claim 7, wherein said one or more heating elements are disposed circumferentially around said proximal portion.

12. The catheter of claim 7, wherein said one or more heating elements form a plurality of generally rectangular shapes.

13. The catheter of claim 9, wherein one of said plurality of heating elements is connected to a first electrical wire and to a second electrical wire, such that said one of said plurality of heating elements supplies current to said distal conductive ring and to said proximal conductive ring.

14. A method of operating a catheter, comprising:

activating a detachment system connecting a proximal portion of a catheter with a distal portion of said catheter by energizing one or more heating elements located near a distal end of said proximal portion of said catheter, so as to melt adhesive located in a proximally-facing groove and connecting said distal portion of said catheter to said proximal portion of said catheter; and,

allowing said one or more heating elements to move out of said proximally-facing groove, thereby separating said distal portion of said catheter from said proximal portion of said catheter.

15. The method of claim 14, wherein said proximally-facing groove is further located in a distal ring fixed to said proximal portion of said catheter.

16. A catheter comprising:

a proximal portion;

a distal portion; and,

a detachment mechanism comprising a first ring, a second ring, a third ring, a plurality of heating elements positioned within a groove of said first ring, and an adhesive fixed to said ring and said plurality of heating elements;

wherein said second ring is in electrical contact with a first end of each of said heating elements and said third ring being in electrical contact with a second end of each of said heating elements;

wherein said detachment mechanism being coupled to a distal end of said proximal portion of said catheter and a proximal end of said distal portion of said catheter; said detachment mechanism being selectively activated by a user to release said distal portion from engagement with said proximal portion.

17. A catheter comprising:

a proximal portion;

a distal portion; and,

a detachment mechanism coupled to a distal end of said proximal portion and a proximal end of said distal portion; said detachment mechanism comprising an adhesive connecting said distal portion of said catheter to said proximal portion of said catheter, and one or more heating elements located near said distal end of said proximal portion of said catheter;

wherein said detachment mechanism is selectively activated by a user to release said distal portion from engagement with said proximal portion;

wherein said one or more heating elements are a plurality of heating elements; and,

further comprising a distal conductive ring and a proximal conductive ring, both of which are selectively supplied

with electrical current; wherein each of said plurality of heating elements are electrically connected to said distal conductive ring and to said proximal conductive ring.

18. A catheter comprising: 5
a proximal portion;
a distal portion; and,
a detachment mechanism coupled to a distal end of said proximal portion and a proximal end of said distal portion; said detachment mechanism comprising an adhesive connecting said distal portion of said catheter to said proximal portion of said catheter, and one or more heating elements located near said distal end of said proximal portion of said catheter; 10
wherein said detachment mechanism is selectively activated by a user to release said distal portion from engagement with said proximal portion; 15
wherein said adhesive further comprises a plurality of adhesive members located in proximity to said one or more heating elements. 20

* * * * *