
G. SCROGGIE. OLOTHES DRIER. APPLICATION FILED APR. 18, 1910.

975,575.

Patented Nov. 15, 1910.



WITNESSES: Claud J. Davinfort. Mary a. Bowman.

INVENTOR
GEOTGE SCROGGIE
BY

A.B.BOWMAN
ATTORNEY

UNITED STATES PATENT OFFICE.

GEORGE SCROGGIE, OF SAN DIEGO, CALIFORNIA.

CLOTHES-DRIER.

975,575.

Specification of Letters Patent. Patented Nov. 15, 1910.

Application filed April 18, 1910. Serial No. 556,227.

To all whom it may concern:

Be it known that I, George Scroggie, a citizen of Canada, and a resident of San Diego, in the county of San Diego, State of California, have invented certain new and useful Improvements in Clothes-Driers; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to the figures of reference marked thereon, which form a part of this specification.

My invention relates to clothes driers adapted for attachment to the sides and more particularly near the top of windows, doors, porches or any convenient places.

The objects of the invention are to provide a simple, durable, comparatively inexpensive device of the character described which may be lowered to a position convenient to hang the clothes on and then raised to a position out of the way.

With these and other objects in view, the invention consists of certain novel features of construction, combination and the arrangements of parts hereinafter described and particularly set forth in the appended

30 claims.
In the accompanying drawings, Figure 1 is a plan view of my improved clothes drier complete, shown attached to the top of a window, Fig. 2 is a side elevational view
35 thereof and showing a lowered position of the reel of the drier in dotted lines and Fig. 3 shows a detailed side view of the connection for the two sections of the reel

Similar characters of reference refer to

40

similar parts throughout the several views.

In the drawings 1 and 2 represent horizontal supports, which are attached to the building over a window, door or other convenient place, by means of a tie piece 3 which in turn is bolted to the building. These supports 1 and 2 are provided with braces 4, connected near the outward extending end of said supports and extending upward connecting with the building some distance above said supports. Between these supports 1 and 2 is pivoted on the extended end of said supports by means of bolts 1^a and 2^a, a swinging frame 11 which is centrally pivoted on said supports 1 and

2 and provided with a cross piece on its inner end 11a and in its outer end with a cross piece 5 and centrally pivoted on said cross piece 5 is a reel 6 which is composed of a plurality of arms. On said reel is provided clothes lines 6b. This reel is made in two sections, the outside section being marked 7, said outside section is made so that it may be readily removed from the inner section leaving the reel smaller when 65 desired and is connected to the inner portion 6 by means of a hook piece 6° attached to arm 6a and eye piece 7a which is attached to the outside arm 7b, the eye piece 7a being hooked over hook 6° and the two surfaces of 70 the arm coming in contact, holds them in the position shown in Figs. 1 and 3. This reel is adapted to revolve in piece 5 and is held in a horizontal plane by means of arms 8 and 9, arm 9 being rigidly attached to the 75 cross piece 5 and is pivotally connected to arm 8, which in turn is pivoted to the lower side of the cross piece 10, which is attached to the lower side of supports 1 and 2. In the inner end of swinging frame 11 is a cross 80 piece 11^a to which is attached a cable and extending through piece 3 centrally, then to the side of the window and downward and on the side of the window is provided a hook 12 for attaching said cable at any 85 desired position.

It will be readily seen, that with this con-

It will be readily seen, that with this construction this reel may be lowered to position as shown best in dotted lines in Fig. 2 and where the clothes may be conveniently placed on said reel, then by the use of the cable the reel containing the clothes may be raised to the position shown by solid lines in Fig. 2 and fastened there by means of the hook 12 and that the reel may be easily re 95

duced in size when desired.

Having thus described my invention, what I claim as new and desire to secure by Letters Patent is:

1. A clothes drier, comprising main supports, a swinging frame pivotally mounted thereon, a clothes reel vertically and horizontally pivoted on said frame, double arms attached to the main supports and to the reel pivot piece, all substantially as set 105 forth.

2. A clothes drier, comprising a supporting frame, another frame centrally pivoted thereon, a cross piece pivoted in the outer extending ends of said last mentioned 110

frame, a clothes reel pivoted vertically thereon, double arm means for holding said reel in a horizontal position at all times, a cable attached to the inward extending end of the pivoted frame extending downward and adapted to be attached to a hook, all substantially as set forth.

In witness whereof, I affix my signature in the presence of two subscribing witnesses.

GEORGE SCROGGIE.

Witnesses:

CLAUD T. DAVENPORT, MARY A. BOWMAN.