



US011441332B2

(12) **United States Patent**
Johnson et al.

(10) **Patent No.:** **US 11,441,332 B2**
(45) **Date of Patent:** **Sep. 13, 2022**

(54) **MESH OF CAMERAS COMMUNICATING WITH EACH OTHER TO FOLLOW A DELIVERY AGENT WITHIN A DWELLING**

(71) Applicant: **August Home, Inc.**, San Francisco, CA (US)

(72) Inventors: **Jason Johnson**, San Francisco, CA (US); **Herve Jacques Clement Letourneur**, San Francisco, CA (US); **Tejash Unadkat**, San Francisco, CA (US); **Christopher Dow**, San Francisco, CA (US)

(73) Assignee: **August Home, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/867,773**

(22) Filed: **Jan. 11, 2018**

(65) **Prior Publication Data**
US 2018/0135336 A1 May 17, 2018

Related U.S. Application Data

(63) Continuation-in-part of application No. 15/798,425, filed on Oct. 31, 2017, now Pat. No. 11,072,945, and (Continued)

(51) **Int. Cl.**
E05B 47/00 (2006.01)
H04N 7/18 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **E05B 47/0012** (2013.01); **E05B 47/00** (2013.01); **E05B 47/0001** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC E05B 47/0012; H04N 7/181; H04N 7/188; H04N 7/186; H04N 5/265; G07C 9/00309; G08B 13/1966; G08B 13/19697
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

2,680,177 A 6/1954 Rosenthal
3,898,976 A 8/1975 Coffman, Jr.
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2014236999 A1 10/2015
CA 2676196 7/2008
(Continued)


OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No. PCT/US2014/026254, dated Nov. 18, 2014.
(Continued)

Primary Examiner — Rowina J Cattungal
(74) *Attorney, Agent, or Firm* — Wolf, Greenfield & Sacks, P.C.

(57) **ABSTRACT**
An intelligent door lock system is coupled to a door at a dwelling. A door status device is at the dwelling. The door status device is coupled to a drive shaft of a lock device to assist in locking and unlocking a lock of a lock device at the door. The lock device is coupled to the door status device and includes a bolt. An engine, an energy source and a memory are coupled together. A plurality of cameras that communicate with each other and with the lock device.

26 Claims, 65 Drawing Sheets



Related U.S. Application Data

a continuation-in-part of application No. 15/497,327, filed on Apr. 26, 2017, now abandoned, said application No. 15/798,425 is a continuation-in-part of application No. 15/497,383, filed on Apr. 26, 2017, now Pat. No. 10,691,953, said application No. 15/497,327 is a continuation-in-part of application No. 15/463,022, filed on Mar. 20, 2017, now Pat. No. 11,043,055, which is a continuation-in-part of application No. 15/410,845, filed on Jan. 20, 2017, now Pat. No. 9,916,746, which is a continuation of application No. 15/066,210, filed on Mar. 10, 2016, now Pat. No. 9,644,399, which is a continuation-in-part of application No. 15/066,091, filed on Mar. 10, 2016, now Pat. No. 10,993,111, and a continuation-in-part of application No. 15/065,657, filed on Mar. 9, 2016, now Pat. No. 9,652,917, which is a continuation-in-part of application No. 14/796,994, filed on Jul. 10, 2015, now Pat. No. 9,922,481, said application No. 15/066,210 is a continuation-in-part of application No. 14/796,994, filed on Jul. 10, 2015, now Pat. No. 9,922,481, said application No. 15/065,657 is a continuation-in-part of application No. 14/732,290, filed on Jun. 5, 2015, now Pat. No. 9,818,247, said application No. 15/066,210 is a continuation-in-part of application No. 14/732,290, filed on Jun. 5, 2015, now Pat. No. 9,818,247, said application No. 15/065,657 is a continuation of application No. 14/730,848, filed on Jun. 4, 2015, now Pat. No. 10,140,828, and a continuation-in-part of application No. 14/731,092, filed on Jun. 4, 2015, now abandoned, said application No. 15/066,210 is a continuation-in-part of application No. 14/622,578, filed on Feb. 13, 2015, now Pat. No. 9,530,262, said application No. 15/065,657 is a continuation-in-part of application No. 14/622,054, filed on Feb. 13, 2015, now Pat. No. 9,613,476, and a continuation-in-part of application No. 14/622,654, filed on Feb. 13, 2015, now Pat. No. 9,530,295, and a continuation-in-part of application No. 14/622,396, filed on Feb. 13, 2015, now Pat. No. 10,198,884, said application No. 15/066,210 is a continuation-in-part of application No. 14/622,654, filed on Feb. 13, 2015, now Pat. No. 9,530,295, and a continuation-in-part of application No. 14/622,054, filed on Feb. 13, 2015, now Pat. No. 9,613,476, said application No. 15/065,657 is a continuation-in-part of application No. 14/622,192, filed on Feb. 13, 2015, now Pat. No. 9,728,023, said application No. 15/066,210 is a continuation-in-part of application No. 14/622,192, filed on Feb. 13, 2015, now Pat. No. 9,728,023, and a continuation-in-part of application No. 14/471,470, filed on Aug. 28, 2014, now Pat. No. 9,704,314, said application No. 15/065,657 is a continuation-in-part of application No. 14/471,414, filed on Aug. 28, 2014, now Pat. No. 9,706,365, and a continuation-in-part of application No. 14/471,470, filed on Aug. 28, 2014, now Pat. No. 9,704,314, and a continuation-in-part of application No. 14/469,186, filed on Aug. 26, 2014, now Pat. No. 9,528,294, which is a continuation-in-part of application No. 14/469,127, filed on Aug. 26, 2014, now Pat. No. 9,574,372, application No. 15/066,210, which is a continuation-in-part of application No. 14/469,186, filed on Aug. 26, 2014, now Pat. No. 9,528,294, said application No. 15/065,657 is a continuation-in-part of application No. 14/465,

527, filed on Aug. 21, 2014, now Pat. No. 9,695,616, said application No. 15/066,210 is a continuation-in-part of application No. 14/465,513, filed on Aug. 21, 2014, now Pat. No. 9,447,609, which is a continuation-in-part of application No. 14/465,527, filed on Aug. 21, 2014, now Pat. No. 9,695,616, said application No. 15/065,657 is a continuation-in-part of application No. 14/465,513, filed on Aug. 21, 2014, now Pat. No. 9,447,609, said application No. 15/463,022 is a continuation-in-part of application No. 14/461,117, filed on Aug. 15, 2014, now abandoned, and a continuation-in-part of application No. 14/459,054, filed on Aug. 13, 2014, now Pat. No. 9,382,739, said application No. 15/066,210 is a continuation-in-part of application No. 14/321,000, filed on Jul. 1, 2014, now Pat. No. 9,725,927, said application No. 15/065,657 is a continuation-in-part of application No. 14/321,260, filed on Jul. 1, 2014, now Pat. No. 9,359,794, and a continuation-in-part of application No. 14/321,000, filed on Jul. 1, 2014, now Pat. No. 9,725,927, said application No. 15/066,210 is a continuation-in-part of application No. 14/321,260, filed on Jul. 1, 2014, now Pat. No. 9,359,794, and a continuation-in-part of application No. 14/308,848, filed on Jun. 19, 2014, now abandoned, and a continuation-in-part of application No. 14/212,569, filed on Mar. 14, 2014, now Pat. No. 9,322,201, said application No. 15/065,657 is a continuation of application No. 14/212,569, filed on Mar. 14, 2014, now Pat. No. 9,322,201, and a continuation of application No. 14/207,833, filed on Mar. 13, 2014, now Pat. No. 9,470,017, and a continuation of application No. 14/207,882, filed on Mar. 13, 2014, now Pat. No. 9,683,392, and a continuation of application No. 14/208,182, filed on Mar. 13, 2014, now Pat. No. 9,534,420, said application No. 15/066,210 is a continuation of application No. 14/208,182, filed on Mar. 13, 2014, now Pat. No. 9,534,420, and a continuation of application No. 14/207,833, filed on Mar. 13, 2014, now Pat. No. 9,470,017, and a continuation of application No. 14/208,947, filed on Mar. 13, 2014, now Pat. No. 9,644,400, said application No. 15/065,657 is a continuation of application No. 14/208,947, filed on Mar. 13, 2014, now Pat. No. 9,644,400, said application No. 15/066,210 is a continuation of application No. 14/207,882, filed on Mar. 13, 2014, now Pat. No. 9,683,392, said application No. 15/065,657 is a continuation of application No. 14/205,783, filed on Mar. 12, 2014, now Pat. No. 9,528,296, and a continuation of application No. 14/206,536, filed on Mar. 12, 2014, now Pat. No. 9,470,018, said application No. 15/066,210 is a continuation of application No. 14/205,973, filed on Mar. 12, 2014, now Pat. No. 9,644,398, and a continuation of application No. 14/206,619, filed on Mar. 12, 2014, now Pat. No. 9,624,695, said application No. 15/065,657 is a continuation of application No. 14/205,608, filed on Mar. 12, 2014, now Pat. No. 9,322,194, said application No. 15/066,210 is a continuation of application No. 14/206,536, filed on Mar. 12, 2014, now Pat. No. 9,470,018, said application No. 15/065,657 is a continuation of application No. 14/205,973, filed on Mar. 12, 2014, now Pat. No. 9,644,398, and a continuation of application No. 14/206,619, filed on Mar. 12, 2014, now Pat. No. 9,624,695, said application No. 15/066,

210 is a continuation of application No. 14/205,608, filed on Mar. 12, 2014, now Pat. No. 9,322,194.

(60) Provisional application No. 62/036,971, filed on Aug. 13, 2014, provisional application No. 62/481,797, filed on Apr. 5, 2017, provisional application No. 62/036,989, filed on Aug. 13, 2014, provisional application No. 62/036,991, filed on Aug. 13, 2014, provisional application No. 62/036,979, filed on Aug. 13, 2014, provisional application No. 62/036,993, filed on Aug. 13, 2014, provisional application No. 61/801,294, filed on Mar. 15, 2013, provisional application No. 61/800,937, filed on Mar. 15, 2013, provisional application No. 61/801,335, filed on Mar. 15, 2013.

(51) **Int. Cl.**
E05C 1/00 (2006.01)
E05B 55/12 (2006.01)
G08B 13/196 (2006.01)
G08B 29/18 (2006.01)
G07C 9/00 (2020.01)
E05B 47/02 (2006.01)
G08B 3/10 (2006.01)
E05B 45/06 (2006.01)
E05B 43/00 (2006.01)

(52) **U.S. Cl.**
 CPC *E05B 47/026* (2013.01); *E05B 55/12* (2013.01); *E05C 1/004* (2013.01); *G07C 9/00309* (2013.01); *G07C 9/00944* (2013.01); *G08B 3/10* (2013.01); *G08B 13/19695* (2013.01); *G08B 29/185* (2013.01); *H04N 7/181* (2013.01); *H04N 7/186* (2013.01); *E05B 43/005* (2013.01); *E05B 45/06* (2013.01); *E05B 2045/069* (2013.01); *E05B 2047/002* (2013.01); *E05B 2047/0022* (2013.01); *E05B 2047/0048* (2013.01); *E05B 2047/0058* (2013.01); *E05B 2047/0068* (2013.01); *E05B 2047/0069* (2013.01); *E05B 2047/0072* (2013.01); *E05B 2047/0091* (2013.01); *E05B 2047/0095* (2013.01); *E05B 2047/0097* (2013.01); *G07C 9/00904* (2013.01); *G07C 2009/00769* (2013.01); *G07C 2209/62* (2013.01); *G08B 13/19656* (2013.01); *Y10T 292/1021* (2015.04)

(56) **References Cited**
 U.S. PATENT DOCUMENTS

5,245,329	A	9/1993	Gokcebay	6,418,764	B1	7/2002	Lerchner
5,306,407	A	4/1994	Hauzer et al.	6,422,457	B1	7/2002	Frich et al.
5,407,035	A	4/1995	Cole et al.	6,568,726	B1	5/2003	Caspi
5,594,430	A	1/1997	Swindler et al.	6,570,557	B1	5/2003	Westerman et al.
5,695,048	A	12/1997	Tseng	6,580,871	B1	6/2003	Proidl
5,712,626	A	1/1998	Andreou	6,612,415	B2	9/2003	Yamane
5,717,379	A	2/1998	Peters	6,624,739	B1	9/2003	Stobbe
5,774,058	A	6/1998	Henry	6,677,932	B1	1/2004	Westerman et al.
5,903,225	A	5/1999	Schmitt	6,729,169	B2	5/2004	Moore
5,933,086	A	8/1999	Tischendorf	6,891,479	B1	5/2005	Eccleston
5,979,199	A	11/1999	Elpern	6,910,301	B2	6/2005	Kalempa et al.
6,032,500	A	3/2000	Collard, Jr.	6,961,763	B1	11/2005	Wang et al.
6,089,058	A	7/2000	Elpern et al.	6,967,562	B2	11/2005	Menard et al.
6,196,936	B1	3/2001	Meckel	6,972,660	B1	12/2005	Montgomery, Jr.
6,215,781	B1	4/2001	Kato	7,127,083	B2	10/2006	Han et al.
6,282,931	B1	9/2001	Padiak	7,248,836	B2	7/2007	Taylor
6,323,846	B1	11/2001	Westerman et al.	7,252,311	B2	8/2007	Pratt et al.
6,334,636	B1	1/2002	Huang et al.	7,351,910	B1	4/2008	Magisano et al.
6,360,573	B1	3/2002	Ming-Chih	7,373,795	B2	5/2008	Kilbourne
6,407,520	B1	6/2002	Kleefeldt et al.	7,420,456	B2	9/2008	Fisher
				7,439,850	B2	10/2008	Boulard
				7,520,152	B2	4/2009	Sabo et al.
				7,614,008	B2	11/2009	Ording
				7,633,076	B2	12/2009	Huppi et al.
				7,643,056	B2	1/2010	Silsby
				7,653,883	B2	1/2010	Hotelling et al.
				7,657,849	B2	2/2010	Chaudhri et al.
				7,663,607	B2	2/2010	Hotelling et al.
				7,734,249	B1	6/2010	Mitchell, Jr.
				7,810,852	B2	10/2010	Alacqua
				7,844,914	B2	11/2010	Andre et al.
				7,891,222	B2	2/2011	Ratkus
				8,006,002	B2	8/2011	Kalayjian et al.
				8,019,353	B1	9/2011	Smithey
				8,024,186	B1	9/2011	De Bonet
				8,035,478	B2	10/2011	Lee
				8,122,645	B2	2/2012	Theile
				8,239,784	B2	8/2012	Hotelling et al.
				8,269,627	B2	9/2012	Gore et al.
				8,279,180	B2	10/2012	Hotelling et al.
				8,310,365	B2	11/2012	Siegler, II
				8,325,039	B2	12/2012	Picard et al.
				8,347,720	B2	1/2013	De Los Santos et al.
				8,351,789	B2	1/2013	Wagener et al.
				8,405,387	B2	3/2013	Novak et al.
				8,445,779	B1	5/2013	Gretz
				8,476,577	B2	7/2013	Nagahama et al.
				8,479,122	B2	7/2013	Hotelling et al.
				8,498,572	B1	7/2013	Schooley et al.
				8,522,596	B2	9/2013	Avery
				8,525,102	B2	9/2013	Augustyniak et al.
				8,533,144	B1	9/2013	Reeser et al.
				8,542,189	B2	9/2013	Milne et al.
				8,544,326	B2	10/2013	Je
				8,586,902	B2	11/2013	Verfuert
				8,600,430	B2	12/2013	Herz et al.
				8,653,982	B2	2/2014	Yulkowski
				8,671,723	B2	3/2014	Dayannikli
				8,826,708	B2	9/2014	Lopes
				8,864,049	B2	10/2014	Nolte
				8,872,915	B1	10/2014	Scalisi et al.
				8,896,416	B1	11/2014	Lundy et al.
				8,918,208	B1	12/2014	Hickman
				9,000,916	B2	4/2015	Meeker
				9,024,759	B2	5/2015	Uyeda
				9,049,352	B2	6/2015	Scalisi et al.
				9,057,210	B2	6/2015	Dumas et al.
				9,113,051	B1	8/2015	Scalisi
				9,187,929	B2	11/2015	Webb
				9,222,282	B2	12/2015	Russo
				9,251,679	B2	2/2016	Wandel
				9,322,194	B2	4/2016	Cheng et al.
				9,322,201	B1	4/2016	Cheng et al.
				9,326,094	B2	4/2016	Johnson et al.
				9,359,794	B2	6/2016	Cheng
				9,382,739	B1	7/2016	Johnson et al.
				9,396,598	B2	7/2016	Daniel-wayman
				9,447,609	B2	9/2016	Johnson
				9,454,893	B1	9/2016	Warren

(56)

References Cited

U.S. PATENT DOCUMENTS

9,470,017	B1	10/2016	Cheng	2007/0056338	A1	3/2007	Sabo
9,470,018	B1	10/2016	Cheng et al.	2007/0090843	A1	4/2007	De Doncker et al.
9,514,585	B2	12/2016	Ahearn	2007/0132849	A1	6/2007	Hill et al.
9,528,294	B2	12/2016	Johnson et al.	2007/0150842	A1	6/2007	Chaudhri et al.
9,528,296	B1	12/2016	Cheng et al.	2007/0188307	A1	8/2007	Lai
9,530,262	B2	12/2016	Johnson	2007/0229350	A1	10/2007	Scalisi
9,530,295	B2	12/2016	Johnson	2007/0246396	A1	10/2007	Brollier
9,534,420	B1	1/2017	Cheng et al.	2008/0011032	A1	1/2008	Groff
9,574,372	B2	2/2017	Johnson	2008/0055241	A1	3/2008	Goldenberg
9,613,476	B2	4/2017	Johnson	2008/0101654	A1	5/2008	Sano
9,624,695	B1	4/2017	Cheng et al.	2008/0125965	A1	5/2008	Carani et al.
9,640,053	B2	5/2017	Siann	2008/0129498	A1	6/2008	Howarter
9,644,398	B1	5/2017	Cheng et al.	2008/0211775	A1	9/2008	Hotelling
9,644,399	B2	5/2017	Johnson et al.	2008/0223093	A1	9/2008	Amir
9,644,400	B1	5/2017	Cheng et al.	2008/0236214	A1	10/2008	Han
9,647,996	B2	5/2017	Johnson et al.	2008/0238669	A1	10/2008	Linford
9,652,917	B2	5/2017	Johnson et al.	2008/0297602	A1	12/2008	Chang
9,683,391	B2	6/2017	Johnson et al.	2008/0309624	A1	12/2008	Hotelling
9,683,392	B1	6/2017	Cheng et al.	2009/0029672	A1	1/2009	Manz
9,685,015	B2	6/2017	Johnson	2009/0066320	A1	3/2009	Posey
9,685,017	B2	6/2017	Johnson	2009/0085878	A1	4/2009	Heubel
9,685,018	B2	6/2017	Johnson	2009/0128329	A1	5/2009	Sato
9,691,198	B2	6/2017	Cheng et al.	2009/0180933	A1	7/2009	Kauling
9,695,616	B2	7/2017	Johnson et al.	2009/0217596	A1	9/2009	Neundorf
9,704,314	B2	7/2017	Johnson et al.	2009/0250552	A1	10/2009	Kearns
9,704,320	B2	7/2017	Johnson et al.	2009/0256676	A1	10/2009	Piccirillo
9,706,365	B2	7/2017	Johnson et al.	2009/0267732	A1	10/2009	Chauvin
9,725,927	B1	8/2017	Cheng	2009/0273438	A1	11/2009	Sultan
9,727,328	B2	8/2017	Johnson	2010/0000750	A1	1/2010	Andel
9,728,023	B2	8/2017	Johnson	2010/0070281	A1	3/2010	Conkie
9,761,073	B2	9/2017	Cheng et al.	2010/0089109	A1	4/2010	Bliding et al.
9,761,074	B2	9/2017	Cheng et al.	2010/0127517	A1	5/2010	Bliding et al.
9,767,632	B2	9/2017	Johnson	2010/0141381	A1	6/2010	Bliding et al.
9,769,435	B2	9/2017	Scalisi et al.	2010/0141762	A1	6/2010	Siann
9,818,247	B2	11/2017	Johnson	2010/0145164	A1	6/2010	Howell
9,916,746	B2	3/2018	Johnson et al.	2010/0156809	A1	6/2010	Nutaro
9,922,481	B2	3/2018	Johnson et al.	2010/0283579	A1	11/2010	Kraus et al.
10,017,963	B2	7/2018	Johnson et al.	2010/0306549	A1	12/2010	Ullmann
10,140,828	B2	11/2018	Johnson et al.	2011/0148631	A1	1/2011	Lanham et al.
10,181,232	B2	1/2019	Cheng et al.	2011/0056253	A1	3/2011	Greiner
10,198,884	B2	2/2019	Johnson	2011/0082634	A1	4/2011	Povirk
10,306,129	B1*	5/2019	Bentley H04N 5/23206	2011/0090334	A1	4/2011	Hicks, III et al.
10,672,238	B2	6/2020	Thomas et al.	2011/0100076	A1	5/2011	Weinstein
2002/0015024	A1	2/2002	Westerman et al.	2011/0109678	A1	5/2011	Schwartz et al.
2002/0099945	A1	7/2002	McLintock et al.	2011/0134243	A1	6/2011	Siann et al.
2002/0117868	A1	8/2002	Bates	2011/0148575	A1	6/2011	Sobecki
2002/0138767	A1	9/2002	Hamid	2011/0154740	A1	6/2011	Matsumoto et al.
2002/0196771	A1	12/2002	Vij et al.	2011/0185554	A1	8/2011	Huang et al.
2003/0160681	A1	8/2003	Menard	2011/0215597	A1	9/2011	Weum
2003/0167693	A1	9/2003	Mainini	2011/0265528	A1	11/2011	Saari
2004/0003257	A1	1/2004	Mitchell	2011/0276207	A1	11/2011	Falkenstein
2004/0012352	A1	1/2004	Kachouh	2011/0277520	A1	11/2011	Nunuparov
2004/0075532	A1	4/2004	Ueda	2011/0285501	A1	11/2011	Chen
2004/0212678	A1	10/2004	Cooper	2011/0316697	A1*	12/2011	Krahnstoever H04N 7/181 340/540
2004/0215910	A1	10/2004	Okaue	2012/0011905	A1	1/2012	Gui
2004/0236918	A1	11/2004	Okaue	2012/0068817	A1	3/2012	Fisher
2004/0237609	A1	12/2004	Hosselet	2012/0073482	A1	3/2012	Meeker
2004/0243779	A1	12/2004	Okaue	2012/0092502	A1	4/2012	Knasel
2005/0007451	A1	1/2005	Chiang	2012/0199374	A1	8/2012	Herth
2005/0029345	A1	2/2005	Waterhouse	2012/0257615	A1	10/2012	Eskildsen
2005/0088145	A1	4/2005	Loch	2012/0280783	A1	11/2012	Gerhardt et al.
2005/0179517	A1	8/2005	Harms	2012/0280789	A1	11/2012	Gerhardt et al.
2005/0212750	A1	9/2005	Marvit	2012/0280790	A1*	11/2012	Gerhardt G07C 9/00571 340/5.61
2005/0212752	A1	9/2005	Marvit	2012/0306655	A1	12/2012	Tan
2005/0248444	A1	11/2005	Joao	2012/0319827	A1	12/2012	Pance et al.
2005/0252739	A1	11/2005	Callahan et al.	2013/0010120	A1	1/2013	Nnoruka
2005/0286466	A1	12/2005	Tagg	2013/0023278	A1	1/2013	Chin
2006/0026536	A1	2/2006	Hotelling et al.	2013/0038550	A1	2/2013	Chien
2006/0033724	A1	2/2006	Chaudhri et al.	2013/0050106	A1	2/2013	Chung
2006/0158144	A1	7/2006	Theile	2013/0062892	A1	3/2013	Chow et al.
2006/0164208	A1	7/2006	Schaffzin	2013/0063138	A1	3/2013	Takahashi et al.
2006/0193262	A1	8/2006	Mcshaffrey	2013/0064378	A1	3/2013	Chuang
2006/0197753	A1	9/2006	Hotelling et al.	2013/0067969	A1	3/2013	Webb
2006/0267409	A1	11/2006	Mullet	2013/0076048	A1	3/2013	Aerts
2006/0283219	A1	12/2006	Bendz	2013/0126666	A1	5/2013	Brown
				2013/0138826	A1	5/2013	Ling et al.
				2013/0154823	A1	6/2013	Ostrer et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0166202	A1	6/2013	Bandyopadhyay	2015/0227201	A1	8/2015	Nakao	
2013/0176107	A1	7/2013	Dumas	2015/0227227	A1	8/2015	Myers	
2013/0178233	A1	7/2013	Mccooy	2015/0228167	A1	8/2015	Scalisi	
2013/0192318	A1	8/2013	Yanar et al.	2015/0233153	A1	8/2015	Smart	
2013/0207773	A1	8/2013	Hathaway	2015/0233154	A1	8/2015	Smart	
2013/0229274	A1	9/2013	Kumar	2015/0240521	A1	8/2015	Vaknin	
2013/0237193	A1	9/2013	Dumas	2015/0240531	A1	8/2015	Blust	
2013/0271261	A1	10/2013	Ribas	2015/0241974	A1	8/2015	Takeda	
2013/0307670	A1	11/2013	Ramaci	2015/0242007	A1	8/2015	Iwaizumi	
2014/0020295	A1	1/2014	Bonahoom	2015/0242036	A1	8/2015	Heidari	
2014/0021725	A1	1/2014	Baty et al.	2015/0242038	A1	8/2015	Steiner et al.	
2014/0028443	A1	1/2014	Ebner	2015/0242045	A1	8/2015	Choi	
2014/0033773	A1	2/2014	Myers	2015/0242047	A1	8/2015	Zafiris	
2014/0039366	A1	2/2014	Vasquez	2015/0242074	A1	8/2015	Iwamoto	
2014/0047878	A1	2/2014	Zheng	2015/0242113	A1	8/2015	Nguyen Thien	
2014/0049366	A1	2/2014	Vasquez	2015/0242115	A1	8/2015	Gao	
2014/0049369	A1	2/2014	Ahearn	2015/0242696	A1	8/2015	Kim	
2014/0051355	A1	2/2014	Ahearn	2015/0259949	A1	9/2015	Cheng	
2014/0051425	A1	2/2014	Ahearn et al.	2015/0287254	A1	10/2015	Ribas	
2014/0052783	A1	2/2014	Swatsky	2015/0300048	A1	10/2015	Yen	
2014/0062466	A1	3/2014	Thibault	2015/0302738	A1	10/2015	Geerlings	
2014/0067452	A1	3/2014	Anderson	2015/0308157	A1	10/2015	Lin	
2014/0125599	A1	5/2014	Seeley	2015/0310712	A1	10/2015	Lyman	
2014/0145666	A1	5/2014	Swanson	2015/0348399	A1	12/2015	Cree	
2014/0159865	A1	6/2014	Eto et al.	2015/0356345	A1	12/2015	Veloze	
2014/0189758	A1	7/2014	Kozlowski	2015/0363989	A1	12/2015	Scalisi	
2014/0202220	A1	7/2014	Denison et al.	2016/0006989	A1*	1/2016	Swanson	G08B 13/19656
2014/0218173	A1	8/2014	Long					348/151
2014/0239647	A1	8/2014	Jadallah	2016/0032621	A1	2/2016	Johnson et al.	
2014/0265359	A1	9/2014	Cheng et al.	2016/0036594	A1	2/2016	Conrad	
2014/0267736	A1	9/2014	DeLean	2016/0037306	A1	2/2016	Johnson et al.	
2014/0267740	A1*	9/2014	Almomani	2016/0042581	A1	2/2016	Kumar et al.	
		 H04N 7/186	2016/0047145	A1	2/2016	Johnson et al.	
			348/156	2016/0049024	A1	2/2016	Johnson et al.	
2014/0292481	A1	10/2014	Dumas	2016/0049025	A1	2/2016	Johnson	
2014/0324590	A1	10/2014	Kong	2016/0049026	A1	2/2016	Johnson	
2014/0340196	A1	11/2014	Myers	2016/0050515	A1	2/2016	Johnson	
2014/0354820	A1	12/2014	Danialian et al.	2016/0055694	A1	2/2016	Saeedi et al.	
2014/0365773	A1	12/2014	Gerhardt et al.	2016/0055695	A1	2/2016	Saeedi et al.	
2014/0375422	A1	12/2014	Huber	2016/0092954	A1	3/2016	Basset et al.	
2015/0008685	A1	1/2015	Beck	2016/0116510	A1	4/2016	Kalous	
2015/0015513	A1	1/2015	Kwak	2016/0127874	A1	5/2016	Kingsmill et al.	
2015/0022466	A1	1/2015	Levesque	2016/0133071	A1	5/2016	Henderson	
2015/0022620	A1*	1/2015	Siminoff	2016/0180618	A1	6/2016	Ho	
		 H04N 7/186	2016/0180620	A1*	6/2016	Eyring	G07C 9/00309
			348/14.02					235/382
2015/0027178	A1	1/2015	Scalisi	2016/0180621	A1	6/2016	Desinor, Jr.	
2015/0049189	A1	2/2015	Yau	2016/0189453	A1	6/2016	Johnson et al.	
2015/0049191	A1	2/2015	Scalisi	2016/0189454	A1	6/2016	Johnson et al.	
2015/0065167	A1	3/2015	Scalisi	2016/0189459	A1	6/2016	Johnson et al.	
2015/0096341	A1	4/2015	Overgaard	2016/0189502	A1	6/2016	Johnson et al.	
2015/0102609	A1	4/2015	Johnson et al.	2016/0189503	A1	6/2016	Johnson et al.	
2015/0102610	A1	4/2015	Johnson et al.	2016/0208541	A1	7/2016	Goto	
2015/0102927	A1	4/2015	Johnson et al.	2016/0284170	A1	9/2016	Kasmir	
2015/0109104	A1	4/2015	Fadell et al.	2016/0284181	A1	9/2016	Johnson	
2015/0116075	A1	4/2015	Cregg et al.	2016/0291966	A1	10/2016	Johnson	
2015/0116080	A1	4/2015	Cregg et al.	2016/0300476	A1	10/2016	Kasmir	
2015/0116082	A1	4/2015	Cregg	2016/0319569	A1	11/2016	Johnson et al.	
2015/0116490	A1	4/2015	Scalisi	2016/0319571	A1	11/2016	Johnson	
2015/0128667	A1	5/2015	Yoon et al.	2016/0326775	A1	11/2016	Johnson	
2015/0130587	A1*	5/2015	Lydecker	2016/0328901	A1	11/2016	Johnson	
		 H05B 47/105	2016/0330413	A1	11/2016	Scalisi	
			340/4.31	2016/0343181	A1	11/2016	Cheng et al.	
2015/0145796	A1	5/2015	Lee	2016/0343188	A1	11/2016	Johnson	
2015/0156031	A1*	6/2015	Fadell	2016/0358433	A1	12/2016	Johnson	
		 G08B 19/005	2016/0358437	A1	12/2016	Johnson et al.	
			700/276	2017/0011570	A1	1/2017	Johnson et al.	
2015/0160770	A1	6/2015	Stewart	2017/0016249	A1	1/2017	Johnson et al.	
2015/0170448	A1	6/2015	Robfogel et al.	2017/0019378	A1	1/2017	Johnson et al.	
2015/0185311	A1	7/2015	Lohier	2017/0032597	A1	2/2017	Johnson	
2015/0194000	A1	7/2015	Schoenfelder et al.	2017/0032602	A1	2/2017	Cheng et al.	
2015/0199860	A1	7/2015	Hong	2017/0053468	A1	2/2017	Johnson	
2015/0211259	A1	7/2015	Dumas	2017/0053469	A1	2/2017	Cheng et al.	
2015/0213658	A1	7/2015	Dumas	2017/0109952	A1	4/2017	Johnson	
2015/0213663	A1	7/2015	Dumas	2017/0134698	A1*	5/2017	Mahar	H04N 7/181
2015/0216326	A1	8/2015	Artwohl	2017/0169679	A1	6/2017	Johnson et al.	
2015/0218850	A1	8/2015	Uyeda	2017/0193724	A1	7/2017	Johnson et al.	
2015/0218857	A1	8/2015	Hamada	2017/0228603	A1	8/2017	Johnson	
2015/0222517	A1	8/2015	Mclaughlin	2017/0243420	A1	8/2017	Lien	

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0243455 A1 8/2017 Johnson et al.
 2017/0263065 A1 9/2017 Johnson
 2018/0040183 A1 2/2018 Cheng et al.
 2018/0073274 A1 3/2018 Johnson et al.
 2018/0135337 A1 5/2018 Johnson et al.
 2018/0179786 A1 6/2018 Johnson
 2018/0253951 A1 9/2018 Johnson et al.
 2018/0261029 A1 9/2018 Johnson et al.
 2018/0268675 A1 9/2018 Johnson et al.
 2018/0340350 A1 11/2018 Johnson et al.
 2019/0019364 A9 1/2019 Cheng et al.

FOREIGN PATENT DOCUMENTS

CA 2834964 11/2012
 CA 2905009 A1 9/2014
 CN 110276876 A 9/2019
 EP 0 244 750 A2 11/1987
 EP 0486657 5/1992
 EP 0907068 4/1999
 EP 1404021 3/2004
 EP 1529904 5/2005
 EP 2428774 3/2012
 EP 2 447 450 A2 5/2012
 EP 2454558 5/2012
 EP 2564165 3/2013
 EP 2579002 4/2013
 EP 2631400 8/2013
 EP 2642252 9/2013
 GB 2 259 737 A 3/1993
 WO WO 91/19986 A1 12/1991
 WO WO 2006/085852 A2 8/2006
 WO WO 2009/142596 A1 11/2009
 WO WO 2011/006515 A1 1/2011
 WO WO 2011/139682 A2 11/2011
 WO 2012151290 11/2012
 WO 2014062321 4/2014
 WO 2014107196 7/2014

WO WO 2014/151692 A2 9/2014
 WO WO 2014/151692 A3 9/2014
 WO 2015023737 2/2015
 WO WO 2015/138726 A1 9/2015
 WO WO 2015/138740 A1 9/2015
 WO WO 2015/138747 A1 9/2015
 WO WO 2015/138755 A1 9/2015
 WO WO 2016/130777 A1 8/2016
 WO WO 2016/196025 A1 12/2016

OTHER PUBLICATIONS

International Preliminary Report on Patentability for International Application No. PCT/US2014/026254, dated Sep. 24, 2015.
 International Search Report and Written Opinion for International Application No. PCT/US2015/020180, dated Jun. 16, 2015.
 International Preliminary Report on Patentability for International Application No. PCT/US2015/020180, dated Sep. 22, 2018.
 International Search Report and Written Opinion for International Application No. PCT/US2015/020206, dated Jun. 29, 2015.
 International Preliminary Report on Patentability for International Application No. PCT/US2015/020206, dated Sep. 22, 2016.
 International Search Report and Written Opinion for International Application No. PCT/US2015/020216, dated Jun. 17, 2015.
 International Preliminary Report on Patentability for International Application No. PCT/US2015/020216, dated Sep. 22, 2016.
 International Search Report and Written Opinion for International Application No. PCT/US2015/020226, dated Jun. 25, 2015.
 International Preliminary Report on Patentability for International Application No. PCT/US2015/020226, dated Sep. 22, 2016.
 International Search Report and Written Opinion for International Application No. PCT/US2016/017508, dated Jun. 14, 2016.
 International Preliminary Report on Patentability for International Application No. PCT/US2016/017508, dated Aug. 24, 2017.
 International Search Report and Written Opinion for International Application No. PCT/US2016/033257, dated Aug. 22, 2016.
 International Preliminary Report on Patentability for International Application No. PCT/US2016/033257, dated Dec. 14, 2017.

* cited by examiner




FIG. 1A




FIG. 1C





FIG. 1D






FIG. 1E




FIG. 1F




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D

FIG. 2E




FIG. 2F




FIG. 3B




FIG. 3A




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 8A




FIG. 8B




FIG. 9A

FIG. 9B




FIG. 9C

FIG. 9E




FIG. 9D




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 11C








FIG. 11D






FIG. 13A




FIG. 13B




FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 19




FIG. 20




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 21E




FIG. 21F




FIG. 21G




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 22D




FIG. 22E

Empty Extension Gear






FIG. 23A

Modular Extension Rod Controller



Extension Gear Adapters

FIG. 23B




FIG. 24




FIG. 24
(Cont'd)




FIG. 25A




FIG. 25B




FIG. 25C




FIG. 25D




FIG. 25E




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41B

FIG. 41A




FIG. 41C




FIG. 41D




FIG. 42



Door Ajar Status	Closed	Ajar	Unlocked
Lock Status	 <p>Closed + Locked = Secured</p>	 <p>Ajar + Lock = Not Secured</p>	 <p>Ajar + unlock = Not Secured</p>
Locked	 <p>Closed + unlocked = Not secured</p>		
Unlocked			

FIG. 43




FIG. 44




FIG. 45




FIG. 46





FIG. 47A



Camera System with RF communication

FIG. 47B

**MESH OF CAMERAS COMMUNICATING
WITH EACH OTHER TO FOLLOW A
DELIVERY AGENT WITHIN A DWELLING**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application claims the priority benefit of all of the following: under 35 U.S.C. § 119 to U.S. Provisional Patent Application No. 62/481,797, filed Apr. 5, 2017, as a Continuation in part of Ser. No. 15/798,425, filed Oct. 31, 2017, which is a Continuation in part of Ser. No. 15/497,383, filed Apr. 26, 2017, which is a Continuation in part of patent application Ser. No. 15/497,327 filed Apr. 26, 2017, which is a Continuation in part of patent application Ser. No. 15/463,022, filed Mar. 20, 2017, which is a Continuation in part of patent application Ser. No. 15/410,845, filed Jan. 20, 2017, which is a Continuation of patent application Ser. No. 15/066,210, filed Mar. 10, 2016, under 35 U.S.C. § 119 to U.S. Provisional Patent Application No. 62/481,797, filed April 5, 2017, as is a Continuation of patent application Ser. No. 14/205,608, filed Mar. 12, 2014, which claims the benefit under 35 U.S.C. § 119 of U.S. Provisional Patent Application No. 61/800,937, filed Mar. 15, 2013, U.S. Provisional Patent Application No. 61/801,335, filed Mar. 15, 2013, and U.S. Provisional Patent Application No. 61/801,294, filed Mar. 15, 2013, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation of patent application Ser. No. 14/205,783, filed Mar. 12, 2014, a Continuation of patent application Ser. No. 14/205,973, filed Mar. 12, 2014, a Continuation of patent application Ser. No. 14/206,536, filed Mar. 12, 2014, which is a Continuation of patent application Ser. No. 14/206,619, filed Mar. 12, 2014, which is a Continuation of patent application Ser. No. 14/207,833, filed Mar. 13, 2014, which is a Continuation of patent application Ser. No. 14/207,882, filed Mar. 13, 2014, a Continuation of patent application Ser. No. 14/208,947, filed Mar. 13, 2014, a Continuation of patent application Ser. No. 14/208,182, filed Mar. 13, 2014, a Continuation of patent application Ser. No. 14/212,569, filed Mar. 14, 2014, a Continuation-In-Part of patent application Ser. No. 14/321,260, filed Jul. 1, 2014, a Continuation-In-Part of patent application Ser. No. 14/321,000, filed Jul. 1, 2014, said Ser. No. 15/463,022 claims the benefit under 35 U.S.C. § 199 of U.S. Provisional Patent Application No. 62/036,971, filed Aug. 13, 2014, U.S. Provisional Patent Application No. 62/036,979, filed Aug. 13, 2014, U.S. Provisional Patent Application No. 62/036,989, filed Aug. 13, 2014, U.S. Provisional Patent Application No. 62/036,991, filed Aug. 13, 2014, U.S. Provisional Patent Application No. 62/036,993, filed Aug. 13, 2014, and said Ser. No. 15/463,022 is a Continuation-In-Part of patent application Ser. No. 14/459,054, filed Aug. 13, 2014, and a Continuation-In-Part of patent application Ser. No. 14/461,177, filed Aug. 15, 2014, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation-In-Part of patent application Ser. No. 14/465,513, filed Aug. 21, 2014, a Continuation-In-Part of patent application Ser. No. 14/465,527 filed Aug. 21, 2014, said Ser. No 15/065,657 is a Continuation-In-Part of patent application Ser. No. 14/469,127, filed Aug. 26, 2014, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation-In-Part of patent application Ser. No. 14/469,186, filed Aug. 26, 2014, said Ser. No. 15/065,657 is a Continuation-In-Part of patent application Ser. No. 14/471,414, filed Aug. 28, 2014, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation-In-Part of patent application Ser. No. 14/471,470, filed Aug. 28, 2014,

a Continuation-In-Part of patent application Ser. No. 14/622,054, filed Feb. 13, 2015, a Continuation-In-Part of patent application Ser. No. 14/622,192, filed Feb. 13, 2015, a Continuation-In-Part of patent application Ser. No. 14/622,578, filed Feb. 13, 2015, said Ser. No. 15/065,657 is a Continuation-In-Part of patent application Ser. No. 14/622,396, filed Feb. 13, 2015, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation-In-Part of patent application Ser. No. 14/622,654, filed Feb. 13, 2015, a Continuation of patent application Ser. No. 14/730,848, filed Jun. 4, 2015, said Ser. No. 15/065,657 is a Continuation-In-Part of patent application Ser. No. 14/731,092, filed Jun. 4, 2015, said Ser. Nos. 15/066,210 and 15/065,657 each respectively is a Continuation-In-Part of patent application Ser. No. 14/732,290, filed Jun. 5, 2015, a Continuation-In-Part of patent application Ser. No. 14/796,994, filed Jul. 10, 2015, a Continuation of patent application Ser. No. 15/065,657, filed Mar. 9, 2016, and a Continuation-In-Part of patent application Ser. No. 15/066,091, filed Mar. 10, 2016, and said Ser. No. 15/065,657 is a Continuation-In-Part of patent application Ser. No. 14/465,527 filed Aug. 21, 2014.

FIELD OF THE INVENTION

This invention relates generally to door lock systems, and more particularly to an intelligent door lock system coupled to or including a plurality of cameras where each of a camera of the plurality of cameras communicates from one camera to another camera.

DESCRIPTION OF THE RELATED ART

Existing security systems for homes and commercial properties feature multiple video camera connected to a security box. The security box contains electronics to convert analog video and optional audio inputs to digital and performs audio and video compression by a System-On-Chip (SoC) processor, which then stores the results on a hard disk. The system could be programmed for continuous recording in a loop, recording upon a trigger caused by external alarm and scene change threshold, or timed scheduled recording. The cameras are connected by cabling and video is transmitted as analog to the main system. Such cabling makes it difficult to install the multiple cameras inside and outside a residence or commercial because of routing of such long cabling between a dwelling user, resource owner, or end-user, resource owner, or end-user accessible box and cameras. Such a system provides 240 frames-per-second capture, which is divided by multiple cameras. For an 8-camera system, each camera video is captured at 240/8, or 30 fps, but capture resolution is usually low at CIF resolution (350×240). Such a security box can display captured video live from cameras or from hard disk on a monitor or TV, and dwelling user, resource owner, or end-user, resource owner, or end-user functions are controlled by front-panel buttons or an infrared remote-control unit (RCU). This means such a security box must be located near a TV and be visible for RCU operation. Such a system also provides means for remote viewing over internet, and can also send email messages with some snap shots of video when an alarm trigger occurs. However, there is much vulnerability in such a system. If internet is not working at the time of intrusion because phone or internet cables are externally cut, then no such email could be send. Thief can easily remove or damage the whole security box which removes all security data.

Another existing video security systems use networked security based where multiple camera units are connected to a PC or laptop computer over local area network or wide-area network. For example, 9 wireless camera units can connect to a PC computer using Ethernet wires or 802.11 wireless communications. Each camera unit contains video camera, video compression, and network interface in this case. Existing systems use JPEG or MPEG-2 or MPEG-4 systems, but in the future this will probably extend to advanced H.264 video compression standard as well in new designs. If there is no local computer, it is also possible to connect the cameras to a router connected to a WAN gateway, so that multiple security video channels could be streamed to a remote PC or laptop. The remote PC or laptop could perform remote viewing or recording of one or multiple channels on its hard disk storage. One of the disadvantages of such a security system is that if internet access deliberately interrupted at the time of a security event, then it is not possible to stream the data for the event to the remote PC for recording.

If the PC is located locally, then it could easily be removed by the perpetrators. Furthermore, such a system requires continuous stream of multiple video streams over local and wide area networks, which places a considerably load on such networks, thus causing unreliable operations and slowing other network activity. Cabled systems using Ethernet cabling also require difficult cabling of multiple camera units. Units configured to use 802.11 g systems contend bandwidth collisions with other systems, cordless phone, wireless microwaves, and other wireless communication systems on a limited number of channels. Thus, it becomes difficult and unreliable to transfer plurality of live compressed video stream in real-time without interruptions. However, such systems consume energy.

There is a need for an intelligent door lock system. There is a further need for an improved intelligent door lock system.

SUMMARY

An object of the present invention is to provide an intelligent door lock system with a plurality of cameras where each of a camera of the plurality of cameras communicates from one camera to another camera.

Another object of the present invention is to provide an intelligent door lock system coupled to a plurality of cameras wherein a first camera of the plurality of cameras opens up and or starts the next camera.

A further object of the present invention is to provide an intelligent door lock system coupled to a plurality of cameras where a dwelling occupant can be on its mobile device to watch what is going on.

A further object of the present invention is to provide an intelligent door lock system with a plurality of cameras where the plurality of cameras is configured to view a third party entering or exiting a dwelling.

Still another object of the present invention is to provide an intelligent door lock system with a plurality of cameras configured to view a third party entering or exiting a dwelling.

Yet another object of the present invention is to provide an intelligent door lock system with a plurality of cameras configured to view a third party entering or exiting a dwelling.

Another object of the present invention is to provide an intelligent door lock system with a plurality of cameras configured to view a third party entering or exiting a dwelling.

A further object of the present invention is to provide an intelligent door lock system with a plurality of cameras configured to view a delivery person's activities in a dwelling.

These and other objects of the present invention are achieved in an intelligent door lock system coupled to a door at a dwelling. A door status device is at the dwelling. The door status device is coupled to a drive shaft of a lock device to assist in locking and unlocking a lock of a lock device at the door. The lock device is coupled to the door status device and includes a bolt. An engine, an energy source and a memory are coupled together. A plurality of cameras communicate with each other and with the lock device.

In another embodiment of the present invention an intelligent door lock system is coupled to a door at a dwelling. An existing door lock system at the dwelling includes: an existing door lock system with a lock device with a lock, and a drive shaft. An intelligent door lock system is retrofitted to the existing door lock system to create a retrofitted intelligent door lock system to lock and unlock the door. The intelligent door lock system includes: a door status device configured to be coupled to the drive shaft of a lock device. The door status device determines lock or unlock status of a lock device. An engine provides power to lock and unlock the lock and coupled to the door status device. A circuit is coupled to the engine, an energy source is coupled to the circuit and provides power to lock or unlock the door, the energy source coupled to the circuit. A plurality of cameras communicate with each other and with the lock device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1(a) is an exploded view of a mounting assembly of an intelligent door lock device that can be used with the present invention.

FIG. 1(b) illustrates various embodiments of a positioning sensing device coupled to a drive shaft.

FIG. 1(c) illustrates one embodiment of a door lock device that can be used for retrofitting with an embodiment of an intelligent door lock device of the present invention.

FIG. 1(d) illustrates coupling of a positioning sensing device with a drive shaft of a door lock device.

FIG. 1(e) illustrates one embodiment of an intelligent door lock system of the present invention with an off-center drive.

FIG. 1(f) illustrates a wireless bridge that can be used in one embodiment of the present invention.

FIG. 1(g) illustrates one embodiment of elements coupled to a circuit in one embodiment of the present invention, including a haptic device.

FIGS. 2(a)-(c) illustrate embodiments of front and back surfaces of a main circuit that can be used and included in the intelligent door lock device of the present invention.

FIGS. 2(d)-(f) illustrate an embodiment of non-wire, direct connection between PCBAs in one embodiment of the present invention, with position of a PCBA in intelligent door lock device.

FIGS. 3(a)-(b) illustrate embodiments of LED lighting that can be used with the present invention.

FIGS. 4(a)-(d) illustrate one embodiment of a faceplate and views of a housing that can be used with the present invention.

FIGS. 5(a) and (b) illustrate the rotation range, with a minimized slot length of a faceplate lock that can be used in one embodiment of the present invention.

FIGS. 6(a) and (b) illustrate hook slots that can be used with the present invention.

FIGS. 7(a) through (e) illustrate one embodiment of a mount, with attachment to the mounting plate that can be used with the present invention.

FIGS. 8(a)-(b) illustrate embodiments of the present invention where magnets are utilized.

FIGS. 9(a)-(e) illustrate embodiments of the present invention with wing latches.

FIGS. 10(a)-(c) and FIGS. 11(a)-(d) illustrate further details of wing latching that is used in certain embodiments of the present invention.

FIGS. 12(a)-(d) illustrate embodiments of battery contacts that can be used with the present invention.

FIGS. 13(a) and (b) illustrate embodiments of a motor and gears in one embodiment of the present invention.

FIG. 14 illustrates an embodiment of the plurality of motion transfer device, including but not limited to gears, used in one embodiment of the present invention.

FIGS. 15(a)-(b) illustrate an embodiment of a speaker mounting.

FIGS. 15(c)-(d) illustrate an embodiment of an accelerometer FPC service loop.

FIG. 16 illustrates one embodiment of a back-end associated with the intelligent door lock system.

FIG. 17 is a diagram illustrating an implementation of an intelligent door lock system.

FIGS. 18(a) and (b) illustrate one embodiment of the present invention with a front view and a back view of a door with a bolt and an intelligent door lock system.

FIG. 19 illustrates more details of an embodiment of an intelligent door lock system of the present invention.

FIG. 20 illustrates one embodiment of the present invention showing a set of interactions between an intelligent door lock system, a mobile or computer and an intelligent door lock system back-end.

FIG. 21(a)-21(g) are examples of a dwelling user, resource owner, or end-user, resource owner, or end-user interface for an owner of a building that has an intelligent door lock system in one embodiment of the present invention.

FIGS. 22(a)-22(e) are examples of a dwelling user, resource owner, or end-user, resource owner, or end-user interface for a guest of an owner of a building that has an intelligent door lock system in one embodiment of the present invention.

FIGS. 23(a) and (b) illustrate one embodiment of an intelligent door lock system with an empty extension and extension gear adapters.

FIG. 24 illustrates one embodiment of a mobile device that is used with the intelligent door lock system.

FIGS. 25(a)-(e) represent a logical diagram of a Cloud lock access services Infrastructure in accordance with one embodiment of the present invention.

FIG. 26 illustrates one embodiment of inputs and outputs.

FIG. 27 shows one embodiment of a flowchart illustrating an example of a process for tracking signal strength.

FIG. 28 is a flowchart illustrating another example of a process for tracking signal strength.

FIG. 29 illustrates one embodiment of a triangulation algorithm for location estimation that can be used with the bridge.

FIG. 30 illustrates one embodiment of a K-nearest neighbor averaging algorithm for location estimate that can be used with the bridge.

FIG. 31 illustrates one embodiment for triangulation where a smallest m-polygon algorithm is used for location estimate

FIG. 32 an overview of the selfloc algorithm to fuse three information sources 1, 2 and 3.

FIG. 33 illustrates one embodiment of a dwelling user, resource owner, or end-user security system of the present invention.

FIG. 34 illustrates one embodiment of a dwelling user, resource owner, or end-user security system of the present invention that includes an authorization sensing device (motion detection device).

FIG. 35 illustrates one embodiment of a Bluetooth/WiFi bridge of the present invention.

FIG. 36 illustrates one embodiment of the intelligent door lock system server and/or cloud based server that provides access to a dwelling user, resource owner, or end-user.

FIG. 37 is a diagram illustrating operation of an automatic unlock in one embodiment of the present invention.

FIG. 38 illustrates one embodiment of security system coupled to a door lock system.

FIG. 39 illustrates one embodiment of the intelligent door lock system with a magnetometer.

FIG. 40 illustrates one embodiment of a magnetometer reader with a door being opened.

FIGS. 41(a)-(d) illustrate one embodiment of a calculated door angel Q using two sensor readings.

FIG. 42 illustrates one embodiment of an intelligent door lock system with a magnet placed on a door frame.

FIG. 43 illustrate one embodiment of combining ajar and lock status information to evaluate if a dwelling is secured.

FIG. 44 illustrates one embodiment of the intelligent door lock system with a wide view camera.

FIGS. 45 and 46 illustrate one embodiment of the intelligent door lock system configured to define a safe zone in which an occupant, a non dwelling occupant third person and the like, is allowed into the dwelling.

FIGS. 47(a) and (b) illustrate one embodiment of the present invention where a camera and uses data from lock device to decide to record video or not.

DETAILED DESCRIPTION

As used herein, the term engine refers to software, firmware, hardware, other component that can be used to effectuate a purpose, serving computing and the like. The engine will typically include software instructions that are stored in non-volatile memory (also referred to as secondary memory). When the software instructions are executed, at least a subset of the software instructions can be loaded into memory (also referred to as primary memory) by a processor. The processor then executes the software instructions in memory. The processor may be a shared processor, a dedicated processor, or a combination of shared or dedicated processors. A typical program will include calls to hardware components (such as I/O devices), which typically requires the execution of drivers. The drivers may or may not be considered part of the engine, but the distinction is not critical.

As used herein, the term database is used broadly to include any known or convenient means for storing data, whether centralized or distributed, relational or otherwise.

As used herein a mobile device includes, but is not limited to, a cell phone, such as Apple's iPhone®, other portable

electronic devices, such as Apple's iPod Touches®, Apple's iPads®, and mobile devices based on Google's Android® operating system, and any other portable electronic device that includes software, firmware, hardware, or a combination thereof that is capable of at least receiving the signal, decoding if needed, exchanging information with a server to verify information. Typical components of mobile device may include but are not limited to persistent memories like flash ROM, random access memory like SRAM, a camera, a battery, LCD driver, a display, a cellular antenna, a speaker, a Bluetooth® circuit, and WIFI circuitry, where the persistent memory may contain programs, applications, and/or an operating system for the mobile device. A mobile device can be a key fob A key fob which can be a type of security token which is a small hardware device with built in authentication mechanisms. It is used to manage and secure access to network services, data, provides access, communicates with door systems to open and close doors and the like.

As used herein, the term "computer" or "mobile device or computing device" is a general purpose device that can be programmed to carry out a finite set of arithmetic or logical operations. Since a sequence of operations can be readily changed, the computer can solve more than one kind of problem. A computer can include of at least one processing element, typically a central processing unit (CPU) and some form of memory. The processing element carries out arithmetic and logic operations, and a sequencing and control unit that can change the order of operations based on stored information. Peripheral devices allow information to be retrieved from an external source, and the result of operations saved and retrieved.

As used herein, the term "Internet" is a global system of interconnected computer networks that use the standard Internet protocol suite (TCP/IP) to serve billions of users worldwide. It is a network of networks that consists of millions of private, public, academic, business, and government networks, of local to global scope, that are linked by a broad array of electronic, wireless and optical networking technologies. The Internet carries an extensive range of information resources and services, such as the inter-linked hypertext documents of the World Wide Web (WWW) and the infrastructure to support email. The communications infrastructure of the Internet consists of its hardware components and a system of software layers that control various aspects of the architecture, and can also include a mobile device network, e.g., a cellular network.

As used herein, the term "extranet" is a computer network that allows controlled access from the outside. An extranet can be an extension of an organization's intranet that is extended to users outside the organization that can be partners, vendors, and suppliers, in isolation from all other Internet users. An extranet can be an intranet mapped onto the public Internet or some other transmission system not accessible to the general public, but managed by more than one company's administrator(s). Examples of extranet-style networks include but are not limited to:

LANs or WANs belonging to multiple organizations and interconnected and accessed using remote dial-up

LANs or WANs belonging to multiple organizations and interconnected and accessed using dedicated lines

Virtual private network (VPN) that is comprised of LANs or WANs belonging to multiple organizations, and that extends usage to remote users using special "tunneling" software that creates a secure, usually encrypted network connection over public lines, sometimes via an ISP

As used herein, the term "Intranet" is a network that is owned by a single organization that controls its security policies and network management. Examples of intranets include but are not limited to:

A LAN

A Wide-area network (WAN) that is comprised of a LAN that extends usage to remote employees with dial-up access

A WAN that is comprised of interconnected LANs using dedicated communication lines

A Virtual private network (VPN) that is comprised of a LAN or WAN that extends usage to remote employees or networks using special "tunneling" software that creates a secure, usually encrypted connection over public lines, sometimes via an Internet Service Provider (ISP)

For purposes of the present invention, the Internet, extranets and intranets collectively are referred to as ("Network Systems").

For purposes of the present invention, Bluetooth LE devices and peripheral devices are Bluetooth low energy devices, marketed as Bluetooth Smart.

For purposes of the present invention, "third party access to a dwelling user, resource owner, or end-user, which can be programmatic" is authorized access to the dwelling user, resource owner, or end-user, and can be secured access, granted by an occupant or owner or end-user of the dwelling user, resource owner, or end-user. In one embodiment the access is access via an intelligent door lock system as described herein. In one embodiment the third party secured access to the dwelling user, resource owner, or end-user, which can by programmatic, is granted by the occupant or owner, or end-dwelling user, resource owner, or end-user of a dwelling user, resource owner, or end-user to a service provider, that can be multi-tiered, and used for only one time, multiple times, recurring times, set times, changeable times, and can be revocable, and the like. In one embodiment the access is a secured access, and in one embodiment it is authenticated with authorization provided to access the dwelling user, resource owner, or end-user via a lock of an intelligent door lock system, and it can include authorized resetting of the lock.

For purposed of the present invention, the term "service provider" means organizations and individuals that provide services for a dwelling user, resource owner, or end-user or occupant at a dwelling user, resource owner, or end-user. The services provided can include, any maintenance of the dwelling user, resource owner, or end-user, delivery and the pick-up of items to and from a dwelling user, resource owner, or end-user, services related to dwelling user, resource owner, or end-users and dwelling user, resource owner, or end-user occupants, including but not limited to craftspeople, housekeeping services, laundry and dry-cleaning, skilled laborers, unskilled laborers delivery people, childcare, housekeeping, hairstyling & barbering, makeup and beauty, laundry and dry-cleaning, pet sitting, pet training, funeral services, pet grooming, tailoring, delivery of packages and other items from delivery companies, the U.S. Post Office, the delivery of household items including groceries and the like. A service provider can be an individual, an organization, including but not limited to one with more than a single person such as a corporation, a DBA, partnership, and the like with multiple layers of management and multiple layers of providers from a CEO down to an individual that performs an actual activity at the dwelling user, resource owner, or end-user. An occupant or owner or end-user of a dwelling user, resource owner, or end-user can grant the service provider access to a corporation or organization, which can grant access to its employees, contrac-

tors, consultants, and the like, all of which can be revoked by the corporation or organization relative to the a person given dwelling user, resource owner, or end-user access, maintain records in a database regarding dwelling user, resource owner, or end-user access dates, times, and the like, all of which can be audited, videoed, monitored and maintained by the service provider and/or the occupant or owner or end-user of the dwelling user, resource owner, or end-user, which can revoke at any times access to the dwelling user, resource owner, or end-user.

In one embodiment of the present invention a dwelling user, resource owner, or end-user security system **11(a)** is provided with a camera coupled to a WiFi/BTLE a cellular/BTLE bridge **11** or more generally a long range networking/low power short range networking bridge **11**.

In one embodiment the present invention provides an improved dwelling user, resource owner, or end-user security system.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11** and wireless camera.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a camera system which is fully wireless, powered by batteries, and has the performance and endurance necessary to ensure a dwelling user, resource owner, or end-user's entry is properly secured.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11** and wireless camera (**10c**), where the camera can be activate via any internet connected device.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11**, wireless camera and a sensor.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that can include a WiFi bridge **11**, a wireless camera **10(c)**, and a sensor selected from at least one of a doorbell, occupancy sensor, entry keypad, touch sensor, pressure sensor, mobile device phone, Keyfob/card and sensor. In one embodiment wireless camera **10(c)** and a motion detection device **10(g)** are integrated as one unit, or are at least in communication with each other.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11** and a wireless camera **10(c)** that does not need a communication cable or external power.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11** and a battery powered wireless camera.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11**, a wireless camera **10(c)** and an intelligent door lock system **10**.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11**, a wireless camera **10(c)** and an intelligent door lock system **10** that is configured to confirm delivery of items to the dwelling user, resource owner, or end-user.

In one embodiment the present invention provides a dwelling user, resource owner, or end-user security system **11(a)** that includes a WiFi bridge **11**, a wireless camera **10(c)**

and an intelligent door lock system **10** that is configured to allow entrance into the dwelling user, resource owner, or end-user of a person delivering item to the dwelling user, resource owner, or end-user.

The specific embodiments of the dwelling user, resource owner, or end-user security system **11(a)** of the present invention are discussed hereafter.

The Intelligent Lock

Referring to FIG. **1(a)** in one embodiment the door lock system **10** includes a vibration/tapping sensing device **11** configured to be coupled intelligent lock system **10**. In one embodiment the intelligent door lock system **10** is in communication with a mobile device that includes a vibration/tapping sensing device to lock or unlock a door associated with the intelligent door lock system **10**.

In one embodiment the vibration/tapping sensing device **11** senses knocking on the door and locks or unlocks the door. In one embodiment the vibration/tapping sensing device **11** is not included as part of the actual intelligent door lock system. In one embodiment the vibration/tapping sensing device **11** is coupled to the drive shaft **14**. It will be appreciated that the vibration/tapping sensing device **11** can be coupled to other elements of the intelligent door lock system **10**. The vibration/tapping sensing device detects vibration or knocking applied to a door that is used to unlock or lock the intelligent door lock system **10**. This occurs following programming the intelligent door lock system **10**. The programming includes a user's vibration code/pattern, and the like. Additionally, a dwelling user, resource owner, or end-user, resource owner, or end-user can give a third person a knock code/pattern to unlock the intelligent door lock system of the door. The knocking is one that is recognized as having been defined by a user of the door lock system as a means to unlock the door. The knocking can have a variety of different patterns, tempos, duration, intensity and the like.

The vibration/tapping sensing device **11** detects oscillatory motion resulting from the application of oscillatory or varying forces to a structure. Oscillatory motion reverses direction. The oscillation may be continuous during some time period of interest or it may be intermittent. It may be periodic or nonperiodic, i.e., it may or may not exhibit a regular period of repetition. The nature of the oscillation depends on the nature of the force driving it and on the structure being driven.

Motion is a vector quantity, exhibiting a direction as well as a magnitude. The direction of vibration is usually described in terms of some arbitrary coordinate system (typically Cartesian or orthogonal) whose directions are called axes. The origin for the orthogonal coordinate system of axes is arbitrarily defined at some convenient location.

In one embodiment, the vibratory responses of structures can be modeled as single-degree-of-freedom spring mass systems, and many vibration sensors use a spring mass system as the mechanical part of their transduction mechanism.

In one embodiment the vibration/tapping sensing device **11** can measure displacement, velocity, acceleration, and the like.

A variety of different vibration/tapping sensing devices **11** can be utilized, including but not limited to accelerometers, optical devices, electromagnetic and capacitive sensors, contact devices, transducers, displacement transducers, piezoelectric sensors, piezoresistive devices, variable capacitance, servo devices, audio devices where transfer of

the vibration can be gas, liquid or solid, including but not limited to microphones, geo-phones, and the like.

Suitable accelerometers include but are not limited to: Piezoelectric (PE); high-impedance output; Integral electronics piezoelectric (IEPE); low-impedance output Piezoresistive (PR); silicon strain gauge sensor Variable capacitance (VC); low-level, low-frequency Servo force balance; and the like.

The vibration/tapping sensing device **11** can be in communication with an intelligent door lock system back-end **68**, via Network Systems, as more fully described hereafter.

In one embodiment, the intelligent door lock system **10** is configured to be coupled to a structure door **12**, including but not limited to a house, building and the like, window, locked cabinet, storage box, bike, automobile door or window, computer locks, vehicle doors or windows, vehicle storage compartments, and the like. In one embodiment, the intelligent door lock system **10** is coupled to an existing drive shaft **14** of a lock device **22** already installed and is retrofitted to all or a portion of the lock device **22**, which includes a bolt/lock **24**. In another embodiment, the intelligent door lock system **10** is attached to a door **12**, and the like, that does not have a pre-existing lock device. FIG. **1(b)** illustrates door lock elements that can be at an existing door, to provide for the mounting of the intelligent door lock system **10** with an existing lock device **22**.

FIG. **1(b)** illustrates door lock elements that can be at an existing door, to provide for the mounting of the intelligent door lock system **10** with an existing lock device **22**.

FIG. **1(b)** illustrates one embodiment of a lock device **22** that can be pre-existing at a door **10** with the intelligent door lock system **10** retrofitted to it. Components of the lock device **22** may be included with the intelligent door lock device **10**, as more fully discussed hereafter.

In one embodiment, the intelligent door lock system **10** includes a positioning sensing device **16**, a motor **38**, an engine/processor **36** with a memory and one or more wireless communication devices **40** coupled to a circuit **18**. The motor **38** converts any form of energy into mechanical energy. As a non-limiting example, three more four wireless communications devices **40** are in communication with circuit **18**. In one embodiment the vibration sensing device can be included with the positioning sensing device.

In one embodiment, the intelligent door lock system **10** is provided with the position sensing device **16** configured to be coupled to the drive shaft **14** of the lock device **22**. The position sensing device **16** senses position of the drive shaft **14** and assists in locking and unlocking the bolt/lock **24** of the lock device **22**. The engine **36** is provided with a memory. The engine **36** is coupled to the positioning sensing device **16**. A circuit **18** is coupled to the engine **36** and an energy source **50** is coupled to the circuit. A device **38** converts energy into mechanical energy and is coupled to the circuit **18**, positioning sensing device **16** and the drive shaft **14**. Device **38** is coupled to the energy source **50** to receive energy from the energy source **50**, which can be via the circuit **18**.

In one embodiment, the intelligent door lock system **10** includes any or all of the following, a face plate **20**, ring **32**, latches such as wing latches **37**, adapters **28** coupled to a drive shaft **14**, one or more mounting plates **26**, a back plate **30**, a power sensing device **46**, energy sources, including but not limited to batteries **50**, and the like.

In one embodiment (see FIG. **1(c)**), the intelligent door lock system **10** retrofits to an existing lock device **22** already installed and in place at a door **12**, and the like. The existing lock device **12** can include one or more of the following

elements, drive shaft **14**, a lock device **22** with the bolt/lock **24**, a mounting plate **26**, one or more adapters **28** for different lock devices **22**, a back plate **30**, a plurality of motion transfer devices **34**, including but not limited to, gears **34**, and the like.

In one embodiment, the memory of engine/processor **36** includes states of the door **12**. The states are whether the door **12** is a left handed mounted door, or a right handed mounted door, e.g., opens from a left side or a right side relative to a door frame. The states are used with the position sensing device **16** to determine via the engine/processor **36** if the lock device **22** is locked or unlocked.

In one embodiment, the engine/processor **36** with the circuit **18** regulates the amount of energy that is provided from energy source **50** to the motor **38**. This thermally protects the motor **38** from receiving too much energy and ensures that the motor **38** does not overheat or become taxed.

FIG. **1(d)** illustrates various embodiments of the positioning sensing device **16** coupled to the drive shaft **14**.

A variety of position sensing devices **16** can be used, including but not limited to, accelerometers, optical encoders, magnetic encoders, mechanical encoders, Hall Effect sensors, potentiometers, contacts with ticks, optical camera encoders, and the like.

As a non-limiting example, an accelerometer **16**, well known to those skilled in the art, detects acceleration. The accelerometer **16** provides a voltage output that is proportional to a detected acceleration. Suitable accelerometers **16** are disclosed in, U.S. Pat. Nos. 8,347,720, 8,544,326, 8,542,189, 8,522,596. EP0486657B1, EP 2428774 A1, incorporated herein by reference.

In one embodiment, the position sensing device **16** is an accelerometer **16**. Accelerometer **16** includes a flex circuit coupled to the accelerometer **16**. The accelerometer reports X, Y, and X axis information to the engine/processor **36** of the drive shaft **14**. The engine/processor **36** determines the orientation of the drive shaft **14**, as well as door knocking, bolt/lock **24** position, door **12** close/open (action) sensing, manual key sensing, and the like, as more fully explained hereafter.

Suitable optical encoders are disclosed in U.S. Pat. Nos. 8,525,102, 8,351,789, and 8,476,577, incorporated herein by reference.

Suitable magnetic encoders are disclosed in U.S. Publication 20130063138, U.S. Pat. No. 8,405,387, EP2579002A1, and EP2642252 A1, incorporated herein by reference.

Suitable mechanical encoders are disclosed in, U.S. Pat. No. 5,695,048, and EP2564165A2, incorporated herein by reference.

Suitable Hall Effect sensors are disclosed in, EP2454558B1 and EP0907068A1, incorporated herein by reference.

Suitable potentiometers are disclosed in, U.S. Pat. No. 2,680,177, EP1404021A3, CA2676196A1, incorporated herein by reference.

In various embodiments, the positioning sensing device **16** is coupled to the drive shaft **14** by a variety of means, including but not limited to the adapters **28**. In one embodiment, the position sensing device **16** uses a single measurement, as defined herein, of drive shaft **14** position sensing which is used to determine movement in order to determine the location of the drive shaft **14** and the positioning sensing device **16**. The exact position of the drive shaft **14** can be measured with another measurement without knowledge of any previous state. Single movement, which is one deter-

13

mination of position sensing, is the knowledge of whether the door **12** is locked, unlocked or in between. One advantage of the accelerator is that one can determine position, leave if off, come back at a later time, and the accelerometer **16** will know its current position even if it has been moved since it has been turned off. It will always know its current position.

In one embodiment, the positioning sensing device **16** is directly coupled to the drive shaft **14**, as illustrated in FIG. 1(d). Sensing position of the positioning sensing device **16** is tied to the movement of the drive shaft **14**. In one embodiment with an accelerometer **16**, the accelerometer **16** can detect X, Y and Z movements. Additional information is then obtained from the X, Y, and Z movements. In the X and Y axis, the position of the drive shaft **14** is determined; this is true even if the drive shaft **14** is in motion. The Z axis is used to detect a variety of things, including but not limited to, door **12** knocking, picking of the lock, break-in and unauthorized entry, door **12** open and closing motion. If a mobile device **201** is used to open or close, the processor **36** determines the lock state.

In one embodiment, the same positioning sensing device **16** is able to detect knocks by detecting motion of the door **12** in the Z axis. As a non-limiting example, position sensing is in the range of counter and clock wise rotation of up to 180 degrees for readings. The maximum rotation limit is limited by the position sensing device **16**, and more particularly to the accelerometer cable. In one embodiment, the result is sub 1° resolution in position sensing. This provides a higher lifetime because sampling can be done at a slower rate, due to knowing the position after the position sensing device **16** has been turned off for a time period of no great 100 milli seconds. With the present invention, accuracy can be enhanced taking repeated measurements. With the present invention, the positioning sensing device **16**, such as the accelerometer, does not need to consume additional power beyond what the knock sensing application already uses.

In one embodiment, the position sensing device **16** is positioned on the drive shaft **14**, or on an element coupled to the drive shaft **14**. In one embodiment, a position of the drive shaft **14** and power sensing device and/or a torque limited link **38** are known. When the position of the drive shaft **14** is known, it is used to detect if the bolt/lock **24** of a door lock device **22** is in a locked or unlocked position, as well as a depth of bolt/lock **24** travel of lock device **22**, and the like. This includes but is not limited to if someone, who turned the bolt/lock **24** of lock device **22** from the inside using the ring **32**, used the key to open the door **12**, if the door **12** has been kicked down, attempts to pick the bolt/lock **24**, bangs on the door **12**, knocks on the door **12**, opening and closing motions of the door **12** and the like. In various embodiments, the intelligent door lock system **10** can be interrogated via hardware, including but not limited to a key, a mobile device **201**, a computer, key fob, key cards, personal fitness devices, such as Fitbit®, nike fuel, jawbone up, pedometers, smart watches, smart jewelry, car keys, smart glasses, including but not limited to Google Glass, and the like.

During a power up mode, the current position of the drive shaft **14** is known.

Real time position information of the drive shaft **14** is determined and the bolt/lock **24** of lock device **22** travels can be inferred from the position information of the drive shaft **14**. The X axis is a direction along a width of the door **12**, the Y axis is in a direction along a length of a door **12**, and the Z axis is in a direction extending from a surface of the door **12**.

14

In one embodiment, the accelerometer **16** is the knock sensor. Knocking can be sensed, as well as the number of times a door **12** is closed or opened, the physical swing of the door **12**, and the motion the door **12** opening and closing. With the present invention, a determination is made as to whether or not someone successfully swung the door **12**, if the door **12** was slammed, and the like. Additionally, by coupling the position sensing device **16** on the moveable drive shaft **14**, or coupled to it, a variety of information is provided, including but not limited to, if the bolt/lock **24** is stored in the correct orientation, is the door **12** properly mounted and the like.

In one embodiment, a calibration step is performed to determine the amount of drive shaft **14** rotations to fully lock and unlock the bolt/lock **24** of lock device **22**. The drive shaft **14** is rotated in a counter-counter direction until it can no longer rotate, and the same is then done in the clock-wise direction. These positions are then stored in the engine memory. Optionally, the force is also stored. A command is then received to rotate the drive shaft **14** to record the amount of rotation. This determines the correct amount of drive shaft **14** rotations to properly lock and unlock the lock device **22**.

In another embodiment, the drive shaft **14** is rotated until it does not move anymore. This amount of rotation is then stored in the memory and used for locking and unlocking the lock device **22**.

In another embodiment, the drive shaft **14** is rotated until it does not move anymore. However, this may not provide the answer as to full lock and unlock. It can provide information as to partial lock and unlock. Records from the memory are then consulted to see how the drive shaft **14** behaved in the past. At different intervals, the drive shaft **14** is rotated until it does not move anymore. This is then statistically analyzed to determine the amount of drive shaft **14** rotation for full locking and unlocking. This is then stored in the memory.

In one embodiment, the engine/processor **36** is coupled to at least one wireless communication device **40** that utilizes audio and RF communication to communicate with a wireless device, including but not limited to a mobile device/key fob **210**, with the audio used to communicate a security key to the intelligent door lock system **10** from the wireless device **210** and the RF increases a wireless communication range to and from the at least one wireless communication device **40**. In one embodiment, only one wireless communication device **40** is used for both audio and RF. In another embodiment, one wireless communication device **40** is used for audio, and a second wireless communication device **40** is used for RF. In one embodiment, the bolt/lock **22** is included in the intelligent door lock system **10**. In one embodiment, the audio communications initial set up information is from a mobile device/key fob **210** to the intelligent door lock system **10**, and includes at least one of, SSID WiFi, password WiFi, a Bluetooth key, a security key and door configurations.

In one embodiment, an audio signal processor unit includes an audio receiver, a primary amplifier circuit, a secondary amplifier circuit, a current amplifier circuit, a wave detection circuit, a switch circuit and a regulator circuit. In one embodiment, the audio receiver of each said audio signal processor unit is a capacitive microphone. In one embodiment, the switch circuit of each audio signal processor unit is selected from one of a transistor and a diode. In one embodiment, the regulator circuit of each audio signal processor unit is a variable resistor. In one embodiment, the audio mixer unit includes a left channel

15

mixer and a right channel mixer. In one embodiment, the amplifier unit includes a left audio amplifier and a right audio amplifier. In one embodiment, the Bluetooth device includes a sound volume control circuit with an antenna, a Bluetooth microphone and a variable resistor, and is electrically coupled with the left channel mixer and right channel mixer of said audio mixer unit. Additional details are in U.S. Publication US20130064378 A1, incorporated fully herein by reference.

In one embodiment, the faceplate **20** and/or ring **32** is electrically isolated from the circuit **18** and does not become part of circuit **18**. This allows transmission of RF energy through the faceplate **20**. In various embodiments, the faceplate and/or ring are made of materials that provide for electrical isolation. In various embodiments, the faceplate **20**, and/or the ring **32** are at center of ground. As non-limiting examples, (i) the faceplate **20** can be grounded and in non-contact with the ring **32**, (ii) the faceplate **20** and the ring **32** are in non-contact with the ring **32** grounded, (iii) the faceplate **20** and the ring can be coupled, and the ring **32** and the faceplate **20** are all electrically isolated from the circuit **18**. In one embodiment, the ring **32** is the outer enclosure to the faceplate **20**, and the bolt/lock **24** and lock device **22** is at least partially positioned in an interior defined by the ring **32** and the faceplate **20**.

In one embodiment, the lock device **22** has an off center drive mechanism relative to the outer periphery that allows up to R displacements from a center of rotation of the bolt/lock **24** of lock device **22**, where R is a radius of the bolt/lock **24**, 0.75 R displacements, 0.5 R displacements, and the like, as illustrated in FIG. 1(e). The off center drive mechanism provides for application of mechanical energy to the lock device **22** and bolt/lock **22** off center relative to the outer periphery.

As illustrated in FIG. 1(f) in one embodiment, a wireless communication bridge **41** is coupled to a first wireless communication device **40** that communicates with Network Systems via a device, including but not limited to a router, a 3G device, a 4G device, and the like, as well as mobile device **210**. The wireless communication bridge **41** is also coupled to a second wireless communication device **40** that is coupled to the processor **38**, circuit **18**, positioning sensing device **16**, motor **38** and the lock device **22** with bolt/lock **24**, and provides for more local communication. The first wireless communication device **40** is in communication with the second wireless communication device **40** via bridge **41**. The second wireless communication device **40** provides local communication with the elements of the intelligent door lock system **10**. In one embodiment, the second communication device **45** is a Bluetooth device. In one embodiment, the wireless communication bridge **41** includes a third wireless communication device **40**. In one embodiment, the wireless communication bridge **41** includes two wireless communication devices **40**, e.g., and third and fourth wireless communication devices **40**. In one embodiment, the wireless communication bridge **41** includes a WiFi wireless communication device **40** and a Bluetooth wireless communication device **40**.

FIG. 1(g) illustrates various elements that are coupled to the circuit **18** in one embodiment of the present invention.

In one embodiment of the present invention, a haptic device **49** is included to provide the user with haptic feedback for the intelligent door lock system **10**, see FIG. 1(g). The haptic device is coupled to the circuit **18**, the processor **38**, and the like. In one embodiment, the haptic device provides a visual indication that the bolt/lock **24** of lock device **22** has reach a final position. In another embodi-

16

ment, the haptic device **49** provides feedback to the user that the bolt/lock **24** of lock device **22** has reached a home open position verses a final position so the dwelling user, resource owner, or end-user, resource owner, or end-user does not over-torque. A suitable haptic device **49** is disclosed in U.S. Publication No. 20120319827 A1, incorporated herein by reference.

In one embodiment, the wing latches **37** are used to secure the intelligent door lock system **10** to a mounting plate **26** coupled to the door **12**. In one embodiment, the wing latches **37** secure the intelligent door lock system **10** to a mounting plate **26** coupled to a door **12** without additional tools other than the wing latches **37**.

FIG. 1(g) illustrates one embodiment of circuit **18**, as well as elements that includes as part of circuit **18**, or coupled to circuit **18**, as discussed above.

FIGS. 2(a)-(c) illustrate front and back views of one embodiment of circuit **18**, and the positioning of circuit **18** in the intelligent door lock system **10**. FIGS. 2(d)-(e) illustrate an embodiment of non-wire, direct connection between PCBAs. FIG. 2 (e) shows the relative positioning of a PCBA in the intelligent door lock device **10**.

In one embodiment, the main circuit **18** is coupled to, the engine **36** with a processor and memory, the motor **38**, wireless communication device **40** such as a WiFi device including but not limited to a Bluetooth device with an antenna, position sensing device **16**, delete speaker (microphone) **17**, temperature sensor **42**, battery voltage sensor **44**, current sensor or power sensor **46** that determines how hard the motor **38** is working, a protection circuit to protect the motor from overheating, an LED array **48** that reports status and one or more batteries **50** that power circuit **18**, see FIG. 1(g).

The current sensor **46** monitors the amount of current that goes to the motor **38** and this information is received and processed by the engine/processor **36** with memory and is coupled to the circuit **18**. The amount of current going to the motor **38** is used to determine the amount of friction experienced by door **12** and/or lock device **22** with lock/bolt **24** in opening and/or closing, as applied by the intelligent door lock system **10** and the positioning sensing device **16** to the drive shaft **14**. The circuit **18** and engine/processor **36** can provide for an adjustment of current. The engine/processor **36** can provide information regarding the door and friction to the dwelling user, resource owner, or end-user, resource owner, or end-user of the door **12**.

FIGS. 3(a)-(b) illustrate embodiments of LED **48** lighting that can include diffusers, a plurality of LED patterns point upward, inward, and outward and a combination of all three. In one embodiment two control PCDs are provide to compare side by side. Each LED **48** can be independently addressable to provide for maximization of light with the fewest LEDs **48**. In one embodiment, an air gap is provided.

FIGS. 4(a)-(d), illustrate one embodiment of a faceplate **20** and views of the housing **32** and faceplate **20**.

FIGS. 5(a) and (b) illustrate the rotation range of the ring **32**, with a minimized slot length of a bolt/lock **24** of lock device **22** in one embodiment of the present invention. In one embodiment, there is a 1:1 relationship of ring **32** and shaft rotation. In other embodiments, the ratio can change. This can be achieved with gearing. In various embodiments, the bolt/lock **24** and/or lock device **22** can have a rotation of 20-5 and less turns clockwise or counter-clockwise in order to open the door **12**. Some lock devices **22** require multiple turns.

FIGS. 6(a) and (b), with front and back views, illustrate hook slots **52** that can be used with the present invention.

FIGS. 7(a) through (f) illustrate an embodiment of a mount 54, with attachment to the mounting plate 26. Screws 56 are captured in the housing 58, and/or ring 32 and accessed through a battery cavity. A dwelling user, resource owner, or end-user, resource owner, or end-user can open holes for access and replace the screws 56. In one embodiment, the screws extend through the mounting plate 26 into a door hole. In one embodiment, a height of the mounting plate 26 is minimized. During assembly, the lock device 22 is held in place, FIG. 7(c), temporarily by a top lip, FIG. 7(d) and the lock drive shaft 14.

In one embodiment the housing 58 has an interior volume of at least 200,000 cubic mm.

In one embodiment the amount of torque applied to the mechanical components of intelligent door lock system 10 is less than 8 in-lbs. In one embodiment the amount of torque applied to the draft shaft 22, bolt 24 and lock device 22 is less than 8 in-lbs. As non-limiting examples, the amount of torque applied is less than: 7 in-lbs; 6 in-lbs; 5 in-lbs; 4 in-lbs and the like.

FIGS. 8(a)-(b) illustrate embodiments where magnets 60 are utilized. The magnet 60 locations are illustrated as are the tooled recesses from the top and side. In one embodiment, the magnets 60 are distanced by ranges of 1-100 mm, 3-90, 5-80 mm apart and the like.

FIGS. 9(a)-(e) illustrate embodiments of the present invention with wing latches 36. The wing latches 36 allow for movement of the lock device 22 with bolt/lock 24 towards its final position, in a Z-axis direction towards the door 12. Once the lock device 22 with bolt/lock 24 is in a final position, the wing latches 36 allows for the secure mounting without external tools. The wing latches 36 do the mounting. Wing latches 36 enable mounting of the lock device 22 and bolt/lock 24 with use of only the Z axis direction only, and X and Y directionality are not needed for the mounting.

In one embodiment, a lead in ramp, FIG. 9 (e) is used to pull the elements together.

FIGS. 10(a)-(c) and FIGS. 11(a)-(d) illustrate further details of wing latching.

FIGS. 12(a)-(d) illustrate embodiments of battery contacts 64.

FIGS. 13(a) and (b) illustrate embodiments of motor 38 and one or more gears 34, with a gearbox 66. In one embodiment, a first gear 34 in sequence takes a large load if suddenly stopped while running.

FIG. 14 illustrates an embodiment of a plurality of motion transfer devices such as gears 34. There can be come backlash in a gear train as a result of fits and tolerances. There can also be play between adapters 28 and lock drive shafts 14. This can produce play in an out gearbox 66 ring. This can be mitigated with a detent that located the outer ring.

The intelligent door lock system 10 can be in communication with an intelligent door lock system back-end 68, via Network Systems, as more fully described hereafter.

In one embodiment, the flex circuit 18, which has an out-of plane deflection of at least 1 degree, includes a position detector connector 46, Bluetooth circuit, and associated power points, as well as other elements.

In one embodiment, the intelligent door lock system 10 can use incremental data transfer via Network Systems, including but not limited to BLUETOOTH® and the like. The intelligent door lock system 10 can transmit data through the inductive coupling for wireless charging. The

dwelling user, resource owner, or end-user, resource owner, or end-user is also able to change the frequency of data transmission.

In one embodiment, the intelligent door lock system 10 can engage in intelligent switching between incremental and full syncing of data based on available communication routes. As a non-limiting example, this can be via cellular networks, WiFi, BLUETOOTH® and the like.

In one embodiment, the intelligent door lock system 10 can receive firmware and software updates from the intelligent lock system back-end 68.

In one embodiment, the intelligent door lock system 10 produces an output that can be received by an amplifier, and decoded by an I/O decoder to determine I/O logic levels, as well as, both clock and data information. Many such methods are available including ratio encoding, Manchester encoding, Non-Return to Zero (NRZ) encoding, or the like; alternatively, a UART type approach can be used. Once so converted, clock and data signals containing the information bits are passed to a memory at the intelligent door lock system 10 or intelligent door lock system back-end 68.

In one embodiment, the intelligent door lock system 10, or associated back-end 68, can include a repeatable pseudo randomization algorithm in ROM or in ASIC logic.

FIGS. 15(a)-(b) illustrate an embodiment of a speaker 17 and speaker mounting 70.

FIGS. 15(c)-(d) illustrate one embodiment of an accelerometer FPC service loop.

As illustrated in FIG. 16, the intelligent door lock system back-end 68 can include one or more receivers 74, one or more engines 76, with one or more processors 78, coupled to conditioning electronics 80, one or more filters 82, one or more communication interfaces 84, one or more amplifiers 86, one or more databases 88, logic resources 90 and the like.

The back-end 68 knows that an intelligent door lock system 10 is with a dwelling user, resource owner, or end-user, resource owner, or end-user, and includes a database with the dwelling user, resource owner, or end-user, resource owner, or end-user's account information. The back-end 68 knows if the dwelling user, resource owner, or end-user, resource owner, or end-user is registered or not. When the intelligent door lock system 10 is powered up, the back-end 68 associated that intelligent door lock system 10 with the dwelling user, resource owner, or end-user, resource owner, or end-user.

The conditioning electronics 80 can provide signal conditioning, including but not limited to amplification, filtering, converting, range matching, isolation and any other processes required to make sensor output suitable for processing after conditioning. The conditioning electronics can provide for, DC voltage and current, AC voltage and current, frequency and electric charge. Signal inputs accepted by signal conditioners include DC voltage and current, AC voltage and current, frequency and electric charge. Outputs for signal conditioning electronics can be voltage, current, frequency, timer or counter, relay, resistance or potentiometer, and other specialized output.

In one embodiment, the one or more processors 78, can include a memory, such as a read only memory, used to store instructions that the processor may fetch in executing its program, a random access memory (RAM) used by the processor 78 to store information and a master clock. The one or more processors 78 can be controlled by a master clock that provides a master timing signal used to sequence the one or more processors 78 through internal states in their execution of each processed instruction. In one embodiment, the

19

one or more processors **78** can be low power devices, such as CMOS, as is the necessary logic used to implement the processor design. Information received from the signals can be stored in memory.

In one embodiment, electronics **92** are provided for use in intelligent door system **10** analysis of data transmitted via System Networks. The electronics **92** can include an evaluation device **94** that provides for comparisons with previously stored intelligent door system **10** information.

Signal filtering is used when the entire signal frequency spectrum contains valid data. Filtering is the most common signal conditioning function, as usually not all the signal frequency spectrum contains valid data.

Signal amplification performs two important functions: increases the resolution of the inputted signal, and increases its signal-to-noise ratio.

Suitable amplifiers **86** include but are not limited to sample and hold amplifiers, peak detectors, log amplifiers, antilog amplifiers, instrumentation amplifiers, programmable gain amplifiers and the like.

Signal isolation can be used in order to pass the signal from to a measurement device without a physical connection. It can be used to isolate possible sources of signal perturbations.

In one embodiment, the intelligent door lock system back-end **68** can provide magnetic or optic isolation. Magnetic isolation transforms the signal from voltage to a magnetic field, allowing the signal to be transmitted without a physical connection (for example, using a transformer). Optic isolation takes an electronic signal and modulates it to a signal coded by light transmission (optical encoding), which is then used for input for the next stage of processing.

In one embodiment, the intelligent door lock system **10** and/or the intelligent door lock system back-end **68** can include Artificial Intelligence (AI) or Machine Learning-grade algorithms for analysis. Examples of AI algorithms include Classifiers, Expert systems, case based reasoning, Bayesian networks, and Behavior based AI, Neural networks, Fuzzy systems, Evolutionary computation, and hybrid intelligent systems.

Information received or transmitted from the back-end **68** to the intelligent door system **10** and mobile device **210** can use logic resources, such as AI and machine learning grade algorithms to provide reasoning, knowledge, planning, learning communication, and create actions.

In one embodiment, AI is used to process information from the intelligent door lock system **10**, from mobile device **210**, and the like. The back-end **68** can compute scores associated with various risk variables involving the intelligent door lock system **10**. These score can be compared to a minimum threshold from a database and an output created. Alerts can be provided to the intelligent door lock system **10**, mobile device **210** and the like. The alert can provide a variety of options for the intelligent door lock system **10** to take, categorizations of the received data from the mobile device **210**, the intelligent door lock system **10**, and the like, can be created. A primary option can be created as well as secondary options.

In one embodiment, data associated with the intelligent door lock system **10** is received. The data can then be pre-processed and an array of action options can be identified. Scores can be computed for the options. The scores can then be compared to a minimum threshold and to each other. A sorted list of the action options based on the comparison can be outputted to the intelligent door lock system **10**, the mobile device **210** and the like. Selections can then be received indicating which options to pursue. Action can then

20

be taken. If an update to the initial data is received, the back-end **68** can then return to the step of receiving data.

Urgent indicators can be determined and directed to the intelligent door lock system **10**, including unlocking, locking and the like.

Data received by the intelligent door lock system **10** and mobile device **210** can also be compared to third party secured access to a dwelling user, resource owner, or end-user, which can be by programmatic data sources.

In data evaluation and decision making, algorithm files from a memory can be accessed specific to data and parameters received from the intelligent door lock system **10** and mobile device **210**.

Scoring algorithms, protocols and routines can be run for the various received data and options. Resultant scores can then be normalized and weights assigned with likely outcomes.

The intelligent door lock system **10** can be a new lock system mounted to a door **12**, with all or most of the elements listed above, or it can be retrofitted over an existing lock device **22**.

To retrofit the intelligent door lock system **10** with an existing lock system, the dwelling user, resource owner, or end-user, resource owner, or end-user makes sure that the existing lock device **22** and bolt/lock **24** is installed right-side up. The existing thumb-turn is then removed. With some lock devices **22**, additional mounting plates **26** need to be removed and the intelligent door lock system **10** can include replacement screws **56** that are used. The correct mounting plate **26** is then selected. With the existing screws **56** in the thumb-turn, the dwelling user, resource owner, or end-user, resource owner, or end-user sequentially aligns with 1 of 4 mounting plates **26** that are supplied or exist. This assists in determining the correct diameter and replace of the screws **56** required by the bolt/lock **24**. The mounting plate **26** is then positioned. The correct adapter **28** is positioned in a center of the mounting plate **26** to assist in proper positioning. Caution is made to ensure that the adapter **28** does not rub the sides of the mounting plate **26** and the screws **56** are then tightened on the mounting plate **26**. The intelligent door lock system bolt/lock **24** of lock device **22** is then attached. In one embodiment, this is achieved by pulling out side wing latches **36**, sliding the lock device **22** and/or bolt/lock **24** over the adapter **28** and pin and then clamping down the wings **36** to the mounting plate **26**. The faceplate is rotated to open the battery compartment and the battery tabs are then removed to allow use of the battery contacts **64**. An outer metal ring **32** to lock and unlock the door **12** is then rotated. An app from mobile device **210** and/or key then brings the dwelling user, resource owner, or end-user, resource owner, or end-user through a pairing process.

A door **12** can be deformed, warped, and the like. It is desirable to provide a customer or dwelling user, resource owner, or end-user, resource owner, or end-user, information about the door, e.g., if it is deformed, out of alignment, if too much friction is applied when opening and closing, and the like.

As recited above, the current sensor **46** monitors the amount of current that goes to the motor **38** and this information is received and processed by the engine/processor **36** with memory and is coupled to the circuit **18**. The amount of current going to the motor **38** is used to determine the amount of friction experienced by door **12** and/or lock device **22** in opening and/or closing, as applied by the intelligent door lock system **10** and the positioning sensing device **16** to the drive shaft **14**. The circuit **18** and engine/

21

processor 36 can provide for an adjustment of current. The engine/processor 36 can provide information regarding the door and friction to the dwelling user, resource owner, or end-user, resource owner, or end-user of the door 12.

In one embodiment of the present invention, the intelligent door lock system 10 provides an ability to sense friction on the lock device 22 and/or door 12 by measuring the torque required to move the bolt/lock 24. The intelligent door lock system 10 increases the applied torque gradually until the bolt/lock 24 moves into its desired position, and the applied torque is the minimum amount of torque required to move the bolt/lock 24, which is directly related to how deformed the door is.

In one embodiment, when a bad door is detected, a customer can be notified that their door may require some servicing. In one embodiment, door deformation can be detected with a torque device is used to determine if the torque applied when the door is rotated is too high. As a non-limiting example, this can be 2-15 in lbs of torque The intelligent door lock system back end 68 can then perform a comparison between the measured torque with a standard, or a norm that is included in the one or more databases 88.

In one embodiment of the present invention, before the door is serviced, the intelligent door lock system 10 allows operation by offering a high-friction mode. As a non-limiting example, the high friction mode is when, as non-limiting examples, 2 inch lbs, 3 inch lbs., 3.5 inch pounds, and the like are required to open the door. In the high friction mode, the bolt/lock 24 is driven while the dwelling user, resource owner, or end-user, resource owner, or end-user is pushing, lifting, torquing the door, pulling, performing visual inspections of rust, blockage, other conditions that can compromise a door and the like, that is applied to the doorknob. The position sensing device 16 is used to determine if the bolt/lock 24 was moved to a final position. In the high friction mode, motion of the door closing is confirmed. Upon detecting the closing of the door, the bolt/lock 24 is then driven. When the dwelling user, resource owner, or end-user, resource owner, or end-user receives an auditory, visual, or any other type of perceptible confirmation, the dwelling user, resource owner, or end-user, resource owner, or end-user then knows that the door has been locked. In one embodiment, the firmware elements, of the intelligent door lock system 10, as well as other door lock device 22 elements, can also attempt to drive the bolt/lock 24 for a second time when the first time fails. However, this can result in more power consumption, reducing lifetime of the power source, particularly when it is battery 50 based.

In one embodiment of the present invention, the intelligent door lock system 10 seeks to have the motor 38 operate with reduced energy consumption for energy source lifetime purposes, as well as eliminate or reduce undesirable noises, operations, and dwelling user, resource owner, or end-user, resource owner, or end-user experiences that occur when this is a failure in door locking and unlocking, particularly due to door deformation, door non-alignment, as well as other problems with the door that can be irritating to the person locking or unlocking the door.

In one embodiment of the present invention, the intelligent door lock system back-end 68 can track performance of doors and friction levels across time and build a service to encourage dwelling user, resource owner, or end-user, resource owner, or end-user to better maintain their doors. Such service can be a comparison of a door's friction level to other users that have similar geographic locations, at similar weather pattern, such that the dwelling user, resource owner, or end-user, resource owner, or end-user is encour-

22

aged to maintain their doors at a competent level. There can be a comparison to standards that at a certain level the door becomes unsafe. Guidelines are provided as to how to maintain their doors. This can be achieved by asking a door dwelling user, resource owner, or end-user, resource owner, or end-user what improves their door, including but not limited to, pushing, lifting, torquing the door, pulling, visual inspections of rust, blockage, other conditions that can compromise a door, and the like. The analysis and comparison can be conducted at the back-end 68 and the results computed to door lock operator as well as others.

In one embodiment of the present invention, the intelligent door lock system 10 has a deformed operation mode that can be activated after a selected amount of time. As a non-limiting example, this can immediately after the dwelling user, resource owner, or end-user, resource owner, or end-user has been notified, more than 1 pico second, 1 second, 5 seconds, and greater periods of time. The deformed operation mode can be activated by the intelligent door lock system 10 itself, or by the intelligent door lock system back-end 68. It can be activated on the door operator's request. In one embodiment, the back-end 68 can anticipate these problems. As non-limiting examples, these can include but are not limited to, due to analysis of doors 12 in similar geographic areas, doors under similar conditions, doors with similar histories, similar environmental conditions, as well as the history of a particular door, and the like.

The deformed mode provides cooperation with the door dwelling user, resource owner, or end-user, resource owner, or end-user to more readily open the door. In one embodiment, this is a mechanism for the door to communicate back to the door lock operator. As a non-limiting example, feedback can be provided to the door operator. Such feedback can include, but is not limited to, communication via, tactile, audio, visual, temperature, electronic, wirelessly, through a computer, mobile device 201 and the like. In another embodiment, the operator can signify to the door the operator's desire to leave by unlocking and opening the door 12. This is a door operator and lock communication. The door operator can close the door, which is sensed by the intelligent door lock system 10, a timer can then be initiated to provide with door operator with a selected time period in which the door operator can manually alleviate the friction problem. When the time has expired, the intelligent door system 10 can then lock the door 12. Upon detecting a successful door locking event, the intelligent door lock system 10 can advise the door operator that there is a successful door locking. If the door locking is not successful, the intelligent door lock system 10 can provide a message to the door operator via a variety of means, including but not limited to a message or alert to the door lock operator's mobile device 201. Such a mobile device message provides the door operator with notification that door locking was not successful or achieved, and the door lock operator can then take action to lock the door 12 either in person, wirelessly, and the like.

For entry, communication with the lock device 22 may be different. In one embodiment, it can be locking coupled with close proximity to a mobile device 201 that is exterior to the door.

In another embodiment of the present invention, the intelligent door lock system back-end 68 can track performance of doors and friction levels across time and build a simple service to encourage dwelling user, resource owner, or end-user, resource owner, or end-users to maintain their doors better, as discussed above.

This information can be stored in the one or more databases **64**.

In one embodiment of the present invention, the intelligent door lock system **10** unlocks when a selected temperature is reached, when smoke is detected, when a fire is detected by processor **38** and the like. As non-limiting examples, the intelligent door lock system **10** unlocks the bolt/lock **24** when a temperature is sensed by the temperature sensor **46** that, as non-limiting examples, is greater than 40 degrees C., any temperature over 45 degrees C. and the like. The temperature sensor **46** **212** sends a signal to the processor **36** which communicates with the motor **38** that will then cause the drive shaft **14** to rotate sufficiently and unlock the bolt/lock **24**. An arm can also be activated. It will be appreciated that the processor **36** can be anywhere as long as it is in communication with the temperature sensor **46**, and the motor **38**, which can be at the intelligent door lock system **10**, at the back-end **68**, anywhere in the building, and at any remote location. The processor **36** determines if there is an unsafe condition, e.g., based on a rise in temperature and this then results in an unlocking of the bolt/lock **24**.

In one embodiment, the intelligent door lock system back-end **68** can track performance of doors and friction levels across time and build a service to encourage dwelling user, resource owner, or end-user, resource owner, or end-users to better maintain their doors, as discussed above.

FIG. **17** is a diagram illustrating an implementation of an intelligent door lock system **100** that allows an intelligent lock on one or more buildings to the controlled, as described above, and also controlled remotely by a mobile device **201** or computer, as well as remotely by an intelligent lock system back-end component **114**, a mobile device **201** or a computing device **210** of a dwelling user, resource owner, or end-user, resource owner, or end-user who is a member of the intelligent door lock system **100**, as disclosed above. The intelligent door lock system back-end component **114** may be any of those listed above included in the intelligent lock system back-end **68**, one or more computing resources, such as cloud lock access services computing resources or server computers with the typical components, that execute a plurality of lines of computer code to implement the intelligent door lock system **100** functions described above and below. Each computing device **210** of a dwelling user, resource owner, or end-user, resource owner, or end-user may be a processing unit based device with sufficient processing power, memory and connectivity to interact with the intelligent door lock system back-end component **114**. As a non-limiting example, the mobile device **201** or computing device **210** may be as defined above, and include those disclosed below, that is capable of interacting with the intelligent door lock back-end component **114**. In one implementation, the mobile device **201** or computing device **210** may execute an application stored in the memory of the mobile device **201** computing device **210** using a processor from the mobile device **201** or computing device **210** to interact with the intelligent door lock back-end component **114**. Examples of a dwelling user, resource owner, or end-user, resource owner or end-user interface for that application is shown in FIGS. **21(a)**-**22(e)** discussed below in more detail.

In another embodiment, the mobile device **201** or computing device **210** may execute a browser stored in the memory of the mobile or computing device **210** using a processor from the mobile device **201** or computing device **210** to interact with the intelligent door lock system back-end component **114**. Each of the elements shown in FIG. **17** may be linked by System Networks, including but not

limited to a cellular network, a Bluetooth system, the Internet (HTTPS), a WiFi network and the like.

As shown in FIG. **17**, each dwelling user, resource owner, or end-user, resource owner, or end-user's mobile device **201** or computer **210** may interact with the intelligent door lock system back-end **68** over System Networks, including but not limited to a wired or wireless network, such as a cellular network, digital data network, computer network and may also interact with the intelligent door lock system **10** using System Networks. Each mobile device **201** or computing device **210** may also communicate with a WiFi network **115** or Network Systems over, as a non-limiting example, a network and the WiFi network **115** may then communicate with the intelligent door lock system **10**.

FIGS. **18(a)** and **(b)** illustrate a front view and a back view, respectively, of a door **120** with intelligent door lock system **10**. The front portion of the door **120** (that is outside relative to a building or dwelling user, resource owner, or end-user) shown in FIG. **17** looks like a typical door **120** with a bolt assembly **122** and a doorknob and lock assembly **124**. The back portion of the door **120**, that is inside of the dwelling user, resource owner, or end-user when the door **120** is closed, illustrated in FIG. **18(b)** has the same doorknob and lock assembly **124**, but then has an intelligent door lock system **100** that is retrofitted onto the bolt assembly **124** as described below in more detail.

The intelligent door lock assembly **100** may have an extension gear which extends through the baseplate of the smart door lock. The baseplate may have one or more oval mounting holes to accommodate various rose screw distances from 18 mm to 32 mm to accommodate various different doors. In one implementation, the intelligent door lock system **100** may have a circular shape and also a rotating bezel. The rotating bezel allows a dwelling user, resource owner, or end-user, resource owner, or end-user to rotate the smart door lock and thus manually lock or unlock the bolt as before. The extension gear extends through the baseplate and then interacts with the existing bolt elements and allows the smart door lock to lock/unlocks the bolt. The extension gear may have a modular adapter slot at its end which interfaces with an extension rod of the bolt assembly **124**. These modular adapters, as shown in FIG. **23(b)**, may be used to match the existing extension rod of the bolt assembly **124**. The smart door lock housing may further include an energy source, such as a battery, a motor assembly, such as a compact, high-torque, high-accuracy stepper motor, and a circuit board that has at least a processor, a first wireless connectivity circuit and a second wireless connectivity circuit, as described above. In one embodiment, the first wireless connectivity circuit may be a Bluetooth chip that allows the smart door lock to communicate using a Bluetooth protocol with a computing device of a dwelling user, resource owner, or end-user, resource owner, or end-user, such as a Smartphone, tablet computer and the like. The second wireless connectivity circuit may be a WiFi chip that allows the smart door lock to communicate using a WiFi protocol with a back-end server system. The circuit board components may be intercoupled to each other and also coupled to the energy source and the motor for power and to control the motor, respectively. Each of the components described here may be coupled to the energy source and powered by the energy source.

FIG. **19** illustrates the smart door lock system **100** being retrofitted onto a bolt in a door **10**. As shown in FIG. **19**, when the intelligent door lock system **100** is installed on the door **120**, the thumb turn **124** is removed (replaced by the bezel that allows the dwelling user, resource owner, or

end-user, resource owner, or end-user to manually unlock or lock the bolt.) In addition, the extension gear **126** of the intelligent door lock system **100**, and more specifically the slotted portion **126(a)** at the end of the extension gear, is mechanically coupled to the extension rod **128** of the bolt assembly as show in FIG. **19**. When the intelligent door lock system **100** is installed, as shown in FIG. **19**, the dwelling user, resource owner, or end-user, resource owner, or end-user can rotate the bezel **132** to manually lock or unlock the bolt assembly. In addition, when commanded to do so, the motor assembly in the intelligent door lock system **100** can also turn the extension gear **126** that in turn turns the extension rod and lock or unlock the bolt assembly. Thus, the extension gear **126** allows the smart door lock to act as a manual thumb turn (using the bezel) and rotate either clockwise or counterclockwise to engage or disengage the bolt of a bolt. The extension gear **126** is designed in a manner to control the physical rotation of extension rods/axial actuators/tail pieces/tongues **128** which are traditional rotated by means of a thumb turn. This is achieved by designing the extension gear **126** with modular gear adapters as shown in FIG. **23(b)** to fit over the extension rod **22** as shown. This allows the extension gear **126** to fit with a variety of existing extension rods.

FIG. **20** illustrates a set of interactions between the intelligent door lock system **100**, mobile or computing device **210** and intelligent door lock system back-end **68** that may include a pairing process **138** and a lock operation process **140**. During the pairing process **138**, the intelligent door lock system **100** and mobile or computing device **210** can be paired to each other and also authenticated by the intelligent door lock system back-end **68**. Thus, as shown in FIG. **20**, during the pairing process, the intelligent door lock system **100** is powered on and becomes discoverable, while the mobile or computing device **210** communicates with the intelligent door lock system back-end **68**, and has its credentials validated and authenticated. Once the mobile or computing device **210**, and the app on the mobile or computing device **210**, is authenticated, the mobile or computing device **210** discovers the lock, such as through a Bluetooth discovery process, since the intelligent door lock system **100** and the mobile or computing device **210** are within a predetermined proximity to each other. The mobile or computing device **210** may then send a pairing code to the intelligent door lock system **100**, and in turn receive a pairing confirmation from the intelligent door lock system **100**. The pairing process is then completed with the processes illustrated in FIG. **20**. The lock operation may include the steps listed in FIG. **20** to operate the intelligent door lock system **100** wirelessly using the mobile or computing device **210**.

The intelligent door lock system **100** may be used for various functions. As a non-limiting example, the intelligent door lock system **100** may enable a method to exchange a security token between mobile or computing device **210** and the intelligent door lock system **100**. All or all of the intelligent door lock systems **100** may be registered with the intelligent door lock back-end **68** with a unique registration ID. The unique ID of the an intelligent door lock system **100** may be associated with a unique security token that can only be used to command a specific intelligent door lock system **100** to lock or unlock. Through a virtual key provisioning interface of the intelligent door lock system back-end **68**, a master user, who may be an administrator, can issue a new security token to a particular mobile or computing device **210**. The intelligent door lock system **100** can periodically broadcast an advertisement of its available services over

System Networks. When the mobile or computing device **210** is within a predetermined proximity of the intelligent door lock system **100**, which varies depending on the protocol being used, the mobile or computing device **210** can detect the advertisement from the intelligent door lock assembly **100**.

The application on the mobile or computing device **210** detects the intelligent door lock system **100** and a communications session can be initiated. The token, illustrated as a key **118** in FIG. **20**, is exchanged and the lock is triggered to unlock automatically. Alternatively, if the intelligent door lock system **100** is equipped with a second wireless communications circuit, then the intelligent door lock system **100** can periodically query the intelligent door lock system back-end **68** for commands. A dwelling user, resource owner, or end-user, resource owner, or end-user can issue commands via a web interface to the intelligent door lock system back-end **68**, and the intelligent door lock system **100** can lock or unlock the door **120**. The intelligent door lock system **100** may also allow the dwelling user, resource owner, or end-user, resource owner, or end-user to disable auto-unlock, at which time the application on the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile or computing device **210** can provide a notification which then allows the dwelling user, resource owner, or end-user, resource owner, or end-user to press a button on the mobile or computing device **210** to lock or unlock the lock.

The intelligent door lock system **100** may also allow for the triggering of multiple events upon connection to an intelligent door lock system **100** by a mobile or computing device **210**. As a non-limiting example, the intelligent door lock system **100** can detect and authenticate the mobile or computing device **210**, as described herein, and initiate a series of actions, including but not limiting to, unlocking doors **100**, turning on lights, adjusting temperature, turning on stereo etc.

As non-limiting examples, suitable devices that can be controlled by a mobile device **201** include but are not limited to: doors and windows, burglar alarms, generators, thermostats, lighting, smoke/co detector, refrigerator, ranges, electronic devices, door locks, water alarm or shutoff, washer and dryer, music systems, heating and air conditioning systems, water systems, sprinklers systems and the like. With the present invention analogies of any of the preceding can be detected. When an anomaly is detected the owner can be detected via its mobile device **201**, via the cloud or through a system backend, and an action be taken. In certain embodiments authorities can be immediately contacted and investigate the situation/dwelling user, resource owner, or end-user.

In one embodiment the motivation for anomaly detection is to discover events that are outside of threshold settings. Events could be malicious ones such as a hacker attempting to remotely operate a lock, a burglar breaking a window or pushing in a door, or non-malicious events such as a door that has been left open for longer than normal.

As a non-limiting example normal events would be normal smart lock operation and door operations that fall within threshold values, such as a commuter who operates the door lock once in the morning, and then once in the evening when they return home.

In one embodiment the calculation of an anomaly could be done by collecting signal values from devices and sensors such as a smart door lock, camera, microphone, etc. that capture video, audio, motion, seismic, or other event data. Data from each device could have a weighting factor

attached to it, and a total event value could be calculated by multiplying each signal value by its weighting factor, and then summing all signal values. If the total event value is greater than the anomaly threshold, then additional alerts or actions could be triggered, such as automatically locking the door or sending a notification to the dwelling user, resource owner, or end-user, resource owner, or end-user.

$$\text{Total Event Value} = w1 * k(\text{door}) + w2 * k(\text{window}) + \dots + wn * kn$$

where w1, w2, wn are weighting factors

where k(door), k(window), kn are signal values from devices or sensors

The commands for these actions may be carried out by the mobile or computing device 210 or the intelligent door lock system back-end 68. In addition, through a web interface of the intelligent door lock system back-end 68, the dwelling user, resource owner, or end-user, resource owner, or end-user may define one or more events to be triggered upon proximity detection and authentication of the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile or computing device 210 to the intelligent door lock system 100.

The intelligent door lock system 100 may also allow for the intelligent triggering of events associated with an individual. In particular, environmental settings may be defined per individual in the intelligent door lock system back-end 68 and then applied intelligently by successive ingress by that person into a building that has an intelligent door lock system 100. For example: person A arrives home and its mobile or computing device 210 is authenticated by the intelligent door lock system 100. His identity is shared with the intelligent door lock system back-end 68. The intelligent door lock system back-end 68 may send environmental changes to other home controllers, such as "adjust heat to 68 degrees". Person B arrives at the same building an hour later and her mobile or computing device 210 is also authenticated and shared with the intelligent door lock system back-end 68. The intelligent door lock system back-end 68 access her preferred environmental variables such as "adjust heat to 71 degrees". The intelligent door lock system back-end understands that person B has asked for a temperature increase and issues the respective command to the dwelling user, resource owner, or end-user thermostat. In one example, the intelligent door lock back-end system 68 has logic that defers to the higher temperature request or can deny it. Therefore if person A entered the home after person B, the temperature would not be decreased.

FIGS. 21(a)-(g) are examples of a dwelling user, resource owner, or end-user, resource owner, or end-user interface for an owner of a dwelling user, resource owner, or end-user that has an intelligent door lock system 100. These dwelling user, resource owner, or end-user, resource owner, or end-user interfaces may be seen by a dwelling user, resource owner, or end-user, resource owner, or end-user who is the owner of a building that has an intelligent door lock system 100 with the unique ID. FIG. 21(a) is a basic home screen while FIG. 22(b) shows the smart door locks (in a keychain) which the dwelling user, resource owner, or end-user, resource owner, or end-user of the mobile or computing device 210 has access rights to in intelligent door lock system 100. FIG. 21(c) illustrates an example of a dwelling user, resource owner, or end-user, resource owner, or end-user interface when a particular intelligent door lock system 100 is locked. FIG. 22(d) illustrates an example of a dwelling user, resource owner, or end-user, resource owner, or end-user interface when a particular intelligent door lock system 100

is unlocked. FIGS. 21(e) and (f) are dwelling user, resource owner, or end-user, resource owner, or end-user interface examples that allow the owner to add other dwelling user, resource owner, or end-user, resource owner, or end-users/people to be able to control the intelligent door lock system 100 of the building. FIG. 21(g) is an example of a configuration interface that allows the owner of the building to customize a set of permissions assigned for each intelligent door lock system 100.

FIGS. 22(a)-(e) are examples of a dwelling user, resource owner, or end-user, resource owner, or end-user interface for a guest of an owner of a building that has an intelligent door lock system 100.

FIGS. 23(a) and (b) illustrate an intelligent door lock system 100 and extension gear adapters 142. In particular, FIG. 23(a) shows the bolt of a lock device with an empty extension gear receptacle that allows different extension gear adapters 150 (shown in FIG. 7B) to be inserted into the receptacle so that the an intelligent door lock system 100 may be used with a number of different bolts of lock devices that each have a different shaped extension rod and/or extension rods that have different cross-sections.

Referring to FIGS. 22-24, the mobile or computing device can include an app for executing the methods of the present invention.

The mobile or computing device can include a display that can be a touch sensitive display. The touch-sensitive display is sometimes called a "touch screen" for convenience, and may also be known as or called a touch-sensitive display system. The mobile or computing device may include a memory (which may include one or more computer readable storage mediums), a memory controller, one or more processing units (CPU's), a peripherals interface, Network Systems circuitry, including but not limited to RF circuitry, audio circuitry, a speaker, a microphone, an input/output (I/O) subsystem, other input or control devices, and an external port. The mobile or computing device may include one or more optical sensors. These components may communicate over one or more communication buses or signal lines.

It should be appreciated that the mobile or computing device is only one example of a portable multifunction mobile or computing device, and that the mobile or computing device may have more or fewer components than shown, may combine two or more components, or a may have a different configuration or arrangement of the components. The various components may be implemented in hardware, software or a combination of hardware and software, including one or more signal processing and/or application specific integrated circuits.

Memory may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory by other components of the mobile or computing device, such as the CPU and the peripherals interface, may be controlled by the memory controller.

The peripherals interface couples the input and output peripherals of the device to the CPU and memory. The one or more processors run or execute various software programs and/or sets of instructions stored in memory to perform various functions for the mobile or computing device and to process data.

In some embodiments, the peripherals interface, the CPU, and the memory controller may be implemented on a single chip, such as a chip. In some other embodiments, they may be implemented on separate chips.

The Network System circuitry receives and sends signals, including but not limited to RF, also called electromagnetic signals. The Network System circuitry converts electrical signals to/from electromagnetic signals and communicates with communications with communications devices via the electromagnetic signals. The Network Systems circuitry may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. The Network Systems circuitry may communicate with Network Systems 110 and other devices by wireless communication.

The wireless communication may use any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), BLUETOOTH®, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for email (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), and/or Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS)), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

The audio circuitry, the speaker, and the microphone provide an audio interface between a user and the mobile or computing device. The audio circuitry receives audio data from the peripherals interface, converts the audio data to an electrical signal, and transmits the electrical signal to the speaker. The speaker converts the electrical signal to human-audible sound waves. The audio circuitry also receives electrical signals converted by the microphone from sound waves. The audio circuitry converts the electrical signal to audio data and transmits the audio data to the peripherals interface for processing. Audio data may be retrieved from and/or transmitted to memory and/or the Network Systems circuitry by the peripherals interface. In some embodiments, the audio circuitry also includes a headset jack. The headset jack provides an interface between the audio circuitry and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

The I/O subsystem couples input/output peripherals on the mobile or computing device, such as the touch screen and other input/control devices, to the peripherals interface. The I/O subsystem may include a display controller and one or more input controllers for other input or control devices. The one or more input controllers receive/send electrical signals from/to other input or control devices. The other input/control devices may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, and joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons may include an up/down button for volume control

of the speaker and/or the microphone. The one or more buttons may include a push button. A quick press of the push button may disengage a lock of the touch screen or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, which is hereby incorporated by reference in its entirety. A longer press of the push button may turn power to the mobile or computing device on or off. The user may be able to customize a functionality of one or more of the buttons. The touch screen is used to implement virtual or soft buttons and one or more soft keyboards.

The touch-sensitive touch screen provides an input interface and an output interface between the device and a user. The display controller receives and/or sends electrical signals from/to the touch screen. The touch screen displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output may correspond to user-interface objects, further details of which are described below.

A touch screen has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. The touch screen and the display controller (along with any associated modules and/or sets of instructions in memory) detect contact (and any movement or breaking of the contact) on the touch screen and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on the touch screen. In an exemplary embodiment, a point of contact between a touch screen and the user corresponds to a finger of the user.

The touch screen may use LCD (liquid crystal display) technology, or LPD (light emitting polymer display) technology, although other display technologies may be used in other embodiments. The touch screen and the display controller may detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with a touch screen.

A touch-sensitive display in some embodiments of the touch screen may be analogous to the multi-touch sensitive tablets described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in their entirety. However, a touch screen displays visual output from the portable mobile or computing device, whereas touch sensitive tablets do not provide visual output.

A touch-sensitive display in some embodiments of the touch screen may be as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 12, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6)

U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

The touch screen may have a resolution in excess of 1000 dpi. In an exemplary embodiment, the touch screen has a resolution of approximately 1060 dpi. The user may make contact with the touch screen using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and mood intensity, which are much less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, the mobile or computing device may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from the touch screen or an extension of the touch-sensitive surface formed by the touch screen.

In some embodiments, the mobile or computing device may include a physical or virtual click wheel as an input control device. A user may navigate among and interact with one or more graphical objects (henceforth referred to as icons) displayed in the touch screen by rotating the click wheel or by moving a point of contact with the click wheel (e.g., where the amount of movement of the point of contact is measured by its angular displacement with respect to a center point of the click wheel). The click wheel may also be used to select one or more of the displayed icons. For example, the user may press down on at least a portion of the click wheel or an associated button. User commands and navigation commands provided by the user via the click wheel may be processed by an input controller as well as one or more of the modules and/or sets of instructions in memory. For a virtual click wheel, the click wheel and click wheel controller may be part of the touch screen and the display controller, respectively. For a virtual click wheel, the click wheel may be either an opaque or semitransparent object that appears and disappears on the touch screen display in response to user interaction with the device. In some embodiments, a virtual click wheel is displayed on the touch screen of a portable multifunction device and operated by user contact with the touch screen.

The mobile or computing device also includes a power system for powering the various components. The power system may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

The mobile or computing device may also include one or more sensors, including not limited to optical sensors. In one embodiment an optical sensor is coupled to an optical sensor controller in I/O subsystem. The optical sensor may include

charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. The optical sensor receives light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with an imaging module (also called a camera module); the optical sensor may capture still images or video. In some embodiments, an optical sensor is located on the back of the mobile or computing device, opposite the touch screen display on the front of the device, so that the touch screen display may be used as a viewfinder for either still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image may be obtained for videoconferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of the optical sensor can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor may be used along with the touch screen display for both video conferencing and still and/or video image acquisition.

The mobile or computing device may also include one or more proximity sensors. In one embodiment, the proximity sensor is coupled to the peripherals interface. Alternately, the proximity sensor may be coupled to an input controller in the I/O subsystem. The proximity sensor may perform as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 11/240,788, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 13/096,386, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 13/096,386, "Automated Response To And Sensing Of User Activity In Portable Devices," filed Oct. 24, 2006; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables the touch screen when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call). In some embodiments, the proximity sensor keeps the screen off when the device is in the user's pocket, purse, or other dark area to prevent unnecessary battery drainage when the device is a locked state.

In some embodiments, the software components stored in memory may include an operating system, a communication module (or set of instructions), a contact/motion module (or set of instructions), a graphics module (or set of instructions), a text input module (or set of instructions), a Global Positioning System (GPS) module (or set of instructions), and applications (or set of instructions).

The operating system (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

The communication module facilitates communication with other devices over one or more external ports and also includes various software components for handling data received by the Network Systems circuitry and/or the external port. The external port (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over Network Systems **110**. In some embodiments, the external port is a multi-pin (e.g., 30-pin)

connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Computer, Inc.) devices.

The contact/motion module may detect contact with the touch screen (in conjunction with the display controller) and other touch sensitive devices (e.g., a touchpad or physical click wheel). The contact/motion module includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred, determining if there is movement of the contact and tracking the movement across the touch screen, and determining if the contact has been broken (i.e., if the contact has ceased). Determining movement of the point of contact may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, the contact/motion module and the display controller also detect contact on a touchpad. In some embodiments, the contact/motion module and the controller detects contact on a click wheel.

Examples of other applications that may be stored in memory include other word processing applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch screen, display controller, contact module, graphics module, and text input module, a contacts module may be used to manage an address book or contact list, including: adding name(s) to the address book; deleting name(s) from the address book; associating mobile device number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing mobile device numbers or e-mail addresses to initiate and/or facilitate communications by mobile device 201, video conference, e-mail, or IM; and so forth

The foregoing description of various embodiments of the claimed subject matter has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the claimed subject matter to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Particularly, while the concept "component" is used in the embodiments of the systems and methods described above, it will be evident that such concept can be interchangeably used with equivalent concepts such as, class, method, type, interface, module, object model, and other suitable concepts. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the relevant art to understand the claimed subject matter, the various embodiments and with various modifications that are suited to the particular use contemplated.

Referring now to FIG. 24, 1212 is a block diagram illustrating embodiments of a mobile or computing device 210 that can be used with intelligent door lock system 10.

The mobile or computing device 210 can include a display 1214 that can be a touch sensitive display. The touch-sensitive display 1214 is sometimes called a "touch screen" for convenience, and may also be known as or called a touch-sensitive display system. The mobile or computing device 210 may include a memory 1216 (which may include one or more computer readable storage mediums), a memory controller 1218, one or more processing units (CPU's) 1220, a peripherals interface 1222, Network Systems circuitry

1224, including but not limited to RF circuitry, audio circuitry 1226, a speaker 1228, a microphone 1230, an input/output (I/O) subsystem 1232, other input or control devices 1234, and an external port 1236. The mobile or computing device 210 may include one or more optical sensors 1238. These components may communicate over one or more communication buses or signal lines 1240.

It should be appreciated that the mobile or computing device 210 is only one example of a portable multifunction mobile or computing device 210, and that the mobile or computing device 210 may have more or fewer components than shown, may combine two or more components, or a may have a different configuration or arrangement of the components. The various components shown in FIG. 24 may be implemented in hardware, software or a combination of hardware and software, including one or more signal processing and/or application specific integrated circuits.

Memory 1216 may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory 1216 by other components of the mobile or computing device 210, such as the CPU 1220 and the peripherals interface 1222, may be controlled by the memory controller 1218.

The peripherals interface 1222 couples the input and output peripherals of the device to the CPU 1220 and memory 1216. The one or more processors 1220 run or execute various software programs and/or sets of instructions stored in memory 1216 to perform various functions for the mobile or computing device 210 and to process data.

In some embodiments, the peripherals interface 1222, the CPU 1220, and the memory controller 1218 may be implemented on a single chip, such as a chip 1242. In some other embodiments, they may be implemented on separate chips.

The Network System circuitry 1244 receives and sends signals, including but not limited to RF, also called electromagnetic signals. The Network System circuitry 1244 converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. The Network Systems circuitry 1244 may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. The Network Systems circuitry 1244 may communicate with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication.

The wireless communication may use any of a plurality of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), BLUETOOTH®, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for email (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation

Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), and/or Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS)), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

The audio circuitry **1226**, the speaker **1228**, and the microphone **1230** provide an audio interface between a dwelling user, resource owner, or end-user, resource owner, or end-user and the mobile or computing device **210**. The audio circuitry **1226** receives audio data from the peripherals interface **1222**, converts the audio data to an electrical signal, and transmits the electrical signal to the speaker **1228**. The speaker **1228** converts the electrical signal to human-audible sound waves. The audio circuitry **1226** also receives electrical signals converted by the microphone **1230** from sound waves. The audio circuitry **1226** converts the electrical signal to audio data and transmits the audio data to the peripherals interface **1222** for processing. Audio data may be retrieved from and/or transmitted to memory **1216** and/or the Network Systems circuitry **1244** by the peripherals interface **1222**. In some embodiments, the audio circuitry **1226** also includes a headset jack. The headset jack provides an interface between the audio circuitry **1226** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

The I/O subsystem **1232** couples input/output peripherals on the mobile or computing device **210**, such as the touch screen **1214** and other input/control devices **1234**, to the peripherals interface **1222**. The I/O subsystem **1232** may include a display controller **1246** and one or more input controllers **1250** for other input or control devices. The one or more input controllers **1250** receive/send electrical signals from/to other input or control devices **1234**. The other input/control devices **1234** may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, and joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **1252** may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons may include an up/down button for volume control of the speaker **1228** and/or the microphone **1230**. The one or more buttons may include a push button. A quick press of the push button may disengage a lock of the touch screen **1214** or begin a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, "Unlocking a Device by Performing Gestures on an Unlock Image," filed Dec. 23, 2005, which is hereby incorporated by reference in its entirety. A longer press of the push button may turn power to the mobile or computing device **210** on or off. The dwelling user, resource owner, or end-user, resource owner, or end-user may be able to customize a functionality of one or more of the buttons. The touch screen **1214** is used to implement virtual or soft buttons and one or more soft keyboards.

The touch-sensitive touch screen **1214** provides an input interface and an output interface between the device and a dwelling user, resource owner, or end-user, resource owner, or end-user. The display controller **1246** receives and/or sends electrical signals from/to the touch screen **1214**. The touch screen **1214** displays visual output to the dwelling user, resource owner, or end-user, resource owner, or end-user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed

"graphics"). In some embodiments, some or all of the visual output may correspond to dwelling user, resource owner, or end-user, resource owner, or end-user-interface objects, further details of which are described below.

A touch screen **1214** has a touch-sensitive surface, sensor or set of sensors that accepts input from the dwelling user, resource owner, or end-user, resource owner, or end-user based on haptic and/or tactile contact. The touch screen **1214** and the display controller **1246** (along with any associated modules and/or sets of instructions in memory **1216**) detect contact (and any movement or breaking of the contact) on the touch screen **1214** and converts the detected contact into interaction with dwelling user, resource owner, or end-user, resource owner, or end-user-interface objects (e.g., one or more soft keys, icons, web pages or images) that are displayed on the touch screen. In an exemplary embodiment, a point of contact between a touch screen **1214** and the dwelling user, resource owner, or end-user, resource owner, or end-user corresponds to a finger of the dwelling user, resource owner, or end-user, resource owner, or end-user.

The touch screen **1214** may use LCD (liquid crystal display) technology, or LPD (light emitting polymer display) technology, although other display technologies may be used in other embodiments. The touch screen **1214** and the display controller **1246** may detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with a touch screen **1214**.

A touch-sensitive display in some embodiments of the touch screen **1214** may be analogous to the multi-touch sensitive tablets described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in their entirety. However, a touch screen **1214** displays visual output from the portable mobile or computing device **210**, whereas touch sensitive tablets do not provide visual output.

A touch-sensitive display in some embodiments of the touch screen **1214** may be as described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, "Multipoint Touch Surface Controller," filed May 12, 2006; (2) U.S. patent application Ser. No. 10/840,862, "Multipoint Touchscreen," filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, "Gestures For Touch Sensitive Input Devices," filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, "Gestures For Touch Sensitive Input Devices," filed Jan. 31, 2005; (5) U.S. patent application Ser. No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

The touch screen **1214** may have a resolution in excess of 1000 dpi. In an exemplary embodiment, the touch screen has a resolution of approximately 1060 dpi. The dwelling user,

resource owner, or end-user, resource owner, or end-user may make contact with the touch screen **1214** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the dwelling user, resource owner, or end-user, resource owner, or end-user interface is designed to work primarily with finger-based contacts and gestures, which are much less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the dwelling user, resource owner, or end-user, resource owner, or end-user.

In some embodiments, in addition to the touch screen, the mobile or computing device **210** may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from the touch screen **1214** or an extension of the touch-sensitive surface formed by the touch screen.

In some embodiments, the mobile or computing device **210** may include a physical or virtual click wheel as an input control device **1234**. A dwelling user, resource owner, or end-user, resource owner, or end-user may navigate among and interact with one or more graphical objects (henceforth referred to as icons) displayed in the touch screen **1214** by rotating the click wheel or by moving a point of contact with the click wheel (e.g., where the amount of movement of the point of contact is measured by its angular displacement with respect to a center point of the click wheel). The click wheel may also be used to select one or more of the displayed icons. For example, the dwelling user, resource owner, or end-user, resource owner, or end-user may press down on at least a portion of the click wheel or an associated button. Dwelling user, resource owner, or end-user, resource owner, or end-user commands and navigation commands provided by the dwelling user, resource owner, or end-user, resource owner, or end-user via the click wheel may be processed by an input controller **1252** as well as one or more of the modules and/or sets of instructions in memory **1216**. For a virtual click wheel, the click wheel and click wheel controller may be part of the touch screen **1214** and the display controller **1246**, respectively. For a virtual click wheel, the click wheel may be either an opaque or semi-transparent object that appears and disappears on the touch screen display in response to dwelling user, resource owner, or end-user, resource owner, or end-user interaction with the device. In some embodiments, a virtual click wheel is displayed on the touch screen of a portable multifunction device and operated by dwelling user, resource owner, or end-user, resource owner, or end-user contact with the touch screen.

The mobile or computing device **210** also includes a power system **1214** for powering the various components. The power system **1214** may include a power management system, one or more power sources (e.g., battery **1254**, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

The mobile or computing device **210** may also include one or more sensors **1238**, including not limited to optical sensors **1238**. An optical sensor can be coupled to an optical sensor controller **1248** in I/O subsystem **1232**. The optical

sensor **1238** may include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. The optical sensor **1238** receives light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with an imaging module **1258** (also called a camera module); the optical sensor **1238** may capture still images or video. In some embodiments, an optical sensor is located on the back of the mobile or computing device **210**, opposite the touch screen display **1214** on the front of the device, so that the touch screen display may be used as a viewfinder for either still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the dwelling user, resource owner, or end-user, resource owner, or end-user's image may be obtained for videoconferencing while the dwelling user, resource owner, or end-user, resource owner, or end-user views the other video conference participants on the touch screen display. In some embodiments, the position of the optical sensor **1238** can be changed by the dwelling user, resource owner, or end-user, resource owner, or end-user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **1238** may be used along with the touch screen display for both video conferencing and still and/or video image acquisition.

The mobile or computing device **210** may also include one or more proximity sensors **1250**. In one embodiment, the proximity sensor **1250** is coupled to the peripherals interface **1222**. Alternately, the proximity sensor **1250** may be coupled to an input controller in the I/O subsystem **1232**. The proximity sensor **1250** may perform as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 11/240,788, "Proximity Detector In Handheld Device," filed Sep. 30, 2005; Ser. No. 13/096,386, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices," filed Oct. 24, 2006; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables the touch screen **1214** when the multifunction device is placed near the dwelling user, resource owner, or end-user, resource owner, or end-user's ear (e.g., when the dwelling user, resource owner, or end-user, resource owner, or end-user is making a phone call). In some embodiments, the proximity sensor keeps the screen off when the device is in the dwelling user, resource owner, or end-user, resource owner, or end-user's pocket, purse, or other dark area to prevent unnecessary battery drainage when the device is a locked state.

In some embodiments, the software components stored in memory **1216** may include an operating system **1260**, a communication module (or set of instructions) **1262**, a contact/motion module (or set of instructions) **1264**, a graphics module (or set of instructions) **1268**, a text input module (or set of instructions) **1270**, a Global Positioning System (GPS) module (or set of instructions) **1272**, and applications (or set of instructions) **1272**.

The operating system **1260** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

The communication module **1262** facilitates communication with other devices over one or more external ports **1274** and also includes various software components for handling data received by the Network Systems circuitry **1244** and/or the external port **1274**. The external port **1274** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with the 30-pin connector used on iPod (trademark of Apple Computer, Inc.) devices.

The contact/motion module **106** may detect contact with the touch screen **1214** (in conjunction with the display controller **1246**) and other touch sensitive devices (e.g., a touchpad or physical click wheel). The contact/motion module **106** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred, determining if there is movement of the contact and tracking the movement across the touch screen **1214**, and determining if the contact has been broken (i.e., if the contact has ceased). Determining movement of the point of contact may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, the contact/motion module **106** and the display controller **1246** also detects contact on a touchpad. In some embodiments, the contact/motion module **1284** and the controller **1286** detects contact on a click wheel.

Examples of other applications that may be stored in memory **1216** include other word processing applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch screen **1214**, display controller **1246**, contact module **1276**, graphics module **1278**, and text input module **1280**, a contacts module **1282** may be used to manage an address book or contact list, including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone, video conference, e-mail, or IM; and so forth.

FIGS. 25(a)-(e) represents a logical diagram of a cloud lock access services infrastructure that can be utilized with the present invention that is in communication with the bridge **11**, Bluetooth devices **21** and/or the intelligent door lock system **10**. As shown, the cloud lock access services encompasses web applications, mobile devices **210**, personal computer and/or laptops and social networks, such as, Twitter®. ("Twitter®" is a trademark of Twitter Inc.). It will be appreciated that other social networks can be included in the cloud lock access services and Twitter® has been given as a specific example. Therefore, every component forms part of the cloud lock access services which comprises servers, applications and clients as defined above.

The cloud lock can provide dwelling user, resource owner, or end-user access services with the utilization and allocation of hardware and software resource(s) to remote clients. The system can concurrently service requests from several clients without participant perception of degraded computing performance as compared to conventional tech-

niques where computational tasks can be performed upon a client or a server within a proprietary intranet. The cloud services provider (e.g., "which can be for secured dwelling user, resource owner, or end-user access with or without an intelligent door lock system **10**") supports a collection of hardware and/or software resources. The hardware and/or software resources can be maintained by an off-premises party, and the resources can be accessed and utilized by identified participants over Network System. Resources provided by the cloud services provider can be centrally located and/or distributed at various geographic locations. For example, the cloud services provider can include any number of data center machines that provide resources. The data center machines can be utilized for storing/retrieving data, effectuating computational tasks, rendering graphical outputs, routing data, and so forth.

In one embodiment the cloud is used for the remote door **12** status operation, remote door operation for locking, unlocking and the like.

According to an illustration, the cloud services provider can provide any number of resources such as data storage services, computational services, word processing services, electronic mail services, presentation services, spreadsheet services, gaming services, web syndication services (e.g., subscribing to a RSS feed), and any other services or applications that are conventionally associated with personal computers and/or local servers. Further, utilization of any number of the cloud service providers similar to the cloud services provider is contemplated. According to an illustration, disparate cloud services providers can be maintained by differing off-premise parties and a participant can employ, concurrently, at different times, and the like, all or a subset of the cloud services providers.

By leveraging resources supported by the cloud services provider, limitations commonly encountered with respect to hardware associated with clients and servers within proprietary intranets can be mitigated. Off-premises parties or Network System administrators of servers within proprietary intranets, can maintain, troubleshoot, replace and update the hardware resources. Further, for example, lengthy downtimes can be mitigated by the cloud services provider utilizing redundant resources; thus, if a subset of the resources are being updated or replaced, the remainder of the resources can be utilized to service requests from participants. According to this example, the resources can be modular in nature, and thus, resources can be added, removed, tested, modified, etc. while the remainder of the resources can support servicing participant requests. Moreover, hardware resources supported by the cloud services provider can encounter fewer constraints with respect to storage, processing power, security, bandwidth, redundancy, graphical display rendering capabilities, etc. as compared to conventional hardware associated with clients and servers within proprietary intranets.

The system can include a client device, which can be the wearable device and/or mobile device **201** that employs resources of the cloud services provider. Although one client device is depicted, it is to be appreciated that the system can include any number of client devices similar to the client device, and the plurality of client devices can concurrently utilize supported resources. By way of illustration, the client device can be a desktop device (e.g., personal computer), mobile device **201**, and the like. Further, the client device can be an embedded system that can be physically limited, and hence, it can be beneficial to leverage resources of the cloud services provider.

Resources can be shared amongst a plurality of client devices subscribing to the cloud services provider. According to an illustration, one of the resources can be at least one central processing unit (CPU), where CPU cycles can be employed to effectuate computational tasks requested by the client device. Pursuant to this illustration, the client device can be allocated a subset of an overall total number of CPU cycles, while the remainder of the CPU cycles can be allocated to disparate client device(s). Additionally or alternatively, the subset of the overall total number of CPU cycles allocated to the client device can vary over time. Further, a number of CPU cycles can be purchased by the participant of the client device. In accordance with another example, the resources can include data store(s) that can be employed by the client device to retain data. The participant employing the client device can have access to a portion of the data store(s) supported by the cloud services provider, while access can be denied to remaining portions of the data store(s) (e.g., the data store(s) can selectively mask memory based upon participant/device identity, permissions, and the like). It is contemplated that any additional types of resources can likewise be shared.

The cloud services provider can further include an interface component that can receive input(s) from the client device and/or enable transferring a response to such input(s) to the client device (as well as perform similar communications with any disparate client devices). According to an example, the input(s) can be request(s), data, executable program(s), etc. For instance, request(s) from the client device can relate to effectuating a computational task, storing/retrieving data, rendering a participant interface, and the like via employing one or more resources. Further, the interface component can obtain and/or transmit data over a Network System connection. According to an illustration, executable code can be received and/or sent by the interface component over the Network System connection. Pursuant to another example, a participant (e.g. employing the client device) can issue commands via the interface component.

In one embodiment, the cloud services provider includes a dynamic allocation component that apportions resources, which as a non-limiting example can be hardware resources supported by the cloud services provider to process and respond to the input(s) (e.g., request(s), data, executable program(s), and the like, obtained from the client device.

Although the interface component is depicted as being separate from the dynamic allocation component, it is contemplated that the dynamic allocation component can include the interface component or a portion thereof. The interface component can provide various adaptors, connectors, channels, communication paths, etc. to enable interaction with the dynamic allocation component.

In one embodiment a system includes the cloud services provider that supports any number of resources (e.g., hardware, software, and firmware) that can be employed by the client device and/or disparate client device(s) not shown. The cloud services provider further comprises the interface component that receives resource utilization requests, including but not limited to requests to effectuate operations utilizing resources supported by the cloud services provider from the client device and the dynamic allocation component that partitions resources, including but not limited to, between participants, devices, computational tasks, and the like. Moreover, the dynamic allocation component can further include a participant state evaluator, an enhancement component and an auction component.

The dwelling user, resource owner, or end-user, resource owner, or end-user state evaluator can determine a state

associated with a dwelling user, resource owner, or end-user, resource owner, or end-user and/or the client device employed by the dwelling user, resource owner, or end-user, resource owner, or end-user, where the state can relate to a set of properties. For instance, the dwelling user, resource owner, or end-user, resource owner, or end-user state evaluator can analyze explicit and/or implicit information obtained from the client device (e.g., via the interface component) and/or retrieved from memory associated with the cloud services provider (e.g., preferences indicated in subscription data). State related data yielded by the dwelling user, resource owner, or end-user, resource owner, or end-user state evaluator can be utilized by the dynamic allocation component to tailor the apportionment of resources.

In one embodiment, the dwelling user, resource owner, or end-user, resource owner, or end-user state evaluator can consider characteristics of the client device, which can be used to apportion resources by the dynamic allocation component. For instance, the dwelling user, resource owner, or end-user, resource owner, or end-user state evaluator can identify that the client device is a mobile device **201** with limited display area. Thus, the dynamic allocation component can employ this information to reduce resources utilized to render an image upon the client device since the cellular telephone may be unable to display a rich graphical dwelling user, resource owner, or end-user, resource owner, or end-user interface.

Moreover, the enhancement component can facilitate increasing an allocation of resources for a particular participant and/or client device.

In one embodiment a system employs load balancing to optimize utilization of resources. The system includes the cloud services provider that communicates with the client device (and/or any disparate client device(s) and/or disparate cloud services provider(s)). The cloud services provider can include the interface component that transmits and/or receives data from the client device and the dynamic allocation component that allots resources. The dynamic allocation component can further comprise a load balancing component that optimizes utilization of resources.

In one embodiment, the load balancing component can monitor resources of the cloud services provider to detect failures. If a subset of the resources fails, the load balancing component can continue to optimize the remaining resources. Thus, if a portion of the total number of processors fails, the load balancing component can enable redistributing cycles associated with the non-failing processors.

In one embodiment a system archives and/or analyzes data utilizing the cloud services provider. The cloud services provider can include the interface component that enables communicating with the client device. Further, the cloud services provider comprises the dynamic allocation component that can apportion data retention resources, for example. Moreover, the cloud services provider can include an archive component and any number of data store(s). Access to and/or utilization of the archive component and/or the data store(s) by the client device (and/or any disparate client device(s)) can be controlled by the dynamic allocation component. The data store(s) can be centrally located and/or positioned at differing geographic locations. Further, the archive component can include a management component, a versioning component, a security component, a permission component, an aggregation component, and/or a restoration component.

The data store(s) can be, for example, either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory. By way of illustration, and not

limitation, nonvolatile memory can include read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), or flash memory. Volatile memory can include random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as static RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), Rambus direct RAM (RDRAM), direct Rambus dynamic RAM (DRDRAM), and Rambus dynamic RAM (RDRAM). The data store(s) of the subject systems and methods is intended to comprise, without being limited to, these and any other suitable types of memory. In addition, it is to be appreciated that the data store(s) can be a server, a database, a hard drive, and the like.

The management component facilitates administering data retained in the data store(s). The management component can enable providing multi-tiered storage within the data store(s), for example. According to this example, unused data can be aged-out to slower disks and important data used more frequently can be moved to faster disks; however, the claimed subject matter is not so limited. Further, the management component can be utilized (e.g. by the client device) to organize, annotate, and otherwise reference content without making it local to the client device. Pursuant to an illustration, enormous video files can be tagged via utilizing a cell phone. Moreover, the management component enables the client device to bind metadata, which can be local to the client device, to file streams (e.g., retained in the data store(s)); the management component can enforce and maintain these bindings.

Additionally or alternatively, the management component can allow for sharing data retained in the data store(s) with disparate participants and/or client devices. For example, fine-grained sharing can be supported by the management component.

The versioning component can enable retaining and/or tracking versions of data. For instance, the versioning component can identify a latest version of a document (regardless of a saved location within data store(s)).

The security component limits availability of resources based on participant identity and/or authorization level. For instance, the security component can encrypt data transferred to the client device and/or decrypt data obtained from the client device. Moreover, the security component can certify and/or authenticate data retained by the archive component.

The permission component can enable a participant to assign arbitrary access permissions to various participants, groups of participants and/or all participants.

Further, the aggregation component assembles and/or analyzes collections of data. The aggregation component can seamlessly incorporate third party data into a particular participant's data.

The restoration component rolls back data retained by the archive component. For example, the restoration component can continuously record an environment associated with the cloud services provider. Further, the restoration component can playback the recording.

FIG. 26 illustrates one embodiment of inputs and outputs.

FIG. 27 is a flowchart illustrating an example of a process for tracking signal strength of between the bridge 11 and the Bluetooth LE devices 21, as well as the intelligent door lock system 10. While FIG. 27 illustrates exemplary steps

according to one embodiment, other embodiments may omit, add to, and/or modify any of the steps shown in FIG. 27.

An algorithm described hereafter computes proximity of a Bluetooth device 21 from the intelligent door lock system 10 of a dwelling user, resource owner, or end-user and from the one or more bridges 11 in the dwelling user, resource owner, or end-user. The relative signal strength of connections to these two devices during lock operations is recorded as a threshold value. When the proximity to the bridge 11, placed inside the home is closer than before the lock operation, we will compute algorithmically that the device is inside the home.

In one embodiment the time spent with a relatively consistent signal strength value is a strong indicator a person being in the dwelling user, resource owner, or end-user. A rapid change of proximity following a lock operation will be an indicator of coming.

In one embodiment a lock device 22 operation of the intelligent door lock system 10 followed by a rapid change of proximity is an indicator of going from the dwelling user, resource owner, or end-user.

The process of FIG. 27 begins by measuring the signal strength of wireless signals between the bridge 11 and the Bluetooth LE devices 21 at step 310. The signal strength may be measured in any of the ways discussed above, including the bridge 11 measuring the power of downstream wireless signals. Step 310 may be initiated in accordance with a predefined schedule or in response to a predetermined event.

At step 320, parameter data of the non-interconnect device is determined. The parameter data may include location, time, and/or velocity coordinates associated with the non-interconnect device at the time of the signal strength measurement. Step 320 may be performed in any variety of ways, including but not limited to the use of GPS information. Further, step 320 may be initiated by a predefined schedule or a predefined event, as discussed above.

At step 330, the signal strength and parameter data are transmitted to the cloud lock access services. Step 330 may be performed in any of the ways discussed above, including using upstream control, communication, or out-of-band channels of Network System. The signal strength and parameter data, and optionally additional data, may be combined to form network status data, which is transmitted to the cloud lock access services at step 330.

At step 340, the signal strength and parameter data are used to analyze the signal strength between the bridge 11 and a Bluetooth LE device 21. The network operations center 150 is able to process the data in any of the ways discussed above, including mapping the signal strength to geographic representations of the bridge 11 and a Bluetooth LE device 21, based on the parameter data. A graphical representation of at least a section of the strength of the signal between the bridge 11 and a Bluetooth LE device 12 may be generated to illustrate instances of measured signal strength plotted based on corresponding parameter data. Network operators may use the output of the cloud lock access services to analyze, configure, reconfigure, overhaul, and/or optimize the wireless network, as discussed above.

FIG. 28 is a flowchart illustrating another example of a process for tracking signal strength between the bridge 11 and a Bluetooth LE device 21. While FIG. 27 illustrates exemplary steps according to one embodiment, other embodiments may omit, add to, and/or modify any of the steps shown in FIG. 28.

45

The process of FIG. 28 begins by measuring the signal strength between the bridge 11 and a Bluetooth LE device 21 at step 410. The signal strength may be measured in any of the ways discussed above, including measuring the power of downstream wireless signals being received from the cloud lock access services relative to bridge 11 and a Bluetooth LE device 21. Step 410 may be initiated in accordance with a predefined schedule or in response to a predetermined event.

At step 420, it is determined whether the measured signal strength is lower than a predetermined threshold. The predetermined threshold may be defined by network operators and may be based on a desired level of signal power that provides effective signal strength. If it is determined at step 420 that the measured signal strength is not lower than the predetermined threshold, the process returns to step 410, at which step another measurement of signal strength is obtained either immediately, according to an established schedule, or in response to a predetermined trigger event.

On the other hand, if it is determined at step 420 that the measured signal strength is lower than the predetermined threshold, the process continues at step 430. In one embodiment, at step 430, parameter data of the Bluetooth LE device 21 is determined. As non-limiting examples, the parameter data may include location, time, and/or velocity coordinates associated with the Bluetooth LE device 21 relative to the bridge 11. Step 430 may be performed in any of the ways discussed above; including using GPS signals to determine GPS coordinate data.

At step 440, it is determined whether the measured signal strength is adequate for transmission of data upstream to the cloud lock access services from the Bluetooth LE device 21. Step 440 may be performed by comparing the measured signal strength to a predetermined transmission threshold, which may be defined by network operators based on a level of signal power that supports reliable upstream data transmissions from the wireless device.

If it is determined at step 440 that the measured signal strength is inadequate for transmission of data, the process continues at step 445. At step 445, the signal strength and parameter data are buffered for subsequent transmission. Step 445 may be performed by storing the data to memory to maintain the data until it can be transmitted. In one embodiment, from step 445, the process returns to step 410 to obtain another measurement of signal strength. Multiple instances of data may be buffered until signal strength becomes strong enough for the stored data to be transmitted from the Bluetooth LE device 21. In other words, steps 410-440 may be repeated with different measurements being gathered and stored for later transmission when the signal strength becomes strong enough to support upstream transmissions.

If it is determined at step 440 that the measured signal strength is adequate for data transmission, the process continues to step 450. At step 450, the signal strength and parameter data are transmitted to the cloud lock access services. Step 450 may be performed in any of the ways discussed above, including using upstream control, communication, or out-of-band channels of the wireless network 144. The signal strength and parameter data, and optionally additional data, may be combined to form network status data, which is transmitted to the cloud lock access services at step 450.

At step 460, the signal strength and parameter data are used to analyze any number of parameters relative to Bluetooth LE device 21, particularly its location. The cloud is able to process the data in any of the ways discussed above, including mapping the signal strength to geographic repre-

46

sentations of the wireless network 144, based on the parameter data. A graphical representation may be generated to illustrate instances of measured signal strength plotted based on corresponding parameter data.

FIG. 29 illustrates one embodiment of a triangulation algorithm for location estimation that can be used for the bridge 11, the intelligent door lock system 10 and a Bluetooth LE device 21. In one embodiment the triangulation computes the location estimate by solving systems of quadratic equations. In one embodiment the triangulation forms circles whose centers are the locations of the transmitters, e.g., access points or base stations. Geometries other than circles can be used. In FIG. 29, the locations and RF characteristics of access points 1, 2, and 3 of the bridge 11, the intelligent door lock system 10 and the Bluetooth LE device 21 have been obtained at numerous known locations. Distances d1 between the object and the access point 1, d2 between the bridge 11, the intelligent door lock system 10 and the access point 2, and d3 between them and the access point 3 are calculated based on radio wave characteristics, e.g., TOA or TDOA. It will be appreciated that communication other than radio waves can be used.

Triangulation forms sets of circles. Each of the reference points, access points 1, 2 or 3, becomes the center of a circle, and the distances between the object and the center, d1, d2 or d3, becomes the radius of that circle.

Triangulation estimates locations based on various intersection areas formed by these circles. If three formed circles meet at a single spot, that spot becomes the location estimate as a result of the triangulation. However, as a practical matter, the three circles rarely will meet at a single spot. More often, if the circles intersect, they will intersect in multiple spots. In FIG. 29, the three circles have six intersection points, P1, P2, P3, P4, P5 and P6. The triangulation algorithm examines areas formed by the intersection points to obtain a location estimate for the bridge 11, the intelligent door lock system 10 and the Bluetooth LE device. Specifically, the triangle formed by P2, P4 and P5 has the smallest area among all possible triangles formed by these intersection points, and the centroid X of the triangle (P2, P4, and P5) is the best location estimate of the object.

FIG. 30 illustrates the K-nearest neighbor averaging algorithm for location estimate, wherein K=5. Typically, K is larger than 2. Experimental analysis shows that K=3 gives the best performance. Let a triplet (Sa, Sb, Sc) represent a set of run-time signal strength measurements at a location of interest from the bridge 11, the intelligent door lock system 10 and the Bluetooth LE device 21, represented as a, b, and c. Five triplets which have the least root mean square (RMS) error in signal strength between the run-time and the off-line measurements are found. The root mean square error in signal strength is calculated as follows:

$$\text{rms} = \sqrt{\frac{\{\text{square root over}((a-a_i)^2+(b-b_i)^2+(c-c_i)^2)\} + \{\text{square root over}((a-a_i)^2+(b-b_i)^2+(c-c_i)^2)\} + \{\text{square root over}((a-a_i)^2+(b-b_i)^2+(c-c_i)^2)\}}{3}} \quad (1)$$

wherein (Sa, Sb, Sc) represents off-line signal strength measurements at the location of interest.

In particular, these five triplets are: signal strength triplet (a1, b1, c1) at position L1 (x1, y1) from a, b and c; signal strength triplet (a2, b2, c2) at position L2 (x2, y2) from a, b and c; and signal strength triplet (a5, b5, c5) at position L5 (x5, y5) from a, b and c. L1, . . . , L5 are determined by using the location information database. The location information database for RF-based static scene analysis typically contains entries used to map RF signal metrics to positions (i.e.,

transfer from signal domain to space domain). The positions of these five locations are averaged to yield the location estimate of the object as follows:

$$L=(L1+L2+L3+L4+L5)/5 \quad (2)$$

FIG. 31 illustrates, in one embodiment, the smallest M-polygon algorithm for location estimate, wherein M=3. M is the number of access points, or base stations, used for the system. M=3 gives reasonably good performance for the algorithm. The bridge 11, intelligent door lock system 10 and Bluetooth LE device 21, represented as A, B, and C provide separate candidate locations A1, A2, B1, B2, C1 and C2 that match best with the off-line measurements. The algorithm then searches for the polygon that has the smallest perimeter formed by candidate locations contributed by each reference base station, wherein one and only one candidate from each base station must constitute a vertex of the polygon. In FIG. 3, candidate locations A1, B2 and C2 form the smallest perimeter polygon, in this case, a triangle. The final location estimate of the object is the centroid X of the polygon:

$$x=(A1+B2+C2)/3 \quad (3)$$

In one embodiment the conventional static scene analysis maps from the radio signal domain to the space domain. The final estimate is typically within a coordinate system. A main drawback of the static scene analysis is that it cannot effectively cope with the impact of errors in the radio signal domain. Due to interference and noise, objects at different locations might be represented similarly in the radio signal domain, a phenomenon called aliasing. The conventional methods cannot detect aliasing, and may provide these different locations with similar location estimates.

In one embodiment selective fusion location estimation (SELFLOC) algorithm selectively combines or fuses multiple location information sources to yield a combined estimate in a theoretically optimal manner. The SELFLOC algorithm is disclosed in U.S. patent application Ser. No. 10/330,523, filed Dec. 27, 2002, which is incorporated herein by reference.

FIG. 32 illustrates, in one embodiment, an overview of the SELFLOC algorithm to fuse three information sources 1, 2 and 3. Each input branch is individually weighted by one of the weights 1, 2, and 3. The sum of the weighted input branches provides the SELFLOC estimate.

The branch weights 1, 2 and 3 are calibrated during the off-line stage using error feedback. A minimum mean square error (MMSE) algorithm can be used for SELFLOC weight training and calibration. As shown in FIG. 4, three location estimates available independently are to be fused, and x-coordinates of these estimates are X1, X2 and X3. The weights for these input branches are w1, w2, and W3 respectively. Thus, the SELFLOC estimate X could be written as:

$$X=w1 \cdot X1+w2 \cdot X2+w3 \cdot X3 \quad (4)$$

In one embodiment, a dwelling user, resource owner, or end-user security system 10(a) is provided as illustrated in FIG. 33. In one embodiment the dwelling user, resource owner, or end-user security system 10(a) is a wireless camera system with one or more wireless bridges 11 each including a computing device 13, an internet-facing radio 15, and a second radio 17 communicating with one or more dual-mode wireless cameras 10(c). In one embodiment the dual mode camera 10(c) includes a camera, a first radio 10(d) within communication range of the second radio 17 of the wireless bridge 11, and a third internet-facing radio 10(e) responsible for transmitting video. A trigger mechanism

10(f) is configured to receive a trigger via Network Systems or directly through hardware in communication with at least one of the bridges 11. The trigger mechanism 10(f) is configured triggers to at least one of the bridges 11 to transmit on its second radio 17 to wake up the dual mode camera 10(c) to transmit video on its third radio 10(e). As a non-limiting example, camera 10(c) can be the camera disclosed in US20040085205, incorporated fully herein by reference.

The camera 10(c) consumes less power in a standby mode because the first radio 10(d) consumes less power when configured to receive triggers and the third radio 10(d) is very efficient at transmitting video over Network Systems.

In one embodiment a generic input device, (hereafter “keypad”) is provided. The key pad can be part of the intelligent door lock system or be an accessory to the intelligent door lock system. In one embodiment the key pad is retrofitted to an existing intelligent door lock system after the intelligent door lock system has been installed. It is retrofitted to the existing intelligent door lock system. In one embodiment the keypad is installed when the intelligent door lock system, and can be sold with the intelligent door lock system. In one embodiment the keypad is an exterior of the dwelling user, resource owner, or end-user and in another embodiment it is in the interior of the dwelling user, resource owner, or end-user.

In one embodiment the keypad includes: a battery, keypad, a Bluetooth chip and board. Optionally included are LED lighting and a proximity sensor. Suitable examples of proximity sensors are disclosed herein.

The keypad provides for entering a communication that is encrypted, in order to gain access to the intelligent door lock system to lock and unlock. In one embodiment the communication is via BLE low energy.

In one embodiment the keypad has a BLE range of range of 20-30 feet. In one embodiment the keypad is within 3-5 feet of the door. As a non-limiting example the keypad can have a communication distance of at least thirty feet.

In one embodiment, the dwelling user, resource owner, or end-user, resource owner, or end-user, on initial setup programs the keypad via its mobile device 201, or other web-enabled device. The initial setup program is encrypted and can be achieved with symmetric key encryption, public key encryption and the like.

The dwelling user, resource owner, or end-user, resource owner, or end-user can communicate with the keypad by a variety of different mechanisms, including but not limited to entering digitals, letters, codes, tapping, a code with a pattern and the like.

In one embodiment the proximity sensor is integral with the proximity sensor. In one embodiment the keypad lights up as the dwelling user, resource owner, or end-user, resource owner, or end-user walks towards the keypad via the LED's.

As non-limiting examples the keypad can be configured to have time codes for expiration, may only be available for a certain of time, codes can be on a recurring identified time basis, the dwelling user, resource owner, or end-user, resource owner, or end-user can set the availability of time for access via the key paid for who can use, and how often it can be used

In one embodiment the keypad can be programmed via a bridge 11. This can be achieved remotely.

As non-limiting examples the keypad can be utilized using a mobile device 201, a computing device, via an API and the like. As a non-limiting example, a delivery company can issue a pass to a delivery person for access to the

dwelling user, resource owner, or end-user. This can be done at any time, or at a last minute via an API.

In one embodiment, illustrated in FIG. 34, a dwelling user, resource owner, or end-user security system 10(a) includes a camera 10(c) that can be coupled to a BLE-WiFi bridge 10(b), as described above and an authorization sensing device (motion detection device) 10(g) which can be long range, short range, and both and the like. As non-limiting examples the authorization sensing device 10(g) can be one or more of a device to sense key fobs/key cards, mobile devices 210, microchips, devices to sense biometrics, occupancy sensors including but not limited to rRF infrared, pressure, and optical-interrupter based sensor. In one embodiment detection device 10(g) is an electronic detection device 10(g). As non-limiting examples, motion detection device 10(g) can include an optical, microwave, or acoustic sensor, and a transmitter for illumination. In one embodiment a passive sensor 10(g) can be used. In one embodiment the intelligent security system 10(a) 10(g) can detect up to distances of at least 15 feet (5 meters).

In one embodiment the intelligent security system 10(a) 10(g) is an infrared detector mounted on circuit board, along with photoresistive detector for visible light. As non-limiting examples the following technologies can be used for the motion detection device 10(g): passive infrared (PIR), micro wave which detects motion through the principle of Doppler radar, and the like, ultrasonic and the like, tomographic motion detector, video camera 10(c) software, and the like.

As non-limiting examples suitable motion detection devices 10(g) include but are not limited to Infrared (passive and active sensors); optics (video and camera systems); radio frequency energy (radar, microwave and tomographic motion detection); sound (microphones and acoustic sensors); vibration (triboelectric, seismic, and inertia-switch sensors); magnetism (magnetic sensors and magnetometers); and the like.

In one embodiment in a first step, motion detection device 10(g) is used to detect motion of an individual approaching the dwelling user, resource owner, or end-user. In a second step, if the motion detection device 10(g) detects the approach of the individual then the camera 10(c) is turned on in sufficient time to take a face or body picture of the individual. In one embodiment, motion detection of the individual and turning on of camera 10(c) is processed in the cloud via its server/engine and the like, and in another embodiment in an intelligent door lock system back-end.

As a non-limiting example the first distance for the motion detection device 10(g) to detect approach of an individual is 5 meters, 10 meters and the like and the first trigger is at 10 meters, 5 meters and the like. As a non-limiting example the second distance to wake up camera 10(c) can be 2 mm, and any suitable distance suffice for a camera 10(c) to identify that there is a person. In one embodiment the second distance can be 5 meters for body detection.

As the person approaching hits, as a non-limiting example, 5 meters, the motion detection device 10(g) says that something has happened and wakes up camera 10(c), and at 2 meters determines if it is a person, the camera 10(c) is awakened in sufficient time to take a picture, and send a notice to the owner, to any device capable of receiving messages and notifications, it can be sent also to the cloud, to the authorities such as law enforcement who can then be dispatched to the dwelling user, resource owner, or end-user

In one embodiment the authorization sensing device 10(g) is a person sensing device, including but not limited to a button. As non-limiting examples, the button can be a

doorbell that can be integrated with a doorbell, a body or person sensing device, a hepatic device and the like. One embodiment of a suitable doorbell is disclosed in US 2004008205, incorporated herein by reference.

In other embodiments the camera 10(c) can be activated by an access authorization event. Suitable access authorization events include but are not limited to, use of an authorized mobile device 201 to unlock a door of the dwelling user, resource owner, or end-user; detection of an approaching face by another camera 10(c) that is powered, someone pressing the doorbell via a mechanical switch, capacitive sensor that senses touch, and the like. In other embodiment's access to a dwelling user, resource owner, or end-user is given to a person with one of the authorized devices recited above. In one embodiment instead of a doorbell a device is provided that translates mechanical movement or contact into an electrical signal. These devices include but are not limited to a rocker switch, body-heat sensitive switches, capacitive switch, pressure sensitive switches and the like.

In one embodiment the camera 10(c) is activated when a person is detected in proximity to an entrance to the dwelling user, resource owner, or end-user. As a non-limiting example this can be achieved using a proximity sensor situated inside the doorbell; by pressure sensors on a dwelling user, resource owner, or end-user floor; with the use of other proximity sensors with coverage in front of the a dwelling user, resource owner, or end-user access such as a door; and the like.

In one embodiment the camera 10(c) is in an interior of the dwelling user, resource owner, or end-user and the camera 10(c) is activated when a person entering the dwelling user, resource owner, or end-user is detected.

In one embodiment a power supply powers the intelligent doorbell by extracting power from the 2 leads from the dwelling user, resource owner, or end-user without ringing the doorbell, and without affecting the doorbells ability to ring. In one embodiment the intelligent doorbell is a bridge 11 configured to communicate with another bridge 11.

In one embodiment the camera 10(c) is positioned at the doorbell and is activated by a sensor or when the doorbell is depressed. In one embodiment a doorbell module is integrated with the camera 10(c). In one embodiment the doorbell module of a dwelling user, resource owner, or end-user is coupled to a wireless camera 10(c) that provides for wireless transmission of an image, and the like.

In one embodiment the camera is a micro-camera 10(c) mounted to a circuit board and is positioned in alignment with a hole defined in a case for photographing the visitor.

In one embodiment of the present invention, illustrated in FIG. 35, a Bluetooth/WiFi bridge 11 is provided that includes, a computing device 13 in an interior or exterior of a dwelling user, resource owner, or end-user 15 with an internet-facing radio 15, and a second radio 17 communicating with one or more Bluetooth LE devices 21. For purposes of the present invention Bluetooth LE devices 21 are Bluetooth LE devices 21, Bluetooth LE peripheral devices 21 and the like, are hereafter collectively Bluetooth LE devices 21. As non-limiting examples the Bluetooth LE devices can have power from 40 mW hours to 40 W hours. As non-limiting examples, Bluetooth devices 21 include but are not limited to: mobile devices 210, wearable devices, wearable devices supporting BLE, including but not limited to: Smart Wristwatches, smart bracelets, smart jewelry, smart tags, smart fobs, smart clothing, shoes, glasses, any type of wearable device, smart access control devices such as smart deadbolts, smart doorknobs, smart doorbells, wire-

less video cameras **10(c)**, wireless thermostats, automated irrigation control systems, smart light bulbs, and the like.

In one embodiment the computing device **13** is configured to connect Bluetooth LE devices **21** to the Network Systems.

In one embodiment the bridge **11** is coupled to the intelligent door lock system **10** via secure digital keys distributed by cloud lock access services lock access services.

In one embodiment the bridge **11** allows BLE devices in the dwelling user, resource owner, or end-user to interact with the cloud lock access services and with other Internet-connected devices via the intermediary that is the cloud lock access services. It will be appreciated that the dwelling user, resource owner, or end-user includes all structures besides homes.

In one embodiment the bridge **11** determines signal strength between the bridge **11**, and the Bluetooth LE device **21**. In another embodiment the bridge **11** determines signal strength of between the bridge **11**, the Bluetooth LE device **21** and the intelligent door lock system **10(a)**.

The retrieved signal strength processed It one embodiment, as described below, a triangulation algorithm is applied between the bridge **11**, the Bluetooth LE device **21** and the intelligent door lock system.

In one embodiment the bridge **11** uses detection of known Bluetooth devices and peripheral devices, hereafter collectively Bluetooth devices **21**, tied to specific individual people in the interior or at an exterior of the dwelling user, resource owner, or end-user. The bridge **11** tracks signal strength over time to: (i) determine if known or unknown people are inside or outside the dwelling user, resource owner, or end-user, (ii) if people are approaching the dwelling user, resource owner, or end-user, entering the dwelling user, resource owner, or end-user, exiting the dwelling user, resource owner, or end-user, moving away from the building and the like. In one embodiment the bridge **11** with the detection of the presence of a Bluetooth device **21** relays lock operations of the intelligent door lock system (manual or via a mobile application), door **12** movements, door **12** knocks to allow making these determinations of presence and movement with an algorithm as set forth below.

In one embodiment the bridge **11** interacts with the cloud lock access services to gather and relay data. This data can be gathered and stored locally, at the back-end **68**, and in a cloud lock access services based data layer. This is then used to determine the location and movement of people in and out the dwelling user, resource owner, or end-user.

In one embodiment the bridge **11** discovers the intelligent door lock system **10** over a Bluetooth device **21** networking. In one embodiment this is achieved by the bridge discovering lock devices **22** and their available services by scanning the Bluetooth LE **21** network for connected devices, advertising their presence and their services for obtaining lock device **22** status (secured or unsecured), communicates lock device **22** activity, communicates door **12** activity (door opening and closing, door **12** knocks, and the like) and operates the lock to lock and unlock the bolt **24** to secure or unsecure the lock device **22**.

In one embodiment the bridge **11** provides communication to other Bluetooth devices **21** without the use of a mobile device **201**. As non-limiting examples, the bridge **11** allows: WiFi-enabled devices in a dwelling user, resource owner, or end-user to interact with Bluetooth devices **21** in the dwelling user, resource owner, or end-user; WiFi-enabled devices in a dwelling user, resource owner, or end-user to interact with the intelligent door lock system **10** over Bluetooth; allows a Bluetooth device **21** in a dwelling user,

resource owner, or end-user to interact with Internet-based services and API's using a dwelling user, resource owner, or end-user's home WiFi network and Network System connection; allows people to operate an intelligent door lock system and other Bluetooth devices over a Network System from anywhere outside a dwelling user, resource owner, or end-user; extend network coverage of Bluetooth devices in a dwelling user, resource owner, or end-user in order to understand who is in the dwelling user, resource owner, or end-user, who is away, who is coming and who is going when doors **12** and lock devices **22** are operated and the like.

In one embodiment the bridge **11** extends Network System coverage of Bluetooth devices **21** other than lock devices **22** to perform device-specific operations, including but not limited to: gathering information about the presence of the Bluetooth device **21**, the operational status of the Bluetooth device **21**, the operational history of the Bluetooth device **21** and performing Bluetooth device **21** specific operations including but not limited to: turning the Bluetooth device **21** off and on, changing the mode of operations of the Bluetooth device **21**, changing the operational settings of the Bluetooth device **21** and scheduling these device operations based on ad hoc, daily, weekly, monthly or other schedules.

In one embodiment the intelligent door lock system **10** trusts the bridge **11** for commands (remote status) after an intelligent door lock system owner or designee is registered at the back-end of the intelligent door lock system using a cloud lock access services-based access system that grants the bridge **11** access to the intelligent door lock system **10**.

In one embodiment the intelligent door lock system **10** owners or designee grants the bridge **11** access to the lock device **22** by using their digital credentials, which can be stored at the cloud lock access services or at the back-end **68**, to pair a specific bridge **11** with a specific intelligent door lock system **10** grant specific rights. As non-limiting example, the specific rights include but are not limited to, gathering of status and operational history of the system **10**, triggering lock device **22** operations in real-time, as well as applications for interfacing with the bridge **11** and a Bluetooth device **21**.

In one embodiment the bridge **11** is used to determine if an intelligent door lock system **10** owners or designee with a non-internet connect device is at an interior or an exterior of a dwelling user, resource owner, or end-user.

In one embodiment the bridge **11** is used to determine if the person is approaching or moving away from the dwelling user, resource owner, or end-user. In one embodiment the bridge **11** measures the signal strength of the Bluetooth LE devices **21**.

In one embodiment as a Bluetooth LE device **21**, coupled to a person moves away from the bridge **11** the signal strength decreases, as more fully discuss hereafter. Similarly, as the signal strength increases this indicates that a person with the Bluetooth LE device is approaching the dwelling user, resource owner, or end-user.

In one embodiment, each room of a dwelling user, resource owner, or end-user with the intelligent door lock system has a bridge **11**. In another embodiment, the major rooms of the dwelling user, resource owner, or end-user each have a bridge **11**.

In one embodiment the bridge **11** learns habits, movements, and the like of the intelligent door lock system **10** owners or designee.

In one embodiment a triangulation is provided between the bridge **11**, the intelligent door lock system **10** and a Bluetooth LE device **21**, as more fully explained hereafter.

is a secure transfer of rights, and the original occupants or owners or end-users of the dwelling user, resource owner, or end-user is then dissociated with access rights without further rights, and can include resetting, and a change of credentials.

In one embodiment this is achieved using server which maintains access right privileges. The server is an intermediary. The person with the dwelling user, resource owner, or end-user and the intelligent door lock system **10** grants permission via server to give third party secured access to the dwelling user, resource owner, or end-user, which can be programmatic. Because that third party secured access to the dwelling user, resource owner, or end-user, which can be programmatic, including but not limited to a service provider is authorized, they can give temporary rights to an individual or dwelling user, resource owner, or end-user service provider, and then the occupant or owner or end-user of the dwelling user, resource owner, or end-user, and lock system **10** can revoke those rights at any time, for one or all. As non-limiting examples cameras **10(c)** are utilized to see the person entering or exiting the dwelling user, resource owner, or end-user. It will be appreciated that cameras **10(c)** as optional. Without the use of cameras **10(c)** the date and time of a third party secured access to a dwelling user, resource owner, or end-user, which can be programmatic unlocking or locking the intelligent door lock system **10** is provided to the third party secured access to a dwelling user, resource owner, or end-user, which can be programmatic, such as a service provider, as well as the person with the dwelling user, resource owner, or end-user and intelligent door lock system.

In one embodiment a lock system is coupled to a lock at a dwelling of a dwelling user, resource owner, or end-user, collectively the user. An intelligent door lock system is provided with a remotely operable lock at the dwelling accessible by the user, as illustrated in FIG. **37**. The intelligent door lock system **10** is configured to be in communication with a server **510**. An automatic unlock system is activated when the user communicates with the server **510** using the user's mobile device **210**. The server **510** is configured to transmit a crossing notification message in response to tracking the user's mobile device **210** and enable an automatic unlock feature of the lock using the server **510** and a mobile device App.

In one embodiment when the dwelling user, resource owner, or end-user, resource owner, or end-user enables an automatic unlock of system **10** it can view its current location on a map as a means of visual verification that it is being set up properly. In one embodiment a dwelling user, resource owner, or end-user threshold region can be viewed and/or adjusted by the dwelling user, resource owner, or end-user, resource owner, or end-user. In this embodiment the dwelling user, resource owner, or end-user, resource owner, or end-user implicitly indicates that when it has left the area then on returning to the area the dwelling user, resource owner, or end-user, resource owner, or end-user would like its door unlocked as the dwelling user, resource owner, or end-user approaches it. A dwelling user, resource owner, or end-user threshold region can be adjusted larger to compensate for poor GPS positioning available in a remote dwelling user, resource owner, or end-user region.

As a non-limiting example the following steps can be followed. The dwelling user, resource owner, or end-user, resource owner, or end-user exits the dwelling user, resource owner, or end-user. One or both inner and outer geo-fences **512**, **514** can be exited. In the event that both geo-fences

512, **514** are exited after a certain period of time door **12** is then locked. When the inner fence **512** is only exited system **10** does not lock door **12**. The server **510** can enable detailed GPS detection to verify that the dwelling user, resource owner, or end-user, resource owner, or end-user has left the area defined by geo-fences **512** and **514**. The dwelling user, resource owner, or end-user, resource owner, or end-user can enter outer geo-fence **514** and mobile device **210** App wakes up. Dwelling user, resource owner, or end-user, resource owner, or end-user mobile device **210** examines a sufficient to determine whether to activate Bluetooth and search for door **12** in order to unlock door **12**. The data can include, time spent outside geo-fence **512** or geo-fence **514**, time of day, past dwelling user, resource owner, or end-user, resource owner, or end-user activity patterns, dwelling user, resource owner, or end-user, resource owner, or end-user habits, motion data recorded (including but not limited to driving activity, walking or running activity, and the like), dwelling user, resource owner, or end-user, resource owner, or end-user activity data, WiFi access point information and the like. The server **510** can enable detailed GPS detection to verify that the dwelling user, resource owner, or end-user, resource owner, or end-user has returned to the dwelling user, resource owner, or end-user. Using this information the server **510** decides if the dwelling user, resource owner, or end-user, resource owner, or end-user is returning to the dwelling user, resource owner, or end-user.

The server **510** synthesizes the configuration data (which can include thresholds and probabilities) with the activity data on the service and determines if the dwelling user, resource owner, or end-user, resource owner, or end-user is returning to the dwelling user, resource owner, or end-user. In the case where there are multiple geo-fences, e.g., more than just inner geo-fence **512**, the server **510** can decide multiple times if this is true in order to determine if the dwelling user, resource owner, or end-user, resource owner, or end-user is returning to the dwelling user, resource owner, or end-user. Bluetooth is activated on the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile phone to search for the dwelling user, resource owner, or end-user lock. When the lock is detected the server **510** connects to it, establishes a secure connection, unlocks door **12**, and can notify the dwelling user, resource owner, or end-user, resource owner, or end-user via mobile device **210** that door **12** has been unlocked.

System **10** receives notifications when the dwelling user, resource owner, or end-user, resource owner, or end-user has left and entered the area as defined by the one or more geo-fences **512**, **514**. At least a portion of the Bayesian algorithm, or other filtering algorithm, filters spurious location events that can be erroneous due to environmental or technical glitches, which as a non-limiting example can be a power outage. If system **10** sees that the dwelling user, resource owner, or end-user, resource owner, or end-user has entered the dwelling user, resource owner, or end-user area less than 90 seconds after entering, then system **10** can discard it.

In one embodiment of the present invention first and second geo-fences **512** and **514** are provided, also known as inner and outer geo-fences **512** and **514**. When first and second geo-fences **512** and **514** are exited, after a certain time period door **12** is then locked or a notification is sent warning the user door **12** at the user's dwelling has been unlocked. If the first geo-fence **512** is only exited system **10** may not lock door **12**. User's mobile device **210** can also enable detailed GPS detection to verify that the user has left the area.

57

In one embodiment of the present invention an automatic-unlock uses a mobile device's **210** location features to tell when the mobile device **210** dwelling user, resource owner, or end-user, resource owner, or end-user has left a geo-fence **512** and/or **514** in an area outside of a dwelling user, resource owner, or end-user. As a non-limiting example, this can be considered the first geo-fence **512**, second geo-fence **514**, both or just one. At a later time when the mobile device **210** dwelling user, resource owner, or end-user, resource owner, or end-user returns to its neighborhood an app of the mobile device **210** prepares to connect to the intelligent door lock system **10** via the system server **510** and/or cloud based server **510**. As the mobile device **210** owner approaches an entrance to the dwelling user, resource owner, or end-user the intelligent lock system **10** can automatically unlocks a door **12**.

In one embodiment the automatic unlock feature is on the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile device **210** app that uses the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile device **210** location features to tell when dwelling user, resource owner, or end-user, resource owner, or end user leaves. At this point the first geo-fence **512** is triggered. As a result of dwelling user, resource owner, or end-user, resource owner, or end user leaving the geo-fence **512/514** is triggered, and when dwelling user, resource owner, or end-user, resource owner, or end user is at the dwelling user, resource owner, or end-user, the geo-fence **512/514** is on and the Bluetooth is also on. At entrance to the first geo-fence **512**, the Bluetooth is turned on and the Bluetooth creates a signal to unlock system **10**. There is no need for dwelling user, resource owner, or end-user, resource owner, or end user to utilize its mobile device **210**.

When dwelling user, resource owner, or end-user, resource owner, or end user enables an automatic unlock of system **10** it may view its current location on a map as a means of visual verification that it is being set up properly. A home threshold region can be viewed, adjusted and the like by the dwelling user, resource owner, or end-user, resource owner, or end-user. In one embodiment dwelling user, resource owner, or end-user, resource owner, or end user implicitly indicates that when it has left the area then upon returning to the area dwelling user, resource owner, or end-user, resource owner, or end user would like their door **12** unlocked as dwelling user, resource owner, or end-user, resource owner, or end user approaches the door **12**. A home threshold region is provided that can be adjusted larger to compensate for poor GPS positioning. As a non-limiting example this can be caused when the dwelling user, resource owner, or end-user is in a remote region and the like.

As dwelling user, resource owner, or end-user, resource owner, or end user exits the dwelling user, resource owner, or end-user the first and second geo-fences **512** and **514** are exited. When this occurs, after a certain time period the door **12** is then locked. If the first geo-fence **512** is only exited system **10** may not lock the door **12**. The system **10** server **510** and/or cloud based server **510** can enable detailed GPS detection to verify that dwelling user, resource owner, or end-user, resource owner, or end user has left the area.

In one embodiment as dwelling user, resource owner, or end-user, resource owner, or end user enters the second geo-fence **514** an app on the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile device **210** wakes up and examines a host of data to determine whether to activate Bluetooth of the mobile device **210** and search for the door **12** to unlock. As non-limiting examples the data can include: the amount of time spent outside the

58

first or second geo-fence **512**, **514** respectfully, time of day, past dwelling user, resource owner, or end-user, resource owner, or end-user activity patterns, motion data recorded device (including driving activity, walking or running activity), WiFi access point information. The system **10** server **510** and/or cloud based server **510** can enable detailed GPS detection to verify that dwelling user, resource owner, or end-user, resource owner, or end user has returned home.

Using this information the system **10** server **510** and/or cloud based server **510** determines if dwelling user, resource owner, or end-user, resource owner, or end user is returning to the dwelling user, resource owner, or end-user. The dwelling user, resource owner, or end-user, resource owner, or end-user's mobile device **210** synthesizes configuration data (which can include thresholds and probabilities) with activity data on the system **10** server **510** and/or cloud based server **510** and determines if dwelling user, resource owner, or end-user, resource owner, or end user is returning to the dwelling user, resource owner, or end-user. Mobile device **210** can employ this logic multiple times over a period of time as input data changes to decide whether mobile device **210** believes that the user is returning home.

The Bluetooth is activated on the dwelling user, resource owner, or end-user, resource owner, or end-user's mobile phone to search for the dwelling user, resource owner, or end-user, resource owner, or end-user's dwelling user, resource owner, or end-user lock. When the lock is detected the system **10** server **510** and/or cloud based server **510** connects to it, establishes a secure connection, unlocks door **12**, and notifies dwelling user, resource owner, or end-user, resource owner, or end user via notification that door **12** has been unlocked.

System **10** receives notifications when dwelling user, resource owner, or end-user, resource owner, or end user has left and entered the area. Spurious location events are filtered out that could be erroneous due to environmental or technical glitches. As a non-limiting example this can be a power outage. If the system sees that dwelling user, resource owner, or end-user, resource owner, or end user has entered the home area less than a selected period of time a debounce signal, from the system **10** server **510** and/or cloud based server **510**, 90 seconds after entering, then the system may discard it.

In one embodiment a debounce is provided by the system and/or cloud based server **510** such that dwelling user, resource owner, or end-user, resource owner, or end user leaves and is outside a geo-fence **512**, **514** (a second geo-fence as described hereafter), and the like for a selected period of time in order for an entrance to trigger a Bluetooth connection to the lock to unlock of door **12**. With the debounce the dwelling user, resource owner, or end-user, resource owner or end user can leave, come back quickly, and then is not considered to have left the dwelling user, resource owner, or end-user. The use of the debounce eliminates false unlocking of system **10** when dwelling user, resource owner, or end-user, resource owner, or end user is at the dwelling user, resource owner, or end-user home and artifacts from cell tower, WiFi and other systems that provide assistance providing location data are faulty and incorrectly assert that the user has left the dwelling user, resource owner, or end-user.

In one embodiment intelligent door lock system **10** is configured to have a remotely operable lock **12** at a dwelling accessible by the user. The intelligent door lock system **10** configured to be in communication with a server **510**. The user communicates with the server **510** using the user's mobile device **210** and the server **510** is configured to

transmit a crossing notification message in response to tracking the user's mobile device **201** and enable an automatic unlock feature of the lock using the server **510** and a mobile device **201** App.

In one embodiment a second geo-fence **514** is provided, or the first geo-fence **512** is extended, for early entrance detection. The second geo-fence **514** is larger than the first geo-fence **512** and can be of different geometric configurations. The second geo-fence **514** increases/decreases and a combination of both, the first geo-fence **512**. In one embodiment the second geo-fence is adjustable **514**. The second geo-fence **514** increases sensitivity.

In another embodiment a map view position and radius adjustment is made. In this embodiment system **10** does not unlock until after the mobile device **210** owner has manually performed an unlock.

In one embodiment data is collected and false motion data is filtered out.

In one embodiment mobile device **210** stores data over time as events occur. As non-limiting examples this can include, motion data, geo-fence regions exited or entered and the like. Any configuration of parameters from the server **510** can be downloaded at any time as well. Each geo-fence **510/512** is associated with a lock or door **12**. When a geo-fence area has been entered, the mobile device **201** collects the history of crossing geo-fences for that lock and creates a data set along with other live data, including but not limited to WiFi access point data, accumulated motion data during the time the user was outside a geo-fence fence, time of day, and other information. That information is processed based on the configuration data, producing a limited set of parameters types and associated values. These are fed to a decision making engine of mobile device **210**, which may be a Bayesian filter, and the like, that associates different probability value on each of these parameters, and combines it to form a single yes no decision on whether the user desires its door **12** is locked or unlocked. In the unlocked case, the device enables Bluetooth and begins trying to connect to the dwelling user, resource owner, or end-user lock. When the dwelling user, resource owner, or end-user lock is connected the device unlocks door **12**. In the case of the lock being bridged to the internet via Wireless access point Bluetooth is not used, the mobile device **210** connects to the bridge **11** via Network system. The lock is then locked or unlocked remotely by mobile device **210** using the Network System to a cloud service and/or system **10** backend that establishes a secure connection to the lock. In this embodiment there is a wall wart, doorbell, or another device that includes Bluetooth and is within an appropriate distance of door **12**.

In one embodiment security system **10(a)** is an intelligent security system that produces fewer false alarms or alerts. In one embodiment security system **10(a)** uses motion detection device **10(g)** to look for an actual person, which can be, an outline of a person at or near the door **12**, or other entrance to the dwelling. If motion detection device **10(g)** with camera **10(c)** sees a person, an outline of a person and the like, an alert is sent to the dwelling user, resource owner, or end-user mobile device **210**. The dwelling user, resource owner, or end-user views the video, picture and the like taken by camera **10(c)** and has various options including but not limited to: determine who is at the dwelling; communicate with the person who is at the dwelling; notify authorities of an unwanted person at the dwelling; unlock or lock the dwelling including but not limited to door **12**, a window and the like in order to allow or deny access to the person.

In one embodiment intelligent security system **10(a)** is split into a plurality of parts. As a non-limiting example intelligent security system **10(a)** can be split into: (i) an intelligent security system **10(a)** used to wake up the motion detection device **10(g)** and prepare for a video call; (ii) detect motion, with or without person detection; (iii) detect people at the dwelling without linger detection; and (iv) detect people at the dwelling and linger.

As a non-limiting example intelligent security system **10(a)** triggers motion detection device **10(g)** to wake up and turn on camera **10(c)** when motion is triggered. As a non-limiting example one use of this capability is to prepare for a video call in response to a doorbell press. When motion is detected, camera **10(c)** takes a still image to be used in a notification and make other preparations for a video call to the dwelling occupant in the event that the doorbell is pressed, or the dwelling occupant initiates a video call in response to a motion/person notification. As a non-limiting example motion detection device **10(g)** does whatever is possible ahead of time to speed up the perceived connection time of notice to the dwelling occupant which can be a video call, and the like.

When the short range motion detection device **10(g)** is triggered, the doorbell wakes up and camera **10(c)** takes a still image. A countdown to a timeout begins.

If the doorbell button is pressed before the timeout, a doorbell press notification is sent to dwelling user, resource owner, or end-user and a motion notification is not sent.

If the doorbell button is not pressed before the timeout, a motion notification can be sent.

As a non-limiting example mobile device OS motion notification can include the following text or equivalent: "Motion detected at <door name> at <house name>". The in-app accept/reject UI can be the same as for a button press except with the following differences: (i) it can have the following text: "Motion detected at <door name> at <house name>"; (ii) it will display the still image taken by camera **10(c)** when it was awakened by the motion it detected; (iii) red X and green check icons can remain the same but the labels below them can be "Dismiss" and "View", note: the timeout can be a variety of different times. As a non-limiting example it can be 5-10 second range, although other ranges can be utilized; (iv) a motion event can be put into an activity feed with the image taken in response to the motion, and this can happen regardless of whether the dwelling user, resource owner, or end-user responds to the notification.

In one embodiment if the dwelling user, resource owner, or end-user taps "View" to initiate a video call, an on-demand video session can be put into the activity feed. In this embodiment, there can be two events in the activity feed, one for the motion and one for the video call.

In one embodiment toggle settings can be provided in settings to enable/disable motion alerts. In one embodiment person notifications are provided. As a non-limiting example the person notifications are sent to the dwelling user, resource owner, or end-user.

As a non-limiting example person detection can be based on whether there is a person in the frames captured by the camera **10(c)** which can be included with the doorbell as described above. As a non-limiting example there is detection of via camera **10(c)**/doorbell and the like. In one embodiment there is not checking that the same person is being detected in every frame captured by camera **10(c)**.

When either the long range or short range motion sensor **10(g)** is triggered, camera **10(c)**/doorbell wakes up, takes a still image and initiates intelli-vision analytics. Camera

61

10(c)/doorbell can continue taking still images, save them, and feed them to the server, see FIGS. 25(a)-(e).

A countdown to a timeout can begin.

If the doorbell button is pressed before the timeout, a doorbell press notification can be sent, and no motion or person notification is sent.

If the doorbell button is not pressed before the timeout, either a motion notification or a person notification is sent.

If the analytics engine does not detect a person at any time during the timeout period, a motion notification is sent as described above.

If the analytics engine does detect a person, at any point during the timeout, a person notification is sent.

In one embodiment the mobile device OS notification can have the following text: "Person detected at <door name> at <house name>". In one embodiment the in-app accept/reject UI is the same as for door bell press, but may not have the following text: "Person detected at <door name> at <house name>". In one embodiment it can display the first image and the server/analytics engine tags as containing a person. The red X and green check icons can remain the same, but the labels below them can be "Dismiss" and "View".

The timeout period is then selected. As a non-limiting example this can be 5-10 seconds. It will be appreciated that other periods of time can be used for the timeout period.

In one embodiment Person events are placed in the Activity Feed the same way described above for motion events. In one embodiment the motion and person events are mutually exclusive. For a given activation of the intelligent security system 10(a), a person event or motion event can be placed into the Activity Feed, not both.

In one embodiment on demand video session events in the Activity Feed work the same as described above. As a non-limiting example these events can include addition to motion/person events.

In one embodiment there are two toggles in settings, one to enable/disable motion notifications, and the other to enable/disable person notifications. The defaults for these settings need to be determined. In one embodiment the person notifications can be on by default and motion notifications can be off by default.

Lingering notifications can be selected.

In one embodiment "Person Notifications" only detects whether a frame contains a person. It does nothing to track a person from frame to frame, or to determine if it's the same person in each frame. The result is that on a busy street where people frequently pass by the doorbell and or camera 10(c), the person notification feature is triggered, even though no one person is actually lingering in front of door 12. This issue can be addressed using the server/analytics engine's ability to detect lingering. From a user perspective, the feature can operate the same way and can surface the same settings. In one embodiment system 10 only sends person notifications when we detect that the same person is lingering in front of the door 12, window and the like. This provides better accuracy and fewer false person notifications.

In one embodiment camera 10(c) is coupled to an analytics engine. The analytics engine includes a person detection module which wakes camera 10(c) from the sleep state earlier.

In one embodiment intelligent security system 10(a) has reduced latency. In one embodiment the reduced latency is achieved by the analytics engine/person detection module. As a person approaches and comes to door 12 or any dwelling available entrance, including but not limited to a window, and the like, camera 10(c) is activated with or with

62

pressing the doorbell, wakes up from a sleep mode and the intelligent security system 10(a) is ready to go. Motion detection device 10(g), with or without analytics engine, wakes camera 10(c) up from the sleep mode and when the person is at the entrance of the dwelling the camera is set to take a picture, video with one or more frames, and the like. This reduces latency and improves speed. As a non-limiting example activation of camera 10(c) integrated or not integrated with the doorbell, from the pressing of the doorbell, when the doorbell and camera 10(c) are coupled and/or integrated to the sending of a picture or video to a mobile device 210 can be on the order of 30 seconds or less. This results from motion detection device 10(g) starting recognition of a person or an object at an earlier time. When the person is at the dwelling entrance camera 10(c) is then is set to start recording.

In one embodiment security system 10(a) has reduced power consumption. In this embodiment the security system 10(a) camera 10(c) is only started up from its sleep state to a wake state when something passes by and/or is in a selected distance relative to camera 10(c) which is detected by. More particularly the person detection module is used along or without motion detection device 10(g) to determine if something or someone passes by. In response to that determination, if a person or something similar to a person passes by, camera 10(c) is awakened and put in an active state. This results in a savings of power because camera 10(c) is in active step less often.

Encryption

In one embodiment a server 510 is in communication with the intelligent door lock system 10. In another embodiment instead of the intelligent door lock system 10, a low power device that communicates with small payloads is used instead of the intelligent door lock system 10. In one embodiment low power means running off of consumer batteries. In one embodiment a small payload is 12 bytes or less. The server 510 has a handshake key (Kh) with a key exchange that provides for a communication session between a mobile device 210 and the intelligent door lock system 10. The mobile device 210 does not have the (Kh). A user mobile device 210 is in communication with the server 510 and uses a cipher to provide a secured communication between the mobile device 210 and the intelligent door lock system 10.

In one embodiment cipher block chaining is utilized to provide the secured communication.

In one embodiment an initialization is done when the intelligent door lock system 10 and/or the lock 22 is created. In one embodiment communication is initialized by generating a session nonce (Ns) on the mobile device 210. In one embodiment the session nonce is encrypted using a handshake key (Kh) that is at the server 510. In one embodiment the (Kh) is a shared secret known to intelligent door lock system 10 and to an entity encrypting the nonce that includes the server 510. In one embodiment the intelligent door lock system 10 modifies the nonce and returns a modified value to the mobile device 210. In one embodiment

An entity with the server 510 has the (Kh) decrypts a session key and the mobile device 210 uses that to encrypt subsequent communication, wherein the intelligent door lock system 10 generates the session key and provides for an unlocking of a lock 22 at the intelligent door lock system 10.

In one embodiment when the intelligent door lock system 10 is assembled a random number is provisioned on the mobile device 210.

63

In one embodiment the (Kh) can be common to all locks 22 of a given lock model.

In one embodiment the (Kh) is a shared secret between the server 510 and all locks 22 of a model class.

As a non-limiting example the (Kh) is exchanged for a unit-specific unit key (Kh). As a non-limiting example the (Kh) is a random number.

In one embodiment the server 510 associates the (Kh) with a unique identification of a lock 22 of the intelligent door lock system 10. In one embodiment the cloud service responds to the mobile device 210 with a unit key encrypted using an open block cipher. As a non-limiting example the server 510 sends the (Kh) to the lock 22 and the lock 22 stores it in a non-volatile memory, with the (Ku) used as a handshake key. In one embodiment the mobile device 210 generates two random numbers that are communicated with the server 510 to create one/half of the (Kh). In response the server 510 generates one or more random numbers to create a second half of the (Kh). For each of session the server 510 creates a different set of one or more numbers for the second half of the (Kh).

In one embodiment in response to the server 510 creating the second half of the (Kh) the mobile device 210 functions without having the (Kh)

In one embodiment the mobile device 210 generates a checksum. In one embodiment the mobile device 210 creates a request for a private communication and in response the server 510 creates a second half of the (Kh) without the mobile device 210 having the (Kh). In response to transmission of the (Kh) a session is initiated that provides for unlocking of the door 12. A production of half of the (Kh) by the mobile device 210 is an initiation of a request for packet for a private communication and thereafter a validation of a source is conducted.

As a non-limiting example a third party mobile device 210 never has on its mobile device 210 an encryption for the intelligent door lock system 10.

Encryption Example 1

Terms

The following terms are used: encryption function: e (key, block)

decryption function: d(key, block)

random number function r(number)

The handshake key will be called Kh

The generated session key, Ks

A 32-bit constant used during Initialization, IC

A 32-bit constant used during Initialization, RC

mFooBar means foobar for the mobile device 210

IFooBar means foobar for the lock (it's an el not an eye).

Communication is initialized by generating a session nonce (Ns) on the mobile device 210. This session nonce is encrypted using a handshake key (Kh). The handshake key is a shared secret known to the lock and to the entity encrypting the nonce. The lock then modifies the nonce and returns the modified value to the mobile device 210. The entity that has the handshake key then decrypts the session key and the mobile device 210 uses that to encrypt subsequent communication.

Factory Initialization

When the lock is assembled, a 16-byte key (random number) can be provisioned on the device. This key can be common to all locks of a given model and referred to as model key (Km). The model key is a shared secret between the August API server 510 and all locks of that model class.

64

It can only be used at setup or factory reset time to exchange a new, unit-specific unit key (Ku).

Owner Initialization

When the owner of the lock sets it up for the first time, or after a factory reset of the lock, the mobile application can generate a 16-byte random number and send it to the server 510. This number can be referred to as the unit key (Ku). The API server 510 associates the unit key with the unique ID of the lock. This is a shared secret between the lock and the service.

After associating the unit key with the lock, the service responds to the mobile device 210 with the unit key encrypted using AES CBC. The mobile device 210 then sends this key to the lock and the lock stores it in non-volatile memory. This unit key can be used as the handshake key (Kh) in future communications.

The mobile device 210 generates a key, sends it to the service server 510 for encryption.

When a mobile device 210 has authenticated against the August REST API and has been authorized to communicate with a particular lock, it generates two 32-bit random values: mRand1 and mRand2, which combined constitute the session nonce (Ns).

It also generates a 32-bit checksum that is the 2s-complement sum for the two random numbers.

The service server 510 encrypts the key, sends encrypted data back to mobile device 210.

This set of numbers is transmitted to the server 510, where it is encrypted using the handshake key:

Kh=Ku
mKeyExchange=e(Kh, {mRand1, mRand2, mKeyChecksum})

mKeyExchange is then returned to the mobile device 210.

The mobile device 210 transmits the key to the low power device where data is validated. When the mobile device 210 receives the encrypted key from the server 510, it sends it to the lock. The lock then decrypts the message:

Kh=Ku
{mRand1', mRand2', mKeyChecksum' }=d(Kh, mKeyExchange)

The lock confirms the validity of the message by summing the four decrypted 32-bit values:

mKeyCheck=mRand1'+mRand2'+mKeyChecksum'

If mKeyCheck is non-zero, the lock disconnects from the mobile devices 210.

Lock Generates Key, Encrypts, and Sends Data

The lock now generates two 32-bit random values: 1Rand1 & 1Rand2, and a 32-bit 1KeyChecksum that is the 2s-complement sum of 1Rand1, 1Rand2, and the 32-bit constant LX.

1KeyChecksum=232-(LX+1Rand1+1Rand2)

The values are combined into a message and encrypted using the unit key, Kh.

1KeyExchange=e(Kh, {LX, 1Rand1, 1Rand2, 1KeyChecksum})

The value 1KeyExchange is sent to the mobile device 210.

Mobile device 210 transmits the encrypted key to service server 510 which validates it. The mobile device 210 sends 1KeyExchange to the server 510, which uses the unit key to decrypt it:

Kh=Ku
{LX', 1Rand1', 1Rand2', 1Keychecksum' }=d(Kh, 1KeyExchange)

The server 510 confirms the validity of the message by summing the four decrypted 32-bit values:

1KeyCheck=LX'+1Rand1'+1Rand2'+1KeyChecksum'

If 1KeyCheck is not zero, the server **510** returns an error to the mobile device and the mobile device **210** disconnects from the lock. If 1KeyCheck is zero, the server **510** returns 1Rand1' and 1Rand2' to the mobile device **210**.

The mobile device **210** generates the candidate session key, mSK:

$$\text{mSK} = \{\text{mRand1}, \text{mRand2}, \text{1Rand1}', \text{1Rand2}'\}$$

The mobile device **210** initiates a test communication.

The mobile device **210** then generates two 32-bit random values: iRand2 and iRand2', as well as another 32-bit value, iInitChecksum, that is the two's-complement of the two random values, and a 32-bit constant, IC:

$$\text{iInitChecksum} = 232 - (\text{IC} + \text{iRand1} + \text{iRand2})$$

The values are combined into a message and encrypted using the candidate session key, mSK.

$$\text{iInitComm} = e(\text{mSK}, \{\text{IC}, \text{iRand1}, \text{iRand2}, \text{iInitChecksum}\})$$

The mobile device **210** then transmits iInitComm to the lock.

The low power device validates an initialization command. When the lock receives the candidate session key from mobile device, it generates its candidate session key (1SK) from the generated and shared random values and decrypts the message:

$$\text{1SK} = \{\text{mRand1}', \text{mRand2}', \text{1Rand1}, \text{1Rand2}\}$$

$$\{\text{IC}', \text{iRand1}', \text{iRand2}', \text{iInitChecksum}'\} = d(\text{1SK}, \text{iInitComm})$$

The low power device confirms the validity of the message by summing the four decrypted 32-bit values:

$$\text{iInitCheck} = \text{ic}' + \text{iRand1}' + \text{iRand2}' + \text{iInitChecksum}'$$

If iInitCheck is non-zero or if IC' does not match the expected value for IC, the lock disconnects from the mobile device **210**. If the message is valid, communication is now considered secure and future messages can be decrypted using $K_s = \text{1SK}$.

The intelligent door lock **10** system sends an Initialization response.

The intelligent door lock **10** now generates a 32-bit value, rInitChecksum, that is the two's-complement sum of the random values iRand1', iRand2', and a 32-bit constant, RC.

$$\text{rInitChecksum} = 232 - (\text{RC} + \text{iRand1}' + \text{iRand2}')$$

The values are combined into a message and encrypted using the session key K_s :

$$\text{rInitResponse} = e(K_s, \{\text{RC}, \text{iRand1}', \text{iRand2}', \text{rInitChecksum}'\})$$

The value rInitResponse is sent to the mobile device **210**.

The mobile device **210** validates initialization response.

When the mobile device **210** receives rInitResponse, it decrypts it using mSK:

$$\{\text{RC}', \text{iRand1}'', \text{iRand2}'', \text{rInitChecksum}'\} = d(\text{mSK}, \text{rInitResponse})$$

The mobile device **210** confirms the validity of the message by summing the four decrypted 32-bit values:

$$\text{rInitCheck} = \text{RC}' + \text{iRand1}'' + \text{iRand2}'' + \text{rInitChecksum}'$$

If all of the conditions below are met, communication is considered secure and future messages can be encrypted or decrypted with $K_s = \text{mSK}$:

$$\text{rInitCheck} = 0$$

$$\text{RC}' = \text{RC}$$

$$\text{iRand1}'' = \text{iRand1}$$

$$\text{iRand2}'' = \text{iRand2}$$

If any of the above conditions are not met, the mobile device **210** disconnects from the low power device.

The low power device can have three states that define its security level:

Not Connected

Connected Not Secure

Connected Secure

The security level defines the behavior of the service characteristics. When advertising, the device is in the Not Connected state. After a connection is established, the peripheral is in the Connected Not Secure state. After the handshake process is complete, the device enters the Connected Secure state.

In one embodiment firmware updates are provided to intelligent door lock system from server. In one embodiment a dwelling Bluetooth device **21** sends a packet with or without acknowledgement. As a non-limiting example server **510** sends updates to mobile device **210** or Bluetooth to WiFi bridge **11**. Mobile device **210** or WiFi bridge **11** then sends the updates to a Bluetooth device **21** at the dwelling, e.g., to lock system **10**.

In one embodiment the update is sent as a payload. As a non-limiting example a payload of N bits is sent. As a non-limiting example the payload can be 96 bits. Each packet includes n number of bits. Each bit has a traceable marker. As a non-limiting example the payload is sent without a response. This increases the speed of sending the payload. As a non-limiting example the speed can be a bit packet three times a second.

Even though the payload is sent without a response, in response to receipt of the payload a notification is required from lock system **10**. In one embodiment the notification is a bit mask of how many bits of the payload were received.

Typically not all of the bits are received by lock system **10**. Notification is then provided to server of the non-received bits. When there is 0 in the bit mask that portion not received is then resent. A payload is resent until all of the bits have been received.

In this manner a backfill of non-received bits is processed. This is repeated until all of the original bits in the update have been received.

With subsequent updates a checksum is made on the payload and a checksum is sent back.

In this embodiment intelligent door lock system **10** receives fast updates of firmware where there have been slow connections.

In one embodiment intelligent door lock system with server **510** notifies the dwelling user, resource owner, or end-user, hereafter (dwelling user) the status of the intelligent door lock system batteries **21**. As a non-limiting example intelligent door lock system **10** reports its battery voltages to server **510**, and then the server **510** determines battery life, more particularly when the batteries will die and need to be changed. Notification is sent to the dwelling user.

In one embodiment intelligent door lock system reports its voltage to server **510**. Server **510** then determines when the one or more batteries **21** are going to die. The user of is then notified of the battery **21** status and can be prompted to change the batteries **21**.

In one embodiment periodically mobile device **210** or Bluetooth to WiFi bridge **11** records the voltage every time intelligent door lock system **10** locks or unlocks. The recorded voltage is sent to server **510**. This is done on a period basis. In one embodiment a band pass filter is used in processing the recorded voltage.

In one embodiment server **510** initially runs a linear regression on the data for a period of a number of different months which can be from 1-6 months. Thereafter server **510** runs a cubic regression on the data set of the recorded voltages.

The server **510** pulls from memory the average lifetime of a battery **21**. As a non-limiting example in the beginning if the recorded voltage is above 5 volts, and a certain threshold

67

is reached, a cubic regression predicts immediate death of batteries **21**. A comparison is run of battery **21** status now and when the battery **21** was charged. When the cubic ticks back up then use linear regression is applied. Linear regression works up to a certain range of battery life. As a non-limiting example linear regression is applied up to 75% of battery life.

In one embodiment server **510** initially runs linear regression on the data set of recorded voltages. Cubic regression is applied. When the cubic regression diverges server **510** switches back to linear regression and this is used as the death date.

The data check of battery life voltages can be for any number of times, including periodically. As a non-limiting example the data check of battery voltages is run every day.

In one embodiment when Bluetooth-WiFi bridge **11** is used the battery check voltage is done automatically.

In one embodiment the dwelling user is notified when a door **12**, window, opening and the like of a dwelling is manually opened. Manually opened includes operation of the keypad, of a key, by any mechanism which can not notify server **510** directly. This in effect provides a notification of "I need attention".

In one embodiment every time the lock **24** is operated a log of that event is put in the lock's memory. One or more bits of this bit information is received by the wireless bridge **11**, which processes all of the logs. This provides a notification of "I need attention". A push notification is sent to the dwelling user.

In another embodiment server **210** can sent a similar push notification also be sent to a third party that provides a service to the dwelling user, including but not limited to an alarm company, which then can cause the alarm to not be activated, and an a notification is also provided to the notification to the dwelling user, which as a non-limiting example can be via mobile device **210**.

The wireless bridge **11** processes all of the logs.

In one embodiment of the, illustrated in FIG. **38**, security system **610**, which can be **11(a)** is configured to provide that a camera sensor **612** and video encoder **614**, which can be video apparatus **10(c)** and camera **10(c)** begins before motion detection begins by motion detection device **10(g)**. In one embodiment video encoder **614** is coupled to a buffer **616**, resources **618** and a PIR **620**. As a non-limiting example video apparatus **10(c)** records all of the time. When events occur there is an existing buffering of an important selected video. In one embodiment the video apparatus **10(c)**, is a camera, including but not limited to a doorbell camera **10(c)**. In one embodiment video apparatus records a buffer for a selected amount of time, which as a non-limiting example can be for 20 seconds or less, 10 seconds, 5 seconds, 2-5 seconds and the like. When motion is detected at a time TO the last buffer is marked for saving. New-upcoming videos are recorded until there is a complete motion. In one embodiment a video file is appended which includes the pre-TO buffer of x seconds to create a video file that shows action starting at time TO-x. In one embodiment security system includes the motion detection device **10(g)**.

In one embodiment the buffer size is selected based on analytics and a determination can be made as to when to start the video. As a non-limiting example motion can be triggered by a PR sensor, but once motion is triggered, the security system **11(a)** analyses the x-second video buffer to pixel changes This provides that the beginning of the video is aligned with the first pixel change. In another embodiment, motion speed is evaluated so that the slower the event, the longer the buffer time x is.

68

Referring to FIG. **39** one embodiment of intelligent door lock system **10** with a magnetic sensor **712** is illustrated. In one embodiment, a magnet sensor **712**, which can be a magnetometer **712**, is provided. As a non-limiting example magnetometer **712** provides a reading that can be used to determine if door **12** is being opened as illustrated in FIG. **40**. Magnetometer **712** can be used in conjunction with sensor **16**. Magnetometer **712** detects movement of the door **12**. In one embodiment sensors **16** and **712** are combined in order to determine an angle in which door **12** is open as illustrated in FIGS. **41(a)**-**42(d)**.

As set forth above sensor **16**, which can be an accelerometer, can be used to detect rotation of the lock device **22** and the magnetometer **712** can detect the movement of the door **12**. The value of knowing the magnetic sensor provides door ajar status, sensor **16** is used to determine if bolt/lock **24** is extended or retracted.

As non-limiting examples, the magnetometer **712** can be: (i) a vector magnetometer **712** that measures vector components of a magnetic field; (ii) a total field magnetometer **712** or scalar magnetometer **712** to measure a magnitude of the vector magnetic field; and the like.

In one embodiment the magnetometer **712** is an absolute magnetometer **712** that measures an absolute magnitude or vector magnetic field, using an internal calibration or known physical constants of the magnetic sensor. In one embodiment magnetometer **712** is a relative magnetometer **712** that measures magnitude or vector magnetic field relative to a fixed but un-calibrated baseline, and can be used to measure variations in magnetic field.

In one embodiment, illustrated in FIG. **42**, the magnetometer **712** is integrated with intelligent door lock system **10**. In one embodiment magnetometer **712** is integrated with the lock of lock device **22** in a single device, which as non-limiting example can be included as a magnetometer integrated circuit **714** on the printed circuit board described above PCB disclosed in Paragraph 00141.

In one embodiment the magnetometer **712** is used to determine if the door **12** is actually closed or ajar. This information, as well as information provided by sensor **16** is used to determine whether or not door **12** is secured. As illustrated in FIG. **43** non-limiting examples include but not are not limited to if the door **12** is: ajar and locked; not secured; ajar and unlocked; not secured; closed and unlocked; closed and locked; secured; and the like.

As a non-limiting example the magnetometer **712** measures magnetism, including but not limited to magnetization of a magnetic material, strength of a magnetic field, a direction of the magnetic field at a point in space. A magnetic material **716** can be existing in the door **12**; be at the door frame; can be added which as a non-limiting example can be a discreet magnet **716** coupled to the door frame; be a magnetic strike plate; and the like, as illustrated in FIG. **42**.

In one embodiment the magnetometer **712** communicates wirelessly, which as a non-limiting example can be RF and the like. In one embodiment magnetometer **712** receives power from power source, battery **50**.

The performance and capabilities of the magnetometer **712** can perform and/or include all or a portion of the following:

Sample rate—the number of readings given per second.

The inverse is the cycle time in seconds per reading.

Sample rate is important in mobile magnetometers **712**; the sample rate and the vehicle speed determine the distance between measurements.

Bandwidth or bandpass—characterizes relative to how well the magnetometer **712** tracks rapid changes in magnetic field.

Have or not have onboard signal processing, and without onboard bandwidth can be determined by a Nyquist limit set by sample rate.

Smoothing or averaging over sequential samples to achieve a lower noise in exchange for lower bandwidth.

Have resolution with the smallest change in magnetic field the magnetometer **712** can resolve. As a non-limiting example the magnetometer **712** can have a resolution smaller than an amount of smallest change desired to be observed to avoid quantization errors.

Absolute error—a difference between the averaged readings of a magnetometer **712** in a constant magnetic field and true magnetic field.

Drift—a change in absolute error over time.

Thermal stability—the dependence of the measurement on temperature. It is given as a temperature coefficient in units of nT per degree Celsius.

Noise—the random fluctuations generated by the magnetometer **712** sensor or electronics, which as a non-limiting example can be given in units of $\sqrt{\text{nT}/\sqrt{\text{Hz}}}$ where frequency component refers to the bandwidth.

Sensitivity—the larger of the noise or the resolution.

Heading error—the change in the measurement due to a change in orientation of the instrument in a constant magnetic field.

A dead zone—the angular region of magnetometer **712** orientation in which the instrument produces poor or no measurements.

Gradient tolerance—the ability of a magnetometer **712** to obtain a reliable measurement in the presence of a magnetic field gradient.

In one embodiment, illustrates in FIG. **44**, intelligent door lock system **10** includes a camera **810**, which as a non-limiting example can be camera **10(c)** or a different camera **810**, with a wide field of view. As a non-limiting example camera **810** can be a camera similar commercially available one such as Arlo, Blink, Zmodo, Nest Cam and the like. Camera **810** can be coupled to intelligent door lock system **10** as disclosed above. As non-limiting examples the field of view can be up to 180 degrees, at least 180 degrees and the like. With the wide field of view the wide field camera **810** allows for viewing everything at the interior of the dwelling, at the exterior of the dwelling and the like. This is useful for viewing any approach to the dwelling, any activity at the interior of the dwelling in the field of view and the like. This can provide for monitoring a person and viewing their activities at or near the dwelling, both internally and at the exterior, viewing a locking and/or locking of the door **12**, viewing of an attempt to tamper with the door or lock, exiting the dwelling, the activities of a person at the exterior or interior of the dwelling and the like.

Additionally the wide field camera **810** can be a doorbell, included as a doorbell and also allow for a resident to see and speak with a third party viewed by the wide field camera **810**. In one embodiment the wide field camera **810** is included with a keypad, can be a keypad and the like, allowing a person to enter a code. In one embodiment the wide field camera **810** also provides for detecting if the door has been closed and can serve as a door sensor, e.g., to determine open or closed door status. As a non-limiting example, the open close status of the door can be used to operate the lock, or trigger alarms.

In one embodiment the wide field camera **810** captures a follow-through video of a third party, who may or may not have been given access to the dwelling by the dwelling occupant, by using the wide field camera **810**, that can be coupled to door **12**, and moves with door **12** as door **12** moves. Because the camera moves with the door, this allows wide angle camera **810** to capture view and capture activities and third party movement inside and outside of the dwelling, all with a single camera system.

Referring to FIGS. **45** and **46**, in one embodiment a camera, which can be camera **10(c)**, camera **810** or a separate camera **812**, is configured to define a safe zone in which an occupant, a non dwelling occupant third person and the like, is allowed into the dwelling. As a non-limiting example an area of the safe zone can be created by the dwelling occupant or its designee. Camera **812** is coupled to and/or included in intelligent door lock system **10** as disclosed above.

In one embodiment the safe zone is delimited by one or more virtual fences **814**, **816** and the like, which the occupant of the dwelling can define, and in the event the one or more virtual fences **814** and **816** are broken, different alerts can be activated, including but not limited a local alarm, notification to the occupants mobile device, vocal warning, a communication with authorities, and the like.

In one embodiment the one or more virtual fences are multi-layer fences that can define multiple concentric zones. This allows for tracking of the occupant, a non-occupant that is granted access to the dwelling by the occupant, including but not limited to a delivery person, housekeeper and the like. In one embodiment, the order in which concentric fences are broken allows tracking of a movement as either towards door **12**, or away from door **12**. As a non-limiting example breaking the first fence **814** can result in a vocal warning, while breaking second fence **816** can result in an alarm being activated, and breaking a third fence can result in a call to authorities.

More particularly as illustrated in FIG. **45** video processing of camera **814** images, and analysis of the virtual fences being broken can be in the Cloud that can be in communication with the dwelling occupants mobile device, an optional local speaker or alarm, as well as an optional authority/police or security contact.

As illustrated in FIG. **46**, in one embodiment the occupant of the dwelling can provide programmed fences **814**, **816** and so forth. The occupant can also provided programmed alerts, including but not limited to notifications, vocal warnings, sounding of alarms, calls to authorities including police, security companies and the like. When camera **812** detects motion, a video analysis is performed to determine if there is a breach of fences **814**, **816** and the like. If a determination is made of a breach, an alert is triggered. A movement analysis can also be made of a person relative to the dwelling, either at the interior, exterior of the dwelling and like. A determination can also be made relative the direction of the movement, e.g., towards the inside or outside of the dwelling. Thread alert levels can be increased, or decreased. Alerts can be made according to the occupants programming.

Referring to FIGS. **47(a)** and **(b)** in one embodiment a camera, which can be camera **10(c)**, camera **812**, and the like, communicates with intelligent door lock system **10** and uses data from lock device **22** to decide to record video or not, including if the door **12** is locked/unlocked or opened/closed. Using information from the door **12** status, e.g., locked or un-locked, the camera **10(c)** begins recording as soon as the door is open until it is closed and locked. The

lock communicates directly to the camera 10(c). As a non-limiting example the camera 10(c) can communicate via Bluetooth.

As a non-limiting example information is used from the open or closes status of the door 12. In one embodiment camera 10(c) begins recording as soon as the door 12 is open and can continue recording until the door 12 is closed. In one embodiment the camera 10(c) continues recording until the door is closed and locked. In one embodiment camera (10c) is a doorbell camera.

In one embodiment the lock communicates information to the camera (10c) that includes multiple status data. As a non-limiting example the multiple status data can include at least one of, if the door 12 is open or closed and if the lock device 22 is locked or unlocked, and the like.

In one embodiment the camera 10(c) uses input from any of the sensors at the dwelling, or included in the intelligent door lock system 10, to decide to begin recording or not.

In one embodiment the intelligent door lock system 10 is retrofitted to an existing lock system. FIG. 47(a) illustrates one embodiment with four cameras 10(c) communicating via RF and Bluetooth. FIG. 47(b) illustrates one embodiment with a camera 10(c) communicating via communication device 40 and a server that is coupled to an image sensor/lens.

In one embodiment a plurality of cameras, which can be camera 10(c), camera 812, a doorbell camera and the like, along with a dwelling occupants mobile device 210, communicate with each other, as well as communicate with lock device 22, which as a non-limiting example can be via Bluetooth, as well as via WiFi to the server in cloud lock access services infrastructure, FIGS. 25(a)-(e). In one embodiment of a camera includes Bluetooth. As a non-limiting example the plurality of cameras 10(c) communicates from one camera 10(c) to another way, which in one embodiment is the next camera 10(c) the next one via the internet and server in cloud lock access services infrastructure. One camera (10c) opens up and or starts the next camera 10(c) the next way is to communicate via the internet and a server, to provide that video turns one camera 10(c) and so on. The dwelling occupant can be on its mobile device 210 to watch what is going on. In this manner a delivery person, and or any third party is always being viewed.

In one embodiment multiple cameras 10(c) can be set along an expected path of the dwelling. As a non-limiting example a third party delivery person can recorded, or other third party, is observed and watched along a desired path as the third party approaches the dwelling, is in the interior the dwelling, and exits the dwelling.

The foregoing description of various embodiments of the claimed subject matter has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the claimed subject matter to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Particularly, while the concept "component" is used in the embodiments of the systems and methods described above, it will be evident that such concept can be interchangeably used with equivalent concepts such as, class, method, type, interface, module, object model, and other suitable concepts. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the relevant art to understand the claimed subject matter, the various embodiments and with various modifications that are suited to the particular use contemplated.

What is claimed is:

1. A system comprising:

an intelligent door lock system coupled to a door, the intelligent door lock system comprising a door status device coupled to a drive shaft of a lock device, the door status device determining lock or unlock status of a lock of the door;

a plurality of cameras configured to operate in a first state and a second state, wherein cameras of the plurality of cameras are configured to record when in the first state and not to record when in the second state; and

at least one processor configured to:

send a command to a first camera of the plurality of cameras instructing the first camera to enter the first state and begin recording;

subsequent to the first camera entering the first state, detect motion of a moving object in a field of view of the first camera of the plurality of cameras;

in response to detection of the motion of the moving object in the field of view of the first camera, send a command to a second camera of the plurality of cameras instructing the second camera to enter the first state to begin recording, wherein the second camera is located inside of a building comprising the door and the second camera comprises a field of view being a greater distance from the door than the field of view of the first camera;

subsequent to the second camera entering the first state, detect, with the second camera, motion of the moving object within the field of view of the second camera;

based on the motion of the moving object within the field of view of the second camera, determine that the moving object has moved away from the door; in response to determining that the moving object has moved away from the door, determine whether the moving object has exceeded a scope of access for the moving object; and

transmit an alert in response to determining that the scope of access has been exceeded.

2. The system of claim 1, wherein the processor is configured to select which camera of the plurality of cameras is the second camera based at least in part on a direction in which the moving object moves outside of the field of view of the first camera.

3. The system of claim 1, wherein the door status device comprises a position sensor coupled to the drive shaft, the position sensor being configured to sense a change in position of the drive shaft, the change in position of the drive shaft indicating a change in lock or unlock status.

4. The system of claim 3, wherein each camera of the plurality of cameras is configured to operate in a lower power mode and a higher power mode and the processor is configured to send a start-up command to the first camera instructing the first camera to operate in the higher power mode and record in response to an indication from the door status device of a change in position of the drive shaft.

5. The system of claim 4, wherein the processor is configured to send a shut-off command to each camera of the plurality of cameras instructing each of the plurality of cameras to enter the second state to stop recording and enter the lower power mode in response to an indication from the door status device that the door is locked and closed.

6. The system of claim 4, wherein the higher power mode comprises the first state and the lower power mode comprises the second state.

73

7. The system of claim 1, wherein the processor is centrally located on a server and the at least one processor is configured to communicate with each of the plurality of cameras.

8. The system of claim 1, wherein the at least one processor comprises a first processor located on the first camera and a second processor located on the second camera, and the first processor is configured to communicate directly with the second processor.

9. The system of claim 1, wherein the second camera is configured to respond to the command sent to the second camera by, when the second camera is in the second state, transitioning from the second state to the first state to begin recording.

10. The system of claim 1, wherein the at least one processor is further configured to determine whether the moving object has crossed one or more virtual fences, the one or more virtual fences delimiting one or more zones at least partially within the field of view of the first camera and/or the second camera.

11. The system of claim 1, wherein the at least one processor is configured to determine whether the moving object is moving towards the door or is not moving towards the door at least in part by determining a direction of motion of the moving object.

12. The system of claim 1, wherein:

the at least one processor is further configured to, based on an identity of the moving object, determine the scope of access for the moving object.

13. The system of claim 12, wherein the at least one processor is configured to identify the moving object at least in part by identifying the moving object as a building occupant from a set of one or more building occupants or as a non-building occupant.

14. The system of claim 13, wherein the scope of access for the non-building occupant is less than a scope of access for a building occupant.

15. The system of claim 1, wherein:

the field of view of the first camera comprises a first region and the field of view of the second camera comprises a second region located further from the door than the first region;

the scope of access for the moving object includes the first region and excludes the second region; and

determining whether the moving object has exceeded the scope of access for the moving object comprises determining whether presence of the moving object in the second region in the field of view of the second camera exceeds the scope of access for the moving object.

16. The system of claim 1, wherein the alert comprises an alarm.

17. A method for monitoring a path of a moving object using a system comprising an intelligent door lock system coupled to a door and comprising a door status device coupled to a drive shaft of a lock device, the door status device determining lock or unlock status of a lock of the door, a plurality of cameras configured to operate in a first state and a second state, wherein cameras of the plurality of cameras are configured to record when in the first state and not to record when in the second state, and at least one processor, the method comprising:

sending a command to a first camera of the plurality of cameras instructing the first camera of the plurality of cameras to enter the first state and begin recording;

subsequent to the first camera entering the first state, detecting motion of the moving object in a field of view of the first camera of the plurality of cameras;

74

sending a command to a second camera of the plurality of cameras instructing the second camera to enter the first state to begin recording in response to detection of motion of the moving object in the field of view of the first camera, wherein the second camera is located inside of a building comprising the door and the second camera comprises a field of view being a greater distance from the door than the field of view of the first camera;

subsequent to the second camera entering the first state, detecting, with the second camera, motion of the moving object within the field of view of the second camera;

based on the motion of the moving object within the field of view of the second camera, determining that the moving object has moved away from the door;

in response to determining that the moving object has moved away from the door, determining whether the moving object has exceeded a scope of access for the moving object; and

transmitting an alert in response to determining that the scope of access has been exceeded.

18. The method of claim 17, further comprising:

before sending the command to the second camera, selecting which camera of the plurality of cameras is the second camera based at least in part on a direction in which the moving object is moving in the field of view of the first camera.

19. The method of claim 17, wherein the at least one processor is centrally located on a server and the at least one processor is configured to communicate with each of the plurality of cameras.

20. The method of claim 17, wherein the at least one processor comprises a first processor located on the first camera and a second processor located on the second camera, and the first processor is configured to communicate directly with the second processor.

21. The method of claim 17, wherein the command causes the second camera to enter the first state to begin recording.

22. At least one non-transitory computer-readable medium storing instructions that, when executed by at least one processor of a system, the system comprising an intelligent door lock system coupled to a door and comprising a door status device coupled to a drive shaft of a lock device, the door status device determining lock or unlock status of a lock of the door, a plurality of cameras configured to operate in a first state and a second state, wherein cameras of the plurality of cameras are configured to record when in the first state and not to record when in the second state, and the at least one processor, cause the system to perform a process comprising:

sending a command to a first camera of the plurality of cameras instructing the first camera to enter the first state and begin recording;

subsequent to the first camera entering the first state, detecting motion of a moving object in a field of view of the first camera of the plurality of cameras;

sending a command to a second camera of the plurality of cameras instructing the second camera to enter the first state to begin recording in response to detection of motion in the field of view of the first camera, wherein the second camera is located inside of a building comprising the door and the second camera comprises a field of view being a greater distance from the door than the field of view of the first camera;

75

subsequent to the second camera entering the first state, detecting, with the second camera, motion of the moving object within the field of view of the second camera;

based on the motion of the moving object within the field of view of the second camera, determining that the moving object has moved away from the door;

in response to determining that the moving object has moved away from the door, determining whether the moving object has exceeded a scope of access for the moving object; and

transmitting an alert in response to determining that the scope of access has been exceeded.

23. The at least one non-transitory computer-readable medium of claim 22, further comprising:

before sending the command to the second camera, selecting which camera of the plurality of cameras is the

76

second camera based at least in part on a direction in which the moving object is moving in the field of view of the first camera.

24. The at least one non-transitory computer-readable medium of claim 22, wherein the at least one processor is centrally located on a server and the at least one processor is configured to communicate with each of the plurality of cameras.

25. The at least one non-transitory computer-readable medium of claim 22, wherein the at least one processor comprises a first processor located on the first camera and a second processor located on the second camera, and the first processor is configured to communicate directly with the second processor.

26. The at least one non-transitory computer-readable medium of claim 22, wherein the command causes the second camera to enter the first state to begin recording.

* * * * *