US 20130149130A1

(19) **United States**

(12) **Patent Application Publication**

Hasting et al.

(10) **Pub. No.: US 2013/0149130 A1**

(43) **Pub. Date: Jun. 13, 2013**

(54) **FAN HUB FRAME FOR DOUBLE OUTLET GUIDE VANE**

(71) Applicant: **General Electric Company**, Schenectady, NY (US)

(72) Inventors: **William Howard Hasting**, Cincinnati, OH (US); **Courtney James Tudor**, Cincinnati, OH (US)

(73) Assignee: **GENERAL ELECTRIC COMPANY**, Schenectady, NY (US)

(21) Appl. No.: **13/652,949**

(22) Filed: **Oct. 16, 2012**

Related U.S. Application Data

(60) Provisional application No. 61/568,976, filed on Dec. 9, 2011.

Publication Classification

(51) **Int. Cl.**
F01D 25/00 (2006.01)

(52) **U.S. Cl.**
USPC **415/208.1**

(57) **ABSTRACT**

A fan hub frame comprises a circular hub having an opening extending axially wherein an engine core is capable of being positioned, the circular hub having a radially outer surface, the radial outer surface having a plurality of cradles, each of the cradles having a lower surface and fillets disposed between the lower surface and upwardly extending sidewalls, the cradles capable of receiving a double outlet guide vane.





FIG. 1



FIG. 2



FIG. 4



FIG. 3



FIG. 6



FIG. 5


200
204
308
312
306
206
208
210
312

FIG. 8


204
312
312
306
208
308
210
206
202
200

FIG. 7


100
200
104
210
202
204
210
306
216
216
220
220
218
102
206
220
220
218
220

FIG. 9



FIG. 10



FIG. 11


412
314
308
208
213
200
209
209
311
324
316
312
322
318
210
202
204
314
306
200
307
316
307
206
330
318
207
312
320
207
211
420
424
416
420
428
410
428
426
426
422
426
419
416
418
420
426
428
426
419

FIG. 12



FIG. 13



FIG. 14

FAN HUB FRAME FOR DOUBLE OUTLET GUIDE VANE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This nonprovisional application claims priority to and benefit under 35 U.S.C. §119(e) to U.S. Provisional Application Ser. No. 61/568,976, filed on Dec. 9, 2011, the entire contents of which are herein incorporated by reference.

BACKGROUND

[0002] The disclosed embodiments generally pertain to gas turbine engines. More particularly present embodiments relate to the structure of double fan outlet guide vanes and structural components of a quick engine change assembly including the double outlet guide vanes.

SUMMARY

[0003] An embodiment of the present invention provides a double outlet guide vane assembly for a gas turbine engine. The assembly has a first guide vane having a first end, a second end opposed to the first end, and a second guide vane having a first end, a second end opposed to its first end. A first end structure spans between the first guide vane first end and the second guide vane first end. A second end structure spans between the first guide vane second end and the second guide vane second end. The first guide vane, the second guide vane, the first end structure, and the second end structure are integrally formed together to form a double vane with a continuous outer surface, and a continuous inner surface.

[0004] An outlet guide vane assembly for a gas turbine engine comprises a first guide vane having a first end, a second end opposed to the first end, a second guide vane having a first end, a second end opposed to the first end, a first end structure spanning between the first guide vane first end and the second guide vane first end, and a second end structure spanning between the first guide vane second end and the second guide vane second end, wherein the first guide vane, the second guide vane, the first end structure, and the second end structure are integrally formed together to form a double vane having a first end and a second end opposed to the first end, and wherein the double vane has a continuous outer surface and a continuous inner surface.

[0005] A double outlet guide vane comprises a first curved guide vane and a second curved guide vane arranged in radially adjacent fashion, each of said first and second curved guide vanes having a pressure side, a suction side, a leading edge and a trailing edge, a first end structure spanning between the first guide vane and the second guide vane at a first end of the first and second guide vanes, a second end structure extending from the first vane toward said second vane at second ends of said first and second guide vanes, the first and second end structures joined at fillets to the first and second guide vanes, a flowpath defined between the first and second curved guide vanes and the first end and the second end, wherein a primary load path between a fan hub frame and forward engine mount is defined through the double outlet guide vane.

[0006] A doublet guide vane, comprises a first end structure having a radially inner surface and a radially outer surface, a second end structure spaced from the first end structure, the second end structure having a second radially inner surface and a second radially outer surface, a first guide vane having a first leading edge, a first trailing edge and first pressure and suction sides extending between the first leading and trailing edges, a second guide vane having a second leading edge, a second trailing edge and second pressure and suction sides extending between the second leading and trailing edges, the first and second end structures joining the first and second guide vanes at fillets, the doublet guide vane being capable of carrying a load between the forward engine core and the forward engine mount.

[0007] A quick engine change assembly, comprises a first circular frame member, a plurality of doublet supports spaced about the first circular frame member, the doublet supports being contoured along the axial direction, a flow surface defined between the plurality of doublet supports and, a plurality of cradles, each of the cradles including the doublet supports, the doublet supports from a lower portion of the cradle to the flow surface.

[0008] A quick engine change assembly, comprises a continuous circular frame having a first ring and a second ring, a cradle formed axially between the first ring and the second ring, the cradle having a radially inner portion and fillets extending radially outward from the radially inner portion, the fillets rising toward a flow path surface disposed adjacent the cradle.

[0009] A quick engine change assembly comprises a circular frame formed of at least one circular ring, cradles extending in an axial direction for receiving a fan double outlet guide vane, the cradles including a plurality of supports for the fan double outlet guide vane, a flow surface disposed between adjacent cradles and extending in an axial direction, fastener apertures extending through the circular frame in an axial direction capable of connection to a fan hub frame.

[0010] A fan hub frame comprises a circular hub having an opening extending axially wherein an engine core is capable of being positioned, the circular hub having a radially outer surface, the radial outer surface having a plurality of cradles, each of the cradles having a lower surface and fillets disposed between the lower surface and upwardly extending sidewalls, the cradles capable of receiving a double outlet guide vane.

[0011] A fan hub frame comprises a circular hub having a radially outer surface and a radially inner opening wherein a propulsor may be positioned, a plurality of cradles circumferentially spaced along the radially outer surface of the circular hub, each of the plurality of cradles defined by fillets capable of receiving a double outlet guide vane, a plurality of fastener apertures extending in a radial direction through the cradles.

[0012] A structural platform comprises a first end, a second end, a first side wall and a second side wall, a platform body extending between the first end and the second end and further between the first side wall and the second side wall, a first fillet joining the first side wall and the platform body, a second fillet joining the second side wall and the platform body, the sidewalls being curved.

[0013] The structural platform, comprises a first side wall extending between a first end and a second end, a second side wall extending between a first end and a second end, a platform body extending between the first side wall and the second side wall, and from the first end to the second end, a fillet disposed between each of the first sidewall and the second side wall, the first side wall and the second side wall curved between the first end and the second end, the curvature approximating a curvature of an airfoil surface.

BRIEF DESCRIPTION OF THE ILLUSTRATIONS

[0014] Embodiments of the invention are illustrated in the following illustrations.

[0015] FIG. **1** is a side section view of an exemplary turbine engine.

[0016] FIG. **2** is a perspective view of a fan hub frame assembly.

[0017] FIG. **3** is a perspective view of a double outlet guide vane detailing the inner features of a radially inward end of the double outlet guide vane and the outer features of a radially outward end of the double outlet guide vane.

[0018] FIG. **4** is a perspective view of the double outlet guide vane detailing the inner features of a radially outward end of the double outlet guide vane and the outer features of the radially inward end of a double outlet guide vane.

[0019] FIG. **5** is a perspective view of a double outlet guide vane detailing the inner features of a radially inward end of a double outlet guide vane and the outer features of a radially outward end of a double outlet guide vane, with both ends having a structural platform therein.

[0020] FIG. **6** is a perspective view of a double outlet guide vane detailing the inner features of a radially outward end of the double outlet guide vane and the outer features of a radially inward end of the double outlet guide vane, with both ends having a structural platform therein.

[0021] FIG. **7** is an exploded assembly illustration of the embodiments shown in FIGS. **5** and **6**.

[0022] FIG. **8** is an exploded assembly illustration of the embodiments shown in FIGS. **5** and **6**.

[0023] FIG. **9** is a perspective illustration of a radially inward end of a double outlet guide vane and a structural platform therein assembled to a fan hub frame.

[0024] FIG. **10** is a perspective illustration of a radially outward end of a double vane and a structural platform therein assembled to a fan case or aft fan case.

[0025] FIG. **11** is a perspective view of an aft fan case assembly.

[0026] FIG. **12** is a partially exploded view of the aft fan case assembly of FIG. **11**.

[0027] FIG. **13** is a side section view of a forward portion of a gas turbine engine.

[0028] FIG. **14** is a partially exploded side section view of the forward engine portion shown in FIG. **13**.

DETAILED DESCRIPTION

[0029] Reference now will be made in detail to embodiments provided, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation, not limitation of the disclosed embodiments. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present embodiments without departing from the scope or spirit of the disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to still yield further embodiments. Thus it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

[0030] Referring to FIGS. **1-14**, various embodiments of a gas turbine engine **10** are depicted having a double outlet guide vane with structural platforms. These structures may, but are not required to, be utilized with a quick engine change assembly which allows rapid removal of a propulsor. The double outlet guide vanes may be formed of lightweight materials while still providing a loadpath for the engine to the engine mount. Various improvements are described herein.

[0031] As used herein, the terms "axial" or "axially" refer to a dimension along a longitudinal axis of an engine. The term "forward" used in conjunction with "axial" or "axially" refers to moving in a direction toward the engine inlet, or a component being relatively closer to the engine inlet as compared to another component. The term "aft" used in conjunction with "axial" or "axially" refers to moving in a direction toward the engine nozzle, or a component being relatively closer to the engine nozzle as compared to another component.

[0032] As used herein, the terms "radial" or "radially" refer to a dimension extending between a center longitudinal axis of the engine and an outer engine circumference. The use of the terms "proximal" or "proximally," either by themselves or in conjunction with the terms "radial" or "radially," refers to moving in a direction toward the center longitudinal axis, or a component being relatively closer to the center longitudinal axis as compared to another component. The use of the terms "distal" or "distally," either by themselves or in conjunction with the terms "radial" or "radially," refers to moving in a direction toward the outer engine circumference, or a component being relatively closer to the outer engine circumference as compared to another component.

[0033] As used herein, the terms "lateral" or "laterally" refer to a dimension that is perpendicular to both the axial and radial dimensions.

[0034] Referring initially to FIG. **1**, a schematic side section view of a gas turbine engine **10** is shown having an engine inlet end **12** wherein air enters the propulsor **13** which is defined generally by a compressor **14**, a combustor **16** and a multi-stage high pressure turbine **20**. Collectively, the propulsor **13** provides thrust or power during operation. The gas turbine **10** may be used for aviation, power generation, industrial, marine or the like. Depending on the usage, the engine inlet end **12** may alternatively contain multi-stage compressors rather than a fan. The gas turbine **10** is axis-symmetrical about engine axis **26** or shaft **24** so that various engine components rotate thereabout. In operation air enters through the air inlet end **12** of the engine **10** and moves through at least one stage of compression where the air pressure is increased and directed to the combustor **16**. The compressed air is mixed with fuel and burned providing the hot combustion gas which exits the combustor **16** toward the high pressure turbine **20**. At the high pressure turbine **20**, energy is extracted from the hot combustion gas causing rotation of turbine blades which in turn cause rotation of the shaft **24**. The shaft **24** passes toward the front of the engine to continue rotation of the one or more compressor stages **14**, a turbofan **18** or inlet fan blades, depending on the turbine design.

[0035] The axis-symmetrical shaft **24** extends through the through the turbine engine **10**, from the forward end to an aft end. The shaft **24** is supported by bearings along its length. The shaft **24** may be hollow to allow rotation of a low pressure turbine shaft **28** therein. Both shafts **24**, **28** may rotate about the centerline axis **26** of the engine. During operation the shafts **24**, **28** rotate along with other structures connected to the shafts such as the rotor assemblies of the turbine **20** and compressor **14** in order to create power or thrust depending on the area of use, for example power, industrial or aviation.

[0036] Referring still to FIG. **1**, the inlet **12** includes a turbofan **18** which has a plurality of blades. The turbofan **18**

is connected by the shaft **28** to the low pressure turbine **19** and creates thrust for the turbine engine **10**. The low pressure air may be used to aid in cooling components of the engine as well.

[0037] A typical gas turbine engine generally possesses a forward end and an aft end with its several components following inline therebetween. An air inlet or intake is at a forward end of the engine. Moving toward the aft end, in order, the intake is followed by a compressor, a combustion chamber, a turbine, and a nozzle at the aft end of the engine. It will be readily apparent from those skilled in the art that additional components may also be included in the engine, such as, for example, low-pressure and high-pressure compressors, high-pressure and low-pressure turbines, and an external shaft. This, however, is not an exhaustive list. An engine also typically has an internal shaft axially disposed through a center longitudinal axis of the engine. The internal shaft is connected to both the turbine and the air compressor, such that the turbine provides a rotational input to the air compressor to drive the compressor blades. A typical gas turbine engine may also be considered to have an outer circumference with a central longitudinal axis therethrough.

[0038] Referring to FIG. **2**, a perspective view of a fan frame assembly **100** is shown. The fan frame assembly **100** is generally provided with a first circular frame member or fan hub frame **102**, a second circular frame member or fan case **104**, and a plurality double outlet ("doublet") guide vanes **200** disposed in a radial array about the hub frame **102** and fan case **104**. The assembly **100** has a central longitudinal axis **101** that disposed therethrough that is generally the longitudinal axis of a gas turbine engine **26** (FIG. **1**) with which the assembly **100** would be associated. The fan hub frame **102** may also be known by other names such as an intermediate compressor case. The doublet guide vanes **200** provide the load path from the fan hub frame (and thereby the propulsor **13**) to the forward engine mount (not shown).

[0039] Referring to FIGS. **3** and **4**, opposing perspective views of a double outlet guide vane **200** are provided. The double vane **200** is provided with a first guide vane **202**, and a second guide vane **204**. A first end structure **206** spans between a radially inward first end of the first guide vane **202** and a radially inward first end of the second guide vane **204**. A second end structure **208** spans between a radially outward second end of the first guide vane **202** and a radially outward second end of the second guide vane **204**. The first guide vane **202**, the second guide vane **204**, the first end structure **206**, and the second end structure **208** are integrally formed together to form a double vane **200** with a substantially continuous outer surface, and a substantially continuous inner surface. A flow path **210** for a fluidized flow is provided therethrough.

[0040] The double outlet guide vane **200** may be manufactured of a variety of materials, such as, for example, composite materials, or metals. One such material may be a fiber composite, such as a carbon fiber composite laminate. The doublet vane **200** may be manufactured in a way that the fibers are continuously and uninterruptedly wound around the doublet vane **200**. The method to manufacture such a structure may be accomplished by, for example, resin transfer molding with dry fiber, automated fiber placement, or a hand layup process with pre-impregnated fiber. The doublet vane **200** may also be manufactured from metal, such as, for example, aluminum alloys, titanium alloys, and other known alloys suitable for use in a gas turbine engine.

[0041] Referring now to FIGS. **5** and **6**, a double outlet vane **200** is shown in perspective view with first and second structural platforms **306**, **308** abutting an inner surface of the first and second end structures **206**, **208**. The first and second structural platforms **306**, **308** have a surface that faces the inner surface of the first and second end structures **206**, **208** and generally matches the geometry and contours of the inner surface of the first and second end structures **206**, **208**. The structural platforms **306**, **308** are utilized to spread loads experienced by the double vanes **200** to the surrounding hardware to which they are attached, such as the fan hub frame **102** and the fan case **104**.

[0042] Referring now to FIGS. **7**, an exploded assembly view of an inner surface of a double vane first end structure **206** and a first structural platform **306** is provided. FIG. **8** is an exploded assembly view of an assembly of an inner surface of a double vane second end structure **208** and a second structural platform **308**. When assembled to the fan hub frame **102** and the fan case **104**, the first end structure **206** is disposed between the first structural platform **306** and the fan hub frame **102** (see FIG. **9**). Likewise, the second end structure **208** is disposed between the second structural platform **308** and the fan case **104** (See FIG. **10**). The first and second end structures and their respective structural platforms may be the fan case assembly by fasteners **312** or by any known bonding methods. The first and second end structures and their respective structural platforms may be mounted to one another by any known bonding methods. The platforms **306**, **308** provide rigidity and stability for the doublets **200** while allowing the doublet **200** to be formed of lightweight materials.

[0043] Referring now to FIGS. **9** and **10**, perspective views of the assembly **100** are shown. The plurality of double vanes **200** are provided assembled to a fan hub frame **102** and a fan case **104**. In FIG. **9**, the first end structure **206** is mounted to a radially outer surface of the fan hub frame **102**. The radially outer surface **216** of the fan hub frame **102** may be provided with a cradle-like structure **218** that conforms to match the geometry and contours of the outer surface of the first end structure **206**. The cradles **218** include fillets **220** which form supports, along with the sidewall of the cradle **218** for the double vane outlets **200**. In FIG. **10**, the second end structure **208** is mounted to a radially inner surface of the fan case **104**. The radially inner surface of the fan case **104** is shown without a cradle-like structure. However, a cradle-like structure may be utilized. Still, the inner surface of the fan case **104** conforms to the outer surface of the second end structure **208**. In both configurations, the first and second end structures **206**, **208** are disposed between the first and second structural platforms **306**, **308** and the fan hub frame **102** and fan case **104**, respectively. As shown, the hub frame **102** is provided with cradle-like structures, and the fan case **104** is not. However, either of the hub frame **102** or the fan case **104** may be provided with or without a cradle-like structure in any combination.

[0044] Referring now to FIG. **11**, a perspective view of an aft fan case assembly **400** is depicted. According to previous embodiments, the double outlet or doublet guide vanes **200** were positioned in a fan hub frame **102** (FIG. **2**). However, the present embodiment provides that the doublet guide vanes **200** are disposed in a quick engine change configuration. As with the previous embodiment, the instant embodiment provides a primary loadpath through the aft fan case assembly **400** and the double outlet guide vanes **200**. The aft fan casing assembly **400** includes a first circular frame **410** at an inner

radius and a second circular frame **412** at an outer radius wherein the doublet guide vanes **200** are disposed therebetween. According to some embodiments, first circular frame **410** is a quick engine change ring and the second circular frame **412** is a fan case, such as an aft fan case, for example. The quick engine change ring **410** allows for easy separation, generally shown in FIG. **14**, of the doublet vane assembly from the propulsor components **13** which are generally in need of more frequent maintenance. The propulsor components **13** may be worked on for scheduled or unscheduled maintenance. Meanwhile a second propulsor may be installed in the quick engine change ring **410** so that the engine can be returned to service sooner, if desired.

[0045] The quick engine change ring **410** includes a first ring **422** and a second ring **424**. The rings **422**, **424** are spaced axially in the direction of the engine axis **26** and may each be formed of one piece continuous or multiple pieces connected together. Extending in an axial direction between the first ring **422** and the second ring **424** are a plurality of flow surfaces **416**. The flowpath surfaces **416** improve air movement across the rings **422**, **424** while allowing the weight saving design of the two rings rather than a solid or other otherwise heavier structure. Extending in the axial direction between the first and second rings **422**, **424** and further between the flow surfaces **416** are cradles **418**. Each of the cradles **418** includes a curved portion where the lowermost portion of the cradle curves up toward the flow surface **416**. A stationary doublet guide vane **200** is positioned within each of the cradles **418** in order to turn an airflow in a desirable manner through portions of a gas turbine engine **10**. Flowpaths are created between each of the vanes **202**,**204** and between the cradles **418**. According to this embodiment, the propulsor **13** may be quickly disconnected for ease of removal and replacement allowing continued service of the engine.

[0046] Referring now to FIG. **12**, an exploded perspective view of a portion of the aft fan case assembly **400** is shown. The quick engine change ring **410** is shown at the bottom of the figure. Extending between the first ring **422** and the second ring **424** are flow surfaces **416**. These provide a flow or control surface along which air can move as it passes between the doublet guide vanes **200**. The flow surface **416** depicted is curved between the forward ring **422** and the rear ring **424**. The flow surface may also be curved in the circumferential direction. The flow surface **416** may alternatively be linear between the first and second rings **422**, **424** and/or the circumferential direction. The quick engine change ring **410** includes the cradles **418** between the flow surfaces **416**. The cradles **418** receive the radially inner ends of the doublet guide vanes **200** and have curved surfaces **420** which transition between the cradles **418** and flow surfaces **416**. Within the cradles **418** along the first ring **422** and second ring **424** are fastener apertures **419** which extend through the rings or hoops in a generally axial direction relative to the engine. The apertures **419** are used to connect the doublet guide vanes **200** to the quick engine change ring **410**. The first and second rings also include apertures **426**, **428** respectively allowing quick disconnect of the aft fan case assembly **400** from the propulsor **13**, as will be discussed further herein.

[0047] Beneath the doublet guide vane **200** is the cradle **418** which provides a seating location for the doublet vane **200**. The cradle **418** has a U-shaped cross-section which curves moving in the axial direction from the first ring **422** to the second ring **424**. The cradles **418** extend up the sides of the vane **200** to support the lowed ends of the guide vanes **202**, **204**. The height at which the flowpath surfaces **416** are disposed and curved portions **420** causes cradling of the doublet vane **200**. This cradling provides additional support and limits flexing of the doublet vane **200** during operation. The cradle **418** further comprises curved surfaces or fillets to improve rigidity of the circular frame **310** and improve manufacturability.

[0048] The outer ring or fan case **412** is also exploded to depict the radially outer ends of the doublet vanes **200**. The fan case **412** receives fasteners which extend through an upper surface **208** of the doublet guide vane **200** and through the fan case **412**. Each doublet vane **200** is connected to the fan case assembly **400** by sandwiching the doublet guide vane **200** between platform **308** and the fan case **412**.

[0049] Also shown within the assembly **400** are structural platforms **306**, **308**. At the radially inner end of the doublet guide vane **200** is an inner structural platform **306** which sandwiches the first or inner end **206** of the vane **200**. The structural platform **306** has a lower surface which curves near lateral sides to match the curvature of **207** the first end **206**. The platform **306** is positioned above the lower portion **206** of the doublet vane **200** which is above the circular quick engine change ring **410**. According to the embodiment depicted, the platform **306** has first and second bolt apertures **307** which are aligned with apertures **211** in the lower end **206** of the doublet vane **200**. The platform **306** and vane **200** are then bolted to the quick engine change ring **410** through apertures **419** in the first ring **422** and the second ring **424**. This sandwiches or captures the lower end **206** of vane **200** in the cradle **418** of the quick engine change ring **410**. Such construction provides various improvements over prior art designs. First the composite guide vane **200** is sandwiched between a structural platform and the quick engine change ring **410**. This provides a significant increase in stiffness. Additionally, the construction does not require any adhesive bonds which may deteriorate due to the high operating temperature of the gas turbine engine. The design also provides that there are no composite to metal transitions or integrations. Finally, the design provides greater aeromechanical margins and greater damping during operation.

[0050] Similarly, at the upper or radially outer end **208** of the guide vane **200** is the structural platform **308** which sandwiches the upper end **208** between the platform **308** and the fan case **412**. Lateral ends of the platform **308** are curved to fit against the curved ends **209** of the platforms **200**, providing structural support in at least the lateral or circumferential directions.

[0051] Each of the lower and upper end structures **206**, **208** has a radially inner and radially outer surface. Each of the structures **206**, **208** may be formed integrally with the vanes **202**, **204** or may be formed of one or more pieces which are joined with the vanes **202**, **204** to form the doublet guide vane **200**.

[0052] Referring still to FIG. **12**, structural platforms **306**, **308** are shown. The platforms **306**, **308** comprise a first end **312**, a second end **314**, a first side wall **316** and a second side wall **318**. A platform body **320** extends between the first end **312** and the second end **314** between the first side wall **316** and said second side wall **318**. A first fillet **322** joins the first side wall **316** and the platform body **320**. Similarly, a second fillet **324** joins the second side wall **318** and the platform body **320**. The sidewalls **316**, **318** are curved to correspond to the curvature of the vanes **202**, **204**. The structural platform sandwiches a doublet guide vane **200** within a cradle **418**. The

platform body **420** may further comprise a skin facing an airflow and having a smooth surface. This may be formed of composite of metal and bonded to the platforms **306**, **308**. The structural platforms **306**, **308** may be formed of one of metal, plastic or composite. The structural platforms may have first side wall and second side walls which extend in a radial direction. The first side wall **316** and the second side wall **318** may be being curved to approximate a mating airfoil surface. The platform body having a plurality of apertures **307**, **311** for receiving fasteners. Additionally, the structural platform may further comprise structural stiffeners (**330**) extending between said first and second side walls.

[0053] Means may be utilized to make connection between the exemplary embodiments of the platforms **306**, **308** to the guide vanes **200** and ring **410** and case **412**. According to exemplary embodiments, fasteners are utilized through apertures **307** and **311**. Additionally, while the inner surface of platform **306** is shown as uneven or non-smooth, an insert, skin or cover may be used to provide a smooth surface for improved airflow through the guide vane **200**. This skin or cover may be used to also cover bolt holes sandwiching the platforms **306**, **308** the doublet vanes **200** and first and second circular frame members **102**, **104** and **410**, **412**.

[0054] The quick engine change ring assembly **400** utilizes a circular frame member **410** formed according to one example of a first continuous ring **422** and a second continuous ring **424** which are positioned parallel to one another in an axial direction. The assembly **400** further comprises flow surfaces **416** which extend from the first ring **422** to the second ring **424** and between the doublet vanes **200**. The flow surfaces **416** are raised from the first and second continuous rings **422**, **424**. As a result, the cradles **418** between the flow surfaces **416** are formed wherein the doublet vanes **200** may be positioned.

[0055] Referring still to FIG. **12**, the doublet guide vanes **200** are shown. As previously described, the guide vanes **200** include first and second vanes **202**, **204** which extend from a leading edge to a trailing edge in a chord-wise direction. Each guide vane has a pressure side and a suction side. The vanes **202**, **204** are shorter at the outer diameter than the inner diameter. Additionally, the doublet guide vanes are wider in a circumferential direction at the upper end **208** than the inner end **206**. At the first, radially inner end **206**, the guide vanes **202**, **204** are joined to provide a rigid lower end. Each vanes **202**, **204** are arranged in circumferentially adjacent fashion, two per guide vane **200** according to one exemplary embodiment. Other arrangements may be utilized. The radially inner end structure **206** joins the guide vanes **202**, **204** at the radially inner end to provide rigidity. Similarly, at the opposed radially outer end **208** the guide vanes **202**, **204** are joined to provide a closed structure. At the upper end **208**, the guide vanes **202**, **204** curve **209** to join the upper end **208** similar to the curved or radius **207** at the lower end **206**. The radiuses **207**, **209** are received in correspondingly curved doublet supports **420** of the cradle **418** and the fan case **412**. These curved areas provide strength and support for the doublet guide vanes **200** and the structural platforms **306**, **308** provide further support. The doublet guide vanes **200** may be formed of metal, or composite material.

[0056] Referring again briefly to FIG. **11**, the assembly **400** includes a plurality of single vanes **500**, as opposed to the doublet guide vanes **200**. The single vanes **500** are generally formed of metal and are of higher strength than the double guide vanes **200**. The single guide vanes **500** are utilized to carry higher loads through to the engine mounts for the gas turbine engine. The vanes **500** include feet **502** which connect the vane **500** to the inner rings **422** and **424**. According to the exemplary embodiment, there are four feet **502** at the radially inner end of the vane **500**, two feet axially forward and two feet axially rearward. The radially inner feet may be connected to, for example, the fan hub frame **102**, or may be connected to a quick engine change assembly described further herein. At the outer end of the vanes **500** there are also four feet **502** (not shown) which connect the vane to the radially outer structure, for example the fan case **104**, **412**.

[0057] Referring now to FIG. **13**, a side section view of a portion of a gas turbine engine **10** is depicted. Specifically forward aft case assembly **110** is shown and the aft fan case assembly **200** is shown joined at a lug or flange connection **112**.

[0058] The forward fan case assembly **110** includes the fan **18** secured to a disc **19** and axially rearward of a spinner or cone **21**. The fan **18** and disc **19** rotate about the engine axis **26**. Aft of the fan **18** is a compressor **14** which is a part of the propulsor **13**, generally referring to all of the core components of the engine causing propulsion such as the turbine, shafts, compressor **14** which extend from the forward fan case assembly **110**, through the aft fan case assembly **200** and aft to define the gas turbine engine **10**. A booster panel **32** extends axially above the compressor **14** and connects to the quick engine change ring **410**. The booster panel **32** limits air flow in the compressor **14** from mixing with air moving through the guide vanes **200**. The guide vanes **200** extend between the quick engine change ring **410** and the aft fan case **412**.

[0059] As previously stated, the quick engine change embodiment provides for easy change engine components, specifically propulsors, which generally have fail parts and wear parts with higher maintenance requirements.

[0060] With reference now to FIG. **14**, the internal components of the of the engine propulsor **13** are disconnected from the aft fan case assembly **400**. This allows the quick change of either the fan case assembly **400** or the propulsor components **13**. Specifically, the spinner or cone **21** is removed from the forward end of the engine at the engine intake area. Next, the fan blades **18** are removed and pulled axially forward from the engine. The booster panels **32** are removed after the fan blades **18**.

[0061] With these parts removed, the axial forward and rearward bolts are removed from the quick engine change ring **410**. The axially forward fastener apertures **426** and axially rearward apertures **428** are best shown in FIG. **12**. These apertures **426**, **428** are used to connect the radially inner propulsor **13** to the radially outer quick engine change ring **410** and the outward components of the aft fan case assembly **400**. With these bolts removed from aperture **426**, **428**, the propulsor **13** can be removed in an axially rearward direction from the aft fan case assembly **400**.

[0062] Various means may be utilized to make connection between the exemplary embodiments of the platforms **306**, **308** to the guide vanes **200** and ring **410** and case **412**. According to exemplary embodiments, fasteners are utilized through apertures **307** and **311**. Additionally, while the inner surface of platform **306** is shown as uneven or non-smooth, an insert or cover may be used to provide a smooth surface for improved airflow through the guide vane **200**.

[0063] The foregoing description of structures and methods has been presented for purposes of illustration. It is not intended to be exhaustive or to limit the invention to the

precise steps and/or forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. Features described herein may be combined in any combination. Steps of a method described herein may be performed in any sequence that is physically possible. It is understood that while certain forms of an outlet guide vane with structural platforms have been illustrated and described, it is not limited thereto and instead will only be limited by the claims, appended hereto.

What is claimed is:

1. A fan hub frame, comprising:

a circular hub having an opening extending axially wherein an engine core is capable of being positioned;

said circular hub having a radially outer surface, said radial outer surface having a plurality of cradles;

each of said cradles having a lower surface and fillets disposed between said lower surface and upwardly extending sidewalls;

said cradles capable of receiving a double outlet guide vane.

2. The fan hub frame of claim **1** further comprising a plurality of apertures in said cradle for connection with said double outlet guide vane.

3. The fan hub frame of claim **2** wherein said double outlet guide vane extends from said circular hub toward a fan case.

4. The fan hub frame of claim **1** further comprising a flowpath surface on circumferential sides of said cradle.

5. The fan hub frame of claim **1** wherein said flowpath surface is curved from a forward toward an aft end of said hub frame.

6. The fan hub frame of claim **1** further wherein said cradles are spaced circumferentially about said radially outer surface.

7. The fan hub frame of claim **1**, said fan hub frame transmitting load through said cradles and double outlet guide vanes to engine mounts.

8. A fan hub frame, comprising:

a circular hub having a radially outer surface and a radially inner opening wherein a propulsor may be positioned;

a plurality of cradles circumferentially spaced along said radially outer surface of said circular hub;

each of said plurality of cradles defined by fillets capable of receiving a double outlet guide vane;

a plurality of fastener apertures extending in a radial direction through said cradles.

9. The fan hub frame of claim **8**, said cradles being curved along the axial direction from a forward to rearward end of said cradles.

10. The fan hub frame of claim **8**, said fillets being curved along the axial direction between axial forward and rearward ends.

* * * * *