

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2008258552 B2**

(54) Title
Receiving element for an implant

(51) International Patent Classification(s)
A61C 8/00 (2006.01)

(21) Application No: **2008258552**

(22) Date of Filing: **2008.06.05**

(87) WIPO No: **WO08/148843**

(30) Priority Data

(31) Number
10 2007 026 504.4

(32) Date
2007.06.05

(33) Country
DE

(43) Publication Date: **2008.12.11**

(44) Accepted Journal Date: **2013.01.10**

(71) Applicant(s)
Straumann Holding AG

(72) Inventor(s)
Bammerlin, Rainer; Guenter, Daniel

(74) Agent / Attorney
**Watermark Patent and Trade Marks Attorneys, Level 2 302 Burwood Road,
HAWTHORN, VIC, 3122**

(56) Related Art
US 2007/0072148

(12) NACH DEM VERTRAG ÜBER DIE INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT) VERÖFFENTLICHTE INTERNATIONALE ANMELDUNG

(19) Weltorganisation für geistiges Eigentum
Internationales Büro



(43) Internationales Veröffentlichungsdatum
11. Dezember 2008 (11.12.2008)

PCT

(10) Internationale Veröffentlichungsnummer
WO 2008/148843 A1

(51) Internationale Patentklassifikation:
A61C 8/00 (2006.01)

BAMMERLIN, Rainer [DE/DE]; Badhof 11/1, 79400 Kandel (DE).

(21) Internationales Aktenzeichen: PCT/EP2008/056997

(74) **Anwalt: MODIANO, Micaela Nadia**; Thierschstrasse 11, München, 80538 Deutschland (DE).

(22) Internationales Anmeldedatum:
5. Juni 2008 (05.06.2008)

(81) **Bestimmungsstaaten** (soweit nicht anders angegeben, für jede verfügbare nationale Schutzrechtsart): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Einreichungssprache: Deutsch

(26) Veröffentlichungssprache: Deutsch

(30) Angaben zur Priorität:
10 2007 026 504.4 5. Juni 2007 (05.06.2007) DE

(71) **Anmelder** (für alle Bestimmungsstaaten mit Ausnahme von US): **STRAUMANN HOLDING AG** [CH/CH]; Peter Merian-Weg 12, CH-4002 Basel, Schweiz (CH).

(72) **Erfinder; und**

(75) **Erfinder/Anmelder** (nur für US): **GUENTER, Daniel** [CH/CH]; Froburgerstr. 14, CH-4437 Waldenburg (CH).

(84) **Bestimmungsstaaten** (soweit nicht anders angegeben, für jede verfügbare regionale Schutzrechtsart): ARIPO (BW,

[Fortsetzung auf der nächsten Seite]

(54) **Title:** RECEIVING ELEMENT FOR AN IMPLANT

(54) **Bezeichnung:** AUFNAHMEELEMENT FÜR EIN IMPLANTAT




Fig. 1

(57) **Abstract:** The present invention relates to a receiving element (1) for a dental implant, comprising a first plate (3) and a second plate (6), extending perpendicular to the center axis (Z) of the receiving element (1) and designed to detachably fixate a dental implant in a stable position, wherein the plates (3, 6) are separated by an open region (5).

(57) **Zusammenfassung:** Die vorliegende Erfindung betrifft ein Aufnahmeelement (1) für ein Dentalimplantat mit einer ersten Platte (3) und einer zweiten Platte (6), die senkrecht zur Mittelachse (Z) des Aufnahmeelements (1) verlaufen und die derart ausgebildet sind, um ein Dentalimplantat lösbar in einer stabilen Lage zu fixieren, wobei die Platten (3, 6) durch einen offenen Bereich (5) getrennt sind.

WO 2008/148843 A1



GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), eurasisches (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), europäisches (AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF,

BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN,
TD, TG).

Veröffentlicht:

— mit internationalem Recherchenbericht

RECEIVING ELEMENT FOR AN IMPLANT

Field of use of the invention

The present invention relates to a receiving element for an implant, in particular for screw- or cylinder-shaped implants.

5 Such implants are already known e.g. from dental technology and are substantially similar to a screw, the apical area of the screw being inserted in a bone and the coronal area being suitable to receive a dental prosthesis. In addition, in dental surgery, different embodiments of holding elements fastened to the implant are known which, on the one hand, fix the implant into place and, on the
10 other hand, allow sterile removal from the receiving element. In addition, they also ensure that from manufacturing until surgical intervention, an implant does not come in contact with non-sterile means, such as hands. The relevant area of application for the invention is where the implants, e.g. for reasons of necessary sterile handling, may at least not directly be touched with one's hands, and where
15 secure grasping of the implants is required.

The function of such receiving elements is to transport the implant safely and provide a sterile environment for storage. To remove the implant during a surgical intervention performed under sterile conditions, the implant is taken from the receiving element which generally has a holding element fastened
20 to the implant (in the following, the combination of implant and holding element attached to it will be called implant assembly for simplification), e.g. by means of a tool applied to the implant, and the implant is subsequently placed on the prepared implant site of the patient and the holding element is removed. For further protection, it is also common to store the receiving element in a secondary
25 protection element until the time of implanting.

Prior Art

From WO98/55039, a cylindrical ampule to be inserted in an outer capsule is known, which ampule is suitable for receiving an implant. The ampule has a face region provided with a recess which is laterally open. This recess is
30 used to insert an implant assembly consisting of the implant and a holding element

5 additionally connected to the implant. The implant assembly is fixed into place in a throat of the ampule by being pressed through an opening. To achieve sufficient fixation, substantial pressure must be applied when the implant is pressed in; with a rigid structure of an ampule and a receiving element, the consequence is that the construction material is subjected to substantial stress, since the forces that occur spread both along the expansion groove and along the cylinder surface. There is a danger of cracks formation on the face side in case of pressure which is too strong, which cracks can reduce or even offset the clamping effect within the throat. Furthermore, due to the rigid construction, insertion is only possible by using great force if the recess has only a small aperture angle, since expansion can only take place within the area of the expansion groove, which is relatively narrow, and the cylinder surface further impedes expansion. An enlargement of the aperture angle of the recess facilitates insertion of the dental implant, however at the cost of a good clamping behavior, so that the implant can easily slide out of the recess and touch non-sterile surfaces. Even worse, the implant can also be damaged if, for instance, it falls down from the operating table to the floor. Also, the face side of the ampule has a relatively small cross-section, and the entire holding force between an implant and the interior of the throat is limited to this narrow area, the holding force or withdrawal force, respectively, being consequently increased by the pressure or compression, respectively, when the implant is removed from the holder. This increases the grip on the implant, making the removal process difficult to control.

25 In addition, storage over a longer time can lead to a weakening at the clamping area which, in the worst case, can cause the implant to be no longer held with full clamping force, making it oscillate within the ampule so that it can be damaged by contact with the ampule.

Furthermore, if deposited, the cylindrical ampule can move about its axis within a certain range, which makes it difficult to grip.

Summary of the invention

30 In view of the above-mentioned drawbacks of the prior art devices for receiving a dental implant, the object of the present invention is to provide a

receiving element for a dental implant which fixes a dental implant assembly in place more secure and which can better convert and carry off the forces occurring when the dental implant assembly is placed on the structure of the receiving element. Furthermore, simpler and safer handling should be provided and
5 economical manufacturing with existing techniques should be possible.

The object of the present invention is to provide a receiving element for a dental implant having improved stability and conversion of forces and which avoids the drawbacks mentioned above.

Within this aim, another object of the present invention is to provide a
10 receiving element for a dental implant which is better protected against slipping on a surface.

Another object of the present invention is that the receiving element can be handled more easily and more safely.

Another object of the present invention is that the receiving element can
15 be manufactured easily and inexpensively with well-known methods.

This aim and these and other objects to be found in the following specification are fulfilled by a receiving element for a dental implant according to Claim 1. Other advantageous embodiments of the present invention are the subject matter of the dependent claims.

20 The constructive characteristics of a substantially cylindrical receiving element according to the present invention consist in that the head area holding the receiving element is nearly uncoupled from the body so that forces occurring during removal of the dental implant from the holder through the aperture provided for this purpose are effectively diverted and/or completely eliminated.
25 The substantially square body portion is advantageously provided with an open side for easy insertion of the dental implant. Furthermore, the head area has a first surface suitable for clamping connection with a dental implant and a second surface which prevents the dental implant from touching the interior wall of the body part.

30 Furthermore, one side of the receiving element is provided with a plane surface ensuring stable positioning on a surface such as the operating table. In a

preferred embodiment, the receiving element has a plurality of reinforcing ribs in its body area which, on the one hand, reinforce the outer wall and, on the other hand, ensure a better grip.

Short description of the figures

5 Further features and advantages of the present invention as well as the operating method of the exemplary embodiments of the present invention are described below with reference to the accompanying drawings.

The accompanying drawings illustrate the present invention and, together with the specification, are used to explain the basics of the invention and
10 to enable a person skilled in the relevant art to manufacture and use the invention. For better comprehensibility, identical elements are for the most part not designated in the following figures as long as they can be clearly recognized as "repeated elements".

Therein:

15 Fig. 1 shows a side view of a receiving element for a dental implant according to an embodiment of the invention;

Fig. 2 shows a front view of a receiving element for a dental implant according to Fig. 1;

20 Fig. 3 shows a longitudinal section of a receiving element for a dental implant according to Fig. 1, taken along line A-A in the direction of the arrow;

Fig. 4 shows a longitudinal section of a receiving element for a dental implant according to Fig. 1, taken along line B-B in the direction of the arrow;

Fig. 5 shows a sectional view of a receiving element for a dental implant according to Fig. 1, taken along line F-F in the direction of the arrow;

25 Fig. 6 shows a sectional view of a receiving element for a dental implant according to Fig. 1, taken along line D-D in the direction of the arrow;

Fig. 7 shows a top view of a receiving element for a dental implant according to Fig. 1.

Description of preferred embodiments of the invention

30 Based on Fig. 1 to Fig. 7, a currently preferred embodiment of the present invention of a receiving element for a dental implant is described, which

element consists of a substantially cylindrical bottom area, a body area enclosing the dental implant and a flexible head area formed by two plates, the head area being provided with a clamping device for receiving a dental implant, which device is suitable for releasably clamping and fixing a dental implant into place.

5 Fig. 1 shows a receiving element 1 for a dental implant, the receiving element 1 basically having three portions. A first portion forming the head area consists of an approximately C-shaped, plane front face 2 comprising a first plate 3 which is suitable for fixing a dental implant (not shown) into place, as is described further in the foregoing. The first plate 3 is adjacent to an open area 5
10 surrounded by a first shoulder 4 bordering on the first plate 3 and a second shoulder 4' below it which borders on a second plate 6. The open area 5 which is preferably jaw-shaped preferably extends from its open side at a respective end of the plates 3, 6 to a theoretical center axis Z of the receiving element 1, the opening width in the area of the center axis Z being advantageously smaller than on the
15 outer side. The jaw-like area 5 achieves a mechanical uncoupling of the plates 3, 6 and of the first plate 3 from the body 7, respectively.

On the side which is not provided with the jaw-like area 5, a chamfer 17 from an outer edge of the plane front face 2 to a plane head area 16 is provided, the plane head area 16 bordering on a plane head edge 15 which borders both on
20 the head area 16 and on a body 7 of the receiving element 1. Part of the second plate 6 which borders on the jaw-like open area 5 and on the second shoulder 4', respectively, is substantially plane. The part of the second plate 6 which is below the jaw-like area 5 then borders on a second portion formed by the body 7 and provided with a plurality of symmetrically arranged reinforcing ribs 8. These
25 protrude from the surface of the body 7 and are preferably arranged equidistant from one another. In the preferred embodiment, these reinforcing ribs 8 have a longitudinal shape. A base surface 9 borders on the edge of the body 7 opposite to the second plate 6, which base surface is substantially symmetrically round and on which the body 7 is arranged perpendicularly. The third portion comprises a
30 perimetric surrounding edge 10 embedded between the base surface 9 and a bottom part 11, with the bottom part 11 transitioning on one side into the standing

area 12 which is suitable for the placement on a surface. A bottom portion 13 formed between the bottom edge 14 and the standing area 12 is preferably plane. The bottom edge 14 which is also plane borders on the bottom portion 13. Due to the plane embodiment of the head edge 15 and of the bottom edge 14, it is possible
5 to position the receiving element 1 stably on a surface and to both prevent it from rolling away and to grip it easily.

Fig. 2 shows further features of the receiving element 1, a first through hole 23 and a second through hole 24 being arranged in the center of the first plate 3. The second through hole 24 can preferably have a smaller diameter than the
10 first through hole 23, although in the presently preferred embodiment the difference in diameter is not indispensable. The first through hole 23 and the second through hole 24 are, in one place, connected to each other by an open groove 39 as is also shown in Fig. 7. The first through hole 23 borders on an opening 40, see Fig. 7, of the first plate 3. Furthermore, a first elongated hole 18
15 and a second elongated hole 19 are provided in the body 7 as can be seen in Fig. 2.

Fig. 3 and Fig. 4 show additional features of the receiving element 1, a portion of the first plate 3 being provided with a chamfered leg 22 which extends from the outer edge approximately up to the area of a theoretical center axis Z of the receiving element 1, the chamfered leg 22 allowing an easy insertion of a
20 dental implant. Furthermore, when the dental implant is pressed in, the first plate 3 can be elastically deformed with respect to the second plate 6 in a direction perpendicular to the center axis Z of the receiving element 1 until the dental implant is locked into place in the first through hole 23 and held there clampingly, a first gap 36 and a second gap 37 of the jaw-like portion 5 mechanically
25 uncoupling the first plate 3 from the body 7 and from the second plate 6, respectively, as mentioned above. In addition, the chamfer 17 on the opposite side advantageously has a resilient effect. A first reinforcement 20 and a second reinforcement 21 are used to strengthen the construction against the tensions produced when the dental implant is pressed in. A first notch 34 and a second
30 notch 35 which can have a conical shape and which are arranged symmetrically in the first plate 3 and adjacent to the first through hole 23 and the second through

hole 24 are suitable for distributing the forces when the dental implant is pressed in through the opening 40 of the first plate 3, and the first plate 3 can be expanded elastically in a direction perpendicular to the center axis Z. The conical shape of the notches is preferred especially for machining reasons if the receiving element is manufactured by injection molding. As mentioned above, the second through hole 24 has a smaller diameter than the first through hole 23 and is connected to it by the groove 39 so that the through hole 24 is used as an expansion through hole and can be enlarged when a dental implant is pressed in. The elastic deformability of the first plate 3 advantageously results both in a clamping and in a snap-in connection which securely fixes the dental implant in the first through hole 23.

Fig. 5 and Fig. 6 show the head area of the receiving element 1, Fig. 5 showing an area 41 which has, in the portion of the opening 40, see Fig. 7, a first chamfer 26 and a second chamfer 27 used for easy insertion of the dental implant. The angle between the first and the second chamfer is preferably within a range of 80 to 120 degrees. The area 41 which is enclosed over the entire cross-section up to the chamfers 26, 27 is rigid so as to form the U-shaped portion 32 shown in Fig. 6. The inner surface of the U-shaped portion 32 forms a stopping portion 33 in which an inserted dental implant is kept in a stable position so that contact with the interior walls of the body 7, e. g. during transport, is excluded. In the portion of the opening 40, the base surface 9 from Fig. 1 has an annular portion 25 having approximately the width of the U-shaped portion 32 and, in its center, the base surface has a third through hole 42 with a larger diameter than the first and the second through hole 23, 24.

Fig. 7 shows that the first through hole 23 is aligned with the third through hole 42. Within the area of the opening 40, the first notch 34 and the second notch 35 extend substantially parallel thereto, slightly curving in the direction of the center of the second through hole 24 near the first 23 and the second 24 through hole.

The receiving element 1 can be manufactured with conventional processes, e. g. casting, and is preferably made of an elastic plastic material.

If technical features mentioned in any claim are provided with a

reference number, these reference numbers have been merely included to increase comprehensibility of the claims. Accordingly, these reference numbers have no limiting effect on the scope of each element identified by way of example by such reference numbers.

5

List of reference numbers

	1	receiving element
	2	front face
10	3	first plate
	4	first shoulder
	4'	second shoulder
	5	jaw-like portion
	6	second plate
15	7	body
	8	reinforcing ribs
	9	base surface
	10	surrounding edge
	11	bottom part
20	12	standing area
	13	plane bottom portion
	14	bottom edge
	15	head edge
	16	plane head area
25	17	chamfer
	18	first elongated hole
	19	second elongated hole
	20	first protrusion
	21	second protrusion
30	22	chamfered leg
	23	first through hole

	24	second through hole
	25	annular portion
	26	first chamfer
	27	second chamfer
5	28	first insertion edge
	29	second insertion edge
	30	first guide rail
	31	second guide rail
	32	stopping portion
10	33	U-shaped portion
	34	first notch
	35	second notch
	36	first gap
	37	second gap
15	38	cylindrical interior wall
	39	groove
	40	opening
	41	area
	42	third through hole
20		

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A receiving element for a dental implant, comprising:

5 a hollow body extending along a center axis of the receiving element;

a first plate and a second plate extending substantially perpendicular to the center axis of the receiving element and configured to fix a dental implant releasably in a stable position, the first plate and the second plate each comprising a front end, a rear end opposite to the front end, a first lateral end and a second lateral end opposite to the first lateral end; and

10 an open portion disposed between the first plate and the second plate to partially separate the first plate and the second plate, the open portion extending from the front end substantially up to the center axis of the receiving element, the open portion comprising a first gap extending from the first lateral end substantially up to the center axis and a second gap extending

15 from the second lateral end substantially up to the center axis, each gap allowing communication along the entire length thereof between an interior of the body and an exterior of the body, wherein

the first plate is elastic to ensure a clamping accommodation of a dental implant in an opening of the first plate, and

the second plate has a substantially U-shaped stopping portion formed to stabilize the position of an inserted dental implant.

2. A receiving element for a dental implant according to claim 1, wherein

25 the open portion is tapered from the front end to center axis when viewed laterally.

3. A receiving element for a dental implant according to claim 1 or 2, wherein the second plate is rigid and provides a guide for the dental implant.

4. A receiving element for a dental implant according to any one of
5 claims 1 to 3, wherein the first plate is elastically deformable in the direction of the center axis of the receiving element.

5. A receiving element for a dental implant according to any one of
10 claims 1 to 4, wherein the first plate is elastically deformable in a direction perpendicular to the center axis of the receiving element.

6. A receiving element for a dental implant according to any one of
claims 1 to 5, wherein the first plate has a first through hole and a second
through hole adjacent to the opening, the second through hole having a
15 smaller diameter than the first through hole and the first and the second through hole being interconnected by a groove.

7. A receiving element for a dental implant according to any one of
claims 1 to 6, wherein the first plate has symmetrically arranged notches
20 which are preferably arranged around the opening.

8. A receiving element for a dental implant according to any one of
claims 1 to 7, wherein the body comprises a plurality of grip elements.

25 9. A receiving element for a dental implant according to claim 8, wherein the body has a substantially square cross-section.

10. A receiving element for a dental implant according to any one of claims 1 to 9, wherein the receiving element is formed from elastically deformable plastic material.
- 5 11. A receiving element for a dental implant according to any one of claims 1 to 10, wherein the body comprises a plurality of grip elements.

STRAUMANN HOLDING AG

WATERMARK PATENT AND TRADE MARKS ATTORNEYS

P32559AU00

2008258552 29 Nov 2012




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7