



(86) Date de dépôt PCT/PCT Filing Date: 1998/11/10
(87) Date publication PCT/PCT Publication Date: 1999/05/20
(45) Date de délivrance/Issue Date: 2006/01/10
(85) Entrée phase nationale/National Entry: 1999/07/09
(86) N° demande PCT/PCT Application No.: JP 1998/005051
(87) N° publication PCT/PCT Publication No.: 1999/025037
(30) Priorité/Priority: 1997/11/11 (9-308294) JP


(51) Cl.Int.⁷/Int.Cl.⁷ H01M 2/12, H01M 2/08

(72) Inventeurs/Inventors:
KASHIHARA, YOSHIHIRO, JP;
MORI, KATSUHIKO, JP;
MASUMOTO, KENJIN, JP;
TSURUTA, KUNIO, JP

(73) Propriétaire/Owner:
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD., JP

(74) Agent: SIM & MCBURNEY

(54) Titre : ELEMENT D'ACCUMULATEUR ELECTROLYTIQUE NON AQUEUX ET A L'EPREUVE DES EXPLOSIONS
ET PROCEDE DE REGLAGE DE LA PRESSION DE RUPTURE DUDIT ELEMENT
(54) Title: EXPLOSION-PROOF NON-AQUEOUS ELECTROLYTE SECONDARY BATTERY AND METHOD OF
SETTING RUPTURE PRESSURE



(57) Abrégé/Abstract:

An explosion-proof non-aqueous electrolyte battery is provided which has a current cutoff device for cutting off electrical connection within the battery with safety and certainty in the event of overcharge while remaining inoperable in normal use or in storage at an elevated temperature. A pair of an upper vent plate 1 and a lower vent plate 2 mechanically and electrically coupled with each other is provided on the sealing part of the battery where the mechanical coupling of the pair of the upper vent plate 1 and the lower vent plate 2 is so configured as to rupture and cut off an electric current in the event the internal pressure of the battery case increases beyond a predetermined value, and the rupture pressure at which the mechanical coupling between the pair of upper vent plate 1 and the lower vent plate 2 is broken has been set to decrease as the spatial volume occupancy ratio of the battery increases.



ABSTRACT

An explosion-proof non-aqueous electrolyte battery is provided which has a current cutoff device for cutting off electrical connection within the battery with safety and certainty in the event of overcharge while remaining inoperable in normal use or in storage at an elevated temperature. A pair of an upper vent plate 1 and a lower vent plate 2 mechanically and electrically coupled with each other is provided on the sealing part of the battery where the mechanical coupling of the pair of the upper vent plate 1 and the lower vent plate 2 is so configured as to rupture and cut off an electric current in the event the internal pressure of the battery case increases beyond a predetermined value, and the rupture pressure at which the mechanical coupling between the pair of upper vent plate 1 and the lower vent plate 2 is broken has been set to decrease as the spatial volume occupancy ratio of the battery increases.

P17255

TITLE

Explosion-Proof Non-Aqueous Electrolyte Secondary Battery and Method of Setting
Rupture Pressure

5

FIELD OF THE INVENTION

The present invention relates to an explosion-proof non-aqueous electrolyte secondary battery adaptable to lithium secondary batteries and the like.

10 BACKGROUND OF THE INVENTION

In recent years there has been a rapid progress in portable and cordless designs of electronic equipment such as audio-visual equipment and personal computers. As the power source of these equipment, non-aqueous electrolyte (organic solvent type liquid electrolyte) secondary batteries as represented by various
15 types of high-capacity alkaline storage batteries and lithium-ion secondary batteries are suitable. Furthermore, as a result of an effort of developing sealed type versions with a high energy density and superior load characteristic, sealed type non-aqueous electrolyte secondary batteries are in wide use as the power source of portable equipment including watches and cameras.

20

Now, with the non-aqueous electrolyte secondary battery, a chemical change in the power generating elements inside the battery takes place in the event of failure of applied equipment including the charger, overcharge, or misuse. For instance, an abnormal reaction due to overcharge or short circuit decomposes the electrolyte or active materials, thus causing unusual gas evolution inside the battery and an excessive
25 internal pressure of the battery. For this reason this type of batteries has to date been provided with the following explosion-proof mechanism. That is, in the event the battery internal pressure increases beyond a designed value, a vent member that has been exerted with the internal pressure is pressed toward the direction of the internal pressure (the direction of diffusion of the internal pressure) and deformed, thereby
30 causing rupture of a thin portion of electrically conducting member or separation of the weld between the vent member and the electrically conducting member thus cutting off the electric current in the initial stage of occurrence of overcharge or short circuit and stopping the abnormal reaction. As a result, an increase in the battery temperature or battery internal pressure due to charging current or short-circuit current can be
35 controlled and safety of the battery is secured.

The battery structure disclosed in U.S. Pat. No. 4,943,497 is valuable in that -it provides a commercially useful product which is fully protected internally against overcharge. The gas evolution mechanism which activates the cut-off device depends on the voltage and temperature of the battery and on time. The speed of gas evolution is not constant; it increases with increasing voltage and temperature of the battery. It is of special significance to note in actual use of the battery that evolution of a gas continues with time at predetermined voltage and temperature. While it is required that evolution of a gas during overcharge assures safe stoppage of battery operation, sustained evolution of the gas in normal operation must be avoided. Unless gas evolution can be avoided, decomposition product of the gas will accumulate with time causing an increase in the gas pressure presenting a possibility of operation of the cut-off device in normal use.

By a proper selection of the liquid electrolyte and positive active material, safety requirements can actually be satisfied to a certain degree. However, these requirements hinder the selection because of such other reasons as cost, complexity, and energy density. Furthermore, when the gas evolution continues in a completely sealed battery, the maximum life of the cut-off device will be limited.

The prime object of the present invention is to provide a safe and explosion-proof non-aqueous electrolyte secondary battery which is equipped with a cut-off device for cutting off electrical connection within the battery with safety and certainty in the event of overcharge while remaining inoperable in normal use or storage at an elevated temperature, and which is free from the danger of explosion by combination and optimization of safety devices and superior in safety in the event of evolution of a gas in excess of the gas discharge capacity as a result of abandonment or throwing into fire of the battery.

SUMMARY OF THE INVENTION

In accordance with an aspect of the present invention, there is provided a method of setting rupture pressure of an explosion-proof non-aqueous secondary battery including a sealing part provided with a pair of upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between said pair of upper and lower vent plates ruptures thus cutting off an electric current in the event the internal pressure of a battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value, an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the rupture pressure at which the mechanical coupling between said pair of upper and lower vent plates ruptures has been set to decrease as a spatial volume occupancy ratio of the battery increases.

In accordance with another aspect of the invention, there is provided an explosion-proof non-aqueous electrolyte secondary battery including a sealing part provided with a pair of an upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between the pair of upper and lower vent plates ruptures
 5 thus cutting off the electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the easy-to-rupture portion is formed on the bottom surface of the battery case
 10 the rupture pressure of which being set at least 16 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion of the upper vent plate.

In accordance with a further aspect of the invention, an explosion-proof non-aqueous electrolyte secondary battery includes a sealing part provided with a pair of an upper and lower vent plates mechanically and electrically coupled with each other, wherein the
 15 mechanical coupling between the pair of upper and lower vent plates ruptures thus cutting off the electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and an easy-
 20 to-rupture portion is formed on the bottom surface of the battery case the rupture pressure of which being set at least 16 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion of the upper vent plate.

BRIEF DESCRIPTION OF THE DRAWINGS

25 Fig. 1 is a vertical cross-sectional view of an explosion-proof battery in an exemplary embodiment of the present invention.

Fig. 2 is a bottom view of the battery.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

30 Preferred embodiments of the present invention are described in the following with reference to drawings. Fig. 1 is a vertical cross-sectional view of an explosion-proof lithium secondary battery in an exemplary embodiment of the present

invention. In the figure, the explosion-proof seal plate employed in the battery includes an upper vent member (upper vent plate) 1 composed of a thin metal foil, a lower vent member (lower vent plate) 2 composed of a thin metal foil and disposed opposite to the upper vent member 1, a ring-shaped insulating inner gasket 3 interposed
 5 between the peripheries of each of the upper vent member 1 and the lower vent member 2, a ring-shaped PTC device 4 placed on top of the periphery of the upper vent member 1, a metal cap 5 laid on top of the PTC device 4 and having 6 discharge holes 5a, and a metal case 6 made of aluminum for receiving and securing each of the above members under a stacked condition and having 4 ventilation holes.

10 The inner gasket 3 is made of synthetic resin having resistance to liquid electrolyte, for example silane-cross-linked polypropylene type polymer, formed in a manner that a tubular portion 3b extends upwardly from the outer edge of a ring-shaped periphery 3a. The upper vent member 1 is composed of an aluminum disk, 0.15 mm in thickness and 12.7 mm in outer diameter, for example, and has a central concave
 15 portion 1a downwardly swelling into a curvature surface, and an easy-to-rupture thin annular C-letter shape portion 1b formed on the circumference of the concave portion 1a by using a C-letter shape stamp.

The lower vent member 2 is composed of an aluminum disk 0.1 mm in thickness and 13.5 mm in outer diameter, for example, and has an easy-to-rupture thin
 20 portion 2b formed on the circumference of the central portion 2a by using an annular stamp. The thin portion 2b has a rupture strength such that it ruptures when the battery internal pressure reaches a predetermined value, and the rupture strength is set at a value lower than the rupture strength of the thin portion 1b of the upper vent member 1.

25 The central portions of each of the upper vent member 1 and the lower vent member 2 are welded to form a bonded part S, and the upper vent member 1 and the lower vent member 2 are electrically connected only through the bonded part S. The PTC device 4 is a positive temperature coefficient resistance element the electrical resistance of which drastically increases when a predetermined temperature range is
 30 exceeded by passage of an electric current in excess of a predetermined value.

Next, a brief description of a battery obtained by sealing the opening of the battery case 7 with the above described explosion-proof seal plate will be given. First, in inserting the explosion-proof seal plate into the battery case 7 having a thin portion 7b on the bottom, a lead member 8 taken out from one of the electrodes (usually
 35 positive electrode) of an electrode group 10 housed inside the battery case 7 is

connected by welding with a battery case 6, followed by pouring liquid electrolyte in the electrode group 10 and fitting the explosion-proof seal plate to inside of the opening of the battery case 7 with intervention of an insulating gasket 9 on the circumference. Subsequently, the peripheral edge portion 7a of the opening of the battery case 7 is caulked inward thus sealing the battery case 7 with the explosion-proof seal plate. In the meantime, the thin portion 7b provided on the bottom is of a C-letter shape and forms an easy-to-rupture portion.

The electric current of this battery flows from the electrode group 10 housed inside the battery case 7 through the lead member 8, metal case 6, lower vent member 2, bonded part S, upper vent member 1, PTC device 4, to the metal cap 5 which also serves as an external terminal thereby enabling the battery to function. Here, in the event an excessive current flows, the PTC device 4 reaches at the operating temperature in a short period of time and increases its resistance thus greatly reducing the current and maintaining it at a low level. As a result severe damage of the battery due to external short circuit or misuse at an excessively large current may be prevented.

In the event of overcharge or reverse charge due to failure of the charger, or overdischarge of many batteries connected in series, it often happens that the current exceeds the allowable safety limit even though it is below the operating current of the PTC device 4 and the battery internal pressure increases. When the battery internal pressure reaches a predetermined value established based on the rupture strength of the thin portion 2b of the lower vent member 2, a part of the thin portion 2b of the lower vent member 2 which receives the battery internal pressure through a ventilation (breathing) hole 6a ruptures, and by the pressure received through the ruptured part the upper vent member 1 is deformed upward by the flip of the concave portion 1a triggering rupture of the thin portion 2b of the lower vent member 2 by shearing. As a result, the portion encircled by the thin portion 2b of the lower vent member 2 is removed away from the lower vent member 2 together with the upper vent member 1, thus the upper vent member 1 and the lower vent member 2 which have been electrically conducting only through the bonded part S are separated, thus cutting off the electric current.

In the event the battery internal pressure further continues to increase due to evolution of a large volume of gas and the battery internal pressure reaches a predetermined value established based on the rupture strength of the thin portion 1b of the upper vent member 1, the thin portion 1b ruptures open and the filled gas is discharged to outside of the battery through the discharge holes 5a.

In the event the battery internal pressure continues to rapidly increase and the battery internal pressure reaches the rupture strength of the thin portion 7b of the bottom of the battery case 7, the thin portion 7b ruptures open and the filled gas is discharged to outside of the battery.

5 Example cylindrical batteries A1 to A7 having the above structure were fabricated as follows. A battery having a spatial volume occupancy ratio, being volume ratio of the empty space in the total space occupied by the battery (namely, the space not constituting a power generation element), of 15-20% and using a seal plate having a rupture pressure of the lower vent member 2 set at 3-11 kgf/cm² is designated
10 A1, a battery having a spatial volume occupancy ratio of 10-14% and using a seal plate having a rupture pressure of the lower vent member 2 set at 4-13 kgf/cm² is designated A2, a battery having a spatial volume occupancy ratio of 9% and using a seal plate having a rupture pressure of the lower vent member 2 set at 5-13 kgf/cm² is designated A3, a battery having a spatial volume occupancy ratio of 8% and using a seal plate
15 having a rupture pressure of the lower vent member 2 set at 5.5-13 kgf/cm² is designated A4, a battery having a spatial volume occupancy ratio of 7% and using a seal plate having a rupture pressure of the lower vent member 2 set at 7-13 kgf/cm² is designated A5, a battery having a spatial volume occupancy ratio of 6% and using a seal plate having a rupture pressure of the lower vent member 2 set at 9-14 kgf/cm² is
20 designated A6, and a battery having a spatial volume occupancy ratio of 5% and using a seal plate having a rupture pressure of the lower vent member 2 set at 13-15 kgf/cm² is designated A7.

Also, example rectangular batteries F1 to F5 were fabricated by setting the rupture pressure of the lower vent member 2 as follows. A battery having a spatial
25 volume occupancy ratio of 15-20% and using a seal plate having a rupture pressure of the lower vent member 2 set at 2-5 kgf/cm² is designated F1, a battery having a spatial volume occupancy ratio of 10-14% and using a seal plate having a rupture pressure of the lower vent member 2 set at 3-7 kgf/cm² is designated F2, a battery having a spatial volume occupancy ratio of 7-9% and using a seal plate having a rupture pressure of the
30 lower vent member 2 set at 4-7 kgf/cm² is designated F3, a battery having a spatial volume occupancy ratio of 6% and using a seal plate having a rupture pressure of the lower vent member 2 set at 4-9 kgf/cm² is designated F4, and a battery having a spatial volume occupancy ratio of 5% and using a seal plate having a rupture pressure of the lower vent member 2 set at 6-10 kgf/cm² is designated F5. Here, the rupture pressure
35 (operating pressure) of the thin portion is measured by gas pressurization.

Results of overcharge test, elevated-temperature storage test, and fire throw-
in test of these batteries are described in the following.

(1) Overcharge test:

5 The overcharge test is a test assuming overcharge under an uncontrolled
condition such as due to failure of the charger. The status of each of the batteries after
the test was observed. As comparative examples of cylindrical batteries, a battery
having a spatial volume occupancy ratio of 15-20% and using a seal plate having a
rupture pressure of the lower vent member 2 set at 13 kgf/cm² is designated B1, a
10 battery having a spatial volume occupancy ratio of 10-14% and using a seal plate
having a rupture pressure of the lower vent member 2 set at 14 kgf/cm² is designated
B2, a battery having a spatial volume occupancy ratio of 6% and using a seal plate
having a rupture pressure of the lower vent member 2 set at 15 kgf/cm² is designated
B3, and a battery having a spatial volume occupancy ratio of 5% and using a seal plate
15 having a rupture pressure of the lower vent member 2 set at 16 kgf/cm² is designated
B4.

On the other hand, as comparative examples of rectangular batteries, a
battery having a spatial volume occupancy ratio of 15-20% and using a seal plate
having a rupture pressure of the lower vent member 2 set at 6 kgf/cm² is designated G1;
20 a battery having a spatial volume occupancy ratio of 7-14% and using a seal plate
having a rupture pressure of the lower vent member 2 set at 8 kgf/cm² is designated G2,
a battery having a spatial volume occupancy ratio of 6% and using a seal plate having a
rupture pressure of the lower vent member 2 set at 10 kgf/cm² is designated G4, and a
battery having a spatial volume occupancy ratio of 5% and using a seal plate having a
25 rupture pressure of the lower vent member 2 set at 11 kgf/cm² is designated G5.
Table 1 shows results of overcharge test of the example batteries of the present
invention and comparative examples.

30

35

Table 1.

Cylindrical batteries

Battery type		Spatial volume occupancy ratio (%)	Lower vent member rupture pressure (kgf/cm ²)	Overcharge ignition ratio
Examples	A1	15 - 20	3 - 11	0 / 100
	A2	10 - 14	4 - 13	0 / 100
	A3	9	5 - 13	0 / 100
	A4	8	5.5 - 13	0 / 100
	A5	7	7 - 13	0 / 100
	A6	6	9 - 14	0 / 100
	A7	5	13 - 15	0 / 100
Comparative examples	B1	15 - 20	13	97 / 100
	B2	10 - 14	14	93 / 100
	B3	6	15	94 / 100
	B4	5	16	96 / 100

Rectangular batteries

Battery type		Spatial volume occupancy ratio (%)	Lower vent member rupture pressure (kgf/cm ²)	Overcharge ignition ratio
Examples	F1	15 - 20	2 - 5	0 / 100
	F2	10 - 14	3 - 7	0 / 100
	F3	7 - 9	4 - 7	0 / 100
	F4	6	4 - 9	0 / 100
	F5	5	6 - 10	0 / 100
Comparative examples	G1	15 - 20	6	97 / 100
	G2	7 - 14	8	95 / 100
	G4	6	10	92 / 100
	G5	5	11	94 / 100

5

From the results of Table 1, it can be seen that while the comparative example cylindrical batteries B1-B4 and rectangular batteries G1-G5 had ignited, none of the cylindrical batteries A1-A7 and rectangular batteries F1-F5 of examples of the present invention have reached the state of igniting. With the comparative example batteries B1-B4 and G1-G5, the timing of cutting off the electrical connection for an electric current was delayed as the rupture pressure of the lower vent member 2 was high, and decomposition of the electrolyte continued, resulting in an increase in the battery internal pressure and continued rise in the battery temperature. The battery thermal runaway start temperature was eventually reached thus releasing oxygen-containing gas and ending in ignition.

15

On the other hand, with each of the example batteries A1-A7 and F1-F5 of the present invention, an optimum rupture pressure for each respective spatial volume occupancy ratio has been set and the timing of cutting off electrical connection for an electric current was never delayed. Consequently, the thermal runaway temperature was never reached due to continued rises in the battery internal pressure and temperature thus never resulting in ignition.

(2) Elevated-temperature storage test:

The elevated-temperature storage test is a test to store a battery in a 85°C thermostat oven for 3 days. Status of the battery after the test is observed. As comparative examples of cylindrical batteries, a battery having a spatial volume occupancy ratio of 15-20% and using a seal plate having a rupture pressure of the lower vent member 2 set at 2 kgf/cm² is designated C1, a battery having a spatial volume occupancy ratio of 10-14% and using a seal plate having a rupture pressure of the lower vent member 2 set at 3 kgf/cm² is designated C2, a battery having a spatial volume occupancy ratio of 9% and using a seal plate having a rupture pressure of the lower vent member 2 set at 4 kgf/cm² is designated C3, a battery having a spatial volume occupancy ratio of 8% and using a seal plate having a rupture pressure of the lower vent member 2 set at 5 kgf/cm² is designated C4, a battery having a spatial volume occupancy ratio of 7% and using a seal plate having a rupture pressure of the lower vent member 2 set at 6 kgf/cm² is designated C5, a battery having a spatial volume occupancy ratio of 6% and using a seal plate having a rupture pressure of the lower vent member 2 set at 8 kgf/cm² is designated C6, and a battery having a spatial volume occupancy ratio of 5% and using a seal plate having a rupture pressure of the lower vent member 2 set at 12 kgf/cm² is designated C7.

Furthermore, as comparative examples of rectangular batteries, a battery having a spatial volume occupancy ratio of 15-20% and using a seal plate having a rupture pressure of the lower vent member 2 set at 1 kgf/cm² is designated H1, a battery having a spatial volume occupancy ratio of 7-14% and using a seal plate having a rupture pressure of the lower vent member 2 set at 2 kgf/cm² is designated H2, a battery having a spatial volume occupancy ratio of 6% and using a seal plate having a rupture pressure of the lower vent member 2 set at 3 kgf/cm² is designated H4, and a battery having a spatial volume occupancy ratio of 5% and using a seal plate having a rupture pressure of the lower vent member 2 set at 5 kgf/cm² is designated H5. Table 2 shows

results of elevated-temperature storage test of example batteries of the present invention and comparative example batteries.

Table 2.

5 Cylindrical batteries

Battery type		Spatial volume occupancy ratio (%)	Lower vent member rupture pressure (kgf/cm ²)	Ratio of erroneous current cutoff
Examples	A1	15 - 20	3 - 11	0 / 100
	A2	10 - 14	4 - 13	0 / 100
	A3	9	5 - 13	0 / 100
	A4	8	5.5 - 13	0 / 100
	A5	7	7 - 13	0 / 100
	A6	6	9 - 14	0 / 100
	A7	5	13 - 15	0 / 100
Comparative examples	C1	15 - 20	2	96 / 100
	C2	10 - 14	3	92 / 100
	C3	9	4	98 / 100
	C4	8	5	93 / 100
	C5	7	6	94 / 100
	C6	6	8	97 / 100
	C7	5	12	93 / 100

Rectangular batteries

Battery types		Spatial volume occupancy ratio (%)	Lower vent member rupture pressure (kgf/cm ²)	Ratio of erroneous current cutoff
Examples	F1	15 - 20	2 - 5	0 / 100
	F2	10 - 14	3 - 7	0 / 100
	F3	7 - 9	4 - 7	0 / 100
	F4	6	4 - 9	0 / 100
	F5	5	6 - 10	0 / 100
Comparative examples	H1	15 - 20	1	92 / 100
	H2	7 - 14	2	95 / 100
	H4	6	3	97 / 100
	H5	5	5	94 / 100

10 It can be seen from Table 2 that, while erroneous current cutoff operation of seal plates took place with the comparative example batteries C1-C7 and H1-H5 thus cutting off electrical conduction in the batteries and not performing as batteries, no erroneous current cutoff operation of seal plates took place with the example batteries A1-A7 and F1-F5 of the present invention. In this test, as a result of exposing

batteries to an elevated temperature of 85°C, the internal pressure rose due to evaporation of the liquid electrolyte and volume expansion of the evolving gas. With the comparative example batteries C1-C7 and H1-H5, electrical connection for the electric current was erroneously cutoff because the rupture pressure of the lower vent member 2 of the seal plate was low. On the other hand, with the example batteries A1-A7 and F1-F5 of the present invention, electrical connection for the electric current was not erroneously cutoff because the rupture pressure had been set at an optimum value relative to each respective spatial volume occupancy ratio. From the above results, it can be seen that, with batteries that are provided with an explosion-proof seal plate which has been set to an optimum rupture pressure relative to each respective spatial volume occupancy ratio, while the cutoff device operates before ignition of the battery in the event of excessive overcharge, the cutoff device does not operate while being stored at an elevated temperature, thus suggesting that batteries safer than conventional batteries and with a high reliability can be fabricated.

(3) Fire throw-in test:

The fire throw-in test is a test assuming incineration after disposal of batteries, where a battery is burnt in a combustion furnace using charcoal or wood. Status of the battery after the test is observed. In the example batteries A1-A7 of the present invention, the rupture pressure of the upper vent member 1, the rupture pressure of the thin portion of the bottom of the case, and the caulking withstand pressure of the sealing part of the seal plate were respectively set at 18-24 kgf/cm², 40-60 kgf/cm², and 70-90 kgf/cm². As comparative examples, batteries D1-D7 were fabricated of which the spatial volume occupancy ratio and the rupture pressure of the lower vent member 2 were the same as those of example batteries A1-A7, the rupture pressure of the upper vent member 1 of the seal plate had been set at 18-24 kgf/cm², the rupture pressure of the thin portion of the bottom of the case had been set at 17 kgf/cm², and the caulking withstand pressure of the sealing part of the seal plate had been set at 70-90 kgf/cm²; comparative batteries E1-E7 were fabricated of which the rupture pressure of the upper vent member 1 had been set at 18-24 kgf/cm², the rupture pressure of the thin portion of the bottom of the case had been set at 40-60 kgf/cm², and the caulking withstand pressure of the sealing part of the seal plate had been set at 30 kgf/cm². Table 3 shows the results of fire throw-in test of the example batteries of the present invention and the comparative example batteries.

Table 3.

Battery type		Upper vent member rupture pressure (kgf/cm ²)	Rupture pressure of case bottom thin portion (kgf/cm ²)	Caulking withstand pressure of sealing part (kgf/cm ²)	Fire throw-in explosion ratio
Examples	A1 - A7	18 - 24	40 - 60	70 - 90	0 / 100
Comparative examples	D1 - D7	18 - 24	17	70 - 90	0 / 100
	E1 - E7	18 - 24	40 - 60	30	100 / 100

(Note) Spatial volume occupancy ratio and lower vent member rupture pressure of D1-D7 and E1-E7 are the same as those of A1-A7

5 It can be seen from Table 3 that, though the comparative example batteries D1-D7 did not explode, as the rupture pressure of the thin portion of the bottom of the battery case was lower than the rupture pressure of the upper vent member 1, in the event of a slight increase in the battery internal pressure owing to temperature rise of the battery due to overcharge and other reasons, there occurred an instance in which the

10 thin portion of the bottom of a battery ruptured even in the case safety could be secured by the rupture of the upper vent member 1 only of the seal plate. This may cause leakage of the liquid electrolyte leading to failure of an equipment. Accordingly, a test was conducted on several values of the difference between the rupture pressure of the upper vent member 1 and the rupture pressure of the case bottom thin portion. As

15 a result, it was found preferable that the rupture pressure of the case bottom thin portion be set higher than the upper limit of the rupture pressure of the upper vent member 1 by at least 16 kgf/cm².

On the contrary, it is to be noted that comparative batteries E1-E7 exploded. This is because when a battery was thrown into fire, rapid chemical reaction took place

20 inside the battery accompanying sudden evolution of a gas inside the battery owing to unusual heating. As a result of evolution of a gas in excess of the gas discharge capacity through the rupture of the upper vent member 1 disposed on the seal plate, the battery internal pressure suddenly increased beyond the caulking withstand pressure of the sealing part thus leading to an explosion. Consequently, a test was conducted by

25 setting different values as the difference between the rupture pressure of the case bottom thin portion and the caulking withstand pressure of the sealing part, from which it was found preferable to set the rupture pressure of the case bottom thin portion lower than the lower limit of the caulking withstand pressure of the sealing part by substantially 10 kgf/cm².

On the other hand, the example batteries A1-A7 of the present invention did not reach the state of exploding. It is conceivable that when the battery internal pressure increased by being thrown into fire, gas discharge took place through rupture of the upper vent member 1 before the caulking withstand pressure of the sealing part had been reached, and in the event a volume of gas in excess of the gas discharge capacity evolved, gas discharge was performed through rupture of the case bottom thin portion, suggesting that proper setting of the operating pressure levels controlled the sequence of gas discharge and allowed the evolved gas inside the battery to smoothly discharge to outside of the battery.

10 In the above exemplary embodiment, although the structure is such that an electric current is cutoff by rupture of the easy-to-rupture portion (thin portion) 2b of the lower vent member 2 in the event the internal pressure of the battery case 7 exceeds a predetermined value, the structure may be configured such that the easy-to-rupture portion 2b is not formed on the lower vent member 2 and the bonded part S ruptures
15 thus cutting off the current. Also, the easy-to-rupture portion provided on the upper vent member 1 and the easy-to-rupture portion provided on the bottom of the battery case can be configured not only by the C-letter shaped thin portions 1b and 7b as shown in the exemplary embodiment but also by various other configurations.

20 INDUSTRIAL APPLICATION

The present invention provides a safe and explosion-proof non-aqueous secondary battery which is equipped with an electric current cutoff device for cutting off electrical connection within the battery with safety and certainty in the event of overcharge while remaining inoperable in normal use or storage at an elevated
25 temperature, and which is free from the danger of explosion and superior in safety by combination and optimization of explosion-proof devices in the event of evolution of a gas in excess of the gas discharge capacity under a wide range of conditions including abandonment and throwing into fire of the battery.

CLAIMS:

1. A method of setting rupture pressure of an explosion-proof non-aqueous secondary battery including a sealing part provided with a pair of upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between said pair of upper and lower vent plates ruptures thus cutting off an electric current in the event the internal pressure of a battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value, an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the rupture pressure at which the mechanical coupling between said pair of upper and lower vent plates ruptures has been set to decrease as a spatial volume occupancy ratio of the battery increases.

2. The method of setting rupture pressure of an explosion-proof non-aqueous electrolyte secondary battery of Claim 1, wherein the relationship between the spatial volume occupancy ratio of the battery and the rupture pressure of the lower vent plate at which the mechanical coupling between the pair of the upper and lower vent plates is broken has been set as shown in the following:

Spatial volume occupancy ratio (%, figures rounded off)	Rupture pressure (kgf/cm ² , figures rounded off)	
	Cylindrical battery	Rectangular battery
15 - 20	3 - 11	2 - 5
10 - 14	4 - 13	3 - 7
9	5 - 13	4 - 7
8	5.5 - 13	4 - 7
7	7 - 13	4 - 7
6	9 - 14	4 - 9
5	13 - 15	6 - 10

3. The method of setting rupture pressure of an explosion-proof non-aqueous electrolyte secondary battery of Claim 1, wherein the rupture pressure of the easy-to-rupture portion of the upper vent plate has been set in the range of 18-24 kgf/cm².

4. An explosion-proof non-aqueous electrolyte secondary battery including a sealing part provided with a pair of an upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between the pair of upper and lower vent plates ruptures thus cutting off an electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the rupture pressure has been set according to the method of setting rupture pressure as claimed in Claim 1.

5. An explosion-proof non-aqueous electrolyte secondary battery including a sealing part provided with a pair of an upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between the pair of upper and lower vent plates ruptures thus cutting off the electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case subsequently further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the easy-to-rupture portion is formed on the bottom surface of the battery case the rupture pressure of which being set at least 16 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion of the upper vent plate.

6. The explosion-proof non-aqueous electrolyte secondary battery of Claim 5, wherein the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case is in the range 40-60 kgf/cm².

7. The explosion-proof non-aqueous electrolyte secondary battery of Claim 5, wherein a caulking withstand pressure of the sealing part has been set at least 10 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case.

8. The explosion-proof non-aqueous electrolyte secondary battery of Claim 7, wherein the caulking withstand pressure of the sealing part is in the range 70-90 kgf/cm²

9. The explosion-proof non-aqueous electrolyte secondary battery of Claim 4, wherein the easy-to-rupture portion is formed on the bottom surface of the battery case and the rupture pressure of said easy-to-rupture portion has been set at least 16 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion of the upper vent plate.

10. The explosion-proof non-aqueous electrolyte secondary battery of Claim 9, wherein the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case is in the range 40-60 kgf/cm².

11. The explosion-proof non-aqueous electrolyte secondary battery of Claim 9, wherein the caulking withstand pressure of the sealing part has been set 10 kgf/cm² higher than the upper limit of the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case.

12. The explosion-proof non-aqueous electrolyte secondary battery of Claim 11, wherein the caulking withstand pressure of the sealing part is in the range 70-90 kgf/cm².

13. The method of setting rupture pressure of an explosion-proof non-aqueous electrolyte secondary battery of Claim 2, wherein the rupture pressure of the easy-to-rupture portion of the upper vent plate has been set in the range of 18-24 kgf/cm².

14. An explosion-proof non-aqueous electrolyte secondary battery including a sealing part provided with a pair of an upper and lower vent plates mechanically and electrically coupled with each other, wherein the mechanical coupling between the pair of upper and lower vent plates ruptures thus cutting off an electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case substantially further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the rupture pressure has been set according to the method of setting rupture pressure as claimed in Claim 2.

15. An explosion-proof non-aqueous electrolyte secondary battery including a sealing part provided with a pair of an upper and lower vent plates mechanically and


electrically coupled with each other, wherein the mechanical coupling between the pair of upper and lower vent plates ruptures thus cutting off an electric current in the event the internal pressure of the battery case increased beyond a predetermined value, and in the event the internal pressure of the battery case substantially further increased beyond a predetermined value an easy-to-rupture portion formed on the upper vent plate ruptures thus releasing the gas inside the battery case to outside, and the rupture pressure has been set according to the method of setting rupture pressure as claimed in Claim 3.

16. The explosion-proof non-aqueous electrolyte secondary battery of Claim 6, wherein a caulking withstand pressure of the sealing part has been set at least 10 kgf/cm^2 higher than the upper limit of the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case.

17. The explosion-proof non-aqueous electrolyte secondary battery of Claim 10, wherein a caulking withstand pressure of the sealing part has been set 10 kgf/cm^2 higher than the upper limit of the rupture pressure of the easy-to-rupture portion formed on the bottom surface of the battery case.


1/3

Fig 1



2/3

Fig 2



LIST OF REFERENCE NUMERALS

- 1 Upper vent plate (upper vent member)
- 1b Easily ruptured portion (thin portion)
- 2 Lower vent plate (lower vent member)
- 2b Easily ruptured portion (thin portion)
- 3 Insulating inner gasket
- 4 PTC device
- 5 Metal cap
- 6 Metal case
- 7 Battery case
- 7b Easily ruptured portion (thin portion)
- 8 Lead member
- 9 Insulating gasket
- 10 Electrode group

