Patented Aug. 28, 1934 1,972,055

UNITED STATES PATENT OFFICE

1,972,055

IMPREGNATED SHEET PRODUCTS

George A. Richter, Berlin, N. H., assignor to Brown Company, Berlin, N. H., a corporation of Maine

No Drawing. Original application December 11, 1931, Serial No. 580,496. Divided and this application July 28, 1932, Serial No. 625,531

1 Claim. (Cl. 91—70)

The subject of this invention is the manufacture of impregnated sheet products wherein novel types of prefabricated fibrous webs serve as foundations or carriers for the impregnant. More especially, the fibrous webs comprehended by the present invention are those which are waterlaid, i. e., deposited from aqueous suspension, on machinery of the papermaking class, such as a Fourdrinier or cylinder machine, and which, while capable of undergoing impregnation with aqueous dispersions of binders like rubber latex, are intended for impregnation with impregnants that can be introduced into the web in heat-liquefied condition and then caused to set or congeal as a continuous phase imparting thereto such desired properties as body, stiffness, strength, tear resistance, mouldability, water-repellency, and weathering capacity.

In making certain types of impregnated sheet products, it is customary practice to start with a suitable prefabricated fibrous web and to immerse the web in a bath of heat-liquefied impregnant of sufficient fluidity to enter into and through the web and then to remove the web from the bath and cause the impregnant to set or harden to its normally solid state. Such, for example, is the practice in making waterproof sheet products for roofing, flooring, and building purposes, a bath of molten asphalt or other bitumen constituting the medium into which the starting web is dipped. Such is also the practice in making shoe stiffener material of the so-called thermoplastic variety, which is prepared by impregnating a suitable fabric with molten compositions, such as rosin or the like, which upon setting impart stiffness and resiliency to the impregnated sheet. The shoe stiffener blanks cut from the impregnated sheet are softenable and mouldable under the application of moderate heat non-injurious to leather, wherefore they can be moulded into the desired shape during assembly with the shoe upper, and then allowed to stiffen in such shape.

In accordance with the present invention, I prepare a waterlaid fibrous web preeminently serviceable as a carrier for an impregnant, and more especially one which is to be associated in a molten state with such web. There are factors which I have found to be of great importance in preparing the web of the present invention, especially when comparatively short-fibered cellulose fibers, such as wood pulp, are employed as the raw material on account of their low cost and easy availability. Thus, I have found that one should not strive primarily for the securement of a strong web as it comes off in dry condition from the paper machine. On the contrary, one may advantageously deposit the web from the aqueous fiber suspension and then dry it with the application of little, if any, outside pressure either during forming or drying. Other than the drawing together of the fibers on account of the action of surface tension during drying, the web may therefore, be in practically the same condition of compactness as deposited from aqueous suspension with its fibers only loosely interfelted. The web may hence be tender or lacking in much tensile strength, but it may be fluffy or bulky and so highly porous and absorbent that it can readily take up far more than its own weight in molten asphalt or other liquid impregnant. In making the webs of the present invention, I use substantially unbleached, preliberated cellulose pulps as raw material, preferably substantially unbleached wood pulps, such as kraft or sulphite, or mixtures of such pulps. Preferably, also, these wood pulps, although substantially unbleached, have undergone refining to a higher alpha cellulose content than that associated with the raw pulp liberated from the wood. The refining treatment may be carried out in a suitable alkaline liquor under conditions to produce an unbleached product having an alpha cellulose content of, say, about 93% to 96%, as is now known to those skilled in the art. These raw or refined pulps in substantially unbleached condition are preferably used in practically unbeaten or unhydrated form in making the webs of the present invention, as beating not only shortens the fibers but generates cellulose hydrate and thereby detracts from the absorbency in the resulting web, even though it makes for greatest tensile strength in the web. As already indicated, however, I am not primarily interested in securing a web of initial high strength at the sacrifice of web absorbency, for reasons which will presently appear.

I have found that webs made as hereinbefore described are far superior to the kinds of webs heretofore used as the carriers for heat-liquefied impregnants. Heretofore, waterlaid webs were prepared with a view toward securing considerable initial strength in the web at the expense of web absorbency. I have found, however, that the waterlaid webs of the present invention are so highly absorbent that, despite their low initial strength, they can be drawn continuously through one or more baths of heat-liquefied impregnants, e. g., molten asphalt, without much trouble on account of breakage. I attribute this success to the high rate at which the asphalt enters into and diffuses throughout the web, thereby serving to

bind together the fibers so that the web immediately upon entering the bath is so greatly strengthened that it can endure the further stresses in its journey without rupturing. I attribute this success also to the substantially unbleached state of the fibers and, if they have been refined, further to their high alpha cellulose content. In unbleached state, the fibers are notably freer from oxycelluloses or other degraded celluloses which are unstable, especially under application of heat. This applies especially to raw pulps, but it holds true even in connection with refined pulps. Under the application of considerable heat, bleached pulps may lose much more of their strength than would be the case if the same pulps were in substantially unbleached condition. Consequently when, as is true of my web, it is made up of unbleached pulp fibers, it is not weakened appreciably in passing through a bath of hot, liquid impregnant. Moreover, unbleached pulps invariably yield "freer" aqueous pulp suspensions than do similar bleached pulps whose oxycellulose content apparently becomes more or less suspended as fine or colloidal particles in the water of suspension, especially under agitation. The unbleached pulp suspension which I use enhances the porosity of the resulting web, for "freeness" in a pulp suspension is consonant with porosity in the web derived therefrom, whereas "slowness" in the pulp suspension makes for density in the web. When the web is made from unbleached, refined pulp, it is especially resistant to being weakened by heat on account of the higher proportion of heat-resisting alpha cellulose in the refined pulp fibers. Moreover, the refined pulp fibers also conduce to a web of enhanced absorbency by virtue of the greater "freeness" possessed by refined pulps as compared with similar unrefined pulps.

Any one of the species of webs made in accordance with the present invention can imbibe more than 250% of its own weight in molten asphalt, without having a superfluity of asphalt on its surfaces. This imbibition of asphalt may take place even more rapidly than when webs of lower asphalt-holding capacity, such as heretofore made, are treated to the limit of their capacity. Accordingly, the webs of the present invention need be in contact with the heat-liquefied asphalt for a shorter period of time, to attain a given asphalt content. There is thus less danger of scorching the fibers and causing their embrittlement.

Non-cellulosic fibers, especially those like wool and asbestos, which are more resistant to heat than cellulose fibers, may be blended with the aqueous suspension of cellulose pulp used in fabricating my web. The cellulose pulp may be preliberated wood pulps or longer-fibered pulps, such as derived from manila, sisal, ramie, or the like, or mixtures of such pulps. Wood pulps offer the advantages of low cost and easy availability, but the blending with such pulps of the longer-fibered pulps derived from manila, sisal, ramie, or the like is desirable, in that the web attainable from such a blend has higher initial strength. A portion of the pulp may be mercerized, as mercerized fibers appreciate the porosity and bulkiness of the web, although it is preferable to use a substantial portion, if not most, of the pulp in unmercerized condition, because of the difficulty in realizing a web of good formation or texture from a pulp furnish mercerized in entirety.

I shall now give an example of procedure practised in accordance with the present invention to produce a bituminized web designed for roofing, building, and analogous purposes. I can take as raw material a kraft pulp which has been refined to an alpha cellulose content of about 93% to about 96%, but which is in essentially unbleached condition. The pulp is suspended in practically unbeaten condition in water to form a homogeneous dilute suspension, which is run off on a paper-making machine operated under conditions leading to a dry web having a compactness falling within the range of about 30 to 55. This means that, in some instances, there must be little, if any, pressure applied to the web during its traverse of both the wet and dry ends of the paper-making machine. Yet, in attaining felts having a compactness at the upper end of the range hereinbefore given, it may be necessary to compact or condense the web more or less during its fabrication on the paper-making machine. Webs or felts whose compactness lies at the upper end of the range are of great value in making bituminized sheets for floorings, where high mouldability, stretchability, and yieldability under distorting or denting influences are undesirable qualities. Felts intended for bituminized roofings, on the other hand, may have a compactness lying at the lower end of the range, since in such case it is desired that the felts imbibe during impregnation a maximum amount of bitumen or asphalt. The compactness values given are obtained by dividing the basis weight in pounds by the thickness in inches and multiplying by the factor 10^{-2}. The expression "basis weight," as known in papermaking circles, represents the weight in pounds of 480 sheets whose dimensions are 24x36 inches, this being equivalent to 2880 square feet of sheet material. In other words, the compactness value really represents the weight of fiber per unit volume of sheet material. The dry starting web thus produced is tender and tears readily under much stress. Nevertheless, it can undergo bituminization satisfactorily as a continuous sheet by running it through one or more baths of molten asphalt, for instance, air-blown asphalt having a melting point of about 150° F. (ball and ring test) and heated to about 300° to 350° F. The stretch of web in contact with the fluid asphalt may be as short as 3 feet at a web speed of about 100 feet per minute to ensure a uniform and complete impregnation into a product containing about 300% or more by weight of asphalt, based on dry fiber, and yet possessing a "dry" surface, that is, one free from superfluous asphalt, after the continuous phase carried by the web has been allowed or caused to congeal or set. Impregnation may be carried out under other conditions, but in each case the contact of web with the fluid asphalt is coordinated with a web speed such that a uniformly and completely impregnated product is secured.

The resulting product has high moisture and weather resistance, which properties are traceable to the high proportion of asphalt present therein as a continuous phase. The high asphalt-to-fiber ratio reduces the cost of the finished product on a pound basis, because asphalt is considerably cheaper than fiber. The product has such remarkably high resistance against tearing, especially against the initiation of tear, that the tender starting web would hardly be associated in one's mind with such a different product. Because the product contains a refined, substantially unbleached wood pulp, it stands up against the action of moisture and weathering, by reason of the high stability of the fibers, as well as of their complete encasement by asphalt.

The foregoing exemplary procedure, with only

a change in the material used as an impregnant, can serve in the manufacture of thermoplastic shoe stiffener material for cutting into shoe stiffener blanks, e. g., box toe blanks. In place of the bath of asphalt, a suitable thermoplastic stiffening composition, like rosin, should be used at a temperature of, say, about 250° F. This temperature is sufficient to liquefy the rosin to a fluency ensuring quick and uniform impregnation of the web. If desired, the asphalt may be blended in the proportion of, say 50% with the rosin, in which case the temperature of the bath of mixed impregnant may be raised to, say, about 300° to 320° F. The impregnated web can be cut up into shoe stiffener blanks, which are characterized by their excellent moulding properties under the application of heat moderate enough not to injure leather. Not only do such blanks lend themselves to moulding in heat-softened condition to the desired shape in the shoe, but they are superior to the article heretofore made. Their excellence for this purpose is evidenced by the fact that they can be nicely moulded even about sharp edge corners while in heat-softened condition and then caused to set in such shape without subsequently tending to undergo deformation.

It is to be observed that the impregnated products for which the webs of the present invention serve as foundations are not in any way depreciated on account of the unbleached state of the fibers, as the fibers are masked by impregnants of the character of molten asphalt, rosin, or the like, or by aqueous dispersions of binders, such as rubber latex, asphalt, or colored waxes, which are dried out in the web to coalesce the dispersed particles as a continuous phase.

By the expression "pre-liberated cellulose pulp" as used in the specification and in the appended claim, I mean a pulp which, like wood pulp, has been liberated by a previous digestion of wood or other fiber-bearing raw material in any suitable liquor capable of isolating the fibers as a pulp from the cementitious material binding them together in the raw material. It is thus seen that the expression is exclusive of cotton fibers or rag pulps which must undergo considerable beating to become converted into a suitable half-stock. Besides, virgin cotton fibers carry waxes on their surfaces, which detract from their absorbency.

This application is a division of my application Serial No. 580,496, filed December 11, 1931, which in turn is a continuation-in-part of my application Serial No. 175,946, filed March 16, 1927.

I claim:

A dried, porous, bulky, waterlaid web made up preponderantly of preliberated, alkali-refined but substantially unbleached wood pulp having an alpha cellulose content of at least 93%, said web being impregnated with a bituminous impregnant initially distributed in heated condition in the web.

GEORGE A. RICHTER.