



- (51) **International Patent Classification:**
A47C 27/00 (2006.01) A47C 27/15 (2006.01)
- (21) **International Application Number:**
PCT/US2016/066166
- (22) **International Filing Date:**
12 December 2016 (12.12.2016)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
14/967,269 12 December 2015 (12.12.2015) US
- (71) **Applicant:** LEVEL SLEEP LLC [US/US]; 561 Fisrt Street, Sonoma, CA 95476 (US).
- (72) **Inventor:** SRAMEK, Roger Anton; 1811 Mar West, Tiburon, CA 94920-1901 (US).
- (74) **Agent:** ADLER, Benjamin Aaron; Adler & Associates, 8011 Candle Ln., Houston, TX 77071 (US).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM,

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) **Title:** EFFICIENT MATTRESS HAVING LOW PRESSURE AND ALIGNMENT

(57) **Abstract:** Provided herein is a mattress that efficiently provides low pressure and alignment to achieve restful and less fragmented sleep to a recumbent body. The mattress comprises a composite and a cover encapsulating the composite. The composite includes a performance layer and a core layer. The performance layer includes a first shoulder section, a first thoracic section and a hip section for location at different longitudinal positions corresponding to the shoulder region, the thoracic region and the hip region of the recumbent body. The first shoulder section, the first thoracic section and the hip section have different displacement parameters to match the body displacements in the shoulder region, the thoracic region, and the hip region for alignment of the body with low body pressure. The performance layer may further comprise a second thoracic section and a second shoulder section. A core layer supports the performance layer.



WO 2017/100766 A1

EFFICIENT MATTRESS HAVING LOW PRESSURE AND ALIGNMENT

5

Cross-Reference to Related Application

This international application claims benefit of priority under 35 U.S.C. §120 of pending non-provisional application U.S. Serial No. 14/967,269, filed December 12, 2015, the entirety of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

15 Field of the Invention

The present invention relates generally to the field of mattresses. More specifically, the present invention relates to a mattress that efficiently provides low pressure and alignment to achieve restful and fragmented sleep.

20 Description of the Related Art

Normally, everyone spends a significant percentage of life sleeping. Restful sleep is important to a person's health, enjoyment of life and the ability to function normally. Sleep affects brain activity, heart rate, blood pressure, sympathetic nerve activity, muscle tone, blood flow, sexual arousal, body temperature and other body conditions. Poor sleep has a strong correlation to obesity, diabetes, stroke, depression, hypertension, and other adverse conditions.

Restful sleep is dependent upon a person's comfort level while recumbent, usually in side-lying and back-lying positions. The concentration of pressure on certain parts of the body and poor body alignment remains a significant cause of restless sleep. During sleep, a healthy person typically passes through four levels of sleep, which include physically restorative stages I-III and a REM (Rapid Eye Movement) sleep stage, which is also the mentally restorative stage. Stages I and II are the lightest sleep and stage III is the deepest. Stages I, II and III are non-REM stages (NREM). The REM stage is that level in which sleepers dream and receive mental health benefits. All levels of sleep are important, but stage III is the deepest and most physically restful sleep, when, for example, human growth hormone is secreted. Normal sleep cyclically passes through the stages from I to III and

back from III to I and at the same time into and out of REM. This sleep cycle is repeated a number of times over a normal sleep period, but can be disrupted due, for example, to body discomfort.

Restfulness and the quality of sleep (mentally and physically restorative sleep) are dependent upon the comfort of sleepers. When sleepers become uncomfortable, they move to relieve the discomfort and the resulting moves are a normal part of sleep. When sleepers move, they frequently change to lighter stages of sleep or awaken. The more discomfort sleepers feel, the more they will move and the more time they will spend in lighter and less restful sleep. Good sleeping is normally associated with a minimum number of interruptions of sleep stages due to a low number of body shifts during the sleep period. The higher the number of interruptions, the more fragmented the sleep and the less restful the sleep.

Comfortable mattresses are important in establishing restful sleep. Bed-induced shifts due to discomfort caused by the bed are a significant cause of poor sleep quality. On conventional mattresses (including feather beds, inner spring mattresses, foam mattresses, orthopedic mattresses, waterbeds, airbeds and the like), most people experience as many as forty major postural body shifts in the course of a night's sleep. Poor sleepers experience as much as sixty percent more major shifts than good sleepers. While some shifts during a sleep period are beneficial, the quality of sleep can be greatly improved for many by reducing the number of bed-induced shifts.

There are two major causes of bed-induced shifting that cause poor sleep. The first major cause of shifting is excessive pressure on parts of the body and the second major cause of shifting is the body's spinal misalignment.

Considering the first major cause of shifting, the buildup of pressures results from prolonged lying in the same position. On conventional mattresses, the pressure tends to be greatest on the body's protrusions (such as shoulders and hips) where body tissues are put in high compression against the mattress. High compression tends to restrict capillary blood flow, which is recognized by the body, after a period of time, as discomfort. The amount of pressure, which causes a discontinuance of capillary blood flow is called the ischemic pressure. The ischemic pressure threshold is normally considered to be approximately thirty mmHg. The discontinuance of capillary blood flow is observable as a red spot on the skin (reactive hyperemia). After pressure is applied, a red spot on the skin is a precursor to tissue damage. When parts of the body (usually shoulders and hips in conventional mattresses) are subjected to pressures above the ischemic threshold, discomfort results and, hence, a person shifts to remove the discomfort and threat to tissue damage.

Considering the second major cause of shifting, body misalignment results from

spinal misalignment due to lateral bending of the vertebral column of the body, particularly for a person in a side-sleeping position. Such lateral bending is typically caused by mattresses that allow sagging of the torso region of the body. Conventional mattresses allow such sagging regardless of the hardness or the softness of the mattress but the spinal sagging effect tends to be more pronounced on firm mattresses. A sagging mattress allows the upper torso (thoracic region) to drop relative to the hips and results in stress to muscles and ligaments. The stress from a sagging mattress frequently manifests as discomfort or even pain in the lumbar region of the back. Such discomfort causes the sleeper to shift in order to relieve the discomfort and avoid tissue damage.

Similarly, when lying in the supine position, the hips form a higher support point than the lumbar region of the spine. A flattening of the lumbar spine due to gravity then occurs and this, again, brings stress to the soft tissues and causes a turning away from this position to avoid discomfort and tissue damage.

In U.S. Patent No. 6,807,698, a bed having low body pressure and alignment includes a mattress for supporting a recumbent body. The mattress includes a resilient top member having a top region possessing uniform placement parameters and also includes resilient supporting means supporting the top member with variable displacement. The combination of members with uniform displacement parameters over members with variable displacement parameters enables the mattresses to support the body in alignment and with uniform low pressure.

In U.S. Patent No. 7,036,172, a bed having low body pressure and alignment includes a mattress supporting a recumbent body with low body pressure and in alignment. The mattress extends in a lateral direction from side to side and extends in a longitudinal direction from a mattress head to a mattress foot where the mattress includes a head part, a shoulder part, a thoracic part, a hip part and a leg part. The recumbent body has a displacement profile that causes the mattress to undergo differing displacements when supporting the recumbent body. The mattress composite has displacement parameters varying to match the displacement profile of the recumbent body while supporting the recumbent body with low body pressure. The composite has a plurality of regions where the displacement in one or more of the regions varies to match the displacement profile of the recumbent body to maintain the recumbent body in alignment.

An ideal mattress has a resiliency over the length of a body on the mattress to support the body in spinal alignment and also has a low surface body pressure over all or most parts of the body in contact with the mattress. Since a recumbent body has both varying density and varying contour in the longitudinal direction, the ideal mattress must conform to these variations. With such variations, in order to achieve spinal alignment, the

supporting forces in the mattress, under load from the recumbent body, must vary along the body to match the varying body density and shape. Also, when the body is in spinal alignment, for an ideal mattress, the supporting pressures in the mattress against the skin must be low. The preferred pressure against the skin of a person in bed for an ideal
5 mattress is generally below the ischemic threshold. The preferred side-lying spinal alignment for a person in bed is generally defined as that alignment in which the spine is generally straight and on the same centerline as the legs and head, a condition that helps provide "spinal neutrality". "Spinal neutrality" is a condition in which the forces on the spine and ligaments have minimum stress, for example, the shear forces on the L1 and L5
10 vertebrae are a minimum.

While the general principles of an ideal mattress have been recognized, actual embodiments of mattresses that have properties that approach the properties of an ideal mattress at reasonable costs have not been fully satisfactory.

Developments in the parameters of and manufacturing capabilities for foam and
15 other materials have provided new components for mattresses that can be used to better approach the technical parameters required for an ideal mattress at economical costs and which can be manufactured with expected standard properties and with the attributes for mattresses that are desired by the public.

There are a number of properties useful in characterizing mattress materials
20 including "Hardness", "Density", "Indentation Load Deflection (ILD)" and "Tensile Strength". Hardness is the resistance against pressure. Density is the mass per unit volume. Hardness and density are interrelated. When density increases, hardness tends to increase. Generally for lower density materials, a growing loss in hardness arises after repeated loading. Tensile Strength is the measure of the resistance against stretching and changes in tensile strength
25 are measured as Tensile % and changes in length after applying a tensile force are measured as Elongation %. Indentation Load Deflection (ILD) is a hardness measurement defined in the ISO 2439 standard. Indentation Load Deflection is defined as the force that is required to compress material a percentage of its original thickness, that is, compressed 25%, 40% and 60% from its original thickness (using in the standard a circular plate of 322
30 cm.sup.2). These Indentation Load Deflections are designated ILD.sub.25%, ILD.sub.40% and ILD.sub.60%.

In consideration of the above background, there is a need for improved mattresses that better approach the properties of ideal mattresses and that can be economically manufactured while satisfying the public expectations and demands for mattresses. The
35 present invention fulfills this long-standing need and desire in the art.

SUMMARY OF THE INVENTION

The present invention is directed to a mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low pressure support to a recumbent body. The mattress comprises a performance layer and a core layer disposed below the performance layer for supporting the performance layer. The performance layer along the longitudinal direction thereof comprises a first shoulder section with first shoulder displacement parameters disposed on an end thereof configured to support a shoulder region of the recumbent body. A first thoracic section with first thoracic displacement parameters is disposed next to a distal end of the first shoulder section configured to support a thoracic region of the recumbent body. A hip section with hip displacement parameters disposed next to a distal end of the first thoracic section configured to support a hip region of the recumbent body. The present invention is directed to a related mattress further comprising a cover having a top, sides and a bottom disposed in a covering relationship to the performance layer and the core layer.

The present invention also is directed to a mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low-pressure support to a recumbent body. The recumbent body has a displacement profile on the mattress where the displacements of a shoulder region, a thoracic region and a hip region of the body on the mattress are different. The mattress comprises a performance layer and a core layer disposed below the performance layer configured to support the performance layer. The performance layer, along the longitudinal direction, comprises a first shoulder section with first shoulder displacement parameters disposed on an end thereof configured to support a shoulder region of the recumbent body. A first thoracic section with first thoracic displacement parameters is disposed next to a distal end of the first shoulder section configured to support a thoracic region of the recumbent body. A hip section with hip displacement parameters disposed next to a distal end of the first thoracic section configured to support a hip region of the recumbent body. A second thoracic section with second thoracic displacement parameters is disposed next to a distal end of the hip section. A second shoulder section with second shoulder displacement parameters is disposed at an end of the performance layer opposite to the end of the first shoulder section in the longitudinal direction. The present invention is directed to a related mattress further comprising a cover in a covering relationship to the performance layer and the core layer and having a top, sides, and a bottom, and a first indicator stripe and a second indicator stripe disposed on the top of the cover at positions corresponding to positions of the first thoracic section and the second thoracic section respectively.

Other and further aspects, features, benefits, and advantages of the present invention will be apparent from the following description of the presently preferred embodiments of the invention given for the purpose of disclosure.

5

BRIEF DESCRIPTION OF THE DRAWINGS

So that the matter in which the above-recited features, advantages and objects of the invention, as well as others that will become clear, are attained and can be understood in detail, more particular descriptions of the invention briefly summarized above may be had by reference to certain embodiments thereof that are illustrated in the appended drawings. These drawings form a part of the specification. It is to be noted, however, that the appended drawings illustrate preferred embodiments of the invention and therefore are not to be considered limiting in their scope.

FIG. 1 depicts an isometric view of a bed including a mattress formed from foam layers having varying displacement parameters capable of supporting a recumbent body with low body pressure and in alignment.

FIG. 2 depicts an isometric view of the mattress without a bedframe. The mattress is formed from foam layers having varying displacement parameters capable of supporting a recumbent body with low body pressure and in alignment.

FIG. 3 depicts an expanded view of an indicator in the cover of the mattress formed from foam layers having varying displacement parameters capable of supporting a recumbent body with low body pressure and in alignment.

FIG. 4 depicts a cover fabric lying in the XY-plane and to be used in covering a mattress composite.

FIG. 5 depicts the bottom view of a mattress with the cover of FIG. 3 attached to a bottom piece by a zipper.

FIG. 6 depicts a top view of a mattress composite for a twin size mattress.

FIG. 7 depicts a front view of the mattress composite for a twin size mattress.

FIG. 8 depicts an end view of the mattress composite of FIG. 6 and FIG. 7.

FIG. 9 depicts a top view of a mattress composite for a twin Long size mattress.

FIG. 10 depicts a front view of the mattress composite of FIG. 9.

FIG. 11 depicts an end view of the mattress composite of FIG. 9 and FIG. 10.

FIG. 12 depicts a top view of a mattress composite for a Full size mattress.

FIG. 13 depicts a front view of the mattress composite of FIG. 12.

FIG. 14 depicts an end view of the mattress composite of FIG. 12 and FIG. 13.

FIG. 15 depicts a top view of a mattress composite for a queen mattress.

FIG. 16 depicts a front view of the mattress composite of FIG. 15.

FIG. 17 depicts an end view of the mattress composite of FIG. 15 and FIG. 16.

FIG. 18 depicts a top view of a mattress composite for an Eastern King mattress.

FIG. 19 depicts a front view of the mattress composite of FIG. 18.

5 FIG. 20 depicts an end view of the mattress composite of FIG. 18 and FIG. 19.

FIG. 21 depicts a top view of a mattress composite for a California King mattress.

FIG. 22 depicts a front view of the mattress composite of FIG. 21.

FIG. 23 depicts an end view of the mattress composite of FIG. 21 and FIG. 22.

FIG. 24 depicts a side lying female recumbent body on a mattress composite.

10 FIG. 25 depicts a side lying male recumbent body on a mattress composite.

FIG. 26 depicts the side lying male recumbent body on a mattress composite of FIG. 25 with a cutaway to show the skeleton of the body.

FIG. 27 depicts side by side male and female bodies on a mattress with cutaway views of the mattress cover.

15 FIG. 28 depicts the male body of FIG. 27 with a cutaway view to show the skeleton and its position over the mattress composite.

FIGS. 29A-29D depicts two-way configurations for the performance layer of the mattress. FIG. 29A shows that the mattress comprises two shoulder sections disposed at the opposite ends thereof, a first thoracic section disposed next to the distal end of the first shoulder section and a hip section disposed between the first thoracic section and the second shoulder section; FIGS. 29B-29D shows that a second thoracic section of the performance layer is disposed next to the proximal end of the second shoulder section. FIG. 29B shows a thin layer of the hip section is disposed therebelow to compensate the thickness thereof; FIG. 29C shows that the second thoracic section of the performance layer has a thin layer of the hip section disposed thereabove to compensate the thickness; FIG. 29D shows that the second thoracic section of the performance layer has a thin layer of the second shoulder section disposed thereabove to compensate the thickness.

20

25

DETAILED DESCRIPTION OF THE INVENTION

30

As used herein in the specification, "a" or "an" may mean one or more. As used herein in the claim(s), when used in conjunction with the word "comprising", the words "a" or "an" may mean one or more than one.

As used herein "another" or "other" may mean at least a second or more of the same or different claim element or components thereof. Similarly, the word "or" is intended to include "and" unless the context clearly indicates otherwise. "Comprise" means "include."

35

As used herein, the term “about” refers to a numeric value, including, for example, whole numbers, fractions, and percentages, whether or not explicitly indicated. The term “about” generally refers to a range of numerical values (e.g., +/- 5-10% of the recited value) that one of ordinary skill in the art would consider equivalent to the recited value (e.g.,
5 having the same function or result). In some instances, the term “about” may include numerical values that are rounded to the nearest significant figure.

As used herein, the term “distal” refers to a direction away from the first shoulder section of the performance layer. The term “proximal” refers to a direction toward the first shoulder section of the performance layer.

10 As used herein, the phrase "maintained in alignment" refers to an alignment from head to foot of a body that avoids or reduces lateral bending of the vertebral column of the body, particularly for a person in a side-sleeping position, and that eliminates or reduces sagging of the body.

As used herein, the term "displacement parameters" refers to any and all the
15 properties and characteristics of materials that determine the static and dynamic tension and compression properties of a mattress.

In one embodiment of the present invention, there is provided a mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low-pressure support to a recumbent body, comprising a performance layer, along the longitudinal
20 direction thereof comprising a first shoulder section with first shoulder displacement parameters disposed on an end thereof configured to support a shoulder region of the recumbent body; a first thoracic section with first thoracic displacement parameters disposed next to a distal end of the first shoulder section configured to support a thoracic region of the recumbent body; and a hip section with hip displacement parameters disposed next to a
25 distal end of the first thoracic section configured to support a hip region of the recumbent body; and a core layer disposed below the performance layer for supporting the performance layer.

Further to this embodiment, the mattress may comprise a cover having a top, sides and a bottom disposed in a covering relationship to the performance layer and the core
30 layer. In this further embodiment, the top and the sides of the cover may comprise a highly stretchable material such that the cover has substantially no effect on the displacement parameters and vertical compression thereof when supporting the recumbent body. For example, the highly stretchable material may have a tensile strength that increases stretching of the cover about 12% or more in the longitudinal direction and about 16% or
35 more in the lateral direction when a recumbent body is on the mattress.

Further still, the cover may comprise a fire retarding material. Also, the cover may further comprise a zipper disposed in a zippering relationship between the top and sides and the bottom of the cover. In addition, the cover may further comprise an indicator stripe disposed on the top of the cover at a position corresponding to a position of the first thoracic section of the performance layer.

In another further embodiment, the performance layer of the mattress may further a second shoulder section with second shoulder displacement parameters disposed at an opposite end of the performance layer to the first shoulder section in the longitudinal direction. Further still, the performance layer of the mattress may comprise a second thoracic section with second thoracic displacement parameters disposed next to an proximal end of the second shoulder section. Further still, the mattress may comprise a cover in a covering relationship to the performance layer and the core layer of the mattress comprising a top, sides, and a bottom, and two indicator stripes disposed on the top of the cover at positions corresponding to the first thoracic section and the second thoracic section respectively.

In an aspect of these further embodiments, the second thoracic section may be thinner than the hip section with a layer of the hip section disposed therebelow to compensate for a thickness thereof such that the performance layer has a uniform thickness. In another aspect, the second thoracic section may be thinner than the hip section with a layer of the hip section disposed thereabove to compensate for a thickness thereof such that the performance layer has a uniform thickness. In yet another aspect, the second thoracic section may be thinner than the second shoulder section with a layer of the second shoulder section disposed thereabove to compensate for a thickness thereof such that the performance layer has a uniform thickness.

In all embodiments, the displacement parameters may include but are not limited to an indentation load deflection and a density. In this particular embodiment the indentation load deflections of the first thoracic section and the second thoracic section are greater than the indentation load deflection of the hip section, which is greater than indentation load deflections of the first shoulder section and the second shoulder section. The exemplary value for the indentation load deflection of the first shoulder section and the second shoulder section may be about 18 to about 19. In this exemplary value the indentation load deflection of the first thoracic section and second thoracic section may be about 27 to about 28 and the indentation load deflection of the hip section is about 23 to about 24. Also in this particular embodiment, a density of the first shoulder section and the second shoulder section is about 2 lb/cf to about 3.5 lb/cf, a density of the first thoracic section and the second thoracic

section is about 2 lb/cf to about 3.5 lb/cf, and a density of the hip second is about 2 lb/cf to about 3.5 lb/cf.

Also, in all embodiments, the core layer may have an indentation load deflection of about 36 and a density of about 1.8 lb/cf. In addition, the performance layer and the core layer may comprise polyurethane, latex or a combination thereof. For example, the performance layer may comprise latex and the core layer may comprise polyurethane. In this embodiment, the mattress may further comprise a fire retarding material disposed on the sides of the performance layer and the core layer.

In another embodiment of the present invention, there is provided a mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low-pressure support to a recumbent body. The recumbent body having a displacement profile on the mattress where displacements of a shoulder region, a thoracic region and a hip region of the recumbent body on the mattress are different. The mattress comprises a performance layer comprising along the longitudinal direction thereof a first shoulder section with first shoulder displacement parameters disposed on an end of thereof configured to support a shoulder region of the recumbent body; a first thoracic section with first thoracic displacement parameters disposed next to a distal end of the first shoulder section configured to support a thoracic region of the recumbent body; and a hip section with hip displacement parameters disposed next to a distal end of the first thoracic section configured to support a hip region of the recumbent body; a second thoracic section with second thoracic displacement parameters disposed next to a distal end of the hip section configured to support a thoracic region of the recumbent body; a second shoulder section with second shoulder displacement parameters disposed at an end of the performance layer opposite to the end of the first shoulder section in the longitudinal direction; and a core layer disposed below the performance layer configured to support the performance layer.

Further to this embodiment, the mattress may comprise a cover in a covering relationship to the performance layer and the core layer, and having a top, sides, and a bottom, and a first indicator stripe and a second indicator stripe disposed on the top of the cover at positions corresponding to positions of the first thoracic section and the second thoracic section respectively. Further still, the cover may comprise a fire retarding material.

In one aspect of these embodiments, the second thoracic section may be thinner than the hip section with a layer of the hip section disposed therebelow to compensate for a thickness thereof such that the performance layer has a uniform thickness. In another aspect of this embodiment, the second thoracic section may be thinner than the hip section with a layer of the hip section disposed thereabove to compensate for a thickness thereof such that the performance layer has a uniform thickness. In yet another aspect of this

embodiment, the second thoracic section may be thinner than the second shoulder section with a layer of the second shoulder section disposed thereabove to compensate for a thickness thereof such that the performance layer has a uniform thickness.

In all embodiments and aspects thereof, the displacement parameters may comprise, but are not limited to, an indentation load deflection and a density. In this particular embodiment the indentation load deflections of the first thoracic section and the second thoracic section may be greater than the indentation load deflection of the hip section, which is greater than indentation load deflections of the first shoulder section and the second shoulder section.

For example, in this particular embodiment, the indentation load deflection of the first shoulder section and the second shoulder section may be from about 18 to about 19, the indentation load deflection of the first thoracic section and second thoracic section is about 27 to about 28 and the indentation load deflection of the hip section is about 23 to about 24. Also, in this particular embodiment, a density of the first shoulder section and the second shoulder section may be about 2 lb/cf to about 3.5 lb/cf, a density of the first thoracic section and the second thoracic section is about 2 lb/cf to about 3.5 lb/cf, and a density of the hip second is about 2 lb/cf to about 3.5 lb/cf.

In all embodiments and aspects thereof, the core layer may have an indentation load deflection of about 36 and a density of about 1.8 lb/cf. Also, the performance layer and the core layer may comprise, but are not limited to, polyurethane, latex or a combination thereof. Preferably, the performance layer comprises latex and the core layer comprises polyurethane. In addition, the mattress may further comprise a fire retarding material disposed on the sides of the performance layer and the core layer.

As described below, the invention provides a number of advantages and uses, however such advantages and uses are not limited by such description. Embodiments of the present invention are better illustrated with reference to the Figure(s), however, such reference is not meant to limit the present invention in any fashion. The embodiments and variations described in detail herein are to be interpreted by the appended claims and equivalents thereof.

FIG. 1 depicts an isometric view of a bed 1 having a mattress 1-1 which is capable of supporting a recumbent body (not shown) where the recumbent body is supported by low body pressure and where the recumbent body is maintained in alignment. The terminology "low body pressure" means a pressure, which is below a pressure threshold (typically the ischemic threshold) for comfortable sleep and of a level which materially reduces the causes of bed-induced shifting.

In FIG. 1, the bed 1 has a mattress 1-1 supported by a supporting foundation 26 and frame 21. The foundation 26 is a box spring, firm box, board or other conventional mattress support. The supporting frame 21 may be any frame and as shown in one embodiment is a conventional "Hollywood" or "Harvard" style of bed frame that is made from right-angled channels and is supported by legs 6 having casters. The bed 1 and mattress 1-1 extend in the longitudinal direction (X-axis direction) from a mattress head 5-1' at bed head 5-1 to a mattress foot 5-2' at bed foot 5-2. The bed 1 and mattress 1-1 also extend in the lateral direction (Y-axis direction) normal to the X-axis and extend in the vertical direction (Z-axis direction) normal to the plane formed by the X axis and the Y-axis.

The mattress 1-1 is for supporting a recumbent person (see recumbent persons in FIG. 24 through FIG. 28, for example) where a person's recumbent body includes a head and shoulder part, a thoracic part, a hip part and a leg part. The mattress 1-1 supports a recumbent body positioned in the longitudinal direction with the head part toward the mattress head 5-1' and the leg part toward the mattress foot 5-2'. A body reclining on mattress 1-1 depresses portions of the mattress 1-1 causing the mattress to compress in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis).

In FIG. 1, the mattress 1-1 includes a composite 1₁ formed of foam member 10, including sections 10-1, 10-2 and 10-3 and a foam member 11. The term "foam" means rubber, plastic, latex, memory foam, urethane, polyurethane, polymer or other material having a cellular structure containing voids to make it soft and resilient, for example, a material filled with many small bubbles of air. The mattress 1-1 has a top side 4-1 and a bottom side 4-2. The members 10 and member 11 support and distribute the weight of a recumbent body (not shown). The members 10 have displacement parameters for providing supporting surface pressure to the recumbent body.

The mattress 1-1 includes an outer cover 3 that encloses the inner foam member 10 and the foam member 11. The cover 3 is formed of stretch material which stretches in both the X-axis and Y-axis directions which sometimes is called a four way stretch. The amount of the stretch allows depression of a recumbent body into the composite 1₁ without significantly modifying the load deflection parameters of the composite 1₁.

The member 10 extends in the longitudinal direction (X-axis direction) from the head 5-1' to the foot 5-2'. The sections 10-1, 10-2 and 10-3 of the member 10 extend in rows in the lateral direction (Y-axis direction) to establish displacement parameters that vary in at least the vertical (Z-axis) direction as a function of the longitudinal position (X-axis position). The sections 10-1, 10-2 and 10-3 undergo different vertical compressions as a function of the longitudinal position (X-axis position) in order to follow the curvature of the recumbent

body so as to establish alignment of the shoulder, thorax, hip and leg parts of the body so as to establish uniform low supporting surface pressure on the body.

In the embodiment of FIG. 1, the foam member 10 has different displacement parameters that determine the compression that occurs in the mattress 1-1 in response to a recumbent body. The sections 10-1, 10-2 and 10-3 of the member 10 function to divide the mattress 1-1 into 1ST, 2ND and 3RD regions. The 1ST region is established by section 10-1 extending to the head of the mattress 5-1' and is for location beneath the head and shoulder parts of a recumbent body. The 2ND region is established by the section 10-2 for location beneath the thoracic part of a body. The 3RD region is established by the member 10-3 for location beneath the hip and leg parts of the body and extending to the foot of the mattress 5-2'. The sections 10-1, 10-2 and 10-3 of the member 10 have different displacement parameters that help establish the different compressions that occur in each of the 1ST, 2ND and 3RD regions in order to achieve alignment of a recumbent body with low supporting body pressure.

The mattress 1-1 includes a cover 3 formed, at least on the top portion, by a stretch fabric. The cover 3 is about 1/16 inch thick extending along the top, sides and bottom portions of the mattress 1-1. The cover 3 functions to cover and contain the inner members 10 and 11 of the mattress and the cover 3 has displacement parameters that provide a soft surface without interfering with the displacement parameters of the inner members 10 and 11 of the mattress 1-1. In some embodiments, the mattress 1-1 includes a fire retarding sock 37 encapsulating the composite 1₁. The sock 37 is a material that provides fire retardation and provides high stretch. The fire retarding sock 37 stretches in both the X-axis and Y-axis directions which sometimes is called a four way stretch. The amount of the stretch allows depression of a recumbent body into the composite 1₁ without significantly modifying the load deflection parameters of the composite 1₁. When the mattress comprises polyurethane and, particularly, latex, an additional fire retarding fabric is adhered around the sides, including the left side, the right side, the head panel, and the foot panel, of the mattress to meet fire safety rules.

In FIG. 2, the mattress 1-1 from the bed 1 of FIG. 1 is shown. The mattress 1-1 is for supporting a recumbent body positioned in the longitudinal direction with the head part toward the mattress head 5-1' and the leg part toward the mattress foot 5-2'. The mattress 1-1 includes 1ST, 2ND and 3RD regions for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on mattress 1-1 depresses portions of the mattress 1-1 causing the mattress

to compress in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis).

In FIG. 2, the mattress 1-1 has a length L in the X-axis direction, a width W in the Y-axis direction and a thickness T in the Z axis direction. The L, W and T dimensions can be any values but typical values in the United States for one embodiment of mattresses are as set forth in the following TABLE 1.

TABLE 1						
	L	1st	2nd	3rd	W	T
Twin	75	20	8	47	39	10
Twin Long	80	22	10	48	39	10
Full	75	20	8	47	54	10
Queen	80	22	10	48	60	10
Eastern King	80	22	10	48	76	10
California King	84	22	10	52	72	10

In FIG. 2, the mattress 1-1 includes an indicator stripe 10-M that indicates the location of the thoracic section 10-2 of the layer 10 of mattress 1-1 of FIG. 1. The indicator stripe 10-M includes indicia such as text which identifies the head direction 5- 1' of the mattress 1-1 as well as indicating the location of the thoracic section 10-2 beneath it. Typically, the indicator stripe 10-M is part of the cover 3 and in one embodiment is weaved into the cover material 3.

In FIG. 3, an expanded view of the indicator stripe 10-M in the cover 3 of FIG. 2 is shown. The indicator stripe 10-M includes indicia 10-S which in the embodiment shown is text "LEVELsleep Levelsleep" on the top and "Smart Support Smart Support" underneath. The text "LEVELsleep LEVELsleep" and "Smart Support Smart Support" is repeated multiple times in the Y-axis direction. As indicated in FIG. 2, the text is on the side of and extends all the way across the top of the mattress 1-1. A person standing on the side of the mattress 1-1 would tend to read text "LEVELsleep LEVELsleep" and "Smart Support Smart Support" in the right side up orientation when the indicator stripe 10-M is closer to the top 5-1 in the bed 1 of FIG. 1. Hence the text tends to identify the head direction 5-1' of the mattress 1-1. A person standing on the side of the mattress 1-1 would tend to read text "LEVELsleep LEVELsleep" and "Smart Support Smart Support" in the up side down orientation when the indicator stripe 10-M is closer to the bottom 5-2 in the bed 1 of FIG. 1. The up side down orientation tends to identify when the mattress 1-1 is being positioned in the wrong direction

on the bed 1. The indicator stripe 10-M and indicia 10-S improves a user's appreciation of the biomechanical nature of the mattress.

In FIG. 4, a cover 3 (ticking) is shown lying in the XY-plane and is sized in FIG. 4 for a queen size mattress. The cover 3 is typically cut as a single piece from a role of fabric equal to or greater than 103" wide. The center portion of the cover 3 measures 80" by 60" and is surrounded by 11.5" extensions 3-1, 3-2, 3-3 and 3-4 indicated by broken lines around the 80" by 60" center. The overall dimensions of the cover 3 including extensions 3-1, 3-2, 3-3 and 3-4 is 103" by 83". The extensions 3-1, 3-2, 3-3 and 3-4 include terminating extensions 3-1-1, 3-2-1, 3-3-1 and 3-4-1 that are each about 1.5" from the outermost edges. To form the cover 3, each of the extensions 3-1, 3-2, 3-3 and 3-4 are folded in the Z-axis direction normal to the XY-plane of FIG. 4. The openings between the extensions 3-1, 3-2, 3-3 and 3-4 in the Z-axis direct are sewn or otherwise attached together so as to form a box-like structure around the mattress composite 11 of FIG. 1.

In FIG. 5, a bottom view of a mattress 1-1 of FIG. 1 and FIG. 2 is shown with the cover of FIG. 4 attached to a bottom piece 66 by a zipper 39 that is sewn or otherwise attached to the terminating extensions 3-1-1, 3-2-1, 3-3-1 and 3-4-1 on one side and to the bottom piece 66 on the other side. The zipper 39 is zipped and unzipped by the zipper handle 38. When unzipped, the cover 3 can be removed from the bottom piece 66 and the mattress composite 11 can be removed from the cover 3.

In FIG. 6, a top view of a mattress composite 11 is shown in the XY -plane for a Twin size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 11 includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y -axis direction. The 1ST, 2ND and 3RD regions of the mattress composite h are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 39" width of the composite 11 in the Y-axis direction. In the X-action direction, the section 10-1 is 20", the section 10-2 is 8" and the section 10-3 is 47" whereby the composite 11 is 75" long in the X-axis direction.

In FIG. 7, a front view of a mattress composite 11 of FIG. 6 is shown in the XZ-plane. The mattress composite 1₁ includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 39" width of the composite 11 in the Y-axis direction. In the X-action direction, the section 10-1 is 20", the

section 10-2 is 8" and the section 10-3 is 47". The layer 10 and each of the sections 10-1, 10-2 and 10-3 a 3" thick foam and are supported by a 7" foam layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 17, and a density of 2 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane foam with an ILD of 23, and a density of 2 lb/cf. While the ILD's and densities are preferred for the embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is more firm than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 8, an end view of a mattress composite 1₁ of FIG. 6 and FIG. 7 is shown in the YZ-plane. The mattress composite 1₁ includes layer 10 and shows the section 10-3 extending across the 39" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 1₁ supports the layer 10 and extends across the 39" width of the composite 1₁ in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 9, a top view of a mattress composite 1₁ is shown in the XY-plane for a Twin Long size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 1₁ includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y-axis direction. The 1ST, 2ND and 3RD regions of the mattress composite 1₁ are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in

the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 39" width of the composite 11 in the Y-axis direction. In the X-action direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48" whereby the composite is 80" long in the X-axis direction.

In FIG. 10, a front view of a mattress composite h of FIG. 9 is shown in the XZ plane. The mattress composite 11 includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 39" width of the composite 1₁ in the Y-axis direction. In the X-action direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48". The layer 10 and each of the sections 10-1, 10-2 and 10-3 are 3" thick foam and are supported by a 7" foam core layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2.0 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 27, and a density of 2.0 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane foam with an ILD of 23, and a density of 2.0 lb/cf. While the ILD's and densities are preferred for one embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is firmer than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 11, an end view of a mattress composite 1₁ of FIG. 9 and FIG. 10 is shown in the YZ-plane. The mattress composite 11 includes layer 10 and shows the section 10-3 extending across the 39" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 11 supports the layer 10 and extends across the

39" width of the composite 1₁ in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 12, a top view of a mattress composite 11 is shown in the XY-plane for a Twin Long size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 1₁ includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y-axis direction. The 1ST, 2ND and 3RD regions of the mattress composite 1₁ are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 54" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 20", the section 10-2 is 8" and the section 10-3 is 47" whereby the composite 11 is 75" long in the X-axis direction.

In FIG. 13, a front view of a mattress composite 11 of FIG. 12 is shown in the XZ plane. The mattress composite 11 includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 54" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 20", the section 10-2 is 8" and the section 10-3 is 47". The layer 10 and each of the sections 10-1, 10-2 and 10-3 are 3" thick foam and are supported by a 7" foam core layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 27, and a density of 2 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane foam with an ILD of 23, and a density of 2 lb/cf. While the ILD's and densities are preferred for one embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is more firm than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 14, an end view of a mattress composite 1₁ of FIG. 12 and FIG. 13 is shown in the YZ-plane. The mattress composite 11 includes layer 10 and shows the section 10-3 extending across the 39" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 11 supports the layer 10 and extends across the 54" width of the composite 11 in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 15, a top view of a mattress composite is shown in the XY-plane for a Queen size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 1₁ includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y-axis direction. The 1ST, 2ND and 3RD regions of the mattress composite 1₁ are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 60" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48" whereby the composite is 80" long in the X-axis direction.

In FIG. 16, a front view of a mattress composite 1₁ of FIG. 15 is shown in the XZ plane. The mattress composite 11 includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 60" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48". The layer 10 and each of the sections 10-1, 10-2 and 10-3 are 3" thick foam and are supported by a 7" foam core layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 27, and a density of 2 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane

foam with an ILD of 23, and a density of 2 lb/cf. While the ILD's and densities are preferred for one embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is more firm than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 17, an end view of a mattress composite h of FIG. 15 and FIG. 16 is shown in the YZ-plane. The mattress composite 1₁ includes layer 10 and shows the section 10-3 extending across the 60" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 11 supports the layer 10 and extends across the 60" width of the composite 1₁ in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 18, a top view of a mattress composite h is shown in the XY-plane for an Eastern King size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 1₁ includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y-axis direction. The 1ST, 2ND and 3RD regions of the mattress composite 1₁ are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 76" width of the composite h in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48" whereby the composite 1₁ is 80" long in the X-axis direction.

In FIG. 19, a front view of a mattress composite 1₁ of FIG. 18 is shown in the XZ plane. The mattress composite 1₁ includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 76" width of

the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 48". The layer 10 and each of the sections 10-1, 10-2 and 10-3 are 3" thick foam and are supported by a 7" foam core layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 27, and a density of 2 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane foam with an ILD of 23, and a density of 2 lb/cf. While the ILD's and densities are preferred for one embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is more firm than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 20, an end view of a mattress composite 11 of FIG. 18 and FIG. 19 is shown in the YZ-plane. The mattress composite 11 includes layer 10 and shows the section 10-3 extending across the 76" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 11 supports the layer 10 and extends across the 76" width of the composite 1₁ in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 21, a top view of a mattress composite is shown in the XY-plane for a California King size mattress 1-1 of the type shown in FIG. 1 and FIG. 2. The mattress composite 1₁ includes 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across in the Y-axis direction. The 1ST, 2ND and 3RD regions of the mattress composite 1₁ are for supporting a recumbent person where a person's recumbent body includes a head and shoulder part intended for the 1ST region, a thoracic part intended for the 2ND region and a hip part and a leg part intended for 3RD region. A

body reclining on a mattress having the composite 1₁ depresses portions of the sections 10-1, 10-2 and 10-3 in the vertical direction (Z-axis direction) normal to the XY plane (formed by the X-axis and the Y-axis). The 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction each extend across the 72" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 52" whereby the composite 1₁ is 84" long in the X-axis direction.

In FIG. 22, a front view of a mattress composite 1₁ of FIG. 21 is shown in the XZ plane. The mattress composite 1₁ includes layer 10 having 1ST, 2ND and 3RD sections 10-1, 10-2 and 10-3, respectively, in the X-axis direction, each extending across the 72" width of the composite 1₁ in the Y-axis direction. In the X-axis direction, the section 10-1 is 22", the section 10-2 is 10" and the section 10-3 is 52". The layer 10 and each of the sections 10-1, 10-2 and 10-3 are 3" thick foam and are supported by a 7" foam core layer 11.

The layer 10 is the performance layer which in one preferred embodiment is 3" thick in the Z-axis direction. The thickness can vary and typically is between 2" and 4". In the embodiment described, the section 10-1, for the head and shoulder region, is polyurethane foam with an ILD of 18, and a density of 2 lb/cf. In the embodiment described, the section 10-2, for the thoracic region, is polyurethane foam with an ILD of 27, and a density of 2 lb/cf. In the embodiment described, the section 10-3, for the hip and leg region, is polyurethane foam with an ILD of 23, and a density of 2 lb/cf. While the ILD's and densities are preferred for one embodiment described, these values may be different typically in a range of $\pm 20\%$. While polyurethane foam is used in one particular embodiment, latex and other foams are also employed in other embodiments.

In the performance layer 10, the thoracic section 10-2 is more firm than the head and shoulder section 10-1 and the hip and leg section 10-3. With this relationship, the head and shoulder section 10-1 and the hip and leg section 10-3 are able to depress in the Z-axis direction greater than the depression of the thoracic section 10-2. This relationship helps to establish proper alignment of the recumbent body.

The core layer 11 is the base layer, for supporting the performance layer 10, and in one preferred embodiment is 7" thick in the Z-axis direction. The thickness can vary and typically is between 6" and 10". In the embodiment described, the core layer 11 is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf and these values may vary typically in a range of $\pm 20\%$.

In FIG. 23, an end view of a mattress composite 1₁ of FIG. 21 and FIG. 22 is shown in the YZ-plane. The mattress composite 1₁ includes layer 10 and shows the section 10-3 extending across the 72" width of the composite 1₁ in the Y-axis direction with a height of 3" in the Z-axis direction. The foam core layer 11 supports the layer 10 and extends across the

72" width of the composite 1₁ in the Y-axis direction with a height of 7" in the Z-axis direction.

In FIG. 24, a side lying female recumbent body 136 is supported on a mattress composite 1₁ of the FIG. 1 and FIG. 2 type. The female body 136 is recumbent on her side parallel to the XZ-plane (sagittal plane). The body 136 is in alignment as indicated by the axis 18 which is generally straight through the body 136. The axis 18 is slightly inclined (for example, approximately 2 degrees) relative to the XY-plane with the axis 18 near the head slightly elevated relative to the axis 18 near the legs. The composite 1₁ has varying displacement parameters that function to support a recumbent body 136 with low body pressure and alignment.

In FIG. 24, the composite 1₁ has 1ST, 2ND and 3RD regions that receive body pressures P1, P2 and P3, respectively. The 1ST region extends to the head of the mattress 5-1' and is located beneath the head and shoulder parts of a body 136. The shoulder part of a body 136 at one location exerts a pressure P1 against the composite 1₁. The 2ND region is located beneath the thoracic part of a body 136 and at one point exerts a pressure P2 against the composite 1₁. The 3RD region is located beneath the hip part of the body 136 in the trochanter region 19 and exerts pressure P3 against the composite 1₁. The varying displacement parameters of the composite 1₁ function to support the recumbent body 136 with low body pressure and alignment.

In FIG. 25, a side lying male recumbent body 135 is supported on a mattress composite 1₁ of the FIG. 1 and FIG. 2 type. The male body 135 is recumbent on his side parallel to the XZ-plane (sagittal plane). The body 135 is in alignment as indicated by the axis 18 which is generally straight through the body 135. The axis 18 is slightly inclined (for example, approximately 2 degrees) relative to the XY-plane with the axis 18 near the head slightly elevated relative to the axis 18 near the legs. The composite 1₁ has varying displacement parameters that function to support the recumbent body 135 with low body pressure and alignment.

In FIG. 25, the composite 1₁ has 1ST, 2ND and 3RD regions that receive body pressures P1, P2 and P3, respectively. The 1ST region extends to the head of the mattress 5-1' and is located beneath the head and shoulder parts of a body 135. The shoulder part of a body 135 at one location exerts a pressure P1 against the composite 1₁. The 2ND region is located beneath the thoracic part of the body 135 and at one point exerts a pressure P2 against the composite 1₁. The 3RD region is located beneath the hip part of the body 136 in the trochanter region 19 and exerts pressure P3 against the composite 1₁. The varying displacement parameters of the composite 1₁ support the recumbent body 135 with low body pressure and alignment.

In FIG. 26, the side lying male recumbent body 135 of FIG. 25 is shown with a partial cutaway to reveal the skeleton of the body. In FIG. 25, the composite 1₁ has 1ST, 2ND and 3RD regions that receive body pressures P1, P2 and P3, respectively. The 1ST region extends to the head of the mattress 5-1' and is located beneath the head and shoulder parts of a body 135. The shoulder part of a body 135 at one location exerts a pressure P1 against the composite 1₁. The 2ND region is located beneath the thoracic part of the body 135 and at one point exerts a pressure P2 against the composite 1₁. The 3RD region is located beneath the hip part of the body 136 in the pelvic girdle region 31 including the iliac crests 31-1 and 31-2 and the greater trochanter of the femur regions 19-1 and 19-2. The pressure P3 is exerted against the composite 1₁ in the pelvic girdle region 31. The varying displacement parameters of the composite 1₁ function to support the recumbent body 135 with low body pressure and alignment.

In FIG. 26, the thoracic section 10-2 of the performance layer 10 is located above the pelvic girdle region 31 and extends toward the head and terminates near the shoulder region 32. In order for a body to be properly located on the mattress relative to the thoracic section 10-2 of the performance layer 10. The difference in hardness can be felt by a hand or other part of the body. Also, the glue seam between section 10-2 and 10-3 is manufacture to leave a small glue bead extending across the width of the mattress that provides a tactile indication of the location of the thoracic region of the performance layer. The thoracic section and the hip section provide a tactile indication of the location of the thoracic region of the performance layer.

In FIG. 27, a partially cutaway top view of one embodiment of the mattress 1-1 of FIG. 1 and FIG. 2 is shown with a female body 136 on her back on the right and a male body 135 on his back on the left. The mattress 1-1 is the same type as described generally in connection with FIG. 1 through FIG. 23. In FIG. 27, a partially cutaway top view of parts of the mattress 1-1 of FIG. 1 is shown. The foam sections 10-1, 10-2 and 10-3 function to divide the mattress 1-1 into 1ST, 2ND and 3RD regions as described in connection with FIG. 1 and FIG. 23. The foam sections 10-1, 10-2 and 10-3 superimposed on foam member 11 (see FIG. 1) have varying displacement parameters that function to support the recumbent bodies 135 and 136 with low body pressure and alignment. In one embodiment when mattress 1-1 is a queen size, the length in the X-axis direction is about 80 inches and the width in the Y-axis direction is about 60 inches. Of course, the mattress 1-1 can be any conventional size as described in connection with FIG. 6 through FIG. 23.

In FIG. 27, the mattress 1-1 includes an indicator stripe 10-M that indicates the location of the thoracic section 10-2 of the mattress 1-1. The indicator stripe 10-M includes indicia such as text which identifies the head direction 5-1' of the mattress 1-1 as well as

indicating the location of the thoracic section 10-2 beneath it generally as described in connection with FIG. 2 and FIG. 3. Typically, the indicator stripe 10-M is part of the cover 3 and is weaved into the cover material 3. The cover 3 is a stretchable fabric, which stretches in the X-axis, Y-axis and Z-axis directions so as not to interfere with the varying displacement parameters of the mattress 1-1 function in order to support the recumbent bodies 135 and 136 with low body pressure and alignment.

In FIG. 28, a sectional cutaway side view of the mattress 1-1 of FIG. 27 is shown with a male body 135 recumbent on his back. The cutaway reveals the thoracic and pelvic girdle regions including the lumbar vertebrae extending from the thoracic 2ND region into the hip and leg 3RD region. The 3RD region includes the coccyx, the sacrum and the coccygeal vertebrae. Because various relatively thick and wide muscles (glutei muscles), tendons and ligaments are present in the 3RD region for a back-lying body, the pressure exerted by the back-lying body on the mattress 1-1 is not as disturbing as the pressure for a side-lying body.

FIGS. 29A-29D show various configuration of a two-way performance layer disposed on top of the core layer. The performance layer has a first shoulder section 10-1 at one end of the mattress and a second shoulder section 10-1' is disposed at the opposite end of the mattress. Both shoulder sections may have the same displacement parameters. In FIG. 29A, the performance layer has one thoracic section (the first thoracic section) 10-2 disposed next to the distal end of the first shoulder section. The hip section 10-3 of the performance in this configuration is disposed between the first thoracic section and the second section 10-1'. In other configurations shown in FIGS. 29B-29D, the performance layer further comprises a second thoracic section 10-2' disposed next to the proximal end of the second shoulder section. In this configuration, the hip section 10-3 of the performance layer is disposed between the two thoracic sections. The second thoracic is thinner than the other sections. In FIG. 29B, a thin layer of the hip section 10-3 is disposed below the second thoracic section to compensate the thickness thereof, ensuring a uniform thickness of the performance layer. Alternatively, in FIG. 29C, a thin layer of hip section 10-3 is disposed on top of the second thoracic section 10-2' to compensate the thickness thereof, ensuring a uniform thickness of the performance layer. In another alternative, shown in FIG. 29D, a thin layer of the second shoulder section 10-1' is disposed on top of the second thoracic section to compensate the thickness thereof, ensuring a uniform thickness of the performance layer. Overall, these configurations enable the mattress to be used in both directions with the shoulder region positioned on either end thereof. The configuration of FIG. 29A is designed for users do not need extra thoracic support (lumber support).

Referring generally to FIG. 1 and also to the other figures, the cover 3 is formed of a material, which provides a soft, luxurious feel while allowing full-contour performance of the mattress. In order to permit full-contour performance, the cover 3 is formed of a material having a stretchability that does not interfere with operation of the performance layer 10.

5 The performance layer 10 permits the shoulder region 10-1 and hip region 10-3 of the reclining body to depress deeper into the mattress at lower pressure than the depression of the thoracic region 10-2. A cover that does not adequately stretch increases the pressure on the shoulder region 10-1 and hip region 10-3 and impedes the depression in these regions. In general, it has been found that a cover that will stretch at least 12 % in the X-axis direction and at least 16% in the Y-axis direction for male and female bodies with a full
10 range of body weights within the 95 percentile is satisfactory. For example, a California King 84" long in the X-axis direction would stretch at least about 10" in the X-axis direction and a California King 72" wide in the Y-axis direction would stretch at least about 12" in the Y-axis direction.

15 The selection of the various materials and parameters for the mattress 1-1, including the cover 3, the performance layer 10, including the three sections 10-1, 10-2 and 10-3 and including the core 11 are made to enable persons to sleep with body pressure below the ischemic threshold.

Although the embodiments described are representative, many variations in the
20 mattresses are also included. One variation includes a performance layer 10 (referring generally to FIG. 1 and also to the other figures) in the composite 1₁ made of latex. In one latex embodiment for performance layer 10, the section 10-1 has a 19 ILD and a 3.5 lb/cf density, the section 10-2 has a 28 ILD and a 3.5 lb/cf density and the section 10-3 has a 24 ILD and a 3.5 lb/cf density. The core layer 11 is polyurethane and has an ILD of 36 and a 1.8
25 lb/cf density.

Although the embodiments described have used a core layer 11 of 7" with a performance layer of 3", the thickness of the core layer in the Z-axis direction is not critical to good full contour performance. Other typical core layer sizes are 10" and 12" but any core level thickness is acceptable to adjust the overall height of the composite 11 and the
30 mattress 1-1. The performance layer 10 is important for establishing good full-contour performance. Contour performance is achieved when a recumbent body is supported with low body pressure (generally below the ischemic threshold). In general, the performance layer can be increased in size by approximately 20% or more.

An efficient mattress, which achieves good full-contour performance, must also
35 achieve efficient manufacturability and low cost. Embodiments of the mattress achieve these objectives due to a number of parameters and features. One feature is that the composite 1

is simple in that it is formed with only two layers, a performance layer 10 and a core layer 11. The performance layer 10 is located at the top of the composite 1₁. Being at the top and just below the cover, a need for other foam layers is eliminated thereby providing a simple structure, which reduces parts and cost of assembly. The performance layer 10 is supported
5 by the robust core layer 11. The core layer 11 in one embodiment is polyurethane foam with an ILD of 36, and a density of 1.8 lb/cf. These values for core layer 11 mean that core layer 11 will tend not to sag over the life time of the mattress and hence provide the mattress 1-1 with long life properties. The performance layer 10 is in itself simple in that only three sections, section 10-1, section 10-2 and section 1-3, are provided and hence only two
10 vertical glue seems are required to form the performance layer 10, one between section 10-1 and section 10-2 and one between section 10-2 and section 10-3. Generally, the fewer the number of glue sections, the lower the cost. The performance layer 10 and cover 3 permit the dissipation of moisture and heat. The horizontal glue seem between the performance layer 10 and the core layer 11 is a sufficient distance from the mattress top, for
15 example 3", so that the glue does not form a significant barrier to air circulation and heat dissipation.

The simple and efficient structure of the mattress 1-1 results in a unidirectional mattress 1- 1 since the head of a recumbent body needs to be toward the head 5-1' of the mattress 1-1. The mattress is not reversible such that the head of the mattress 1-1 can be
20 toward the foot 5-2 of the bed 1 (see FIG. 1) while the head of the recumbent body is toward the foot 5-2' of the mattress 1-1.

The simple and efficient structure of the mattress 1-1 renders the mattress easily compressed, folded and roll-packed for easy shipping and delivery in compact form. In the folding, the vertical seems of glue between section 10-1 and section 10-2 and between
25 section 10-2 and section 10-3 are folded so as to be toward the outside. The mattresses of FIG. 1 and FIG. 2, for any of the sizes of TABLE 1, in such compact form are easily packaged in a 19" by 19" by 44" box or smaller. The mattress is initially placed in a plastic bag. The mattress in the plastic bag is compressed from approximately 10" or more in the Z-axis direction to approximately 4" and then the plastic bag is sealed airtight to maintain the
30 mattress in the compressed state. Thereafter, the compressed mattress is folded in the middle along the longitudinal direction. The folded mattress is then rolled with a diameter that is less than approximately 19".

The foam mattress 1-1 has significant pressure reduction on the prominences of a body with simultaneous improvement of spinal alignment. Even though the mattress 1- 1 is
35 flat in appearance, a reclining body pleasantly feels the full-contour performance especially

at the shoulder and the hip and the causes of sleep-disturbance common to other mattresses are dramatically reduced.

The present invention is well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are
5 illustrative only, as the present invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular illustrative embodiments disclosed above may be altered or modified and all such
10 variations are considered within the scope and spirit of the present invention. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee.

WHAT IS CLAIMED IS:

1. A mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low-pressure support to a recumbent body, comprising:

5 a performance layer comprising along the longitudinal direction thereof:

a first shoulder section with first shoulder displacement parameters disposed on an end thereof configured to support a shoulder region of the recumbent body;

10 a first thoracic section with first thoracic displacement parameters disposed next to a distal end of said first shoulder section configured to support a thoracic region of the recumbent body; and

a hip section with hip displacement parameters disposed next to a distal end of said first thoracic section configured to support a hip region of the recumbent body; and

15 a core layer disposed below said performance layer for supporting said performance layer.

2. The mattress of claim 1, further comprising a cover having a top, sides and a bottom disposed in a covering relationship to said performance layer and said core layer.

3. The mattress of claim 2, wherein the top and the sides of said cover comprise
20 a highly stretchable material such that said cover has substantially no effect on the displacement parameters and vertical compression thereof when supporting said recumbent body.

4. The mattress of claim 3, wherein said cover comprises a fire retarding
25 material.

5. The mattress of claim 3, wherein said cover further comprises a zipper disposed in a zippering relationship between the top and sides and the bottom of said cover

30 6. The mattress of claim 3, wherein said cover further comprises an indicator stripe disposed on the top of the cover at a position corresponding to a position of the first thoracic section of the performance layer.

35 7. The mattress of claim 3, wherein said highly stretchable material has a tensile strength that increases stretching of the cover about 12% or more in the longitudinal

direction and about 16% or more in the lateral direction when a recumbent body is on the mattress.

8. The mattress of claim 1, wherein said performance layer further comprises a second shoulder section with second shoulder displacement parameters disposed at an opposite end of the performance layer to said first shoulder section in the longitudinal direction.

9. The mattress of claim 8, wherein said performance layer further comprises a second thoracic section with second thoracic displacement parameters disposed next to an proximal end of the second shoulder section.

10. The mattress of claim 9, further comprising a cover in a covering relationship to the performance layer and the core layer of the mattress comprising a top, sides and a bottom, and two indicator stripes disposed on the top of the cover at positions corresponding to the first thoracic section and the second thoracic section respectively.

11. The mattress of claim 9, wherein the second thoracic section is thinner than the hip section with a layer of said hip section disposed therebelow to compensate for a thickness thereof such that the performance layer has a uniform thickness.

12. The mattress of claim 9, wherein the second thoracic section is thinner than the hip section with a layer of said hip section disposed thereabove to compensate for a thickness thereof such that the performance layer has uniform a thickness.

13. The mattress of claim 9, wherein the second thoracic section is thinner than the second shoulder section with a layer of said second shoulder section disposed thereabove to compensate for a thickness thereof such that the performance layer has a uniform thickness.

14. The mattress of claim 1, wherein said displacement parameters comprise an indentation load deflection (ILD) and a density.

15. The mattress of claim 14, wherein the indentation load deflections of the first thoracic section and the second thoracic section are greater than the indentation load

deflection of the hip section, which is greater than the indentation load deflections of the first shoulder section and the second shoulder section.

16. The mattress of claim 15, wherein the indentation load deflection of the first shoulder section and the second shoulder section is about 18 to about 19 no, the indentation load deflection of the first thoracic section and second thoracic section is about 27 to about 28 and the indentation load deflection of the hip section is about 23 to about 24.

17. The mattress of claim 14, wherein the density of the first shoulder section and the second shoulder section is about 2 lb/cf to about 3.5 lb/cf, the density of the first thoracic section and the second thoracic section is about 2 lb/cf to about 3.5 lb/cf, and the density of the hip second is about 2 lb/cf to about 3.5 lb/cf.

18. The mattress of claim 1, wherein the core layer has an indentation load deflection of about 36 and a density of about 1.8 lb/cf.

19. The mattress of claim 1, wherein the performance layer and the core layer comprise polyurethane, latex or a combination thereof.

20. The mattress of claim 19, further comprising a fire retarding material disposed on the sides of the performance layer and the core layer.

21. The mattress of claim 1, wherein the performance layer comprises latex and the core layer comprises polyurethane.

22. A mattress extendable in a longitudinal direction and a lateral direction for improved sleep quality and low-pressure support to a recumbent body, said recumbent body having a displacement profile on the mattress where displacements of a shoulder region, a thoracic region and a hip region of the recumbent body on the mattress are different, the mattress comprising:

a performance layer comprising along the longitudinal direction thereof:

a first shoulder section with first shoulder displacement parameters disposed on an end of thereof configured to support a shoulder region of the recumbent body;

a first thoracic section with first thoracic displacement parameters disposed next to a distal end of said first shoulder section configured to support a thoracic region of the recumbent body; and

a hip section with hip displacement parameters disposed next to a distal end of said first thoracic section configured to support a hip region of the recumbent body;

a second thoracic section with second thoracic displacement parameters disposed next to a distal end of the hip section configured to support a thoracic region of the
5 recumbent body;

a second shoulder section with second shoulder displacement parameters disposed at an end of the performance layer opposite to the end of said first shoulder section in the longitudinal direction; and

a core layer disposed below said performance layer configured to support said
10 performance layer.

23. The mattress of claim 22, further comprising a cover in a covering relationship to the performance layer and the core layer and having a top, sides, and a bottom, and a first indicator stripe and a second indicator stripe disposed on the top of the cover at
15 positions corresponding to positions of the first thoracic section and the second thoracic section respectively.

24. The mattress of claim 23, wherein the cover comprises a fire retarding material.
20

25. The mattress of claim 22, wherein the second thoracic section is thinner than the hip section with a layer of said hip section disposed therebelow to compensate for a thickness thereof such that the performance layer has a uniform thickness.

26. The mattress of claim 22, wherein the second thoracic section is thinner than the hip section with a layer of said hip section disposed thereabove to compensate for a thickness thereof such that the performance layer has uniform a uniform thickness.
25

27. The mattress of claim 22, wherein the second thoracic section is thinner than
30 the second shoulder section with a layer of said second shoulder section disposed thereabove to compensate for a thickness thereof such that the performance layer has uniform a uniform thickness.

28. The mattress of claim 22, wherein the displacement parameters comprise an
35 indentation load deflection, and a density.

29. The mattress of claim 28, wherein the indentation load deflections of the first thoracic section and the second thoracic section are greater than the indentation load deflection of the hip section, which is greater than the indentation load deflections of the first shoulder section and the second shoulder section.

5

30. The mattress of claim 29, wherein the indentation load deflection of the first shoulder section and the second shoulder section is about 18 to about 19, the indentation load deflection of the first thoracic section and second thoracic section is about 27 to about 28 and the indentation load deflection of the hip section is about 23 to about 24.

10

31. The mattress of claim 28, wherein the density of the first shoulder section and the second shoulder section is about 2 lb/cf to about 3.5 lb/cf, the density of the first thoracic section and the second thoracic section is about 2 lb/cf to about 3.5 lb/cf, and the density of the hip second is about 2 lb/cf to about 3.5 lb/cf.

15

32. The mattress of claim 22, wherein the core layer has an indentation load deflection of about 36 and a density of about 1.8 lb/cf.

33. The mattress of claim 22, wherein the performance layer and the core layer comprises polyurethane, latex or a combination thereof.

20

34. The mattress of claim 33, wherein the performance layer comprises latex and the core layer comprises polyurethane.

35. The mattress of claim 33, further comprising a fire retarding material disposed on the sides of the performance layer and the core layer thereof.

25




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7







FIG. 8






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27






FIG. 28






FIG. 29C




FIG. 29D

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 2016/066166

A. CLASSIFICATION OF SUBJECT MATTER <i>A47C 27/00 (2006.01)</i> <i>A47C 27/15 (2006.01)</i> According to International Patent Classification (IPC) or to both national classification and IPC				
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) A47C 27/00-27/15, 21/04, A61F 13/15 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)				
C. DOCUMENTS CONSIDERED TO BE RELEVANT				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.		
X	WO 2014/121665 A1 (SLEEPCARE LIMITED) 14.08.2014, p. 7-20, abstract, fig. 1-24	1-3, 5-9, 11-19, 21, 22, 25-34		
Y		4, 6, 10, 20, 23, 24, 35		
Y	CN 201200173 Y (SHAO Y) 04.03.2009, abstract	4, 20, 24, 35		
Y	US 4372309 A1 (FOWLER GEORGE B.) 08.02.1983, abstract	6, 10, 23		
☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.				
* Special categories of cited documents: <table border="0"> <tr> <td style="vertical-align: top;"> “A” document defining the general state of the art which is not considered to be of particular relevance “E” earlier document but published on or after the international filing date “L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) “O” document referring to an oral disclosure, use, exhibition or other means “P” document published prior to the international filing date but later than the priority date claimed </td> <td style="vertical-align: top;"> “T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention “X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone “Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art “&” document member of the same patent family </td> </tr> </table>			“A” document defining the general state of the art which is not considered to be of particular relevance “E” earlier document but published on or after the international filing date “L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) “O” document referring to an oral disclosure, use, exhibition or other means “P” document published prior to the international filing date but later than the priority date claimed	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention “X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone “Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art “&” document member of the same patent family
“A” document defining the general state of the art which is not considered to be of particular relevance “E” earlier document but published on or after the international filing date “L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) “O” document referring to an oral disclosure, use, exhibition or other means “P” document published prior to the international filing date but later than the priority date claimed	“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention “X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone “Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art “&” document member of the same patent family			
Date of the actual completion of the international search 18 April 2017 (18.04.2017)		Date of mailing of the international search report 04 May 2017 (04.05.2017)		
Name and mailing address of the ISA/RU: Federal Institute of Industrial Property, Berezhkovskaya nab., 30-1, Moscow, G-59, GSP-3, Russia, 125993 Facsimile No: (8-495) 531-63-18, (8-499) 243-33-37		Authorized officer A. Artemiev Telephone No. (495)531-64-81		