



- (51) **International Patent Classification:**
G10L 19/008 (2013.01) *H04S 3/00* (2006.01)
- (21) **International Application Number:**
PCT/EP2014/065427
- (22) **International Filing Date:**
17 July 2014 (17.07.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
- | | | |
|------------|------------------------------|----|
| EP13177357 | 22 July 2013 (22.07.2013) | EP |
| EP13177371 | 22 July 2013 (22.07.2013) | EP |
| EP13177378 | 22 July 2013 (22.07.2013) | EP |
| EP13189290 | 18 October 2013 (18.10.2013) | EP |
- (71) **Applicants:** **FRAUNHOFER-GESELLSCHAFT ZUR FÖRDERUNG DER ANGEWANDTEN FORSCHUNG E.V.** [DE/DE]; Hansastraße 27c, 80686 München (DE). **FRIEDRICH-ALEXANDER-UNIVERSITÄT ERLANGEN-NÜRNBERG** [DE/DE]; Schlossplatz 4, 91054 Erlangen (DE).
- (72) **Inventors:** **HERRE, Jürgen**; Rathsherger Str. 10a, 91054 Erlangen (DE). **MURTAZA, Adrian**; Str. Constantin Argetoianu nr. 8, bl.6, sc.1, ap.2, R-200082 Craiova (RO). **PAULUS, Jouni**; Am Erlanger Weg 46, 91052 Erlangen (DE). **DISCH, Sascha**; Wilhelmstrasse 70, 90766 Fürth (DE). **FUCHS, Harald**; Amselstr. 5, 91341 Röttenbach

(DE). **HELLMUTH, Oliver**; Geschwister-Voemel-Weg 60, 91052 Erlangen (DE). **RIDDERBUSCH, Falko**; Büchenbacher Anlage 13a, 91056 Erlangen (DE). **TER-ENTIV, Leon**; Am Europakanal 36, App. 11, 91056 Erlangen (DE).

(74) **Agents:** **ZINKLER, Franz** et al.; Postfach 246, 82043 Pullach (DE).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) **Title:** APPARATUS AND METHOD FOR ENHANCED SPATIAL AUDIO OBJECT CODING




FIGURE 1

(57) **Abstract:** An apparatus for generating one or more audio output channels is provided. The apparatus comprises a parameter processor (110) for calculating mixing information and a downmix processor (120) for generating the one or more audio output channels. The downmix processor (120) is configured to receive an audio transport signal comprising one or more audio transport channels. One or more audio channel signals are mixed within the audio transport signal, and one or more audio object signals are mixed within the audio transport signal, and wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals. The parameter processor (110) is configured to receive downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio transport channels, and wherein the parameter processor (110) is configured to receive covariance information. Moreover, the parameter processor (110) is configured to calculate the mixing information depending on the downmix information and depending on the covariance information. The downmix processor (120) is configured to generate the one or more audio output channels from the audio transport signal depending on the mixing information. The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

WO 2015/011024 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, **Published:**
KM, ML, MR, NE, SN, TD, TG).

— *with international search report (Art. 21(3))*

Apparatus and Method for Enhanced Spatial Audio Object Coding

Description

5

The present invention is related to audio encoding/decoding, in particular, to spatial audio coding and spatial audio object coding, and, more particularly, to an apparatus and method for enhanced Spatial Audio Object Coding.

10

Spatial audio coding tools are well-known in the art and are, for example, standardized in the MPEG-surround standard. Spatial audio coding starts from original input channels such as five or seven channels which are identified by their placement in a reproduction setup, i.e., a left channel, a center channel, a right channel, a left surround channel, a right surround channel and a low frequency enhancement channel. A spatial audio

15

encoder typically derives one or more downmix channels from the original channels and, additionally, derives parametric data relating to spatial cues such as inter-channel level differences in the channel coherence values, inter-channel phase differences, inter-channel time differences, etc. The one or more downmix channels are transmitted together with the parametric side information indicating the spatial cues to a spatial audio

20

decoder which decodes the downmix channel and the associated parametric data in order to finally obtain output channels which are an approximated version of the original input channels. The placement of the channels in the output setup is typically fixed and is, for example, a 5.1 format, a 7.1 format, etc.

25

Such channel-based audio formats are widely used for storing or transmitting multi-channel audio content where each channel relates to a specific loudspeaker at a given position. A faithful reproduction of these kind of formats requires a loudspeaker setup where the speakers are placed at the same positions as the speakers that were used during the production of the audio signals. While increasing the number of loudspeakers

30

improves the reproduction of truly immersive 3D audio scenes, it becomes more and more difficult to fulfill this requirement – especially in a domestic environment like a living room.

35

The necessity of having a specific loudspeaker setup can be overcome by an object-based approach where the loudspeaker signals are rendered specifically for the playback setup.

For example, spatial audio object coding tools are well-known in the art and are standardized in the MPEG SAOC standard (SAOC = spatial audio object coding). In contrast to spatial audio coding starting from original channels, spatial audio object coding starts from audio objects which are not automatically dedicated for a certain rendering reproduction setup. Instead, the placement of the audio objects in the reproduction scene is flexible and can be determined by the user by inputting certain rendering information into a spatial audio object coding decoder. Alternatively or additionally, rendering information, i.e., information at which position in the reproduction setup a certain audio object is to be placed typically over time can be transmitted as additional side information or metadata. In order to obtain a certain data compression, a number of audio objects are encoded by an SAOC encoder which calculates, from the input objects, one or more transport channels by downmixing the objects in accordance with certain downmixing information. Furthermore, the SAOC encoder calculates parametric side information representing inter-object cues such as object level differences (OLD), object coherence values, etc. As in SAC (SAC = Spatial Audio Coding), the inter object parametric data is calculated for parameter time/frequency tiles, i.e., for a certain frame of the audio signal comprising, for example, 1024 or 2048 samples, 28, 20, 14 or 10, etc., processing bands are considered so that, in the end, parametric data exists for each frame and each processing band. As an example, when an audio piece has 20 frames and when each frame is subdivided into 28 processing bands, then the number of parameter time/frequency tiles is 560.

In an object-based approach, the sound field is described by discrete audio objects. This requires object metadata that describes among others the time-variant position of each sound source in 3D space.

A first metadata coding concept in the prior art is the spatial sound description interchange format (SpatDIF), an audio scene description format which is still under development [M1]. It is designed as an interchange format for object-based sound scenes and does not provide any compression method for object trajectories. SpatDIF uses the text-based Open Sound Control (OSC) format to structure the object metadata [M2]. A simple text-based representation, however, is not an option for the compressed transmission of object trajectories.

Another metadata concept in the prior art is the Audio Scene Description Format (ASDF) [M3], a text-based solution that has the same disadvantage. The data is structured by an

extension of the Synchronized Multimedia Integration Language (SMIL) which is a sub set of the Extensible Markup Language (XML) [M4], [M5].

5 A further metadata concept in the prior art is the audio binary format for scenes (AudioBIFS), a binary format that is part of the MPEG-4 specification [M6], [M7]. It is closely related to the XML-based Virtual Reality Modeling Language (VRML) which was developed for the description of audio-visual 3D scenes and interactive virtual reality applications [M8]. The complex AudioBIFS specification uses scene graphs to specify routes of object movements. A major disadvantage of AudioBIFS is that is not designed
10 for real-time operation where a limited system delay and random access to the data stream are a requirement. Furthermore, the encoding of the object positions does not exploit the limited localization performance of human listeners. For a fixed listener position within the audio-visual scene, the object data can be quantized with a much lower number of bits [M9]. Hence, the encoding of the object metadata that is applied in AudioBIFS is
15 not efficient with regard to data compression.

The object of the present invention is to provide improved concepts for Spatial Audio Object Coding. The object of the present invention is solved by an apparatus according to claim 1, by an apparatus according to claim 14, by a system according to claim 16, by a
20 method according to claim 17, by a method according to claim 18 and by a computer program according to claim 19.

An apparatus for generating one or more audio output channels is provided. The apparatus comprises a parameter processor for calculating mixing information and a
25 downmix processor for generating the one or more audio output channels. The downmix processor is configured to receive an audio transport signal comprising one or more audio transport channels. One or more audio channel signals are mixed within the audio transport signal, and one or more audio object signals are mixed within the audio transport signal, and wherein the number of the one or more audio transport channels is smaller
30 than the number of the one or more audio channel signals plus the number of the one or more audio object signals. The parameter processor is configured to receive downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio transport channels, and wherein the parameter processor is configured to receive covariance
35 information. Moreover, the parameter processor is configured to calculate the mixing information depending on the downmix information and depending on the covariance information. The downmix processor is configured to generate the one or more audio output channels from the audio transport signal depending on the mixing information. The

covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

Moreover, an apparatus for generating an audio transport signal comprising one or more audio transport channels is provided. The apparatus comprises a channel/object mixer for generating the one or more audio transport channels of the audio transport signal, and an output interface. The channel/object mixer is configured to generate the audio transport signal comprising the one or more audio transport channels by mixing one or more audio channel signals and one or more audio object signals within the audio transport signal depending on downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals have to be mixed within the one or more audio transport channels, wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals. The output interface is configured to output the audio transport signal, the downmix information and covariance information. The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

Furthermore, a system is provided. The system comprises an apparatus for generating an audio transport signal as described above and an apparatus for generating one or more audio output channels as described above. The apparatus for generating the one or more audio output channels is configured to receive the audio transport signal, downmix information and covariance information from the apparatus for generating the audio transport signal. Moreover, the apparatus for generating the audio output channels is configured to generate the one or more audio output channels depending from the audio transport signal depending on the downmix information and depending on the covariance information.

Moreover, a method for generating one or more audio output channels is provided. The method comprises:

- Receiving an audio transport signal comprising one or more audio transport channels, wherein one or more audio channel signals are mixed within the audio transport signal, wherein one or more audio object signals are mixed within the audio transport signal, and wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals.
- Receiving downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio transport channels.
- Receiving covariance information.
- Calculating mixing information depending on the downmix information and depending on the covariance information. And:
- Generating the one or more audio output channels.

Generating the one or more audio output channels from the audio transport signal depending on the mixing information. The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

Furthermore, a method for generating an audio transport signal comprising one or more audio transport channels. The method comprises:

- Generating the audio transport signal comprising the one or more audio transport channels by mixing one or more audio channel signals and one or more audio object signals within the audio transport signal depending on downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals have to be mixed within the one or more audio transport channels, wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals. And:

- Outputting the audio transport signal, the downmix information and covariance information.

The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

- Moreover, a computer program for implementing the above-described method when being executed on a computer or signal processor is provided.

In the following, embodiments of the present invention are described in more detail with reference to the figures, in which:

15

Fig. 1 illustrates an apparatus for generating one or more audio output channels according to an embodiment,

20

Fig. 2 illustrates an apparatus for generating an audio transport signal comprising one or more audio transport channels according to an embodiment,

Fig. 3 illustrates a system according to an embodiment,

25

Fig. 4 illustrates a first embodiment of a 3D audio encoder,

Fig. 5 illustrates a first embodiment of a 3D audio decoder,

Fig. 6 illustrates a second embodiment of a 3D audio encoder,

30

Fig. 7 illustrates a second embodiment of a 3D audio decoder,

Fig. 8 illustrates a third embodiment of a 3D audio encoder,

Fig. 9 illustrates a third embodiment of a 3D audio decoder, and

35

Fig. 10 illustrates a joint processing unit according to an embodiment.

Before describing preferred embodiments of the present invention in detail, the new 3D Audio Codec System is described.

- 5 In the prior art, no flexible technology exists combining channel coding on the one hand and object coding on the other hand so that acceptable audio qualities at low bit rates are obtained.

This limitation is overcome by the new 3D Audio Codec System.

10

Before describing preferred embodiments in detail, the new 3D Audio Codec System is described.

- Fig. 4 illustrates a 3D audio encoder in accordance with an embodiment of the present invention. The 3D audio encoder is configured for encoding audio input data 101 to obtain audio output data 501. The 3D audio encoder comprises an input interface for receiving a plurality of audio channels indicated by CH and a plurality of audio objects indicated by OBJ. Furthermore, as illustrated in Fig. 4, the input interface 1100 additionally receives metadata related to one or more of the plurality of audio objects OBJ. Furthermore, the 3D audio encoder comprises a mixer 200 for mixing the plurality of objects and the plurality of channels to obtain a plurality of pre-mixed channels, wherein each pre-mixed channel comprises audio data of a channel and audio data of at least one object.
- 15
- 20

- Furthermore, the 3D audio encoder comprises a core encoder 300 for core encoding core encoder input data, a metadata compressor 400 for compressing the metadata related to the one or more of the plurality of audio objects.
- 25

- Furthermore, the 3D audio encoder can comprise a mode controller 600 for controlling the mixer, the core encoder and/or an output interface 500 in one of several operation modes, wherein in the first mode, the core encoder is configured to encode the plurality of audio channels and the plurality of audio objects received by the input interface 1100 without any interaction by the mixer, i.e., without any mixing by the mixer 200. In a second mode, however, in which the mixer 200 was active, the core encoder encodes the plurality of mixed channels, i.e., the output generated by block 200. In this latter case, it is preferred to not encode any object data anymore. Instead, the metadata indicating positions of the audio objects are already used by the mixer 200 to render the objects onto the channels
- 30
- 35

as indicated by the metadata. In other words, the mixer 200 uses the metadata related to the plurality of audio objects to pre-render the audio objects and then the pre-rendered audio objects are mixed with the channels to obtain mixed channels at the output of the mixer. In this embodiment, any objects may not necessarily be transmitted and this also
5 applies for compressed metadata as output by block 400. However, if not all objects input into the interface 1100 are mixed but only a certain amount of objects is mixed, then only the remaining non-mixed objects and the associated metadata nevertheless are transmitted to the core encoder 300 or the metadata compressor 400, respectively.

10 Fig. 6 illustrates a further embodiment of an 3D audio encoder which, additionally, comprises an SAOC encoder 800. The SAOC encoder 800 is configured for generating one or more transport channels and parametric data from spatial audio object encoder input data. As illustrated in Fig. 6, the spatial audio object encoder input data are objects which have not been processed by the pre-renderer/mixer. Alternatively, provided that the
15 pre-renderer/mixer has been bypassed as in the mode one where an individual channel/object coding is active, all objects input into the input interface 1100 are encoded by the SAOC encoder 800.

Furthermore, as illustrated in Fig. 6, the core encoder 300 is preferably implemented as a
20 USAC encoder, i.e., as an encoder as defined and standardized in the MPEG-USAC standard (USAC = Unified Speech and Audio Coding). The output of the whole 3D audio encoder illustrated in Fig. 6 is an MPEG 4 data stream, MPEG H data stream or 3D audio data stream having the container-like structures for individual data types. Furthermore, the metadata is indicated as "OAM" data and the metadata compressor 400 in Fig. 4
25 corresponds to the OAM encoder 400 to obtain compressed OAM data which are input into the USAC encoder 300 which, as can be seen in Fig. 6, additionally comprises the output interface to obtain the MP4 output data stream not only having the encoded channel/object data but also having the compressed OAM data.

30 Fig. 8 illustrates a further embodiment of the 3D audio encoder, where in contrast to Fig. 6, the SAOC encoder can be configured to either encode, with the SAOC encoding algorithm, the channels provided at the pre-renderer/mixer 200 not being active in this mode or, alternatively, to SAOC encode the pre-rendered channels plus objects. Thus, in Fig. 8, the SAOC encoder 800 can operate on three different kinds of input data, i.e.,
35 channels without any pre-rendered objects, channels and pre-rendered objects or objects alone. Furthermore, it is preferred to provide an additional OAM decoder 420 in Fig. 8 so

that the SAOC encoder 800 uses, for its processing, the same data as on the decoder side, i.e., data obtained by a lossy compression rather than the original OAM data.

The Fig. 8 3D audio encoder can operate in several individual modes.

5

In addition to the first and the second modes as discussed in the context of Fig. 4, the Fig. 8 3D audio encoder can additionally operate in a third mode in which the core encoder generates the one or more transport channels from the individual objects when the pre-renderer/mixer 200 was not active. Alternatively or additionally, in this third mode the SAOC encoder 800 can generate one or more alternative or additional transport channels from the original channels, i.e., again when the pre-renderer/mixer 200 corresponding to the mixer 200 of Fig. 4 was not active.

10

Finally, the SAOC encoder 800 can encode, when the 3D audio encoder is configured in the fourth mode, the channels plus pre-rendered objects as generated by the pre-renderer/mixer. Thus, in the fourth mode the lowest bit rate applications will provide good quality due to the fact that the channels and objects have completely been transformed into individual SAOC transport channels and associated side information as indicated in Figs. 3 and 5 as "SAOC-SI" and, additionally, any compressed metadata do not have to be transmitted in this fourth mode.

15

20

Fig. 5 illustrates a 3D audio decoder in accordance with an embodiment of the present invention. The 3D audio decoder receives, as an input, the encoded audio data, i.e., the data 501 of Fig. 4.

25

The 3D audio decoder comprises a metadata decompressor 1400, a core decoder 1300, an object processor 1200, a mode controller 1600 and a postprocessor 1700.

Specifically, the 3D audio decoder is configured for decoding encoded audio data and the input interface is configured for receiving the encoded audio data, the encoded audio data comprising a plurality of encoded channels and the plurality of encoded objects and compressed metadata related to the plurality of objects in a certain mode.

30

Furthermore, the core decoder 1300 is configured for decoding the plurality of encoded channels and the plurality of encoded objects and, additionally, the metadata decompressor is configured for decompressing the compressed metadata.

35

- Furthermore, the object processor 1200 is configured for processing the plurality of decoded objects as generated by the core decoder 1300 using the decompressed metadata to obtain a predetermined number of output channels comprising object data and the decoded channels. These output channels as indicated at 1205 are then input into a postprocessor 1700. The postprocessor 1700 is configured for converting the number of output channels 1205 into a certain output format which can be a binaural output format or a loudspeaker output format such as a 5.1, 7.1, etc., output format.
- Preferably, the 3D audio decoder comprises a mode controller 1600 which is configured for analyzing the encoded data to detect a mode indication. Therefore, the mode controller 1600 is connected to the input interface 1100 in Fig. 5. However, alternatively, the mode controller does not necessarily have to be there. Instead, the flexible audio decoder can be pre-set by any other kind of control data such as a user input or any other control. The 3D audio decoder in Fig. 5 and, preferably controlled by the mode controller 1600, is configured to either bypass the object processor and to feed the plurality of decoded channels into the postprocessor 1700. This is the operation in mode 2, i.e., in which only pre-rendered channels are received, i.e., when mode 2 has been applied in the 3D audio encoder of Fig. 4. Alternatively, when mode 1 has been applied in the 3D audio encoder, i.e., when the 3D audio encoder has performed individual channel/object coding, then the object processor 1200 is not bypassed, but the plurality of decoded channels and the plurality of decoded objects are fed into the object processor 1200 together with decompressed metadata generated by the metadata decompressor 1400.
- Preferably, the indication whether mode 1 or mode 2 is to be applied is included in the encoded audio data and then the mode controller 1600 analyses the encoded data to detect a mode indication. Mode 1 is used when the mode indication indicates that the encoded audio data comprises encoded channels and encoded objects and mode 2 is applied when the mode indication indicates that the encoded audio data does not contain any audio objects, i.e., only contain pre-rendered channels obtained by mode 2 of the Fig. 4 3D audio encoder.

Fig. 7 illustrates a preferred embodiment compared to the Fig. 5 3D audio decoder and the embodiment of Fig. 7 corresponds to the 3D audio encoder of Fig. 6. In addition to the 3D audio decoder implementation of Fig. 5, the 3D audio decoder in Fig. 7 comprises an SAOC decoder 1800. Furthermore, the object processor 1200 of Fig. 5 is implemented as

a separate object renderer 1210 and the mixer 1220 while, depending on the mode, the functionality of the object renderer 1210 can also be implemented by the SAOC decoder 1800.

5 Furthermore, the postprocessor 1700 can be implemented as a binaural renderer 1710 or a format converter 1720. Alternatively, a direct output of data 1205 of Fig. 5 can also be implemented as illustrated by 1730. Therefore, it is preferred to perform the processing in the decoder on the highest number of channels such as 22.2 or 32 in order to have flexibility and to then post-process if a smaller format is required. However, when it becomes clear from the very beginning that only small format such as a 5.1 format is
10 required, then it is preferred, as indicated by Fig. 5 or 6 by the shortcut 1727, that a certain control over the SAOC decoder and/or the USAC decoder can be applied in order to avoid unnecessary upmixing operations and subsequent downmixing operations.

15 In a preferred embodiment of the present invention, the object processor 1200 comprises the SAOC decoder 1800 and the SAOC decoder is configured for decoding one or more transport channels output by the core decoder and associated parametric data and using decompressed metadata to obtain the plurality of rendered audio objects. To this end, the OAM output is connected to box 1800.

20

Furthermore, the object processor 1200 is configured to render decoded objects output by the core decoder which are not encoded in SAOC transport channels but which are individually encoded in typically single channeled elements as indicated by the object
renderer 1210. Furthermore, the decoder comprises an output interface corresponding to
25 the output 1730 for outputting an output of the mixer to the loudspeakers.

In a further embodiment, the object processor 1200 comprises a spatial audio object coding decoder 1800 for decoding one or more transport channels and associated parametric side information representing encoded audio signals or encoded audio
30 channels, wherein the spatial audio object coding decoder is configured to transcode the associated parametric information and the decompressed metadata into transcoded parametric side information usable for directly rendering the output format, as for example defined in an earlier version of SAOC. The postprocessor 1700 is configured for calculating audio channels of the output format using the decoded transport channels and
35 the transcoded parametric side information. The processing performed by the post

processor can be similar to the MPEG Surround processing or can be any other processing such as BCC processing or so.

5 In a further embodiment, the object processor 1200 comprises a spatial audio object coding decoder 1800 configured to directly upmix and render channel signals for the output format using the decoded (by the core decoder) transport channels and the parametric side information

10 Furthermore, and importantly, the object processor 1200 of Fig. 5 additionally comprises the mixer 1220 which receives, as an input, data output by the USAC decoder 1300 directly when pre-rendered objects mixed with channels exist, i.e., when the mixer 200 of Fig. 4 was active. Additionally, the mixer 1220 receives data from the object renderer performing object rendering without SAOC decoding. Furthermore, the mixer receives SAOC decoder output data, i.e., SAOC rendered objects.

15

The mixer 1220 is connected to the output interface 1730, the binaural renderer 1710 and the format converter 1720. The binaural renderer 1710 is configured for rendering the output channels into two binaural channels using head related transfer functions or binaural room impulse responses (BRIR). The format converter 1720 is configured for
20 converting the output channels into an output format having a lower number of channels than the output channels 1205 of the mixer and the format converter 1720 requires information on the reproduction layout such as 5.1 speakers or so.

25 The Fig. 9 3D audio decoder is different from the Fig. 7 3D audio decoder in that the SAOC decoder cannot only generate rendered objects but also rendered channels and this is the case when the Fig. 8 3D audio encoder has been used and the connection 900 between the channels/pre-rendered objects and the SAOC encoder 800 input interface is active.

30 Furthermore, a vector base amplitude panning (VBAP) stage 1810 is configured which receives, from the SAOC decoder, information on the reproduction layout and which outputs a rendering matrix to the SAOC decoder so that the SAOC decoder can, in the end, provide rendered channels without any further operation of the mixer in the high channel format of 1205, i.e., 32 loudspeakers.

35

the VBAP block preferably receives the decoded OAM data to derive the rendering matrices. More general, it preferably requires geometric information not only of the reproduction layout but also of the positions where the input signals should be rendered to on the reproduction layout. This geometric input data can be OAM data for objects or
 5 channel position information for channels that have been transmitted using SAOC.

However, if only a specific output interface is required then the VBAP state 1810 can already provide the required rendering matrix for the e.g., 5.1 output. The SAOC decoder 1800 then performs a direct rendering from the SAOC transport channels, the associated
 10 parametric data and decompressed metadata, a direct rendering into the required output format without any interaction of the mixer 1220. However, when a certain mix between modes is applied, i.e., where several channels are SAOC encoded but not all channels are SAOC encoded or where several objects are SAOC encoded but not all objects are SAOC encoded or when only a certain amount of pre-rendered objects with channels are
 15 SAOC decoded and remaining channels are not SAOC processed then the mixer will put together the data from the individual input portions, i.e., directly from the core decoder 1300, from the object renderer 1210 and from the SAOC decoder 1800.

The following mathematical notation is employed:

20

$N_{Objects}$ number of input audio object signals

$N_{Channels}$ number of input channels

25

N number of input signals;
 N can be equal with $N_{Objects}$, $N_{Channels}$ or $N_{Objects} + N_{Channels}$

N_{DmxCh} number of downmix (processed) channels

30

$N_{Samples}$ number of processed data samples

$N_{OutputChannels}$ number of output channels at the decoder side

35

D downmix matrix, size $N_{DmxCh} \times N$

X input audio signal, size $N \times N_{Samples}$

	$\mathbf{E}_X$	input signal covariance matrix, size $N \times N$ defined as $\mathbf{E}_X = \mathbf{X} \mathbf{X}^H$
	$\mathbf{Y}$	downmix audio signal, size $N_{DmxCh} \times N_{Samples}$ defined as $\mathbf{Y} = \mathbf{D} \mathbf{X}$
5	$\mathbf{E}_Y$	covariance matrix of the downmix signals, size $N_{DmxCh} \times N_{DmxCh}$ defined as $\mathbf{E}_Y = \mathbf{Y} \mathbf{Y}^H$
	$\mathbf{G}$	parametric source estimation matrix, size $N \times N_{DmxCh}$ which approximates $\mathbf{E}_X \mathbf{D}^H (\mathbf{D} \mathbf{E}_X \mathbf{D}^H)^{-1}$
10	$\hat{\mathbf{X}}$	parametrically reconstructed input signals, size $N_{Objects} \times N_{Samples}$ which approximates $\mathbf{X}$ and defined as $\hat{\mathbf{X}} = \mathbf{G} \mathbf{Y}$
15	$(\cdot)^H$	self-adjoint (Hermitian) operator which represents the conjugate transpose of $(\cdot)$
	$\mathbf{R}$	rendering matrix of size $N_{OutputChannels} \times N$
20	$\mathbf{S}$	output channel generation matrix of size $N_{OutputChannels} \times N_{DmxCh}$ defined as $\mathbf{S} = \mathbf{R} \mathbf{G}$
	$\mathbf{Z}$	output channels, size $N_{OutputChannels} \times N_{Samples}$, generated on the decoder side from the downmix signals, $\mathbf{Z} = \mathbf{S} \mathbf{Y}$
25	$\hat{\mathbf{Z}}$	desired output channels, size $N_{OutputChannels} \times N_{Samples}$, $\hat{\mathbf{Z}} = \mathbf{R} \mathbf{X}$

Without loss of generality, in order to improve readability of equations, for all introduced variables the indices denoting time and frequency dependency are omitted in this document.

30

In the 3D Audio context, loudspeaker channels are distributed in several height layers, resulting in horizontal and vertical channel pairs. Joint coding of only two channels as defined in USAC is not sufficient to consider the spatial and perceptual relations between channels.

35

In order to consider the spatial and perceptual relations between channels, in the 3D Audio context, one could use SAOC-like parametric technique to reconstruct the input

channels (audio channel signals and audio object signals that are encoded by the SAOC encoder) to obtain reconstructed input channels $\hat{\mathbf{X}}$ at the decoder side. SAOC decoding is based on a Minimum Mean Squared Error (MMSE) Algorithm:

$$\hat{\mathbf{X}} = \mathbf{G}\mathbf{Y} \text{ with } \mathbf{G} \approx \mathbf{E}_X \mathbf{D}^H (\mathbf{D} \mathbf{E}_X \mathbf{D}^H)^{-1} .$$

Instead of reconstructing input channels to obtain reconstructed input channels $\hat{\mathbf{X}}$, the output channels $\mathbf{Z}$ can be directly generated at the decoder side by taking the rendering matrix $\mathbf{R}$ into account.

10

$$\mathbf{Z} = \mathbf{R} \hat{\mathbf{X}}$$

$$\mathbf{Z} = \mathbf{R}\mathbf{G}\mathbf{Y}$$

15

$$\mathbf{Z} = \mathbf{S}\mathbf{Y} ; \text{ with } \mathbf{S} = \mathbf{R}\mathbf{G}$$

As can be seen, instead of explicitly reconstructing the input audio objects and the input audio channels, the output channels $\mathbf{Z}$ may be directly generated by applying the output channel generation matrix $\mathbf{S}$ on the downmix audio signal $\mathbf{Y}$.

20

To obtain the output channel generation matrix $\mathbf{S}$, rendering matrix $\mathbf{R}$ may, e.g., be determined or may, e.g, be already available. Furthermore, the parametric source estimation matrix $\mathbf{G}$ may, e.g, be computed as described above. The output channel generation matrix $\mathbf{S}$ may then be obtained as the matrix product $\mathbf{S} = \mathbf{R}\mathbf{G}$ from the rendering matrix $\mathbf{R}$ and the parametric source estimation matrix $\mathbf{G}$.

25

A 3D Audio system may require a combined mode in order to encode channels and objects.

30

In general, for such a combined mode, SAOC encoding/decoding may be applied in two different ways:

35

One approach could be to employ one instance of a SAOC-like parametric system, wherein such an instance is capable to process channels and objects. This solution has the drawback that it is computational complex, because of the high number of input signals the number of transport channels will increase in order to maintain a similar reconstruction quality. As a consequence the size of the matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$ will increase and the inversion complexity will increase. Moreover, such a solution may introduce more

numerical instabilities as the size of the matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$ increases. Furthermore, as another disadvantage, the inversion of the matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$ may lead to additional cross-talk between reconstructed channels and reconstructed objects. This is caused because some coefficients in the reconstruction matrix $\mathbf{G}$ which are supposed to be equal to zero are set to non-zero values due to numerical inaccuracies.

Another approach could be to employ two instances of SAOC-like parametric systems, one instance for the channel based processing and another instance for the object based processing. Such an approach would have the drawback that the same information is transmitted twice for the initialization of the filterbanks and decoder configuration. Moreover, it is not possible to mix the channels and objects together if this is required, and consequently not possible to use correlation properties between channels and objects.

To avoid the disadvantages of the approach which employs different instances for audio objects and audio channels, embodiments employ the first approach and provide an Enhanced SAOC System capable of processing channels, objects or channels and objects using only one system instance, in an efficient way. Although audio channels and audio objects are processed by the same encoder and decoder instance, respectively, efficient concepts are provided, so that the disadvantages of the first approach can be avoided.

Fig. 2 illustrates an apparatus for generating an audio transport signal comprising one or more audio transport channels according to an embodiment.

The apparatus comprises a channel/object mixer 210 for generating the one or more audio transport channels of the audio transport signal, and an output interface 220.

The channel/object mixer 210 is configured to generate the audio transport signal comprising the one or more audio transport channels by mixing one or more audio channel signals and one or more audio object signals within the audio transport signal depending on downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals have to be mixed within the one or more audio transport channels.

The number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals. Thus, the channel/object mixer 210 is capable of downmixing the one or more

audio channel signals plus and the one or more audio object signals, as the channel/object mixer 210 is adapted to generate an audio transport signal that has fewer channels than the number of the one or more audio channel signals plus the number of the one or more audio object signals.

5

The output interface 220 is configured to output the audio transport signal, the downmix information and covariance information.

10

For example, the channel/object mixer 210 may be configured to feed the downmix information, that is used for downmixing the one or more audio channel signals and the one or more audio object signals, into the output interface 220. Moreover, for example, the output interface 220, may, for example, be configured to receive the one or more audio channel signals and the one or more audio object signals and may moreover be configured to determine the covariance information based on the one or more audio channel signals and the one or more audio object signals. Or, the output interface 220 may, for example, be configured to receive the already determined covariance information.

15

20

The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

25

Fig. 1 illustrates an apparatus for generating one or more audio output channels according to an embodiment.

30

The apparatus comprises a parameter processor 110 for calculating mixing information and a downmix processor 120 for generating the one or more audio output channels.

35

The downmix processor 120 is configured to receive an audio transport signal comprising one or more audio transport channels. One or more audio channel signals are mixed within the audio transport signal. Moreover, one or more audio object signals are mixed within the audio transport signal. The number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals.

The parameter processor 110 is configured to receive downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio transport channels. Moreover, the
5 parameter processor 110 is configured to receive covariance information. The parameter processor 110 is configured to calculate the mixing information depending on the downmix information and depending on the covariance information.

10 The downmix processor 120 is configured to generate the one or more audio output channels from the audio transport signal depending on the mixing information.

The covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals. However, the covariance information
15 does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

In an embodiment, the covariance information may, e.g., indicate a level difference information for each of the one or more audio channel signals and, may further, e.g.,
20 indicate a level difference information for each of the one or more audio object signals.

According to an embodiment, two or more audio object signals may, e.g., be mixed within the audio transport signal and two or more audio channel signals may, e.g., be mixed within the audio transport signal. The covariance information may, e.g., indicate
25 correlation information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals. Or, the covariance information may, e.g., indicate correlation information for one or more pairs of a first one of the two or more audio object signals and a second one of the two or more audio object signals. Or, the covariance information may, e.g., indicate correlation
30 information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals and indicates correlation information for one or more pairs of a first one of the two or more audio object signals and a second one of the two or more audio object signals.

35 A level difference information for an audio object signal may, for example, be an object level difference (OLD). "Level" may, e.g., relate to an energy level. "Difference" may, e.g., relate to a difference with respect to a maximum level among the audio object signals.

A correlation information for a pair of a first one of the audio object signals and a second one of the audio object signals may, for example, be an inter-object correlation (IOC).

- For example, according to an embodiment, in order to guarantee optimum performance of SAOC 3D it is recommended to use the input audio object signals with compatible power. The product of two input audio signals (normalized according the corresponding time/frequency tiles) is determined as:

$$nrg_{i,j}^{l,m} = \frac{\sum_{n \in l} \sum_{k \in m} x_i^{n,k} (x_j^{n,k})^H}{\sum_{n \in l} \sum_{k \in m} 1} + \varepsilon .$$

10

Here, i and j are indices for the audio object signals x_i and x_j , respectively, n indicates time, k indicates frequency, l indicates a set of time indices and m indicates a set of frequency indices. ε is an additive constant to avoid division by zero, e.g., $\varepsilon = 10^{-9}$.

- 15 The absolute object energy (NRG) of the object with the highest energy may, e.g., be calculated as:

$$NRG^{l,m} = \max_i (nrg_{i,i}^{l,m}) .$$

- 20 The ratio of the powers of corresponding input object signal (OLD) may, e.g., be given by

$$OLD_i^{l,m} = \frac{nrg_{i,i}^{l,m}}{NRG^{l,m}} .$$

A similarity measure of the input objects (IOC), may, e.g., be given by the cross correlation:

25

$$IOC_{i,j}^{l,m} = \text{Re} \left\{ \frac{nrg_{i,j}^{l,m}}{\sqrt{nrg_{i,i}^{l,m} nrg_{j,j}^{l,m}}} \right\} .$$

For example, in an embodiment, the IOCs may be transmitted for all pairs of audio signals i and j , for which a bitstream variable `bsRelatedTo[i][j]` is set to one.

- 30 A level difference information for an audio channel signal may, for example, be a channel level difference (CLD). "Level" may, e.g., relate to an energy level. "Difference" may, e.g., relate to a difference with respect to a maximum level among the audio channel signals.

A correlation information for a pair of a first one of the audio channel signals and a second one of the audio channel signals may, for example, be an inter-channel correlation (ICC).

5 In an embodiment, the channel level difference (CLD) may be defined in the same way as the object level difference (OLD) above, when the audio object signals in the above formulae are replaced by audio channel signals. Moreover, the inter-channel correlation (ICC) may be defined in the same way as the inter-object correlation (IOC) above, when the audio object signals in the above formulae are replaced by audio channel signals.

10

In SAOC, an SAOC encoder downmixes (according to downmix information, e.g., according to a downmix matrix **D**) a plurality of audio object signals to obtain (e.g., a fewer number of) one or more audio transport channels. On the decoder side, a SAOC decoder decodes the one or more audio transport channels using the downmix information
15 received from the encoder and using covariance information received from the encoder. The covariance information may, for example, be the coefficients of a covariance matrix **E**, which indicates the object level differences of the audio object signals and the inter object correlations between two audio object signals. In SAOC, a determined downmix matrix **D** and a determined covariance matrix **E** is used to decode a plurality of samples of
20 the one or more audio transport channels (e.g., 2048 samples of the one or more audio transport channels). By employing this concept, bitrate is saved compared to transmitting the one or more audio object signals without encoding.

Embodiments are based on the finding, that although audio object signals and audio
25 channel signals exhibit significant differences, an audio transport signal may be generated by an enhanced SAOC encoder, so that in such an audio transport signal, not only audio object signals, but also audio channel signals are mixed.

Audio object signals and audio channel signals significantly differ. For example, each of a
30 plurality of audio object signals may represent an audio source of a sound scene. Therefore, in general, two audio objects may be highly uncorrelated. In contrast, audio channel signals represent different channels of a sound scene, as if being recorded by different microphones. In general, two of such audio channel signals are highly correlated, in particular, compared to the correlation of two audio object signals, which are, in
35 general, highly uncorrelated. Thus, embodiments are based on the finding that audio channel signals particularly benefit from transmitting the correlation between a pair of two audio channel signals and by using this transmitted correlation value for decoding.

Moreover, audio object signals and audio channel signals differ in that, position information is assigned to audio object signals, for example, indicating an (assumed) position of a sound source (e.g., an audio object) from which an audio object signal originates. Such position information (e.g., comprised in metadata information) can be
5 used when generating audio output channels from the audio transport signal on the decoder side. However, in contrast, audio channel signals do not exhibit a position, and no position information is assigned to audio channel signals. However, embodiments are based on the finding that it is nevertheless efficient to SAOC encode audio channel signals together with audio object signals, e.g., as generating the audio channel signals
10 can be divided into two subproblems, namely, determining decoding information (for example, determining matrix $\mathbf{G}$ for unmixing, see below), for which no position information is needed, and determining rendering information (for example, by determining a rendering matrix $\mathbf{R}$, see below), for which position information on the audio object signals may be employed to render the audio objects in the audio output channels that are
15 generated.

Moreover, the present invention is based on the finding that no correlation (or at least no significant) exists between any pair of one of the audio object signals and one of the audio channel signals. Therefore, when the encoder does not transmit correlation information for
20 any pair of one of the one or more audio channel signals and one of the one or more audio object signals. By this, significant transmission bandwidth is saved and a significant amount of computation time is saved for both encoding and decoding. A decoder that is configured to not process such insignificant correlation information saves a significant amount of computation time when determining the mixing information (which is employed
25 for generating the audio output channels from the audio transport signal on the decoder side).

According to an embodiment, the parameter processor 110 may, e.g., be configured to receive rendering information indicating information on how the one or more audio
30 channel signals and the one or more audio object signals are mixed within the one or more audio output channels. The parameter processor 110 may, e.g., be configured to calculate the mixing information depending on the downmix information, depending on the covariance information and depending on rendering information.

35 For example, the parameter processor 110 may, for example, be configured to receive a plurality of coefficients of a rendering matrix $\mathbf{R}$ as the rendering information, and may be configured to calculate the mixing information depending on the downmix information, depending on the covariance information and depending on the rendering matrix $\mathbf{R}$. E.g.,

- the parameter processor may receive the coefficients of the rendering matrix $\mathbf{R}$ from an encoder side, or from a user. In another embodiment, the parameter processor 110 may, for example, be configured to receive metadata information, e.g., position information or gain information, and may, e.g., be configured to calculate the coefficients of the rendering matrix $\mathbf{R}$ depending on the received metadata information. In a further embodiment, the parameter processor may be configured to receive both (rendering information from encoder and from the user) and to create the rendering matrix based on both (which basically means that interactivity is realized).
- Or, the parameter processor may, e.g., receive two rendering submatrices $\mathbf{R}_{\text{ch}}$, $\mathbf{R}_{\text{obj}}$, as rendering information, wherein $\mathbf{R}=(\mathbf{R}_{\text{ch}}, \mathbf{R}_{\text{obj}})$, wherein $\mathbf{R}_{\text{ch}}$ e.g., indicates how to mix the audio channel signals to the audio output channels and wherein $\mathbf{R}_{\text{obj}}$ may be a rendering matrix obtained from the OAM information, wherein $\mathbf{R}_{\text{obj}}$ may, e.g., be provided by the VBAP block 1810 of Fig. 9.
- In a particular embodiment, two or more audio object signals may, e.g., be mixed within the audio transport signal, two or more audio channel signals are mixed within the audio transport signal. In such an embodiment, the covariance information may, e.g., indicate correlation information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals. Moreover, in such an embodiment, the covariance information (that is e.g., transmitted from an encoder side to a decoder side) does not indicate correlation information for any pair of a first one of the one or more audio object signals and a second one of the one or more audio object signals, because the correlation between the audio object signals may be so small, that it can be neglected, and is thus, for example, not transmitted to save bitrate and processing time. In such an embodiment, the parameter processor 110 is configured to calculate the mixing information depending on the downmix information, depending on a the level difference information of each of the one or more audio channel signals, depending on the second level difference information of each of the one or more audio object signals, and depending on the correlation information of the one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals. Such an embodiment employs the above described finding that a correlation between audio object signals is in general relatively low and should be neglected, while a correlation between two audio channel signals is in general, relatively high and should be considered. By not processing irrelevant correlation information between audio object signals, processing time can be saved. By processing relevant correlation between audio channel signals, coding efficiency can be enhanced.

In particular embodiments, the one or more audio channel signals are mixed within a first group of one or more of the audio transport channels, wherein the one or more audio object signals are mixed within a second group of one or more of the audio transport channels, wherein each audio transport channel of the first group is not comprised by the second group, and wherein each audio transport channel of the second group is not comprised by the first group. In such embodiments, the downmix information comprises first downmix subinformation indicating information on how the one or more audio channel signals are mixed within the first group of the one or more audio transport channels, and the downmix information comprises second downmix subinformation indicating information on how the one or more audio object signals are mixed within the second group of the one or more audio transport channels. In such embodiments, the parameter processor 110 is configured to calculate the mixing information depending on the first downmix subinformation, depending on the second downmix subinformation and depending on the covariance information, and the downmix processor 120 is configured to generate the one or more audio output signals from the first group of one or more audio transport channels and from the second group of audio transport channels depending on the mixing information. By such an approach coding efficiency is increased, as between audio channel signals of a sound scene, a high correlation exists. Moreover, coefficients of the downmix matrix indicating an influence of audio channel signals on the audio transport channels, which encode audio object signals, and vice versa, do not have to be calculated by the encoder, do not have to be transmitted, and can be set to zero by the decoder without the need of processing them. This saves transmission bandwidth and computation time for encoder and decoder.

In an embodiment, the downmix processor 120 is configured to receive the audio transport signal in a bitstream, the downmix processor 120 is configured to receive a first channel count number indicating the number of the audio transport channels encoding only audio channel signals, and the downmix processor 120 is configured to receive a second channel count number indicating the number of the audio transport channels encoding only audio object signals. In such an embodiment, the downmix processor 120 is configured to identify whether an audio transport channel of the audio transport signal encodes audio channel signals or whether an audio transport channel of the audio transport signal encodes audio object signals depending on the first channel count number or depending on the second channel count number, or depending on the first channel count number and the second channel count number. For example, in the bitstream, the audio transport channels which encode audio channel signals appear first and the audio transport channels which encode audio object signals appear afterwards. Then, if the first channel count number is, e.g., 3 and the second channel count number

is, e.g., 2, the downmix processor can conclude that the first three audio transport channels comprise encoded audio channel signals and the subsequent two audio transport channels comprise encoded audio object signals.

5 In an embodiment, the parameter processor 110 is configured to receive metadata information comprising position information, wherein the position information indicates a position for each of the one or more audio object signals, and wherein the position information does not indicate a position for any of the one or more audio channel signals. In such an embodiment the parameter processor 110 is configured to calculate the mixing
10 information depending on the downmix information, depending on the covariance information, and depending on the position information. Additionally or alternatively, the metadata information further comprises gain information, wherein the gain information indicates a gain value for each of the one or more audio object signals, and wherein the gain information does not indicate a gain value for any of the one or more audio channel
15 signals. In such an embodiment, the parameter processor 110 may be configured to calculate the mixing information depending on the downmix information, depending on the covariance information, depending on the position information, and depending on the gain information. For example, the parameter processor 110 may be configured to calculate the mixing information furthermore depending depending on the submatrix R_{ch} described
20 above.

According to an embodiment, the parameter processor 110 is configured to calculate a mixing matrix S as the mixing information, wherein the mixing matrix S is defined according to the formula $S = RG$, wherein G is a decoding matrix depending on the
25 downmix information and depending on the covariance information, wherein R is a rendering matrix depending on the metadata information. In such an embodiment, the downmix processor (120) may be configured to generate the one or more audio output channels of the audio output signal by applying the formula $Z = SY$, wherein Z is the audio output signal, and wherein Y is the audio transport signal. E.g., R may depend on
30 the submatrices R_{ch} and/or R_{obj} (e.g., $R = (R_{ch}, R_{obj})$) described above.

Fig. 3 illustrates a system according to an embodiment. The system comprises an apparatus 310 for generating an audio transport signal as described above and an apparatus 320 for generating one or more audio output channels as described above.

35

The apparatus 320 for generating the one or more audio output channels is configured to receive the audio transport signal, downmix information and covariance information from the apparatus 310 for generating the audio transport signal. Moreover, the apparatus 320

for generating the audio output channels is configured to generate the one or more audio output channels depending from the audio transport signal depending on the downmix information and depending on the covariance information.

5 According to embodiments, the functionality of the SAOC system, which is an object oriented system that realizes object coding, is extended so that audio objects (object coding) or audio channels (channel coding) or both audio channels and audio objects (mixed coding) can be encoded.

10 The SAOC encoder 800 of Fig. 6 and 8 described above is enhanced, so that not only it can receive audio objects as input, but it can also receive audio channels as input, and so that the SAOC encoder can generate downmix channels (e.g., SAOC transport channels) in which the received audio objects and the received audio channels are encoded. In the above-described embodiments, e.g., of Fig. 6 and 8, such a SAOC encoder 800 receives
15 not only audio objects but also audio channels as input and generates downmix channels (e.g., SAOC transport channels) in which the received audio objects and the received audio channels are encoded. For example, the SAOC encoder of Fig. 6 and 8 is implemented as an apparatus for generating an audio transport signal (comprising one or more audio transport channels, e.g., one or more SAOC transport channels) as described
20 with reference to Fig. 2, and the embodiments of Fig. 6 and 8 are modified such that not only objects but also one, some or all of the channels are fed into the SAOC encoder 800.

The SAOC decoder 1800 of Fig. 7 and 9 described above is enhanced, so that it can receive downmix channels (e.g., SAOC transport channels) in which the audio objects and
25 the audio channels are encoded, and so that it can generate the output channels (rendered channel signals and rendered object signals) from the received downmix channels (e.g., SAOC transport channels) in which the audio objects and the audio channels are encoded. In the above-described embodiments, e.g., of Fig. 7 and 9, such a SAOC decoder 1800 receives downmix channels (e.g., SAOC transport channels) in
30 which not only audio objects but also audio channels are encoded and generates the output channels (rendered channel signals and rendered object signals) from the received downmix channels (e.g., SAOC transport channels) in which the audio objects and the audio channels are encoded. For example, the SAOC decoder of Fig. 7 and 9 is implemented as an apparatus for generating one or more audio output channels as
35 described with reference to Fig. 1, and the embodiments of Fig. 7 and 9 are modified such that one, some or all of the channels illustrated between the USAC decoder 1300 and the mixer 1220 are not generated (reconstructed) by the USAC decoder 1300, but are instead

reconstructed by the SAOC decoder 1800 from the SAOC transport channels (audio transport channels).

Depending on the application, different advantages of a SAOC system can be exploited
5 by using such an enhanced SAOC system.

According to some embodiments, such an enhanced SAOC system supports an arbitrary number of downmix channels and rendering to arbitrary number of output channels. In some embodiments, for example, the number of downmix channels (SAOC Transport
10 Channels) can be reduced (e.g., at runtime), e.g., to scale down the overall bitrate significantly. This will lead to low bitrates.

Moreover, according to some embodiments, the SAOC decoder of such an enhanced SAOC system may, for example, have an integrated flexible renderer which may, e.g.,
15 allow user interaction. By this, the user can change the position of the objects in the audio scene, attenuate or increase the level of individual objects, completely suppress objects, etc. For example, considering the channel signals as background objects (BGOs) and the object signals as foreground objects (FGOs), the interactivity feature of SAOC may be used for applications like dialogue enhancement. By such an interactivity feature, the user
20 may have the freedom to manipulate, in a limited range, the BGOs and FGOs, in order to increase the dialogue intelligibility (e.g., the dialogue may be represented by foreground objects) or to obtain a balance between dialogue (e.g., represented by FGOs) and the ambient background (e.g., represented by BGOs).

Furthermore, according to embodiments, depending on the available computation complexity at the decoder side, the SAOC decoder can scale down automatically the computational complexity by operating in a "low-computaton-complexity" mode, for example, by reducing the number of decorrelators, and/or, for example, by rendering directly to the reproduction layout and deactivate the subsequent format converter 1720
30 that has been described above. For example, rendering information may steer how to downmix the channels of a 22.2 system to the channels of a 5.1 system.

According to embodiments, the Enhanced SAOC encoder may process a variable number of input channels ($N_{Channels}$) and input objects ($N_{Objects}$). The number of channels and
35 objects are transmitted into the bitstream in order to signal to the decoder side the presence of the channel path. The input signals to the SAOC encoder are always ordered such that the channel signals are the first ones and the object signals are the last ones.

According to another embodiment, channel/object mixer 210 is configured to generate the audio transport signal so that the number of the one or more audio transport channels of the audio transport signal depends on how much bitrate is available for transmitting the audio transport signal.

5

For example, the number of downmix (transport) channels may, e.g., be computed as a function of the available bitrate and total number of input signals:

$$N_{DmxCh} = f(\text{bitrate}, N).$$

10

The downmix coefficients in $\mathbf{D}$ determine the mixing of the input signals (channels and objects). Depending on the application, the structure of the matrix $\mathbf{D}$ can be specified such that the channels and objects are mixed together or kept separated.

15

Some embodiments, are based on the finding that it is beneficial not to mix the objects together with the channels. To not mix the objects together with the channels, the downmix matrix may, e.g., be constructed as:

$$\mathbf{D} = \begin{bmatrix} \mathbf{D}_{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{D}_{obj} \end{bmatrix}$$

20

In order to signal the separate mixing into the bitstream the values of the number of downmix channels assigned to the channel path (N_{DmxCh}^{ch}) and the number of downmix channels assigned to the object path (N_{DmxCh}^{obj}) may, e.g., be transmitted.

25

The block-wise downmixing matrices $\mathbf{D}_{ch}$ and $\mathbf{D}_{obj}$ have the sizes: $N_{DmxCh}^{ch} \times N_{Channels}$ and respectively $N_{DmxCh}^{obj} \times N_{Objects}$.

30

At the decoder the coefficients of the parametric source estimation matrix $\mathbf{G} \approx \mathbf{E}_X \mathbf{D}^H (\mathbf{D} \mathbf{E}_X \mathbf{D}^H)^{-1}$ are computed in a different fashion. Using a matrix form, this can be expressed as:

$$\mathbf{G} = \begin{bmatrix} \mathbf{G}_{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{G}_{obj} \end{bmatrix}$$

with:

- $\mathbf{G}_{ch} \approx \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H (\mathbf{D}_{ch} \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H)^{-1}$ of size $N_{Channels} \times N_{DmxCh}^{ch}$
- $\mathbf{G}_{obj} \approx \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H (\mathbf{D}_{obj} \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H)^{-1}$ of size $N_{Objects} \times N_{DmxCh}^{obj}$

5

The values of the channels signal covariance ($\mathbf{E}_X^{ch}$) and object signal covariance ($\mathbf{E}_X^{obj}$) may, e.g., be obtained from the input signals covariance matrix ($\mathbf{E}_X$) by selecting only the corresponding diagonal blocks:

10

$$\mathbf{E}_X = \begin{bmatrix} \mathbf{E}_X^{ch} & \mathbf{E}_X^{ch,obj} \\ \mathbf{E}_X^{obj,ch} & \mathbf{E}_X^{obj} \end{bmatrix}$$

As a direct consequence the bitrate is reduced by not sending the additional information (e.g., OLDs, IOC) to reconstruct the cross-covariance matrix between channels and objects: $\mathbf{E}_X^{ch,obj} = (\mathbf{E}_X^{obj,ch})^H$.

15

According to some embodiments, $\mathbf{E}_X^{ch,obj} = (\mathbf{E}_X^{obj,ch})^H = 0$, and thus:

$$\mathbf{E}_X = \begin{bmatrix} \mathbf{E}_X^{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{E}_X^{obj} \end{bmatrix}.$$

20 According to an embodiment, the enhanced SAOC encoder is configured to not transmit information on a covariance between any one of the audio objects and any one of the audio channels to the enhanced SAOC decoder.

Moreover, according to an embodiment, the enhanced SAOC decoder is configured to not
25 receive information on a covariance between any one of the audio objects and any one of the audio channels.

The off-diagonal block-wise elements of $\mathbf{G}$ are not computed, but set to zero. Therefore possible cross-talk between reconstructed channels and objects is avoided. Moreover, by
30 this, reduction of computational complexity is achieved as less coefficients of $\mathbf{G}$ have to be computed.

Moreover, according to embodiments, instead of inverting the larger matrix:

$\mathbf{D} \mathbf{E}_X \mathbf{D}^H$ of size $[N_{DmxCh}^{ch} + N_{DmxCh}^{obj}] \times [N_{DmxCh}^{ch} + N_{DmxCh}^{obj}]$,

the two following small matrices are inverted:

5 $\mathbf{D}_{ch} \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H$ of size $N_{DmxCh}^{ch} \times N_{DmxCh}^{ch}$

$\mathbf{D}_{obj} \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H$ of size $N_{DmxCh}^{obj} \times N_{DmxCh}^{obj}$

10 Inverting the smaller matrices $\mathbf{D}_{ch} \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H$ and $\mathbf{D}_{obj} \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H$ is much cheaper regarding computational complexity than inverting the larger matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$.

Furthermore, by inverting separate matrices $\mathbf{D}_{ch} \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H$ and $\mathbf{D}_{obj} \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H$, possible numerical instabilities are reduced compared to inverting the larger matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$. For example, in the worst case scenario, when the covariance matrices of the transport channels $\mathbf{D}_{ch} \mathbf{E}_X^{ch} \mathbf{D}_{ch}^H$ and $\mathbf{D}_{obj} \mathbf{E}_X^{obj} \mathbf{D}_{obj}^H$ have linear dependencies due to signal similarities, the full matrix $\mathbf{D} \mathbf{E}_X \mathbf{D}^H$ may be ill-conditioned while the separate smaller matrices can be well-conditioned.

After

20

$$\mathbf{G} = \begin{bmatrix} \mathbf{G}_{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{G}_{obj} \end{bmatrix}$$

is computed at the decoder side, then it is possible to, for example, parametrically estimate the input signals to obtain reconstructed input signals $\hat{\mathbf{X}}$ (the input audio channel signals and the input audio object signals), e.g., using:

$$\hat{\mathbf{X}} = \mathbf{G} \mathbf{Y}.$$

Moreover, as described above, rendering may be conducted on the decoder side to obtain the output channels $\mathbf{Z}$, e.g., by employing a rendering matrix $\mathbf{R}$:

30

$$\mathbf{Z} = \mathbf{R} \hat{\mathbf{X}}$$

$$\mathbf{Z} = \mathbf{R} \mathbf{G} \mathbf{Y}$$

35

$$\mathbf{Z} = \mathbf{S}\mathbf{Y} ; \text{ with } \mathbf{S} = \mathbf{R}\mathbf{G}$$

Instead of explicitly reconstructing the input signals (the input audio channel signals and the input audio object signals) to obtain reconstructed input channels $\hat{\mathbf{X}}$, the output channels $\mathbf{Z}$ may be directly generated at the decoder side by applying the output channel generation matrix $\mathbf{S}$ on the downmix audio signal $\mathbf{Y}$.

As already described above, to obtain the output channel generation matrix $\mathbf{S}$, rendering matrix $\mathbf{R}$ may, e.g., be determined or may, e.g., be already available. Furthermore, the parametric source estimation matrix $\mathbf{G}$ may, e.g., be computed as described above. The output channel generation matrix $\mathbf{S}$ may then be obtained as the matrix product $\mathbf{S} = \mathbf{R}\mathbf{G}$ from the rendering matrix $\mathbf{R}$ and the parametric source estimation matrix $\mathbf{G}$.

Regarding the reconstructed audio object signals, compress metadata on the audio objects that is transmitted from the encoder to the decoder may be taken into account. For example, the metadata on the audio objects may indicate position information on each of the audio objects. Such position information may for example be an azimuth angle, an elevation angle and a radius. This position information may indicate a position of the audio object in a 3D space. For example, when an audio object is located close to an assumed or real loudspeaker position, such an audio object has a higher weight in the output channel for said loudspeaker compared to the weight of another audio object in the output channel being located far away from said loudspeaker. For example, vector base amplitude panning (VBAP) may be employed (see, for example, [VBAP]) to determine the rendering coefficients of the rendering matrix $\mathbf{R}$ for the audio objects.

Furthermore, in some embodiments, the compress metadata may comprise a gain value for each of the audio objects. For example, for each of the audio object signal, a gain value may indicate a gain factor for said audio object signal.

In contrast to the audio objects, no position information metadata is transmitted from the encoder to the decoder for the audio channel signals. A additional matrix (e.g., to convert 22.2 to 5.1) or identity matrix (when input configuration of the channels equals the output configuration) may, for example, be employed to determine the rendering coefficients of the rendering matrix $\mathbf{R}$ for the audio channels.

Rendering matrix $\mathbf{R}$ may be of size $N_{\text{OutputChannels}} \times N$. Here, for each of the output channels, a row exists in the matrix $\mathbf{R}$. Moreover, in each row of the rendering matrix $\mathbf{R}$, N coefficients determine the weight of the N input signals (the input audio channels and the

input audio objects) in the corresponding output channel. Those audio objects being located close to the loudspeaker of said output channel have a greater coefficient than the coefficient of the audio objects being located far away from the loudspeaker of the corresponding output channel.

5

For example, Vector Base Amplitude Panning (VBAP) may be employed (see, e.g., [VBAP]) to determine the weight of an audio object signal within each of the audio channels of the loudspeakers. E.g., with respect to VBAP, it is assumed that an audio object relates to a virtual source.

10

As, in contrast to audio objects, audio channels do not have a position, the coefficients relating to audio channels in the rendering matrix may, e.g., be independent from position information.

15

In the following, the bitstream syntax according to embodiments is described.

In context of MPEG SAOC, signaling of the possible modes of operation (channel based, object based or combined mode) can be accomplished by using, for example, one of the two following possibilities (first possibility: using flags for signaling the operation mode; second possibility: without using flags for signaling the operation mode):

20

Thus, according to a first embodiment, flags are used for signaling the operation mode.

To use flags for signaling the operation mode a syntax of a SAOCSpecifyConfig() element or SAOC3DSpecifyConfig() element may, for example, comprise:

25

```

bsSaocChannelFlag;                                1      uimsbf
NumInputSignals = 0;
bsSaocCombinedModeFlag = 0;
30  if (bsSaocChannelFlag) {
        bsNumSaocChannels;                            5      uimsbf
        bsNumSaocDmxChannels;                        5      uimsbf
        NumInputSignals += bsNumSaocChannels + 1;
    }
35  bsSaocObjectFlag;                                1      uimsbf
    if (bsSaocObjectFlag) {
        bsNumSaocObjects;                            7      uimsbf
        bsNumSaocDmxObjects;                        5      uimsbf
    }

```

```

        bsSaocCombinedModeFlag;                                1
        uimbsfNumInputSignals += bsNumSaocObjects + 1;
    }
    for ( i=0; i< bsNumSaocChannels+1; i++ ) {
5        bsRelatedTo[i][i] = 1;
        for( j=i+1; j< bsNumSaocChannels+1; j++ ) {
            bsRelatedTo[i][j];                                1    uimbsf
            bsRelatedTo[j][i] = bsRelatedTo[i][j];
        }
10    }
    for ( i= bsNumSaocChannels+1; i< bs NumInputSignals; i++ ) {
        for( j=0; j< bsNumSaocChannels+1; j++ ) {
            bsRelatedTo[i][j] = 0
            bsRelatedTo[j][i] = 0
15        }
    }
    for ( i= bsNumSaocChannels+1; i< bs NumInputSignals; i++ ) {
        bsRelatedTo[i][i] = 1;
        for( j=i+1; j< NumInputSignals; j++ ) {
20            bsRelatedTo[i][j];                                1    uimbsf
            bsRelatedTo[j][i] = bsRelatedTo[i][j];
        }
    }
}

```

25

If the bitstream variable **bsSaocChannelFlag** is set to one the first **bsNumSaocChannels+1** input signals are treated like channel based signals. If the bitstream variable **bsSaocObjectFlag** is set to one the last **bsNumSaocObjects+1** input signals are processed like object signals. Therefore in case that both bitstream variables (**bsSaocChannelFlag**, **bsSaocObjectFlag**) are different than zero the presence of channels and objects into the audio transport channels is signaled.

30

If the bitstream variable **bsSaocCombinedModeFlag** is equal to one the combined decoding mode is signaled into the bitstream and, the decoder will process the **bsNumSaocDmxChannels** transport channels using the full downmix matrix **D** (this meaning that the channel signals and object signals are mixed together).

35

If the bitstream variable **bsSaocCombinedModeFlag** is zero the independent decoding mode is signaled and the decoder will process (**bsNumSaocDmxChannels**+1) + (**bsNumSaocDmxObjects**+1) transport channels using a block-wise downmix matrix as described above.

5

According to a preferred second embodiment, no flags are needed for signaling the operation mode.

10 Signaling the operation mode without using flags, may, for example, be realized by employing the following syntax

Signaling:

Syntax of SAOC3DSpecificConfig():

15

bsNumSaocDmxChannels;	5	uimsbf
bsNumSaocDmxObjects;	5	uimsbf
NumInputSignals = 0;		
if (bsNumSaocDmxChannels > 0) {		
bsNumSaocChannels;	6	uimsbf
bsNumSaocLFEs;	2	uimsbf
NumInputSignals += bsNumSaocChannels;		
}		
bsNumSaocObjects;	8	uimsbf
NumInputSignals += bsNumSaocObjects;		

Restrict the cross-correlation between channels and objects to be zero:

for (i=0; i<bsNumSaocChannels; i++) {		
bsRelatedTo[i][i] = 1;		
for(j=i+1; j< bsNumSaocChannels; j++) {		
bsRelatedTo[i][j];	1	uimsbf
bsRelatedTo[j][i] = bsRelatedTo[i][j];		
}		
}		
for (i=bsNumSaocChannels;		

```

i<NumInputSignals; i++ ) {
    for( j=0; j<bsNumSaocChannels; j++ ) {
        bsRelatedTo[i][j] = 0;
        bsRelatedTo[j][i] = 0;
    }
}
for ( i=bsNumSaocChannels;
i<NumInputSignals; i++ ) {
    bsRelatedTo[i][i] = 1;
    for( j=i+1; j<NumInputSignals; j++ ) {
        bsRelatedTo[i][j]; 1 uimsbf
        bsRelatedTo[j][i] = bsRelatedTo[i][j];
    }
}

```

Read the downmixing gains differently for the case when the audio channels and audio objects are mixed in different audio transport channels and when they are mixed together within the audio transport channels:

5

```

if (bsNumSaocDmxObjects==0) {
    for( i=0; i< bsNumSaocDmxChannels; i++ ) {
        idxDMG[i] = EcDataSaoc(DMG, 0, NumInputSignals);
    }
} else {
    dmglDx = 0;
    for( i=0; i<bsNumSaocDmxChannels; i++ ) {
        idxDMG[i] = EcDataSaoc(DMG, 0, bsNumSaocChannels);
    }
    dmglDx = bsNumSaocDmxChannels;
    if (bsSaocDmxMethod == 0) {
        for( i=dmglDx; i<dmglDx + bsNumSaocDmxObjects; i++ ) {
            idxDMG[i] = EcDataSaoc(DMG, 0, bsNumSaocObjects);
        }
    }
    if (bsSaocDmxMethod == 1) {
        for( i= dmglDx; i<dmglDx + bsNumSaocDmxObjects; i++ ) {
            idxDMG[i] = EcDataSaoc(DMG, 0, bsNumPremixedChannels);
        }
    }
}

```

If the bitstream variable **bsNumSaocChannels** is different than zero the first **bsNumSaocChannels** input signals are treated like channel based signals. If the bitstream variable **bsNumSaocObjects** is different than zero the last

bsNumSaocObjects input signals are processed like object signals. Therefore in case that both bitstream variables are different than zero the presence of channels and objects into the audio transport channels is signaled.

5

If the bitstream variable **bsNumSaocDmxObjects** is equal to zero the combined decoding mode is signaled into the bitstream and, the decoder will process the **bsNumSaocDmxChannels** transport channels using the full downmix matrix **D** (this meaning that the channel signals and object signals are mixed together).

10

If the bitstream variable **bsNumSaocDmxObjects** is different than zero the independent decoding mode is signaled and the decoder will process **bsNumSaocDmxChannels** + **bsNumSaocDmxObjects** transport channels using a block-wise downmix matrix as described above.

15

In the following, aspects of downmix processing according to an embodiment are described:

20

The output signal of the downmix processor (represented in the hybrid QMF domain) is fed into the corresponding synthesis filterbank as described in ISO/IEC 23003-1:2007 yielding the final output of the SAOC 3D decoder.

25

The parameter processor 110 of Fig. 1 and the downmix processor 120 of Fig. 1 may be implemented as a joint processing unit. Such a joint processing unit is illustrated by Fig. 1, wherein units U and R implement the parameter processor 110 by providing the mixing information.

30

The output signal $\hat{Y}$ is computed from the multi-channel downmix signal X and the decorrelated multi-channel signal X_d as:

$$\hat{Y} = P_{dry} R U X + P_{wet} M_{post} X_d .$$

where U represents the parametric unmixing matrix.

35

The mixing matrix $P = \begin{pmatrix} P_{dry} & P_{wet} \end{pmatrix}$ is a mixing matrix.

The decorrelated multi-channel signal $\mathbf{X}_d$ is defined as

$$\mathbf{X}_d = \text{decorrFunc}(\mathbf{M}_{\text{pre}} \mathbf{Y}_{\text{dry}}).$$

- 5 The decoding mode is controlled by the bitstream element **bsNumSaocDmxObjects**:

bsNumSaocDmxObjects	Decoding Mode	Meaning
0	Combined	The input channel based signals and the input object based signals are downmixed together into N_{ch} channels.
≥ 1	Independent	The input channel based signals are downmixed into N_{ch} channels. The input object based signals are downmixed into N_{obj} channels.

In case of combined decoding mode the parametric unmixing matrix $\mathbf{U}$ is given by:

10
$$\mathbf{U} = \mathbf{E} \mathbf{D}^* \mathbf{J}.$$

The matrix $\mathbf{J}$ of size $N_{dmx} \times N_{dmx}$ is given by $\mathbf{J} \approx \mathbf{\Delta}^{-1}$ with $\mathbf{\Delta} = \mathbf{D} \mathbf{E} \mathbf{D}^*$.

In case of independent decoding mode the unmixing matrix $\mathbf{U}$ is given by:

15
$$\mathbf{U} = \begin{pmatrix} \mathbf{U}_{ch} & 0 \\ 0 & \mathbf{U}_{obj} \end{pmatrix},$$

where $\mathbf{U}_{ch} = \mathbf{E}_{ch} \mathbf{D}_{ch}^* \mathbf{J}_{ch}$ and $\mathbf{U}_{obj} = \mathbf{E}_{obj} \mathbf{D}_{obj}^* \mathbf{J}_{obj}$.

- 20 The channel based covariance matrix $\mathbf{E}_{ch}$ of size $N_{ch} \times N_{ch}$ and the object based covariance matrix $\mathbf{E}_{obj}$ of size $N_{obj} \times N_{obj}$ are obtained from the covariance matrix $\mathbf{E}$ by selecting only the corresponding diagonal blocks:

$$\mathbf{E} = \begin{pmatrix} \mathbf{E}_{ch} & \mathbf{E}_{ch,obj} \\ \mathbf{E}_{obj,ch} & \mathbf{E}_{obj} \end{pmatrix},$$

where the matrix $\mathbf{E}_{\text{ch,obj}} = (\mathbf{E}_{\text{obj,ch}})^*$ represents the cross-covariance matrix between the input channels and input objects and is not required to be calculated.

The channel based downmix matrix $\mathbf{D}_{\text{ch}}$ of size $N_{\text{ch}}^{\text{dmx}} \times N_{\text{ch}}$ and the object based downmix matrix $\mathbf{D}_{\text{obj}}$ of size $N_{\text{obj}}^{\text{dmx}} \times N_{\text{obj}}$ are obtained from the downmix matrix $\mathbf{D}$ by selecting only the corresponding diagonal blocks:

$$\mathbf{D} = \begin{pmatrix} \mathbf{D}_{\text{ch}} & 0 \\ 0 & \mathbf{D}_{\text{obj}} \end{pmatrix}.$$

10 The matrix $\mathbf{J}_{\text{ch}} \approx (\mathbf{D}_{\text{ch}} \mathbf{E}_{\text{ch}} \mathbf{D}_{\text{ch}}^*)^{-1}$ of size $N_{\text{ch}}^{\text{dmx}} \times N_{\text{ch}}^{\text{dmx}}$ is derived from the definition of matrix $\mathbf{J}$ for

$$\Delta = \mathbf{D}_{\text{ch}} \mathbf{E}_{\text{ch}} \mathbf{D}_{\text{ch}}^*.$$

15 The matrix $\mathbf{J}_{\text{obj}} \approx (\mathbf{D}_{\text{obj}} \mathbf{E}_{\text{obj}} \mathbf{D}_{\text{obj}}^*)^{-1}$ of size $N_{\text{obj}}^{\text{dmx}} \times N_{\text{obj}}^{\text{dmx}}$ is derived from the definition of matrix $\mathbf{J}$ for

$$\Delta = \mathbf{D}_{\text{obj}} \mathbf{E}_{\text{obj}} \mathbf{D}_{\text{obj}}^*$$

20

The matrix $\mathbf{J} \approx \Delta^{-1}$ is calculated using the following equation:

$$\mathbf{J} = \mathbf{V} \Delta^{\text{inv}} \mathbf{V}^*.$$

25 Here the singular vectors $\mathbf{V}$ of the matrix Δ are obtained using the following characteristic equation

$$\mathbf{V} \Delta \mathbf{V}^* = \Delta.$$

30 The regularized inverse Δ^{inv} of the diagonal singular value matrix Δ is computed as

$$\lambda_{i,j}^{\text{inv}} = \begin{cases} \frac{1}{\lambda_{i,j}}, & \text{if } i = j \text{ and } \lambda_{i,j} \geq T_{\text{reg}}^{\Delta} \\ 0, & \text{otherwise} \end{cases},$$

The relative regularization scalar T_{reg}^{Λ} is determined using absolute threshold T_{reg} and maximal value of Λ as

$$T_{reg}^{\Lambda} = \max(\lambda_{i,i}) T_{reg}, \quad T_{reg} = 10^{-2}.$$

5

In the following, the rendering matrix according to an embodiment is described:

The rendering matrix $\mathbf{R}$ applied to the input audio signals $\mathbf{S}$ determines the target rendered output as $\mathbf{Y} = \mathbf{R}\mathbf{S}$. The rendering matrix $\mathbf{R}$ of size $N_{out} \times N$ is given by

10

$$\mathbf{R} = \begin{pmatrix} \mathbf{R}_{ch} & \mathbf{R}_{obj} \end{pmatrix},$$

where $\mathbf{R}_{ch}$ of size $N_{out} \times N_{ch}$ represents the rendering matrix associated with the input channels and $\mathbf{R}_{obj}$ of size $N_{out} \times N_{obj}$ represents the rendering matrix associated with the

15

input objects.

In the following, decorrelated multi-channel signal $\mathbf{X}_d$ according to an embodiment is described:

20

The decorrelated signals $\mathbf{X}_d$ are, for example, created from the decorrelator described in 6.6.2 of ISO/IEC 23003-1:2007, with `bsDecorrConfig == 0` and, e.g., a decorrelator index, X . Hence, the *decorrFunc*() for example, denotes the decorrelation process:

$$\mathbf{X}_d = \text{decorrFunc}(\mathbf{M}_{pre} \mathbf{Y}_{dry}).$$

25

Although some aspects have been described in the context of an apparatus, it is clear that these aspects also represent a description of the corresponding method, where a block or device corresponds to a method step or a feature of a method step. Analogously, aspects described in the context of a method step also represent a description of a corresponding block or item or feature of a corresponding apparatus.

30

The inventive decomposed signal can be stored on a digital storage medium or can be transmitted on a transmission medium such as a wireless transmission medium or a wired transmission medium such as the Internet.

35

Depending on certain implementation requirements, embodiments of the invention can be implemented in hardware or in software. The implementation can be performed using a

digital storage medium, for example a floppy disk, a DVD, a CD, a ROM, a PROM, an EPROM, an EEPROM or a FLASH memory, having electronically readable control signals stored thereon, which cooperate (or are capable of cooperating) with a programmable computer system such that the respective method is performed.

5

Some embodiments according to the invention comprise a non-transitory data carrier having electronically readable control signals, which are capable of cooperating with a programmable computer system, such that one of the methods described herein is performed.

10

Generally, embodiments of the present invention can be implemented as a computer program product with a program code, the program code being operative for performing one of the methods when the computer program product runs on a computer. The program code may for example be stored on a machine readable carrier.

15

Other embodiments comprise the computer program for performing one of the methods described herein, stored on a machine readable carrier.

20

In other words, an embodiment of the inventive method is, therefore, a computer program having a program code for performing one of the methods described herein, when the computer program runs on a computer.

25

A further embodiment of the inventive methods is, therefore, a data carrier (or a digital storage medium, or a computer-readable medium) comprising, recorded thereon, the computer program for performing one of the methods described herein.

30

A further embodiment of the inventive method is, therefore, a data stream or a sequence of signals representing the computer program for performing one of the methods described herein. The data stream or the sequence of signals may for example be configured to be transferred via a data communication connection, for example via the Internet.

35

A further embodiment comprises a processing means, for example a computer, or a programmable logic device, configured to or adapted to perform one of the methods described herein.

A further embodiment comprises a computer having installed thereon the computer program for performing one of the methods described herein.

In some embodiments, a programmable logic device (for example a field programmable gate array) may be used to perform some or all of the functionalities of the methods described herein. In some embodiments, a field programmable gate array may cooperate
5 with a microprocessor in order to perform one of the methods described herein. Generally, the methods are preferably performed by any hardware apparatus.

The above described embodiments are merely illustrative for the principles of the present invention. It is understood that modifications and variations of the arrangements and the
10 details described herein will be apparent to others skilled in the art. It is the intent, therefore, to be limited only by the scope of the impending patent claims and not by the specific details presented by way of description and explanation of the embodiments herein.

References

- 5 [SAOC1] J. Herre, S. Disch, J. Hilpert, O. Hellmuth: "From SAC To SAOC - Recent Developments in Parametric Coding of Spatial Audio", 22nd Regional UK AES Conference, Cambridge, UK, April 2007.
- 10 [SAOC2] J. Engdegård, B. Resch, C. Falch, O. Hellmuth, J. Hilpert, A. Hölzer, L. Terentiev, J. Breebaart, J. Koppens, E. Schuijers and W. Oomen: "Spatial Audio Object Coding (SAOC) – The Upcoming MPEG Standard on Parametric Object Based Audio Coding", 124th AES Convention, Amsterdam 2008.
- 15 [SAOC] ISO/IEC, "MPEG audio technologies – Part 2: Spatial Audio Object Coding (SAOC)," ISO/IEC JTC1/SC29/WG11 (MPEG) International Standard 23003-2.
- 20 [VBAP] Ville Pulkki, "Virtual Sound Source Positioning Using Vector Base Amplitude Panning"; J. Audio Eng. Soc., Level 45, Issue 6, pp. 456-466, June 1997.
- [M1] Peters, N., Lossius, T. and Schacher J. C., "SpatDIF: Principles, Specification, and Examples", 9th Sound and Music Computing Conference, Copenhagen, Denmark, Jul. 2012.
- 25 [M2] Wright, M., Freed, A., "Open Sound Control: A New Protocol for Communicating with Sound Synthesizers", International Computer Music Conference, Thessaloniki, Greece, 1997.
- 30 [M3] Matthias Geier, Jens Ahrens, and Sascha Spors. (2010), "Object-based audio reproduction and the audio scene description format", Org. Sound, Vol. 15, No. 3, pp. 219-227, December 2010.
- [M4] W3C, "Synchronized Multimedia Integration Language (SMIL 3.0)", Dec. 2008.
- 35 [M5] W3C, "Extensible Markup Language (XML) 1.0 (Fifth Edition)", Nov. 2008.

- [M6] MPEG, "ISO/IEC International Standard 14496-3 - Coding of audio-visual objects, Part 3 Audio", 2009.
- 5 [M7] Schmidt, J.; Schroeder, E. F. (2004), "New and Advanced Features for Audio Presentation in the MPEG-4 Standard", 116th AES Convention, Berlin, Germany, May 2004.
- 10 [M8] Web3D, "International Standard ISO/IEC 14772-1:1997 - The Virtual Reality Modeling Language (VRML), Part 1: Functional specification and UTF-8 encoding", 1997.
- [M9] Sporer, T. (2012), "Codierung räumlicher Audiosignale mit leichtgewichtigen Audio-Objekten", Proc. Annual Meeting of the German Audiological Society (DGA), Erlangen, Germany, Mar. 2012.

15

Claims

1. An apparatus for generating one or more audio output channels, wherein the apparatus comprises:
- 5 a parameter processor (110) for calculating mixing information, and
- a downmix processor (120) for generating the one or more audio output channels,
- 10 wherein the downmix processor (120) is configured to receive an audio transport signal comprising one or more audio transport channels, wherein one or more audio channel signals are mixed within the audio transport signal, wherein one or more audio object signals are mixed within the audio transport signal, and wherein the number of the one or more audio transport channels is smaller than the
- 15 number of the one or more audio channel signals plus the number of the one or more audio object signals,
- wherein the parameter processor (110) is configured to receive downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio
- 20 transport channels, and wherein the parameter processor (110) is configured to receive covariance information,
- wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information and depending on the
- 25 covariance information, and
- wherein the downmix processor (120) is configured to generate the one or more audio output channels from the audio transport signal depending on the mixing
- 30 information,
- wherein the covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals, and
- 35 wherein the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

2. An apparatus according to claim 1, wherein the covariance information indicates a level difference information for each of the one or more audio channel signals and further indicates a level difference information for each of the one or more audio object signals.

5

3. An apparatus according to claim 1 or 2,

wherein two or more audio object signals are mixed within the audio transport signal, and wherein two or more audio channel signals are mixed within the audio transport signal,

10

wherein the covariance information indicates correlation information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals, or

15

wherein the covariance information indicates correlation information for one or more pairs of a first one of the two or more audio object signals and a second one of the two or more audio object signals, or

20

wherein the covariance information indicates correlation information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals and indicates correlation information for one or more pairs of a first one of the two or more audio object signals and a second one of the two or more audio object signals.

25

4. An apparatus according to one of the preceding claims,

30

wherein the covariance information comprises a plurality of covariance coefficients of a covariance matrix $\mathbf{E}_X$ of size $N \times N$, wherein N indicates the number of the one or more audio channel signals plus the number of the one or more audio object signals,

wherein the downmix matrix $\mathbf{E}_X$ is defined according to the formula

35

$$\mathbf{E}_X = \begin{bmatrix} \mathbf{E}_X^{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{E}_X^{obj} \end{bmatrix},$$

wherein $\mathbf{E}_X^{ch}$ indicates the coefficients of a first covariance submatrix of size $N_{Channels} \times N_{Channels}$, wherein $N_{Channels}$ indicates the number of the one or more audio channel signals,

5 wherein $\mathbf{E}_X^{obj}$ indicates the coefficients of a second covariance submatrix of size $N_{Objects} \times N_{Objects}$, wherein $N_{Objects}$ indicates the number of the one or more audio object signals,

wherein $\mathbf{0}$ indicates a zero matrix,

10

wherein the parameter processor (110) is configured to receive the plurality of downmix coefficients of the downmix matrix $\mathbf{E}_X$, and

15

wherein the parameter processor (110) is configured to set all coefficients of the downmix matrix $\mathbf{E}_X$ to 0, that are not received by the parameter processor (110).

5. An apparatus according to one of the preceding claims,

20

wherein the one or more audio channel signals are mixed within a first group of one or more of the audio transport channels, wherein the one or more audio object signals are mixed within a second group of one or more of the audio transport channels, wherein each audio transport channel of the first group is not comprised by the second group, and wherein each audio transport channel of the second group is not comprised by the first group, and

25

wherein the downmix information comprises first downmix subinformation indicating information on how the one or more audio channel signals are mixed within the first group of the one or more audio transport channels, and wherein the downmix information comprises second downmix subinformation indicating information on how the one or more audio object signals are mixed within the second group of the one or more audio transport channels,

30

wherein the parameter processor (110) is configured to calculate the mixing information depending on the first downmix subinformation, depending on the second downmix subinformation and depending on the covariance information, and

35

wherein the downmix processor (120) is configured to generate the one or more audio output signals from the first group of one or more audio transport channels and from the second group of audio transport channels depending on the mixing information.

5

6. An apparatus according to claim 5,

10

wherein the downmix information comprises a plurality of downmix coefficients of a downmix matrix $\mathbf{D}$ of size $N_{DmxCh} \times N$, wherein N_{DmxCh} indicates the number of the one or more audio transport channels, and wherein N indicates the number of the one or more audio channel signals plus the number of the one or more audio object signals,

15

wherein the downmix matrix $\mathbf{D}$ is defined according to the formula

$$\mathbf{D} = \begin{bmatrix} \mathbf{D}_{ch} & \mathbf{0} \\ \mathbf{0} & \mathbf{D}_{obj} \end{bmatrix},$$

20

wherein $\mathbf{D}_{ch}$ indicates the coefficients of a first downmix submatrix of size $N_{DmxCh}^{ch} \times N_{Channels}$, wherein indicates N_{DmxCh}^{ch} the number of the one or more audio transport channels of the first group of the one or more audio transport channels, and wherein $N_{Channels}$ indicates the number of the one or more audio channel signals,

25

wherein $\mathbf{D}_{obj}$ indicates the coefficients of a second downmix submatrix of size $N_{DmxCh}^{obj} \times N_{Objects}$, wherein indicates N_{DmxCh}^{obj} the number of the one or more audio transport channels of the second group of the one or more audio transport channels, and wherein $N_{Objects}$ indicates the number of the one or more audio channel signals,

30

wherein $\mathbf{0}$ indicates a zero matrix,

wherein the parameter processor (110) is configured to receive the plurality of downmix coefficients of the downmix matrix $\mathbf{D}$, and

35

wherein the parameter processor (110) is configured to set all coefficients of the downmix matrix $\mathbf{D}$ to 0, that are not received by the parameter processor (110).

7. An apparatus according to claim 5 or 6,
- 5 wherein the downmix processor (120) is configured to receive a data stream comprising the audio transport channels of the audio transport signal,
- wherein the downmix processor (120) is configured to receive a first channel count number indicating the number of the audio transport channels of the first group of one or more audio transport channels,
- 10 wherein the downmix processor (120) is configured to receive a second channel count number indicating the number of the audio transport channels of the second group of one or more audio transport channels,
- 15 wherein the downmix processor (120) is configured to identify whether an audio transport channel within the data stream belongs to the first group or to the second group depending on the first channel count number or depending on the second channel count number, or depending on the first channel count number and the second channel count number.
- 20
8. An apparatus according to one of the preceding claims,
- wherein the parameter processor (110) is configured to receive rendering information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio output channels,
- 25
- wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information, depending on the covariance information and depending on rendering information.
- 30
9. An apparatus according to claim 8,
- wherein the parameter processor (110) is configured to receive a plurality of coefficients of a rendering matrix $\mathbf{R}$ as the rendering information, and
- 35

wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information, depending on the covariance information and depending on the rendering matrix $\mathbf{R}$.

5 10. An apparatus according to claim 8,

wherein the parameter processor (110) is configured to receive metadata information as the rendering information, wherein the metadata information comprises position information,

10

wherein the position information indicates a position for each of the one or more audio object signals,

15

wherein the position information does not indicate a position for any of the one or more audio channel signals,

20

wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information, depending on the covariance information, and depending on the position information.

11. An apparatus according to claim 10,

wherein the metadata information further comprises gain information,

25

wherein the gain information indicates a gain value for each of the one or more audio object signals,

30

wherein the gain information does not indicate a gain value for any of the one or more audio channel signals,

35

wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information, depending on the covariance information, depending on the position information, and depending on the gain information.

12. An apparatus according to claim 10 or 11,

wherein the parameter processor (110) is configured to calculate a mixing matrix S as the mixing information, wherein the mixing matrix S is defined according to the formula

5 $S = RG,$

wherein G is a decoding matrix depending on the downmix information and depending on the covariance information,

10 wherein R is a rendering matrix depending on the metadata information,

wherein the downmix processor (120) is configured to generate the one or more audio output channels of the audio output signal by applying the formula

15 $Z = SY,$

wherein Z is the audio output signal, and wherein Y is the audio transport signal.

13. An apparatus according to one of the preceding claims,

20

wherein two or more audio object signals are mixed within the audio transport signal, and wherein two or more audio channel signals are mixed within the audio transport signal,

25 wherein the covariance information indicates correlation information for one or more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals,

30 wherein the covariance information does not indicate correlation information for any pair of a first one of the one or more audio object signals and a second one of the one or more audio object signals, and

35 wherein the parameter processor (110) is configured to calculate the mixing information depending on the downmix information, depending on a the level difference information of each of the one or more audio channel signals, depending on the second level difference information of each of the one or more audio object signals, and depending on the correlation information of the one or

more pairs of a first one of the two or more audio channel signals and a second one of the two or more audio channel signals.

14. An apparatus for generating an audio transport signal comprising one or more audio transport channels, wherein the apparatus comprises:

a channel/object mixer (210) for generating the one or more audio transport channels of the audio transport signal, and

an output interface (220),

wherein the channel/object mixer (210) is configured to generate the audio transport signal comprising the one or more audio transport channels by mixing one or more audio channel signals and one or more audio object signals within the audio transport signal depending on downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals have to be mixed within the one or more audio transport channels, wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals,

wherein the output interface (220) is configured to output the audio transport signal, the downmix information and covariance information,

wherein the covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals, and

wherein the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

15. An apparatus according to claim 14, wherein channel/object mixer (210) is configured to generate the audio transport signal so that the number of the one or more audio transport channels of the audio transport signal depends on how much bitrate is available for transmitting the audio transport signal.

16. A system, comprising:

an apparatus (310) according to claim 14 or 15 for generating an audio transport signal, and

5 an apparatus (320) according to one of claims 1 to 13 for generating one or more audio output channels,

wherein the apparatus (320) according to one of claims 1 to 13 is configured to receive the audio transport signal, downmix information and covariance
10 information from the apparatus (310) according to claim 14 or 15, and

wherein the apparatus (320) according to one of claims 1 to 13 is configured to generate the one or more audio output channels from the audio transport signal depending on the downmix information and depending on the covariance
15 information.

17. A method for generating one or more audio output channels, wherein the method comprises:

20 receiving an audio transport signal comprising one or more audio transport channels, wherein one or more audio channel signals are mixed within the audio transport signal, wherein one or more audio object signals are mixed within the audio transport signal, and wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus
25 the number of the one or more audio object signals,

receiving downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals are mixed within the one or more audio transport channels,
30

receiving covariance information,

calculating mixing information depending on the downmix information and depending on the covariance information, and
35

generating the one or more audio output channels,

generating the one or more audio output channels from the audio transport signal depending on the mixing information,

wherein the covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals, and

wherein the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

18. A method for generating an audio transport signal comprising one or more audio transport channels, wherein the method comprises:

generating the audio transport signal comprising the one or more audio transport channels by mixing one or more audio channel signals and one or more audio object signals within the audio transport signal depending on downmix information indicating information on how the one or more audio channel signals and the one or more audio object signals have to be mixed within the one or more audio transport channels, wherein the number of the one or more audio transport channels is smaller than the number of the one or more audio channel signals plus the number of the one or more audio object signals, and

outputting the audio transport signal, the downmix information and covariance information,

wherein the covariance information indicates a level difference information for at least one of the one or more audio channel signals and further indicates a level difference information for at least one of the one or more audio object signals, and

wherein the covariance information does not indicate correlation information for any pair of one of the one or more audio channel signals and one of the one or more audio object signals.

19. A computer program for implementing the method of claim 17 or 18 when being executed on a computer or signal processor.

1/10




FIGURE 1




FIGURE 2

3/10





FIGURE 3



MODE1: individual channel/object coding
MODE2: mixing of channels and rendered objects

FIGURE 4
(ENCODER)




FIGURE 5
(DECODER)




FIGURE 6
(ENCODER)




FIGURE 7
(DECODER)

8/10




FIGURE 8
(ENCODER)

9/10




FIGURE 9
(DECODER)




FIGURE 10

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2014/065427

A. CLASSIFICATION OF SUBJECT MATTER
 INV. G10L19/008 H04S3/00
 ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 G10L H04S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data, COMPENDEX, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2009/326958 A1 (KIM DONG SOO [KR] ET AL) 31 December 2009 (2009-12-31)	1,14,
A	paragraph [0023] - paragraph [0040]	16-19
	paragraph [0132]; figure 16	2-13,15

A	ENGDEGARD J ET AL: "Spatial Audio Object Coding (SAOC) - The Upcoming MPEG Standard on Parametric Object Based Audio Coding", JOURNAL OF THE AUDIO ENGINEERING SOCIETY, AUDIO ENGINEERING SOCIETY, NEW YORK, NY, US, no. Paper Number: 7377, 17 May 2008 (2008-05-17), pages 1-16, XP002685475, ISSN: 0004-7554 the whole document	2-13,15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

31 October 2014

Date of mailing of the international search report

10/11/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040,
 Fax: (+31-70) 340-3016

Authorized officer

De Meuleneire, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/065427

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009326958	A1	31-12-2009	AT 526659 T 15-10-2011
		AU 2008215230 A1	21-08-2008
		AU 2008215231 A1	21-08-2008
		AU 2008215232 A1	21-08-2008
		BR PI0802613 A2	30-08-2011
		BR PI0802614 A2	30-08-2011
		CA 2645912 A1	21-08-2008
		CA 2645913 A1	21-08-2008
		CA 2645915 A1	21-08-2008
		EP 2111616 A1	28-10-2009
		EP 2111617 A1	28-10-2009
		EP 2115739 A1	11-11-2009
		JP 5232795 B2	10-07-2013
		JP 5254983 B2	07-08-2013
		JP 5291227 B2	18-09-2013
		JP 2010506231 A	25-02-2010
		JP 2010506232 A	25-02-2010
		JP 2010508545 A	18-03-2010
		JP 2012198556 A	18-10-2012
		KR 20090030323 A	24-03-2009
		KR 20090082339 A	30-07-2009
		KR 20090082340 A	30-07-2009
		TW 200847136 A	01-12-2008
		TW 200907932 A	16-02-2009
		TW 200921642 A	16-05-2009
		US 2009210238 A1	20-08-2009
		US 2009326958 A1	31-12-2009
		US 2010076772 A1	25-03-2010
		US 2011200197 A1	18-08-2011
		US 2011202356 A1	18-08-2011
		US 2011202357 A1	18-08-2011
		US 2014297294 A1	02-10-2014
		WO 2008100098 A1	21-08-2008
		WO 2008100099 A1	21-08-2008
		WO 2008100100 A1	21-08-2008
