

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 July 2008 (10.07.2008)

PCT

(10) International Publication Number
WO 2008/082860 A1

- (51) International Patent Classification:
G06F 3/033 (2006.01) *G06F 3/03* (2006.01)
- (21) International Application Number:
PCT/US2007/086911
- (22) International Filing Date:
10 December 2007 (10.12.2007)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
11/617,352 28 December 2006 (28.12.2006) US
- (71) Applicant (for all designated States except US): **3M INNOVATIVE PROPERTIES COMPANY** [US/US];
3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

WEAVER, Billy L.; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).


(74) Agents: **BERN, Steven A.** et al.; 3M Center, Office of Intellectual Property Counsel, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MAGNETIC SHIELD FOR USE IN A LOCATION SENSING SYSTEM



(57) Abstract: An energy transfer apparatus with a magnetic shield is configured to magnetically couple energy from a fixed location to a mobile or moveable device within a field-activated space of the energy transfer apparatus. Apparatuses include a location sensing surface and a drive coil arranged in relation to a periphery of the location sensing surface. A magnetic shield plate is disposed below the location sensing surface and the drive coil. The shield plate includes a number of radially oriented slots originating at, and distributed about, a periphery of the shield plate.

WO 2008/082860 A1



Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

MAGNETIC SHIELD FOR USE IN A LOCATION SENSING SYSTEM

5

The present invention relates generally to magnetic shielding apparatuses and, more particularly, to magnetic shield apparatuses that are of particular use in location sensing systems.

10

BACKGROUND

Personal computing systems of varying type and configuration typically provide one or more user interface devices to facilitate user interaction with such computing systems. Well known user interface devices include a keyboard, mouse, trackball, joystick, and the like. Various types of personal computing devices, such as tablet PCs, provide a pen apparatus that can be manipulated by the user, much in the same way as a pencil or ink pen.

15

Conventional computing devices that provide for user input via a pen or other pointer implement typically employ an electromagnetic inductive system. The electromagnetic inductive system usually comprises an electromagnetic pen or pointer apparatus and a digitizer in the form of a tablet. Changes in pen location relative to the digitizer's sensing surface are detected and location computations are made to determine the coordinates of the pen.

20

SUMMARY OF THE INVENTION

25

The present invention is directed to apparatuses that provide magnetic shielding. Embodiments of the present invention are directed to an energy transfer apparatus with a magnetic shield that magnetically couples energy from a fixed location to a mobile or moveable device within a field-activated space of the energy transfer apparatus.

30

According to various embodiments, apparatuses of the present invention may include a location sensing surface and a drive coil arranged in relation to a periphery of the location sensing surface. A magnetic shield plate is disposed below the location sensing surface and the drive coil. The shield plate includes a number of radially oriented

slots originating at, and distributed about, a periphery of the shield plate. The shield plate may be fabricated from a ferrous metal, such as steel.

5 In some implementations, the shield plate may have relatively low reluctance along a first direction, and relatively high reluctance along a second direction, wherein the first direction is approximately orthogonal to the second direction. In other implementations, the shield plate may have relatively low reluctance along a radial direction, and relatively high reluctance along a circumferential direction.

10 In further implementations, the shield plate may have relatively low electrical resistance along a first direction, and relatively high electrical resistance along a second direction, wherein the first direction is approximately orthogonal to the second direction. In other implementations, the shield plate may have relatively low electrical resistance along a radial direction, and relatively high electrical resistance along a circumferential direction.

15 In some implementations, the shield plate may have relatively low reluctance along a first direction, and relatively high electrical resistance along a second direction, wherein the first direction is approximately orthogonal to the second direction. The first and second directions may vary relative to one another across a surface of the shield plate. The first direction may be oriented in alignment with a direction of a magnetic field generated by the drive coil. In further implementations, the shield plate may have
20 relatively low reluctance along a radial direction, and relatively high electrical resistance along a circumferential direction.

25 The shield plate may include a bent portion extending along the periphery of the shield plate. At least some of the slots of the shield plate may be curved. At least some of the slots may have a curved portion situated near or at the drive coil, the curved portion oriented substantially perpendicular to the drive coil. The drive coil may be arranged in a substantially circular or rectangular shape. The shield plate may include one or more patterns of slots arranged near the drive coil and oriented parallel to the drive coil.

30 In accordance with other embodiments, apparatuses of the present invention may include a location sensing surface and a drive coil disposed relative to a periphery of the location sensing surface. A magnetic shield plate is disposed below the location sensing surface and the drive coil. The shield plate is preferably formed to provide a relatively low reluctance and electrical resistance in a first direction, and a relatively high reluctance

and electrical resistance in a second direction, the second direction differing from the first direction.

5 The reluctance associated with the first and second directions may differ by a factor of 5:1 or greater. The electrical resistance associated with the first and second directions may differ by a factor of 5:1 or greater.

10 The first direction may be a substantially radially inward direction relative to a periphery of the shield plate, and the second direction may be a substantially circumferential direction relative to the periphery of the shield plate. The first direction may be substantially orthogonal to the second direction. The first and second directions may change relative to one another as a function of position across a surface of the shield plate. The first direction may be oriented generally in alignment with a direction of a magnetic field generated by the drive coil.

15 The above summary of the present invention is not intended to describe each embodiment or every implementation of the present invention. Advantages and attainments, together with a more complete understanding of the invention, will become apparent and appreciated by referring to the following detailed description and claims taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 shows a magnetic shielding apparatus positioned about the exterior of a metal bracket;

Figure 2 shows a magnetic shielding apparatus positioned about the periphery of ferrite shield material;

25 Figure 3A shows a magnetic shielding apparatus according to embodiments of the present invention;

Figure 3B shows a magnetic shielding apparatus according to other embodiments of the present invention;

Figure 3C shows a magnetic shielding apparatus according to further embodiments of the present invention;

30 Figure 4 shows a bended peripheral portion of a magnetic shielding apparatus according to embodiments of the present invention;

Figures 5-7 show embodiments of magnetic shields that provide for preferential directivity of reluctance and/or electrical resistance characteristics in accordance with the present invention;

5 Figure 8 is a diagram of a location sensing system that includes an untethered stylus and a location sensing device that incorporates a magnetic shielding apparatus in accordance with embodiments of the present invention; and

Figure 9 is a diagram of an apparatus for generating an excitation magnetic field which is received by a stylus, the apparatus incorporating a magnetic shielding apparatus in accordance with embodiments of the present invention.

10 While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It is to be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the scope of the
15 invention as defined by the appended claims.

DETAILED DESCRIPTION OF EMBODIMENTS

In the following description of the illustrated embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of
20 illustration, various embodiments in which the invention may be practiced. It is to be understood that the embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

The present invention is generally directed to apparatuses that provide magnetic shielding for use in a variety of applications. In broad terms, the present invention is
25 directed to an energy transfer apparatus with a magnetic shield that magnetically couples energy from a fixed location to a mobile or moveable device within a field-activated space of the energy transfer apparatus. Embodiments of magnetic shielding apparatuses of the present invention find particular usefulness in stylus location sensing devices, such as those that incorporate an electromagnetic digitizer.

30 Although the embodiments described herein are generally directed to stylus location sensing devices involving a digitizer or a touch-sensitive sensor in combination with a digitizer, it is understood that magnetic shielding apparatuses implemented in

accordance with the principles of the present invention may be used in many other devices and applications. In this regard, the term digitizer used herein is intended to refer to a location sensing apparatus or energy transfer device that can be used in a variety of applications.

5 For example, apparatuses of the present invention may be configured to sense the location of game pieces on a game board. Identification or discrimination among game pieces on a game board or individual playing cards on a table may also be achieved, alone or in combination with location determinations, such as by providing each game piece or playing card with an RFID circuit having a unique resonance frequency, for example.

10 Other location sensing devices and movable objects are contemplated, such as apparatuses configured to sense the location of a machine tool head or measure liquid level by sensing the location of a float.

 Further, energy may be transferred from the location sensing device or source device to the movable object for purposes other than location detection or identification.
15 For example, a display could be activated when a movable device is placed in the field-activated space of the display. One implementation may include a simple LCD device configured to change from opaque to transparent, revealing a game clue or a letter/number, for example. In other implementations, a low-power LED could illuminate when a movable device that includes the LED is placed within the field-activated space of
20 the display or other form of energy transfer or sensing device.

 Some digitizers have been developed that interact with untethered active styluses. Such styluses are generally configured for hand-held manipulation by a user, and are used as an input device. One method of supplying power to such a stylus is by coupling a magnetic field from a digitizer to the stylus. If the digitizer is transparent, the magnetic
25 field is typically generated by a coil of wire or wires disposed around the periphery of the digitizer. For non-transparent digitizers, the coil of wire or wires may be disposed in the active area of the digitizer. The operating region of a digitizer is typically a large, flat rectangular area (e.g., $\sim 1 \text{ Ft}^2$). The magnetic field is preferably distributed evenly over the stylus operating region. Low power is also preferable. Typical operating frequencies are
30 in the range of 50KHz to 200KHz.

 Surfaces of conductive material or low magnetic reluctance material parallel to the plane of the digitizer and nearby may create magnetic shorting paths to the magnetic coil

that is intended to supply power to the stylus. These magnetic shorting paths result when the magnetic field induces eddy currents in a nearby conductive material. A number of solutions have been proposed, two of which are described below with reference to Figures 1 and 2.

5 Figure 1 shows a system 10 that incorporates a coil 12 positioned about the exterior of a metal bracket 14. Bracket 14 may be part of an LCD display located near (typically behind) the digitizer coil 12, or it may be part of the mechanical structure of system 10. The coil 12 generates a magnetic field when an AC signal is applied across the coil 12 at an input 13. The metal bracket 14 has a gap 15 that prevents circular electrical
10 current, referred to as eddy currents, from flowing around the length of the metal bracket 14. Bracket 14 has a large open area 18, so it does not provide substantial shielding of magnetic flux generated by coil 12.

 Figure 2 shows a known system 20 that incorporates a coil 12 positioned about the periphery of ferrite shield material 28. The coil 12 generates a magnetic field when an AC
15 signal is applied across the coil 12 at an input 13. The ferrite shield material 28 largely prevents magnetic fields from penetrating through shield 28 and extending behind shield 28. In addition, significant eddy currents cannot flow in the electrically resistive ferrite material 28. Ferrite material, however, is prohibitively expensive in many applications. High silica steel has been proposed as an alternative material, but has too high an
20 electrical conductivity so it will support excessive eddy currents, and is also prohibitively expensive in many applications.

 A magnetic shielding apparatus of the present invention provides excellent magnetic shielding performance while being fabricated from low cost materials. In the case of a magnetic shield of the present invention being used in the context of an
25 electromagnetic digitizer, such a magnetic shield advantageously reduces or minimizes magnetic reluctance so that a magnetic field can be generated over the top of the digitizer with minimum power applied. A magnetic shield of the present invention may also minimize eddy currents that would reduce magnetic field strength in the stylus operating area. A magnetic shield of the present invention may further shield the magnetic field
30 from radiating behind the digitizer surface.

 According to embodiments of the present invention, a magnetic shield may be fabricated from a low cost ferrous metal, such as steel, and include a number of apertures

that are aligned with desired magnetic flux lines. A magnetic shield according to embodiments of the present invention may be configured to shape a magnetic field preferentially in a desired direction, such as a radial direction. For example, a magnetic shield may be fabricated to include radial slots aligned with the desired magnetic flux lines.

5

In the context of an electromagnetic digitizer, a magnetic shield of the present invention may be employed as a magnetic field shaping shield, such that the shield shapes a magnetic field preferentially in a desired manner or direction, such as in a radial direction. The shield may also direct electrical current flow in a desired direction, such as in a radial direction. The edges of the magnetic shield may be bent upward at a desired angle to further reduce the reluctance path of flux generated by the drive coil of the digitizer.

10

In accordance with various embodiments, a magnetic shield of the present invention may be incorporated in an electromagnetic digitizer to provide for magnetic shielding and magnetic field shaping. According to such embodiments, a magnetic field is generated over the surface of a digitizer and couples power and signals to an untethered stylus. The magnetic field is generated by a coil of wire or wires disposed around the periphery of the digitizer. The magnetic shield, fabricated from a ferrous metal plate, maximizes field strength over the surface of the digitizer at minimum applied power (by minimizing reluctance of the magnetic field), and minimizes magnetic field coupling to nearby conductive components. The shield plate is provided with a number of radial slots that reduce or minimize eddy currents.

15

20

Figures 3A-3C show various configurations of a magnetic shielding apparatus according to embodiments of the present invention. The apparatus 40 shown in Figure 3A includes a shield plate 48 and a coil 42 disposed about a peripheral portion of the shield plate 48. The coil 42 generates a magnetic field when an AC signal is applied across the coil at input 13. Although coil 42 is shown arranged in a generally rectangular shape, coil 42 may be arranged according to other shapes, such as squares, circles, and ellipses, among others. In a typically system configuration, the shield plate 48 is positioned behind the coil 42 and preferably behind a display (not shown), such as an LCD for example.

25

30

The shield plate 48 is preferably formed from a ferrous metal, such as steel, or other material that provides a low reluctance path for magnetic fields 51-55, for example,

induced by coil 42. The shield plate 48 provides a low reluctance path for magnetic fields, such as fields 51–55, and also largely prevents magnetic fields generated by coil 42 from penetrating through shield plate 48.

5 Figures 3A-3C show a number of slots 46 provided in the shield plate 48. The slots 46 may be arranged in a variety of ways in the shield plate 48 for purposes of preferentially directing magnetic flux. In general, it is desirable that the magnetic flux follow the radial paths between the radial slots 46.

10 The density of a magnetic field is referred to as flux, or more precisely, magnetic flux is the product of the average magnetic field multiplied by the perpendicular area that it penetrates. Magnetic flux tends to follow the path of lowest reluctance, akin to electric current following the path of least resistance. As such, magnetic flux follows the paths provided between the slots 46 in the low-reluctance metal shield plate 48.

15 Figure 3A further shows a number of slots 46 that originate at the peripheral edge of the shield plate 48 and have a generally radial direction. As shown, the slots 46 are distributed about the periphery of the shield plate 48 and define discontinuities along the shield plate's peripheral edge. The slots 46 are also shown to vary in length, and may also vary in terms of width. In Figure 3A, alternating long and short slots 46 are shown distributed about the periphery of the shield plate 48. The slots 46 are shown directed in a radial manner toward a central location of the shield plate 48.

20 In general terms, the slots 46 are situated within the shield plate 48 in a manner that reduces or minimizes eddy currents. For example, the radial slots 46 shown in Figure 3A prevent significant eddy currents from flowing radially around the periphery of shield 48. It is understood that the slots 46 may have varying lengths and widths, and that these dimensions may vary as a function of position across the shield plate 48. Slots may originate at the edges of shield plate 48 or both ends of a slot may be located within the surface of the shield plate 48. Slots may also follow curved paths that vary with the slot position.

30 The slots 46 provided in the shield plate 48 of the shield apparatus 40 shown in Figure 3A are generally straight. In Figures 3B and 3C, many of the slots 46 of shield apparatuses 50 and 60 are curved or have curved portions proximate the coil 42. Because the magnetic flux emanating from the 42 coil is perpendicular to the coil 42, it may be beneficial to bend the slots 46 so that the slot portions near the coil 42 are oriented

substantially perpendicular to the coil 42. The magnetic flux will preferentially follow the curved path of the curved slots 46 cut into the shield plate 48.

Figure 3C shows another configuration of a shield plate 48 according to embodiments of the present invention. The shield plate 48 of Figure 3C is identical to that shown in Figure 3B, except that rectangular patterns of short slots 58, 59 have been added. These patterns of short slots 58, 59 are arranged near the coil 42. The slots 58, 59 are preferably numerous, short in length, and oriented generally perpendicular to the field-guiding slots 46.

Generally, short slots 58, 59 have a higher density (i.e., more shield material is removed) nearer to the coil 42 and a lower density of removed material further from the coil 42. Unlike slots 46, slots 58, 59 are intended to increase the reluctance of the shield nearest to coil 42, relative to the reluctance nearer the center of the shield 48. This has the effect of making the magnetic field more uniform across the surface of the shield 48, by reducing field strength near coil 42. The overall field strength may be reduced as a result of short slot patterns 58 and 59.

The shield plate 48 may be fabricated to include apertures other than slots. For example, pie shaped apertures or apertures of other shapes may be employed, alone or in combination with radial slots. Moreover, the direction of such apertures need not be directed exclusively in a radial direction, and apertures of greater complexity may be included that have more than one direction (e.g., a primary aperture feature having a primary direction and a secondary aperture feature having a secondary direction, where the primary and secondary directions may be different). Accordingly, the aperture configurations and orientations differing from those shown in the Figures may be employed to achieve desired magnetic field shaping and eddy current flow prevention.

As is shown in Figure 4, a peripheral edge portion of the magnetic shield 48 may be bent upward at a desired angle, θ , to further reduce the reluctance path of flux generated by the drive coil of the digitizer. The angle, θ , of the bend 49 formed along the peripheral edge of the magnetic shield plate 48 can be varied, for example, to achieve desired reluctance path characteristics.

Figures 5-7 show embodiments of a magnetic shield 48 of the present invention that provide for preferential directivity of reluctance and/or electrical resistance characteristics in the shield plate 48. According to the embodiment shown in Figure 5, a

magnetic shield 48 is fabricated to have relatively low reluctance in one direction, D_1 , and relatively high reluctance in a different direction, D_2 . The two directions, D_1 and D_2 , may be approximately orthogonal to one another, as is shown by angle φ . The magnetic shield 48 is preferably fabricated so that reluctance is low in a radial direction, D_1 , while
5 reluctance is high in a circumference direction, D_2 . The relative difference in reluctance in the two directions D_1 and D_2 may be 5:1 or greater.

According to the embodiment shown in Figure 6, a magnetic shield 48 is fabricated to have relatively low electrical resistance in one direction, D_1 , and relatively high electrical resistance in a different direction, D_2 . The two directions, D_1 and D_2 , may be
10 approximately orthogonal to one another, as is shown by angle φ . The magnetic shield 48 is preferably fabricated so that electrical resistance is low in a radial direction, D_1 , while electrical resistance is high in a circumference direction, D_2 . The relative difference in electrical resistance in the two directions D_1 and D_2 may be 5:1 or greater.

As is shown in Figure 7, embodiments of the present invention are further directed
15 to a magnetic shield 48 with low reluctance in one direction, D_1 , and high electrical resistance in a different direction, D_2 . The two directions D_1 and D_2 may be orthogonal, for example. The magnetic shield 48 may be fabricated so that reluctance is low in a radial direction, D_1 , while electrical resistance is high in a circumference direction, D_2 .

Although the angle φ defined between the directions of low and high
20 reluctance/electrical resistance in Figures 5-7 is preferably about 90° , the angle φ may vary by several or tens of degrees from orthogonal. Moreover, the angle φ may vary as a function of position across the surface of the magnetic shield plate 48. For example, an angle φ_1 may be defined between directions D_1 and D_2 at a surface position proximate the peripheral edge of the shield plate 48, and vary as a function of shield plate position until
25 an angle φ_N is defined between directions D_1 and D_2 at a position proximate the center of the shield plate 48.

Turning now to Figure 8, there is shown an embodiment of a location sensing system that incorporates a magnetic shield 48 of the present invention. A location sensing system 110 includes a stylus 112 that interacts with a sensing device 111. The sensing
30 device 111 includes a location sensor 114, such as a digitizer. The sensing device 111 is shown to include a drive loop or coil 118 coupled to drive loop electronics 116 that

cooperate to generate a magnetic field, which may be a continuously varying magnetic field having a single frequency or multiple frequency components.

5 A magnetic shield 48 of a type previously described is situated under the sensor 114 and the drive coil 118. The magnetic shield 48 preferably increases field strength over the surface of the location sensor 114 at reduced levels of applied power, reduces magnetic field coupling to nearby conductive components, and reduces eddy currents that would decrease magnetic field strength in the stylus operating area. The magnetic shield 48 also shields the magnetic field from radiating behind the surface of location sensor 114.

10 The stylus 112 is preferably configured as a tetherless or cordless implement. The stylus 112 derives power from the magnetic field generated by the sensing device 111. The stylus 112, having derived power from the magnetic field emanating from the drive coil 118, is configured to broadcast a signal from which stylus location and status may be determined by the sensing device 111. Although preferred embodiments of an untethered stylus do not include a battery, some embodiments may employ a battery, such as a
15 rechargeable battery that is recharged from energy derived from the magnetic field of the drive signal. A battery may be used to provide power to various circuits of the stylus, such as a modulator or pressure sensor (e.g., tip or eraser pressure sensor).

20 The stylus 112 is preferably configured to include one or more user-actuatable buttons or switches, such as those commonly employed to implement various mouse functions (e.g., right and left mouse buttons). The tip of the stylus 112 may incorporate a pressure sensor from which applied pressure can be resolved and transmitted to the sensing device 111. Eraser functionality may also be incorporated in the form of a switch or pressure sensor at the stylus end opposite the tip.

25 Sensor interface electronics 120 is coupled to the sensor 114 and facilitates measurement of signals developed at the sensor 114 in response to signals broadcast by the stylus 112. The sensor interface electronics 120 is preferably connected to the sensor 114 via a shielded connector. The sensor interface electronics 120 includes circuitry for measuring the signal levels present on the individual traces of the sensor 114, and is typically configured to reject as much noise as possible.

30 According to one configuration, the sensor 114 includes a digitizer that incorporates a detection grid and electronics as is known in the art. For example, such a detection grid may include pairs of position resolving conductors each of which forms one

or more differential coil elements in the sensor 114, with each conductor pair receiving a magnetic signal transmitted by the stylus 114. An illustrative example of a digitizer having such a detection grid configuration, elements of which may be employed in a location sensor system of the present invention, is disclosed in U.S. Patent Nos. 4,786,765; 5,218,174; 5,633,471; 5,793,360; 6,667,740; and 7,019,672; which are hereby
5 incorporated herein by reference.

According to another configuration, the sensing device 111 may incorporate a sensor 114 that effectively incorporates a stylus digitizer and a touch-sensitive sensor. The digitizer, according to this configuration, allows the location and status of the stylus
10 112 to be determined. The touch-sensitive sensor allows the location of a finger touch to be determined. This configuration allows a user to use either the stylus 112 or a finger to indicate a desired location on a computer display, for example, as well as determine the location and status of the stylus 112.

The touch-sensitive sensor 114 typically includes a matrix that capacitively
15 couples to the stylus 112 and/or a finger. In this configuration, the sensor 114 of the sensing device 111 is preferably made up of a series of transparent conductors arranged on a glass or plastic cover that can be placed in front of an LCD display. One side of the glass or plastic sheet has conductors in the X direction, and the opposite side has conductors in the Y direction. Examples of suitable touch-sensitive sensors 114 are
20 disclosed in commonly owned U.S. Patent Nos. 6,133,906 and 6,970,160, in commonly owned U.S. Published Application No. 2005/0083307, in U.S. Patent Nos. 6,762,752 and 6,690,156, and in U.S. Published Application No. 2004/0095333, each of which is hereby incorporated herein by reference.

A system embodiment that incorporates a digitizer and touch-sensitive sensor
25 advantageously allows a user to point a stylus at a computer display and have the location and status of the pointing device determined and, when a finger is used to point at the display device, allows for the determination of the location of a finger touch at the display device. The dual use aspects of this embodiment of a sensing device 111 make it particularly useful in tablet PC applications.

30 For example, a digitizer arrangement allows a user to use a stylus to input information, indicate operations the user wants to take, and write or draw on the display. The touch-sensitive sensor allows the user to “type” information onto a virtual keyboard

on the display screen, for example. This would allow the vendor of the computing system, in which a dual touch location sensor system of the present invention is implemented, to eliminate the keyboard and the associated bulk it requires. It is understood that a digitizer and a touch-sensitive sensor need not be implemented together in all configurations, but
5 inclusion of both sensing devices provides for enhanced user interaction with a computing system that incorporates a sensing system 110 of the present invention.

According to one illustrative embodiment, the drive coil 118 may be constructed of wire, such as 36 gauge wire, looped several times (e.g., 4 times) around the periphery of the frame of sensing device 111. In one implementation, the drive coil 118 may have an
10 inductance of about 21 μH and an impedance of about 14 Ohms at 100 kHz. The drive coil 118 is connected to a signal generator of the drive loop electronics 16. The signal generator may be configured to produce signals comprising 200 periods of a 100 kHz sine wave signal gated at 250 Hz, for example. The signal generator may, for example, produce an output signal of 0.4 V_{pp} , resulting in approximately 28mA of current that flows
15 in the drive coil 118.

Figure 9 is a simplified illustration of drive coil 118 and a signal generator 117 that cooperate to generate a magnetic excitation field. In this illustrative example, one or more coils are preferably arranged in the plane of the location sensor 114. The coils are typically arranged in a rectangular shape, but may take on other shapes as discussed
20 above. A sinusoidal current is produced by the signal generator 117 with peak magnitude A_I at radian frequency ω_1 and is applied to the rectangular coil 118.

The stylus 112 is configured to collect energy from the magnetic field emanating from the drive coil 118 using a tank circuit. The tank circuit may initially be tuned to resonate at the frequency that the drive coil 118 is driven. In this illustrative example, the
25 frequency is set at 100 kHz. The tank circuit of the stylus 112 builds amplitude during the burst produced by the drive coil 118 and then gradually loses signal amplitude after the drive coil 118 is turned off. The time associated with the exponential charging and discharging of the resonant tank circuit of the stylus 112 is determined by the capacitive and inductive elements in the tank circuit. Changes in the resonance frequency of the tank
30 circuit, due to drift or purposeful modification (e.g. resulting from stylus switch state changes), may be accommodated by detecting and/or tracking such changes by the sensing device 111. Alternatively, the resonance frequency of the tank circuit can be modified to

track changes in the drive frequency of the magnetic field emanating from the drive coil 118.

5 In some embodiments, the location sensor 114 includes a matrix that capacitively couples to the stylus 112. In other embodiments, the invention may be implemented with magnetic-sensing digitizer systems as are known in the art. An untethered magnetic stylus is similar to a capacitive stylus, except the resonant tank circuit of the magnetic stylus need not be connected to a tip or to a shield of the stylus. Untethered magnetic styluses are well known in the art, and are described in previously incorporated U.S. Patent Nos. 4,786,765; 5633471; 5793360; 6,667,740, and 7,019,672. Embodiments of the present invention that are implemented using an untethered magnetic stylus may employ a location sensor that includes multiple drive loops as disclosed in the referenced patents. In such embodiments, a separate sensing grid and separate drive loops need not be used. Rather, each of the drive loop coils is alternately coupled to transmitting circuitry and then to receiving circuitry to alternately transmit and receive from one of multiple drive loop coils that are placed in the active area, typically under the display.

15 Referring again to Figure 8, a processor 122 is coupled to the drive loop electronics 116, sensor interface electronics 120, and a communications interface 124. The processor 122 coordinates the operations of drive loop electronics 116 and sensor interface electronics 120, and is configured to determine stylus status and stylus/finger location and/or angle. Stylus status and stylus/finger location and/or angle determinations are preferably made by the processor 122 in accordance with the methodologies disclosed in commonly owned U.S. Patent Application No. 11/557,829, entitled "Touch Location Sensing System and Method Employing Sensor Data Fitting to a Predefined Curve," filed on November 8, 2006, which is hereby incorporated herein by reference.

25 The stylus location and status information computed by the processor 122 is communicated to a computer and/or display 126 via the communications interface 124. The communications interface 124 may be configured as an RS-232 or USB interface, for example. The processor 122 may be configured to drive a display 126 directly. Alternatively, a computer 128 may be coupled to the communications interface 124 and receive the location and status information from the processor 122, and drive its display. The processor 122 or computer 128 may be configured to control cursor velocity, momentum and other factors to enhance the user experience with the sensing system 111.

It is noted that demodulator circuitry may be included within sensor interface electronics 120 to recover stylus status data, and that this status data may be communicated to the processor 122. For example, known amplitude demodulation circuitry may be employed to detect the amplitude modulation of a received stylus signal.

5 Known frequency demodulation circuitry may be used to detect the frequency of the amplitude modulation, such frequency indicating the state of a stylus status switch for example.

The foregoing description of the various embodiments of the invention has been presented for the purposes of illustration and description. It is not intended to be

10 exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto.

CLAIMS

What is claimed is:

- 5 1. An apparatus, comprising:
 a location sensing surface;
 a drive coil arranged in relation to a periphery of the location sensing surface; and
 a magnetic shield plate disposed below the location sensing surface and the drive
10 coil, the shield plate comprising a plurality of radially oriented slots originating at, and
 distributed about, a periphery of the shield plate.
2. The apparatus of claim 1, wherein the shield plate is fabricated from a ferrous
 metal.
- 15 3. The apparatus of claim 1, wherein the shield plate is fabricated from steel.
4. The apparatus of claim 1, wherein the shield plate has relatively low reluctance
 along a first direction, and the shield plate has relatively high reluctance along a second
 direction, wherein the first direction is approximately orthogonal to the second direction.
20 5. The apparatus of claim 1, wherein the shield plate has relatively low reluctance
 along a radial direction, and the shield plate has relatively high reluctance along a
 circumferential direction.
- 25 6. The apparatus of claim 1, wherein the shield plate has relatively low electrical
 resistance along a first direction, and the shield plate has relatively high electrical
 resistance along a second direction, wherein the first direction is approximately orthogonal
 to the second direction.
- 30 7. The apparatus of claim 1, wherein the shield plate has relatively low electrical
 resistance along a radial direction, and the shield plate has relatively high electrical
 resistance along a circumferential direction.

8. The apparatus of claim 1, wherein the shield plate has relatively low reluctance along a first direction, and the shield plate has relatively high electrical resistance along a second direction, wherein the first direction is approximately orthogonal to the second direction.
9. The apparatus of claim 8, wherein first and second directions vary relative to one another across a surface of the shield plate.
10. The apparatus of claim 8, wherein first direction is oriented in alignment with a direction of a magnetic field generated by the drive coil.
11. The apparatus of claim 1, wherein the shield plate has relatively low reluctance along a radial direction, and the shield plate has relatively high electrical resistance along a circumferential direction.
12. The apparatus of claim 1, wherein the drive coil is arranged in a substantially circular or rectangular shape.
13. The apparatus of claim 1, wherein the shield plate comprises a bent portion extending along the periphery of the shield plate.
14. The apparatus of claim 1, wherein at least some of the slots are curved.
15. The apparatus of claim 1, wherein at least some of the slots have a curved portion situated near or at the drive coil, the curved portion oriented substantially perpendicular to the drive coil.
16. The apparatus of claim 1, wherein the shield plate comprises at least one pattern of slots arranged near the drive coil and oriented parallel to the drive coil.
17. An apparatus, comprising:

a location sensing surface;

a drive coil disposed relative to a periphery of the location sensing surface; and

a magnetic shield plate disposed below the location sensing surface and the drive coil, the shield plate formed to provide a relatively low reluctance and electrical resistance in a first direction, and a relatively high reluctance and electrical resistance in a second direction, the second direction differing from the first direction.

18. The apparatus of claim 17, wherein the first direction is a substantially radially inward direction relative to a periphery of the shield plate, and the second direction is a substantially circumferential direction relative to the periphery of the shield plate.

19. The apparatus of claim 17, wherein the first direction is substantially orthogonal to the second direction.

20. The apparatus of claim 17, wherein the first and second directions change relative to one another as a function of position across a surface of the shield plate.

21. The apparatus of claim 17, wherein the first direction is oriented generally in alignment with a direction of a magnetic field generated by the drive coil.

22. The apparatus of claim 17, wherein the drive coil is arranged in a substantially circular or rectangular shape.

23. The apparatus of claim 17, wherein the shield plate comprises a bent portion extending along the periphery of the shield plate.

24. The apparatus of claim 17, wherein the reluctance associated with the first and second directions differ by a factor of 5:1 or greater.

25. The apparatus of claim 17, wherein the electrical resistance associated with the first and second directions differ by a factor of 5:1 or greater.




Figure 1




Figure 2




Figure 3A




Figure 3B




Figure 3C




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2007/086911**A. CLASSIFICATION OF SUBJECT MATTER***G06F 3/033(2006.01)i, G06F 3/03(2006.01)i*

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 8 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility Models and Applications for Utility Models since 1975

Japanese Utility Models and Applications for Utility Models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS (KIPO internal) " Keyword : (wireless, untethered), (magnetic), (resonance, resonant), (coil, inductor), (frequency), (capacitor)

"

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US06667740 B2 (DAVID T. ELY, et.al.) 23 Dec. 2003 Abstract, Claims 1,6,7,17,23,37, Figs. 1,3,9, Column 1 Line 3 - Column 4 Line 3	1-25
A	US07019672 B2 (DAVID T. E. ELY) 28 Mar. 2006 Abstract, Claims 1,2,29-32,40,48, Figs. 1,3,15, Column 1 Line 9 - Column 1 Line 63	1-25
A	US06476799 B1 (JEFFREY LEE, et.al.) 05 Nov. 2002 Abstract, Claims 1,8,13, Figs. 1,3,4, Column 1 Line 7 - Column 2 Line 27	1-25
A	US04786765 A (TSUGUYA YAMANAMI, et.al.) 22 Nov. 1988 Abstract, Claims 1,7,8, Figs. 1-4, Column 1 Line 6 - Column 4 Line 3	1-25

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

20 MAY 2008 (20.05.2008)

Date of mailing of the international search report

20 MAY 2008 (20.05.2008)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
Government Complex-Daejeon, 139 Seonsa-ro, Seo-
gu, Daejeon 302-701, Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

CHUN, Dae Sik

Telephone No. 82-42-481-5871



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2007/086911

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US06667740 B2	23. 12. 2003	US20010001430A1 US2002179339A1 US6888538BB	24. 05. 2001 05. 12. 2002 03. 05. 2005
US07019672 B2	28. 03. 2006	US20010006369A1	05. 07. 2001
US06476799 B1	05. 11. 2002	TW413784B	01. 12. 2000
US04786765 A	22. 11. 1988	DE3752068C0 EP00254297A2 EP432139A2 JP3006530B4 JP63029829A2 US34187E	03. 07. 1997 27. 01. 1988 12. 06. 1991 30. 01. 1991 08. 02. 1988 02. 03. 1993