
## F. DIETRICH ET AL

## ELECTROMAGNETIC SOUND REPRODUCER

Filed March 5, 1926



## UNITED STATES PATENT OFFICE

FREDERICK DIETRICH, OF NEW YORK, N. Y., AND WILLIAM H. GERNS, OF EAST ORANGE, NEW JERSEY, ASSIGNORS TO BRANDES LABORATORIES, INC., OF NEW-ARK, NEW JEBSEY. A CORPORATION OF NEW JERSEY.

TEDESTROMAGNETIC SOUND KELLODUCER.

Application filed March 5, 1926. Serial No. 92,540.

Our invention relates broadly to electromagnetic sound reproducers, and more particularly to a construction of cone speaker for use in radio broadcast reproduction.

One of the objects of our invention is to provide a simplified construction of cone speaker which may be manufactured inexpensively on a quantity production basis idly mount cone diaphragms at their peand yet have parts arranged for the efficient riphery by an annular supporting member 10 reproduction of a broad band of frequencies over the entire musical scale.

Another object of our invention is to provide a construction of cone speaker having its parts arranged for the reinforcement of 15 sound waves emanating from the front of a cone diaphragm by the sound waves emanating from the rear of the cone diaphragm for reproduction of radio broadcast enter-tainment at relatively large amplitude.

Still another object of our invention is to provide an assembly of conical sound reproducing diaphragm in a casing shaped in such manner that sound emanating from the rear of the diaphragm is reflected in 25 such manner as to reinforce the sound emanating from the front of the diaphragm for efficiently reproducing sound over a broad band of frequencies:

Still another object of our invention is to 30 provide a casing for an electromagnetic sound reproducer having its parts pressed from sheet metal and locked together to form a rigid casing from the interior of which sound is directed outwardly in a di-35 rection by which the sound may be distributed over a relatively large area at the desired amplitude.

Other and further objects of our invention will be understood from the specifica-40 tion hereinafter following by reference to the accompanying drawings, in which:

Figure 1 is a front view of the cone speaker of our invention; Fig. 2 is a lateral cross-sectional view taken through the cone 45 speaker casing of Fig. 1 and showing the electromagnetic driver and a portion of the cone diaphragm in side elevation; Fig. 3 is casing. a fragmentary cross-sectional view showing the method we employ for locking together 50 the edges of the cone speaker casing; and the parts of the cone speaker is represented Fig. 4 is a detailed fragmentary view showing one of the pressed side joints by which the sides of the cone speaker casing are bound together.

Heretofore in the art cone speakers have 55 been constructed with both sides thereof freely exposed to unconfined air. It has been supposed that the confinement of air around the diaphragm would largely impair the sound reproducing characteristics 60 thereof. It has also been proposed to rigwith a relatively large sized rim between the supporting member and the conical por- 65 tion of the diaphragm. Heretofore in the art various forms of mechanical movements have been interposed between the driver and the cone diaphragm proper. It has also been considered heretofore that in order to 70 secure a desired degree of amplitude in sound reproduction it was necessary to employ a cone diaphragm having a diameter of more than nine inches. By our invention we radically depart from the characteristics 75 of the prior art and provide a relatively small sized cone diaphragm as a sound reproducer for radio broadcast entertainment and we flexibly suspend the cone diaphragm at its periphery for free plunger movement. 80 Reciprocating forces are imparted to the cone diaphragm from an electromagnetic driver. The cone diaphragm is assembled within a casing substantially closing one side of the diaphragm whereby the diaphragm 85 operates in substantially confined air. We so shape the casing with respect to the rear of the conical diaphragm that the sound waves emanating from the rear of the conical diaphragm are reflected in phase with 90 the sound waves emanating from the front of the diaphragm for reinforcing such waves. and increasing the amplitude of the reproduced sound. We prefer to construct the casing for the cone speaker from sheet metal 25 which is pressed into a hollow triangular prism for housing all of the sound reproducer parts. Abutting edges of the casing are provided with locked-together joints for insuring a tight seal at the edges of the 100

Referring now to the drawings in more detail, the sheet metal casing which encloses as having contiguous quadrangular walls 1 105 and 2 bent with respect to each other. The side portion 1 is provided with a grille 3 through which sound waves may emanate,

The sides of the casing are formed by triangular sheet members 4 and 5. The lower edges of the front and rear walls 1 and 2 terminate in curved portions 6 and 7 which co-5 operate with the similarly curved portions 8 and 9 of a base plate 10, forming a rigid lock joint therebetween. The front and rear walls 1 and 2 are also provided with turned over edges 11 and 12 to form rigid 10 connections with the side members 4 and 5. The electromagnetic driver is mounted within the casing upon an angularly disposed bracket member 14. The electromagnetic driver is enclosed by a case 15 and is pro-15 vided with a permanent magnet system 16. The mounting of the driver within the casing is such that the reciprocating member 17 which leads from the armature within the case 15, is disposed in a line substan-20 tially normal to the front plate 1 of the casing. Behind the front wall 1 but substantially spaced therefrom we provide a supporting member 18 carried by means of a bracket 19 secured to the base plate 10. 25 The supporting member 18 is centrally apertured, as represented at 20, and extending inwardly from the edges of the aperture is a resilient annular gasket 21 to which the outer periphery of cone dia-30 phragm 22 is secured. The apex of the cone diaphragm 22 is secured by means of a reinforcing member 23, to the plunger 17 whereby sound vibrations are imparted to the sound reproducing diaphragm 22 35 from the electromagnetic driver within case 15. It will be observed that the supporting member 18 for the cone diaphragm 22 is spaced, as represented at 24, from the rear of the front wall 1, thereby avoiding 40 undesirable compression forces within the

As illustrated the rear wall 2 and the base plate 10 of the casing are disposed at such an angle that the divergence of these plate 45 members forms a pocket behind the rear of the conical diaphragm 22 tending to reflect sound waves from the rear of the diaphragm in the direction of the sound waves emanating from the front of the 60 diaphragm, thereby reinforcing such sound waves and increasing the amplitude of the reproduced sound. The direction of propagation of the reproduced sound is upwardly and outwardly, consequently the 55 sound is distributed over a relatively large area when the cone speaker is mounted upon a horizontal support. The wall 2 and the base plate 10 diverge in the same direction that the side walls of the diaphragm 22 di-60 verge, thus insuring a uniform distribution 65 tions. The triangular prism of the casing said cone diaphragm, and a connection be-

provides angles of sixty degrees between the front, rear, and bottom walls, giving symmetry of construction and simplifying the pressing operations employed in the manufacture of the cone speaker.

While we have described one constructional form of our invention we desire that it be understood that modifications may be made and that no limitations upon the invention are intended other than are 75 imposed by the scope of the appended

What we claim as new and desire to secure by Letters Patent of the United States is as follows:

1. An electromagnetic sound reproducer comprising in combination a prism shaped casing, an electromagnetic driver positioned within said casing, and a cone diaphragm having its base disposed adjacent one wall 85 of said casing and its apex connected with said electromagnetic driver within said casing whereby sound waves reproduced by said cone diaphragm are directed upwardly and outwardly when said triangularly 90 shaped casing is mounted upon a horizontal

2. An electromagnetic sound reproducer comprising in combination a casing having an apertured front and a rear wall diverging with respect to each other, an electromagnetic driver positioned within said casing in a plane substantially between said walls, a cone diaphragm having its base located in a plane substantially parallel with the front wall and its apex connected with said electromagnetic driver, whereby sound reproduced by said cone diaphragm is directed, upwardly and outwardly when said casing is disposed on a horizontal base.

3. An electromagnetic sound reproducer comprising in combination a casing in a shape of a hollow triangular prism, an elec tromagnetic driver mounted within said casing, a cone diaphragm having its base disposed in a plane substantially parallel with one wall of said casing and having its apex connected with said electromagnetic driver at a central point within said casing whereby sound reproduced by said cone diaphragm is directed upwardly and outwardly when said casing is mounted upon a horizontal base.

4. An electromagnetic sound reproducer comprising in combination a casing having three quadrangular closure members disposed at substantially equal angles with respect to each other, an electromagnetic driver mounted substantially at the center of one of said closure members, a cone diaphragm of the sound. It will be manifest that the having its base disposed in a plane substanentire casing for the cone speaker may be tiully parallele to another of said closure pressed from sheet metal and the edges members, and means secured to said first thereof locked together in pressing opera- mentioned closure member for supporting

tween the apex of said cone diaphragm and phragm for reflecting sound waves emanatsaid electromagnetic driver whereby mechanical vibrations are imparted to said cone direction of sound waves emanating from the

diaphragm.

5. In an electromagnetic sound reproducer the combination of a casing in the shape of a hollow triangular prism, an electromagnetic driver positioned centrally within said casing, a plunger member connected with 10 said electromagnetic driver, and lying in the plane that bisects one of the angles of said casing, a cone diaphragm, means for mounting said cone diaphragm adjacent the side of said casing opposite the aforesaid angle, 15 and a connection between the apex of said cone diaphragm and said plunger member whereby sound reproduced by said diaphragm is propagated upwardly and out-20 a horizontal base.

6. An electromagnetic sound reproducer comprising in combination a casing in the shape of a hollow triangular prism, an electromagnetic driver centrally disposed within 25 said casing, a cone diaphragm having its apex connected with said electromagnetic driver and having its base extending in a tures. plane substantially parallel with one side of said casing, the remaining sides of said cas-30 ing forming a pocket in the rear of said dia-

ing from the rear of said diaphragm in the front of said diaphragm for the reinforcement thereof.

7. In an electromagnetic sound reproducer the combination of a casing formed by three quadrangular wall portions locked together at the edges thereof with a pair of end wallportions forming closures for said first men- 40 tioned wall portions, a pair of bracket members mounted on one of said first mentioned wall portions, an electromagnetic driver mounted on one of said bracket members, a support for a cone diaphragm mounted upon 45 the other of said bracket members, a cone diaphragm resiliently suspended in said support and having its base lying in a plane subwardly when said casing is mounted upon stantially parallel with one of said first mentioned wall portions, and a connection be- 50 tween said electromagnetic driver and the apex of said cone diaphragm whereby sound reproduced by said diaphragm is directed upwardly and outwardly when said casing is mounted upon a horizontal base.

In testimony whereof we affix our signa-

FREDERICK DIETRICH. WILLIAM H. GERNS.