

**(12) PATENT
(19) AUSTRALIAN PATENT OFFICE**

**(11) Application No. AU 200112522 B2
(10) Patent No. 779642**

(54) Title
Cover for electromagnetic treatment applicator

(51)⁷ International Patent Classification(s)
A61B 019/00

(21) Application No: **200112522** (22) Application Date: **2000.09.14**

(87) WIPO No: **WO01/19275**

(30) Priority Data

(31) Number **60/154435** (32) Date **1999.09.17** (33) Country **US**

(43) Publication Date : **2001.04.17**
(43) Publication Journal Date : **2001.06.14**
(44) Accepted Journal Date : **2005.02.03**

(71) Applicant(s)
Regenesis Biomedical, Inc.

(72) Inventor(s)
Frank R. George; Robert T. Bryant; Michael F. Daly; Arthur A. Loya; Mary C. Ritz

(74) Agent/Attorney
F B Rice and Co, 605 Darling Street, BALMAIN NSW 2041

(56) Related Art
US 3942023
US 4605124
US 4715366

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number
WO 01/19275 A3

(51) International Patent Classification⁷: H05K 9/00 (74) Agents: RILEY, Paul, J. et al.; Morrison & Foerster LLP, 425 Market Street, San Francisco, CA 94105-2482 (US).

(21) International Application Number: PCT/US00/40903 (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 14 September 2000 (14.09.2000) (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English (26) Publication Language: English

(30) Priority Data: 60/154,435 17 September 1999 (17.09.1999) US (71) Applicant (for all designated States except US): REGENESIS BIOMEDICAL, INC. [US/US]; 1435 North Hayden Road, Scottsdale, AZ 85257-3773 (US).


(72) Inventors; and (75) Inventors/Applicants (for US only): GEORGE, Frank, R. [US/US]; 10187 E. San Salvadore Drive, Scottsdale, AZ 85258 (US). BRYANT, Robert, T. [US/US]; - (US). DALY, Michael, F. [US/US]; 6814 North First Place, Phoenix, AZ 85012 (US). LOYA, Arthur, A. [US/US]; 510 S. Extension, No. 1037, Mesa, AZ 85210 (US). RITZ, Mary, C. [US/US]; 10187 E. San Salvadore Drive, Scottsdale, AZ 85258 (US).

Published: — with international search report

(88) Date of publication of the international search report: 1 November 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COVER FOR ELECTROMAGNETIC TREATMENT APPLICATOR



WO 01/19275 A3

(57) Abstract: A disposable cover for electromagnetic treatment applicators prevents undesired exposure to potentially harmful radiation. The cover is a pouch-like structure having a back surface (which faces opposite, or away from, the treatment area) constructed from shielding material, such as metallized polyethylene. At least a portion of the cover which faces the treatment area is constructed solely from non-shielding material. Securing means, such as adhesive strips, ZIP-LOCK®, or other interlocking edges, secure the applicator inside the cover and close off any leaks. The electromagnetic properties of the cover are integrated into the circuitry for the treatment applicator, such that the applicator is not functional in the absence of the cover. In use, an electromagnetic treatment applicator is inserted into the cover and positioned over the area to be treated, with the non-shielding, or "window", portion of the cover overlying the treatment area. Once assembled, the applicator/cover combination forms a closely matched and tuned network for effecting a highly efficient RF output. When activated, the generated electromagnetic energy only exits the cover through the opening or "window", thereby preventing exposure of the patient or caregiver to potentially harmful radiation.

COVER FOR ELECTROMAGNETIC TREATMENT APPLICATOR**Cross-Reference to Related Applications**

5 This application claims the benefit of provisional application no. 60/154,435, filed September 17, 1999.

Field of the Invention

10 The present invention relates to electromagnetic treatment devices, and more particularly to an apparatus for covering an electromagnetic energy treatment applicator which protects the applicator from biohazards and provides selective radio frequency (RF) shielding.

Background of the Invention

15 Electrotherapy includes various means of applying an electric or electromagnetic field to a wound area to facilitate growth and proliferation of new tissue, i.e., healing. In an earlier patent application filed by the present inventors, an electromagnetic treatment device is disclosed. The device includes a pulsed electromagnetic energy generator, a power level controller and one or more applicators. Each applicator is a pad comprising one or more 20 etched copper printed circuits laminated between insulating sheets of material having high dielectric properties. Sensing units, including an electromagnetic signal strength detector and an applicator-to-patient proximity detector, are incorporated in each applicator and are in communication with the power level controller to provide for direct monitoring of the electromagnetic energy field and precise control of the treatment dosage. The applicators, 25 which are constructed in a variety of shapes and sizes to best match the wound size and area

on the patient, are placed over, under or around a bandaged wound site. Since the applicators are not disposable items, needs exist for apparatus which prevent cross-contamination between patients.

5 In addition, electromagnetic treatment applicators remain in direct contact with the wound site during treatment. Thus, the patient, and possibly the health care providers, are potentially exposed to the emitted radiation. Needs exist for apparatus which limit undesired exposure of the patient and health care provider to the treatment radiation.

Existing covers for radiation shielding and medical applications are unacceptable for use with electromagnetic treatment applicators, such as the one described above.

10 Typical covers for use in medical applications are disclosed in U.S. Patent Nos. 3,942,023, 4,605,124 and 4,715,366. Examples of other devices which provide radiation shielding are disclosed in U.S. Patent Nos. 5,336,896 and 5,523,581. Needs exist for covers for electromagnetic treatment applicators which are cost effective, disposable and easy to use.

15 Citation of the above documents is not intended as an admission that any of the foregoing is pertinent prior art. All statements as to the date or representation as to the contents of these documents is based on the information available to the applicants and does not constitute any admission as to the correctness of the dates or contents of these documents. Further, all documents referred to throughout this application are incorporated in their entirety by reference herein.

Summary of the Invention

It should be apparent that there exists a need for facilitating the safe and effective treatment of patients with electromagnetic energy. It is therefore an aim of the present invention to fulfil that need by providing a cost effective, easy

5 to use, disposable cover for use with an electromagnetic energy treatment applicator. The present cover is easy to affix to the treatment applicator, assists in easy application of the applicator to the patient, promotes the transmission of RF energy waves to the patient while blocking the propagation for those waves in any other direction, and provides biohazard shielding fro

10 protecting against the transmission of diseases between patients. Further, the cover is configured in a manner which integrates the electromagnetic properties of the cover into the circuitry for the treatment applicator, such that the applicator is not functional in the absence of the cover, thereby providing additional safeguards that the intended treatment is safe and efficacious.

15 In a first aspect, the present invention provides an apparatus for covering a treatment applicator comprising a cover having a front surface, a back surface, and at least one open end, wherein at least a portion of said cover is constructed of an RF shielding material, wherein said apparatus is configured to cover said treatment applicator.

20 In a second aspect, the present invention provides an apparatus for covering a treatment applicator comprising a cover having a front surface, a back surface, at least one open end, and at least one strip of RF shielding material removable connected to said cover, wherein said apparatus is configured to cover said treatment applicator.

25 In a third aspect, the present invention provides an electromagnetic treatment apparatus comprising an RF generating system, a cover, and an applicator connected to said RF generating system and located within said cover, wherein said cover further comprises RF shielding that conveys a capacitance upon circuitry in said applicator and wherein said apparatus is configured to cover said treatment applicator.

30 Throughout this specification the word "comprise", or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated element, integer or step, or group of elements, integers or steps, but not the exclusion of any other element, integer or step, or group of elements,

35 integers or steps.

More particularly, the present invention is a disposable cover for devices that are used for therapeutically treating humans with dosages of electromagnetic energy. The cover includes RF shielding material oriented 5 toward the backside of the cover, opposite the treatment area. At least a portion of the cover which faces the treatment area is constructed solely from non-shielding material. Securing means, such as adhesive strips, ZIP-LOCK®, or other interlocking edges, are provided for securing the applicator inside the cover and closing off any leaks. The cover also includes portions which wrap 10 around the cord leading from the applicator to the generating unit.

In use, an electromagnetic treatment applicator is inserted into the present cover and positioned over the area to be treated, with the non-shielding, or "window", portion of the

15

20

25

3A

cover overlying the treatment area. In one embodiment, the dimensions of the "window" are formed by removing selected strips from the outer surface of the cover. Once assembled, the applicator/cover combination forms a closely matched and tuned network for effecting a highly efficient RF output. When activated, the generated electromagnetic energy only exits the cover through the opening or "window", thereby preventing exposure of the patient or caregiver to potentially harmful radiation.

5 The present invention has immediate commercial market potential in the field of chronic wound healing. Beyond that immediate market, the present invention may also be utilized in other treatment fields where increasing the rate of growth and proliferation of 10 human or other living cells is essential, including the treatment of burns and surgically implanted skin or soft tissue grafts, sports and rehabilitation medicine, post surgical repair, and neuronal/brain/spinal injury repair and regeneration. In addition to the medical treatment of soft tissue, the present invention has applications in the field of laboratory growth/manufacturing of skin grafts to be sold and used in various surgical settings, 15 veterinary medicine and related fields.

These and further and other objects and features of the invention are apparent in the disclosure, which includes the above and ongoing written specification, with the drawings.

Brief Description of the Drawings

20 FIG. 1 is a plan view of the disposable cover;
FIG. 2 is a block diagram showing how the cover is configured to integrate its electromagnetic properties into the circuitry of the applicator; and
FIG. 3 is a plan view of the disposable cover with mating interlocking structures.

Detailed Description of the Invention

Referring now to the drawings, where like elements are designated by like reference numerals throughout, FIG. 1 shows an apparatus, more fully described below, for covering an electromagnetic energy treatment applicator. Apparatus 1 includes a front sheet 3 and a back sheet 5. Edges of the sheets 3, 5 are sealed or otherwise connected to form a pouch-like structure with an open end 7 for receiving an applicator (not shown). In alternative embodiments, the apparatus 1 is made from a single sheet, which is folded and sealed such that it has an open end 7. The front sheet 3 (which faces the treatment area) is preferably made, at least partially, of a non-shielding material, such as transparent polyethylene. The back sheet 5 (which faces opposite, or away from, the treatment area) is preferably constructed entirely from shielding material, such as metallized polyethylene, thereby ensuring the blockage of unintended RF transmissions in nontreatment directions. One or more light adhesive strips are located along the outer surface of the front sheet 3 for affixing the cover 1 to a bandage. Preferably, the front sheet 3 of the cover 1 has a patch of adhesive at its center for securing the applicator over the treatment area. The selected adhesive is of low bonding force enabling easy separation from the mating surface.

As shown in FIG. 1, a tab portion 11 extends from the front sheet 3. After the applicator is inserted in the cover 1 through its open end 7, tab portion 11 is folded over such that it overlies a section of the outer surface 13 of the back sheet 5. In one embodiment, an adhesive strip 15 is provided along the outer surface 13 of the back sheet 5 for securing the tab portion 11 in its folded position. In another embodiment, tab portion 11 has a permanent adhesive strip which preferably runs the length of the unsealed end. It

should be understood that other attachment means for securing the tab portion 11 in its folded position are contemplated by the present invention. Preferably, tab portion 11 includes a semi-circular notch 17 or other similar opening or spacing which allows a coaxial cable to protrude therethrough when the cover 1 is sealed. Tab portion 11 further 5 includes perforations 19, preferably provided along the length of the tab portion 11, for enabling easy removal. It should also be understood that, in yet another embodiment, tab portion 11 consists of a ZIP-LOCK® strip or other interlocking means to connect it to a second tab portion extending along the top of front sheet 3. (FIG. 3)

For additional biohazard protection, the tab portion 11 is extended, thereby allowing 10 the tab portion 11 to be wrapped around the cable. In such embodiments, no notch is required. Rather, the extended tab portion 11 is wrapped around the cable and secured thereto with adhesive located along a surface of the tab portion. The tab portion is also secured to the back sheet 5 to seal off entry to the interior of the cover 1 where the applicator is located.

15 It should be understood that the tab portion 11 can extend from the back sheet 5, as opposed to the front sheet 3, or from both the back sheet 5 and the front sheet 3 without departing from the scope of the present invention. Other means for sealing off the open end of the cover 1, including, but not limited to, mating tabs, ZIP-LOCK® strips, or other fastening means, are also contemplated by the present invention.

20 In an alternative preferred embodiment, shown in FIG. 3, tab portions extend from both the front sheet 3 and the back sheet 5. Mating interlocking means 12, such as ZIP-LOCK® strips, are located along each tab portion 11.

In its preferred form, the cover 1 is rectangular in shape and approximately 10

inches by 12 inches in size. The thickness of the cover 1 is approximately 1/100 of an inch.

At least the outer surface of the cover 1 is water proof and bacterial resistant, and is designed to be placed directly on the patient or on top of any standard dressings used over the area to be treated.

5 As described earlier, the cover 1 is composed of a combination of two types of materials - one selected for its properties of resistance to transmission of RF waves and one selected for its ability to be mechanically joined to the first material. Both materials are preferably also good barriers to moisture absorption, thereby preventing biohazards from coming in contact with the applicator surfaces. The RF shielding material prevents
10 emission from the applicator in any direction other than that to be focused at the wound site. The shielding enables the use of the electromagnetic treatment device while being compliant with standards for transmission of radio frequency and other forms of electromagnetic energy.

In its simplest form, the front sheet 3 is made of a non-shielding material and the
15 back sheet 5 is made of a shielding material. It should be understood, however, that variations of this embodiment are also contemplated by the present invention. For example, the entire cover can be constructed of RF shielding material except for a window over the treatment zone (the treatment zone is characterized as the area above the applicator transmitting antenna). In an alternative embodiment, the entire cover, or a portion thereof,
20 can be constructed of non-shielding material, with strips of shielding material adhered thereto. For example, RF shielding material perforated in concentric circles, or other shapes, are bonded to the outer surface of the transparent material. In such embodiments, the window over the treatment zone can be variable in size, with the user able to peel off

certain shielding strips to match the transmission region to that of the wound to be treated.

Other variations are also considered within the scope of the present invention.

In preferred embodiments, proper placement of the cover 1 over the applicator is required for the device to operate. Preferably, the applicator (such as the one disclosed in the present applicants' earlier patent application) incorporates RF shielding material as a capacitor which is part of the electronic tuning of the applicator. Without the cover, the applicator cannot be tuned, thus the electromagnetic energy treatment device will detect a fault and will not operate. In one embodiment, as shown in FIG. 2, cover 1 includes a shielded side which conveys a particular capacitance upon the circuitry enclosed within the applicator. When the requisite capacitance is present, the applicator sends an appropriate voltage signal to a previously described power generator device (described in earlier application filed by inventors), enabling the device. In the absence of the cover conveying the requisite capacitance, the voltage signal remains outside of a predetermined range and the power generating device is disabled. In other words, the RF shielding provided by the cover acts as an additional source of capacitance (Y) which changes the final capacitance of system (Z). The RF generating system is adjusted such that it is only operable when the capacitance is within the range provided by the capacitance within the internal applicator pad shield circuitry (X) plus the capacitance (Y) provided by the cover.

The present invention is operated by placing the treatment applicator into the cover through its open end, with the treatment side of the applicator oriented towards the front sheet and the coaxial cable of the applicator protruding through the open end. A permanent adhesive peel strip (which is located on the tab portion or the back sheet) is removed, exposing the adhesive. Tab portion is folded over the end of the applicator, with the semi-

circular cutout notch aligned with the coaxial cable. The tab portion is then pressed against the back sheet to fully close the cover.

Where the cover includes an extended tab portion, there is no semi-circular cable cutout. Rather the extended tab portion is folded over and wrapped around the coaxial cable and bonded together to form a biohazard barrier. For further securement, a portion of the tab portion also adheres to the back sheet.

5 Next, the peel strip material is removed from the outer surface of the front sheet to expose a low bonding force adhesive. The covered applicator is aligned with the wound site. Indicia, such as printed designs, may be located on the outer surface of the front sheet for facilitating proper alignment. The cover is then adhered to the bandaged wound site, 10 thus ensuring proper location of the applicator to the wound site. The adhesive is not permanent and can easily be pulled away from the bandaged site.

15 Following treatment, the cover is removed from the applicator and properly disposed. Preferably, removal of the cover involves the following steps. First, the cover is gripped at the two corners away from the end with the protruding coaxial cable. Pulling the corners in opposite directions causes the cover to tear at the center. As the tear clears the cover can be removed from the applicator and disposed. For embodiments including the extended tab portion, the user continues the tear the cover past the intersection of the applicator and cable until the cover can be removed.

20 From the foregoing, it will be appreciated by those skilled in the art that the present invention provides a particularly effective and advantageous method of and apparatus for overcoming many of the limitations associated with the treatment of patients using electromagnetic energy. It will also be readily appreciated by one with ordinary skill in the

art to use the method and apparatus of the present invention in other applications, such as veterinary applications.

Although certain presently preferred embodiments of the present invention have been specifically described herein, it will be apparent to those skilled in the art to which the invention pertains that variations and modifications of the various embodiments shown and described herein may be made without departing from the spirit and scope of the invention.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. An apparatus for covering a treatment applicator comprising a cover having a front surface, a back surface, and at least one open end, wherein at least a portion of said cover is constructed of an RF shielding material, wherein said apparatus is configured to cover said treatment applicator.
- 5 2. Apparatus according to claim 1, wherein said back surface of said cover is constructed of said RF shielding material.
3. Apparatus according to claim 2, wherein at least a portion of said front 10 surface of said cover is constructed of said RF shielding material.
- 10 4. Apparatus according to any one of the preceding claims, wherein said RF shielding material is metallized polyethylene.
5. Apparatus according to any one of the preceding claims, further comprising at least one adhesive strip located on said front surface.
- 15 6. Apparatus according to any one of the preceding claims, further comprising means for closing said open end of said cover.
7. Apparatus according to claim 6, wherein said closing means further comprises a tab extending from said front surface and means for securing said tab to said back surface.
- 20 8. Apparatus according to claim 7, wherein said securing means is selected from the group consisting of adhesive, mating fasteners and mating ZIP-LOCK® strips.
9. Apparatus according to claim 7 or 8, wherein said tab has an opening located therein.
- 25 10. Apparatus according to claim 9, wherein said opening is a semi-circular notch.
11. Apparatus according to any one of claims 7 to 10, further comprising perforations located along said tab.
12. Apparatus according to claim 6, wherein said closing means further 30 comprises a tab extending from said back surface and means for securing said tab to said front surface.
13. Apparatus according to claim 6, wherein said closing means further comprises a first tab extending from said front surface, a second tab extending from said back surface, and means for securing said first tab to said second
- 35 tab.

14. Apparatus according to any one of the preceding claims, wherein said cover is waterproof and bacterial resistant.
15. An apparatus for covering a treatment applicator comprising a cover having a front surface, a back surface, at least one open end, and at least one strip of RF shielding material removable connected to said cover, wherein said apparatus is configured to cover said treatment applicator.
- 5 16. Apparatus according to claim 15, wherein said front surface is made of a non-shielding material, wherein said at least one strip overlies said front surface, and wherein said at least one strip further comprises a perforated strip.
- 10 17. Apparatus according to claim 15 or 16, wherein said at least one strip is removably adhered to the front surface.
18. Apparatus according to claim 15, 16 or 17, wherein said at least one strip further comprises multiple strips, each adhered to the front surface of the cover and separably removable therefrom.
- 15 19. An electromagnetic treatment apparatus comprising an RF generating system, a cover, and an applicator connected to said RF generating system and located within said cover, wherein said cover further comprises RF shielding that conveys a capacitance upon circuitry in said applicator and wherein said apparatus is configured to cover said treatment applicator..

24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
259
260
261
262
263
264
265
266
267
268
269
269
270
271
272
273
274
275
276
277
278
279
279
280
281
282
283
284
285
286
287
288
289
289
290
291
292
293
294
295
296
297
298
299
299
300
301
302
303
304
305
306
307
308
309
309
310
311
312
313
314
315
316
317
318
319
319
320
321
322
323
324
325
326
327
328
329
329
330
331
332
333
334
335
336
337
338
339
339
340
341
342
343
344
345
346
347
348
349
349
350
351
352
353
354
355
356
357
358
359
359
360
361
362
363
364
365
366
367
368
369
369
370
371
372
373
374
375
376
377
378
379
379
380
381
382
383
384
385
386
387
388
389
389
390
391
392
393
394
395
396
397
398
399
399
400
401
402
403
404
405
406
407
408
409
409
410
411
412
413
414
415
416
417
418
419
419
420
421
422
423
424
425
426
427
428
429
429
430
431
432
433
434
435
436
437
438
439
439
440
441
442
443
444
445
446
447
448
449
449
450
451
452
453
454
455
456
457
458
459
459
460
461
462
463
464
465
466
467
468
469
469
470
471
472
473
474
475
476
477
478
479
479
480
481
482
483
484
485
486
487
488
489
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
509
510
511
512
513
514
515
516
517
518
519
519
520
521
522
523
524
525
526
527
528
529
529
530
531
532
533
534
535
536
537
538
539
539
540
541
542
543
544
545
546
547
548
549
549
550
551
552
553
554
555
556
557
558
559
559
560
561
562
563
564
565
566
567
568
569
569
570
571
572
573
574
575
576
577
578
579
579
580
581
582
583
584
585
586
587
588
589
589
590
591
592
593
594
595
596
597
598
599
599
600
601
602
603
604
605
606
607
608
609
609
610
611
612
613
614
615
616
617
618
619
619
620
621
622
623
624
625
626
627
628
629
629
630
631
632
633
634
635
636
637
638
639
639
640
641
642
643
644
645
646
647
648
649
649
650
651
652
653
654
655
656
657
658
659
659
660
661
662
663
664
665
666
667
668
669
669
670
671
672
673
674
675
676
677
678
679
679
680
681
682
683
684
685
686
687
688
689
689
690
691
692
693
694
695
696
697
697
698
699
699
700
701
702
703
704
705
706
707
708
709
709
710
711
712
713
714
715
716
717
718
719
719
720
721
722
723
724
725
726
727
728
729
729
730
731
732
733
734
735
736
737
738
739
739
740
741
742
743
744
745
746
747
748
749
749
750
751
752
753
754
755
756
757
758
759
759
760
761
762
763
764
765
766
767
768
769
769
770
771
772
773
774
775
776
777
778
779
779
780
781
782
783
784
785
786
787
788
789
789
790
791
792
793
794
795
796
797
797
798
799
799
800
801
802
803
804
805
806
807
808
809
809
810
811
812
813
814
815
816
817
818
819
819
820
821
822
823
824
825
826
827
828
829
829
830
831
832
833
834
835
836
837
838
839
839
840
841
842
843
844
845
846
847
848
849
849
850
851
852
853
854
855
856
857
858
859
859
860
861
862
863
864
865
866
867
868
869
869
870
871
872
873
874
875
876
877
878
879
879
880
881
882
883
884
885
886
887
888
889
889
890
891
892
893
894
895
896
897
897
898
899
899
900
901
902
903
904
905
906
907
908
909
909
910
911
912
913
914
915
916
917
918
919
919
920
921
922
923
924
925
926
927
928
929
929
930
931
932
933
934
935
936
937
938
939
939
940
941
942
943
944
945
946
947
948
949
949
950
951
952
953
954
955
956
957
958
959
959
960
961
962
963
964
965
966
967
968
969
969
970
971
972
973
974
975
976
977
978
979
979
980
981
982
983
984
985
986
987
988
988
989
989
990
991
992
993
994
995
995
996
997
997
998
999
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1088
1089
1089
1090
1091
1092
1093
1094
1095
1096
1097
1097
1098
1099
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1188
1189
1189
1190
1191
1192
1193
1194
1195
1196
1197
1197
1198
1199
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1288
1289
1289
1290
1291
1292
1293
1294
1295
1296
1297
1297
1298
1299
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1388
1389
1389
1390
1391
1392
1393
1394
1395
1396
1397
1397
1398
1399
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1488
1489
1489
1490
1491
1492
1493
1494
1495
1496
1497
1497
1498
1499
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1588
1589
1589
1590
1591
1592
1593
1594
1595
1596
1597
1597
1598
1599
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1688
1689
1689
1690
1691
1692
1693
1694
1695
1696
1697
1697
1698
1699
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1788
1789
1789
1790
1791
1792
1793
1794
1795
1796
1797
1797
1798
1799
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808<br

280604 12522





FIG. 1

280004 12522




2 / 3

CAPACITANCE FROM INTERNAL SHIELD (X) + CAPACITANCE
FROM COVER SHIELD (Y) = FINAL SYSTEM CAPACITANCE (Z)

FIG._2

260004 12522



3 / 3

FIG._3